Topic 38b DE-SC0001232 **Advanced Simulation and Optimization Tools for Dynamic Aperture of Non-Scaling FFAGs and Related Accelerators including Modern User Interfaces**

a. 2008 Phase I-SBIR/STTR Cover Page/Summary

(All information provided on this page is subject to release to the public.)

FIRM NAME: Particle Accelerator Corp.	RESEARCH INSTITUTION: Michigan State University Prof. Martin Berz, Subgrant PI
ADDRESS: 4513 Cornell Ave., Downers Grove, IL 60515	ADDRESS: Department of Physics, MSU East Lansing, MI 48824

NAME of PRINCIPAL INVESTIGATOR: **Dr. Kyoko Makino**

PHONE NUMBER: **(517) 230-4951**

PROJECT TITLE: **Modern Simulation and Optimization Tools for Non-Scaling FFAGs and Related Accelerators**

TECHNICAL ABSTRACT (Limit to space provided)

Statement of the problem or situation that is being addressed - typically, one to three sentences.

With the U.S. experimental effort in HEP largely located at laboratories supporting the operations of large, highly specialized accelerators, the understanding and prediction of high energy particle accelerators becomes critical to the overall success of the DOE HEP program. One area in which small businesses can contribute to the ongoing success of the U.S. program in HEP is through innovations in computer techniques and sophistication in the modeling of high-energy accelerators. A specific newly identified problem lies in the simulation and optimization of FFAGs and related devices, for which currently available tools originally developed for other purposes provide only approximate and inefficient simulation. We propose to develop a set of tools for this purpose based on modern techniques and simulation approaches.

General statement of how this problem is being addressed. This is the overall objective of the combined Phase I and Phase II projects.

The simulation framework of the code COSY INFINITY is highly accurate, efficient and well-developed with a large user base, and provides powerful tools for global, non-local optimization. For the specific problem at hand, new tools need to be developed that can describe the complex specific electromagnetic fields, including high-order fringe fields, edge effects, and general field profiles, and that can accommodate the necessary very large emittance of the beam by dynamic subdivision of the phase space. In order to simplify design needs, modern global, non-local optimization techniques will be connected to the tools to allow efficient probing of the usually very high dimensional parameter space. User-friendly interfaces will also be developed to enhance the audience and lessen the expertise typically required in the use of accelerator codes.

What will be done in Phase I – typically, two to three sentences.

Phase I will consist of the development of a bare-bones prototype of the core numerical engines necessary for the task, including the ability to treat arbitrary field arrangements, computation of local closed orbits, tunes, tune shifts, and parameter optimization, as well as analysis and benchmarking of their performance characteristics.

COMMERCIAL APPLICATIONS AND OTHER BENEFITS as described by the applicant. (Limit to space provided).

The development of broad, highly-accurate accelerator models with powerful optimization tools and user-friendly interfaces and graphics will not only aid in the critical development of new accelerators for the core mission of the DOE HEP program, but also promote the transfer of accelerator technology into commercial and medical applications such as hadrontherapy, neutron and light sources, and other potential markets for accelerators.

Key Words:

Non-Scaling FFAG, Large Emittance, Simulation, High-Order Methods, Global Optimization

SUMMARY FOR MEMBERS OF CONGRESS: (LAYMAN'S TERMS, TWO SENTENCES MAX.)

The development of broad, highly-accurate accelerator models with powerful optimization tools and user-friendly interfaces will enhance not only the HEP program but also benefit established and future applications of accelerators in science, technology, and medicine ranging from treatment of cancers, radiopharmaceuticals, and medical isotope production to secondary production beams for material science and basic research in nuclear physics.

Summary of Phase I Work

In Phase I, various core modules for the design and analysis of FFAGs were developed. The key items of phase I are enumerated below, and details can be found in the text below.

1. **Assessment of tools for dynamic aperture studies, including high-order out of plane expansions**
2. **Study of global optimization tools based on genetic algorithms, local search, and other global tools**
3. **Development of both the philosophy of a user front end and a code back end of a graphical user interface**
4. **Case studies pertaining to common design and optimization tasks in FFAGs.**
5. **Initial Assessments of novel methods to treat space charge effects.**

The developments executed under this contract represent significant enhancements of the code COSY INFINITY for the particularly challenging case of simulating FFAG accelerators. The development build on the following currently existing features in the current COSY environment useful for FFAG simulation:

- **Arbitrary Order Maps** COSY allows the computation of all dynamics of the system to arbitrary order, including out-of-plane expansions of fields and any nonlinear terms in the Hamiltonian
- **Arbitrary Fields** There is no principal limitation of the fields COSY can treat, as long as they can be modeled in a reasonable way. For efficient initial simulation and optimization, it is particularly useful to utilize very high order out-of-plane expansions of suitable midplane models.
- **Symplectic Tracking** There are various methods to perform tracking in COSY that preserve the symplectic symmetry inherent in Hamiltonian systems, including methods that do so with minimal modifications based on the Expo approach [22][23]. These allow a very faithful estimation of dynamic aperture.
- **Nonlinear Analysis Tools** In addition to the mere empirical study, there are various tools for analysis of nonlinear effects, including the normal form-based computation of high-order amplitude dependent tune shifts and resonances.
- **Sophisticated Global Optimization** COSY allows the automatic adjustment and optimization of arbitrary system parameters; and different from other tools, the search uses methods of global optimization with constraints over a pre-specified search region, and not merely local optimization from a starting parameter setting.

To provide an illustrative example of the behavior to be expected, we study a sample FFAG having six-fold symmetry, with focusing stemming from an azimuthal field variation expressed as a single Fourier mode as well as edge focusing. The system is studied to various orders of out-of-plane expansion, and conclusions about dynamic aperture are drawn. We show the results for orders three and five, which are typical for the situation of conventional out-of-plane expansion in codes like Cyclops. Because the method used in COSY is not based on divided differences,

Topic 38b DE-SC0001232 Advanced Simulation and Optimization Tools for Dynamic Aperture of Non-Scaling FFAGs and Related Accelerators including Modern User Interfaces

the necessary in-plane derivatives can actually be calculated to any order desired with an accuracy that is always close to machine precision [9], [10].

The results of tracking without symplectification and with Expo symplectification are shown in figures 1 – 4. Apparently symplectification greatly affects the dynamic aperture to be inferred in the system. Tracking is performed using the Expo symplectification scheme which is known to minimize the alterations to the non-symplectic tracking results compared to other symplectification methods.

Fig. 1: Tracking in a model non-scaling FFAG with third-order out of plane expansion, without symplectification.

Fig. 2: Tracking in a model non-scaling FFAG with third-order out of plane expansion, with Expo symplectification.

Fig. 3: Tracking in a model non-scaling FFAG with fifth-order out of plane expansion, without Expo symplectification.

Fig. 4: Tracking in a model non-scaling FFAG with fifth-order out of plane expansion, with Expo symplectification.

However, figures 5 and 6, which are both based on order eleven out-of-plane expansion, show significant additional effects and different dynamic aperture, suggesting that the low order methods for out-of-plane expansion and dynamics are not sufficient to capture the details of the dynamics. It would in fact lead to an incorrect prediction of dynamic aperture, underestimating it in the horizontal direction and overestimating it in the vertical. Further increases in order beyond eleven do not significantly affect the details of the symplectic motion shown, but continue to influence the non-symplectic motion. A rough estimate reveals that in this particular case, the dynamics as seen in non-symplectic tracking seems to begin to stabilize around order 17, which is still rather easily obtained within the power of a modern workstation.

Fig. 5: Tracking in a model non-scaling FFAG with fifth-order out of plane expansion, without Expo symplectification.

Fig. 6: Tracking in a model non-scaling FFAG with eleventh-order out of plane expansion, with Expo symplectification.

Orders higher than eleven do not lead to significant additional effects.

The following methods of increasing sophistication were developed for FFAG simulations, although they are not available for general use in COSY.

- **Fourier modes** of orders up to around 20 describing the azimuthal dependence. The modes are provided on a set of suitably many radii and interpolated for intermediate values of radius.
- **Superimposed combined-function magnets** described by high-order edge curves and radially dependent fields. The fringe fields of the edges are described in terms of the common Enge fringe field model [9] [11] in a way similar to what is traditionally done in the study of high-resolution particle spectrographs.

The advantage of the two previous approaches is that they result in a rather accurate and proven field model without requiring the use of field calculation tools, which is particularly useful for the design and optimization phase where models need to be modified quickly. The following is also implemented in COSY, but currently requires expertise to use.

- **Measured midplane field data** that are interpolated through Gaussian interpolation and other wavelet methods [24]

Topic 38b DE-SC0001232 Advanced Simulation and Optimization Tools for Dynamic Aperture of Non-Scaling FFAGs and Related Accelerators including Modern User Interfaces

In order to facilitate the day to day use of COSY for FFAG simulations, Graphical User Interfaces (GUI) have been investigated for the user instead of the more general yet less easily manageable console-type output COSY provides. The following features were chosen.

- Java based version for maximum portability across platforms and ease of future maintenance. Currently supported platforms are Mac, Windows PC, Linux; the addition of others is relatively straightforward due to the general availability of Java. Additionally a wxWidgets-based version is provided for particularly easy implementation and retention of conventional console I/O if so desired.
- Possibility of easy integration of GUI into web browsers through Java-based interface. This will allow simple remote operation including on local mainframe clusters as well as cloud-based computing
- Direct connection to the low-level COSY I/O pipes, as an equal alternative and replacement of the current console-type I/O
- Ease of programmability of the actual appearance by the user instead of a rigidly pre-specified set of features via seamless integration of GUI formatting commands into COSY console syntax
- Automatic generation of an acceptable GUI from legacy, console-based I/O.

Topic 38b DE-SC0001232 **Advanced Simulation and Optimization Tools for Dynamic Aperture of Non-Scaling FFAGs and Related Accelerators including Modern User Interfaces**

In the following we will illustrate several of these features, provide a snapshot of their current status. The first set of examples will be shown for a Macintosh environment. At the beginning of the execution of the FFAG simulation tool, the user is shown a flash screen that allows the selection of the system being studied, as well as the initial selection of design tasks.

The next screen shows the behavior of the “Design” GUI page, which allows the setup of the device in various ways. One can specify the number of cells and magnets per cell via pulldown menus, a choice to specify edges via curves or via data points in a file, and likewise a choice to specify fringe fields based on standard falloff in the Enge model, or again through reading from files. In a similar way, magnet fields can be specified either based on data on meshes, or through various other models.

The next screen shows an example of a GUI interface for the performance analysis of the device under study. It offers some common tasks as pre-existing options, including the determination of closed orbits, tunes, tune shifts and resonances, and it also allows various methods of performing stationary tracking or tracking under acceleration.

Topic 38b DE-SC0001232 **Advanced Simulation and Optimization Tools for Dynamic Aperture of Non-Scaling FFAGs and Related Accelerators including Modern User Interfaces**

The openness of the COSY GUI interface will allow the user to add own features and analysis methods based on specific needs. In a similar fashion, many common optimization tasks are possible directly from the GUI, while for more advanced such features it is necessary to specify custom-made objective functions in the COSY console interface, or to include additional features.

Topic 38b DE-SC0001232 Advanced Simulation and Optimization Tools for Dynamic Aperture of Non-Scaling FFAGs and Related Accelerators including Modern User Interfaces

The GUI features shown so far allow for a rather straightforward control of common features in the simulation tasks, and other features can easily be added into the GUI environment. In addition to the above GUI interfaces, we considered developing a second one that retains COSY's console I/O feature, and only augments it with certain pre-selected options that can be selected by mouseclick. The window below shows the corresponding setup, with the console output on the left, and the programmable selectable choices on the left. In addition to these selections, it remains possible to read from the console as is historically done.

Compact high-performance devices like FFAG-type accelerators often are operated in a regime where space charge effects in the form of electrostatic self-forces of the beam on itself becomes significant. However, different from other types of accelerators, the situation in compact FFAGs is often particularly complicated to analyze because of the space charge cross talk of beams at different nearby radii in the device. In more conventional machines, it is often possible to arrive at good space charge models based on studies of individual bunches and their fields on themselves and as necessary the preceding and subsequent bunches; and depending on the level of accuracy that is needed, either semi-analytical models are sufficient, or the system is at least amenable to many of the highly developed particle-in-cell (PIC) and related approaches.

Because of the fine structure of possibly hundreds of nearby beams, the use of PIC approaches in FFAGs would requires meshes of rather high resolution; and yet, most of the detail obtained for a far away region is not necessarily relevant for the fate of a given particle of interest. This situation is conceptually similar to that of the simulation of the dynamics of galaxies that have strong density non-uniformities with relatively dense spiral arms, and significantly less dense

material in between. For such kinds of simulations, the so-called Fast Multipole Methods (FMM) have gained prominence [27-31]. They attempt to capitalize on the fact that distant charge distributions influence local behavior less than nearby ones, and suitably grouping those distant ones into collective representations with an error that scales with a high power of distance. Specifically, the method is based on the representation of the potential of a charge distribution at a distance in terms of spherical harmonics via

$$V(r, \theta, \varphi) = \sum_{l=0}^{\infty} \sum_{m=-l}^l a_{lm} \frac{Y_l^m(\theta, \varphi)}{r^{l+1}}$$

Where the a_{lm} are the so-called far field multipoles of the distribution. Truncating the expansion at a given order of the radial expansion in r allows an accurate representation of the far-field effects.

The Fast Multipole Methods now consist of two separate algorithms, namely the determination of a global field representation on the one hand,, and the computation of the field of a single particle resulting from it. Both of these methods can be shown to scale with $N \log(N)$, where N is the number of particles or macroparticles, and thus have a much more favorable scaling than direct summation as in the conventional force calculation, while avoiding all the issues of meshing and their required resolution of the PIC-like methods.

The algorithm we developed to obtain a field representation is as follows.

1. Discretize the relevant region of space into a fine mesh of cells, and identify the cell into which each particle falls
2. Determine the far field multipole distribution of each cell at the finest structure by summation over the corresponding particles in the cell.
3. Iteratively, use the far field multipoles of the next finer structure to determine the corresponding values for the next coarser structure.

The result is a multi-layer representation of the field through far field multipoles of different granularity. For the second part of the method, namely the computation of the fields on each particle, the following approach is used:

1. Determine an acceptance angle and an expansion order compatible with the desired accuracy
2. Determine all cells of the coarsest discretization that fall into the acceptance angle when viewed from the particle of interest. Determine their field on the particle of interest by summing their multipole expansions.
3. Determine all cells not yet treated, determine the cells of the next finer mesh corresponding to the yet untreated regions, and repeat the multipole summation for those cells.
4. Repeat the procedure until the finest mesh has been reached. Treat the few particles in the remaining nearby finest cells by direct summation.

For the purposes of our study, it is of particular relevance that all of the steps in the above algorithms can be carried out using the differential-algebra based high order methods we are using, and it is also possible to extract the necessary high-order expansions for the fields. Specifically, DA methods are used for

- Manipulation of the far field multipoles, which are polynomials in $1/r$, θ and φ .
- Combination of far field multipoles for finer mesh cells to those of the coarser mesh cells
- Computation of local high-order field expansions, which are necessary within the map computation framework of the DA methods.

To assess the practical performance of the space charge computation using FMM algorithm, a 2D test version has been implemented. The performance of the method was analyzed by selecting a distribution of $N=10,000$ point charges randomly placed in a box. The fields on each particle were then calculated directly by summing over the remaining $(N-1)$ particles, which apparently scales with the square of N . Next, space is discretized in a hierarchy of meshes, and the force on each of the particles is calculated using the method above and compared with an opening angle of around 30 degrees was chosen, and the resulting accuracies were obtained for different orders of the FMM expansion by comparing to the exact direct summation. The following table summarizes the results that were obtained:

Expansion Order	5	10	15
Relative Error	5.5e-5	2.2E-7	1.5E-10

So apparently the accuracy is indeed very high, and significantly exceeds what can be obtained with conventional field solvers.

The next phase, would have involved development of a full 3D version of the method.

Initial Benchmarking of Some Preliminary Code Modules

To conclude the study of the feasibility of the approach, a mockup with the various ingredients of the final code with the exception of space charge features that are still in their infancy was developed. While not connected to the main code in a functional way, and very cumbersome to operate, the resulting toolkit could be used to get a first impression of the eventual feature set. In order to make the study as realistic as possible, we applied the various subsystems to a common design and analysis problem of a novel FFAG accelerator.

The devices in question are two reverse-bend eight cell structures, one based on a FODO design and the other one on a triplet design, with basic parameters shown in tables 1 and 2.

Table 1: General Parameters of the FODO 30-250 MeV nonscaling FFAG design.

<i>Parameter</i>	<i>Unit</i>	<i>Injection</i>	<i>Extraction</i>
Energy Range	MeV	30	250
Tune/cell (ν_x / ν_y)	2π -rad	0.33 / 0.24	0.31 / 0.25
Ring tune (ν_x / ν_y)		2.98/2.12	2.79/1.99
Average Radius	M	1.98	2.49
No. Cells		9	
Straight	M	0.241	0.29
Peak Field	T		
F		1.13	2.70
D		-1.55	-3.81

Topic 38b DE-SC0001232 **Advanced Simulation and Optimization Tools for Dynamic Aperture of Non-Scaling FFAGs and Related Accelerators including Modern User Interfaces**

Magnet Lengths	M		
F		0.735	0.958
D		0.187	0.231
Apertures	M		
F		0.53	
D		0.47	

Table 2: General Parameters of the triplet 30-250 MeV nonscaling FFAG design.

<i>Parameter</i>	<i>Unit</i>	<i>Injection</i>	<i>Extraction</i>
Energy Range	MeV	30	250
Tune/cell (ν_x / ν_y)	2π -rad	0.31 / 0.16	0.31 / 0.21
Ring tune (ν_x / ν_y)		2.51/1.28	2.51/1.66
Average Radius	M	2.75	3.39
No. Cells		8	
Long Straight	M	1.17	1.17
Peak Field	T		
F		1.21	3.13
D		-1.37	-3.41
Magnet Lengths	M		
F		0.646	0.803
D		0.129	0.176
Apertures	M		
F		0.63	
D		0.55	

As a first part of the design, the edges of magnets forming the FFAG as well as their field profiles were adjusted so that the tunes of the devices were more uniform, a general feature that is desirable for FFAGs.

Table 3: General Parameters of the triplet 30-250 MeV nonscaling FFAG design after tune optimization in COSY – only tune variations are affected.

<i>Parameter</i>	<i>Unit</i>	<i>Injection</i>	<i>Extraction</i>
Energy Range	MeV	30	250
Tune/cell (ν_x / ν_y)	2π -rad	0.31 / 0.16	0.31 / 0.21

Topic 38b DE-SC0001232 **Advanced Simulation and Optimization Tools for Dynamic Aperture of Non-Scaling FFAGs and Related Accelerators including Modern User Interfaces**

Ring tune (ν_x/ν_y)		2.48/1.28	2.48/1.66
Average Radius	m	2.75	3.39
No. cells		8	
Long Straight	m	1.17	1.17
Peak Field	T		
F		1.21	3.13
D		-1.37	-3.41
Magnet Lengths	m		
F		0.646	0.803
D		0.129	0.176
Apertures	M		
F		0.63	
D		0.55	

The final geometry of the edges of the magnets of system can be drawn directly from within COSY, and the results are as follows, for both a single cell and the resulting ring. Also shows is one of the innermost and outermost closed orbits obtained by COSY’s fitting tools.

The resulting situation for the triplet case is as follows. Shown are again innermost and outermost closed orbits.

Topic 38b DE-SC0001232 **Advanced Simulation and Optimization Tools for Dynamic Aperture of Non-Scaling FFAGs and Related Accelerators including Modern User Interfaces**

For the next examples, a sequence of closed orbits were determined for different energies by optimization. Then, the linear part of the COSY transfer map which is calculated using differential algebraic methods is used to determine the tunes, which are shown in the following tune-versus-radius plots, showing horizontal (red) and vertical (green) tunes.

It can be seen that the vertical tunes of the second system are not as uniform as those of the first; so COSY's global optimizers were utilized to try to fit them comfortably below the half integer resonance by shaping of the pole face radially. The resulting vertical tune swing reduced by a factor of two.

Topic 38b DE-SC0001232 Advanced Simulation and Optimization Tools for Dynamic Aperture of Non-Scaling FFAGs and Related Accelerators including Modern User Interfaces

The next picture shows the radial dependence of the reference orbit as a function of momentum based on the COSY simulations.

We conclude the brief overview of the current state of the COSY test bench by showing tracking simulations to assess the dynamic aperture at various radii for one of the system.

Figure 7. Dynamic aperture a midpoint, 112 MeV, FODO (top), triplet (middle, bottom). DA in all cases for both planes are extremely large.

It has been shown that modern tools for nonlinear tracking using high order effects of all orders are able to simulate in principle the details of the dynamics in FFAGs. It has also been shown that in principle, modern global optimization tools are able to solve many of the complex design questions of modern FFAG layouts. Furthermore, first tests indicate that a novel space charge algorithm based on the so-called Fast Multipole Method (FMM), which has a very favorable cost scaling property of $N \log(N)$ where N is the number of simulation particles, allows the treatment of the intricate beam-to-beam space charge effects that appear.

Bibliography and References – Background on FFAGs

- [1] C. Prior, Editor ICFA Beam Dynamics Newsletter #43, August 2007, <http://www-bd-fnal.gov/icfabd/Newsletter43.pdf>.
- [2] Y. Tanabe, et al., “Evaluation of Magnetic Alloys for JHF Cavity”, APAC ’98, March 1998.
- [3] M. K. Craddock, “New Concepts in FFAG Design for Secondary Beam Facilities and Other Applications”, PAC’05, Knoxville, TN, USA, 16-20, May 2005, p261.
- [4] T. Ohkawa “FFAG Electron Cyclotron” Phys. Rev. 100, 1247 (1955).
- [5] The RACCAM project, France: http://lpsc.in2p3.fr/service_accelerateurs/raccam.htm
- [6] S. Machida, International FFAG designs: <http://hadron.kek.jp/~machida/mirror/misl/publications20090415.pdf>

Topic 38b DE-SC0001232 **Advanced Simulation and Optimization Tools for Dynamic Aperture of Non-Scaling FFAGs and Related Accelerators including Modern User Interfaces**

- [7] E. Keil, Nonscaling FFAG work: publications, <http://keil.home.cern.ch/keil/keil.bib>
- [8] see also the CONFORM project, U.K. (EMMA and PAMELA): <http://www.conform.ac.uk>
- [9] H.S. Synder, private communication.
- [10] A.A. Kolomenskij. "A symmetric circular phasotron with oppositely directed beams" Soviet Physics, JETP, 6, p. 231-3, 1958. English version of 1957 paper in Russian.
- [11] K.R. Symon, D.W. Kerst, L.W. Jones, L.J. Laslett, and K.M. Terwilliger. Fixed-Field Alternating-Gradient Particle Accelerators. Phys. Rev. 103, pp. 1837-1859, Sept. 15, 1956.
- [12] Keith R. Symon. A Strong Focussing Accelerator with a DC Ring Magnet. MURA Notes, 8/13/1954 and D.W. Kerst, K.R. Symon, L.J. Laslett, L.W. Jones, and K.M. Terwilliger. "Fixed field alternating particle accelerators" CERN Symposium Proceedings, v. I, 1956, p. 366.
- [13] D.W. Kerst "Properties of an Intersecting-Beam Accelerating System" CERN Symposium Proceedings V.1 (1956) pp 36-39.
- [14] K. Symon, "MURA Days", PAC'03, Portland, May, 2003, p452.
- [15] K. Long (Ed), "An International Scoping Study of a Neutrino Factory and Super-beam Facility", CARE-Report-2005-024-BENE, 2005.
- [16] C. Johnstone, et al., "Fixed Field Circular Accelerator Designs", PAC'99, New York, P. 3068.
- [17] M. Schillo, AIP Conf. Proc. 600, Cyclotrons and Their Applications 2001, 16th Int. Conf., M.S.U., E. Lansing, MI, USA, pp.37-39.
- [18] NuPECC Report on Impact, Applications, Inter-actions of Nuclear Science (2002). Nuclear Physics European Collaboration Committee <http://www.nupecc.org/iai2001/>
- [19] Keith R. Symon, A Strong Focussing Accelerator with a DC Ring Magnet. MURA Notes, 8/13/1954 and D.W. Kerst, K.R. Symon, L.J. Laslett, L.W. Jones, and K.M. Terwilliger. "Fixed field alternating particle accelerators" CERN Symposium Proceedings, v. I, 1956, p. 366.
- [20] P.B. Keating, et. al., "Electric-field Induced Electron Detachment of 800 MeV H- Ions", Phys Rev A, volume 52 number 6, Dec 1995, p.4547
- [21] M. Berz and K. Makino, COSY INFINIT Version 9.0 Beam Physics Manual, MSUHEP-060803, and COSY INFINITY Version 9.0 Programmer's Manual, MSUHEP-060804, both Dept. Of Physics and Astronomy, Michigan State University (2006) and URL <http://cosyinfinity.org>
- [22] S. Machida, Proc. U.S. Particle Accelerator Conference PAC07, Albuquerque NM, 2007. See also this edition of ICFA Beam Dynamics Newsletter.
- [23] Original patent paper, provisional patent pending, submitted, 2007.
- [24] C. Johnstone, et.al., "A New Nonscaling FFAG for Medical Applications," ICFA Beam Dynamics Newsletter No. 43, July, 2007, <http://www-bd.fnal.gov/icfabd/Newsletter43.pdf>, pp.125-132
- [25] C. Johnstone, et. al., "New Nonscaling FFAG for Medical Applications," *Proceedings of the 2007 Particle Accelerator Conference, Albuquerque, NM, June 25-29, 2007*, pp. 2951.
- [26] C. Johnstone, et. al., "Tune-stabilized Linear Field FFAG for Carbon Therapy," *Proceedings of the 2006 European Particle Accelerator Conference, Edinburgh, UK June 26-30, 2006*, pp. 2290-2292.

Bibliography and References - Beam Dynamics Aspects of FFAGs

- [1] C. Prior, Editor ICFA Beam Dynamics Newsletter #43, August 2007, <http://www-bd.fnal.gov/icfabd/Newsletter43.pdf>.
- [2] M. K. Craddock, "New Concepts in FFAG Design for Secondary Beam Facilities and Other Applications", PAC'05, Knoxville, TN, USA, 16-20, May 2005, p261.
- [3] K.R. Symon, D.W. Kerst, L.W. Jones, L.J. Laslett, and K.M. Terwilliger. Fixed-Field Alternating-Gradient Particle Accelerators. Phys. Rev. 103, pp. 1837-1859, Sept. 15, 1956.
- [4] Y. Mori, FFAG05 Workshop, FNAL, U.S., May, 2005.
- [5] R. Baartman, et. al., CYCLOPS.
- [6] F. Meot, The Ray-Tracing Code Zgoubi, Nuclear Instruments and Methods, A, v. 427, pp. 353—356. 1999.

Topic 38b DE-SC0001232 **Advanced Simulation and Optimization Tools for Dynamic Aperture of Non-Scaling FFAGs and Related Accelerators including Modern User Interfaces**

- [7] F. Lemuett and F. Meot, Developments in the Ray-Tracing Code Zgoubi for 6-D Multiturn Tracking in FFAG Rings, Nuclear Instruments and Methods, A, v. 547, pp. 638—651. 2005.
- [8] MAD Version 9, <http://www.slac.cern.ch/mad/>.
- [9] M. Berz, Modern Map Methods in Particle Beam Physics, Academic Press, San Diego, 1999.
- [10] M. Berz, “Differential Algebraic Description of Beam Dynamics to Very High Orders”, Particle Accelerators, v. 24, p. 109, 1989.
- [11] M. Berz and K. Makino, COSY INFINITY Version 9.0 Beam Physics Manual, MSUHEP-060804, Michigan State University, 2006. <http://cosyinfinity.org> .
- [12] K. Makino and M. Berz, COSY INFINITY Version 9, Nuclear Instruments and Methods, v. 558, pp. 346-350, 2005.
- [13] M. Tawarmalani and N. Sahinidis, Convexification and Global Optimization and Continuous and Mixed-Integer Programming, Kluwer, 2002.
- [14] C. Floudas, Nonlinear and Mixed-Integer Optimization, Oxford University Press, 1995.
- [15] K. Lange, Optimization, Springer, 2004.
- [16] C. Floudas and P. Pardalos, Test Problems for Constrained Global Optimization, 1990.
- [17] V. Lebedev, OptiM.
<http://www.bdnw.fnal.gov/pbar/organizationalchart/lebedev/OptiM/optim.htm> .
- [18] P. Snopok, A Converter Program for Tevatron Lattices from OptiM to COSY INFINITY, MSUHEP-40909, Michigan State University, 2004.
- [19] MATLAB, The MathWorks. <http://www.mathworks.com/products/matlab/> .
- [20] M. Berz, K. Makino, Y.-K. Kim, Long-Term Stability of the Tevatron by Verified Global Optimization, Nucl. Instr. Meth. A 558 (2005) 1-10
- [21] A. Poklonskiy, Evolutionary Optimization Methods for Beam Physics, Ph.D. Thesis, Michigan State University, 2008
- [22] B. Erdelyi, M. Berz, Optimal Symplectic Approximation of Hamiltonian Flows, Phys. Rev. Lett. 87(11) (2001) 114302
- [23] B. Erdelyi, M. Berz, Local Theory and Applications of Extended Generating Functions, Int. J. Pure Appl. Math. 11(3) (2004) 241-282
- [24] K. Makino, Rigorous Analysis of Nonlinear Motion in Particle Accelerators, Ph.D. Thesis, Michigan State University, 1999
- [25] S. Manikonda, M. Berz, Multipole Expansion Solution of the Laplace Equation using Surface Data, Nucl. Instr. Meth. A558, 1 (2006) 175-183
- [26] S. Manikonda, M. Berz, K. Makino, High-Order Verified Solutions of the 3D Laplace Equation, Trans. Comp. 11,4 (2005) 1604-1610
- [27] J. Barnes, and P. Hut. A Hierarchical $O(N \log N)$ Force-Calculation Algorithm. Nature Vol. 324, pp. 446-449, Dec. 4, 1986
- [28] L. Greengard, and V. Rokhlin. A Fast Algorithm for Particle Simulations. J. Comput. Phys. 73, pp. 325-348, 1987
- [29] J. Carrier, L. Greengard, and V. Rokhlin. A Fast Adaptive Multipole Algorithm for Particle Simulations. SIAM J. Sci. Stat. Comput. Vol. 9, No. 4, pp. 669-686, July 1988.
- [30] R. Beatson and L. Greengard. A Short Course on Fast Multipole Methods. Numerical Mathematics and Scientific Computation, Wavelets, Multilevel Methods and Elliptic PDEs. Oxford University Press, pp. 1-37, 1997
- [31] B. Shanker and H. Huang. Accelerated Cartesian Expansions - A Fast Method for Computing of Potentials of the Form $R^{-(n)}$ for All Real n . J. Comput. Phys. 226, pp. 732-753, 2007.