Westinghouse
Astronuclear
Laboratory

SNPO-C

Records

WANL-TME-2756
FEBRUARY 1971

DATA ITEM S-39

**LOADS ANALYSIS REPORT
NUCLEAR SUBSYSTEM**

MASTER

DISTRIBUTION OF THIS DOCUMENT UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

RECEIVED

LEVEL
OHIO

NOV 15 AM 9 47

SUP O-C
CLEVELAND, OHIO

Westinghouse Astronuclear Laboratory

Subcontract NP-1
CODE IDENT NO. 14683

WANL-TME-2756
FEBRUARY 1971

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

DATA ITEM S-39

LOADS ANALYSIS REPORT, NUCLEAR SUBSYSTEM.

APPROVED BY:

F. D. Retallick
F. D. Retallick, Manager
NERVA Engineering

INFORMATION CATEGORY

Unclassified

J. M. Hargrave 2/3/71
AUTHORIZED CLASSIFIER DATE

DISTRIBUTION OF THIS DOCUMENT UNLIMITED

ABSTRACT

This data item identifies the primary structural design loads to which the NERVA engine and its major components are subjected during launch and nuclear stage operation. The loads contained in this report are the basis for structural analysis, design, testing and related documentation. The basic loads report is a working document which directs all structural analysis, design and testing efforts to achieve a high level of structural efficiency, performance and reliability. This analysis will be subject to continuing revision and updating during the design and development phase.

BLANK

TABLE OF CONTENTS

Section

1.0	INTRODUCTION
1.1	PURPOSE OF REPORT
1.2	CONTENTS OF REPORT
2.0	NUCLEAR SUBSYSTEM
2.1	INTRODUCTION
2.1.1	Description of NSS
2.1.2	Contents of Chapter
2.2	SUMMARY OF RESULTS AND CONCLUSIONS
2.2.1	Composite Core
2.2.2	Graphite Core
2.3	APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION
2.3.1	Specification Identification
2.3.2	Applicable Requirements
2.4	METHOD OF ANALYSIS (DESIGN PRACTICES)
2.4.1	Analytical Procedures
2.4.2	Analytical Models
2.4.3	Maturity of Input Data
2.4.4	Validity of Analysis
2.5	RESULTS OF ANALYSIS AND INTERPRETATION
2.5.1	Composite Core
2.5.2	Graphite Core
2.6	REFERENCES

3.0 FUEL ELEMENTS

3.1 INTRODUCTION

3.1.1 Description of Fuel Elements

3.1.2 Contents of Chapter

3.2 SUMMARY OF RESULTS AND CONCLUSIONS

3.2.1 Composite Core

3.2.2 Graphite Core

3.3 APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION

3.3.1 Specification Identification

3.3.2 Applicable Requirements

3.4 METHOD OF ANALYSIS (DESIGN PRACTICES)

3.4.1 Analytical Procedures

3.4.2 Analytical Models

3.4.3 Maturity of Input Data

3.4.4 Validity of Analysis

3.5 RESULTS OF ANALYSIS AND INTERPRETATION

3.5.1 Composite Core

3.5.2 Graphite Core

3.6 REFERENCES

4.0 CLUSTER HARDWARE

4.1 INTRODUCTION

4.1.1 Description of Cluster Hardware

4.1.2 Contents of Chapter

4.2 SUMMARY OF RESULTS AND CONCLUSIONS

4.2.1 Composite Core

4.2.2 Graphite Core

4.3 APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION

4.3.1 Specification Identification

4.3.2 Applicable Requirements

4.4 METHOD OF ANALYSIS (DESIGN PRACTICES)

4.4.1 Analytical Procedures

4.4.2 Analytical Models

4.4.3 Maturity of Input Data

4.4.4 Validity of Analysis

4.5 RESULTS OF ANALYSIS AND INTERPRETATION

4.5.1 Composite Core

4.5.2 Graphite Core

4.6 REFERENCES

5.0 CORE PERIPHERY

5.1 INTRODUCTION

5.1.1 Description of Core Periphery

5.1.2 Contents of Chapter

5.2 SUMMARY OF RESULTS AND CONCLUSIONS

5.2.1 Composite Core

5.2.2 Graphite Core

5.3 APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION

5.3.1 Specification Identification

5.3.2 Applicable Requirements

5.4 METHOD OF ANALYSIS (DESIGN PRACTICES)

5.4.1 Analytical Procedures

5.4.2 Analytical Models

5.4.3 Maturity of Input Data

5.4.4 Validity of Analysis

5.5 RESULTS OF ANALYSIS AND INTERPRETATION

5.5.1 Composite Core

5.5.2 Graphite Core

5.6 REFERENCES

6.0 SUPPORT PLATE AND PLENA

6.1 INTRODUCTION

6.1.1 Description of Support Plate and Plena

6.1.2 Contents of Chapter

6.2 SUMMARY OF RESULTS AND CONCLUSIONS

6.2.1 Composite Core

6.2.2 Graphite Core

6.3 APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION

6.3.1 Specification Identification

6.3.2 Applicable Requirements

6.4 METHOD OF ANALYSIS (DESIGN PRACTICES)

- 6.4.1 Analytical Procedures**
- 6.4.2 Analytical Models**
- 6.4.3 Maturity of Input Data**
- 6.4.4 Validity of Analysis**

6.5 RESULTS OF ANALYSIS AND INTERPRETATION

- 6.5.1 Composite Core**
- 6.5.2 Graphite Core**

6.6 REFERENCES

7.0 INTERNAL SHIELD

7.1 INTRODUCTION

- 7.1.1 Description of Internal Shield**
- 7.1.2 Contents of Chapter**

7.2 SUMMARY OF RESULTS AND CONCLUSIONS

- 7.2.1 Composite Core**
- 7.2.2 Graphite Core**

7.3 APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION

- 7.3.1 Specification Identification**
- 7.3.2 Applicable Requirements**

7.4 METHOD OF ANALYSIS (DESIGN PRACTICES)

- 7.4.1 Analytical Procedures**
- 7.4.2 Analytical Models**
- 7.4.3 Maturity of Input Data**
- 7.4.4 Validity of Analysis**

7.5 RESULTS OF ANALYSIS AND INTERPRETATION

7.5.1 Composite Core

7.5.2 Graphite Core

7.6 REFERENCES

8.0 REFLECTOR ASSEMBLY

8.1 INTRODUCTION

8.1.1 Description of Reflector Assembly

8.1.2 Contents of Chapter

8.2 SUMMARY OF RESULTS AND CONCLUSIONS

8.2.1 Composite Core

8.2.2 Graphite Core

8.3 APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION

8.3.1 Specification Identification

8.3.2 Applicable Requirements

8.4 METHOD OF ANALYSIS (DESIGN PRACTICES)

8.4.1 Analytical Procedures

8.4.2 Analytical Models

8.4.3 Maturity of Input Data

8.4.4 Validity of Analysis

8.5 RESULTS OF ANALYSIS AND INTERPRETATION

8.5.1 Composite Core

8.5.2 Graphite Core

8.6 REFERENCES

9.0 CONTROL DRUM DRIVE ASSEMBLY

9.1 INTRODUCTION

9.1.1 Description of Control Drum Drive Assembly

9.1.2 Contents of Chapter

9.2 SUMMARY OF RESULTS AND CONCLUSIONS

9.2.1 Composite Core

9.2.2 Graphite Core

9.3 APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION

9.3.1 Specification Identification

9.3.2 Applicable Requirements

9.4 METHOD OF ANALYSIS (DESIGN PRACTICES)

9.4.1 Analytical Procedures

9.4.2 Analytical Models

9.4.3 Maturity of Input Data

9.4.4 Validity of Analysis

9.5 RESULTS OF ANALYSIS AND INTERPRETATION

9.5.1 Composite Core

9.5.2 Graphite Core

9.6 REFERENCES

10.0 STRUCTURAL SUPPORT COOLANT ASSEMBLY

10.1 STRUCTURAL SUPPORT COOLANT VALVE

10.2 STRUCTURAL SUPPORT COOLANT VALVE ACTUATOR

- 10.2.1 Introduction
- 10.2.2 Summary of Results and Conclusions
- 10.2.3 Applicable Requirements and Compatibility of Structural Performance with the NSS Specification
- 10.2.4 Method of Analysis (Design Practices)
- 10.2.5 Results of Analysis
- 10.2.6 References

LIST OF ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
2-1	Schematic of Nuclear Subsystem	2-42
2-2	"Reference Profiles" for Startup and Shutdown	2-43
2-3	Flow Chart of Nuclear, Thermal and Structural Analyses	2-44
2-4	Flow Chart for the Development of Structural Analytic Models	2-45
2-5	Flow Chart of Structural Boundary Conditions	2-46
2-6	Flow Chart of Structural Calculations	2-47
2-7	Schematic of TNT-2 Program	2-48
2-8	Cumulative Distribution Function for Transformation of Random Numbers to Random Multiplication Factors	2-49
2-9	Flow Scheme for S-039 Data Generation	2-50
2-10	Nozzle Chamber Temperature and Pressure, Composite Core, Sol, Shutdown	2-51
2-11	Thermal and Fluid Parameters, Composite Core, Sol, Shutdown	2-52

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
6-1. Support Plate Displacement And Bow Diagram	6-11
6-2. Piping Cylinder Load and Displacement Diagram	6-12
6-3. Support Stem Feed and Bypass Piping Load, Moment And Displacement Diagram	6-13
6-4. Axial Load, Top of Piping Cylinder Versus Time, CSUS	6-46
6-5. Axial Load, Top of Piping Cylinder Versus Time, CSUE	6-47
6-6. Axial Load, Top of Piping Cylinder Versus Time, CSDSE	6-48
6-7. Axial Displacement, Top of Piping Cylinder Versus Time, CSUS	6-49
6-8. Axial Displacement, Top of Piping Cylinder Versus Time, CSUE	6-50
6-9. Axial Displacement, Top of Piping Cylinder Versus Time, CSDSE	6-51
6-10. Support Plate Bow Versus Time, CSUS	6-52
6-11. Support Plate Bow Versus Time, CSUE	6-53
6-12. Support Plate Bow Versus Time, CSDSE	6-54
6-13. Support Plate Slope at the Periphery Versus Time, CSUS	6-55
6-14. Support Plate Slope at the Periphery Versus Time, CSUE	6-56
6-15. Support Plate Slope at the Periphery Versus Time, CSDSE	6-57
6-16. Radial Growth of Support Plate Versus Time, CSUS	6-58
6-17. Radial Growth of Support Plate Versus Time, CSUE	6-59
6-18. Radial Growth of Support Plate Versus Time, CSDSE	6-60
6-19. Radial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUS	6-61

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
6-20. Radial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUE	6-62
6-21. Radial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSDSE	6-63
6-22. Axial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUS	6-64
6-23. Axial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUE	6-65
6-24. Axial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSDSE	6-66
6-25. Tangential Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUS	6-67
6-26. Tangential Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUE	6-68
6-27. Tangential Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSDSE	6-69
6-28. Radial Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUS	6-70
6-29. Radial Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUE	6-71
6-30. Radial Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSDSE	6-72
6-31. Torsional Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUS	6-73
6-32. Torsional Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUE	6-74

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
6-33. Torsional Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSDSE	6-75
6-34. Tangential Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUS	6-76
6-35. Tangential Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUE	6-77
6-36. Tangential Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSDSE	6-78
6-37. Radial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, CSUS	6-79
6-38. Radial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, CSUE	6-80
6-39. Radial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, CSDSE	6-81
6-40. Axial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, CSUS	6-82
6-41. Axial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, CSUE	6-83
6-42. Axial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, CSDSE	6-84
6-43. Radial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUS	6-85
6-44. Radial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUE	6-86
6-45. Radial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSDSE	6-87

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
6-46. Axial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUS	6-88
6-47. Axial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUE	6-89
6-48. Axial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSDSE	6-90
6-49. Tangential Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUS	6-91
6-50. Tangential Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUE	6-92
6-51. Tangential Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSDSE	6-93
6-52. Radial Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUS	6-94
6-53. Radial Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUE	6-95
6-54. Radial Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSDSE	6-96
6-55. Torsional Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUS	6-97
6-56. Torsional Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUE	6-98
6-57. Torsional Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSDSE	6-99
6-58. Tangential Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUS	6-100

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
6-59. Tangential Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUE	6-101
6-60. Tangential Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSDSE	6-102
6-61. Axial Load, Top of Piping Cylinder Versus Time, GSUSE	6-103
6-62. Axial Load, Top of Piping Cylinder Versus Time, GSDS	6-104
6-63. Axial Load, Top of Piping Cylinder Versus Time, GSDE	6-105
6-64. Axial Displacement, Top of Piping Cylinder Versus Time, GSUSE	6-106
6-65. Axial Displacement, Top of Piping Cylinder Versus Time, GSDS	6-107
6-66. Axial Displacement, Top of Piping Cylinder Versus Time, GSDE	6-108
6-67. Support Plate Bow Versus Time, GSUSE	6-109
6-68. Support Plate Bow Versus Time, GSDS	6-110
6-69. Support Plate Bow Versus Time, GSDE	6-111
6-70. Support Plate Slope at the Periphery Versus Time, GSUSE	6-112
6-71. Support Plate Slope at the Periphery Versus Time, GSDS	6-113
6-72. Support Plate Slope at the Periphery Versus Time, GSDE	6-114
6-73. Radial Growth of Support Plate Versus Time, GSUSE	6-115
6-74. Radial Growth of Support Plate Versus Time, GSDS	6-116
6-75. Radial Growth of Support Plate Versus Time, GSDE	6-117
6-76. Radial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSUSE	6-118

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
6-77. Radial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDS	6-119
6-78. Radial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDE	6-120
6-79. Axial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSUSE	6-121
6-80. Axial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDS	6-122
6-81. Axial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDE	6-123
6-82. Tangential Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSUSE	6-124
6-83. Tangential Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDS	6-125
6-84. Tangential Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDE	6-126
6-85. Radial Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSUSE	6-127
6-86. Radial Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDS	6-128
6-87. Radial Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDE	6-129
6-88. Torsional Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSUSE	6-130
6-89. Torsional Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDS	6-131

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
6-90. Torsional Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDE	6-132
6-91. Tangential Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSUSE	6-133
6-92. Tangential Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDS	6-134
6-93. Tangential Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDE	6-135
6-94. Radial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, GSUSE	6-136
6-95. Radial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, GSDS	6-137
6-96. Radial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, GSDE	6-138
6-97. Axial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, GSUSE	6-139
6-98. Axial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, GSDS	6-140
6-99. Axial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, GSDE	6-141
6-100. Radial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSUSE	6-142
6-101. Radial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDS	6-143
6-102. Radial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDE	6-144
6-103. Axial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSUSE	6-145

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
6-104. Axial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDS	6-146
6-105. Axial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDE	6-147
6-106. Tangential Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSUSE	6-148
6-107. Tangential Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDS	6-149
6-108. Tangential Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDE	6-150
6-109. Radial Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSUSE	6-151
6-110. Radial Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDS	6-152
6-111. Radial Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDE	6-153
6-112. Torsional Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSUSE	6-154
6-113. Torsional Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDS	6-155
6-114. Torsional Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDE	6-156
6-115. Tangential Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSUSE	6-157
6-116. Tangential Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDS	6-158
6-117. Tangential Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDE	6-159

LIST OF ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
7-1.	Internal Shields Pressure Load Diagram	7-9
7-2.	Axial Pressure Load Across Central Shield Versus Time, CSUS	7-12
7-3.	Axial Pressure Load Across Central Shield Versus Time, CSUE	7-13
7-4.	Axial Pressure Load Across Central Shield Versus Time, CSDSE	7-14
7-5.	Axial Pressure Load Across Peripheral Shield Versus Time, CSUS	7-15
7-6.	Axial Pressure Load Across Peripheral Shield Versus Time, CSUE	7-16
7-7.	Axial Pressure Load Across Peripheral Shield Versus Time, CSDSE	7-17
7-8.	Axial Pressure Load Across Central Shield Versus Time, GSUSE	7-18
7-9.	Axial Pressure Load Across Central Shield Versus Time, GSDS	7-19
7-10.	Axial Pressure Load Across Central Shield Versus Time, GSDE	7-20
7-11.	Axial Pressure Load Across Peripheral Shield Versus Time, GSUSE	7-21
7-12.	Axial Pressure Load Across Peripheral Shield Versus Time, GSDS	7-22
7-13.	Axial Pressure Load Across Peripheral Shield Versus Time, GSDE	7-23

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
8-1. Top of Reflector Barrel Loads, Moments And Displacements Diagram	8-10
8-2. Nozzle, Standoff, And Bottom Of Reflector Barrel Loads, Moments And Displacements Diagram	8-11
8-3. Radial Force, Top of Reflector Barrel Versus Time, CSUS	8-20
8-4. Radial Force, Top of Reflector Barrel Versus Time, CSUE	8-21
8-5. Radial Force, Top of Reflector Barrel Versus Time, CSDSE	8-22
8-6. Axial Load, Top of Reflector Barrel Versus Time, CSUS	8-23
8-7. Axial Load, Top of Reflector Barrel Versus Time, CSUE	8-24
8-8. Axial Load, Top of Reflector Barrel Versus Time, CSDSE	8-25
8-9. Tangential Moment, Top of Reflector Barrel Versus Time, CSUS	8-26
8-10. Tangential Moment, Top of Reflector Barrel Versus Time, CSUE	8-27
8-11. Tangential Moment, Top of Reflector Barrel Versus Time, CSDSE	8-28
8-12. Radial Displacement, Top of Reflector Barrel Versus Time, CSUS	8-29
8-13. Radial Displacement, Top of Reflector Barrel Versus Time, CSUE	8-30

LIST OF ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
8-14.	Radial Displacement, Top of Reflector Barrel Versus Time, CSDSE	8-31
8-15.	Axial Displacement, Top of Reflector Barrel Versus Time, CSUS	8-32
8-16.	Axial Displacement, Top of Reflector Barrel Versus Time, CSUE	8-33
8-17.	Axial Displacement, Top of Reflector Barrel Versus Time, CSDSE	8-34
8-18.	Axial Nozzle Load Versus Time, CSUS	8-35
8-19.	Axial Nozzle Load Versus Time, CSUE	8-36
8-20.	Axial Nozzle Load Versus Time, CSDSE	8-37
8-21	Axial Standoff Load Versus Time, CSUS	8-38
8-22.	Axial Standoff Load Versus Time, CSUE	8-39
8-23.	Axial Standoff Load Versus Time, CSDSE	8-40
8-24.	Axial Displacement, Bottom of Reflector Barrel Versus Time, CSUS	8-41
8-25.	Axial Displacement, Bottom of Reflector Barrel Versus Time, CSUE	8-42
8-26.	Axial Displacement, Bottom of Reflector Barrel Versus Time, CSDSE	8-43
8-27.	Radial Force, Top of Reflector Barrel Versus Time, GSUSE	8-44

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
8-28. Radial Force, Top of Reflector Barrel Versus Time, GSDS	8-45
8-29. Radial Force, Top of Reflector Barrel Versus Time, GSDE	8-46
8-30. Axial Load, Top of Reflector Barrel Versus Time, GSUSE	8-47
8-31. Axial Load, Top of Reflector Barrel Versus Time, GSDS	8-48
8-32. Axial Load, Top of Reflector Barrel Versus Time, GSDE	8-49
8-33. Tangential Moment, Top of Reflector Barrel, Versus Time, GSUSE	8-50
8-34. Tangential Moment, Top of Reflector Barrel Versus Time, GSDS	8-51
8-35. Tangential Moment, Top of Reflector Barrel Versus Time, GSDE	8-52
8-36. Radial Displacement, Top of Reflector Barrel Versus Time, GSUSE	8-53
8-37. Radial Displacement, Top of Reflector Barrel Versus Time, GSDS	8-54
8-38. Radial Displacement, Top of Reflector Barrel Versus Time, GSDE	8-55
8-39. Axial Displacement, Top of Reflector Barrel Versus Time, GSUSE	8-56
8-40. Axial Displacement, Top of Reflector Barrel Versus Time, GSDS	8-57
8-41. Axial Displacement, Top of Reflector Barrel Versus Time, GSDE	8-58

LIST OF ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
8-42.	Axial Nozzle Load Versus Time, GSUSE	8-59
8-43.	Axial Nozzle Load Versus Time, GSDS	8-60
8-44.	Axial Nozzle Load Versus Time, GSDE	8-61
8-45.	Axial Standoff Load Versus Time, GSUSE	8-62
8-46.	Axial Standoff Load Versus Time, GSDS	8-63
8-47.	Axial Standoff Load Versus Time, GSDE	8-64
8-48.	Axial Displacement, Bottom of Reflector Barrel Versus Time, GSUSE	8-65
8-49.	Axial Displacement, Bottom of Reflector Barrel Versus Time, GSDS	8-66
8-50.	Axial Displacement, Bottom of Reflector Barrel Versus Time, GSDE	8-67

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
9-1. CDA Housing Pedestal And Bolt Load And Moment Diagram	9-10
9-2. Axial Load From CDA Housing to Dome Pedestal Versus Time, CSUS	9-14
9-3. Axial Load From CDA Housing to Dome Pedestal Versus Time, CSUE	9-15
9-4. Axial Load From CDA Housing to Dome Pedestal Versus Time, CSDSE	9-16
9-5. Tensile Load on CDA Housing Bolt Versus Time, CSUS	9-17
9-6. Tensile Load on CDA Housing Bolt Versus Time, CSUE	9-18
9-7. Tensile Load on CDA Housing Bolt Versus Time, CSDSE	9-19
9-8. Axial Load from CDA Housing to Dome Pedestal Versus Time, GSUSE	9-20
9-9. Axial Load From CDA Housing to Dome Pedestal Versus Time, GSDS	9-21
9-10. Axial Load from CDA Housing to Dome Pedestal Versus Time, GSDE	9-22
9-11. Tensile Load on CDA Housing Bolt Versus Time, GSUSE	9-23
9-12. Tensile Load on CDA Housing Bolt Versus Time, GSDS	9-24
9-13. Tensile Load on CDA Housing Bolt Versus Time, GSDE	9-25

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
10-1. SSCVA Housing Pedestal And Bolt Load And Moment Diagram	10-8
10-2. Axial Load From SSCVA to Valve Housing Pedestal Versus Time, CSUS"	10-12
10-3. Axial Load From SSCVA to Valve Housing Pedestal Versus Time, CSUE"	10-13
10-4. Axial Load From SSCVA to Valve Housing Pedestal Versus Time, CSDSE"	10-14
10-5. Tensile Load on SSCVA Housing Bolt Versus Time, CSUS	10-15
10-6. Tensile Load on SSCVA Housing Bolt Versus Time, CSUE	10-16
10-7. Tensile Load on SSCVA Housing Bolt Versus Time, CSDSE	10-17
10-8. Axial Load from SSCVA to Valve Housing Pedestal Versus Time, GSUSE	10-18
10-9. Axial Load From SSCVA to Valve Housing Pedestal Versus Time, GSDS	10-19
10-10. Axial Load from SSCVA to Valve Housing Pedestal Versus Time, GSDE	10-20
10-11. Tensile Load on SSCVA Housing Bolt Versus Time, GSUSE	10-21
10-12. Tensile Load on SSCVA Housing Bolt Versus Time, GSDS	10-22
10-13. Tensile Load on SSCVA Housing Bolt Versus Time, GSDE	10-23

LIST OF TABLES

<u>Table</u>		<u>Page</u>
2-1	ECCs In The Nuclear Subsystem	2-40
2-2	Selection of Random Multiplication Factors (RMF) To Prepare TNT and Rats Input for 30 Monte Carlo Calculations	2-41
6-1	Support Plate Bow - in.	6-14
6-2	Radial Growth of Support Plate	6-15
6-3	Axial Load, Top of Piping Cylinder - lb.	6-16
6-4	Axial Displacement, Top of Piping Cylinder - in.	6-17
6-5	Radial Force on Stem Feed Pipe at the Pressure Vessel Dome - lb.	6-18
6-6	Axial Force on Stem Feed Pipe at the Pressure Vessel Dome - lb.	6-19
6-7	Tangential Force on Stem Feed Pipe at the Pressure Vessel Dome - lb.	6-20
6-8	Radial Moment on Stem Feed Pipe at the Pressure Vessel Dome - in. - lb.	6-21
6-9	Torsional Moment on Stem Feed Pipe at the Pressure Vessel Dome - in. - lb.	6-22
6-10	Tangential Moment on Stem Feed Pipe at the Pressure Vessel Dome - in. - lb.	6-23
6-11	Radial Force on Stem Bypass Pipe at the Pressure Vessel Dome - lb.	6-24
6-12	Axial Force on Stem Bypass Pipe at the Pressure Vessel Dome - lb.	6-25
6-13	Tangential Force on Stem Bypass Pipe at the Pressure Vessel Dome - lb.	6-26
6-14	Radial Moment on Stem Bypass Pipe at the Pressure Vessel Dome - in. - lb.	6-27
6-15	Torsional Moment on Stem Bypass Pipe at the Pressure Vessel Dome - in. - lb.	6-28
6-16	Tangential Moment on Stem Bypass Pipe at the Pressure Vessel dome - in. - lb.	6-29
6-17	Radial Force on Stem Feed Pipe at the Support Plate - lb.	6-30
6-18	Axial Force on Stem Feed Pipe at the Support Plate - lb.	6-31
6-19	Tangential Force on Stem Feed Pipe at the Support Plate - lb.	6-32

LIST OF TABLES

<u>Table</u>		<u>Page</u>
6-20	Radial Moment on Stem Feed Pipe at the Support Plate - in. - lb.	6-33
6-21	Torsional Moment on Stem Feed Pipe at the Support Plate - in. - lb.	6-34
6-22	Tangential Moment on Stem Feed Pipe at the Support Plate - in. - lb.	6-35
6-23	Radial Force on Stem Bypass Pipe at the Support Plate - lb.	6-36
6-24	Axial Force on Stem Bypass Pipe at the Support Plate - lb.	6-37
6-25	Tangential Force on Stem Bypass Pipe at the Support Plate - lb.	6-38
6-26	Radial Moment on Stem Bypass Pipe at the Support Plate - in. - lb.	6-39
6-27	Torsional Moment on Stem Bypass Pipe at the Support Plate - in. - lb.	6-40
6-28	Tangential Moment on Stem Bypass Pipe at the Support Plate - in. - lb.	6-41
6-29	Radial Displacement of Stem Feed at Pressure Vessel Dome Relative to Support Plate - in.	6-42
6-30	Radial Displacement of Stem Bypass at Pressure Vessel Dome Relative to Support Plate - in.	6-43
6-31	Axial Displacement of Stem Feed at Pressure Vessel Dome Relative to Support Plate - in.	6-44
6-32	Axial Displacement of Stem Bypass at Pressure Vessel Dome Relative to Support Plate - in.	6-45
7-1	Axial Pressure Load Across Central Shield - lb.	7-10
7-2	Axial Pressure Load Across Peripheral Shield - lb.	7-11
8-1	Axial Load, Top of Reflector Barrel - lb.	8-12
8-2	Radial Force, Top of Reflector Barrel - lb.	8-13
8-3	Axial Displacement, Top of Reflector Barrel - in.	8-14
8-4	Radial Displacement, Top of Reflector Barrel - in.	8-15

LIST OF TABLES

<u>Table</u>		<u>Page</u>
8-5	Tangential Moment, Top of Reflector Barrel - in. - lb.	8-16
8-6	Axial Nozzle Load - lb.	8-17
8-7	Axial Displacement, Bottom of Reflector Barrel - in.	8-18
8-8	Axial Standoff Load - lb.	8-19
9-1	Axial Load From CDA Housing to Dome Pedestal - lb.	9-11
9-2	Tensile Load on CDA Housing Bolt - lb.	9-12
9-3	Axial Torque From CDA to Dome Pedestal - IN- LB.	9-13
10-1	Axial Load From SSCVA to Valve Housing Pedestal - lb.	10-9
10-2	Tensile Load on SSCVA Housing Bolt - lb.	10-10
10-3	Axial Torque From SSCVA to Dome Pedestal - IN-LB.	10-11

1.0 INTRODUCTION

1.1 PURPOSE OF REPORT

This Structural Design Analysis Report documents the detailed analysis conducted for the following:

1. To derive and establish performance and design requirements for the NERVA NSS subsystem and components.
2. To establish and substantiate appropriate parameters of the subject design.
3. To provide the source for steady state and transient environment conditions for structural evaluations of ECC components.

1.2 CONTENTS OF REPORT

This report contains the results of steady state and transient analyses, for both composite and graphite fueled cores, based on the thermal and hydraulic data contained in the S-31⁽¹⁾ data item. Curves and/or tables are included giving the resultant loads, displacements, bending moments and torsional moments for each ECC. These data are calculated at selected critical stations to sufficiently provide comprehensive structural verification of the design. An evaluation of the effects of uncertainties is included. All statistical data is reported at a calculated confidence level of .95. Structural analysis is performed in accordance with the criteria of SNSO-C-1⁽¹²⁾, "NERVA Program Structural Design Requirements."

Structural data are presented for Nuclear Subsystem (NSS) as a whole in Chapter 2 and for the following Engineering Critical Components (ECC) in the chapter indicated:

1. Support Plate and Plena, ECC 677561 (Chapter 6)
2. Internal Shield, ECC 677562 (Chapter 7)
3. Reflector Assembly, ECC 677559 (Chapter 8)

4. Control Drum Drive Assembly, ECC 677585 (Chapter 9)
5. Structural Support Coolant Assembly, ECC 677575 (Chapter 10)
6. NSS Instrumentation, ECC 677565 (Chapter 11)

Structural data for the following ECCs are not presented because these ECCs are involved in Trade Studies:

1. Fuel Element, ECC 677566 (Chapter 3), Trade Study No. 772
2. Cluster Hardware, ECC 677558 (Chapter 4), Trade Study No. 774
3. Core Periphery, ECC 677564 (Chapter 5), Trade Study No. 778
4. The Lateral Support portion of the Reflector Assembly, ECC 677562 (Chapter 8), Trade Study No. 782

This document consists of eleven chapters, nine of which refer specifically to a given ECC. Major sections of each chapter are uniform throughout this report and include:

1. Summary of Results and Conclusions - A critical evaluation of the results obtained in the preparation of this document is presented. Results are reviewed and compared with respect to various reactor operating conditions.
2. Requirements - The environmental requirements are documented for each ECC.
3. Method of Analysis (Design Practices) - The results of each analysis include a description and justification of the analytical procedures and methods of analysis.
4. Maturity of Data Input - Parameters on which the data are based, such as material properties, geometry input and hydraulic state points are referenced.
5. Validity of Analysis - An evaluation of the validity and applicability of analytical methods and procedures is presented for each ECC.
6. References - Documents and computer outputs supporting the data presentation are referenced and available for review.

2.0 NUCLEAR SUBSYSTEM CP-677555

2.1 INTRODUCTION

The Nuclear Subsystem (NSS) is a part of the Contract End Item described as Engine, NERVA, 75K, Full Flow, as established by SNSO-NPRD-1, and is listed as a subsystem in detail specification CP-90290. The NSS is used as a source of thermal energy for the engine when used in both manned and unmanned space vehicle application.

2.1.1 Description of Nuclear Subsystem

The following general design features are given in CP-677555A for the NSS:

"3.3.1 General Design Features

The NSS consists of a hydrogen cooled, graphite moderated, intermediate neutron energy reactor and its associated reactivity control devices consisting of neutron absorbing control drums with their actuation system and the Structural Support Coolant Assembly."

Supplemental descriptive information follows:

The reactor includes a core, reflector, core support plate and associated piping and an internal shield. The core contains fuel element clusters. Each cluster, except for the irregular clusters in the periphery, consists of 6 fueled elements surrounding a central unfueled element. A counterflow support stem passes through each central element to the support plate. The support stems carry the core pressure drop load to the core support plate and also accommodate a varying hydrogen inventory for core reactivity control.

The core support plate transmits the core pressure drop load to the reflector and also incorporates plenums for support stem hydrogen feed, exhaust and bypass.

The reflector surrounds the core and as its name implies reflects neutrons into the core to sustain reactivity. A lateral support system is also housed in the reflector. This supplies radial restraint for the core acting through the core periphery which consists of thermal and flow barriers backed up by filler strips which round the core into a cylindrical shape for interfacing with the lateral support. Eighteen control drums are contained in the

reflector. Each control drum has a neutron absorbing plate covering approximately 120 degrees of its external surface. Synchronous rotation of the control drums provides the means then to establish reactor criticality.

An internal shield which provides radiation protection for engine components and NSS instrumentation complete the major components of the reactor.

Figure 2-1 presents a schematic representation of the NSS

2.1.2 Contents of Chapter

This chapter contains the NSS static loads environment description, analytical models, results and conclusions of calculations determining the static loads and displacements of ECC interfaces for the NSS during handling and shipping, ground tests, launch and boost, startup, nominal flight steady state, shutdown, non-operation, growth and malfunction modes. Table 2-1 lists the engineering critical components of the NSS.

2.2 SUMMARY OF RESULTS AND CONCLUSIONS

Structural analyses on a nuclear subsystem level have been performed for the Reference Design Drawing 939J740, with the reference composite core as well as with a graphite core. The principal intent of these analyses was to provide steady-state and transient boundary conditions for the detailed structural analysis of the NSS components. In addition to the nominal calculations, selected steady state conditions were analyzed probabilistically with the purpose of providing guidance for the detailed component analyses with regard to load and stress uncertainties.

The mean values of loads, displacements and moments calculated for the individual components are supplied in the component chapters. The conditions covered for both composite and graphite cores are Start of Life (SOL) and End of Life (EOL) for

Rated Power

65% Throttle

80% Power, Single TPA

65% Throttle, Single TPA

Growth Mode, $T_c = 4500^\circ\text{R}$

The Rated Power condition was analyzed for both transient and steady state operation while the other modes were analyzed for steady state operation only.

Uncertainties are given for Rated Power, 65% Throttle, and 80% Power, Single TPA. Only the reference composite core has been analyzed statistically.

A review of the NSS structural model results indicates the following conditions as the times of greatest mechanical or hydraulic load for the majority of individual components:

Support Plate and Plena	80% Power, Single TPA, SOL Composite Core
Internal Shield	Growth Mode, SOL (Graphite Core)
Reflector Assembly	80% Power, Single TPA, SOL (Composite Core)
Control Drum Drive Assembly	80% Power, Single TPA, SOL
Structural Support Coolant Valve Actuator	Rated Power, SOL

2.3 APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION

The Nuclear Subsystem is required to satisfactorily support loads during handling, shipping, ground test, launch, boost and reactor operations. The requirements and design conditions stated in this Section are specified in CP-677555A, Section 3.0, issued on September 28, 1970.

"3.1.1.1.1 Operational Modes - The NSS shall be capable of operation within the following modes:

- (a) Normal Mode
- (b) Malfunction Mode
 - (1) Single Turbopump Operation
 - (2) Component Malfunction Mode
- (c) Emergency Modes

In this chapter, only the Normal Mode and the Malfunction Mode, Single Turbopump Operation, will be reported at the maturity level required at NSS PDR.

"3.1.1.1.2 Rated Performance - The NSS performance rating is based on the capability of steady state operation identified by the following:

- (a) Nominal thermal Power 1510 Mw
- (b) Mixed mean chamber inlet stagnation temperature
(Nominal $\pm 2.326 \sigma$
including $\bar{\alpha}$ controllability
tolerance of tbd) $4250^{\circ}R \pm 40^{\circ}R$
- (c) Nominal chamber stagnation pressure 450 psia
- (d) Nominal chamber flow rate 91.2 lb/sec
- (e) Normal Mode Endurance --
600 minutes at rated temperature
(accumulated in up to 60 cycles
of varying duration up to 60 minutes maximum per cycle)."

The NSS design parameters and environment at steady state rated operation is reported in Data Item S-031 and satisfy the rated performance requirements stated in Section 3.1.1.1.2, (a) through (d).

"3.1.1.1.5.1.2 Startup Operations - Startup operations consist of temperature conditioning, nuclear startup, bootstrap and thrust buildup. Startup begins at the receipt of a command signal to initiate propellant flow or nuclear startup and is completed when rated performance has been achieved within specified controllability limits."

"3.1.1.1.5.1.2.2 Bootstrap - Bootstrap operation consists of the establishment of powered pump operation using the heat energy available within the engine system. Bootstrap is initiated at the completion of Temperature Conditioning and Nuclear Startup and propellant flow is admitted to the turbine. It is terminated with the initiation of Thrust Buildup which is coincident with the achievement of chamber conditions of (tbd)."

"3.1.1.1.5.1.2.3 Thrust Buildup - Following Bootstrap, a programmed increase in chamber temperature and pressure is initiated and completed at the attainment of Steady State Operations.

The NSS shall be capable of rates of change of temperature and pressures consistent with the following rates of change of chamber temperature and pressure.

(a) $150 \pm 25^{\circ}\text{R}/\text{sec}$ for $1100^{\circ}\text{R} \leq T_c \leq 4250^{\circ}\text{R}$

(b) $50 \pm 10 \text{ psi}/\text{sec}$ for $293 \text{ psia} \leq P_c \leq 450 \text{ psia}$

During this phase, the control drum shutdown capability shall not be less than \$0.25; and the mixed mean chamber inlet temperatures shall not exceed (tbd) $^{\circ}\text{R}$."

The reference nominal high impulse startup is shown on the demand profile Drawing 939J746, Figure 2-2. This reference startup produces a chamber temperature ramp rate of $175^{\circ}\text{R}/\text{sec}$. This T_c ramp of $175^{\circ}\text{R}/\text{sec}$ equals the nominal startup ramp of $150^{\circ}\text{R}/\text{sec}$ specified in the NSS Requirement Specification CP-677555A, plus an uncertainty of $+ 25^{\circ}\text{R}/\text{sec}$. This presents the specification extreme on the T_c ramp parameter for the NSS

assembly and was used to provide material temperature and pressure data under extreme transient ramp conditions. The static load environment for this flight operation startup is documented in (TBD).

"3.1.1.1.5.1.3 Steady State Operation - Steady State is initiated by the attainment of specified conditions of chamber temperature and pressure and is terminated by receipt of a command signal to begin retreat from this point. The NSS shall be capable of the operation specified in 3.1.1.1.2 (Rated Performance)."

"3.1.1.1.5.1.3.1 Core Temperature Profile - Based on preselected fixed drum operation at rated performance, the NSS shall be capable of limiting the radial and axial variations in core exit gas temperatures during rated performance operation to $\pm 150^{\circ}\text{R}$ with respect to the instantaneous average core exit gas temperature. (This requirement shall not apply to the lateral support and core periphery flow). As an aid in achieving the above, the NSS shall be designated such that reactivity adjustment requirements at rated operations can be satisfied by adjustments in the support stem assembly (SSA) flow rate equivalent of ± 2.00 as a minimum."

"3.1.1.1.5.1.3.2 Temperature Controllability - The NSS shall have the capability for reactivity adjustments at rated operation such that the measured chamber temperature can be held within $\pm$ (tbd) $^{\circ}\text{R}$ while the chamber temperature is varied by $\pm$ (tbd) psi about its nominal value."

The static loads environment for flight steady state reactor operation is similar to the ground test loads without gravity considerations. The loads environment is documented in IED 482 - C, Reference (3).

"3.1.1.1.5.1.4 Shutdown Operations - Shutdown Operations consist of Throttling, Throttle Hold, Temperature Retreat, and Pump Tailoff. Shutdown is initiated by a command signal to depart from steady state conditions and is completed upon termination of powered pump operation. During these operations, the control drums shall be commanded to the position

to provide maximum reactivity shutdown. The NSS shall be capable of providing the dynamic reactivity to reduce thermal power from steady state operation when satisfying the following requirements."

"3.1.1.1.5.1.4.1 Throttling - Throttling consists of a ramp down in chamber pressure at rated temperature. The throttling phase is initiated by a command signal to depart from steady state operation and is terminated when the throttle point is reached. The NSS shall be capable of rates of change of pressure consistent with a chamber pressure transient of -50 ± 10 psi/sec for $293 \text{ psia} \leq P_c \leq 450 \text{ psia}$, and shall be capable of reactivity adjustments consistent with maintaining rated chamber temperature within $\pm$ (tbd) $^{\circ}\text{R}$ during the transient. So far as possible, the reactivity adjustment shall be effected by changes in structural support flow."

"3.1.1.1.5.1.4.2 Throttle Hold - The NSS shall be capable of a throttle hold identified by a nominal chamber pressure of 293 psia and a mixed mean chamber inlet temperature of $4250^{\circ}\text{R} \pm 40^{\circ}\text{R}$ (2.326σ). While at the operating point, the NSS shall be capable of satisfying the pressure, temperature, and flow requirements shown on Tables 3* and 4*. The throttle hold phase is initiated when the throttle point is reached and is terminated by a command signal to depart from rated temperature. The temperature controllability requirements of Paragraphs 3.1.1.1.5.1.3.1 (Core Temperature Profile) and 3.1.1.1.5.1.3 (Temperature Controllability) shall also apply during the Throttle Hold with the loss of core reactivity of \$1.20.

The maximum duration for single throttle hold operations shall not exceed (tbd) seconds; and the throttle hold shall be limited to chamber pressures greater than (tbd) psia."

* These Tables contain flow characteristics data, and refer to the specification CP-677555A.

"3.1.1.1.5.1.4.3 Temperature Retreat - Following the throttle hold phase, a programmed decrease in chamber temperature and pressure is initiated and is completed when pump tailoff is initiated.

The NSS shall be capable of rates of change of temperature and pressures consistent with the following rates of change of chamber temperature and pressure.

- (a) $-150 \pm 25^{\circ}\text{R}/\text{sec}$ for $(\text{tbd})^{\circ}\text{R} \leq T_c \leq 4250^{\circ}\text{R}$
- (b) $(\text{tbd}) \pm (\text{tbd}) \text{ psi}/\text{sec}$ for $(\text{tbd}) \text{ psia} \leq P_c \leq 293 \text{ psia}."$

"3.1.1.1.5.1.4.4 Pump Tailoff - The pump tailoff phase is that portion of shutdown between the end of Temperature Retreat and the termination of powered pump operation. The NSS shall have a shutdown reactivity capability of (tbd) \$. This phase shall be completed within (tbd) seconds."

The reference nominal high impulse shutdown is shown on Drawing 939J746, Figure 2-2. This reference shutdown produces a chamber temperature ramp rate of $-175^{\circ}\text{R}/\text{sec}$. This T_c ramp of $-175^{\circ}\text{R}/\text{sec}$ equals the nominal shutdown ramp of $-150^{\circ}\text{R}/\text{sec}$ specified in the NSS Requirement Specification CP-677555A, plus an uncertainty of $-25^{\circ}\text{R}/\text{sec}$. This presents the specification extreme on the T_c ramp parameter for the NSS assembly and was used to provide material temperature and pressure data under extreme transient ramp conditions. The loads environment for the high impulse flight operation shutdown is given in (TBD).

"3.1.1.1.5.1.5 Cooldown Operations - Cooldown is initiated upon completion of shutdown and is completed upon final termination of propellant flow or the receipt of a command signal for restart; (i. e., prestart and cooldown may overlap)."

Cooldown operations are not included in this Data End Item Report.

"3.1.1.1.5.2 Malfunction Modes - The NSS shall be capable of meeting the following performance requirements when operating under the following malfunction conditions. The NSS shall be capable of direct transition to the malfunction modes during any phase of NSS operations."

The single turbopump operation mode is the only malfunction mode considered in this issue of the S-039 Data End Item Report.

"3.1.1.1.5.2.1 Single Turbopump Operation Mode - The NSS shall be capable of operating with one Propellant Feed Subsystem (PFS) leg inoperative. The NSS requirements differ from the Normal Model only in propellant pressures and temperatures within the NSS. The phases of the Single Turbopump Operation are identical to those of the Normal Mode with the following exceptions:

- (a) During Steady State Operations, the NSS shall be capable of satisfying the pressure, temperature, and flow requirements shown on Tables 5* and 6*.
- (b) During Throttle Hold, the NSS shall be capable of satisfying the pressure, temperature and flow requirements shown on Tables 7* and 8*.

During steady state single turbopump operation, the NSS thermal and fluid environment satisfies the pressure, temperature and flow requirements of 80% thrust at full temperature.

During throttle hold single turbopump operation, the NSS environment satisfies the pressure, temperature, and flow requirements of 65% power at rated temperature.

"3.3.1.1.7 Growth Characteristics - The NSS design shall incorporate such features as necessary (exclusive of fuel elements) to allow growth, to operate at a nominal mixed mean chamber temperature of 4500°R at 450 psia pressure. NSS performance shall be shown in Tables 13* and 14*. The NSS shall have the capability to operate at this condition for a minimum of 120 minutes accumulated into multiple cycles, up to 12, of varying duration up to 60 minutes."

The thermal and fluid environment for the growth mode operation is discussed in Sections 2.5.1.1 and 2.5.1.2 of Data Item S-031,

2.4 METHOD OF ANALYSIS (DESIGN PRACTICES)

This section describes the analytical methods and models employed in the structural analysis of the overall NSS. Also included in this section is a discussion of the status/maturity of the data. The validity of the structural analysis is described and uncertainty factors applicable to the calculated structural data are developed.

The NERVA engine is, essentially, an assemblage of primary and secondary structural components joined or fastened at various interfaces. Each component is treated in a separate subsection as indicated in the Table of Contents. The related interfaces of each component are identified and the associated critical loads specified.

The loads obtained are the result of the external and internal environments acting on the engine. They result in stress levels and margins of safety that will be compared against permissible values listed in applicable specifications. In general, load requirements must be associated with specific load conditions.

Basic loads analysis consists essentially of rigid body mechanics and conventional structural analysis. Rigid body mechanics is utilized to determine the external force and moments required to maintain static and dynamic equilibrium. The internal forces and moments are determined from techniques of structural analysis based on the elastic theory of structures.

For purposes of detail stress analysis, it is convenient to consider each component as a free-body in equilibrium under the influence of the interface loads. The magnitude of these loads depends on the relative stiffness of the various components which are interconnected at the interfaces. Consequently, a comprehensive structural analysis is essential to the determination of loads at the interfaces.

Loads between components (at the major engine interfaces) have been determined by using the Structural Design code Reactor Analytical Transient Stress (RATS). Temperature and pressure data are input to RATS from the results of Thermal Design's code TNT -II. Additional reference to these codes can be found in Section 2.4.2 of this report. Section 2.4.1 presents the overall flow chart of the nuclear, thermal and structural analyses.

2.4.1 Analytical Procedures

The purpose of this section is to describe 1) the overall framework of nuclear, radiation thermal and structural analyses, 2) the relationship of structural computations to this overall framework, and 3) the details of the procedure by which structural results are obtained.

2.4.1.1 Overall Design Engineering Procedures

Figure 2-3 displays the flow chart of nuclear, thermal and structural analyses. In this figure, and in all subsequent figures describing analytical procedures, the following symbolism is employed:

- 1) An inverted trapezoid (shorter baseline on the bottom) denotes an input of information.
- 2) An upright trapezoid (shorter baseline at the top) denotes an output of information.
- 3) A rectangular block represents an operation.
- 4) All functions have a number in the upper left hand corner which identifies the function on any subsequent flow chart.
- 5) When the operations performed for a given function are expanded into several subfunctions, the base identification number will remain the same and suffix numbers identifying the subfunctions will be added (i.e., the subfunctions for block 11 will be numbered 11-1, 11-2, etc.)
- 6) When a specific function is performed by an existing operational computer code, the name of the computer code will appear at the bottom of the function block.

The procedure for performing nuclear, thermal and structural analyses has been broken down into four steps which are as follows:

Step 1 The first step consists of developing or obtaining the data necessary to define the engineering model of the NSS.

Step 2 The second step consists of translating the information in the engineering model of the NSS into the analytical models required to perform nuclear, thermal and structural analyses.

- Step 3** The third step consists of employing the analytical model, developed in Step 2, to obtain nuclear, thermal and structural results for the NSS.
- Step 4** The fourth step consists of: 1) employing the detailed component models developed in Step 2 and the boundary conditions from the NSS calculational results developed in Step 3 to accomplish individual component thermal and structural analyses, and 2) reporting the results of nuclear, radiation, thermal and structural analyses. Note that the nuclear analysis is performed only on the NSS as a whole and no component nuclear analysis is performed. The fourth step also briefly indicates the Design Engineering validation approach which includes: 1) comparing analytical and experimental results to obtain uncertainties in the calculational technique, and 2) employing experimental or other reference information to validate/improve the analytical model or technique.

Before a detailed description of the four steps followed in the analytic process, it is important to describe the incorporation of uncertainties and propagation of error methods throughout the analysis chain. These items, which constitute the essence of the reliability-related calculations, must begin with the input information of Step 1 being described probabilistically, namely, that drawings be a source not only of a nominal dimensions but also of geometric uncertainties, that the materials properties be expressed as means, standard deviations, and (where available) test sample size, and that engine component simulation in the NSS performance models be described by nominal characteristics as well as uncertainties. The NSS level analysis, Step 3, is performed probabilistically in that the nuclear analytic results include uncertainty estimates, while the thermal and structural analyses are performed in random trial, or Monte Carlo fashion. The thermal and structural NSS computer representations are equipped with the necessary programming logic to select random, values of all input parameters, perform a selected number of random trial (Monte Carlo) runs, and reduce the resulting output data in terms of mean values and standard deviations. At present, 30 Monte Carlo cases for a given operating condition have been selected as a reasonable compromise between available resources and approach to an exact solution. In current practice, the Monte Carlo analyses are restricted to steady state conditions. The Step 4 component analyses must depend, of course, on the geometric and property

information of Step 1 and boundary conditions as generated by the Step 4 gross NSS analysis. The probabilistic aspects of Step 1 and 3 as just described provide the raw material for probabilistic analysis at the Step 4 level. At this level of detailed component analysis, no fixed method of propagation of error analysis is followed.

If Monte Carlo techniques were applied to every component finite difference or finite element model, required computer time would far exceed available program resources. The propagation of error analysis at the component level is performed by some scheme created by the ingenuity of the engineering analyst and best suited to the individual component analysis. Some suggested methods are available in NRPs 403, 411 and 605.⁽⁴⁾⁽⁵⁾⁽⁶⁾ The final result of probabilistic component analysis is, of course, a statistical description of component failure-governing "stress," stress in a broad sense which could actually be temperature, predicted reactivity loss, or structural load. The failure-governing stress is combined with the "strength," or the component ability to sustain the particular form of "stress," through the stress interference method as described in NRP 307.⁽⁷⁾ The interference analysis yields the probability of occurrence of a given component failure mechanism. The failure mechanism probabilities are indicated at the bottom of Figure 2- 3 as a unique output of the probabilistic design process, distinct from the radiation environment, heating distribution, temperatures, pressures, stresses, and displacement which result from a conventional reactor analysis.

From Figure 2-3 it is seen that Step 1 consists of the following inputs of information:

- 1) Block 1 is NSS and/or component drawings.
- 2) Block 2 is the bill of materials defining the type, quantity, and composition of individual parts.
- 3) Block 3 is material properties information which includes the nominal value and standard deviation for each property.
- 4) Block 4 is the run profile, state points, and engine component data information.
- 5) Block 5 consists of optional input data for malfunction and emergency mode which can be input into the analysis process in another reliability-related task, namely, prediction of the effects of engine component malfunctions.

The information from Blocks 1 through 5 is combined together to generate the engineering model of the NSS in Block 7. A Design Engineering goal is automation of this entire procedure. A computer description of each component and the bill of materials would be handled by the Weights And Moments of Inertia (WAMI) code to generate the weights, center of gravity, and moments of inertia for each component (Block 6). The WAMI code would also act as the file manager for the majority of the information in the engineering model and would provide the information needed to generate analytical models. The Nuclear, Thermal Stress (NUTS) code handles the material properties information and provides the information in a format which is directly useable by the design computation codes. Codes, such as the Design Performance Reliability (DPR) code, are being developed which will automatically generate probability of failure mechanism information via the Monte Carlo technique to evaluate propagation of errors (NRP 605) for the NSS as a whole. The DPR code is being developed as a specific tool to predict core assembly reliability.

A vast quantity of information is obtained from the drawings. The process of translating drawing information to computer input is being investigated. This process can be automated via the use of a digitizer. This machine takes the x and y coordinates of a point and/or any grouping of symbols and produces computer input from this information on punched cards (a magnetic tape is also available). Therefore, an operator using a digitizer, essentially traces a drawing to produce a computer description of the component and any other information shown on the drawing. The computer description can then be used directly in calculations with WAMI to generate analytical models.

Step 2 in the nuclear, thermal, and structural analyses consists of developing the analytical models required by each discipline (Blocks 8, 9, and 10) from the information contained in the common engineering data bank (Block 7). This procedure may also be automated with the Nuclear Analytical Model (NAM), Thermal Analytical Model (TAM), Stress Analytical Model (SAM) codes in order to make the optimum utilization of manpower and avoid duplication of effort. The NAM, TAM, and SAM codes are currently only names which may apply to several computer codes, some of which are already in existence, used to generate an analytical mode. The LOBO and MESHER codes that generate spatial mesh patterns for nuclear and thermal calculations have been programmed. The codes to translate

data from WAMI into weights and atom densities for nuclear and thermal calculations have been formulated.

Step 3 in the nuclear, thermal, and structural analyses consists of performing the analysis related to the NSS as a whole. The nuclear analytical model developed in Block 8 is employed to perform the nuclear and radiation calculations in Block 11. In addition, in order to perform the nuclear computations, the region average temperatures and hydrogen densities are required (Block 12) from the thermal analyses. However, note that the thermal analyses, both the NSS and components (Blocks 13 and 19), require heating rates, fission distribution, and reactivity coefficients in order to be performed (Block 15). Therefore, as can be seen from Figure 2-3, the nuclear and thermal computations form a closed loop which require some iteration in order to obtain nuclear and thermal data.

The thermal calculations for the NSS (Block 13) employ the thermal analytical model (Block 9) and nuclear information (Block 15) to generate thermal data for the NSS and thermal-flow boundary conditions (Block 16) which are used in the thermal calculations for components (Block 19) and in the stress calculations for both the NSS (Block 14) and components (Block 21). The stress calculations for the NSS employ the stress analytical model (Block 10) and the thermal-flow boundary conditions (Block 16) to generate the stress data for the NSS and the loads and displacement boundary conditions (Block 17) which are used in the stress calculations for components (Block 21).

Step 4 in the nuclear, radiation, thermal and structural analyses consists of the following three phases:

- 1) Thermal and stress calculations are performed on a component level (Note that nuclear and radiation calculations are not performed on a component level).
- 2) Analytical and experimental results are compared to derive uncertainties or experimental results or other reference information are employed to improve the analytical model or technique (Block 18). This function provides feedback to the second step of this procedure.
- 3) Nuclear, radiation, thermal and stress computations are reported in the appropriate data item. In addition, the results of malfunction and emergency mode condition

calculations for Monte Carlo analyses to evaluate failure mode probabilities with the aid of interference theory and/or malfunction analyses to evaluate FMECAs which have been obtained essentially the same calculational technique are reported.

The thermal calculations for component analysis (Block 19) employ the thermal analytical model (Block 19), the nuclear information (Block 15), and the thermal-flow boundary conditions from the NSS computations (Block 16) to generate thermal data for the components and the thermal boundary conditions (Block 20) for the components. The stress calculations for component analysis (Block 21) employ the stress analytical model (Block 10), the thermal-flow boundary conditions from the NSS and component analyses (Blocks 16 and 20) and the loads and displacement boundary conditions from the NSS computations (Block 17) to generate the stress data for the components. Radiation data are also provided to Thermal and Structural Analysis to modify radiation sensitive property data in the analyses.

2.4.1.2 Structural Design Procedure

Figures 2-4, 2-5, and 2-6 detail Blocks 10, 14 and 21 respectively, in Figure 2-3, and present the general procedure used to develop the structural analysis models for Step 2, Step 3 and Step 4 calculations.

Figure 2-4 displays the detailed flow chart of Block 10 to achieve Step 2 in the Structural Design procedure. This block outlines the development of analytical models used by Structural Design. Model input is generated either manually or internally by the specific code used in the analysis (Blocks 10-1 and 10-2 in Figure 2-4). In addition, common engineering data and detailed NSS component data with their associated uncertainties are included in the final NSS dynamic, static and component models.

Figure 2-5 displays the detailed flow chart of Block 14 to achieve Step 3 in the Structural Design procedure. This Block employs the analytical models along with detailed static, dynamic, hydraulic and thermal boundary conditions specifying the NSS or component environment. Structural dynamic and static results are then obtained on a reactor assembly level.

Figure 2-6 displays the detailed flow chart of Block 21 to achieve Step 4 in the Structural Design procedure. This Block employs the results of Step 3 with suitable boundary conditions to perform detailed component structural analyses.

Descriptions of all the important Structural Design programs called out on Figure 2-6 are available in Chapter 2.0 of Reference 8 (TME-2754, S-036) and in Reference 9 (Structural Design Computer Manual). Only the NSS level program, RATS, will be discussed in this Data Item, as well as some statistical computer programs which directly support the RATS Monte Carlo Analysis.

In addition to the overall calculation sequence just described, other specific design procedures or practices are followed within the Structural Design Department. These procedures are related to the methods of analysis, the definition of structural allowances, the sources of analytic input, analysis traceability, and cross checks of the analysis.

The methods of analysis in terms of interfaces with the other design engineering disciplines have been displayed in detail in Figures 2-3 through 2-6.

The specific stress analysis methods are to a large extent influenced by Reference 2 (SNPO-C-1). Such matters as the methods of analysis applicable to brittle materials, definition of primary and secondary stresses, and the depth of analysis appropriate to a given level of design maturity are all covered in the reference.

In addition to the more conventional stress analytic procedures, special methods of analysis have been developed to calculate the probability of occurrence of component failure mechanisms and to perform propagation of error computations. The method of performing propagation of error analyses on the nuclear subsystem level is a Monte Carlo¹ or random trial analysis. The procedure is described in Reference 10 (DRM 52137). Although the Monte Carlo trials have been increased from 15 to 30, the procedure described in Reference 10 remains valid.

Although individual component failure probability analytic methods are not generally applicable in the loads analysis, a discussion of these methods provides a better understanding of the overall Structural Design analysis practices. The specific methods of individual component propagation of error analysis vary in complexity. When manual calculations are performed, the solution exists in closed form and is amenable to error propagation by partial differentiation (NRP 605), algebra of normal functions (NORF code),⁽¹¹⁾ or Monte Carlo (MAD code).⁽¹²⁾ Finite element calculational results are not as conveniently handled. Lacking any reasonable method of greater precision, some uncertainties on finite element results must be based entirely on engineering estimates of the coefficient of variation (ratio of standard deviation to mean value).

A second level of sophistication is to express the maximum stress from a finite element analysis in a simplified form. In this case, the coefficient of variation is calculated from the simplified expression and assumed to apply also for the finite element result. The approximate closed form equation for the parameter of interest (usually maximum combined stress) is equipped with corrective constants; the constants are calculated from comparisons between finite element and the simplified closed form results. Propagation of error calculations of the final equation, including the constants, are simply completed by methods already mentioned. It should be remarked that the essential element in these

reliability-related calculations is formulation of an approximate closed form expression for combined stress at a point and this formulation is heavily dependent on engineering inventiveness. This general approach is described in Reference 13 (DRM 53238) and Reference 6 (NRP 605).

A related method makes use of the nuclear subsystem approximate stress analyses generated by the RATS code. Monte Carlo RATS analyses, described in detail in Section 2.4.2.3, provide steady state uncertainties. The coefficient of variation for the RATS approximate stress results is then assumed to apply to a related result from detailed component analysis.

Codes to automate Monte Carlo and algebra of normal function analyses, MAD and NORF, respectively, are described in paragraph 2.4.1.2, Reference 8, (S-036.) When feasible, the Monte Carlo type calculations are, of course, to be preferred since an exact propagation of error analysis is approached (dependent only on the number of random trials in a properly formulated Monte Carlo calculational scheme) regardless of the parameter variance-to-mean ratio whereas normal function algebra and partial differentiation methods become less dependable as this ratio increases.

Having determined a statistical description of the failure governing stress as just described, a comparison must be made with the appropriate strength value (statistically described) via stress-interference theory as defined in Reference 7 (NRP 307) and discussed in Reference 15 (Kececioglu and Cormier). In specific cases when these are the logical criteria, such things as yield stress, an appropriate creep limit, or critical buckling will be used for the "strength" parameter. In other cases, however, the strength will be assumed to be the ultimate strength for brittle materials and for primary stresses in ductile materials. For primary-secondary stress situations with ductile materials, the maximum primary stress will first be compared with the ultimate strength. Then the maximum combined primary plus secondary stress will be compared with the stress associated with the failure strain (stress derived from a linear elastic approach, i.e., initial modulus of elasticity X failure strain). The lower reliability of the two will be the value reported.

The reliability methods which have been described are essentially consistent with procedures described in published reliability procedures, especially References 4 and 5 (NRPs 403 and 411). However, most of the methodology has been developed in Structural Design during CY 70 in parallel with and in cooperation with the preparation within the Reliability discipline of the formal NERVA Reliability Procedures.

Moving on from the methods of analysis to structural allowables, a joint requirement exists. In the first place, there are the stress intensity limits defined in Reference 2 (SNPO-C-1). These stress limits (typically 99% probable with 95% confidence minimum strength values reduced by a specified factor of safety) are to be compared with the 99/95 limit load. In a second step, component reliabilities are to be calculated and compared with allocations. The reliability of the components, in the sense of a major Engineering Critical Component, like the Reflector Assembly, will not be calculated by Structural Design. However, when the component reliability is calculated by the Reliability Department (based on failure mechanism probabilities supplied by Structural Design or the Design Engineering groups), the comparison between calculated and allocated reliability may require iteration with part sizing according to the SNPO-C-1 allowables. If the reliability as calculated differs from the reliability as allocated, the design may be changed in the direction of increased or reduced conservatism, or alternatively, the reliability allocation may be changed. This process of initial design according to SNPO-C-1 allowables, followed by designing to meet reliability requirements is described in both Reference 2 and Reference 16 (Schroeder to Feldman, "Structural Design Basis for Engine PDR and Subsystem PDR, " June 2, 1970).

The next topic in this discussion of Structural Design practices is the sources of input. These are largely shown in the Figure 2-3 functional diagram. State points and thermal environment are supplied by Thermal Design. Material properties are taken from the NERVA Material Properties Data Book or from official Data Release Memoranda released by the WANL Materials Department. Static and dynamic loads analyses require, in addition, load environmental information. Sources are Reference 17 (SNPO-C-6) for external environmental conditions and ANSC for dynamic forcing function

data at the NSS-engine interface.

Traceability of Structural Design analyses is insured by documentation of all significant stress analyses in DRM (or higher order document) form and the serialization (and retention) of all supporting computer runs. All NERVA component drawings are signed or initialed by Structural Design before release (see Reference 18, PMD 30A). Every signed drawing is supported by a DRM and Drawing Sign-off Sheets are transmitted to SNPO-C.

The final point in this discussion of Structural Design practices is checks of the analysis. Every analysis performed by a Structural Design engineer is checked in detail by a supervisor. Every DRM is countersigned by the appropriate supervisor. More formal documents (TMEs and TMLs) are countersigned by the Manager of Structural Design.

2.4.2 Analytical Models

A description of the thermal, structural and statistical models used in the Structural Design analyses is contained in the following sections. A single Design Performance and Reliability (DPR) code will eventually combine several select thermal, structural and statistical codes into a single system model.

2.4.2.1 Thermal Model

Several thermal codes from the Thermal Design Group provide input to Structural Design analyses. Data are transmitted by direct communication, DRM and/or computer stored tape files.

The calculation of the NSS loads environment requires a complete thermal and hydraulic NSS environment to be specified. The TNT-II (Thermal and Nuclear Transients) code provides such information. Data are stored in computer tape files which are in turn used directly by Structural Design. TNT-II models the flow pattern, orificing and thermal impedances of the reactor for a given set of operating conditions. A schematic of the TNT-II program is shown in Figure 2-7, where the lines between components represent flow channels. The blocks representing components are further reduced to more detailed models. Fluid temperatures and pressures are computed along each channel and material temperatures are computed for each mass point in the model. The TNT-II code has been documented in DRM 52252⁽¹⁹⁾.

A detailed description of all Thermal Design codes appears in Chapter 2 of Data Item S-031, "Thermal and Fluid Flow Analysis Report, Nuclear Subsystem."

2.4.2.2 Structural Model

The major Structural Design code used in the analysis of the Nuclear Subsystem and its associated ECC components is the RATS (Reactor Analytical Transient Stress) Code. A brief description of RATS is given below:

The RATS Computer Program is an analytical systems model which solves the equations of equilibrium and compatibility at the interface between critical components. Using temperature and pressure data obtained from the TNT-II thermal model, RATS fits equations to these data to obtain pressure and thermal distributions along the longitudinal axis of each component. With these equations, the free longitudinal and radial deformations of each component are calculated at various reactor axial stations. When these free deformations are substituted into equations of equilibrium and compatibility derived from structural models of the components, the resulting loads and final displacements of the given ECC interface are determined. The RATS code is in reality is a collection of equations which together approximate the gross behavior of the nuclear subsystem. The equations are formulated from the individual component configuration and previously generated detailed stress analysis results on the component. Some indication of the form of the RATS component representation is given by the free body diagram supplied in the component chapters. Figure 2-6 shows the RATS code to be an integral part of the S-039 data flow scheme.

The analysis to determine the system response to transient conditions is accomplished by an iterative process. First, the initial and final points of the reactor transients are defined by well-established state point conditions. The transition between these points is defined by a demand thermal mapping of the chamber conditions. Both the thermal and structural computer models simulate the reactor response as a function of time by numerically integrating the initial and demand conditions over a series of small time steps. A measure of the system's response can be obtained by comparing the computed conditions with the state conditions at the end of the transient analysis.

The steady state analyses require no time-iterative process and represent the NSS response during the entire steady state operational period.

2.4.2.3 Statistical Model

The Monte Carlo method was used to compute the mechanical load, moment, and displacement uncertainties given in each chapter. This method is essentially a computer experiment which simulates the manufacturing and subsequent testing of a number of NERVA engines. Thirty engines simulated by the TNT-II thermal and hydraulic model and the RATS model were used for this analysis. The TNT-II model is the thermal and hydraulic equivalent to the RATS structural model. Thirty random sets of TNT-II and RATS inputs were prepared using the standard deviations of the important model parameters and a random number table. These thirty sets of model input may be considered as the analytical models corresponding to thirty actual engines constructed from the same set of drawings. The TNT-II and RATS programs were then used to calculate the operating characteristics of the thirty simulated engines. The results of these calculations consisted of 30 values of all dependent parameters such as fluid and material temperatures, computed loads, displacements and moments. In the final step each parameter was statistically analyzed to determine the standard deviation and tolerance limits. The various steps of the Monte Carlo method as outline in this paragraph are described below in more detail:

Step 1 Uncertainties for Independent Parameter

The first step of the Monte Carlo Method consisted of the selection of the one standard deviation for all important independent parameters of the RATS equations and model. The estimated standard deviation at the completion of the qualification program were used for this analysis. In other words, the attempt was to analyze flight engine rather than ground test reactor uncertainties. These parameters were then cataloged into groups consisting of one independent parameter or several independent parameters that were determined to be mutually dependent. The grouping of independent parameters with mutually dependent behavior is necessary in order to correctly simulate the NSS in Monte Carlo analysis. A total of 346 groups consisting of one or more parameters were obtained. Relative index numbers from 1 to 346 were assigned to these groups for use in Step 3 of the Monte Carlo method.

Step 2 Random Number Multiplication Factors

A random number table and the assumption that all independent parameters selected in Step 1 follow a Gaussian distribution were used to determine the random number multiplication factors. The CDC 6600 computer subroutine "RANF" was used to generate a table of 20,000 random numbers between zero and one. RANF uses the mathematical method described in Reference 20. For this analysis, it was assumed that all selected independent parameters would vary according to a Gaussian distribution between the limits of -4 to $+4$ sigma. Mathematically, the cumulative distribution function for a standard normal variable was used to transform the random numbers obtained from RANF to random multiplication factors between -4 and $+4$ sigma. The following equation was used for this transformation:

$$N = F(M) = \int_{-4\sigma}^{M\sigma} f(x) dx$$

where,

N = Random Number

$F(M)$ = Cumulative Distribution Function

$f(x)$ = Density Function for Standard Normal Variable

M = Random Multiplication Factor Corresponding to Random Number N

This transformation is graphically illustrated by a plot of the cumulative distribution function shown on Figure 2-8. The random Number (N) is entered on the ordinate of the figure and is used to find the corresponding random multiplication factor (M) on the abscissa. In this example, the random number with a numerical value of approximately 0.74 yields a random multiplication factor of approximately 0.6. Using this procedure, the table of 20,000 random numbers obtained with RANF was transformed to 20,000 corresponding random multiplication factors. These random multiplication factors are used in the next step to obtain RATS input for all random cases.

Step 3 RATS Input for Random Cases

The standard deviations selected in Step 1, the random multiplication factors obtained in Step 2, and the nominal input values of the RATS model were used to compute input for thirty random RATS models. Table 2-2 illustrates the procedure that was used to select the random number multipliers for each set of input. The first column shows the storage locations of the 20,000 random multiplication factors. The relative index numbers assigned to the TNT-II and RATS independent input parameters are shown in Column 2. The TNT-II program computes the thermal and hydraulic conditions required as input to RATS. The selection of the relative index numbers for each independent parameter or groups of independent parameters that were mutually dependent was described in Step. 1. The starting location on the random multiplication factor table of 145 was randomly selected. From this starting point, sets of 600 random multiplication factors were used to compute input for each random TNT-II and RATS calculation. The first 200 random multiplication factors were available for TNT-II and the next 400 for RATS. The random multiplication factor corresponding to location 145 was used with the first independent TNT input parameter to determine the input value for the first random Monte Carlo calculation. The 116 random multiplication factors required to determine the input values for the first random TNT-II calculation were obtained from locations 145 through 260. The random multiplication factors in location 261 through 344 were not required. Locations 345 through 744 were assigned to the input values for the first RATS calculation. Random multiplication factors to determine input for the second TNT-II calculation were obtained from locations 745 through 860. This process was repeated in increments of 600 to determine random multiplication factors to compute thirty sets of randomly selected TNT-II and RATS input parameters.

Step 4 RATS Calculation

For each steady state operating condition, 31 RATS calculations were performed. The first calculation consisted for the nominal case with no variations followed by 30 calculations with randomly selected input. The results of these 31 calculations were stored on tape for input to statistical analysis codes.

The major input to these RATS calculations were the thermal and hydraulic results from 31 corresponding TNT-II Monte Carlo calculations. The results and a description of these TNT-II calculations are given in Reference 1.

Step 5 Statistical Analysis

The results of the thirty-one calculations (the nominal calculations followed by thirty calculations with random input) were used to compute the sample standard deviation and tolerance limits for the RATS output parameters. The following equation was used to determine the sample standard deviation for each parameter:

$$S = \sqrt{\frac{\sum_{i=1}^{i=N} (Y_N - Y_i)^2}{N}} \quad (2)$$

where,

S = The sample one standard deviation for any RATS output parameter

Y_N = Nominal value of RATS output parameter

Y_i = Value of RATS output parameter for one of the N random calculations

N = Number of random calculations. A value of N equal to 30 was used for this analysis.

Tolerance limits were determined with the following equation:

$$U = (K)(S) \quad (3)$$

where,

U = Uncertainty of dependent RATS parameters for the proportion and probability corresponding to the K factor

K = Tolerance factor obtained from Reference 21

S = Standard deviation of dependent RATS parameter for the sample

The K factor was selected to give one-sided tolerance limits of 99 percent proportion at 95 percent confidence. This corresponds to a numerical K value of 3.064 according to Table III of Reference 21. One-sided tolerance limits mean that either only the upper uncertainty limit (nominal value plus uncertainty) or the lower uncertainty limit (nominal value minus uncertainty) are applicable at one time; both limits do not apply simultaneously.

Tolerance limits define the location of a proportion of the population. In this case, the population is defined as all engines that can be manufactured from a set of drawings and specifications. Tolerance limits are used to define either the upper or the lower limit of any parameter. The SNPO-C-1 document describes the use of tolerance limits to define either the upper or lower limit of any parameter. The following example is given to describe the interpretation of one-sided tolerance limits. Assuming that a certain parameter has a nominal value of 200 and an uncertainty value of 30 corresponding to 99 percent proportion at 95 percent confidence. The resulting upper tolerance limit with 99 percent proportions at 95 percent confidence is $200 + 30$ or 230. The interpretation of this tolerance limit is as follows: If 100 samples containing 100 engines each are randomly selected from the total population of engines, then in 95 of the 100 samples, 99 engines out of 100 in each sample will have values of this parameter less than 230.

Figure 2-9 outlines the entire data flow scheme which generates the statistical data contained in this document. A brief description of the statistical codes used by Structural Design follows.

A. MONTE

Statistical code generating n sets of normalized random input data for use by the RATS code.

B. MNTCRL

Applies standard statistical methods to the n sets of randomized output from the RATS code to estimate variability for each output parameter.

C. MAD

A statistical code applying Monte Carlo sampling techniques to an algebraic expression or a series of such expressions. Calculates mean, standard deviation, coefficient of variation and nominal value of the dependent variable. Also plots a histogram showing the dependent variable's computed distribution. In addition, a method for determining parametric sensitivity is available. This code is particularly useful in generating statistical output for complex structural models such as a finite element representation, when that model can be expressed in some reduced parametric form. The major advantages over the algebra of normal function methods are that parameters of large coefficients of variation are permissible and the output includes sufficient data for normalcy tests.

D. IFENCE

Computes the probability of interference (failure), and reliability of two normal distributions by the overlap method. In addition, the code calculates the probability that no items out of a system of N items will fail given that each item in the system has the same probability of failure.

2.4.3 Maturity of Input Data

This section describes the major input data required to generate structural performance data.

2.4.3.1 Material Property Input

The material thermal properties for NSS performance and detailed component analyses are obtained from a material DRM file * which is maintained by Structural Design for code utilization. The material property data DRMs are obtained, in turn, from the WANL Materials Department. This file is updated periodically when additional data are received. The PDS numbers, source of data, and other pertinent information concerning the properties are included in each DRM. The material property input to Structural Design is shown in the overall calculation flow chart, Block 3, of Figure 2-3. The typical data for each ductile material within the DRM file are density, thermal conductivity, specific heat, Poisson's ratio, ultimate tensile strength, tensile yield strength, modulus of elasticity,

* A complete file of Material's DRMs used in PDR analyses is given in Appendix 1 to Data Item E-105, Reference (22)

percent creep, mean coefficient of linear thermal expansion and fatigue strengths and rupture data. These data are supplied as a function of temperature. In addition, the estimated one sigma variation at different temperatures and non-irradiated and irradiated properties at one or more irradiation doses are presented.

At the present time, the Structural Design Material file contains about 95 different materials' DRMs. These DRMs are continually updated to reflect the latest type A, B and C data from the WANL Materials Department.

2.4.3.2 NSS and Component Input

Input required for NSS and component description (Blocks 1 and 2 of Figure 2-3) are contained in the E-105⁽²²⁾ package, "Engineering Data and Design Evaluation," containing the NSS and component drawings and bills of material. Current up-to-date lists of drawings used for NSS and component analyses are continually revised and documented per the latest revision to Reference (23) issued by the Reactor Design Department.

The analyses conducted by the Structural Design Department follow the NSS and component descriptions as defined in the above mentioned documents.

2.4.3.3 Operational State Point Input

Detailed operational state point data defining the thermal and hydraulic environments of the NSS are obtained from the output of Thermal Design's TNT-II Code. State points are defined by WANL and ANSC concurrence. Analyses conducted for this report are based on the state points as documented in Thermal Design's S-031 Data Item.

State point input is shown as Block 14 in the overall analysis flow chart in Figure 2-3.

2.4.4 Validity of Analysis

The validity of the data presented in this document is based on the verification of each model in the data flow scheme.

2.4.4.1 Verification of Structural Model

Performance analyses for the previous NRX-A and XE series reactors had been conducted using the RATS code. Both pre-test and post-test analyses were performed comparing the actual test data to the computer-model calculations.

Specifically, the NRX-A6 post-test evaluation, Reference 24, incorporated a simulated NSS response analysis using the RATS code. Thermal and hydraulic input to RATS were identical to the measured data during the reactor test. The quasi-static measured data included tie rod strains, standoff strains, and core radial and axial displacements. These transducer generated data were compared with the response predicted by the RATS program. All data showed good to excellent agreement.

Since the NRX-A6 test evaluation, several improvements in modeling and computational techniques have been incorporated into the RATS code. Although these changes have not been verified by actual test data, it is expected that the RATS results are a valid means of evaluating NSS performance based on past experience and previous test comparisons.

2.4.4.2 Verification of Thermal Model

The verification of the thermal and hydraulic NSS model has been documented in Reference 1 (Data Item S-31).

2.4.4.3 Verification of Statistical Model

A weighted Monte Carlo method has been chosen to provide the means by which the voluminous number of calculations contained in both the TNT-II and RATS codes can be handled efficiently to provide an estimate of variability of each output parameter.

The essence of the Monte Carlo method, chosen to provide the S-039 statistical data, is in its treatment of deterministic numbers as if they were probabilistic in

nature. For each input parameter of both the TNT-2 and RATS codes, the mean and standard deviation is specified. Through use of a statistical code, a randomizer picks a number from a family of random numbers of normal distribution, between the limits of -4 to $+4$ sigma. Consistent with the probabilistic distribution for each input variable, the randomizer then generates n sets of randomized input data. With a finite number, n , of model runs with truly random input, an estimate of the output variable's variance can be made. This method actually simulates the assembly and testing of n reactors. As n increases, the bounds on the estimates of the statistical properties of the population become narrower at a fixed confidence level. The Central Limit Theorem states that if the number of runs were infinite, the distribution of the output loads and displacements would be Gaussian or normal. Preliminary calculations (DRM 52138) have shown, for $n = 14$, this type of analysis is sufficiently accurate to estimate output statistics at a 90% confidence level. The statistical data obtained in this manner are then corrected, with a one sided tolerance limit to account for the finite number of samples, and the population standard deviation, σ , is calculated for a 95% confidence level. The population mean, μ , of an output variable, assumes the same value as that calculated with all nominal input.

The use of a weighted Monte Carlo analysis (random numbers are picked from a normal distribution) has been shown to be many times more efficient than other Monte Carlo methods.

A sample thermal-stress problem described in Reference 1 was used to check-out the Monte Carlo method. The sample problem consisted of a thick walled hollow cylinder with internal heat generation and convective heat exchange on both inner and outer surfaces.

A closed solution was obtained for the maximum thermal stress. Ten of the parameters were randomly varied for each calculation and 4000 maximum stresses were computed. Samples of 20 stresses were drawn from this simulated population and were used to compute the tolerance limits of the maximum thermal stress. These tolerance limits which define the location of a certain proportion of the population were compared against the

simulated population and good agreement was found, In addition, the results were found to follow a normal distribution.

2.5 RESULTS OF ANALYSIS AND INTERPRETATION

This section presents the results of analysis on composite and graphite cores to determine the structural environment of the NSS assembly at various steady state and transient operating conditions. These results will be used in the design analysis of component hardware and as input to more detailed models for further structural analysis. The loads moments and displacements presented in this document represent only the contribution due to static loading conditions. The dynamic analysis and detailed structural analysis are included in reports S-38 and S-36 respectively.

The loads analysis results for both composite and graphite core designs are presented for the following reactor operational modes:

- a. Normal mode operation start of life (SOL)(includes startup, steady state rated, throttled hold, and shutdown).
- b. Normal mode operation, end of life (EOL) (includes startup, steady state rated and throttle hold, and shutdown).
- c. Malfunction mode operation, single turbopump start of life (SOL) (includes steady state at 80% thrust and throttle hold).
- d. Malfunction mode operation, single turbopump, end of life (EOL) (includes steady state at 80% thrust and throttle hold).
- e. Growth mode operation at $T_c = 4500^{\circ}\text{R}$ at rated condition start of life (SOL), Steady State.
- f. Growth mode operation at $T_c = 4500^{\circ}\text{R}$ at rated condition end of life (EOL), Steady State.

The term "start of life" (SOL) is used to designate that portion of a first cycle of 10 minutes operation, including the startup, steady state at rated conditions, and the shutdown phases of the cycle. The term "end of life" (EOL) is used to designate that portion of the last cycle of 10 minutes rated condition run including the last normal startup and shutdown after 60

cycles and 600 minutes at rated chamber temperature. At the last cycle of operation the reactivity loss of the core due to corrosion has been accumulated to the specified maximum value of \$1.00. The startup operation at the first cycle is, therefore, called the SOL startup. The 10 minutes at rated conditions is called the SOL steady state operation and the shutdown is called the SOL shutdown operation. Similarly, the startup, rated condition, and shutdown at the last cycle is called the EOL startup, EOL rated condition, and EOL shutdown.

The load, moment and displacement coordinate systems are localized for each component as shown on each component diagram. All systems follow the same sign convention:

Axial vectors are positive aft.

Radial vectors are positive outward from the reactor core centerline.

Tangential vectors are positive into the plane of the diagram

(counterclockwise looking aft) and are represented by the symbol $\otimes$

Moments follow the right-hand rule about the given axis and moments about the axial axis are referred to as torsions.

Radial displacements are measured relative to a fixed core centerline.

Axial displacements are measured relative to the fixed reflector assembly-nozzle interface.

A three digit number followed by a date found in the lower right hand corner of each data table and figure refer to the day-file sequence number and date respectively, of the computer run which generated the data. In addition, a four or five letter code appears at the end of each figure showing transient component response. The first letter refers to the type of core, either composite (C) or Graphite (G). The next two letters refer to either the startup (SU) or shutdown (SD) modes. The last one and/or two letter (s) refer to the start-of-life (S) or end-of-life (E) condition. For instance, GSUSE would refer to a figure with data for a graphite core, during the startup ramp, for both the SOL and EOL operating conditions.

Data are presented in each ECC chapter by core type, composite being first. Next, the loads, moments then displacements are given for each of the three coordinate directions, radial, axial, then tangential. Data for each coordinate direction are further

divided by presenting startup data before shutdown and start-of-life before end-of-life conditions. All steady-state data are presented in tables and all transient data are shown in figures. The component diagrams make no attempt at presenting loads of different value with different identifying symbols. As a result one diagram may show several different axial loads, each identified as F_A .

2.5.1 Composite Core

2.5.1.1 Results of Nominal NSS Analysis

The relative severity of the NSS response can be determined by comparing data for each of the operating modes listed in section 2.5.

For the steady-state analyses, the operating mode that tends to consistently show the largest magnitude for any given component parameter is the Rated Power mode. In order of decreasing parameter magnitude, the other modes are: growth mode; 80% power single TPA; 65% throttle, single TPA; and finally the 65% throttle mode. This general trend holds true for both the composite and graphite cores. However, comparison between cores must be made on an individual item basis.

Transient analyses were conducted for the rated power condition only. The figures for the transient response of a component parameter all show similar characteristic curvature, ramps and peaks. These features can be explained when the NSS thermal and hydraulic environment is analyzed. Because of the nature of the NSS, the components respond to both a temperature and pressure influence. This influence is most evident during the shutdown phase. Figures 2-10 and 2-11 show a typical thermal and hydraulic environment profile during the "referenced extreme" shutdown. (These figures are based on data contained in the S-031 Data Item and the reader is referred to that document for further detail). The two most important characteristics are the reactor pressure drop and central dome plenum temperature. These profiles are representative of the local pressures and temperatures around the support plate, shields, reflector, control drum actuator assembly and structural support coolant assembly.

Phase 1, Throttle, 600-603.15 seconds

Nozzle chamber pressure is decreased at -50 psi/sec with constant chamber temperature. The SSCV position is controlled as a function of chamber pressure. During this phase, reactor pressures and pressure drops and flow rates decrease linearly, while the NSS plenum temperatures increase slightly similar to the behavior of the central dome temperature profile.

Phase 2, Throttle Hold, 603.15-643.15 seconds

Constant chamber temperature, pressure and SSCV position are maintained at this time. Consequently, the NSS component response to the thermal and hydraulic environment remains fairly constant.

Phase 3, Temperature Retreat, 643.15-680 seconds

During this phase, a nozzle chamber temperature ramp of $-175^{\circ}\text{R}/\text{sec}$ is required. Here, the controlling parameter is chamber pressure. The pressure profile necessary to achieve the desired temperature ramp is shown in Figure 2-10. The chamber pressure first decreases very rapidly then increases to approximately one-half of its throttle hold value, with a final decrease to some predetermined value. It is this chamber pressure profile which causes the peaks in the reactor pressure drops and the corresponding peaks in the structural transient response figures for each component. The control drums are also ramped during this phase to their zero degree position, while the SSCV is simultaneously stepped to its minimum position.

2.5.1.2 Results of Monte Carlo Analysis

Monte Carlo analyses were performed for the following three operating conditions:

Case 1. Composite Core, Rated Performance, Start of Life, Normal Mode

Case 2. Composite Core, Steady State Performance, Start of Life, Single Turbo-Pump Operation

Case 3. Composite Core, Throttle Hold Performance, End of Life, Normal Mode

Cases 1 and 2 were analyzed since these represent critical design conditions. Case 3 was analyzed to estimate the probability of requiring control drum motion for this operating

condition. Monte Carlo analysis was limited to these essential cases in order to minimize the computer costs involved in the TNT-II calculations which are required to obtain the thermal and hydraulic conditions. Each of these cases required between 90 and 140 minutes of CDC-6600 computer time for the TNT-II calculation.

The results from these three cases were used to estimate uncertainties for the following three additional cases:

Case 4. Composite Core, Rated Performance, End of Life Normal Mode

Case 5. Composite Core, Steady State Performance, End of Life, Single Turbo-Pump Operation

Case 6. Composite Core, Throttle Hold Performance, Start of Life, Normal Mode.

The procedure consisted of computing the coefficient of variation for all necessary parameters of case 1 and using these variations to estimate the standard deviations for case 4. In the same manner, case 2 was used to estimate the results for case 5, and case 3 was used to estimate the results for case 6. The following equation illustrates this procedure for any parameter:

$$S' = \left(S / X_N \right) X' (X'_N)$$

where,

S' = Standard deviation estimated for cases 4, 5, or 6

S = Standard deviation computed from the Monte Carlo results of cases 1, 2, or 3

X_N = Nominal value of cases 1, 2, or 3

X'_N = Nominal value of cases 4, 5, or 6

The nominal values, sample standard deviations and one sided upper and lower limits for the component loads, displacements and moments computed by RATS are found in their respective chapter. These results represent the random variations expected after the completion of the qualification program. The results do not include any non-random errors or biases that could exist in the computer programs and models.

2.5.2 Graphite Core

2.5.2.1 Results of Nominal NSS Analysis

The same comments contained in Section 2.5.1.1 are applicable here.

2.5.2.2 Results of Monte Carlo Analysis

No Monte Carlo analyses were conducted for the graphite core.

2.6 REFERENCES

1. WANL-TME-2753, Data Item S-031, Thermal and Fluid Flow Analysis Report, March 1971
2. SNSO - C-1, NERVA Program Structural Design Requirements
3. IED 482-C NSS Input to Data Items S-039, and S-047, July 1970
4. NRP 403, Structural Reliability Technical Procedure
5. NRP 411, Simplified Pre-PDR Techniques for Assessing Component Reliability
6. NRP 605, Mathematical Techniques for Analysis of Preparation of Error
7. NRP 307, Glossary of Reliability Terms
8. WANL-TME- 2754, Data Item S-036, Structural Analysis Report, February 1971
9. Structural Design Computer Manual
10. DRM 52137, Monte Carlo Techniques as Applied to RI-RATS Code Output, 12/18/69
11. DRM 51888, "NORF Code for Estimating Reliability of Components"
12. DRM 53072, MAD-A Code Applying Monte Carlo Techniques to an Algebraic Expression or a Series of Such Expressions
13. DRM 53238, An Approximate Method to Evaluate the Stress Variability and Parameter Sensitivity in a Complex Structural Mode, 10/6/70
14. DRM 52138, Results from a Preliminary RATS and TNT-II Monte Carlo Analysis, 12/18/69
15. D. Kececioglu and D. Cormier, "Designing Reliability into a Component", SAE-ASME-AIAA Conference Proceedings, Third Aerospace Reliability and Maintainability Conference, Washington, D. C., June, 1964
16. Schroeder to Feldman, "Structural Design Basis for Engine PDR and Subsystem PDR", June 2, 1970
17. SNSO-C-6, NERVA Program External Environments Definition and Requirements, June 22, 1970
18. PMD 30A, NERVA Drawing Sign-off Requirements, October 20, 1970
19. DRM 52252, A Write-Up of MCAP (Multiple Channel Analysis Program) for Production Use
20. A. Rotenberg, A New Pseudo - Random Number Generator, J. Assoc., March, Volume 7 (1960), 75-77
21. NRP 600, Statistical Distributions, Their Application, and Tables

2.6 REFERENCES (continued)

22. WANL-TME-2759, Engineering Data for Design Evaluation, December 1970
23. DRM 51068, NERVA Reactor Component Alternates
24. WANL-TME -1832, NRX-A6, Reactor Structural Performance, March, 1969.
25. Peak Inertial Loads for Launch Operations, ANSC letter 704D:0472L dated - August 1970
26. DRM 52832, Weight and Mass Property Status, 10/27/70

TABLE 2-1
ECCs IN THE NUCLEAR SUBSYSTEM

<u>ECC Number</u>	<u>Component</u>	<u>Description</u>
EC - 677566	Fuel Elements	Refer to Trade Study 772
EC - 677558	Cluster Hardware	Refer to Trade Study 774
EC - 677564	Core Periphery	Refer to Trade Study 778
EC - 677561	Support Plate & Plena	Axial Support Mechanism with Associated Coolant Piping and Plena
EC - 677562	Internal Shield	Central and Peripheral Radiation Attenuating Shields
EC - 677559	Reflector Assembly	Reactor Reactivity - Control Assembly
EC - 677585	Control Drum Drive Assembly	Control Drum Rotation Mechanism
EC - 677575	Structural Support Coolant Assembly	Structural Support Coolant Flow Control Assembly

TABLE 2-2

SELECTION OF RANDOM MULTIPLICATION FACTORS (RMF) TO PREPARE TNT AND RATS
INPUT FOR 30 MONTE CARLO CALCULATIONS

LOCATIONS OF RMF	INDEX NUMBERS ASSIGNED TO TNT AND RATS PARAMETER RANDOMLY VARIED	COMMENTS
1 . . 144		RMF Not Used
145 . 260	1 . 116	RMF Used to Prepare TNT Input for Calculation No. 1
261 . 344	117 . 200	RMF Not Required
345 . 744	201 . 600	RMF Used to Prepare RATS Input For Calculation No. 1
745 . 860	1 . 116	RMF Used to Prepare TNT Input for Calculation No. 2
861 . 944	117 . 200	RMF Not Required
945 . 1344	201 . 600	RMF Used to Prepare RATS Input for Calculation No. 2
. . .	. . .	
17545 . 17660	. . 116	RMF Used to Prepare TNT Input for Calculation No. 30
17661 . 17744	117 . 200	RMF Not Required
17745 . 18144	201 . 600	RMF Used to Prepare RATS Input for Calculation No. 30

Figure 2-1 Schematic of Nuclear Subsystem

Figure 2-2 "Reference Profiles" for Startup and Shutdown

Figure 2-3 Flow Chart of Nuclear, Thermal and Structural Analyses

Figure 2-4 Flow Chart for the Development of Structural Analytic Models

Figure 2-5 Flow Chart of Structural Boundary Conditions

Figure 2-6 Flow Chart of Structural Calculations

Figure 2-7 Schematic of TNT-2 Program

FIGURE 2-8 CUMULATIVE DISTRIBUTION FUNCTION FOR
TRANSFORMATION OF RANDOM NUMBERS TO RANDOM MULTIPLICATION FACTORS

Figure 2-9 Flow Scheme for S-039 Data Generation

FIGURE 2 - 10 NOZZLE CHAMBER TEMPERATURE
AND PRESSURE, COMPOSITE CORE, SOL, SHUTDOWN

FIGURE 2-11. THERMAL AND FLUID PARAMETERS,
COMPOSITE CORE, SOL, SHUTDOWN

LOADS ANALYSIS IS NOT REPORTED FOR THE
FUEL ELEMENT, A CATEGORY "C" COMPONENT

LOADS ANALYSIS IS NOT REPORTED
FOR THE CLUSTER AND HOT END HARDWARE,
A CATEGORY "C" COMPONENT.

LOADS ANALYSIS IS NOT REPORTED
FOR THE CORE PERIPHERY, A
CATEGORY "C" COMPONENT

6.0 SUPPORT PLATE AND PLENA

6.1 INTRODUCTION

The functional requirements of the Support Plate and Plena (SPP) is to provide support for the core, distribute and collect stem and by-pass flow and provide a mechanism for separating the turbine inlet from the turbine outlet flow within the NSS. Additionally, the SPP must carry the structural loads imposed upon it by the Internal Shield.

6.1.1 Description of Support Plate and Plena

6.1.1.1 Support Plate and Plena and Plenum Closure Ring

The support plate and plena consist of:

- (a) A core support plate with three integral plena: an SSCA bypass flow plenum, a support stem inlet flow plenum and a plenum which combined the bypass flow with the support stem effluent.
- (b) A piping arrangement which distributes the SSCA outlet flow to the support plate.
- (c) Flow separation baffles and associated hardware which separate the flow to the turbine from the turbine exit flow.
- (d) A diffuser or baffle and associated hardware which distributes turbine exit flow to the central shield.

6.1.1.2 Support Plate Plena, Feed and Bypass System

A. Inlet Torus

The SSCA feed flow enters the pressure vessel closure through a single pipe with a flexible joint and enters the inlet torus. The flow is channeled from the

torus to thirty sections of inlet tubing distributed around the torus.

B. Inlet Tubing

The inlet tubing directs the support stem inlet flow through the internal shield, into the plenum closure ring and subsequently through the feed plenum.

C. Bypass Torus

The bypass flow enters the pressure vessel closure through a single pipe with a flexible joint and enters the bypass torus. This torus directs the flow to six sections of bypass tubing uniformly spaced around the circumference.

D. Bypass Tubing

The bypass tubing directs the flow through the internal shield through the plenum closure ring and subsequently into the aft or bypass plenum.

6.1.1.3 Piping Cylinder

The piping cylinder is an aluminum structure which keeps the flow to the turbine inlet separated from the turbine discharge flow. It serves an additional function of carrying the axial load imposed by the internal shield and transmitting this load to the support plate.

6.1.1.4 Central Dome

The central dome is an aluminum structure which separates the turbine inlet from the discharge flow and mates with the forward flange of the piping cylinder. The dome has a penetration and accommodates an interface seal through which the turbine discharge flow re-enters the NSS.

A. Flow Diffuser

The flow diffuser is essentially a curved cylinder mounted to the central dome in the vicinity of its penetration and serves to direct the flow uniformly into the forward position of the central shield.

6.1.2 Contents of Chapter

The following items are contained in this chapter:

- a. Support plate bow - Table 6-1
- b. Radial growth of support plate - Table 6-2
- c. Axial load, top of piping cylinder - Table 6-3
- d. Axial displacement top of piping cylinder - Table 6-4
- e. Radial force on stem feed pipe at the pressure vessel dome - Table 6-5
- f. Axial force on stem feed pipe at the pressure vessel dome - Table 6-6
- g. Tangential force on stem feed pipe at the pressure vessel dome - Table 6-7
- h. Radial moment on stem feed pipe at the pressure vessel dome - Table 6-8
- i. Torsional moment on stem feed pipe at the pressure vessel dome - Table 6-9
- j. Tangential moment on stem feed pipe at the pressure vessel dome - Table 6-10
- k. Radial force on stem bypass pipe at the pressure vessel dome - Table 6-11
- l. Axial force on stem bypass pipe at the pressure vessel dome - Table 6-12
- m. Tangential force on stem bypass pipe at the pressure vessel dome - Table 6-13
- n. Radial moment on stem bypass pipe at the pressure vessel dome - Table 6-14
- o. Torsional moment on stem bypass pipe at the pressure vessel dome - Table 6-15
- p. Tangential moment on stem bypass pipe at the pressure vessel dome - Table 6-16
- q. Radial force on stem feed pipe at the support plate - Table 6-17
- r. Axial force on stem feed pipe at the support plate - Table 6-18
- s. Tangential force on stem feed pipe at the support plate - Table 6-19
- t. Radial moment on stem feed pipe at the support plate - Table 6-20
- u. Torsional moment on stem feed pipe at the support plate - Table 6-21
- v. Tangential moment on stem feed pipe at the support plate - Table 6-22
- w. Radial force on stem bypass pipe at the support plate - Table 6-23
- x. Axial force on stem bypass pipe at the support plate - Table 6-24
- y. Tangential force on stem bypass pipe at the support plate - Table 6-25
- z. Radial moment on stem bypass pipe at the support plate - Table 6-26

- aa. Torsional moment on stem bypass pipe at the support plate - Table 6-27
- ab. Tangential moment on stem bypass pipe at the support plate - Table 6-28
- ac. Radial displacement of stem feed at pressure vessel dome relative to support plate - Table 6-29
- ad. Radial displacement of stem bypass at pressure vessel dome relative to support plate - Table 6-30
- ae. Axial displacement of stem feed at pressure vessel dome relative to support plate - Table 6-31
- af. Axial displacement of stem bypass at pressure vessel dome relative to support plate - Table 6-32

The analyses were conducted for static flight steady state and transient reactor operating conditions for the support plate piping and associated hardware components, for both the composite and graphite cores.

Uncertainty analyses were conducted for each component for certain select operational modes. The structural uncertainty analysis is consistent with the thermal uncertainty analysis as documented in Data Item S-31, Reference 1.

6.2 Summary of Results and Conclusions

Data are reviewed to determine the operating mode giving the largest magnitude of load, moment, or displacement. Figures 6-1, 6-2 and 6-3 diagram the loads, moments and displacements on the support plate, the piping cylinder and the support stem feed and bypass piping.

The support plate bow is a function of the core pressure drop.* The radial growth of the support plate is a function of the support plate temperature. The load and displacements at the top of the piping cylinder are a function of the pressure drop and temperature difference at the dome. The loads, displacements and moments on the stem feed and bypass pipes are a function of pressure drop across the pipes and the relative radial and axial displacements between the support plate and pressure vessel dome region.

* Thermal contribution calculated in Reference 8 (S-036)

6.2.1 Composite Core

6.2.1.1 The Steady State Operation

Most of the significant structural loads and deflections in this ECC attain their peak values at or near to steady state operations. This is particularly true of items concerning the support plate and the piping cylinder shown in Tables 6-1 through 6-4 and also in the transient plots shown in Figures 6-61 through 6-75.

6.2.1.2 Transient Operation

Some of the piping loads and deflections reach their peak values during the reactor transient operation. The values of peak loads and deflections are shown in Tables 6-5 through 6-32 and also in the transient plots in Figures 6-19 through 6-60. One should note that while some of the piping loads components may peak during the transients the piping stresses must be computed from the cumulative effects of all the load components and also the temperature and pressure effects at any one time and, hence, the time of maximum piping stresses may not necessarily coincide with the time of occurrence of any of the transient peaks shown.

6.2.2 Graphite Core

6.2.2.1 The Steady State Operation

Most of the significant structural loads and deflections in this ECC attain their peak values at or near to steady state operations. This is particularly true of items concerning the support plate and the piping cylinder shown in Tables 6-1 through 6-4 and also in the transient plots shown in Figures 6-61 through 6-75.

6.2.2.2 Transient Operation

Some of the piping loads and deflections reach their peak values during the reactor transient operation. The values of peak loads and deflections are shown in Tables 6-5 through 6-32 and also in the transient plots in Figures 6-19 through 6-60. One should note

6.2.2.2 Transient Operation (Cont.)

that while some of these piping loads components may peak during the transients the piping stresses must be computed from the cumulative effects of all the load components and also the temperature and pressure effects at any one time and, hence, the time of maximum piping stresses may not necessarily coincide with the time of occurrence of any of the transient peaks shown.

6.3 APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION

6.3.1 Specification Identification

The specification document governing the Support Plate and Plena is EC-677561, 7-27-70.

6.3.2 Applicable Requirements

The E-105 document lists the applicable requirements.

6.4 METHOD OF ANALYSIS (DESIGN PRACTICES)

6.4.1 Analytical Procedures

Refer to Section 2.4.1.

6.4.2 Analytical Models

6.4.2.1 Thermal Model, Description

Refer to Section 2.4.2.1.

6.4.2.2 Structural Model, Description

A. Support Plate

The support plate was modeled as a circular flat plate, simply supported at its periphery. The bow calculation assumes the plate is only pressure loaded axially aft.* This pressure load is the difference between the plate inlet plenum pressure and the core exit pressure (the core pressure drop influences the plate since the stems transmit this load back to the support plate).

The radial growth calculation assumes only thermal influence.

The slope calculation was based directly on the bow results.

All the above calculations were based on standardized flat plate equations where the modulus was reduced to account for the support stem flow channel voids in the plate.

The detailed support plate system model appears in the RATS code.

B. Piping Cylinder

The piping support structure was modeled as a thick cylinder, loaded axially by the pressure drop between the turbine inlet, and turbine exit (this is referred to as the dome pressure drop). Displacements were based on the pressure load and thermal expansions, assuming no buckling.

C. Piping

The support stem feed and bypass piping system was modeled in the STASYS code to provide a stiffness matrix to be incorporated into the RATS systems model. (Refer to Data Item S-36, Reference 8. The RATS model then calculates the loads, moments and displacements of both piping systems at the pressure vessel dome and support plate interfaces, as a function of the pressure drops in the pipes and relative radial and axial

* Thermal contributions increase the bow and are discussed in Reference 8 (S-036).

displacements between the pipes fore and aft attachments.

6.4.2.3 Statistical Model Description

Refer to Section 2.4.2.3.

6.4.3 Maturity of Input Data

Refer to Section 2.4.3.

6.4.4 Validity of Analysis

Refer to Section 2.4.4.

6.5 Results of Analysis and Interpretation

6.5.1 Composite Core

6.5.1.1 Handling and Shipping

Handling and shipping procedures and equipment are designed so that the loads transmitted to the NSS during these non-operative phases are less than those encountered during vehicle boost and reactor operation.

6.5.1.2 Ground Testing

Ground test data are required for reactor testing in two test cells.

A. Test Cell "C"

This item is not required for PDR.

B. ETS-1 Test Stand

This item is not required for PDR.

6.5.1.3 Launch and Boost

The launch and boost loads imposed on the NSS result from non-operative vehicle launch conditions during maximum dynamic pressure and booster engine cut-off

(BECO), and are given below.

Reference 25 documents the inertial loads encountered during the maximum dynamic pressure and BECO phases, for the component weights given in Reference 26.

Phase	Nominal Weight	Axial G Load	Inertial Load
MAX Q T+160 secs.	896 lbs.	5.2	4659 lbs.
BECO T+165 secs.	896 lbs.	0.0	0.0 lb.

6.5.1.4 Startup

High Impulse Transient data are presented in Figures 6-4 through 6-60.

6.5.1.5 Flight Steady State

Steady State Data are presented in Tables 6-1 through 6-32.

6.5.1.6 Shutdown - High Impulse

Data are shown in Figures 6-4 through 6-60.

6.5.1.7 Space - Non-Operation

This item not required for PDR.

6.5.2 Graphite Core

6.5.2.1 Handling and Shipping

Refer to Section 6.5.1.1.

6.5.2.2 Ground Testing

Refer to Section 6.5.1.2.

6.5.2.3 Launch and Boost

Refer to Section 6.5.1.3.

6.5.2.4 Startup - High Impulse

Transient startup data are presented in Figures 6-61 through 6-117.

6.5.2.5 Flight Steady State

Steady state data are found in Tables 6-4 through 6-32.

6.5.2.6 Shutdown - High Impulse

Data are shown in Figures 6-61 through 6-117.

6.5.2.7 Space Non-Operation

Refer to Section 6.5.1.7.

6.6 References

Refer to Section 2.6.

SUPPORT PLATE

Figure 6-1. Support Plate Displacement And Bow Diagram.

Figure 6-2. Piping Cylinder Load And Displacement Diagram.

Figure 6-3. Support Stem Feed and Bypass Piping Load, Moment And Displacement Diagram.

TABLE 6-1
SUPPORT PLATE BOW - in.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	.0347	.0021	.0410	.0284
	EOL	.0347	.0021	.0410	.0284
65% Throttle	SOL	.0249	.0015	.0295	.0203
	EOL	.0249	.0015	.0295	.0203
80% Power Single TPA	SOL	.0292	.0017	.0344	.0240
	EOL	.0292	.0017	.0344	.0240
65% Throttle Single TPA	SOL	.0250	----	----	----
	EOL	.0249	----	----	----
Growth Mode Tc = 4500°R	SOL	.0354	----	----	----
	EOL	.0354	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	.035	----	----	932 10/22/70
	EOL	.035	----	----	902 10/23/70
65% Throttle	SOL	.025	----	----	929 10/26/70
	EOL	.025	----	----	829 10/27/70
80% Power Single TPA	SOL	.0297	----	----	816 11/19/70
	EOL	.0296	----	----	888 11/20/70
65% Throttle Single TPA	SOL	.0253	----	----	681 11/25/70
	EOL	.0252	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	.0359	----	----	821 11/30/70
	EOL	.0359	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-2
RADIAL GROWTH OF SUPPORT PLATE

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-0.0250	.0032	-.0348	-.0152
	EOL	-0.0268	.0034	-.0373	-.0163
65% Throttle	SOL	- .0249	.0032	-.0346	-.0152
	EOL	- .0267	.0034	-.0371	-.0163
80% Power Single TPA	SOL	-.0239	.0030	-.0331	-.0147
	EOL	-.0260	.0033	-.0360	-.0160
65% Throttle Single TPA	SOL	-.0239	----	----	----
	EOL	-.0261	----	----	----
Growth Mode Tc = 4500°R	SOL	-.0223	----	----	----
	EOL	-.0245	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-.0221	----	----	932 10/22/70
	EOL	-.0245	----	----	902 10/23/70
65% Throttle	SOL	-.0224	----	----	929 10/26/70
	EOL	-.0245	----	----	829 10/27/70
80% Power Single TPA	SOL	-.0213	----	----	816 11/19/70
	EOL	-.0237	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-.0216	----	----	681 11/25/70
	EOL	-.0239	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-.0193	----	----	821 11/30/70
	EOL	-.0217	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-3
AXIAL LOAD, TOP OF PIPING CYLINDER - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	536662	5989	555012	518312
	EOL	531765	5934	549948	513582
65% Throttle	SOL	265864			
	EOL	262712			
80% Power Single TPA	SOL	748168	7328	770623	725713
	EOL	741909	7267	764174	719644
65% Throttle Single TPA	SOL	489680	-----	-----	-----
	EOL	485564	-----	-----	-----
Growth Mode T _c = 4500°R	SOL	513228	-----	-----	-----
	EOL	507961	-----	-----	-----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	521127	-----	-----	932 10/22/70
	EOL	516200	-----	-----	902 10/23/70
65% Throttle	SOL	269905	-----	-----	929 10/26/70
	EOL	256287	-----	-----	829 10/27/70
80% Power Single TPA	SOL	726479	-----	-----	816 11/19/70
	EOL	720135	-----	-----	888 11/20/70
65% Throttle Single TPA	SOL	475719	-----	-----	681 11/25/70
	EOL	470957	-----	-----	820 11/30/70
Growth Mode T _c = 4500°R	SOL	498428	-----	-----	821 11/30/70
	EOL	492279	-----	-----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-4
AXIAL DISPLACEMENT, TOP OF PIPING CYLINDER - in.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	0.2309	.0106	.2633	.1985
	EOL	0.2271	.0104	.2589	.1953
65% Throttle	SOL	0.1875	.0112	.2218	.1532
	EOL	0.1767	.0106	.2092	.1442
90% Power Single TPA	SOL	0.2150	.0104	.2468	.1832
	EOL	0.2097	.0101	.2407	.1787
65% Throttle Single TPA	SOL	0.1918	----	----	----
	EOL	0.1823	----	----	----
Growth Mode Tc = 4500°R	SOL	0.2133	----	----	----
	EOL	0.2086	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	.2211	----	----	932 10/22/70
	EOL	.2170	----	----	902 10/23/70
65% Throttle	SOL	.1757	----	----	929 10/26/70
	EOL	.1626	----	----	829 10/27/70
80% Power Single TPA	SOL	.2050	----	----	816 11/19/70
	EOL	.1982	----	----	888 11/20/70
65% Throttle Single TPA	SOL	.1806	----	----	681 11/25/70
	EOL	.1686	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	.2027	----	----	821 11/30/70
	EOL	.1969	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-5
RADIAL FORCE ON STEM FEED PIPE AT THE PRESSURE VESSEL DOME - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	93.6	11.1	127.7	59.5
	EOL	88.4	10.5	120.6	56.2
65% Throttle	SOL	74.0	12.5	112.4	35.6
	EOL	69.9	11.8	106.2	33.6
80% Power Single TPA	SOL	85.5	10.6	118.2	52.9
	EOL	79.5	9.8	100.8	49.1
65% Throttle Single TPA	SOL	75.3	----	----	----
	EOL	70.3	----	----	----
Growth Mode Tc = 4500°R	SOL	86.3	----	----	----
	EOL	79.8	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	90.9	----	----	932 10/22/70
	EOL	84.3	----	----	902 10/23/70
65% Throttle	SOL	69.3	----	----	929 10/26/70
	EOL	64.5	----	----	829 10/27/70
80% Power Single TPA	SOL	81.7	----	----	816 11/19/70
	EOL	75.0	----	----	888 11/20/70
65% Throttle Single TPA	SOL	71.0	----	----	681 11/25/70
	EOL	65.1	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	82.8	----	----	821 11/30/70
	EOL	75.5	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-6
AXIAL FORCE ON STEM FEED PIPE AT THE PRESSURE VESSEL DOME - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	178	116	533	-177
	EOL	-120	78	-361	119
65% Throttle	SOL	-650	107	-979	-322
	EOL	-1013	167	-1525	-502
80% Power Single TPA	SOL	180	112	525	-165
	EOL	-34	22	-101	32
65% Throttle Single TPA	SOL	-293	----	----	----
	EOL	-558	----	----	----
Growth Mode Tc = 4500°R	SOL	-9	----	----	----
	EOL	-307	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	113	----	----	932 10/22/70
	EOL	151	----	----	902 10/23/70
65% Throttle	SOL	-715	----	----	929 10/26/70
	EOL	-1124	----	----	829 10/27/70
80% Power Single TPA	SOL	203	----	----	816 11/19/70
	EOL	-60	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-299	----	----	681 11/25/70
	EOL	-626	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	24	----	----	821 11/30/70
	EOL	-406	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-7
TANGENTIAL FORCE ON STEM FEED PIPE AT THE PRESSURE VESSEL DOME - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	42.4	1.92	48.3	36.5
	EOL	45.0	2.04	51.3	38.7
65% Throttle	SOL	41.9	1.97	48.0	35.8
	EOL	44.8	2.11	51.3	38.3
80% Power Single TPA	SOL	41.2	1.88	47.0	35.4
	EOL	44.4	2.02	50.6	38.2
65% Throttle Single TPA	SOL	41.1	----	----	----
	EOL	44.3	----	----	----
Growth Mode Tc = 4500°R	SOL	38.7	----	----	----
	EOL	41.9	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	38.6	----	----	932 10/22/70
	EOL	41.9	----	----	902 10/23/70
65% Throttle	SOL	38.8	----	----	929 10/26/70
	EOL	42.1	----	----	829 10/27/70
80% Power Single TPA	SOL	38.0	----	----	816 11/19/70
	EOL	41.5	----	----	888 11/20/70
65% Throttle Single TPA	SOL	38.0	----	----	681 11/25/70
	EOL	41.6	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	34.9	----	----	821 11/30/70
	EOL	38.4	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-8
RADIAL MOMENT ON STEM FEED PIPE AT THE PRESSURE VESSEL DOME - in. - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-1089	23.1	-1160	-1018.
	EOL	-1128	23.9	-1201	-1054.
65% Throttle	SOL	-1028	30.3	-1121.	-935.
	EOL	-1074	31.6	-1171.	-977.
80% Power Single TPA	SOL	-1045	23.8	-1118.	-972.
	EOL	-1091	24.8	-1167.	-1014.
65% Throttle Single TPA	SOL	-1015	----	----	----
	EOL	-1065	----	----	----
Growth Mode Tc = 4500°R	SOL	- 997	----	----	----
	EOL	-1043	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-1008.	----	----	932 10/22/70
	EOL	-1056.	----	----	902 10/23/70
65% Throttle	SOL	- 954.	----	----	929 10/26/70
	EOL	-1006.	----	----	829 10/27/70
80% Power Single TPA	SOL	- 971.	----	----	816 11/19/70
	EOL	-1023.	----	----	888 11/20/70
65% Throttle Single TPA	SOL	- 943.	----	----	681 11/25/70
	EOL	- 998.	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	- 913.	----	----	821 11/30/70
	EOL	- 962.	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-9
TORSIONAL MOMENT ON STEM FEED PIPE AT THE PRESSURE VESSEL DOME - in. - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-237.	4.88	-252.	-222.
	EOL	-245.	5.05	-260.	-230.
65% Throttle	SOL	-224.	6.27	-243.	-204.
	EOL	-234.	6.55	-254.	-214
80% Power Single TPA	SOL	-227.	5.06	-243.	-212.
	EOL	-237.	5.28	-254.	-221.
65% Throttle Single TPA	SOL	-221.	----	----	----
	EOL	-232.	----	----	----
Growth Mode Tc = 4500°R	SOL	-217.	----	----	----
	EOL	-227.	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-219.	----	----	932 10/22/70
	EOL	-230.	----	----	902 10/23/70
65% Throttle	SOL	-208	----	----	929 10/26/70
	EOL	-219.	----	----	829 10/27/70
80% Throttle Single TPA	SOL	-211.	----	----	816 11/19/70
	EOL	-223.	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-205.	----	----	681 11/25/70
	EOL	-217.	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-199.	----	----	821 11/30/70
	EOL	-209.	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-10
TANGENTIAL MOMENT ON STEM FEED PIPE AT THE PRESSURE VESSEL DOME - in. - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-1976.	56.1	-2148	-1804
	EOL	-2046.	58.1	-2254.	-1868.
65% Throttle	SOL	-1866.	68.0	-2074.	-1657.
	EOL	-1949	71.1	-2167.	-1731.
80% Power Single TPA	SOL	-1896.	57.7	-2073.	-1719.
	EOL	-1979	60.2	-2163.	-1794.
65% Throttle Single TPA	SOL	-1841.	----	----	----
	EOL	-1933.	----	----	----
Growth Mode Tc = 4500°R	SOL	-1809.	----	----	----
	EOL	-1892.	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-1829.	----	----	932 10/22/70
	EOL	-1916.	----	----	902 10/23/70
65% Throttle	SOL	-1732.	----	----	929 10/26/70
	EOL	-1826.	----	----	829 10/27/70
80% Power Single TPA	SOL	-1762.	----	----	816 11/19/70
	EOL	-1856.	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-1710.	----	----	681 11/25/70
	EOL	-1811.	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-1658.	----	----	821 11/30/70
	EOL	-1746.	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-11
RADIAL FORCE ON STEM BYPASS PIPE AT THE PRESSURE VESSEL DOME - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	4.08	0.211	4.73	3.43
	EOL	3.97	0.206	4.60	3.34
65% Throttle	SOL	3.44	.231	4.15	2.73
	EOL	3.37	.226	4.06	2.68
80% Power Single TPA	SOL	3.76	.206	4.39	3.13
	EOL	3.66	.201	4.27	3.05
65% Throttle Single TPA	SOL	3.41	----	----	----
	EOL	3.34	----	----	----
Growth Mode Tc = 4500°R	SOL	3.52	----	----	----
	EOL	3.41	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	3.42	----	----	932 10/22/70
	EOL	3.31	----	----	902 10/23/70
65% Throttle	SOL	2.79	----	----	929 10/26/70
	EOL	2.72	----	----	829 10/27/70
80% Power Single TPA	SOL	3.12	----	----	816 11/19/70
	EOL	3.01	----	----	888 11/20/70
65% Throttle Single TPA	SOL	2.78	----	----	681 11/25/70
	EOL	2.69	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	2.83	----	----	821 11/30/70
	EOL	2.68	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-12
AXIAL FORCE ON STEM BYPASS PIPE AT THE PRESSURE VESSEL DOME - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	268.	44.5	404.	131.
	EOL	270.	44.8	407.	132.
65% Throttle	SOL	114.	55.0	283.	-53.
	EOL	108.	51.7	266.	-50.
80% Power Single TPA	SOL	268.	44.5	404.	131.
	EOL	270.	44.9	407.	132.
65% Throttle Single TPA	SOL	165.	----	----	----
	EOL	161.	----	----	----
Growth Mode Tc = 4500°R	SOL	258.	----	----	----
	EOL	259.	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	297.	----	----	932 10/22/70
	EOL	304.	----	----	902 10/23/70
65% Throttle	SOL	147.	----	----	929 10/26/70
	EOL	141.	----	----	829 10/27/70
80% Power Single TPA	SOL	297.	----	----	816 11/19/70
	EOL	299.	----	----	888 11/20/70
65% Throttle Single TPA	SOL	194.	----	----	681 11/25/70
	EOL	191.	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	294.	----	----	821 11/30/70
	EOL	299.	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-13
TANGENTIAL FORCE ON STEM BYPASS PIPE AT THE PRESSURE VESSEL DOME - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	20.1	0.991	23.1	17.1
	EOL	19.8	0.974	22.7	16.8
65% Throttle	SOL	17.2	1.014	20.3	14.1
	EOL	17.1	1.003	20.1	14.0
80% Power Single TPA	SOL	18.6	0.958	21.6	15.7
	EOL	18.3	.942	21.2	15.4
65% Throttle Single TPA	SOL	17.0	----	----	----
	EOL	16.9	----	----	----
Growth Mode Tc = 4500°R	SOL	17.3	----	----	----
	EOL	16.9	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	16.6	----	----	932 10/22/70
	EOL	16.3	----	----	902 10/23/70
65% Throttle	SOL	13.9	----	----	929 10/26/70
	EOL	13.7	----	----	829 10/27/70
80% Power Single TPA	SOL	15.3	----	----	816 11/19/70
	EOL	15.0	----	----	888 11/20/70
65% Throttle Single TPA	SOL	13.8	----	----	681 11/25/70
	EOL	13.5	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	13.7	----	----	821 11/30/70
	EOL	13.2	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-14
RADIAL MOMENT ON STEM BYPASS PIPE AT THE PRESSURE VESSEL DOME - in. - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	7.90	.423	9.20	6.60
	EOL	7.85	.420	9.14	6.56
65% Throttle	SOL	6.93	.389	8.12	5.74
	EOL	6.95	.390	8.14	5.76
80% Power Single TPA	SOL	7.36	.401	8.59	6.13
	EOL	7.35	.401	8.58	6.12
65% Throttle Single TPA	SOL	6.80	----	----	----
	EOL	6.86	----	----	----
Growth Mode Tc = 4500°R	SOL	6.75	----	----	----
	EOL	6.73	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	6.41	----	----	932 10/22/70
	EOL	6.40	----	----	902 10/23/70
65% Throttle	SOL	5.54	----	----	929 10/26/70
	EOL	5.58	----	----	829 10/27/70
80% Power Single TPA	SOL	5.97	----	----	816 11/19/70
	EOL	5.95	----	----	888 11/20/70
65% Throttle Single TPA	SOL	5.45	----	----	681 11/25/70
	EOL	5.48	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	5.20	----	----	821 11/30/70
	EOL	5.14	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-15
TORSIONAL MOMENT ON STEM BYPASS PIPE AT THE PRESSURE VESSEL DOME - in. - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-48.5	2.46	-56.2	-40.9
	EOL	-48.2	2.45	-55.7	-40.7
65% Throttle	SOL	-42.5	2.25	-49.4	-35.6
	EOL	-42.6	2.26	-49.5	-35.7
80% Power Single TPA	SOL	-45.2	2.33	-52.3	-38.0
	EOL	-45.1	2.33	-52.2	-38.0
65% Throttle Single TPA	SOL	-41.8	----	----	----
	EOL	-42.1	----	----	----
Growth Mode Tc = 4500°R	SOL	-41.4	----	----	----
	EOL	-41.3	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-39.3	----	----	932 10/22/70
	EOL	-39.3	----	----	902 10/23/70
65% Throttle	SOL	-34.0	----	----	929 10/26/70
	EOL	-34.2	----	----	829 10/27/70
80% Power Single TPA	SOL	-36.6	----	----	816 11/19/70
	EOL	-36.5	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-33.5	----	----	681 11/25/70
	EOL	-33.6	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-31.9	----	----	821 11/30/70
	EOL	-31.6	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-16
TANGENTIAL MOMENT ON STEM BYPASS PIPE AT THE PRESSURE VESSEL DOME - in. - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	219.	11.3	254.	184.
	EOL	218.	11.2	252.	183.
65% Throttle	SOL	192.	10.3	224.	161.
	EOL	193.	10.3	224.	161.
80% Power Single TPA	SOL	204.	10.6	237.	171.
	EOL	204.	10.6	236.	171.
65% Throttle Single TPA	SOL	189.	----	----	----
	EOL	190.	----	----	----
Growth Mode Tc = 4500°R	SOL	187.	----	----	----
	EOL	187.	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	178.	----	----	932 10/22/70
	EOL	178.	----	----	902 10/23/70
65% Throttle	SOL	154.	----	----	929 10/26/70
	EOL	155.	----	----	829 10/27/70
80% Power Single TPA	SOL	166.	----	----	816 11/19/70
	EOL	165.	----	----	888 11/20/70
65% Throttle Single TPA	SOL	151.	----	----	681 11/25/70
	EOL	152.	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	144.	----	----	821 11/30/70
	EOL	143.	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-17
RADIAL FORCE ON STEM FEED PIPE AT THE SUPPORT PLATE - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-24.7	.787	-27.2	-22.3
	EOL	-27.6	.878	-30.3	-24.9
65% Throttle	SOL	-28.6	.931	-31.5	-25.8
	EOL	-32.0	1.042	-35.2	-28.8
80% Power Single TPA	SOL	-23.7	.746	-26.0	-21.4
	EOL	-26.2	.825	-28.8	-23.7
65% Throttle Single TPA	SOL	-26.0	----	----	----
	EOL	-29.0	----	----	----
Growth Mode Tc = 4500°R	SOL	-23.7	----	----	----
	EOL	-26.8	----	----	----
Graphire Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-23.2	----	----	932 10/22/70
	EOL	-26.1	----	----	902 10/23/70
65% Throttle	SOL	-27.2	----	----	929 10/26/70
	EOL	-31.1	----	----	829 10/27/70
80% Power Single TPA	SOL	-21.8	----	----	816 11/19/70
	EOL	-24.8	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-24.3	----	----	681 11/25/70
	EOL	-27.8	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-21.5	----	----	821 11/30/70
	EOL	-25.4	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-18
AXIAL FORCE ON STEM FEED PIPE AT THE SUPPORT PLATE - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-110	10.2	-141	-78
	EOL	-142	13.2	-183	-101
65% Throttle	SOL	-179	11.6	-215	-143
	EOL	-218	14.2	-262	-175
80% Power Single TPA	SOL	-105	9.5	-134	-75
	EOL	-130	11.8	-166	-94
65% Throttle Single TPA	SOL	-145	----	----	----
	EOL	-175	----	----	----
Growth Mode Tc = 4500°R	SOL	-116	----	----	----
	EOL	-149	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-106	----	----	932 10/22/70
	EOL	-136	----	----	902 10/23/70
65% Throttle	SOL	-177	----	----	929 10/26/70
	EOL	-220	----	----	829 10/27/70
80% Power Single TPA	SOL	-94	----	----	816 11/19/70
	EOL	-124	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-137	----	----	681 11/25/70
	EOL	-174	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-103	----	----	821 11/30/70
	EOL	-149	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-19
TANGENTIAL FORCE ON STEM FEED PIPE AT THE SUPPORT PLATE - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-29.1	2.61	-37.2	-21.1
	EOL	-36.8	3.30	-46.9	-26.7
65% Throttle	SOL	-45.7	2.83	-54.3	-37.0
	EOL	-55.1	3.41	-65.5	-44.6
80% Power Single TPA	SOL	-27.6	2.42	-35.0	-20.1
	EOL	-33.5	2.94	-42.5	-24.5
65% Throttle Single TPA	SOL	-37.2	----	----	----
	EOL	-44.4	----	----	----
Growth Mode Tc = 4500°R	SOL	-30.6	----	----	----
	EOL	-38.4	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-28.3	----	----	932 10/22/70
	EOL	-35.4	----	----	902 10/23/70
65% Throttle	SOL	-45.0	----	----	929 10/26/70
	EOL	-55.5	----	----	829 10/27/70
80% Power Single TPA	SOL	-24.9	----	----	816 11/19/70
	EOL	-32.0	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-35.2	----	----	681 11/25/70
	EOL	-43.9	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-27.5	----	----	821 11/30/70
	EOL	-38.3	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-20
RADIAL MOMENT ON STEM FEED PIPE AT THE SUPPORT PLATE - in. - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-197.	12.3	-234.	-159.
	EOL	-231.	14.4	-275.	-186.
65% Throttle	SOL	-262.	12.8	-301.	-223.
	EOL	-304.	14.9	-350.	-259.
80% Power Single TPA	SOL	-186.	11.0	-220.	-152.
	EOL	-212.	12.5	-251.	-174.
65% Throttle Single TPA	SOL	-224.	--	--	--
	EOL	-257.	--	--	--
Growth Mode Tc = 4500°C	SOL	-198.	--	--	--
	EOL	-232.	--	--	--
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-189.	--	--	932 10/22/70
	EOL	-220.	--	--	902 10/23/70
65% Throttle	SOL	-255.	--	--	929 10/26/70
	EOL	-302.	--	--	829 10/27/70
80% Power Single TPA	SOL	-170.	--	--	816 11/19/70
	EOL	-202.	--	--	888 11/20/70
65% Throttle Single TPA	SOL	-212.	--	--	681 11/25/70
	EOL	-251.	--	--	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-179.	--	--	821 11/30/70
	EOL	-227.	--	--	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-21
TORSIONAL MOMENT ON STEM FEED PIPE AT THE SUPPORT PLATE - in. - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	23.0	1.39	27.3	18.8
	EOL	27.8	1.68	33.0	22.7
65% Throttle	SOL	32.5	1.60	37.4	27.5
	EOL	38.3	1.89	44.1	32.5
80% Power Single TPA	SOL	22.0	1.29	25.9	18.0
	EOL	25.8	1.52	30.5	21.2
65% Throttle Single TPA	SOL	27.5	----	----	----
	EOL	32.2	----	----	----
Growth Mode Tc = 4500°R	SOL	23.3	----	----	----
	EOL	28.3	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	22.0	----	----	932 10/22/70
	EOL	26.6	----	----	902 10/23/70
65% Throttle	SOL	31.6	----	----	929 10/26/70
	EOL	38.1	----	----	829 10/27/70
80% Power Single TPA	SOL	20.0	----	----	816 11/19/70
	EOL	24.6	----	----	888 11/20/70
65% Throttle Single TPA	SOL	25.9	----	----	681 11/25/70
	EOL	31.4	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	21.0	----	----	821 11/30/70
	EOL	27.7	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-22
TANGENTIAL MOMENT ON STEM FEED PIPE AT THE SUPPORT PLATE - in. - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	96.5	6.24	115.6	77.4
	EOL	86.6	5.60	103.7	69.4
65% Throttle	SOL	55.0	11.07	88.9	21.0
	EOL	42.7	8.61	69.2	16.3
80% Power Single TPA	SOL	93.2	6.12	111.9	74.4
	EOL	87.7	5.76	105.3	70.0
65% Throttle Single TPA	SOL	69.8	----	----	----
	EOL	62.4	----	----	----
Growth Mode Tc = 4500°R	SOL	80.6	----	----	----
	EOL	71.3	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	86.8	----	----	932 10/22/70
	EOL	79.3	----	----	902 10/23/70
65% Throttle	SOL	46.0	----	----	929 10/26/70
	EOL	32.2	----	----	829 10/27/70
80% Power Single TPA	SOL	88.1	----	----	816 11/19/70
	EOL	80.9	----	----	888 11/20/70
65% Throttle Single TPA	SOL	63.6	----	----	681 11/25/70
	EOL	53.8	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	75.1	----	----	821 11/30/70
	EOL	60.2	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-23
RADIAL FORCE ON STEM BYPASS PIPE AT THE SUPPORT PLATE - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-24.2	3.50	-35.0	-13.5
	EOL	-24.8	3.58	-25.8	-13.8
65% Throttle	SOL	-12.7	3.92	-24.8	-0.7
	EOL	-12.9	3.97	-25.0	-0.7
80% Power Single TPA	SOL	-22.3	3.48	-33.0	-11.7
	EOL	-23.0	3.59	-33.0	-12.0
65% Throttle Single TPA	SOL	-15.1	----	----	----
	EOL	-15.5	----	----	----
Growth Mode Tc = 4500°R	SOL	-23.8	----	----	----
	EOL	-24.6	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-26.9	----	----	932 10/22/70
	EOL	-28.0	----	----	902 10/23/70
65% Throttle	SOL	-15.6	----	----	929 10/26/70
	EOL	-16.1	----	----	829 10/27/70
80% Power Single TPA	SOL	-25.0	----	----	816 11/19/70
	EOL	-25.8	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-17.7	----	----	681 11/25/70
	EOL	-18.3	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-27.1	----	----	821 11/30/70
	EOL	-28.2	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-24
AXIAL FORCE ON STEM BYPASS PIPE AT THE SUPPORT PLATE - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	- 45.9	29.1	-135.3	43.4
	EOL	- 43.7	27.7	-128.9	41.3
65% Throttle	SOL	-114.8	31.8	-212.3	-17.3
	EOL	-119.6	33.1	-221.2	-18.1
80% Power Single TPA	SOL	- 31.6	28.9	-120.3	56.9
	EOL	- 30.3	27.7	-115.3	54.6
65% Throttle Single TPA	SOL	- 80.3	----	----	----
	EOL	- 84.2	----	----	----
Growth Mode Tc = 4500°R	SOL	- 21.5	----	----	----
	EOL	- 20.0	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	12.1	----	----	932 10/22/70
	EOL	16.0	----	----	902 10/23/70
65% Throttle	SOL	-57.7	----	----	929 10/26/70
	EOL	-62.2	----	----	829 10/27/70
80% Power Single TPA	SOL	23.8	----	----	816 11/19/70
	EOL	25.3	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-26.3	----	----	681 11/25/70
	EOL	-28.8	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	42.5	----	----	821 11/30/70
	EOL	47.0	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-25
TANGENTIAL FORCE ON STEM BYPASS PIPE AT THE SUPPORT PLATE - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-1.42	2.84	-10.12	7.28
	EOL	-.96	1.93	-6.90	4.97
65% Throttle	SOL	-7.86	3.13	-17.45	1.73
	EOL	-8.06	3.21	-17.90	2.78
80% Power Single TPA	SOL	-.14	2.83	-8.81	8.53
	EOL	.30	6.10	19.00	-18.40
65% Throttle Single TPA	SOL	-4.73	----	----	----
	EOL	-4.78	----	----	----
Growth Mode Tc = 4500°R	SOL	.34	----	----	----
	EOL	.81	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	3.18	----	----	932 10/22/70
	EOL	3.89	----	----	902 10/23/70
65% Throttle	SOL	-3.20	----	----	929 10/26/70
	EOL	-3.33	----	----	829 10/27/70
80% Power Single TPA	SOL	4.33	----	----	816 11/19/70
	EOL	4.82	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-.35	----	----	681 11/25/70
	EOL	-.25	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	5.51	----	----	821 11/30/70
	EOL	6.27	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-26
RADIAL MOMENT ON STEM BYPASS PIPE AT THE SUPPORT PLATE - in. - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-50.2	9.62	-79.6	-20.7
	EOL	-47.7	9.15	-75.8	-19.7
65% Throttle	SOL	-13.8	16.2	-63.7	35.9
	EOL	- 9.6	11.2	-44.1	24.9
80% Power Single TPA	SOL	-50.3	9.46	-79.4	-21.3
	EOL	-47.3	8.90	-74.6	-20.0
65% Throttle Single TPA	SOL	-26.4	----	----	----
	EOL	-22.3	----	----	----
Growth Mode Tc = 4500°R	SOL	-49.6	----	----	----
	EOL	-46.3	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-60.4	----	----	932 10/22/70
	EOL	-58.0	----	----	902 10/23/70
65% Throttle	SOL	-23.4	----	----	929 10/26/70
	EOL	-18.9	----	----	829 10/27/70
80% Power Single TPA	SOL	-59.7	----	----	816 11/19/70
	EOL	-56.3	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-35.2	----	----	681 11/25/70
	EOL	-30.9	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-61.1	----	----	821 11/30/70
	EOL	-58.2	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-27
TORSIONAL MOMENT ON STEM BYPASS PIPE AT THE SUPPORT PLATE - in.-lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	12.5	3.67	23.7	1.2
	EOL	12.1	3.56	23.0	1.2
65% Throttle	SOL	19.9	4.04	32.3	7.6
	EOL	20.5	4.15	33.2	7.8
80% Power Single TPA	SOL	10.2	3.63	21.4	-.88
	EOL	10.0	3.55	20.9	-.86
65% Throttle Single TPA	SOL	15.6	----	----	----
	EOL	16.1	----	----	----
Growth Mode Tc = 4500°R	SOL	8.5	----	----	----
	EOL	8.2	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	4.18	----	----	932 10/22/70
	EOL	3.53	----	----	902 10/23/70
65% Throttle	SOL	11.80	----	----	929 10/26/70
	EOL	12.30	----	----	829 10/27/70
80% Power Single TPA	SOL	2.32	----	----	816 11/19/70
	EOL	2.04	----	----	888 11/20/70
65% Throttle Single TPA	SOL	7.95	----	----	681 11/25/70
	EOL	8.21	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	0.57	----	----	821 11/30/70
	EOL	1.24	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-28
TANGENTIAL MOMENT ON STEM BYPASS PIPE AT THE SUPPORT PLATE - in. - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	119	31	214	24
	EOL	123	32	221	25
65% Throttle	SOL	28	39	147	-90
	EOL	26	35	134	-83
80% Power Single TPA	SOL	123	31	223	27
	EOL	127	32	225	28
65% Throttle Single TPA	SOL	61	----	----	----
	EOL	61	----	----	----
Growth Mode Tc = 4500°R	SOL	121	----	----	----
	EOL	125	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	148	----	----	932 10/22/70
	EOL	155	----	----	902 10/23/70
65% Throttle	SOL	59	----	----	929 10/26/70
	EOL	58	----	----	829 10/27/70
80% Power Single TPA	SOL	151	----	----	816 11/19/70
	EOL	156	----	----	888 11/20/70
65% Throttle Single TPA	SOL	89	----	----	681 11/25/70
	EOL	90	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	155	----	----	821 11/30/70
	EOL	162	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-29

RADIAL DISPLACEMENT OF STEM FEED AT PRESSURE VESSEL DOME RELATIVE TO SUPPORT PLATE - in.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-.0113	.0036	-.0222	-.0004
	EOL	-.0090	.0029	-.0178	-.0002
65% Throttle	SOL	-.0061			
	EOL	-.0041			
80% Power Single TPA	SOL	-.0095	.0034	-.0199	.0009
	EOL	-.0068	.0024	-.0143	.0006
65% Throttle Single TPA	SOL	-.0068	-----	-----	-----
	EOL	-.0043	-----	-----	-----
Growth Mode Tc = 4500°R	SOL	-.0105	-----	-----	-----
	EOL	-.0077	-----	-----	-----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-.0118	-----	-----	932 10/22/70
	EOL	-.0089	-----	-----	902 10/23/70
65% Throttle	SOL	-.0059	-----	-----	929 10/26/70
	EOL	-.0035	-----	-----	829 10/27/70
80% Power Single TPA	SOL	-.0095	-----	-----	816 11/19/70
	EOL	-.0065	-----	-----	888 11/20/70
65% Throttle Single TPA	SOL	-.0066	-----	-----	681 11/25/70
	EOL	-.0038	-----	-----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-.0108	-----	-----	821 11/30/70
	EOL	-.0077	-----	-----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-30
RADIAL DISPLACEMENT OF STEM BYPASS AT PRESSURE VESSEL DOME RELATIVE TO SUPPORT PLATE - in.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-.0142	.0036	-.0254	-.0031
	EOL	-.0119	.0030	-.0213	-.0026
65% Throttle	SOL	-.0087			
	EOL	-.0066			
80% Power Single TPA	SOL	-.0122	.0034	-.0228	-.0016
	EOL	-.0095	.0026	-.0178	-.0012
65% Throttle Single TPA	SOL	-.0093	-----	-----	-----
	EOL	-.0068	-----	-----	-----
Growth Mode Tc = 4500°R	SOL	-.0132	-----	-----	-----
	EOL	-.0104	-----	-----	-----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-.0146	-----	-----	932 10/22/70
	EOL	-.0116	-----	-----	902 10/23/70
65% Throttle	SOL	-.0082	-----	-----	929 10/26/70
	EOL	-.0058	-----	-----	829 10/27/70
80% Power Single TPA	SOL	-.0120	-----	-----	816 11/19/70
	EOL	-.0090	-----	-----	888 11/20/70
65% Throttle Single TPA	SOL	-.0089	-----	-----	681 11/25/70
	EOL	-.0062	-----	-----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-.0133	-----	-----	821 11/30/70
	EOL	-.0101	-----	-----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-31

AXIAL DISPLACEMENT OF STEM FEED AT PRESSURE VESSEL DOME RELATIVE TO SUPPORT PLATE - in.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	.0111	.0117	.0471	.0247
	EOL	.0124	.0130	.0524	.0275
65% Throttle	SOL	-.0204			
	EOL	-.0214			
80% Power Single TPA	SOL	.0122	.0116	.0478	.0234
	EOL	.0133	.0127	.0522	.0256
65% Throttle Single TPA	SOL	-.0088	-----	-----	-----
	EOL	-.0095	-----	-----	-----
Growth Mode Tc = 4500°R	SOL	.0185	-----	-----	-----
	EOL	.0198	-----	-----	-----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	.0316	-----	-----	932 10/22/70
	EOL	.0339	-----	-----	902 10/23/70
65% Throttle	SOL	-.0001	-----	-----	929 10/26/70
	EOL	-.0007	-----	-----	829 10/27/70
80% Power Single TPA	SOL	.0318	-----	-----	816 11/19/70
	EOL	.0331	-----	-----	888 11/20/70
65% Throttle Single TPA	SOL	.0103	-----	-----	681 11/25/70
	EOL	.0102	-----	-----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	.0413	-----	-----	821 11/30/70
	EOL	.0439	-----	-----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 6-32
AXIAL DISPLACEMENT OF STEM BYPASS AT PRESSURE VESSEL DOME RELATIVE TO SUPPORT PLATE - in.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	.0129	.0117	.0488	-.0228
	EOL	.0142	.0128	.0534	-.0250
65% Throttle	SOL	-.0188			
	EOL	-.0199			
80% Power Single TPA	SOL	.0138	.0116	.0493	-.0217
	EOL	.0149	.0125	.0533	-.0234
65% Throttle Single TPA	SOL	-.0073	-----	-----	-----
	EOL	-.0080	-----	-----	-----
Growth Mode Tc = 4500°R	SOL	.0201	-----	-----	-----
	EOL	.0214	-----	-----	-----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	.033	-----	-----	932 10/22/70
	EOL	.0355	-----	-----	902 10/23/70
65% Throttle	SOL	.0013	-----	-----	929 10/26/70
	EOL	.0006	-----	-----	829 10/27/70
80% POWER Single TPA	SOL	.0333	-----	-----	816 11/19/70
	EOL	.0346	-----	-----	888 11/20/70
65% Throttle Single TPA	SOL	.0117	-----	-----	681 11/25/70
	EOL	.0116	-----	-----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	.0428	-----	-----	821 11/30/70
	EOL	.0453	-----	-----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-4. Axial Load, Top of Piping Cylinder Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-5. Axial Load, Top of Piping Cylinder Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-6. Axial Load, Top of Piping Cylinder Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-7. Axial Displacement, Top of Piping Cylinder Versus Time, CSUS

AXIAL DISPLACEMENT TOP OF PIPING CYLINDER - INCHES

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-8. Axial Displacement, Top of Piping Cylinder Versus Time, CSUE

AXIAL DISPLACEMENT TOP OF PIPING CYLINDER - INCHES

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-9. Axial Displacement, Top of Piping Cylinder Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-10. Support Plate Bow Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-11. Support Plate Bow Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-12. Support Plate Bow Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-13. Support Plate Slope at the Periphery Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-14. Support Plate Slope at the Periphery Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-15. Support Plate Slope at the Periphery Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-16. Radial Growth of Support Plate Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-17. Radial Growth of Support Plate Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-18. Radial Growth of Support Plate Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-19. Radial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-20. Radial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-21. Radial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-22. Axial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-23. Axial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUE

Figure 6-24. Axial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-25. Tangential Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-26. Tangential Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-27. Tangential Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-28. Radial Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-29. Radial Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-30. Radial Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-31. Torsional Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-32. Torsional Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-33. Torsional Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-34. Tangential Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-35. Tangential Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-36. Tangential Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-37. Radial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-38. Radial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-39. Radial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-40. Axial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-41. Axial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-42. Axial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-43. Radial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-44. Radial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-45. Radial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-46. Axial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-47. Axial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-48. Axial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-49. Tangential Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-50. Tangential Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-51. Tangential Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-52. Radial Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-53. Radial Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-54. Radial Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-55. Torsional Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-56. Torsional Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-57. Torsional Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 6-58. Tangential Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 6-59. Tangential Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 6-60. Tangential Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, CSDSE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-61. Axial Load, Top of Piping Cylinder Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-62. Axial Load, Top of Piping Cylinder Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-63. Axial Load, Top of Piping Cylinder Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-64. Axial Displacement, Top of Piping Cylinder Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-65. Axial Displacement, Top of Piping Cylinder Versus Time, GSDS

AXIAL DISPLACEMENT TOP OF PIPING CYLINDER - INCHES

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-66. Axial Displacement, Top of Piping Cylinder Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-67. Support Plate Bow Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-68. Support Plate Bow Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-69. Support Plate Bow Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-70. Support Plate Slope at the Periphery Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-71. Support Plate Slope at the Periphery Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-72. Support Plate Slope at the Periphery Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-73. Radial Growth of Support Plate Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-74. Radial Growth of Support Plate Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-75. Radial Growth of Support Plate Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-76. Radial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-77. Radial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-78. Radial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-79. Axial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-80. Axial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-81. Axial Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-82. Tangential Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-83. Tangential Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-84. Tangential Force on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-85. Radial Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-86. Radial Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-87. Radial Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-88. Torsional Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE.

Figure 6-89. Torsional Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-90. Torsional Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-91. Tangential Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-92. Tangential Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-93. Tangential Moment on Stem Feed and Bypass Pipes at the Pressure Vessel Dome Versus Time, GSDE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-95. Radial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-96. Radial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-97. Axial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-98. Axial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-99. Axial Displacement of Stem Feed and Bypass Pipes at Pressure Vessel Dome Relative to Support Plate Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-100. Radial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-101. Radial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-102. Radial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDE

Figure 6-103. Axial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-104. Axial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-105. Axial Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-106. Tangential Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-107. Tangential Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-108. Tangential Force on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-109. Radial Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-110. Radial Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-111. Radial Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-112. Torsional Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-113. Torsional Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-114. Torsional Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 6-115. Tangential Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 6-116. Tangential Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 6-117. Tangential Moment on Stem Feed and Bypass Pipes at the Support Plate Versus Time, GSDE

7.0 INTERNAL SHIELD

7.1 INTRODUCTION

The NSS incorporates an Internal Shield which consists of a central and peripheral shield. The central shield is located in the area forward of the core support plate. The peripheral shield covers the annulus area forward of the reflector.

The primary functions of the Internal Shield are to attenuate radiation to specified levels to protect engine components and to provide flow passages for reactor propellant.

7.1.1 Description of Internal Shield

The Internal Shield consists of a Lead and Boron Carbide-Aluminum-Titanium Hydride (BATH) central shield located forward of the core extending in radius to the outer radius of the core, and peripheral shield located above the reflector extending from the inner radius of the reflector to the inner radius of the pressure vessel.

7.1.1.1 Supporting Structure

The central shield is supported by a .805 inch thick aluminum plate. The plate is attached at its outer periphery to a radial flange on the piping cylinder (see Chapter 6, Support Plate and Plena for description) load transmission is then from the shield support plate to the piping cylinder plenum closure ring and thence into the reactor core load path.

The peripheral shield is supported by the forward radial flange of the piping cylinder.

7.1.1.2 Central Shield

A. BATH Module

The central shield is made up of hexagonal cross section BATH modules. BATH is an extruded material consisting of a boron carbide, aluminum and titanium hydride mixture. The across flats dimension of the module is approximately two inches and the length is 11.1 inches. In the peripheral region of the central shield, irregular modules required to form the circumference are cut from the regular hexagonal shaped modules.

Coolant channels are provided by grooving 3 faces of each module and drilling 6 axial holes through the module. Assembly of the modules to form the central shield by locating grooved faces against ungrooved faces effectively provides flow channels on all faces. Modules are arranged in arrays of seven. The central module is located by a stud through the cover plate, lead cluster, BATH module and into the support plate.

The six surrounding modules are pinned to the support plate. Close tolerances on hexagonal envelope and pin hole locations minimize gaps between adjacent modules.

B. Lead Cluster

The lead cluster, 1.3 inches thick, is shaped to cover a seven BATH module array. The lead cluster is retained by a stud which passes through the cover plate, lead cluster, central BATH module of the array and into the support Plate.

Flow channels in the lead align with those in the BATH modules. These flow channels are sized to compensate for the difference in CTE between the lead and BATH material.

7.1.1.3 Peripheral Shield

A. BATH Peripheral Module

The peripheral shield BATH modules are rectangular shapes (sections of rings). Four circumferential rows of modules make up the peripheral shield. Each module is grooved on either 2 or 3 faces, depending upon its location in the shield. Modules on the inner most row of the peripheral shield are also provided with axial coolant channels. Assembly of modules is such that coolant channels are provided at all module faces. Special shaped modules surround the propellant flow and bypass feed pipes.

B. Lead Peripheral Sector

Eighteen lead sectors, 1.3 inches thick, cover the BATH modules circumferentially between the control drum drive shaft penetrations and radially from the feed and bypass pipes to the support ring. Lead filler blocks cover the outer row of BATH modules between the feed and bypass pipes and piping cylinder.

7.1.2 Contents of Chapter

The following items are contained in this chapter:

- a. Axial Pressure Load across the Central Shield, Table 7-1
- b. Axial Pressure Load across the Peripheral Shield, Table 7-2

The analyses were conducted for static, flight steady state and transient reactor operating conditions for the internal shield and associated hardware, for both the composite and graphite cores.

Uncertainty analyses were conducted for each component for certain select operational modes. The structural uncertainty is consistent with the thermal uncertainty analysis as documented in Data Item S-031.

7.2 SUMMARY OF RESULTS AND CONCLUSIONS

Data were reviewed to determine the operating mode giving the largest value of pressure load across the shields. Figure 7-1 diagrams the pressure loads across the central and peripheral shields. Loads result from the flow induced pressure drop across each shield.

7.2.1 Composite Core

7.2.1.1 Steady State Operation

In order of decreasing pressure load across the shields the following list applies:

A. Central Shield

- 1. Growth mode, EOL then SOL
- 2. Rated Power, EOL then SOL
- 3. 80% Power, single TPA, EOL then SOL
- 4. 65% Throttle, EOL then SOL
- 5. 65% Throttle, single TPA, EOL then SOL

B. Peripheral Shield

1. Growth mode, EOL then SOL
2. Rated Power, EOL then SOL
3. 65% Throttle, EOL then SOL
4. 80% Power single TPA, EOL then SOL
5. 65% Throttle single TPA, EOL then SOL

Refer to Tables 7-1 and 7-2 for loads.

7.2.1.2 Transient Operation

Figures 7-2 through 7-7 show the transient response of both shields to their respective pressure loads. At no time during the transient do the loads surpass the value at steady state. All figures show the same characteristic curvature and peaks as Figures 2-10 and 2-11.

7.2.2 Graphite Core

7.2.2.1 Steady State Analyses

The graphite core reactor results in slightly larger shield pressure loads than the composite core. In addition, the relative ranking of operational modes is slightly different. Refer to Tables 7-1 and 7-2 for data.

A. Central Shield

1. Growth mode, EOL then SOL
2. Rated Power, EOL then SOL
3. 80% Power, single TPA, EOL and SOL
4. 65% Throttle , EOL
5. 65% Throttle, single TPA, EOL
6. 65% Throttle, SOL
7. 65% Throttle, single TPA, SOL

B. Peripheral Shield

1. Growth mode, EOL then SOL
2. Rated Power, EOL then SOL
3. 65% Throttle, EOL then SOL
4. 80% Power, single TPA, EOL then SOL
5. 65% Throttle, single TPA, EOL then SOL

7.2.2.2 Transient Operation

Figures 7-8 through 7-13 record the transient startup and shutdown response of both shields to pressure loading for the graphite core. Only the peripheral shield load for the GSDS case exceeds the value at steady state.

7.3 APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION

7.3.1 Specification Identification

The specification document governing the Internal Shield is EC-677562, July 16, 1970.

7.3.2 Applicable Requirements

The E-105 document lists the applicable Internal Shield requirements.

7.4 METHOD OF ANALYSIS (DESIGN PRACTICES)

7.4.1 Analytical Procedures

Refer to Section 2.4.1.

7.4.2 Analytical Models

7.4.2.1 Thermal Model, Description

Refer to Section 2.4.2.1.

7.4.2.2 Structural Model, Description

The pressure loads on the shields are due to the fluid pressure drops across each shield and their associated areas. The exact model appears in the RATS code.

7.4.2.3 Statistical Model, Description

Refer to Section 2.4.2.3.

7.4.3 Maturity of Input Data

Refer to Section 2.4.3.

7.4.4 Validity of Analysis

Refer to Section 2.4.4.

7.5 RESULTS OF ANALYSIS AND INTERPRETATION

7.5.1 Composite Core

7.5.1.1 Handling and Shipping

Handling and shipping equipment and procedures are designed so that the loads transmitted to the NSS during these non-operative phases are less than those encountered during vehicle boost and reactor operation.

7.5.1.2 Ground Testing

Ground test data are required for reactor testing in two test cells.

A. Test Cell "C"

This item is not required for PDR.

B. ETS-1 Test Stand

This item is not required for PDR.

7.5.1.3 Launch and Boost

The launch and boost loads imposed on the NSS result from non-operative vehicle launch conditions during maximum dynamic pressure and booster engine cut-off (BECO), are given below.

Reference 25 documents the inertial loads encountered during the maximum dynamic pressure and BECO phases, for the component weights given in Reference 26.

<u>Phase</u>	<u>Nominal Weight</u>	<u>Axial G Load</u>	<u>Inertial Load</u>
Max Q	3550 lb.	5.2	17420 lb.
T + 160 seconds			
BECO	3350 lb.	0.0	0.0 lb.
T + 165 seconds			

7.5.1.4 Startup - High Impulse

Transient data are presented in Figures 7-2 through 7-7.

7.5.1.5 Flight Steady State

Steady state data are presented in Tables 7-1 through 7-2.

7.5.1.6 Shutdown - High Impulse

Data are shown in Figures 7-2 through 7-7.

7.5.1.7 Space Non-Operation

This item is not required for PDR.

7.5.2 Graphite Core

7.5.2.1 Handling and Shipping

Refer to Section 7.5.1.1.

7.5.2.2 Ground Testing

Refer to Section 7.5.1.2.

7.5.2.3 Launch and Boost

Refer to Section 7.5.1.3.

7.5.2.4 Startup - High Impulse

Transient startup data are presented in Figures 7-8 through 7-13.

7.5.2.5 Flight Steady State

Steady state data are found in Tables 7-1 through 7-2.

7.5.2.6. Shutdown - High Impulse

Data are shown in Figures 7-8 through 7-13.

7.5.2.7 Space Non-Operation

Refer to Section 7.5.1.7.

7.6 REFERENCES

Refer to Section 2.6.

Figure 7-1. Internal Shields Pressure Load Diagram.

TABLE 7-1
AXIAL PRESSURE LOAD ACROSS CENTRAL SHIELD - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	12571	464	13991	11151
	EOL	12745	470	14186	11304
65% Throttle	SOL	9598			
	EOL	9663			
80% Power Single TPA	SOL	10895	415	12167	9623
	EOL	11007	419	12292	9722
65% Throttle Single TPA	SOL	9590	---	-----	-----
	EOL	9657	---	-----	-----
Growth Mode Tc = 4500°R	SOL	12847	---	-----	-----
	EOL	12980	---	-----	-----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	13078	---	-----	932 10/22/70
	EOL	13239	---	-----	902 10/23/70
65% Throttle	SOL	9967	---	-----	929 10/26/70
	EOL	10024	---	-----	829 10/27/70
80% Power Single TPA	SOL	11278	---	-----	816 11/19/70
	EOL	11409	---	-----	888 11/20/70
65% Throttle Single TPA	SOL	9954	---	-----	681 11/25/70
	EOL	10019	---	-----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	13927	---	-----	821 11/30/70
	EOL	13500	---	-----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 7-2
AXIAL PRESSURE LOAD ACROSS PERIPHERAL SHIELD - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-10294.	453	-11683	-8905
	EOL	-10462.	460	-11873	-9051
65% Throttle	SOL	-8280			
	EOL	-8351			
80% Power Single TPA	SOL	-6954	314	-7916	-5992
	EOL	-7058	319	-8034	-6082
65% Throttle Single TPA	SOL	-6649	---	----	-----
	EOL	-6711	---	----	-----
Growth Mode T _c = 4500°R	SOL	-10583	---	----	-----
	EOL	-10732	---	----	-----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-10786	---	----	932 10/22/70
	EOL	-10916	---	----	902 10/23/70
65% Throttle	SOL	-8623.	---	----	929 10/26/70
	EOL	-8696.	---	----	829 10/27/70
80% Power Single TPA	SOL	-7309.	---	----	816 11/19/70
	EOL	-7424.	---	----	888 11/20/70
65% Throttle Single TPA	SOL	-6952.	---	----	681 11/25/70
	EOL	-7031.	---	----	820 11/30/70
Growth Mode T _c = 4500°R	SOL	-11066	---	----	821 11/30/70
	EOL	-11274	---	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 7-2. Axial Pressure Load Across Central Shield Versus Time, CSUS

Figure 7-3. Axial Pressure Load Across Central Shield Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 7-4. Axial Pressure Load Across Central Shield Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 7-5. Axial Pressure Load Across Peripheral Shield Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 7-6. Axial Pressure Load Across Peripheral Shield Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 7-7. Axial Pressure Load Across Peripheral Shield Versus Time, CSDSE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 7-8. Axial Pressure Load Across Central Shield Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 7-9. Axial Pressure Load Across Central Shield Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 7-10. Axial Pressure Load Across Central Shield Versus Time, GSDE

Figure 7-11. Axial Pressure Load Across Peripheral Shield Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 7-12. Axial Pressure Load Across Peripheral Shield Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 7-13. Axial Pressure Load Across Peripheral Shield Versus Time, GSDE

8.0 REFLECTOR ASSEMBLY

8.1 INTRODUCTION

The primary function of the Reflector Assembly (RA) is to provide a means of controlling the reactivity of the Nuclear Reactor. The RA must also be structurally adequate to transmit loads imposed upon it by the other components within the pressure vessel as well as the fluid pressure differentials to which it is exposed.

8.1.1 Description of Reflector Assembly

The Reflector Assembly consists of a hollow right circular cylinder which encompasses the core from its forward to aft surface. The basic load-bearing member is an aluminum support structure to which are attached beryllium segments required to fulfill the primary function of neutron reflection. The reactivity control function is satisfied by 18 control drums which are mounted within the reflector and rotate on bearings mounted on each end of the reflector. Rotation of the drums changes the position of the control plates to vary the reactivity.

8.1.1.1 Structure

The primary support structure is the aluminum structural cylinder which is utilized to transmit the NSS axial and radial loads to the interfacing nozzle flange and ultimately to the aft pressure vessel flange. Additionally the structure must withstand the radial fluid pressure drop and support the reflector beryllium segments and control drums.

8.1.1.2 Forward Extension Ring and Aft Support Ring

The forward extension ring is an extension of the aluminum structural cylinder which mates with the core support plate at its forward surface. The radial flange of the ring supports the axial and radial load developed by the 18 control drums. The outer most axial cylindrical portion of the forward support ring serves the function of a coolant flow restrictor for the pressure vessel coolant flow passage.

The aft support ring located at the aft end of the aluminum structure positions the aft end of the control drums and the reflector baffle can.

8.1.1.3 Standoff, Pad and Clamp Ring

A set of 18 standoffs are located at the aft end of the reflector assembly to provide an axial loading capability to force the aluminum structure - nozzle interface together. The load is transmitted from the standoffs into the pads which are bolted to the pressure vessel interior. The standoffs are adjusted for proper preload after installation of the nozzle at final assembly. A redundant feature to assure closure of the aluminum structure - nozzle interface is provided by the clamp ring. The forward lip of the nozzle is clamped to the aft end of the aluminum structure by the clamp ring and its bolts.

8.1.1.4 Locating Cylinder

The locating cylinder is sandwiched between the pads and the forward face of the aft pressure vessel flange. The forward rim of the cylinder mates with a circumferential groove near the outer diameter of the clamp ring. The cylinder centers the NSS within the pressure vessel prior to insertion of the nozzle and supports the NSS during assembly.

8.1.1.5 Reflector Segments

Beryllium segments, required to provide the necessary nuclear characteristics for neutron reflection, are attached to the aluminum structure. Small segments of beryllium are utilized and are attached by the lateral support spring capsules; hence the beryllium is not used as a part of the structural support system of the reflector assembly. The beryllium segments consist of inner and outer segments which interface approximately at the control drum centerline. Division into inner and outer segments is required to facilitate operation within acceptable limits established by thermal - structural considerations.

8.1.1.6 Control Drums

Eighteen control drums are located within the beryllium portion of the reflector assembly. They are supported by bearings located in the forward extension ring and aft support rings. The cylindrical beryllium drums have copper boron composite control vanes mounted within a recess at the outer diameter of the beryllium. The control drum is encased within a thin wall aluminum structure which is welded to aluminum bearing shafts

located at each end of the control drum. Axial holes through the beryllium cylinder and a channel around the control vane provide for adequate removal of heat from the control drum assembly.

8.1.1.7 Reflector Baffle Can and Control Drum Bore Liner

The diameter of the reflector is essentially defined by the outer surface of the beryllium segments mounted upon the aluminum structural cylinder. The complete reflector assembly is surrounded by a thin aluminum cylinder which provides a circumferential barrier between the pressure vessel and the reflector assembly to eliminate radial flow of the fluid. Tubular control drum bore liners are located between the forward and aft bearing support rings to line the control drum cavities and separate the drums from the beryllium segments. This directs the coolant flow through drums and segments to provide more efficient utilization of the coolant fluid.

8.1.1.8 Seal Segments and Insulation Segment*

8.1.1.9 Lateral Support Spring, Plunger, Capsule Assembly*

* The Lateral Support System is a Trade Study and is discussed in S-054 TS 782, Lateral Support.

8.1.2 Contents of Chapter

The following items are contained in this chapter:

a. Axial load, Top of the Reflector barrel	Table 8-1
b. Radial Force, Top of the Reflector barrel	Table 8-2
c. Axial Displacement, Top of Reflector barrel	Table 8-3
d. Radial Displacement, Top of Reflector barrel	Table 8-4
e. Tangential Moment, Top of Reflector barrel	Table 8-5
f. Axial nozzle load	Table 8-6
g. Axial displacement, Bottom of Reflector barrel	Table 8-7
h. Axial standoff load	Table 8-8

The analyses were conducted for static, flight steady state and transient reactor operating conditions for the reflector assembly and associated hardware, for both the composite and graphite cores.

Uncertainty analyses were conducted for each component for certain select operational modes. The structural uncertainty analysis is consistent with the thermal uncertainty analysis as documented in Data Item S-031.

8.2 SUMMARY OF RESULTS AND CONCLUSIONS

Data are reviewed to determine the operating mode giving the largest magnitude of load, moment or displacement. Figures 8-1 and 8-2 diagram the loads moments and displacements on the forward end of the reflector support barrel, nozzle flange and standoff. The moments and displacements at the top of the reflector barrel are a function of the relative mechanical and thermal displacements of the support plate and reflector support structures. The reflector barrel axial load is a function of the pressure drops across the shields, core, support plate and dome.

The nozzle load includes the load to the top of the reflector barrel plus the influence of the reflector pressure drop and standoff load. The nozzle displacement is a function of its load and thermal growth.

The standoff load is a function of some initial preload and the relative mechanical and thermal displacements between it and the nozzle flange. The standoff is initially preloaded to 11.6 times the NSS weight, Reference 26.

8.2.1 Composite Core

8.2.1.1 Steady State Operation

For items a, b, e, and f in Section 8.1.2 the operating modes in decreasing order of severity are:

1. 80% Power, Single TPA, SOL, EOL
2. Rated Power, SOL, EOL
3. Growth Mode SOL, EOL
4. 65% Throttle, Single TPA, SOL, EOL
5. 65% Throttle, SOL, EOL

For items c, d, g, and h in Section 8.1.2 no consistent ordering can be assigned. Refer to Tables 8-1 through 8-8 for the actual data.

8.2.1.2 Transient Operation

Figures 8-3 through 8-26 show the transient response of each of the above items. The characteristic curvature and peaks apparent in Figures 2-10 and 2-11 also are evident.

Note Figure 8-14 (Radial Displacement - Top of Reflector Barrel). During shutdown, for both SOL and EOL, the displacement radially inward increases above nominal steady state conditions. This is due to the cooling effect on the support plate during shutdown.

Figures 8-21, 8-22 and 8-23 (Axial Standoff Load) also show higher transient loads than during the rated steady state condition.

The Axial Displacement at the bottom of the Reflector Barrel show similar larger values during the startup ramp, Figures 8-24 and 8-25.

8.2.2 Graphite Core

8.2.2.1 Steady State Operation

Although the graphite core data (Tables 8-1 through 8-8) show a smaller magnitude for a given item than the composite core, the same relative severity ranking applies as in Section 8.2.1.1.

8.2.2.2 Transient Operation

Figures 8-27 through 8-50 show the transient rated response of each item in Section 8.1.2. The same characteristic curvature and peaks associated with Figures 2-10 and 2-11 are evident.

Note Figures 8-37 and 8-38 (Radial Displacement- Top of Reflector Barrel). During shutdown, for both SOL and EOL, the displacement radially inward increases above nominal steady state conditions. This is due to the cooling effect on the support plate during shutdown.

Figures 8-45, 8-46 and 8-47 (Axial Standoff Load) also show higher transient loads than during the rated steady state condition.

The axial displacement at the bottom of the Reflector Barrel shows a similar larger value during the startup SOL and EOL, ramp, Figure 8-48.

8.3 APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION

8.3.1 Specification Identification

The specification document governing the Reflector Assembly is EC-677559, July 28, 1970.

8.3.2 Applicable Requirements

The E-105 document lists the applicable Reflector Assembly requirements.

8.4 METHOD OF ANALYSIS (DESIGN PRACTICES)

8.4.1 Analytical Procedures

Refer to Section 2.4.1.

8.4.2 Analytical Models

8.4.2.1 Thermal Model, Description

Refer to Section 2.4.2.1.

8.4.2.2 Structural Model, Description

The detailed structural models for the Reflector Assembly analysis are contained in the RATS code. Section 8.2 outlines the thermal and hydraulic parameters influencing each calculation.

8.4.2.3 Statistical Model, Description

Refer to Section 2.4.2.3.

8.4.3 Maturity of Input Data

Refer to Section 2.4.3.

8.4.4 Validity of Analysis

Refer to Section 2.4.4.

8.5 RESULTS OF ANALYSIS AND INTERPRETATION

8.5.1 Composite Core

8.5.1.1 Handling and Shipping

Handling and shipping procedures and equipment are designed so that the loads transmitted to the NSS during these non-operative phases are less than those encountered during vehicle boost and reactor operation.

8.5.1.2 Ground Testing

Ground test data are required for reactor testing in two test cells.

A. Test Cell "C"

This item is not required for PDR.

B. ETS-1 Test Stand

This item is not required for PDR.

8.5.1.3 Launch and Boost

The launch and boost loads imposed on the NSS result from non-operative vehicle launch conditions during maximum dynamic pressure and booster engine cut-off (BECO), and are given below.

Reference 25 documents the inertial loads encountered during the maximum dynamic pressure and BECO phases, for the component weights given in Reference 26.

<u>Phase</u>	<u>Nominal Weight</u>	<u>Axial G Load</u>	<u>Inertial Load</u>
Max Q T + 160 seconds	3813 lb.	5.2	19827 lb.
BECO T + 165 seconds	3813 lb.	0.0	0.0 lb.

8.5.1.4 Startup - High Impulse

Transient data are presented in Figures 8-3 through 8-26.

8.5.1.5 Flight Steady State

Steady state data are presented in Tables 8-1 through 8-8.

8.5.1.6 Shutdown - High Impulse

Data are shown in Figures 8-3 through 8-26.

8.5.1.7 Space Non-Operation

This item not required for PDR.

8.5.2 Graphite Core

8.5.2.1 Handling and Shipping

Refer to Section 8.5.1.1.

8.5.2.2 Ground Testing

Refer to Section 8.5.1.2.

8.5.2.3 Launch and Boost

Refer to Section 8.5.1.3.

8.5.2.4 Startup - High Impulse

Transient startup data are presented in Figures 8-27 through 8-50.

8.5.2.5 Flight Steady State

Steady state data are found in Tables 8-1 through 8-8.

8.5.2.6 Shutdown - High Impulse

Data are shown in Figures 8-27 through 8-50.

8.5.2.7 Space Non-Operation

Refer to Section 8.5.1.7.

8.6 REFERENCES

Refer to Section 2.6.

Figure 8-1. Top of Reflector Barrel Loads, Moments And Displacements Diagram.

Figure 8-2. Nozzle, Standoff, And Bottom Of Reflector Barrel Loads, Moments And Displacements Diagram.

TABLE 8-1
AXIAL LOAD, TOP OF REFLECTOR BARREL - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	768540	7420	791240	745840
	EOL	764390	7379	786990	741790
65% Throttle	SOL	436380	4383	449780	422980
	EOL	433420	4354	446720	420120
80% Power Single TPA	SOL	944500	8569	970700	918300
	EOL	938800	8517	964800	912800
65% Throttle Single TPA	SOL	659970	----	----	----
	EOL	655950	----	----	----
Growth Mode Tc = 4500°R	SOL	749410	----	----	----
	EOL	744630	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	754770	----	----	932 10/22/70
	EOL	750550	----	----	902 10/23/70
65% Throttle	SOL	431040	----	----	929 10/26/70
	EOL	428000	----	----	829 10/27/70
80% Power Single TPA	SOL	924330	----	----	816 11/19/70
	EOL	918490	----	----	888 11/20/70
65% Throttle Single TPA	SOL	647170	----	----	681 11/25/70
	EOL	642610	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	736150	----	----	821 11/30/70
	EOL	731000	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 8-2
RADIAL FORCE, TOP OF REFLECTOR BARREL - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-0.726	.0211	-.791	-.661
	EOL	-.716	.0208	-.780	-.652
65% Throttle	SOL	-.289	.0282	-.376	-.202
	EOL	-.266	.0260	-.346	-.186
80% Power Single TPA	SOL	-1.029	.0244	-1.104	-.954
	EOL	-1.015	.0241	-1.089	-.941
65% Throttle Single TPA	SOL	-.623	----	----	----
	EOL	-.599	----	----	----
Growth Mode Tc = 4500°R	SOL	-.671	----	----	----
	EOL	-.666	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-.683	----	----	932 10/22/70
	EOL	-.679	----	----	902 10/23/70
65% Throttle	SOL	-.263	----	----	929 10/26/70
	EOL	-.246	----	----	829 10/27/70
80% Power Single TPA	SOL	-.987	----	----	816 11/19/70
	EOL	-.974	----	----	888 11/20/70
65% Throttle Single TPA	SOL	-.592	----	----	681 11/25/70
	EOL	-.570	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-.650	----	----	821 11/30/70
	EOL	-.626	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 8-3
AXIAL DISPLACEMENT, TOP OF REFLECTOR BARREL - in.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	0.1612	.0082	.1863	.1361
	EOL	0.1571	.0079	.1813	.1329
65% Throttle	SOL	0.1288	.0097	.1584	.0992
	EOL	0.1181	.0089	.14545	.09091
80% Power : Single TPA	SOL	0.1490	.0081	.1738	.1242
	EOL	0.1433	.0077	.1669	.1197
65% Throttle Single TPA	SOL	0.1321	----	----	----
	EOL	0.1224	----	----	----
Growth Mode Tc = 4500°R	SOL	0.1495	----	----	----
	EOL	0.1444	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	.1553	----	----	932 10/22/70
	EOL	.1507	----	----	902 10/23/70
65% Throttle	SOL	.1213	----	----	929 10/26/70
	EOL	.1084	----	----	829 10/27/70
80% Power Single TPA	SOL	.1492	----	----	816 11/19/70
	EOL	.1359	----	----	888 11/20/70
65% Throttle Single TPA	SOL	.1250	----	----	681 11/25/70
	EOL	.1131	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	.1432	----	----	821 11/30/70
	EOL	.1371	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 8-4
RADIAL DISPLACEMENT, TOP OF REFLECTOR BARREL - in.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-.0250	.0032	-.0348	-.0152
	EOL	-.0268	.0034	-.0373	-.0163
65% Throttle	SOL	-0.0249	.0032	-.0346	-.0152
	EOL	-0.0267	.0034	-.0371	-.0163
80% Power Single TPA	SOL	-.0239	.0030	-.0331	-.0147
	EOL	-.0260	.0033	-.0360	-.0160
65% Throttle Single TPA	SOL	-.0239	-----	-----	-----
	EOL	-.0261	-----	-----	-----
Growth Mode Tc = 4500°R	SOL	-.0223	-----	-----	-----
	EOL	-.0245	-----	-----	-----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-.0221	-----	-----	932 10/22/70
	EOL	-.0245	-----	-----	902 10/23/70
65% Throttle	SOL	-.0224	-----	-----	929 10/26/70
	EOL	-.0245	-----	-----	829 10/27/70
80% Power Single TPA	SOL	-.0213	-----	-----	816 11/19/70
	EOL	-.0237	-----	-----	888 11/20/70
65% Throttle Single TPA	SOL	-.0216	-----	-----	681 11/25/70
	EOL	-.0239	-----	-----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	-.0193	-----	-----	821 11/30/70
	EOL	-.0214	-----	-----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 8-5
TANGENTIAL MOMENT, TOP OF REFLECTOR BARREL - in. - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-93	2.46	-101	-86
	EOL	-92	2.43	-99	-85
65% Throttle	SOL	-39	3.33	-49	-28
	EOL	-35	3.32	-46	-25
80% Power	SOL	-131	2.89	-140	-122
	Single TPA	-129	2.85	-138	-120
65% Throttle	SOL	-80	---	---	--
	Single TPA	-77	---	---	--
Growth Mode Tc = 4500°R	SOL	-86	---	---	--
	EOL	-85	---	---	--
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	-88	---	---	932 10/22/70
	EOL	-87	---	---	902 10/23/70
65% Throttle	SOL	-35	---	---	929 10/26/70
	EOL	-33	---	---	829 10/27/70
80% Power	SOL	-126	---	---	816 11/19/70
	Single TPA	-124	---	---	888 11/20/70
65% Throttle	SOL	-76	---	---	681 11/25/70
	Single TPA	-73	---	---	820 11/30/70
Growth Mode	SOL	-83	---	---	821 11/30/70
	Tc = 4500°R	-80	---	---	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 8-6
AXIAL NOZZLE LOAD - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	1005940	11405	1040840	971040
	EOL	1006990	11416	1041990	971990
65% Throttle	SOL	702160	9184	730160	674160
	EOL	707620	9256	735920	679320
80% Power Single TPA	SOL	1192940	11773	1228940	1156940
	EOL	1192120	11764	1228120	1156120
65% Throttle Single TPA	SOL	923560	---	---	---
	EOL	926660	---	---	---
Growth Mode Tc = 4500°R	SOL	996880	---	---	---
	EOL	997930	---	---	---
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	992020	---	---	932 10/22/70
	EOL	992340	---	---	902 10/23/70
65% Throttle	SOL	696750	---	---	929 10/26/70
	EOL	702890	---	---	829 10/27/70
80% Power Single TPA	SOL	1171990	---	---	816 11/19/70
	EOL	1171890	---	---	888 11/20/70
65% Throttle Single TPA	SOL	910190	---	---	681 11/25/70
	EOL	913400	---	---	820 11/30/70
Growth Mode Tc = 4500°R	SOL	982250	---	---	821 11/30/70
	EOL	984450	---	---	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 8-7
AXIAL DISPLACEMENT, BOTTOM OF REFLECTOR BARREL - in.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	0.01194	.0005	.01347	.01041
	EOL	0.01178	.0005	.01331	.01025
65% Throttle	SOL	0.01038	.0005	.01191	.00885
	EOL	0.00998	.0005	.01151	.00845
80% Power Single TPA	SOL	0.01171	.0005	.01324	.01018
	EOL	0.0115	.0005	.01303	.00997
65% Throttle Single TPA	SOL	0.01076	---	---	---
	EOL	0.01039	---	---	---
Growth Mode Tc = 4500°R	SOL	0.01149	---	---	---
	EOL	0.01131	---	---	---
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	.01183	---	---	932 10/22/70
	EOL	.01169	---	---	902 10/23/70
65% Throttle	SOL	.01028	---	---	929 10/26/70
	EOL	.00983	---	---	829 10/27/70
80% Power Single TPA	SOL	.01163	---	---	816 11/19/70
	EOL	.01138	---	---	888 11/20/70
65% Throttle Single TPA	SOL	.01067	---	---	681 11/25/70
	EOL	.01027	---	---	820 11/30/70
Growth Mode Tc = 4500°R	SOL	.01141	---	---	821 11/30/70
	EOL	.01120	---	---	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 8-8
AXIAL STANDOFF LOAD - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	253160	7719	276760	229560
	EOL	255560	7792	279360	231760
65% Throttle	SOL	272770	7963	297170	248370
	EOL	278330	8126	303130	253530
80% Power Single TPA	SOL	251820	7718	275420	228220
	EOL	254670	7805	278570	230770
65% Throttle Single TPA	SOL	265520	---	---	---
	EOL	270560	---	---	---
Growth Mode Tc = 4500°R	SOL	263200	---	---	---
	EOL	265950	---	---	---
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	252370	---	---	932 10/22/70
	EOL	254190	---	---	902 10/23/70
65% Throttle	SOL	271950	---	---	929 10/26/70
	EOL	278100	---	---	829 10/27/70
80% Power Single TPA	SOL	250780	---	---	816 11/19/70
	EOL	254280	---	---	888 11/20/70
65% Throttle Single TPA	SOL	264640	---	---	681 11/25/70
	EOL	270080	---	---	820 11/30/70
Growth Mode Tc = 4500°R	SOL	261660	---	---	821 11/30/70
	EOL	265020	---	---	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

COMPOSITE CORE - STARTUP TRANSIENT AT START OF LIFE

Figure 8-3. Radial Force, Top of Reflector Barrel Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END OF LIFE

Figure 8-4. Radial Force, Top of Reflector Barrel Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 8-5. Radial Force, Top of Reflector Barrel Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START OF LIFE

Figure 8-6. Axial Load, Top of Reflector Barrel Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END OF LIFE

Figure 8-7. Axial Load, Top of Reflector Barrel Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 8-8. Axial Load, Top of Reflector Barrel Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START OF LIFE

Figure 8-9. Tangential Moment, Top of Reflector Barrel Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END OF LIFE

Figure 8-10. Tangential Moment, Top of Reflector Barrel Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 8-11. Tangential Moment, Top of Reflector Barrel Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START OF LIFE

Figure 8-12. Radial Displacement, Top of Reflector Barrel Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END OF LIFE

Figure 8-13. Radial Displacement, Top of Reflector Barrel Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 8-14. Radial Displacement, Top of Reflector Barrel Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START OF LIFE

Figure 8-15. Axial Displacement, Top of Reflector Barrel Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END OF LIFE

Figure 8-16. Axial Displacement, Top of Reflector Barrel Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 8-17. Axial Displacement, Top of Reflector Barrel Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START OF LIFE

Figure 8-18. Axial Nozzle Load Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END OF LIFE

Figure 8-19. Axial Nozzle Load Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 8-20. Axial Nozzle Load Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START OF LIFE

Figure 8-21. Axial Standoff Load Versus Time, CSUS

Figure 8-22. Axial Standoff Load Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 8-23. Axial Standoff Load Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START OF LIFE

Figure 8-24. Axial Displacement, Bottom of Reflector Barrel Versus Time, CSUS

Figure 8-25. Axial Displacement, Bottom of Reflector Barrel Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 8-26. Axial Displacement, Bottom of Reflector Barrel Versus Time, CSDSE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 8-27. Radial Force, Top of Reflector Barrel Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 8-28. Radial Force, Top of Reflector Barrel Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 8-29. Radial Force, Top of Reflector Barrel Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 8-30. Axial Load, Top of Reflector Barrel Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 8-32. Axial Load, Top of Reflector Barrel Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 8-33. Tangential Moment, Top of Reflector Barrel, Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 8-34. Tangential Moment, Top of Reflector Barrel Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 8-35. Tangential Moment, Top of Reflector Barrel Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 8-36. Radial Displacement, Top of Reflector Barrel Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 8-37. Radial Displacement, Top of Reflector Barrel Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 8-38. Radial Displacement, Top of Reflector Barrel Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 8-39. Axial Displacement, Top of Reflector Barrel Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 8-40. Axial Displacement, Top of Reflector Barrel Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 8-41. Axial Displacement, Top of Reflector Barrel Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 8-42. Axial Nozzle Load Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 8-43. Axial Nozzle Load Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 8-44. Axial Nozzle Load Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 8-45. Axial Standoff Load Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 8-46. Axial Standoff Load Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 8-47. Axial Standoff Load Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 8-48. Axial Displacement, Bottom of Reflector Barrel Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 8-49. Axial Displacement, Bottom of Reflector Barrel Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END OF LIFE

Figure 8-50. Axial Displacement, Bottom of Reflector Barrel Versus Time, GSDE

9.0 CONTROL DRUM DRIVE ASSEMBLY

9.1 INTRODUCTION

The primary function of the Control Drum Drive Assembly is to supply torque to a control drum imparting drum rotation to a specified setting.

9.1.1 Description of Control Drum Drive Assembly

The CDDA consists of eighteen (18) individual subassemblies, each consisting of an electrical stepper motor actuator mechanism, a controller and an actuator malfunction override device.

9.1.1.1 Actuator Housing

The housing serves as both the frame of the actuator, mounting all of the component subassemblies, and as a pressure vessel, capable of containing the system coolant pressure. The housing also accomplishes the electrical interfacing function with the controller, by means of an electrical connector, and the mechanical mounting interfacing function with the pressure vessel by means of three bolts and indexing dowels.

9.1.1.2 Motor

The motor is of the type generally referred to as a "stepper" since its rotor motion is usually incremental, responding to discrete pulse excitation of the stator, and would only be continuous when slewing at synchronous speed. The rotor has twelve radially salient poles of permanent magnet material, alternately polarized. The substantial detent torque, deriving from the employment of a permanent magnet rather than a variable reluctance type motor, serves to lock the drum in place when the motor is deenergized, thereby realizing power economies during quiescent periods of operation. This locking torque negates the need for any electromechanical safety lock in the actuator to insure that the drums are constrained to the shutdown position and, additionally, makes possible a time period during which the reactor may be maintained at power while controller malfunctions are diagnosed and corrected.

The motor stator has 24 poles, which establish a step angle of 15° , with a two phase power winding. Auxiliary coils wound on the stator act in conjunction with the rotor permanent magnets to supply step response feedback signals.

9.1.1.3 Transmission

A two stage epicyclic transmission carrying motor torque to the actuator output shaft end, with a ratio of 150/1, reduces the incremental motion of the drum to one tenth degree. This transmission is comprised of two internal ring gears and a duplex pinion. The pinion gears are carried by two bearings on an eccentric extension of the motor shaft. These pinions mesh respectively with a stationary internal gear piloted in the motor housing bore, and with a slightly smaller internal gear carried by the output shaft.

9.1.1.4 Potentiometer

Although the stepper motor and transmission which comprise the drive elements of the actuator have the capability and are intended to accurately position the drum under conditions of widely varying load and environmental conditions without dependence on closed loop position feedback, the system is nevertheless augmented by diagnostic position instrumentation. This is provided by two potentiometers monitoring the output shaft. They are electrically independent by virtue of having separate power supplies. Used in conjunction with a count of the stepper motor pulse feedback, there is thus provided triple redundancy of position information for use in diagnosing and correcting malfunctions.

A single molding incorporates the resistance track, slip ring, wiper protective resistor, and terminal inserts for both potentiometers. Since the actuator working range is restricted to less than 180° , a single working face on this molding is adequate to accommodate both potentiometer elements without necessitating dissimilar geometry. The slip ring and resistance elements are bridged by multiple, adjustable, wiper finger contacts which are attached to but electrically insulated from the output shaft.

9.1.1.5 AMOD Trigger

Adjacent to the potentiometer and at the aft end of the actuator there is a trigger mechanism used to activate the actuator malfunction override device.

The trigger device consists of a magnetic circuit employing both a permanent magnet and an externally excited field coil used respectively to hold and release the hammer. The holding flux derived from the permanent magnet is nulled by a counter flux generated by the field coil during receipt of a triggering current pulse of appropriate

polarity. Excitation circuits commuting to the various actuators shall be interlocked to preclude inadvertant, simultaneous triggering of more than one AMOD. A cup surrounding the trigger hammer permits its convenient recovery during replacement of an actuator.

9.1.1.6 AMOD

The AMOD mechanism utilizes components of the drive shaft to effect economies in system weight and complexity. A helical compression spring, which supplied the AMOD drive energy, is housed inside the drive shaft tube rather than inside the actuator, and thus avoids increasing the pressurized actuator housing envelope.

The drive shaft and actuator mating splines serve also as clutch elements to permit decoupling of a malfunctioned actuator so that the spring energy is expended only in driving the drum to the orifice angle position. The cylindrical ram carrying the male spline is fitted, telescopic fashion, to the drive shaft bore, and is driven axially by the spring into the hollow actuator shaft, when the AMOD is activated. The drive shaft is keyed to follow angular motion of the splined ram by radially projecting cam followers carried by the ram which extend through slots in the drive shaft tube walls. The initial linear motion of the ram is used to impart rotation to the drive shaft and drum by interaction of the cam follower projections with stationary helical cam surfaces. These cam surfaces are comprised to two sets of opposing slope occupying quadrants at either side of the orifice angle.

Reliability was given prime consideration in devising the latch which controls the release of the spring loaded ram. In order to avoid the detrimental frictional effects normally attendant to dry lubricated elements in the handling of relatively large forces, the latch mechanism incorporates only rolling load carrying elements. These are comprised of an array of nine balls. They are distributed into groups of three, each group being confined to one of three equally spaced pockets milled into the drive shaft tube wall. The innermost of the three balls in each group protrudes from the tube wall and engages a circumferential groove in the ram to interfere with its displacement while in the quiescent mode. The drive spring load is diverted through these inboard balls to an adjacent second set resting against a raceway in the ball pocket. The relationship of these two ball sets

is designed so as to absorb most of the spring load in the shaft tube at the raceway contact, with a smaller force component transmitted radially outward to a third outermost ball set. The forces transmitted to these outboard balls are absorbed in tension by an annular target ring having a cylindrical race surface concentric with the shaft. The ball configuration is thus one displaying a condition of unstable equilibrium and could be triggered by a force which need only be large enough to overcome rolling friction except for the supplementary force provided by a latch spring which loads an internal shoulder on the target ring against the outboard balls. This additional spring load protects against inadvertent release by shock and vibration forces.

To release the latch mechanism the target ring is struck by a hammer ring which is spring loaded to overcome the latch spring. The latch ring rolls on the three outboard balls which are thus displaced to free constraint on the main load carrying ball sets. These two inner ball sets roll against each other and against the pocket raceway in a radially outward direction which releases the ram. The balls remain stored in an equilateral array in the ball pocket until such time as the malfunctioned actuator with the trigger hammer is removed for replacement. At such time the AMOD is restored to its quiescent mode by forcing the ram back into the drive shaft. The latch spring and target ring will automatically restore the balls to their latched configuration.

The radiused exterior of the drive shaft in the region of the ball pockets, and the taper on the ram adjacent to the circumferential groove, serve to avoid binding of the target ring and erratic movement of the balls if the ball groups are released sequentially rather than simultaneously, as would occur if the target ring were struck by the hammer in a skewed orientation.

A demonstration model of the latch mechanism has served to confirm its functional feasibility.

The trigger mechanism controlling the release of the latch is housed in the actuator. Since in the quiescent mode, the spring loaded hammer is retained in clearance from the latch target ring, rotational motion is not required of the triggering device. This arrangement permits hard wiring to the actuator connector for the triggering signal and thus avoids the complexities involved in commutating a signal to the rotating

drive shaft. Also, since the triggering mechanism is integral with the actuator, complex procedures are avoided during replacement of a malfunctioned actuator and resetting the AMOD.

9.1.1.7 CDA Controller

The actuator controller utilizes digital techniques to interpret binary coded control signals transmitted from the EPIC for motor stator phase control. The mode of control is primarily open loop in nature, although step detection techniques are utilized to signal completion of a rotor incremental step to the EPIC.

9.1.2 Contents of Chapter

The following items are contained in this chapter :

- a. Axial load from CDA housing to dome pedestal, Table 9-1.
- b. Tensile load on CDA housing bolt, Table 9-2.
- c. Axial torque on CDA housing pedestal, Table 9-3.

The analyses were conducted for static, flight steady state and transient reactor operating conditions for the control drum drive assembly and associated hardware, for both the composite and graphite cores.

Uncertainty analyses were conducted for each component for certain select operational modes. The structural uncertainty analysis is consistent with the thermal uncertainty analysis as documented in Data Item S-031.

9.2 SUMMARY OF RESULTS AND CONCLUSIONS

Data are reviewed to determine the operating mode giving the largest magnitude of load, moment, or displacement. Figure 9-1 diagrams the pressure loads and torques on the CDA housing pedestal and bolts. Loads result from the extension shield outlet pressure acting on the CDA housing closure cap and a control drum arm spring preload.

9.2.1 Composite Core

9.2.1.1 Steady State Operation

For both the CDA housing pedestal and pedestal bolts the 80% Power Single TPA, SOL mode gives the largest nominal axial pressure load. The loads decrease in magnitude in the following order:

- a. 80% Power Single TPA, EOL
- b. Rated Power, SOL then EOL
- c. Growth mode, SOL then EOL
- d. 65% Throttle Single TPA, SOL then EOL
- e. 65% Throttle, SOL then EOL

Refer to Tables 9-1 and 9-2 for pressure loads.

The nominal torque on the CDA pedestal resulting from the valve driving mechanism remains constant for each operating mode. However, the pedestal must be able to withstand a higher torque as a result of some abnormal resistance in the system. This higher value is referred to as the stall torque limit. Refer to Table 9-3 for torque loads.

9.2.1.2 Transient Operation

Figures 9-2 through 9-7 show the transient response of the pedestal housing and bolts to the pressure loads. The figures show the same characteristic curvatures and peaks as figures 2-10 and 2-11. Transient loads are less than steady state loads.

9.2.2 Graphite Core

9.2.2.1 Steady State Operation

The graphite core reactor results in slightly smaller pressure loads to the CDA pedestal and housing bolts. However, the relative operational mode ranking as in Section 9.2.1.1 still applies.

Refer to Tables 9-1 and 9-2 for the nominal pressure loads.

Table 9-3 shows the same nominal and stall torque values as for the composite core.

9.2.2.2 Transient Operation

Figures 9-8 through 9-13 show the transient response of the pedestal housing and bolts to the pressure loads. The figures show the same characteristic curvatures and peaks as Figures 2-10 and 2-11.

9.3 APPLICABLE REQUIREMENTS AND COMPATIBILITY OF STRUCTURAL PERFORMANCE WITH THE NSS SPECIFICATION

9.3.1 Specification Identification

The specification document governing the CDA is EC-677585, July 28, 1970.

9.3.2 Applicable Requirements

The E-105 document lists the applicable CDA requirements.

9.4 METHOD OF ANALYSIS (DESIGN PRACTICES)

9.4.1 Analytical Procedures

Refer to Section 2.4.1.

9.4.2 Analytical Models

9.4.2.1 Thermal Model, Description

Refer to Section 2.4.2.1.

9.4.2.2 Structural Model, Description

The axial pressure load to the CDA housing pedestal is a result of the fluid pressure at the extension shield outlet and a control drum actuator spring preload. The bolt load is divided between three housing bolts which are loaded in the same manner as the pedestal with an additional load from the seal springs.

9.4.2.3 Statistical Model, Description

Refer to Section 2.4.2.3.

9.4.3 Maturity of Input Data

Refer to Section 2.4.3.

9.4.4 Validity of Analysis

Refer to Section 2.4.4.

9.5 RESULTS OF ANALYSIS AND INTERPRETATION

9.5.1 Composite Core

9.5.1.1 Handling and Shipping

Handling and shipping equipment and procedures are designed so that the loads transmitted to the NSS during these non-operative phases are less than those encountered during vehicle boost and reactor operation.

9.5.1.2 Ground Testing

Ground test data is required for reactor testing in two cells.

A. Test Cell "C"

This item is not required for PDR.

B. ETS-1 Test Stand

This item is not required for PDR.

9.5.1.3 Launch and Boost

The launch and boost loads imposed on the NSS result from non-operative vehicle launch conditions during maximum dynamic pressure and booster engine cut-off (BECO), are given below.

Reference 25 documents the inertial loads encountered during the maximum dynamic pressure and BECO phases for the component weights given in Reference 26.

<u>Phase</u>	<u>Nominal Weight</u>	<u>Axial G Load</u>	<u>Inertial Load</u>
Max Q			
T + 160 seconds	321	5.2	1669 lb.
BECO			
T + 165 seconds	321	0.0	0.0 lb.

9.5.1.4 Startup - High Impulse

Transient data are presented in Figures 9-2 through 9-7.

9.5.1.5 Flight Steady State

Steady state data are presented in Tables 9-1 through 9-3.

9.5.1.6 Shutdown - High Impulse

Data are shown in Figures 9-2 through 9-7.

9.5.1.7 Space Non-Operation

This item is not required for PDR.

9.5.2 Graphite Core

9.5.2.1 Handling and Shipping

Refer to Section 9.5.1.1.

9.5.2.2 Ground Testing

Refer to Section 9.5.1.2.

9.5.2.3 Launch and Boost

Refer to Section 9.5.1.3.

9.5.2.4 Startup - High Impulse

Transient startup data are presented in Figures 9-8 through 9-13.

9.5.2.5 Flight Steady State

Steady state data are found in Tables 9-1 through 9-3.

9.5.2.6 Shutdown - High Impulse

Data are shown in Figures 9-8 through 9-13.

9.5.2.7 Space Non-Operation

Refer to Section 9.5.1.7.

9.6 REFERENCES

Refer to Section 2.6.

Figure 9-1. CDA Housing Pedestal And Bolt Load And Moment Diagram.

TABLE 9-1
AXIAL LOAD FROM CDA HOUSING TO DOME PEDESTAL - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	15125	99	15429	14821
	EOL	15097	99	15400	14794
65% Throttle	SOL	9104	70	9407	8801
	EOL	9076	70	9286	8866
80% Power Single TPA	SOL	15807	115	16159	15455
	EOL	15750	115	16102	15398
65% Throttle Single TPA	SOL	11618	----	----	----
	EOL	11575	----	----	----
Growth Mode T _c = 4500°R	SOL	14912	----	----	----
	EOL	14870	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	14997	----	----	932 10/22/70
	EOL	14955	----	----	902 10/23/70
65% Throttle	SOL	9062	----	----	929 10/26/70
	EOL	9034	----	----	829 10/27/70
80% Power Single TPA	SOL	15594	----	----	816 11/19/70
	EOL	15537	----	----	888 11/20/70
65% Throttle Single TPA	SOL	11490	----	----	681 11/25/70
	EOL	11433	----	----	820 11/30/70
Growth Mode T _c = 4500°R	SOL	14784	----	----	821 11/30/70
	EOL	14728	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 9-2
TENSILE LOAD ON CDA HOUSING BOLT - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	6991	61	7178	6804
	EOL	6981	61	7168	6794
65% Throttle	SOL	4984	56	5156	4812
	EOL	4974	56	5145	4803
80% Power Single TPA	SOL	7218	64	7413	7023
	EOL	7199	64	7395	7003
65% Throttle Single TPA	SOL	5822	----	----	----
	EOL	5807	----	----	----
Growth Mode Tc = 4500°R	SOL	6919	----	----	----
	EOL	6905	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	6948	----	----	932 10/22/70
	EOL	6934	----	----	902 10/23/70
65% Throttle	SOL	4970	----	----	929 10/26/70
	EOL	4960	----	----	829 10/27/70
80% Power Single TPA	SOL	7147	----	----	816 11/19/70
	EOL	7128	----	----	888 11/20/70
65% Throttle Single TPA	SOL	5779	----	----	681 11/25/70
	EOL	5760	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	6877	----	----	821 11/30/70
	EOL	6858	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 9-3
AXIAL TORQUE FROM CDA TO DOME PEDESTAL - IN-LB.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power 65% Throttle 80% Power Single TPA 65% Throttle Single TPA Growth Mode Tc = 4500°R	SOL	100 ↓	-	123** ↓	77 ↓
	EOL				
	SOL				
	EOL				
	SOL				
	EOL				
	EOL				
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power 65% Throttle 80% Power Single TPA 65% Throttle Single TPA Growth Mode Tc = 4500°R	SOL	100 ↓	-	123** ↓	77 ↓
	EOL				
	SOL				
	EOL				
	SOL				
	EOL				
	EOL				

* One sided tolerance limits for .99 reliability and .95 confidence ** maximum stall torque 300 in.-lb.

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 9-2. Axial Load From CDA Housing to Dome Pedestal Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 9-3. Axial Load From CDA Housing to Dome Pedestal Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 9-4. Axial Load From CDA Housing to Dome Pedestal Versus Time, CSDSE

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 9-5. Tensile Load on CDA Housing Bolt Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 9-6. Tensile Load on CDA Housing Bolt Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 9-7. Tensile Load on CDA Housing Bolt Versus Time, CSDSE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 9-8. Axial Load from CDA Housing to Dome Pedestal Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 9-9. Axial Load From CDA Housing to Dome Pedestal Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 9-10. Axial Load from CDA Housing to Dome Pedestal Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 9-11. Tensile Load on CDA Housing Bolt Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 9-13. Tensile Load on CDA Housing Bolt Versus Time, GSDE

10.0 STRUCTURAL SUPPORT COOLANT ASSEMBLY

10.1 STRUCTURAL SUPPORT COOLANT VALVE

(Input to be supplied by ANSC Data Item S-039.)

10.2 STRUCTURAL SUPPORT COOLANT VALVE ACTUATOR

10.2.1 Introduction

The primary function of the Structural Support Coolant Valve Actuator is to regulate the Structural Support Flow per cooling and reactivity requirements.

10.2.1.1 Description of SSCVA

A. Actuator Housing

The housing serves as both the frame of the actuator, mounting all of the component subassemblies, and as a pressure vessel, capable of containing the system coolant pressure. The housing also accomplishes the electrical interfacing function with the controller, by means of an electrical connector, and the mechanical mounting interfacing function with the valve housing by means of three bolts and indexing dowels.

B. Motor

The motor is of the type generally referred to as a "stepper" since its rotor motion is usually incremental, responding to discrete pulse excitation of the stator, and would only be continuous when slewing a synchronous speed. The rotor has twelve radially salient poles of permanent magnet material, alternately polarized. The substantial detent torque deriving from the employment of a permanent magnet rather than a variable reluctance type rotor serves to lock the valve in place when the motor is deenergized, thereby realizing power economies during quiescent periods of operation. This locking torque negates the need for electromechanical safety lock in the actuator to insure that the valves are constrained to the shutdown position and, additionally, make possible a time period during which the reactor may be maintained at power while controller malfunctions are diagnosed and corrected.

The motor stator has 24 poles, which establish a step angle of 15° , with a two phase power winding. Auxiliary coils wound on the stator act in conjunction with the rotor permanent magnets to supply step response feedback signals.

C. Transmission

A two stage epicyclic transmission carries motor torque to the actuator output shaft and, with a ratio of 150/1, reduces the incremental motion of the valve to one tenth degree. This transmission is comprised of two internal ring gears and a duplex pinion. The pinion gears are carried by two bearings on an eccentric extension of the motor shaft. These pinions mesh respectively with a stationary internal gear piloted in the motor housing bore and with a slightly smaller internal gear carried by the output shaft.

D. Potentiometer

Although the stepper motor and transmission which comprise the drive elements of the actuator have the capability and are intended to accurately position the valve under conditions of widely varying load and environmental conditions without dependence on closed loop position feedback, the system is nevertheless augmented by diagnostic position instrumentation. This is provided by two potentiometers monitoring the output shaft. They are electrically independent by virtue of having separate power supplies. Used in conjunction with a count of the stepper motor pulse feedback, there is thus provided triple redundancy of position information for use in diagnosing and correcting malfunctions.

A single molding incorporates the resistance track, slip ring, wiper protective resistor and terminal inserts for both potentiometers. Since the actuator working range is restricted to less than 180° , a single working face on this molding is adequate to accommodate both potentiometer elements without necessitating dissimilar geometry. The slip ring and resistance elements are bridged by multiple, adjustable, wiper finger contacts which are attached to, but electrically insulated from, the output shaft.

E. Coupling Shaft

Actuator output torque is carried to the valve through a crown spline coupling shaft. Misalignment of valve and actuator axis of up to one degree are compensated

for in this coupling.

F. SSCVA Controller

The actuator controller utilizes digital techniques to interpret binary coded control signals transmitted from the EPIC for motor stator phase control. The mode of control is primarily open loop in nature, although step detection techniques are utilized to signal completion of a rotor incremental step to the EPIC.

10.2.1.2 Contents of Chapter

The following items are contained in this chapter:

- a. Axial load from SSCVA housing to dome pedestal, Table 10-1
- b. Tensile load on SSCVA housing bolt, Table 10-2
- c. Axial torque on SSCVA housing pedestal, Table 10-3

The analyses were conducted for static, flight steady state and transient reactor operating conditions for the structural support coolant assembly and associated hardware, for both the composite and graphite cores.

Uncertainty analyses were conducted for each component for certain select operational modes. The structural uncertainty analysis is consistent with the thermal uncertainty analysis as documented in Data Item S-031.

10.2.2 Summary of Results and Conclusions

Data are reviewed to determine the operating mode giving the largest magnitude of load, moment or displacement. Figure 10-1 diagrams the pressure loads and torque on the SSCVA housing pedestal and the pedestal bolts. Loads result from the SSCV inlet pressure acting on the pedestal closure cap.

10.2.2.1 Composite Core

A. Steady State Operation

For both the SSCVA housing pedestal and pedestal housing bolts the Rated Power SOL mode gives the largest nominal axial pressure load. These pressure loads decrease in magnitude in the following order:

- a. Growth mode, SOL
- b. Rated, SOL
- c. Growth mode, EOL
- d. 80% Power single TPA, SOL then EOL
- e. 65% Throttle single TPA, SOL then EOL
- f. 65% Throttle, SOL then EOL

Refer to Tables 10-1 and 10-2 for pressure loads.

The nominal axial torque on the SSCVA pedestal resulting from the valve driving mechanism remains constant for each operating mode. However, the pedestal must be able to withstand a higher torque as a result of some abnormal resistance in the system. This higher value is referred to as the stall torque limit.

B. Transient Operation

Figures 10-2 through 10-7 show the transient response of the pedestal housing and bolts to the pressure loads. The figures show the same characteristic curvatures and peaks as figures 2-10 and 2-11. Transient loads are less than steady state loads.

10.2.2.2 Graphite Core

A. Steady State Operation

The graphite core reactor results in slightly smaller pressure loads to the SSCVA pedestal and housing bolts. However, the relative operational mode ranking as in Section 10.2.2.1 A still applies.

Refer to Tables 10-1 and 10-2 for the nominal pressure loads.

Table 10-3 shows the same nominal and stall torque values as for the composite core.

B. Transient Operation

Figures 10-8 through 10-13 show the transient response of the pedestal housing and bolts to the pressure loads.

The figures show the same characteristic curvatures and peaks as figures 2-10 and 2-11.

10.2.3 Applicable Requirements and Compatibility of Structural Performance with the NSS Specification

10.2.3.1 Specification Identification

The specification document governing the SSCVA is EC-677565, July 27, 1970.

10.2.3.2 Applicable Requirements

The E-105 document lists the applicable SSCVA requirements.

10.2.4 Method of Analysis (Design Practices)

10.2.4.1 Analytical Procedures

Refer to Section 2.4.2.1.

10.2.4.2 Analytical Models

A. Thermal Model, Description

Refer to Section 2.4.2.1.

B. Structural Model, Description

The load to the SSCVA housing is a result of the SSCV inlet pressure acting on the housing pedestal cap. The bolt load is distributed between three bolts which are loaded as the pedestal with an additional load from the seal spring.

C. Statistical Model, Description

Refer to Section 2.4.2.3.

10.2.4.3 Maturity of Input Data

Refer to Section 2.4.3.

10.2.4.4 Validity of Analysis

Refer to Section 2.4.4.

10.2.5 Results of Analysis and Interpretation

10.2.5.1 Composite Core

A. Handling and Shipping

Handling and shipping procedures and equipment are designed so that the loads transmitted to the NSS during these non-operative phases are less than those encountered during vehicle boost and reactor operation.

B. Ground Testing

Ground test data are required for reactor testing in two test cells.

1. Test Cell "C"

This item is not required for PDR.

2. ETS-1 Test Stand

This item is not required for PDR.

C. Launch and Boost

The launch and boost loads imposed on the NSS result from non-operative vehicle launch conditions during maximum dynamic pressure and booster engine cut-off (BECO), are given below.

Reference 25 documents the inertial loads encountered during the maximum dynamic pressure and BECO phases, for the component weights given in Reference 26.

<u>Phase</u>	<u>Nominal Weight</u>	<u>Axial G Load</u>	<u>Inertial Load</u>
Max. Q			
T + 160 seconds	36	5.2	187 lb.
BECO			
T + 165 seconds	36	0.0	0.0 lb.

D. Startup - High Impluse

Transient data are presented in Figures 10-2 through 10-7.

E. Flight Steady State

Steady state data are presented in Tables 10-1 through 10-3.

F. Shutdown - High Impulse

Data are shown in Figures 10-2 through 10-7.

G. Space Non-Operation

This item not required for PDR.

10.2.5.2 Graphite Core

A. Handling and Shipping

Refer to Section 10.2.5.1 A.

B. Ground Testing

Refer to Section 10.2.5.1 B.

C. Launch and Boost

Refer to Section 10.2.5.1 C.

D. Startup - High Impulse

Transient startup data are presented in Figures 10-8 through 10-13.

E. Flight Steady State

Steady state data are found in Tables 10-1 through 10-3.

F. Shutdown - High Impulse

Data are shown in Figures 10-8 through 10-13.

G. Space Non-Operation

Refer to Section 10.2.5.1. G.

10.2.6 References

Refer to Section 2.6.

Figure 10-1. SSCVA Housing Pedestal And Bolt Load And Moment Diagram

TABLE 10-1
AXIAL LOAD FROM SSCVA TO VALVE HOUSING PEDESTAL - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	19251	176	19791	18711
	EOL	18971	173	19502	18440
65% Throttle	SOL	11431	111	11773	11089
	EOL	11175	109	11509	10841
80% Power Single TPA	SOL	18360	145	18805	17915
	EOL	18119	143	18557	17681
65% Throttle Single TPA	SOL	13603	----	----	----
	EOL	13390	----	----	----
Growth Mode Tc = 4500°R	SOL	18985	----	----	----
	EOL	18644	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	19113	----	----	932 10/22/70
	EOL	18800	----	----	902 10/23/70
65% Throttle	SOL	11360	----	----	929 10/26/70
	EOL	11090	----	----	829 10/27/70
80% Power Single TPA	SOL	18147	----	----	816 11/19/70
	EOL	17877	----	----	888 11/20/70
65% Throttle Single TPA	SOL	13461	----	----	681 11/25/70
	EOL	13220	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	18843	----	----	821 11/30/70
	EOL	18474	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

TABLE 10-2
TENSILE LOAD ON SSCVA HOUSING BOLT - lb.

Composite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	8366	102	8606	8126
	EOL	8272	101	8581	7963
65% Throttle	SOL	5759	63	5952	5566
	EOL	5674	62	5865	5483
80% Power Single TPA	SOL	8069	70	8283	7855
	EOL	7988	69	8200	7766
65% Throttle Single TPA	SOL	6483	----	----	----
	EOL	6412	----	----	----
Growth Mode Tc = 4500°R	SOL	8277	----	----	----
	EOL	8163	----	----	----
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
Rated Power	SOL	8320	----	----	932 10/22/70
	EOL	8215	----	----	902 10/23/70
65% Throttle	SOL	5736	----	----	929 10/26/70
	EOL	5646	----	----	829 10/27/70
80% Power Single TPA	SOL	7998	----	----	816 11/19/70
	EOL	7908	----	----	888 11/20/70
65% Throttle Single TPA	SOL	6436	----	----	681 11/25/70
	EOL	6356	----	----	820 11/30/70
Growth Mode Tc = 4500°R	SOL	8230	----	----	821 11/30/70
	EOL	8107	----	----	822 11/30/70

* One sided tolerance limits for .99 reliability and .95 confidence

Composite Core		Mean	S	Upper Limit *	Lower Limit *
		200	-	246**	154
Rated Power	SOL EOL	↓		↓	↓
65% Throttle	SOL EOL				
80% Power	SOL EOL				
Single TPA	SOL EOL				
65% Throttle	SOL EOL				
Single TPA	SOL EOL				
Growth Mode	SOL EOL				
Tc = 4500°R	SOL EOL				
Graphite Core		Mean	S	Upper Limit *	Lower Limit *
		200	-	246**	154
Rated Power	SOL EOL	↓		↓	↓
65% Throttle	SOL EOL				
80% Power	SOL EOL				
Single TPA	SOL EOL				
65% Throttle	SOL EOL				
Single TPA	SOL EOL				
Growth Mode	SOL EOL				
Tc = 4500°R	SOL EOL				

* One sided tolerance limits for .99 reliability and .95 confidence ** maximum stall torque 300 in.-lb.

* One sided tolerance limits for .99 reliability and .95 confidence ** maximum stall torque 300 in. -lb.

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 10-2. Axial Load From SSCVA to Valve Housing Pedestal Versus Time, CSUS"

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 10-3. Axial Load From SSCVA to Valve Housing Pedestal Versus Time, CSUE"

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 10-4. Axial Load From SSCVA to Valve Housing Pedestal Versus Time, CSDSE"

COMPOSITE CORE - STARTUP TRANSIENT AT START-OF-LIFE

Figure 10-5. Tensile Load on SSCVA Housing Bolt Versus Time, CSUS

COMPOSITE CORE - STARTUP TRANSIENT AT END-OF-LIFE

Figure 10-6. Tensile Load on SSCVA Housing Bolt Versus Time, CSUE

COMPOSITE CORE - SHUTDOWN TRANSIENT

Figure 10-7. Tensile Load on SSCVA Housing Bolt Versus Time, CSDSE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 10-8. Axial Load from SSCVA to Valve Housing Pedestal Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 10-9. Axial Load From SSCVA to Valve Housing Pedestal Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 10-10. Axial Load from SSCVA to Valve Housing Pedestal Versus Time, GSDE

GRAPHITE CORE - STARTUP TRANSIENT

Figure 10-11. Tensile Load on SSCVA Housing Bolt Versus Time, GSUSE

GRAPHITE CORE - SHUTDOWN TRANSIENT AT START-OF-LIFE

Figure 10-12. Tensile Load on SSCVA Housing Bolt Versus Time, GSDS

GRAPHITE CORE - SHUTDOWN TRANSIENT AT END-OF-LIFE

Figure 10-13. Tensile Load on SSCVA Housing Bolt Versus Time, GSDE

11.0 NSS INSTRUMENTATION

11.1 INTRODUCTION

Neither instrument nor instrument mounting hardware are represented in the NSS structural model (RATS code). When instrumentation installations are completely designed, this area will be reviewed. At that time, an assessment will be made of the usefulness of incorporating instrumentation and/or related hardware in the NSS structural model.

TITLE Data Item S-039 - Loads Analysis Report, Nuclear Subsystem	
	DOCUMENT NO. WANL-TME-2756	DATE 12/15/70
ABSTRACT <p>This data item identifies the primary structural design loads to which the NERVA engine and its major components are subjected during launch and nuclear stage operation. These loads are the basis for structural analysis, design testing and related documentation.</p>		
DATA ITEM NO. S-039	SECURITY CLASSIFICATION OF DOCUMENT Unclassified	
CDRL LINE NO	TOTAL NO. OF PAGES 356	
KEY WORDS <p>NERVA, Loads, Moments, Displacements, NSS, ECC, Nominal, Tolerance Limits, Monte Carlo</p>		
AUTHOR/EDITOR T. A. Tomaszewski		PREPARING DEPT Structural Design
<small>W Form 59943</small> <small>DOCUMENT INFORMATION SUMMARY</small>		

Fold
or Cut

Fold
or Cut