ANNUAL REPORT

for period

1 October 1973 - 30 September 1974

Purdue - U. S. Atomic Energy Commission Contract AT(11-1)-1428, Task C

Principal Investigator: Earle C. Fowler

The work partially supported under this contract during the stated period consists of:

1. The Purdue portion of two hybrid experiments concentrated on the search for exotic mesons produced in reactions dominated by baryon exchange. Our collaborators are from Indiana University, the Stanford Linear Accelerator Center, and Vanderbilt University. One experiment (SLAC E-82) is essentially complete except for final publication. The other (SLAC E-103) has been under preparation and will continue to occupy most of our effort during the coming year.
2. The Purdue portion of "Study of the neutrino capture cross section in ^{37}Cl with μ^+ decay neutrinos" at the Los Alamos Meson Physics Facility. This experiment has approval contingent upon the neutron background being sufficiently low. Our collaborators are Drs. Raymond Davis, Jr. and John Evans at the Brookhaven National Laboratory, and Professor Stuart Meyer at Northwestern University.
3. The Purdue portion of a neutrino experiment for the Fermi National Accelerator Laboratory described in FNAL Proposal #254. Our collaborators in this experiment are Dr. George Kalbfleisch of the Brookhaven National Laboratory and Professors Barry Barish and Frank Sciulli of the California Institute of Technology. Final approval for this experiment is contingent on completion of a test

NOTICE

A report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

run to predict and determine the number and distribution of muons coming from the decay of pions and kaons in the drift space of the FNAL narrow neutrino beam.

Drs. Earle Fowler, Neil Baggett and James Cunnane, as well as two students, Mike Huebschman and Art Kreymer, with the help of Purdue technical staff, have carried the work forward. A more detailed account follows.

1. The SLAC Experiments

A. E-82

Most of the analysis on this hybrid experiment has been completed. In the experiment nearly 25 million expansions of the SLAC 15" rapid-cycling chamber yielded about 85,000 triggered photographs. Beams of 8.4 GeV π^+ were incident on hydrogen imbedded in a magnetic field of about 17,500 Gauss. The trigger selected fast (> 3 GeV/c) forward neutrons and the neutron detector contained spark chambers which were photographed so that the neutron's direction could be determined. The main conclusion is: "No clear evidence for narrow exotic mesons was found with masses ≤ 3.0 GeV in the decay modes accessible in this study of $\pi^+, p \rightarrow X^{++} + n$ (forward) where $X^{++} \rightarrow \pi^+ \pi^+, \pi^+ \pi^+ \pi^+ \pi^-, 4\pi^+$ and $2\pi^-,$ and $\bar{p} p \pi^+ \pi^-.$ " Appendix A gives more details in the form of two papers submitted to the XVII International Conference on High Energy Physics (Imperial College, London, 1 - 10 July 1974). A-1 is "Search for Backwards-Produced Exotic Meson Resonances in 8.4 GeV/c $\pi^+ p$ Interactions," and A-2 is "A Study of Particle Spectra and Correlations in the Reaction $\pi^+ + p \rightarrow n$ (forward) + (2 π , 4 π , 6 π) at 8.4 GeV/c."

B. E-103

Our collaboration group (with Indiana, Vanderbilt and SLAC) is continuing the search for exotic mesons produced in baryonic exchange processes. In order to achieve the order of 10^3 events/microbarn, which now seems required to have a reasonable chance to observe these elusive

Purdue University
Contract No. AT(11-1)-1428, Task C

COO-1428-391

particles, we are shifting to the SLAC Streamer Chamber. We are collaborating with two or three members of Dr. Robert Mozley's group. In order to improve the precision with which events can be detected and measured, we will use π^- incident on deuterium, putting most of our effort on π^- , $n \rightarrow X^{--} + p$ (forward). This necessitates a Cherenkov counter for identifying the proton and counter hodoscopes, wire chambers and a downstream magnet for precision triggers and analysis. Vanderbilt is responsible for the Cherenkov counter, Purdue for the counter hodoscopes, and Indiana for the wire chambers. By October 1, 1974, all this gear will have been assembled and surveyed. Testing with negative pions will be under way. At this writing most of the physicists in our collaboration are at SLAC, getting all the equipment together. Tentatively, the experiment is expected to begin in January 1975. We are not enclosing a copy of the proposal for SLAC E-103, but would be glad to supply it on request. The experiment will be divided between running at 8.4 GeV/c and 14 GeV/c. Some people believe that the exotic mesons are massive enough that they decay primarily via baryon-antibaryon channels. If so, the higher energy of the 14 GeV/c run will be essential. We are optimistic about this experiment.

2. Study of the neutrino capture cross section in ^{37}Cl with μ^+ decay neutrinos.

Two large tanks and the necessary gear to test the effect of machine-produced neutrons in producing background events have been put into operation in the neutrino laboratory of the Los Alamos Meson Physics Facility. Several test runs have been made, and preliminary results indicate that the flux neutrons which can make ^{37}Ar from ^{37}Cl are well below our calculated rate. We tentatively conclude that we will be able to go down to a shield thickness of three meters. The neutron flux must be measured at that thickness, but we are well within

limits of a feasible measurement of the production of ^{37}Ar from ^{37}Cl by neutrinos from the decay of stopped μ^+ produced in the LAMPF beam dump. This work will place a firm experimental base under Dr. Davis' solar neutrino work at Lead, South Dakota, and will give a significant measurement of the fraction of the μ^+ decays which yield ν_e . If the "muon number" is additively conserved, every μ^+ decay should give a ν_e . All of us feel that good progress has been made in this experiment.

3. FNAL E-254

"Experimental Test of the Identity of the Neutrino from K-decay to That from π -Decay." Kalbfleisch and Fowler have joined with the FNAL-Cal Tech group (originally FNAL Exp. 21) to utilize that group's detector chain and narrow dichromatic neutrino beam to compare the total cross section on nuclei of the neutrinos from K-decay with those from π -decay. We believe that it is not necessary to attach the actual proposal, but it is available on request. The main features of the present set-up are that the narrow-band beam consists of two peaks in the energy distribution of the neutrinos. When the momentum of the charged mesons in the drift space is about 160 GeV/c, the neutrinos from K-decay are concentrated at about 140 GeV/c and those from π -decay are concentrated at about 70 GeV/c. The detector consists of a sandwich of steel plates and scintillation counters (mass > 100 tons) which make up a high-energy hadron "calorimeter." This unit is followed by a thick, large toroidal magnet which has a reasonable efficiency for identifying μ 's. The FNAL-Cal Tech group has measured the total cross sections at the two energies and has recently identified neutral current events with its set-up.

Three new elements are being added to make the desired comparison of total cross sections to about a 5% level (measurements to date are at about the 30% level).

- a. Two different momenta will be used for the charged hadrons in the drift space such that the energy of the neutrinos from K-decay in the second run will be identical to that of the neutrinos from π -decay in the first run. For our test, this is essential.
- b. A new, more accurate Monte Carlo calculation for the production, focussing, and decay of the charged hadrons will be prepared. Close attention will be paid to the course of muons produced in the same decays which give the neutrinos.
- c. The drift tube is terminated by a 10-foot-thick steel shielding plug. At least eight scintillation counter muon telescopes will be placed just downstream of the steel shield. Measurement of the distribution of muons at this point in the beam will be used to calibrate and monitor the neutrino flux in the detector.

During the period of this report, work has gone forward mostly in the planning and study way. In order to have a more definite plan to present to FNAL's program committee, a written agreement between the FNAL - Cal Tech group and Fowler and Kalbfleisch has been worked out. Copies of this agreement are available. Tests of the feasibility of counting muons behind the drift space (in FNAL Enclosure #100 of the neutrino beam) have been run. Based on these tests, a definite design for the telescopes has been completed. Appendix B is a brief summary of our muon-monitoring feasibility tests. We feel that we've made good progress on this experiment.

During this year, it has become clear that there is broad interest in doing something similar to what Kalbfleisch and Fowler attempted in putting the leptons into the Han-Nambu system of integrally-charged quarks. The notable leaders at this writing seem to be that of Professor Glashow (with its charmed particles) and that of Professors Pati and Salam. We make no claim for our specific choice, but it is what led us to think and to realize that the identity of the neutrinos from K- and π -decay had not been tested. Our note has been published in Nuovo Cimento. A reprint is attached as Appendix C. *Spurk Revised*

Purdue University
Contract No. AT(11-1)-1428, Task C

COO-1428-391

To complete this report, we should add that:

1. Mike Huebschman belonged to the Army Reserve as an officer and was called to active duty about 15 January 1974. We are hopeful that he will return at some future date.
2. Art Kreymer, for personal reasons, is transferring to Indiana University at the end of this summer. He is likely to participate in the running of SLAC #-103. We are sorry to lose him at Purdue, but glad to keep him in the experiment.
3. Dr. James Cunnane is leaving Purdue at the end of this summer. We are replacing him with Dr. Robert Yamartino, whose vita and publication list appears in our renewal proposal.

*Appendix A-1 and A-2 removed and recycled
as Conf. papers.*

APPENDIX: NAL #254

Muon Monitoring - Preliminary Measurements

Summary

Muon monitoring was envisaged in the proposal to be made in enclosure #100 immediately after the secondary hadron stopper at the end of the 350-meter decay region. We report here the feasibility of such a muon monitor which can operate at least to a beam level of 7×10^{12} protons (per pulse) per second (with the ≈ 50 MHz RF structure).

Two measurements were made: the first, December 7, 1973, with the narrow-band train load, $1.5-2 \times 10^{12}$ ppp with 10' of steel in the stopper and the protons dumped on the train; the second, June 8, 1974, with the $\mu 98$ triplet quad train, $4-8 \times 10^{12}$ ppp with 15' of steel in the stopper and an 18" Al production target with the unabsorbed $\approx 2 \times 10^{12}$ ppp being dumped in the upstream end of the steel stopper.

The muon monitor will consist of eight 5-fold telescopes, each of 0.05 in.² cross-section, which will monitor muons (and accidentals) pulse by pulse.

The Measurements

Two measurements of the fluxes immediately after the enclosure 100 secondary hadron stopper were made. The first, with the narrow-band beam, was made December 7, 1973, at $1.5-2 \times 10^{12}$ ppp. With the rapid five-fold increase of the intensity of the FNAL accelerator this spring, a second measurement was indicated. This was carried out June 8, 1974, with the $\mu 98$ triplet train at $4-8 \times 10^{12}$ ppp.

The December measurement was done at one radial position ($\approx 9"$ from beam centerline) at four train momenta (95, 120, 145 and 170 GeV), and for both positive and negative beam (simultaneously with monitor calibrations being made by v21). The June measurement was done at various radial positions (7" to 12" from centerline) at one momentum, 150 GeV/c positive beam, during $\mu 98$ data taking.

Telescope

December: Three $1/2" \times 1/2" \times 1/2"$ cubes of scintillator were viewed through 36"-long air light guides (conical tubes of aluminized mylar). The scintillators were aligned on an Al bar mounted normal to the end plate of the enclosure 100 beam stopper.

June: Four scintillators, 0.75" long $\times$ 0.05 in² area (0.2" $\times$ 0.25"), were used. The telescope was movable via remote control over a 7" travel.

The tubes used were 56 AVP's. For the June run, the resistor string carried 4 ma at 2000 volts, and the last two dynodes were "boosted," i.e. held at constant voltage, with 3 ma and 10 ma of current supplied to the respective dynodes of each tube by auxiliary power supplies during pulses with a singles counting rate of $\sim 10^7$ /second. No "sagging" of the pulses occurs with "boosting" at these rates.

Electronics

Three- or four-fold real coincidence and accidental coincidences with appropriate gate. The accidentals are with delays of 0, 1, 2, and 3 times one RF bunch (~ 18.5 ns) in each of the four inputs. The gate was 0.1

second per spill at the beginning of the spill for the December run (to avoid possible "sagging" during the measurement period) and 0.2 seconds near the middle of the spill for the June run (in between the 0.25-second spaced 30" beam "pings" to exclude that "fast" spill).

The coincidences, accidentals, and the "90° monitor" were scaled. The 90° monitor is failing as of June but still is proportional to beam: in December there were approximately four 90° monitor counts per 10^9 protons (via SEM) whereas there were ~ 1 in June.

Single Counting Rates

December 1973: 0.25 in² area, 2-6 MHz at 10^{12} protons/second.

June 1974: 0.05 in² area, 10 MHz at 5×10^{12} protons/second with minimal discrimination. The large length/transverse size ratio (~ 3) in June setup gives "coincidence" pulses which are ~ 2 times the "accidental" pulses. Thus with proper discrimination (efficiency to be measured and corrected for in actual monitor of course), the singles counting rate was measured to be ~ 5 MHz / 7.5×10^{12} protons per pulse (~ 1 second duration), of which a substantial fraction is due to true "coincidence" pulses. The singles rates decrease somewhat ($\sim$ factor of two) with change of radius 7" to 12".

All "accidental" coincidence rates measured check out with the singles rates measured using the ~ 50 MHz structure of the proton beam.

Coincidence Counting Rates

December 1973: (2-40) thousand/ 10^{12} protons for momenta 170-95 GeV/c at $\sim 9"$ radius, 0.25 in^2 . Fig. 5 of the NAL 254 proposal expected $\sim 50\text{K}$ at $7"$ radius and a factor of a few less at a somewhat larger radius. The true centering of the counter telescope in these runs relative to the beam is uncertain, but the rates are in the correct ballpark. In addition the energy dependence, shown in Fig. 1, is roughly correct (relative to Expt. 104's measurements (Kycia, et al.)).

June 1974: 2.5 MHz /pulse of 7.5×10^{12} pps at $7"$ radius and 0.5 MHz at $12"$ radius with $\leq 10\%$ accidentals.

These coincidences are presumably due almost entirely to muons produced in the stopper. The secondary hadron beam incident on the stopper is $\sim \text{few} \times 10^9$ /pulse; about 10% decay to muons over an $\sim 100 \text{ in}^2$ area, i.e. roughly $\sim 0.3 \text{ MHz}$ $\mu/0.05 \text{ in}^2$ of telescope area. A large fraction of the protons pass through the target and were dumped on the upstream end of the stopper (since the train dump is inoperative at this time), i.e. some 2×10^{12} protons. The hadron feedthrough is less than 10^{-8} - 10^{-9} for 15' of steel and is negligible. But the 2×10^{12} of 300-GeV protons will produce $\sim 2 \times 10^{13}$ pions of some 30 GeV each (on average); each will have > 0.2 meters in which to decay (on average), i.e. $> 10^{-4}$ probability. This gives a plug produced μ flux of the order of $> 2 \times 10^9$ over $\sim 100 \text{ in}^2$, i.e. $\gtrsim 1 \text{ MHz}/0.05 \text{ in}^2$ area of the telescope at the close-in radius of $\sim 7"$. Also, the $\mu 98$ experiment was keeping the proton beam spray through the $4" \times 4"$ hole in the center of the stopper to less than a few $\times 10^{10}$ (measured downstream with a SEM). The "spray" from these protons in the walls of the hole and elsewhere should give a substantial singles rate (not "coincident" since

telescope "views" edges of hole only thru greater than 7' or so of steel). This spray, $\sim 10^{10}$ per $\sim 100 \text{ in}^2$ should give a singles rate $\sim 5 \text{ MHz}$ in telescope, comparable to what was seen.

Discussion

These measurements show the feasibility of μ monitoring in enclosure 100 for slow spill narrow-band running. With the anticipated 20' of stopper (15' of steel + 5' of aluminum), the hadron leakage should yield even lower singles rates at the telescope. With only secondary hadrons in the decay pipe, the plug produced muons will be nearly negligible ($\lesssim 10^{-3}$ of 2.5 MHz measured in June run) as expected. Thus the μ 's from π and K decay will dominate the counting rate seen by the telescope. The accidentals should be less than 10% for intensities about $7 \times 10^{12} \text{ ppp}$:

$$\text{accidental rate} = 50 \text{ MHz} \left(\frac{\lesssim 5 \text{ MHz singles}}{50 \text{ MHz RF}} \right)^5$$

$$= 0.5 \text{ KHz (at most a factor of 10 higher at smaller radii)}$$

vs. coincidence rate = 70 KHz at small radii for μ from π decay

and vs. at large radii = 7 KHz for μ from K decay.

Detailed calculations of the radial dependence of the μ flux arising from π, K decays in the 350m decay pipe and interactions in the stopper will be checked against careful test run data to be made after approval of this proposal. Careful attention to leakage of protons from the train dump and construction of the telescope may lead to sufficient reductions in the singles rates such that even higher proton intensity can be utilized. However, a maximum of $\sim 7 \times 10^{12} \text{ ppp}$ appears reasonable in any case. It is to be noted

that no deterioration of scintillators or phototubes at these rates ($10^7/\text{second}$) for 10^6 pulses has been observed by us in an experiment at the AGS; at 10^{14} particles, this may change, but it is comfortably adequate; we will remove the μ telescopes from the beam when slow spill narrow-band running is not in progress.

Fig 1.