BROOKHAVEN NATIONAL LABORATORY
Associated Universities, Inc.
Upton, New York

GRISP 73-17

ACCELERATOR DEPARTMENT
Informal Report

The Brickwall Effect

M. Month

September 18, 1973

ABSTRACT

A quantitative account of the brickwall effect is given. By combining the theory of the resistive wall instability with the theory of a nonuniform incoherent tune shift, it is shown how the brickwall effect manifests itself as a limit on the current tune density (current/tune spread) at some critical stack width. A description of the effect in the CERN ISR is given. It is also shown, by an example, how the limiting current condition can be used in a certain class of storage ring design.

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

MASTER
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

1. Introduction

The term "brickwall effect" refers to a transverse coherent beam instability observed at the CERN ISR.¹ A most interesting characteristic of this instability is the presence of a current threshold. Such a threshold makes it clear that the observations cannot be explained by the classical transverse resistive wall instability.² This is the case because of the following two facts: First, resistive wall theory gives an instability threshold proportional, not to current alone, but to I/Δ , where I is the current and Δ is a measure of the ν -value (betatron tune) distribution. And secondly, current is stacked in the ISR with the ratio I/Δ kept essentially constant. These two facts are incompatible with a current threshold. To explain it, therefore, another physical factor must be sought.

The suggestion has been made that resistive wall theory is still applicable, but must be coupled with space-charge effects.^{1,3} It has, in fact, been shown that if one includes in the resistive wall theory a nonuniform incoherent tune shift, then, the observations connected with the brickwall phenomenon in the ISR can be adequately described.⁴ However, in Ref. (4), estimates of the space-charge effects were not included. It was simply assumed that they were of an appropriate magnitude.

Here we will combine the instability theory with the recently developed theory of a nonuniform incoherent tune shift due to image forces⁵ in order to obtain a quantitative criterion for the brickwall effect. We will show that the criterion is a limitation on I/Δ which is a function of the width of the stack. The picture is as follows: The brickwall criterion can be expressed as

$$I/\Delta < (I/\Delta)_{bw} ,$$

with $(I/\Delta)_{bw}$ conceptually ∞ for zero width stacks, and for the case of narrow stacks, the classical resistive wall limit on I/Δ determines the current limitation. Now, as the beam is stacked, the beam width increases and the brickwall limit, $(I/\Delta)_{bw}$, decreases until it reaches a minimum. From this point the limit $(I/\Delta)_{bw}$ increases again as the stack further widens. The minimum in the function $(I/\Delta)_{bw}$ is an interesting point. It means that there is a particular beam width (or current) which limits the

stacking. Note the point that if the stacking proceeds past the critical current (or critical stack width), the limit on I/Δ recedes. It is presumably the existence of this singular current which gives rise to the name "brickwall", implying that one simply has to pass it to be safe. If $(I/\Delta)_{bw}$ (minimum) is less than $(I/\Delta)_{rw}$, the classical resistive wall limit, then for a particular value of the current, the brickwall presents a stricter current limit than the standard resistive wall limit.

We will calculate the critical stack width (and so, the critical, or brickwall current). Parallel plate geometry is assumed, as was done in Ref. 5. We will obtain the brickwall limit of I/Δ and show how it compares to the classical resistive wall limit. The CERN ISR will be treated as an example. Finally, we will discuss small gap designs, and show how the critical stack width depends on the size of the magnet gap.

2. The Critical Current (Stack Width)

Consider a storage ring such that the tune, ν , is a function of momentum. Let ν_c be the central tune, corresponding to a central momentum, p_c . Let Δ be the half-width of the distribution in ν -units, in the absence of space charge. We denote the unperturbed ν -value, ν_o . Then a convenient variable indicating the momentum deviation from its central value is

$$x_o = \frac{\nu_o - \nu_c}{\Delta} = \frac{\nu' \delta_p}{\Delta}, \quad (2.1)$$

where $\delta_p = \Delta p/p$ is relative momentum deviation from p_c , and

$$\nu' = \frac{p d\nu}{dp} \quad (2.2)$$

is the slope of ν -value with respect to p . Since ν' is assumed to be constant, x_o is linear in δ_p .

If we define x in terms of the real tune ν by

$$x = \frac{\nu - \nu_c}{\Delta}, \quad (2.3)$$

then, from

$$\nu = \nu_c + \nu' \delta_p, \quad (2.4)$$

which, as assumed, is linear in δp , we have

$$x = x_0 \quad (2.5)$$

The effect of space charge is to distort the v versus p curve (i.e. the working line). This is equivalent to a distortion of the $x(x_0)$ curve [Eq. (2.5)]. Three properties of the space charge effect are: The center of the working line, v_c , is changed; the straight line joining the ends of the working line has the unperturbed slope, v' ; and a quadratic term in δp is introduced. (We neglect terms of third or higher order in x_0 .) We sketch these effects in Fig. 1. By an appropriate redefinition of v_c (and thus x_0) we can write the tune, v (or, x), in the presence of space charge, in the form

$$x = x_0 + r(1 - x_0^2) \quad (2.6)$$

The quantity r represents the nonuniformity of the space charge tune shifts across the beam.

From Ref. 5, the parameter r can be expressed in terms of the electric and magnetic incoherent tune shifts (for zero stack width) and form factors which depend on the stack width. Let f_{el} , f_{mag} be form factors which decrease the corresponding tune shifts at the stack center as a function of stack size. Further, let $\hat{f}_{el}$, $\hat{f}_{mag}$ be the ratio of tune shift at stack edge to tune shift at stack center for electric and magnetic cases respectively. We then find that r can be written

$$r = \frac{\Delta v_{el} f_{el} (1 - \hat{f}_{el}) + \Delta v_{mag} f_{mag} (1 - \hat{f}_{mag})}{\Delta} \quad (2.7)$$

where Δv_{el} and Δv_{mag} are electric and magnetic incoherent tune shifts at the beam center (for zero width). It can be shown, using Ref. 5, which assumes parallel plate geometry, that

$$F_{el}(\alpha) = f_{el} (1 - \hat{f}_{el}) = \frac{18}{\pi^2} \left[1 - \frac{2\pi\alpha}{3 \sinh \frac{1}{2}\pi\alpha} + \frac{\pi\alpha}{3 \sinh \pi\alpha} \right] \quad (2.8)$$

$$F_{mag}(\alpha') = f_{mag} (1 - \hat{f}_{mag}) = - \frac{9}{\pi^2} \left[1 - \frac{2\pi\alpha'}{3 \tanh \frac{1}{2}\pi\alpha'} + \frac{\pi\alpha'}{3 \tanh \pi\alpha'} \right] \quad (2.9)$$

$$\text{with } \alpha = a/h, \quad (2.10)$$

$$\alpha' = a/g, \quad (2.11)$$

while a is the half-stack width,
 h is the half-chamber height,
 and g is the half-gap height.

The tune shift variation across the beam is more sensitive to electric image forces⁶ and we accordingly simplify our expression for the distortion parameter, r , by simply neglecting the magnetic effect. We thus have

$$r(\alpha) = \frac{\Delta v_{el} F_{el}(\alpha)}{\Delta} . \quad (2.12)$$

In Ref. 4 it was shown that a quadratic distortion of the working line (tune versus p), that is, r , could excite a transverse coherent instability. The stability criterion established there was

$$|r| < \frac{1}{2} . \quad (2.13)$$

From the simple form of (2.12), it can be seen that the critical stack width for the brickwall effect can be obtained from the maximum of $r(\alpha)$ as a function of α , or

$$\frac{d F_{el}(\alpha)}{d\alpha} = 0 . \quad (2.14)$$

Thus, the critical stack width is directly proportional to the chamber height and independent of other machine parameters. If α_{crit} solves (2.14), then the critical stack width is

$$a_{crit} = \alpha_{crit} h = 1.3 h . \quad (2.15)$$

From a_{crit} and the current density per unit width stacked, we can find the critical current:

$$I_{crit} = a_{crit} \left(\frac{\partial I}{\partial a} \right) . \quad (2.16)$$

Assuming that the critical stack width is utilized, the brickwall stability criterion is

$$|r(\alpha_{crit})| = \left| \frac{\Delta v_{el} F_{el}(\alpha_{crit})}{\Delta} \right| < \frac{1}{2} . \quad (2.17)$$

This is a limit on the quantity I/Δ , but we will assume it to be independent of the limitation on I/Δ placed by the classical resistive wall effect. It can be shown⁷ that combining the two just means a more severe current limit.

3. The Brickwall in the ISR

The threshold condition for stability against the classical transverse instability, resulting from image forces due to the resistive walls, can be expressed as⁸

$$\frac{I}{\Delta} < \frac{ev\beta\gamma h^3}{2\epsilon_p R^2} \sqrt{\frac{\Omega|k-v|}{2\epsilon_0\rho}} \left[f_{rw} \left(\frac{a}{h} \right) \right]^{-1}, \quad (3.1)$$

where

Δ is the half-tune spread in the beam,

I is the current in A,

v is the vertical betatron tune,

β is the particle velocity in units of c ,

γ is the energy in units of particle mass,

h is the chamber half-height,

R is the ring radius,

k is the azimuthal mode number for the instability,

Ω is the particle angular velocity ($= \beta c/R$),

ρ is the chamber resistivity in units of ohm-m,

a is the beam half-width,

r_p is the classical proton radius, $= 1.54 \times 10^{-18}$ m,

e is the proton charge, $= 1.602 \times 10^{-19}$ coulombs,

ϵ_0 is the free space dielectric constant, $= 1/36\pi \times 10^{-9}$ sec/ohm-m,

and $f_{rw}(a/h)$ is a form factor normalized to $f_{rw}(0) = 1$.

This form factor is derived in Ref. 2. A plot is shown in Ref. 8. The condition (3.1) is not a general one, but is suitable as an estimate for the threshold in the ISR. If we use the values of these parameters for the ISR: $\gamma = 26$, $\beta \approx 1$, $v = 8.75$, $R = 150$ m, $k = 9$, $\rho = 0.7 \times 10^{-6}$ ohm-m (273° K stainless steel), $h = 2.5$ cm, $a = 2.5$ cm, then we obtain, with $f_{rw}(1) = 0.75$,

$$\frac{I}{\Delta} < 2202.0 \text{ (A/unit } \frac{1}{2}\text{-tune spread)} \quad (3.2)$$

So, for example, if the total tune spread is 0.04, $\Delta = 0.02$, and the current limitation is

$$I < 44 \text{ A} .$$

In the ISR, much less than this current is stacked with a spread of 0.04 in tune. In fact, a rough value of I/Δ for the ISR can be taken to be

$$\frac{I}{\Delta} = \frac{15}{0.03} = 500 , \quad (3.3)$$

which is well below the threshold set in (3.2).

Why, then, is there an instability at currents well below 15 A? We will show how the brickwall mechanism, as discussed in the previous section, can produce a separate and much lower current limit.

We start by writing an expression for the electric incoherent tune shift at the beam center for zero beam width. Without significant error, we can treat only the electric images, that is, those arising from the metallic chamber boundary. We thus have⁵

$$(\Delta\nu)_{el} = - \frac{\pi^2 I_r R^2}{24 c c v \beta^3 \gamma h^2} . \quad (3.4)$$

Using ISR values, this can be simplified to

$$(\Delta\nu)_{el} = - 0.03 (I/5) . \quad (3.5)$$

The stability criterion, Eq. (2.17), against the brickwall effect can therefore be written

$$\left(\frac{I}{15\Delta} \right) F_{el}(\alpha_{crit}) < 16.7 , \quad (3.6)$$

or, with $F_{el}(\alpha_{crit}) = 0.35$,

$$\frac{I}{\Delta} < 716 , \quad (3.7)$$

very close to the estimated ISR operating value (3.3).

The critical stack size ($a = \frac{1}{2}$ -width) is

$$a_{crit} = 1.3 h = 3.25 \text{ cm} . \quad (3.8)$$

Considering the approximations used:

- (a) Ideal parallel plate geometry,
- (b) Uniform density, hard-edged beam distribution horizontally,
- (c) Neglect of magnetic effects,

and the fact that we have only a rough estimate of ISR operations [as in (3.3)], these results represent a good description of the brickwall phenomenon. Concerning the somewhat high value for a_{crit} , Eq. (3.8), we should mention that the function $F_{cl}(\alpha)$, Eq. (2.8), has a rather broad maximum. Thus, when $\alpha = 0.7$, the value of F_{cl} is already 0.25. This corresponds to a total stack width ($= 2a$) of 3.5 cm.

With this success in describing the brickwall effect in the ISR, we will use this theory to estimate the effect for a storage ring design for high energy protons, one which utilizes a very small magnet gap.

4. The Brickwall Effect in a Small Gap, Large Radius Storage Ring

A storage ring design⁹ which demands a high energy, a room temperature magnet and a small magnet gap is strongly constrained by transverse collective effects.⁸ The relevant parameters are the small gap and the implied large radius, which follows from the low magnetic field, high energy requirements. To counter this, it is proposed⁹ to stack a very wide ribbon beam.

We first consider the current constraint imposed by the classical resistive wall instability. A rough threshold condition is given by Eq. (3.1). Using $v = 20.25$, $\gamma = 30$, $h = 1.25$ cm (half-chamber height, corresponding to a half-gap of 2 cm), $R = 540$ m, $k = 21$ (lowest mode with a potential instability), and $\rho = 1.6 \times 10^{-8}$ ohm-m (273° K copper), we obtain

$$\frac{I}{A} < 168 \left[f_{rw} \left(\frac{a}{h} \right) \right]^{-1} \quad (\Lambda/1/2\text{-tune spread}) \quad (4.1)$$

Assuming energy stacking, the current is proportional to the stack width¹:

$$I = \frac{a}{a_{max}} I_{max} \quad (4.2)$$

Thus, (4.1) becomes

$$\frac{I_{\max}}{\Delta} < 168 \frac{a_{\max}}{a} \left[f_{rw} \left(\frac{a}{h} \right) \right]^{-1} . \quad (4.3)$$

Using the curve of f_{rw} in Ref. 8, we see that the strongest constraint is at maximum current: With $a = a_{\max}$, and $a_{\max} = 4 h = 5$ cm (corresponding to a 10 cm stack), $f_{rw}(4) = 0.30$, we have

$$\frac{I_{\max}}{\Delta} < 560 . \quad (4.4)$$

Because the constraint is a decreasing function of a , stability against the transverse resistive wall effect at maximum current implies stability during stacking.

For a stack of total tune spread 0.02 ($\Delta = 0.01$), we have a current limitation,

$$I_{\max} < 5.6 \text{ A} . \quad (4.5)$$

Next we will estimate the constraint imposed by the brickwall effect. The space charge tune shift at the beam center for a zero width beam can be computed from (3.4):

$$(\Delta\nu)_{cl} = 0.057 I . \quad (4.6)$$

Since $\alpha_{crit} = 1.3$, and $F_{cl}(1.3) = 0.35$, the brickwall stability criterion (2.17) leads to

$$\frac{I}{\Delta} < 25.1 \text{ (A per } \frac{1}{2} \text{ tune spread)} . \quad (4.7)$$

The critical stack width is

$$a_{crit} = \alpha_{crit} h = 1.6 \text{ cm} . \quad (4.8)$$

This means that for a 10 cm stack ($a_{\max} = 5$ cm), the brickwall has its peak effect when about 1/3 of the current is stacked. If I/Δ is kept constant during stacking and $\Delta = 0.01$, this leads to a current limitation,

$$I_{\max} < 0.25 \text{ A} . \quad (4.9)$$

Even without specifying Δ , the condition (4.7) is severe, as can be seen by comparing with the ISR brickwall limit (3.7). It appears that high order fields will be required to correct the nonuniformity of the space charge tune shifts across the stack width. If this is done, condition (4.7) would give way to (4.4), which is the current limit due to the classical resistive wall effect.

5. Conclusions:

We have treated the brickwall effect in quantitative terms. In computing the brickwall current limit, the classical resistive wall effect was ignored. Combining the two would lead to a more stringent brickwall limit than has been obtained. However, it is in the spirit of the approximations used here to treat the two separately.

We have obtained a quantitative description of the brickwall effect in the ISR by combining the theory of the resistive wall instability with the theory of a nonuniform incoherent tune shift. We have further given an example of the use of the brickwall stability criterion in storage ring design.

Distr.: CRISP

References

1. B. Zotter, CERN Report, CERN-ISR-TH/72-36 (1972).
2. L.J. Laslett, V.K. Neil, and A.M. Sessler, Rev. Sci. Instr. 36, 436 (1965).
3. R. Gluckstern, BNL Informal Report, CRISP 72-33 (1972).
4. M. Month and K. Jellet, BNL Informal Report, AADD 73-2 (1973).
(To be published in Nucl. Instr. & Meth.)
5. M. Month and R.L. Gluckstern, BNL Informal Report, AADD 73-8 (1973).
(To be published in Particle Accelerators.)
6. To see this, compare Figs. 4 and 5 in Ref. 5.
7. To see this, consider Fig. 1 of Ref. 4. If the classical resistive wall effect is included, the " $\frac{1}{2}$ " in the brickwall criterion, $r < \frac{1}{2}$, must be decreased.
8. See, for example, M. Month, BNL Informal Report CRISP 73-7 (1973); or see the basic paper on this subject, Ref. 2.
9. G.T. Danby, H. Hahn, H.J. Halama, A.W. Maschke, M. Month, I. Polk, and W.J. Willis, "200 GeV ISA with Room Temperature Magnets," BNL Accelerator Department Report, to be published.

5. Conclusions:

We have treated the brickwall effect in quantitative terms. In computing the brickwall current limit, the classical resistive wall effect was ignored. Combining the two would lead to a more stringent brickwall limit than has been obtained. However, it is in the spirit of the approximations used here to treat the two separately.

We have obtained a quantitative description of the brickwall effect in the ISR by combining the theory of the resistive wall instability with the theory of a nonuniform incoherent tune shift. We have further given an example of the use of the brickwall stability criterion in storage ring design.

Distr.: CRISP

References

1. B. Zotter, CERN Report, CERN-ISR-TH/72-36 (1972).
2. L.J. Laslett, V.K. Neil, and A.M. Sessler, Rev. Sci. Instr. 36, 436 (1965).
3. R. Gluckstern, BNL Informal Report, CRISP 72-33 (1972).
4. M. Month and K. Jellett, BNL Informal Report, AADD 73-2 (1973).
(To be published in Nucl. Instr. & Meth.)
5. M. Month and R.L. Gluckstern, BNL Informal Report, AADD 73-8 (1973).
(To be published in Particle Accelerators.)
6. To see this, compare Figs. 4 and 5 in Ref. 5.
7. To see this, consider Fig. 1 of Ref. 4. If the classical resistive wall effect is included, the " $\frac{1}{2}$ " in the brickwall criterion, $r < \frac{1}{2}$, must be decreased.
8. See, for example, M. Month, BNL Informal Report CRISP 73-7 (1973); or see the basic paper on this subject, Ref. 2.
9. G.T. Danby, H. Hahn, H.J. Halama, A.W. Maschke, M. Month, I. Polk, and W.J. Willis, "200 GeV ISA with Room Temperature Magnets," BNL Accelerator Department Report, to be published.

Fig. 1 Incoherent space charge tune shift

Fig. 1 Incoherent space charge tune shift