

3

MLM-2106


MLM-2106

***LES 8/9 Vibration Test on  
a Multihundred Watt FSA***

***C. G. Anderson and C. O. Brewer***

May 2, 1974

**MASTER**



**Monsanto**

**MOUND LABORATORY**

Miamisburg, Ohio  
operated by

**MONSANTO RESEARCH CORPORATION**

a subsidiary of Monsanto Company  
for the

**U. S. ATOMIC ENERGY COMMISSION**

U. S. Government Contract No. AT-33-1-GEN-53

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

## **DISCLAIMER**

**This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.**

## **DISCLAIMER**

**Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.**

# **LES 8/9 Vibration Test on a Multihundred Watt FSA**

C. G. Anderson and C. O. Brewer

Issued: May 2, 1974

## **NOTICE**

*This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.*

### **PRINTED IN THE UNITED STATES OF AMERICA**

Available from  
National Technical Information Service  
U. S. Department of Commerce  
5285 Port Royal Road  
Springfield, Virginia 22151  
Microfilm \$1.45

## **MONSANTO RESEARCH CORPORATION**

A Subsidiary of Monsanto Company

## **MOUND LABORATORY**

Miamisburg, Ohio 45342

operated for

## **UNITED STATES ATOMIC ENERGY COMMISSION**

U. S. Government Contract No. AT-33-1-GEN-53

**MASTER**

DISTRIBUTION STATEMENT IS UNLIMITED

*pen*

#### ABSTRACT

A random vibration test was performed on a  $^{238}\text{PuO}_2$  fueled Multihundred Watt (MHW) fuel sphere assembly (FSA). The FSA (MHFT-11) was mounted in a Mound Laboratory test fixture and subjected to sinusoidal and random vibration energies on three orthogonal axes while in a simulated operational condition. The FSA temperature was maintained at  $1000^\circ\text{C}$  during the vibration test. Visual and radiographic inspections subsequent to the test indicated no apparent degradation of the FSA.

The MHFT-11 fuel sphere assembly (FSA) was vibrated to determine its ability to withstand the vibration environment levels expected to be encountered during the powered flight phase of a Titan III C vehicle during a LES 8/9 launch. The tests were designed to evaluate the effect of the graphite/metal and metal/fuel clearances as well as vent performance. Safety considerations and dynamic response characteristics were incorporated into the test fixture.

The original test requested was a LES 8/9 qualification-level test utilizing a  $^{238}\text{PuO}_2$  fueled FSA (MHFT-11). Pre- and post-baseline tests were conducted. General Electric, Energy Systems Program (GE/ESP) provided Monsanto Research Corporation, Mound Laboratory (Mound) with a modified LES 8/9 qualification-level spectrum (Schedule A). This schedule reflects vibrations input to an FSA as observed during a generator-simulated shaker test on a heat source assembly conducted at GE/ESP.

GE/ESP analyzed the Mound vibration data for Runs 1-21 which used Schedule A. After this data reduction, Schedule B was provided to Mound. Schedule B was a qualification test schedule that took into account the transmittance responses of the Mound test fixture. Schedule B was used by Mound for the tests on MHFT-11, Runs 22-27.

Schedule C was submitted to Mound by GE/ESP as an acceptance test schedule for LES 8/9 after data reduction indicated Schedule B was valid as a qualification test. Schedule C was used for the dynamic tests which were performed subsequent to the  $\text{PuO}_2$  fueled tests on the seven fueled safety sequential test (SST) units.

The test data, as well as the inspections conducted after the tests, indicated that the FSA is satisfactory for its intended use.

ATTACHMENTS

	<u>Page</u>
A. Test Plan	
1. Alpha Fuels Environmental Test Facility . . . . .	5
2. Health Physics Procedure for the Vibration Test of the Pioneer Source. . . . .	13
B. Test Run Summary Sheet. . . . .	17
C. Random Vibration Schedules. . . . .	19
D. Data Sheets . . . . .	21
E. Post-Test Inspection Comments . . . . .	63
F. Safety Sequential Test Documentation. . . . .	87
G. Radiographs and Photographs . . . . .	89

## ATTACHMENT A

### 1. ALPHA FUELS ENVIRONMENTAL TEST FACILITY

#### Fueled FSA Fixture Vibration Test Procedure

The fueled FSA fixture shall be subjected to a vibration environment to determine its ability to withstand the specified vibration levels and duration.

#### 1.0 Objectives

To evaluate the performance of an FSA under the LES 8/9 vibration environment, such as would be encountered during the powered flight phase of a Titan III C launch vehicle.

- a) Evaluate the effect of the clearance between the fuel sphere and the PISA (post-impact sphere assembly) on the integrity of the fuel sphere, particularly the production of fines resulting from exposure to a vibration environment.
- b) Evaluate the effect of the clearance between the fuel sphere and the PICS (post-impact containment shell) on the integrity of the iridium PICS.
- c) Evaluate the performance of the PISA vent after exposure to a vibration environment.
- d) Time permitting, evaluate the effect of clearance between the PISA and the Graphite Impact Shell.

#### 2.0 Scope

The fueled FSA fixture will be subjected to sinusoidal and random vibration in three orthogonal axes while in a simulated operational condition.

#### 3.0 Facilities and Equipment

##### 3.1 Test Fire Facility

3.1.1 Random Frequency Generator

3.1.2 XY Recorder



### 3.2 Alpha Fuels Facility

#### 3.2.1 M.B. Electronics

- 3.2.1.1 Shaker, Model C21
- 3.2.1.2 Exciter, Model 1025
- 3.2.1.3 Accelerometer, MB304
- 3.2.1.4 Liner Driver
- 3.2.1.5 Zero Drive Amplifier, N400

#### 3.2.2 Vibration Readout Equipment

- 3.2.2.1 XY Recorder Input Selector, MB N-74
- 3.2.2.2 Log Converter, Hewlett Packard, 7560 AM
- 3.2.2.3 XY Recorder, Hewlett Packard, 135
- 3.2.2.4 Oscilloscope, Tekronics
- 3.2.2.5 True RMS Voltmeter, Ballantine Lab M320
- 3.2.2.6 DC-AC Calibrator, Ballantine Lab M421A

#### 3.2.3 Functional Readout Equipment

- 3.2.3.1 Digital Voltmeter, Weston, 1240
- 3.2.3.2 Recorder, Bausch & Lomb, VOM5

#### 3.2.4 Miscellaneous Electrical Equipment

- 3.2.4.1 Volt-Ohm Meter, Simpson 260

#### 3.2.5 Hand Tools

- 3.2.5.1 Test Fixture Handling Gloves
- 3.2.5.2 Torque Wrench
- 3.2.5.3 Allen Wrench Set
- 3.2.5.4 Slip Table Wrench Set
- 3.2.5.5 Open End Wrench Set

### 3.3 Hardware

The following hardware will be utilized:

- Vibration Test Fixture - Drawing SK-D-2380, Figure 1, designed and fabricated by MRC.
- PuO<sub>2</sub> - Fueled PISA - S/N MHFT-11.
- ThO<sub>2</sub> - Simulated PISA - S/N MHT-3.
- Graphite Impact Shell - S/N 854134 (HITCO).
- Graphite Impact Shell - S/N Body 420 with Cap 415B (Sanders).
- Graphite Impact Shell - S/N Body 421 with Cap 416A (Sanders).

## 4.0 Overall Instructions

### 4.1 Handling

4.1.1 Lift the FSA fixture, using the handling gloves, properly held by the fins.

### 4.2 Operating

4.2.1 The rate of change in the fin root temperature should not exceed 33°F in 10 min.

4.2.2 The PISA temperature should not exceed 2100°F.

4.2.3 The fin root temperature should not exceed 360°F.

4.2.4 Record data at approximately 20 min intervals during generator instability, and note in log any irregularities. When temperatures are stable, 1-hr intervals are adequate.

4.2.5 The temperature is to be 1832°F - 2100°F during testing.

### 4.3 Abort Conditions

4.3.1 A PISA temperature exceeding 2100°F may require termination of the test.

4.3.2 A sudden decrease in output power will terminate the test until adjustments are made.

### 4.4 Health Physics

4.4.1 Health Physics documents and/or requirements will be considered a part of this procedure.

4.4.2 In the event of a spill or health physics hazard, the test is terminated and the health physics supervisor will assume command of the operation, others will assist in any way possible.

4.4.2.1 Primary consideration will be given to reduce further hazard.

4.4.2.2 Secondary consideration will be given to reduce damage and waste of equipment.

## 5.0 Pretest Procedure

5.1 Open log.

5.2 Record date, time, and serial number of parts and test section generator.

- 5.3 Make a general survey to determine that all facilities and equipment are ready to perform the required tests and that sufficient standards lab calibrations have been made to validate the tests.
- 5.4 Zero and calibrate the recorders used for temperature and power.
- 5.5 Accept the FSA fixture in hot hall behind the test cell.
- 5.6 Visually inspect fixture for good physical condition and make log notation.
- 5.7 Move fixture into cell and connect power and instrumentation.
- 5.8 Record data and note acceptable condition in log.

## 6.0 Test Plan and Sequence

### 6.1 Test 1 - Hot Thermal Checkout Bench Test (This is not a shake test)

This test uses simulated PISA S/N MHT-3 and graphite impact shell S/N Body 420 with Cap 415B.

- Heat-treat simulated (ThO<sub>2</sub>) PISA 1 hr at 1500°C according to specific instructions.
- Assemble simulated FSA in test fixture.
- Instrument PISA and fixture.
- Power up to 1832°F - 2100°F, as measured on the PISA, steady state.
- Record fixture and PISA temperatures after they reach steady state.
- Record power and temperature at several points as power is applied.
- Record temperature in accelerometer and shaker table mounting plate areas.
- Verify by post-test examination that preload and differential thermal expansion are acceptable.

### 6.2 Test 2 - Cold Dynamic Test

This test uses graphite impact shell S/N Body 421 with Cap 416A.

- Mount one accelerometer on fixture.
- Mount one accelerometer in metal simulated fuel core.

- Assemble simulated FSA in test fixture according to specific instructions.
- Perform both the sine sweep and random vibration test on two axes; the excluded axis is either one of the two symmetrical axes.
- Perform a 1-G sine sweep from 20 to 2000 Hz in 3 min.
- Perform the random vibration test spectrum, Schedule A.
- Verify by post-test examination the cold dynamic structural integrity of the fixture.

### 6.3 Test 3 - Hot Safety Test With Simulated FSA

This test uses simulated (ThO<sub>2</sub>) PISA S/N MHT-3 and graphite impact shell S/N Body 420 with Cap 415B (same as Test 1).

- Assemble simulated FSA in test fixture.
- Mount one accelerometer on fixture upper extremity.
- Mount one accelerometer on shaker mounting plate at bolt circle.
- Connect fixture and FSA thermocouples and instrument fixture external surface.
- Attain steady state FSA temperature of 1832°F - 2100°F.
- Perform a 1-G sine sweep similar to Test 2 on the same two axes.
- Perform the random vibration test spectrum, Schedule A, similar to Test 2 on the same two axes.
- Monitor thermocouples and heater power.
- Verify by post-test examination adequacy of fixture assembly.
- Retain assembled simulated FSA intact for future GE evaluation.

### 6.4 Test 4 - Fueled FSA Dynamic Test

This test uses PuO<sub>2</sub> fueled PISA S/N MHFT-11 and graphite impact shell S/N 854134.

- Heat-treat PISA 18 hr at 1500°C, according to specific directions.
- Open fueled PISA burst disk.
- Assemble fueled FSA.
- Assemble FSA in test fixture.

- Mount one accelerometer on fixture upper extremity similar to Test 3.
- Mount one accelerometer on shaker mounting plate similar to Test 3.
- Connect fixture thermocouples.
- Attain steady state FSA temperature of 1832°F - 2100°F.
- Perform the random vibration test spectrum, Schedule B, on x axis; and record response.
- Radiograph PISA, while in the fixture, through the PISA poles and at two points 90° apart through the equator.
- Attain required steady state temperature; perform the random vibration test, Schedule B, on y axis; and record response.
- Radiograph PISA, while in the fixture, through the PISA poles and at two points 90° apart through the equator.
- Attain required steady state temperature; perform the random vibration test, Schedule B, on the z axis; and record response.

## 7.0 Post-Test Procedure

- 7.1 Remove the FSA fixture from the vibration equipment.
- 7.2 Record in the log the results of a complete physical condition inspection.
- 7.3 Close out log, making comment as required.

### Post-Test Evaluation - Phase 1:

Performed at MRC:

- Remove FSA from fixture.
- Drill out FSA lock pin.
- Remove PISA from FSA.
- Swipe components for fuel release.
- Visually inspect components.
- Radiograph PISA through the poles and at two points 90° apart through the equator.
- Test PISA for helium leak.
- Reassemble PISA in FSA (using new lock pin).

- Ship fueled FSA intact (PuO<sub>2</sub> fueled PISA S/N MHFT-7 and Graphite Impact Shell S/N 854134) to LASL for post-test evaluation - Phase 2.
- Provide to GE for further independent evaluation the following hardware:
  - Simulated FSA intact (ThO<sub>2</sub> PISA S/N MHT-3 and Graphite Impact Shell S/N Body 420 with Cap 415B).
  - Graphite Impact Shell - S/N Body 421 with Cap 416A.




FIGURE 1 - Generator and pickup mounting.

Blank page

ATTACHMENT A

2. HEALTH PHYSICS PROCEDURE FOR THE VIBRATION TEST  
OF THE PIONEER SOURCE

Objective

The purpose of this procedure is to ensure good health physics precautions are used during the vibration test of the Pioneer Source and Generator.

- I. The building will be checked out by a health physics surveyor before the source is removed from the universal shipping container.
  - A) The air sample pump will be started and new air samples will be installed.
    - 1) The time the air samples are changed will be recorded.
    - 2) The changed air samples will be counted by the SM counting room for background reference.
  - B) The stack monitors will be checked out to ensure they are in operating condition.
    - 1) New filter media will be installed.
    - 2) The instruments will be set on the X1 scale, alarm at 50 counts/min, and the air flow at 40 liters/min.
  - C) The air monitors in the building will be checked with a source and set to operating levels.
- II. Cell 107 shall be prepared by the following:
  - A) Five to ten general wipes shall be taken throughout the cell to check for levels of contamination.
  - B) A plastic sheet shall be installed over the entrance to the cell to act as a contamination control barrier between the cell and the cell main door and operating Corridor 114.
  - C) Film badges shall be worn at all times by the operating personnel, and personnel working with the source will be issued wrist badges.



- D) Work shall be done in two-piece whites, safety shoes, and respirators (worn either in use or around the neck).
- E) The operating corridors will be treated as a yellow control zone.

III. The source will be monitored for unloading inside the cell.

- A) Gamma-neutron readings shall be taken on the generator at approximately those distances where personnel will be working.
- B) Wipes shall be taken on the generator to check for alpha contamination which may be present from a possible ruptured capsule.
- C) If no high levels of contamination are present, the capsule will be permitted to be prepared for the test. When the preparation of the capsule is completed, the personnel in the cell shall be checked for contamination upon their clothes and person before leaving the cell. After checkout, personnel shall leave the cell by the hole in the plastic barrier, and the plastic barrier shall be sealed and the cell main door shut.

IV. Before and during the test, health physics shall monitor the outside operating corridors by:

- A) Performing gamma-neutron surveys at the cell window and walls.
- B) Checking air samples in the corridors.
- C) Observing the air monitor inside the cell to notice any increase in the meter or the alarming of the monitor by the flashing of the red visual alarm if a release has occurred.
- D) Checking the air monitors in the corridors for increases on the meters and possible alarming.
- E) Taking spot wipes in the corridors to check contamination levels.

V. Upon reentry into the cell, the cell main door shall be opened and the plastic barrier shall be wiped on the outside to check for alpha contamination. The plastic barrier shall then be cut and wipes shall be taken on the inside of the plastic to check for contamination. If no, or low level, contamination is present, operating personnel shall be allowed to enter the cell for preparation of the capsule. General wipes shall be taken on the inside of the cell for contamination checks.

Exiting from the cell shall be in the same manner as prescribed in III.

- VI. If, during the preparation or testing of the source, the source should accidentally rupture, appropriate health physics actions shall be taken to protect all operating personnel from high levels of contamination, and the spread of contamination from the cell.
- VII. After the tests are completed on the source:
- A) All air samples shall be collected and counted.
  - B) Wipe surveys shall be taken of cell 107, the operating corridors and of all areas in the yellow control zone.
  - C) Records will be gathered and a report issued on the health physics aspects of the test.
- VIII. The source will be loaded into the shipping cask at the completion of the test. The health physics surveyor will take the necessary surveys to return the source into the shipping cask.

Blank page

ATTACHMENT B

MHW TEST RUN SUMMARY SHEET

TEST #	NAME	RUN #	PURPOSE	REMARKS
1	Bench Test	---	To validate vibration fixture temperature and structure capabilities.	After several runs Kanthal D (0.020) wire was final choice. Expansion was not a problem. See Temperature vs. Input Power Plot.
2	Dynamic	1-8	To validate vibration fixture dynamic strength capability and dynamic transfer functions.	No tape cal. signal on tape. <u>Random Schedule A.</u>
3	Electric Heater Hot Safety Test	9-10	To validate fixture safety and heater capability.	(1) Tape Cal. on tape but not satisfactory to GE. Heater burned out during run -- did not affect test. Heater wire was changed to Kanthal A-1 (0.051) and potted in with Dylon-C cement.  (2) <u>Random Schedule A.</u>

(1) GE wanted this test run while previous tapes were analyzed.

(2) GE wanted to re-run dynamic tests immediately.

MHW TEST RUN SUMMARY SHEET (Continued)

TEST #	NAME	RUN #	PURPOSE	REMARKS
2	Dynamic	11-19	Re-run of Dynamic runs using F.S. Tape Cal. & Added Accelerometer Data After Run 13.	Runs OK Per GE. <u>Random Schedule A</u>
3	Hot Safety and Elec. Heat	20-21	Re-run of Safety and Electric Heater Tests	Runs OK. <u>Random Schedule A</u>
4	Real Fuel Test	22-27	LES 8/9 Test on Fueled Capsule	Runs OK. <u>Random Schedule B</u>
2	Dynamic	28A-51A	Post Fueled Test Dynamic Test	More data desired by GE after above tests. <u>Random Schedule C.</u>
4	Safety Sequential	52-58	Launch Power Phase Vibration Input to FSA	Runs OK. <u>Random Schedule C</u>

ATTACHMENT C  
RANDOM VIBRATION SCHEDULES




FIGURE 2 - Random vibration test schedule A.




FIGURE 3 - Random vibration test schedule B & C.




FIGURE 4 - MHW Test #1.

ATTACHMENT D

VIBRATION DATA SHEET

DATE 9/26/72

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine  
.707 G's RMS 20-2000 HZ

RUN # 1  
Sine Z Axis

SERIAL # --  
 TEMPERATURE Room Temperature

EQUIPMENT MB

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1				MTG Plate	Servo
2			4	Metal Ball	300 grams simulated fuel ball
3			5	Graph - Same Axis	
4			6	Graph - Off Axis	



VIBRATION DATA SHEETDATE 9/26/72TEST PIECE DynamicVIBRATION SCHEDULE A, RandomRUN # 2SERIAL # --EQUIPMENT Test Fire

Random

Z Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1				MTG Plate	
2			4	Metal Ball	
3			5	Graphite - Same Axis	
4			6	Graph - Off Axis	




FIGURE 5 - Test #2, Run #2 (Sept. 26, 1972).

VIBRATION DATA SHEETDATE 10/2/72TEST PIECE DynamicVIBRATION SCHEDULE Sine  
.707 G's RMS 20-2000 HZRUN # 3SERIAL # ---

EQUIPMENT \_\_\_\_\_

Sine X Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1				MTG Plate	Servo
2			4	Metal Ball	
3			5	Graph - Same Axis	
4			6	Graph - Off Axis	

VIBRATION DATA SHEET

DATE 10/2/72

TEST PIECE Dynamic

VIBRATION SCHEDULE A, Random

RUN # 4

SERIAL # ---

EQUIPMENT Test Fire

Random X Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1				MTG Plate	Servo
2		4		Metal Ball	
3		5		Graph - Same Axis	
4		6		Graph - Off Axis	




FIGURE 6 - Test #2, Run #4 (Oct. 2, 1972).

VIBRATION DATA SHEET

DATE 10/4/72

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine

.707 G's RMS 20-2000 HZ

RUN # 5

SERIAL # --

EQUIPMENT M.B.

Sine Z Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1				MTG Plate	Servo
2	.92	30	4	Metal Ball	
3	.94	30	5	Graphite - Same Axis	
4	.93	30	6	Graph - Off Axis	

VIBRATION DATA SHEETDATE 10/4/72TEST PIECE DynamicVIBRATION SCHEDULE A, RandomRUN # 6SERIAL # --EQUIPMENT Test Fire

Random Z Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1				MTG Plate	Servo
2	.92	100	4	Metal Ball	
3	.94	100	5	Graph - Same Axis	
4	.93	100	6	Graph - Off Axis	




FIGURE 7 - Test #2, Run #6 (Oct. 4, 1972).



VIBRATION DATA SHEETDATE 10/5/72TEST PIECE DynamicVIBRATION SCHEDULE Sine  
.707 G's **RMS** 20-2000 HZRUN # 7SERIAL # --EQUIPMENT M.B.

Sine X Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1				MTG Plate	Servo
2	.92	30	4	Metal Ball	
3	.94	30	5	Graph - Same Axis	
4	.93	30	6	Graph - Off Axis	

VIBRATION DATA SHEET

DATE 10/5/72 TEST PIECE Dynamic VIBRATION SCHEDULE A, Random

RUN # 8 SERIAL # -- EQUIPMENT Test Fire

Random X Axis TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1				MTG Plate	Servo
2	.92	100	4	Metal Ball	
3	.94	100	5	Graph - Same Axis	
4	.93	100	6	Graph - Off Axis	




FIGURE 8 - Test #2, Run #8 (Oct. 5, 1972).

VIBRATION DATA SHEET

DATE 10/16/72

TEST PIECE ThO<sub>2</sub>  
Electric Heat

VIBRATION SCHEDULE Sine  
.707G's RMS 20-2000 HZ

RUN # 9

SERIAL # --

EQUIPMENT M.B.

Sine X Axis TEMPERATURE 1000°C

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1				MTG Plate	Servo
2				MTG Plate @ 180°	

VIBRATION DATA SHEETDATE 10/16/72TEST PIECE ThO<sub>2</sub>  
Electric HeatVIBRATION SCHEDULE A, RandomRUN # 10

SERIAL # \_\_\_\_\_

EQUIPMENT Test Fire

Random X Axis

TEMPERATURE 1000°C

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1				MTG Plate	Servo
2				MTG Plate @ 180°	

VIBRATION DATA SHEET

DATE 11/8/72

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine

.707 G's RMS 20-2000 HZ

RUN # 11

SERIAL # --

EQUIPMENT M.B.

Sine Z Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	3	4	MTG Plate	
2	3	3	5	Metal Ball	
3	3	3	6	Graph - Same Axis	

VIBRATION DATA SHEETDATE 11/8/72TEST PIECE DynamicsVIBRATION SCHEDULE SineRUN # 12SERIAL # --

.707 G's RMS 20-2000 HZ

EQUIPMENT M.B.

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	10	4	MTG Plate	Servo
2	3	10	5	Metal Ball	
4	3	10	6	Graph - Off Axis	

VIBRATION DATA SHEET

DATE 11/8/72 TEST PIECE Dynamic VIBRATION SCHEDULE A, Random  
 RUN # 13 SERIAL # -- EQUIPMENT Test Fire  
 Random Z Axis TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG Plate	
2	3	100	5	Metal Ball	
3	3	100	6	Graph - Same Axis	
1A				MTG Plate @ 180°	Servo






FIGURE 9 - Test #2, Run #13 (Nov. 8, 1972).

VIBRATION DATA SHEET

DATE 11/9/72

TEST PIECE Dynamic

VIBRATION SCHEDULE A, Random

RUN # 15

SERIAL # --

EQUIPMENT Test Fire

Random Z Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG Plate	
2	3	100	5	Metal Ball	
4	3	100	6	Graph - Off Axis	
1A					Servo




FIGURE 10 - Test #2, Run #15 (Nov. 9, 1972).

VIBRATION DATA SHEET

DATE 11/10/72

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine

RUN # 16

SERIAL # --

.707 G's RMS20-2000 HZ

EQUIPMENT M.B.

Sine X Axis      TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	10	4	MTG Plate	
2	3	10	5	Metal Ball	
3	3	10	6	Graph - Same Axis	

VIBRATION DATA SHEETDATE 11/10/72TEST PIECE DynamicVIBRATION SCHEDULE SineRUN # 17SERIAL # --.707 G's RMS 20-2000 HZEQUIPMENT M.B.

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Sine	X Axis			
	TEMPERATURE		Room Temperature		
1	3	10	4	MTG Plate	Servo
2	3	10	5	Metal Ball	
4	3	10	6	Graph - Off Axis	

VIBRATION DATA SHEET

DATE 11/10/72

TEST PIECE Dynamic

VIBRATION SCHEDULE A, Random

RUN # 18

SERIAL # - -

EQUIPMENT Test Fire

Random X Axis TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG Plate	
2	3	100	5	Metal Ball	
3	3	100	6	Graph - Same Axis	
1A				MTG Plate @ 180°	Servo




FIGURE 11 - Test #2, Run #18 (Nov. 10, 1972).

VIBRATION DATA SHEET

DATE 11/10/72

TEST PIECE Dynamic

VIBRATION SCHEDULE A, Random

RUN # 19

SERIAL # --

EQUIPMENT Test Fire

Random X Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG Plate	
2	3	100	5	Metal Ball	
4	3	100	6	Graph - Off Axis	
1A				MTG Plate @ 180°	Servo ToTF






FIGURE 12 - Test #2, Run #19 (Nov. 10, 1972).

VIBRATION DATA SHEET

DATE 11/22/72

TEST PIECE ThO<sub>2</sub>

VIBRATION SCHEDULE Sine  
.707 G's RMS 20-2000 HZ

RUN # 20

SERIAL # --

EQUIPMENT M.B.

Sine X Axis TEMPERATURE 1000°C

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1				MTG Plate	Servo
2	3	10	4	Same @ 180°	
3	3	10	5	Fix. Top - Same Axis	
4	3	10	6	Fix. Top - Off Axis	

VIBRATION DATA SHEETDATE 11/22/72TEST PIECE ThO<sub>2</sub>VIBRATION SCHEDULE A, RandomRUN # 21SERIAL # --EQUIPMENT Test Fire, M.B.

Random X Axis TEMPERATURE 1000°C

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1				MTG Plate	Servo
2	3	100	4	Same @ 180°	
3	3	100	5	Fix. Top - Same Axis	
4	3	100	6	Fix. Top - Off Axis	




FIGURE 13 - Test #2, Run #21 (Nov. 22, 1972).

VIBRATION DATA SHEETDATE 12/9/72TEST PIECE Real FSAVIBRATION SCHEDULE Sine .707 RMS  
20-2000 cpsRUN # 22SERIAL # MHFT-11EQUIPMENT M.B.

Sine Z Axis

TEMPERATURE 1000°C

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1		10	--	MTG Plate	Servo Accel.
2	3	10	4	Same Above @ 180°	
3	3	10	5	Fix. Top - Same Axis	
4	3	10	6	Fix. Top - Off Axis	




FIGURE 14 - Sine Run #22 (Dec. 9, 1972).

VIBRATION DATA SHEETDATE 12/9/72TEST PIECE Real FSAVIBRATION SCHEDULE E, RandomRUN # 23SERIAL # MHFT-11EQUIPMENT Test Fire - M.B.

Random Z Axis

TEMPERATURE 1000°C

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1		100	--	MTG Plate	Servo Accel.-T.F.
2	3	100	4	Same Above @ 180°	
3	3	100	5	Fix. Top - Same Axis	
4	3	100	6	Fix. Top - Off Axis	




FIGURE 15 - Actual Run #23 (Dec. 9, 1972).



VIBRATION DATA SHEETDATE 12/14/72TEST PIECE Real FSAVIBRATION SCHEDULE Sine .707 G's RMS  
20-2000 HZRUN # 24SERIAL # MHFT-11EQUIPMENT M.B.

Sine X Axis

TEMPERATURE 1000°C

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1		10	--	MTG Plate	Servo
2	3	10	4	Same @ 180°	
3	3	10	5	Fix. Top - Same Axis	
4	3	10	6	Fix. Top - Off Axis	




FIGURE 16 - Sine Run #24, x axis (Dec. 14, 1972).

VIBRATION DATA SHEETDATE 12/14/73TEST PIECE Real FSAVIBRATION SCHEDULE E, RandomRUN # 25SERIAL # MHFT-11EQUIPMENT Test Fire

Random X Axis

TEMPERATURE 1000°C

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1		-	-	MTG. Plate	Servo
2	3	100	4	Same @ 180°	
3	3	100	5	Fix. Top - Same Axis	
4	3	100	6	Fix. Top - Off Axis	




FIGURE 17 - Actual Run #25 (Dec. 14, 1972).

VIBRATION DATA SHEETDATE 12/15/72TEST PIECE Real FSAVIBRATION SCHEDULE Sine - .707 G's  
RMS 20-2000 HZRUN # 26SERIAL # MHFT-11EQUIPMENT M.B.

Sine Y Axis

TEMPERATURE 1000°C

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1		-	-	MTG Plate	Servo
2	3	10	4	Same @ 180°	
3	3	10	5	Fix. Top - Same Axis	
4	3	10	6	Fix. Top - Off Axis	




FIGURE 18 - Sine Run #26, y axis (Dec. 15, 1972).

VIBRATION DATA SHEETDATE 12/15/72TEST PIECE Real FSAVIBRATION SCHEDULE E, RandomRUN # 27SERIAL # MHFT-11EQUIPMENT Test Fire - M.B.

Random Y Axis

TEMPERATURE 1000°C

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1			-	MTG. Plate	Servo
2	3	100	4	Same @ 180°	
3	3	100	5	Fix. Top - Same Axis	
4	3	100	6	Fix. Top - Off Axis	




FIGURE 19 - Actual Run #27 (Dec. 15, 1972).



Blank page

ATTACHMENT E  
POST-TEST INSPECTION COMMENTS

Date: 12-19-72

RADIOGRAPHIC INSPECTION REPORT  
ITEM: MULTIHUNDRED WATT SPHERE

The sphere was radiographed at 0°, 90°, and pole to inspect for condition of the sphere after tests.

Inspection results are as follows:

MHFT-11

- (1) The sphere appears to be broken into three or four major sections with several smaller pieces.
- (2) No indication of any appreciable amount of fine material in fuel cavity.
- (3) No apparent damage to sphere encapsulation.

NOTE: Before tests, radiographs indicated three to five cracks in the sphere 0.3 in. to 0.7 in. in length but the sphere appeared to be intact.

Inspected by: \_\_\_\_\_

Applied Technology, TR-27

January 3, 1973

Telephone Conversation Between  
C. O. Brewer and R. N. R. Mulford  
of LASL

S. G. Abrahamson

Mr. Mulford called to give the preliminary visual observations of MHFT-11, the vibration test capsule. He said that the inside of the iridium was very clean with no visual black deposit. The only damage noted was the weld shield bond had broken away at the tack welds.

The fuel sphere was broken into eight (8) pieces, five (5) large and three (3) small; however, no fines had been determined to date.

C. O. Brewer

COB:tr

VIBRATION DATA SHEET

DATE 2/5/73

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine

RUN # 28A

SERIAL # \_\_\_\_\_

.707 G RMS 20-2000 HZ  
EQUIPMENT M.B.

Sine      Z Axis      TEMPERATURE      Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3.0	10	4	MTG. Plate	Servo
2	3.0	10	5	Metal Ball	
3	3.0	10	6	Graph - Same Axis	
5	3.0	10	7	Fix. Top - Same Axis	

VIBRATION DATA SHEETDATE 2/5/73 TEST PIECE Dynamic VIBRATION SCHEDULE RandomRUN # 29A SERIAL # \_\_\_\_\_ EQUIPMENT Test Fire

	Random	Z Axis	TEMPERATURE	Room Temperature		
ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS	
	Volts	G's				
1	3	100	4	MTG. Plate		
2	3	100	5	Metal Ball		
3	3	100	6	Graph - Same Axis		
5	3	100	7	Fix. Top - Same Axis		
T.F.						Servo

VIBRATION DATA SHEET

DATE 2/6/73

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine  
.707 G RMS 20-2000 HZ

RUN # 30A

SERIAL # \_\_\_\_\_

EQUIPMENT M.B.

Sine Z Axis

TEMPERATURE

Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	10	4	MTG. Plate	Servo
2	3	10	5	Metal Ball	
4	3	10	6	Graph - Off Axis	
6	3	10	7	Fix. Top - Off Axis	

VIBRATION DATA SHEETDATE 2/6/73TEST PIECE DynamicVIBRATION SCHEDULE RandomRUN # 31A

SERIAL # \_\_\_\_\_

EQUIPMENT Test Fire

Random    Z Axis    TEMPERATURE    Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG. Plate	
2	3	100	5	Metal Ball	
4	3	100	6	Graph - Off Axis	
6	3	100	7	Fix. Top - Off Axis	
T.F.					Servo

VIBRATION DATA SHEET

DATE 2/7/73

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine

RUN # 34A

SERIAL # \_\_\_\_\_

EQUIPMENT .707 G RMS 20-2000 HZ  
M.B.

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	10	4	MTG. Plate	Servo
2	3	10	5	Metal Ball	
4	3	10	6	Graph - Off Axis	
6	3	10	7	Fix. Top - Off Axis	



VIBRATION DATA SHEETDATE 2/7/73TEST PIECE DynamicVIBRATION SCHEDULE RandomRUN # 35ASERIAL # --EQUIPMENT Test Fire M.B.

X Axis OFF Axis Accels. TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG. Plate	MHW Fixture
2	3	100	5	Metal Ball	
4	3	100	6	Graph - Off Axis	Chan. 6 Clipping Data
6	3	100	7	Fixture Top - off Axis	
T.F.					Servo

VIBRATION DATA SHEET

DATE 2/8/73

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine

.707 G RMS 20-2000 HZ

RUN # 36A

SERIAL # \_\_\_\_\_

EQUIPMENT M.B.

Sine X Axis

TEMPERATURE

Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	10	4	MTG. Plate	Repeat of 32A
2	3	10	5	Metal Ball	
3	3	10	6	Graph - Same Axis	
5	3	10	7	Fix. Top - Same Axis	

VIBRATION DATA SHEETDATE 2/8/73 TEST PIECE Dynamic VIBRATION SCHEDULE RandomRUN # 37A SERIAL # \_\_\_\_\_ EQUIPMENT Test Fire M.B.

X Axis

Same Axis Accels. TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG. Plate	MHW Fixture
2	3	100	5	Metal Ball	
3	3	300	6	Graph - Same Axis	Chan. 6 Clipping Data
5	3	100	7	Fix. Top - Same Axis	
T.F.					Servo

VIBRATION DATA SHEET

DATE 2/14/73

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine

.707 G RMS 20-2000 HZ

RUN # 38A

SERIAL # \_\_\_\_\_

EQUIPMENT M.B.

Sine . X Axis

TEMPERATURE

Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	10	4	MTG. Plate	Servo
2	3	10	5	Metal Ball	
3	3	100	6	Graph - Same Axis	
5	3	10	7	Fix. Top - Same Axis	

VIBRATION DATA SHEETDATE 2/14/73TEST PIECE DynamicVIBRATION SCHEDULE RandomRUN # 39ASERIAL # -EQUIPMENT Test Fire M.B.

X Axis Same Axis Accels. TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG. Plate	MHW Fixture
2	3	100	5	Metal Ball	
3	3	1000	6	Graph - Same Axis	
5	3	100	7	Fix. Top - Same Axis	
T.F.					

VIBRATION DATA SHEET

DATE 2/14/73

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine

RUN # 40A

SERIAL # \_\_\_\_\_

.707 G RMS 20-2000 HZ  
EQUIPMENT M.B.

Sine X Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	10	4	MTG. Plate	Servo
2	3	10	5	Metal Ball	
4	3	100	6	Graph - Off Axis	
6	3	10	7	Fix. Top - Off Axis	

VIBRATION DATA SHEET

DATE 2/15/73 TEST PIECE Dynamic VIBRATION SCHEDULE Random  
 RUN # 41A SERIAL # \_\_\_\_\_ EQUIPMENT Test Fire M.B.

X Axis Off Axis Accels. TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG. Plate	MHW Fixture
2	3	100	5	Metal Ball	
4	3	1000	6	Graph - Off Axis	
6	3	100	7	Fix. Top - Off Axis	
T.T.					

VIBRATION DATA SHEET

DATE 2/15/73

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine

RUN # 42A

SERIAL # \_\_\_\_\_

EQUIPMENT .707 G RMS 20-2000 HZ  
M.B.

Sine Z Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	10	4	MTG. Plate	Servo
2	3	10	5	Metal Ball	
3	3	100	6	Graph - Same Axis	
5	3	10	7	Fix. Top - Same Axis	



VIBRATION DATA SHEET

DATE 2/15/73 TEST PIECE Dynamic VIBRATION SCHEDULE Random  
 RUN # 43A SERIAL # \_\_\_\_\_ EQUIPMENT Test Fire M.B.  
 Z Axis  
 Same Axis Accels. TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG. Plate	MHW Fixture
2	3	100	5	Metal Ball	
3	3	1000	6	Graph - Same Axis	
5	3	100	7	Fix. Top - Same Axis	
T.F.					

VIBRATION DATA SHEET

DATE 2/15/73

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine

RUN # 44A

SERIAL # \_\_\_\_\_

EQUIPMENT .707 G RMS 20-2000 HZ  
M.B.

Sine Z Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	10	4	MTG. Plate	Servo
2	3	10	5	Metal Ball	
4	3	100	6	Graph - Off Axis	
6	3	10	7	Fix. Top - Off Axis	

VIBRATION DATA SHEETDATE 2/15/73TEST PIECE DynamicVIBRATION SCHEDULE RandomRUN # 45ASERIAL # --EQUIPMENT Test Fire M.B.Z Axis  
Off Axis Accels.TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG. Plate	MHW Fixture
2	3	100	5	Metal Ball	
4	3	1000	6	Graph - Off Axis	
6	3	100	7	Fix. Top - Off Axis	
T.F.					

VIBRATION DATA SHEET

DATE 4/17/73

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine  
~~.707 G RMS 20-2000 HZ~~

RUN # 48A

SERIAL # \_\_\_\_\_

EQUIPMENT M.B.

Sine Z Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	10	4	MTG. Plate	Servo
2	3	10	5	Metal Ball	
3	3	10	6	Graph - Off Axis	
4	3	10	7	Fix. Top - Off Axis	
					Repeat of 46A

VIBRATION DATA SHEETDATE 4/17/73TEST PIECE DynamicVIBRATION SCHEDULE RandomRUN # 49A

SERIAL # \_\_\_\_\_

EQUIPMENT T/D

Z Axis

Off Axis Accels. TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG. Plate	MHW Fixture
2	3	100	5	Metal Ball	
3	3	100	6	Graph - Off Axis	
4	3	100	7	Fix. Top - Off Axis	
T/D					Servo This run a repeat of 47A which had 60 HZ noise.

VIBRATION DATA SHEET

DATE 4/17/73

TEST PIECE Dynamic

VIBRATION SCHEDULE Sine  
~~.707 G RMS 20-2000 HZ~~

RUN # 50A

SERIAL # \_\_\_\_\_

EQUIPMENT M.B.

Sine Z Axis

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	10	4	MTG. Plate	
2	3	10	5	Metal Ball	
3	3	10	6	Graph - Same Axis	
4	3	10	7	Fix. Top - Same Axis	

VIBRATION DATA SHEETDATE 4/17/73TEST PIECE DynamicVIBRATION SCHEDULE RandomRUN # 51A

SERIAL # \_\_\_\_\_

EQUIPMENT T/D

Z Axis

Same Axis Accels.

TEMPERATURE Room Temperature

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
1	3	100	4	MTG. Plate	Servo
2	3	100	5	Metal Ball	
3	3	100	6	Graph - Same Axis	
4	3	100	7	Fix. Top - Same Axis	
T/D					

VIBRATION DATA SHEET

DATE 4/30/73  
thru 5/25/73  
 RUN # 52 thru 58

TEST PIECE FSA  
 SERIAL # MHFT-25  
thru -31  
 TEMPERATURE 1000°C

VIBRATION SCHEDULE C. Random  
 EQUIPMENT T/D

ACCELEROMETER	FULL SCALE		RECORDER CHANNEL	ACCEL. LOCATION	REMARKS
	Volts	G's			
#5 to T/D via Endeveco Chg. Ampl.	--	10	--	MTG. Plate	8.704 G's RMS
#1 to M.B. N 400 Ampl.	--	30	--	MTG. Plate @ 180°	



Blank page

ATTACHMENT F

SAFETY SEQUENTIAL TEST DOCUMENTATION

RANDOM SCHEDULE C  
MHFT-25 THROUGH -31

1  
1 BANDWIDTH, HZ.: 2048  
2 FREQUENCY RESOLUTION 64/128/256: 128  
FREQUENCY INCREMENT, HZ.: 16

REFERENCE SPECTRUM:

3 INITIAL SLOPE DB/OCT: 3  
4 FREQUENCY HZ.: 16  
LEVEL GSQR/HZ.: 0.0165  
5 FREQUENCY HZ.: 256  
LEVEL GSQR/HZ.: 0.216  
6 FREQUENCY HZ.: 336  
LEVEL GSQR/HZ.: 0.216  
7 FREQUENCY HZ.: 448  
LEVEL GSQR/HZ.: 0.01  
8 FREQUENCY HZ.: 608  
LEVEL GSQR/HZ.: 0.01  
9 FREQUENCY HZ.: 992  
LEVEL GSQR/HZ.: 0.024  
10 FREQUENCY HZ.: 1296  
LEVEL GSQR/HZ.: 0.024  
11 FINAL SLOPE DB/OCT: 12  
ACCEL. LEVEL, GRMS = 8.704  
12 START UP TIME SEC: 3  
13 SHUT DOWN TIME SEC: 3  
14 TEST TIME HRS, MIN, SEC: 0 3 0  
15 3 SIGMA CLIPPING 1=YES 0=NO: 1

CORRECTIONS 1=YES 0=NO: 0

LIST 1=YES 0=NO: 1






FIGURE 20 - Random run for MFFT-30, typical for MFFT-25 to 31.

ATTACHMENT G


RADIOGRAPHS AND PHOTOGRAPHS




MHFT-25  
0° View



MHFT-25  
90° View



MHFT-26  
0° View




MHFT-26  
90° View


FIGURE 21 - Radiographs of safety sequential test capsules MHFT-25 and -26 after vibration.




MHFT-27  
0° View



MHFT-27  
90° View




MHFT-28  
0° View




MHFT-28  
90° View


FIGURE 22 - Radiographs of safety sequential test capsules MHFT-27 and -28 after vibration.




MHFT-29  
0° View



MHFT-29  
90° View




MHFT-30  
0° View




MHFT-30  
90° View

FIGURE 23 - Radiographs of safety sequential test capsules MHFT-29 and -30 after vibration.



730966


MHFT-31  
0° View




730967

MHFT-31  
90° View

FIGURE 24 - Radiographs of safety sequential test capsule MHFT-31 after vibration.



*FIGURE 25 - MHW vibration test fixture.*



*FIGURE 26 - C-21 vibration shaker.*






FIGURE 27 - Lid for vibration fixture graphite container.




FIGURE 28 - FSA installed in vibration fixture container.