AERIAL RADIOLOGICAL MEASURING SURVEY OF THE AREA SURROUNDING THE MILLSTONE NUCLEAR POWER STATION, WATERFORD, CONNECTICUT, AUGUST 29 AND SEPTEMBER 11, 1969

EG&G, Inc., Las Vegas, Nevada

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

This report is part of a series on the continuing activities of the Aerial Radiological Measuring System operated for the U. S. Atomic Energy Commission. The ARMS program is managed by the Division of Operational Safety and is a cooperative effort among various offices and divisions of the Commission.

Issuance Date: May 1974

Published by
Technical Information Center, Office of Information Services
UNITED STATES ATOMIC ENERGY COMMISSION

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

WORK PERFORMED BY

Analyst - Navigator

M. D. Severt

Instrumentation Specialist

W. G. Markland

Pilot

E. Raschke

ABSTRACT

The Aerial Radiological Measuring System (ARMS) was used to survey the area surrounding the Millstone Nuclear Power Station during August 1969. The survey measured terrestrial background gamma radiation.

A high-sensitivity detection system collected gamma-ray spectral and gross-count data. The data were then computer processed into a map of a 450 square mile area showing isoexposure contours three feet above the ground. Exposure rates and isotopes identified are consistent with normal terrestrial background.

ACKNOWLEDGMENTS

Special appreciation is given to L. J. Deal (Assistant Director, DOS/Health Protection, USAEC) and to Dr. Charles Pelletier (Chief, Environmental Inspection Branch, Regulatory Operations, USAEC) for their support and encouragement in this program.

CONTENTS

1.	INTRODUCTION	1
1.1	Identification of Surveyed Plant and Area . . .	1
1.2	ARMS Program.	1
1.3	ARMS Equipment and Procedures.	1
1.4	Reduction and Presentation of Data	4
2.	REACTOR AND SITE CHARACTERISTICS.	5
2.1	Reactor Characteristics.	5
2.2	Site Area Characteristics	5
3.	SURVEY PLAN	7
3.1	Specification of Flight Lines	7
3.2	Coordination with Local Authorities	7
4.	RADIOLOGICAL SURVEY	8
4.1	Survey Missions	8
4.2	Gross-Count Data	8
4.3	Spectral Data	8
5.	SUMMARY AND CONCLUSIONS	12

1. INTRODUCTION

1.1 Identification of Surveyed Plant and Area

The Aerial Radiological Measuring System (ARMS) (Ref. 1) operated by EG&G, Inc., Las Vegas, Nevada, for the U. S. Atomic Energy Commission was used to survey an extensive area surrounding the Millstone Nuclear Power Station during August 1969, prior to reactor start-up. The Millstone station is located near Waterford, Connecticut. The size of the survey area was 450 square miles.

1.2 ARMS Program

The present survey was made as part of a continuing nationwide ARMS program started in 1958 to monitor radiation levels surrounding facilities producing or utilizing radioactive materials. This is the first such survey performed in the Millstone area.

The detection system on board the aircraft collects gamma-ray gross-count and spectral data on each flight line of the survey. The gamma radiation and aircraft position information are processed by a computer into an isoexposure contour map of the area surveyed.

1.3 ARMS Equipment and Procedures

The ARMS aircraft and its on-board radiation detection equipment were used in the survey. Since the ARMS equipment and procedures have been discussed in detail elsewhere (Ref. 1), they will only be described briefly here.

The ARMS surveys are flown in a Beechcraft Twin Bonanza at an altitude of 300 to 500 feet above ground level at a ground speed of about 140 knots (235 ft/sec). The ground position of the aircraft and its altitude above terrain are measured and recorded every other second by a radar navigation computer system. The position and altitude measurements are accurate to ± 350 ft and ± 5 ft, respectively.

A typical flight pattern consists of a series of parallel lines spaced one nautical mile (6080 feet) apart, covering all of the land area within a twelve and one-half nautical mile radius of the facility.

At an altitude of 300 feet, the field of view of the detectors is approximately 1/4 mile wide for a mean gamma energy of naturally occurring isotopes.

The aerial radiation measurements are of two distinct types, made simultaneously: (1) gross gamma count (intensity) measurements and (2) gamma spectral measurements. The detector system consists of an array of fourteen 4x4 in. NaI (Tl) scintillation crystals, each coupled to its own photomultiplier assembly. The detector system output is directed both to the gross gamma count computing system and to the multichannel spectrum analyzer. The data collecting system is shown in Figure 1.

The gross gamma count system consists of an amplifier-discriminator-computer unit that counts and records the total number of gamma-rays of energy greater than 50 keV that are detected during a 1-second time interval. The gross gamma count rate (number of gamma-rays detected per second) is digitally recorded along with aircraft position and altitude every other second. Aircraft position data are supplied by a track navigational computer and doppler radar. Altitude above terrain is measured with a radar altimeter. As a backup and complement to the digital recording of the gross-count data, a record is made on a continuous strip chart of both gross gamma count rate and radar altitude as a function of distance. Typical gross-count rates for natural background are several thousand per second.

Whereas the gross gamma count data specify the intensity of radiation as a function of position, the gamma spectral data are useful in identifying particular radioactive isotopes. A pulse-height analyzer automatically sorts detected gamma-rays according to energy, thereby generating a number per unit-energy versus energy spectrum. Although gamma rays occur only at well known discrete energies characteristic of the emitting species, air scattering tends to smear the detected distribution. Nevertheless, the characteristic peaks that permit isotope identification are readily observable. In wide area surveys the typical acquisition time for a gamma-ray spectrum is several minutes; thus, the spectrum represents the average radiological properties of a tract several miles in length. However, if an area of interest is indicated by an increase in the gross gamma count rate, spectral data acquisition times of only a few seconds are used to isolate the area spatially. If further investigation is warranted, a ground mobile unit with equipment similar to that in the aircraft is available to provide greater spatial and energy resolution.

FIGURE 1. View of the interior of the Aerial Radiological Measuring System (ARMS) aircraft showing detector package and electronic data collection system.

In addition to the equipment just described, the ARMS aircraft also carries an air sampling and analysis system for the measurement of airborne radioactivity.

1.4 Reduction and Presentation of Data

The raw data from the gross gamma count and the gamma spectral measurements are permanently recorded on paper tape, which is computer processed and analyzed to characterize the radiological properties of the area surveyed. Using an altitude-dependent conversion factor obtained from prior calibration measurements, the raw gross-count rate is converted to exposure rate ($\mu\text{R/hr}$) at three feet above ground.

The exposure rate conversion factor was obtained from repeated flights 200 to 1000 feet above terrain containing known distributions of natural isotopes. Such conversion factors have proved valid over distributed fission product fields, with a variation of less than 25%. In practice, variations of 2 $\mu\text{R/hr}$ or greater can be reliably observed in repeated flights over the same area.

2. REACTOR AND SITE CHARACTERISTICS

2.1 Reactor Characteristics

The Millstone Reactor is located in New London County, Connecticut, two miles south of Waterford.

The principal nuclear contractor is the General Electric Company. The facility is operated by the Connecticut Light and Power Company, the Hartford Electric Light Company, and the Western Massachusetts Electric Company.

Table 1 gives the specifications of the reactor facility at the time of the survey. The reactor had not yet commenced operating.

TABLE 1. Reactor facility specifications.

Reactor Unit	Reactor Type	Start-Up Date	Power Levels (Megawatts)		Status
			Electrical	Thermal	
1	Boiling Water	1970	652	2, 011	Pre-operational

2.2 Site Area Characteristics

The area surrounding the reactor site is hilly and covered by vegetation. Two major rivers, the Connecticut and the Thames, run through the area. The region contains numerous small streams, lakes, and swamps.

Table 2 lists the towns in the survey area with significant populations, by distance and direction from the reactor site.

TABLE 2. Population distribution within the Millstone Power Station area.

Town	Direction from Power Station	Population*		
		Distance from Station (Miles)		
		0 - 5	5 - 10	10 - 15
Deep River	NW			3,690
Essex	WNW			4,911
Fenwick	WSW			45
Groton	NE		38,523	
Groton Borough	NE		8,933	
Ledyard	NE			14,558
Lyme	NW	1,484		
Mantic	NW	3,422		
Montville	N		15,662	
Mystic	E			2,568
New London	ME	31,630		
Old Lyme	W		4,964	
Old Saybrook	W			8,468
Poquonock Bridge	ENE		3,165	
Salem	NNW			1,453
Stonington	E			15,940
Uncasville	NNE		1,750	
Waterford	N	17,227		
West Mystic	E			3,694
Westbrook	W			3,820
Totals		53,763	72,997	59,147
Grand Total		185,907		

* 1970 census figures (Ref. 2).

3. SURVEY PLAN

3.1 Specification of Flight Lines

The flight pattern for the Millstone survey consisted of 25 flight lines approximately 10 to 12 nautical miles long and spaced one nautical mile apart. The flight lines were oriented in a north-south direction. Radiation data together with aircraft position and meteorological information were collected along each flight line.

3.2 Coordination with Local Authorities

ARMS survey missions are conducted under special waiver from the Federal Aviation Administration. The survey plan was discussed with the appropriate General Aviation District Office, and public announcements were published in the local newspapers prior to the survey operation in accordance with the FAA waiver for low-level flights.

The base of operations for the survey mission was Springfield, Massachusetts.

4. RADIOLOGICAL SURVEY

4.1 Survey Missions

The aerial survey of the Millstone Reactor area was conducted on 29 August and 11 September 1969. This survey required a total flying time of 6.4 hours.

Gross-count and spectral data were simultaneously collected at an altitude of 300 feet. Spectra were accumulated over a 4 minute interval during which the aircraft traveled approximately 12 miles; consequently, one spectrum per line was collected.

4.2 Gross-Count Data

As a first step in the analysis of the gross-count data, the background due to nonterrestrial radiation was subtracted. This background consists of cosmic-ray, aircraft, and airborne radioactivity contributions (Ref. 3). After correction for background, the data were normalized to a standard air mass. The resultant net-count data were then converted to exposure rate in microroentgens per hour ($\mu\text{R/hr}$) at the 3-foot level above the ground. The cosmic-ray exposure rate was then added back to the terrestrial exposure rate. Finally, the composite exposure rate data, together with aircraft position information, were processed into an isoexposure contour map for overlay on U. S. Geological Survey topographic maps of the survey area.

An isoexposure map of the Millstone area is shown in Figure 2. The data shown on the map include a cosmic radiation contribution of 2 to 4 $\mu\text{R/hr}$. Spatial resolution of the exposure rate data is determined by the field of view of the detector system, which is about 1/4 mile.

4.3 Spectral Data

Spectral data were recorded from about 0.03 to 3.0 MeV. The recording system was calibrated prior to takeoff with an yttrium-88 source, which emits two prominent gamma-rays of 0.898 and 1.836 MeV. The gain for each crystal in the 14-crystal detector array was set independently.

BASE FROM USGS TOPOGRAPHIC MAP SCALE 1:250,000

Figure 2.

EXPOSURE RATE CONTOURS,
MILLSTONE NUCLEAR POWER STATION,
CONNECTICUT, AUGUST 1969

2-4 μ R/hr

4-6 μ R/hr

6-8 μ R/hr

8-10 μ R/hr

10-12 μ R/hr

12-14 μ R/hr

A spectrum typical of those taken during the survey is shown in Figure 3. Table 3 lists the prominent gamma-ray energies and associated source isotopes identified in the spectrum. Differences in shape between spectra taken over different portions of the survey area are minor, and the isotopes identified in all spectra are the same. Only isotopes consistent with normal background radiation are apparent.

FIGURE 3. Typical pulse height spectrum for survey area.

TABLE 3. Gamma-ray energies and isotopes consistent with spectral data of Figure 3.

Observed Energy (MeV)	Radionuclides Consistent With Spectral Photopeaks		
	Fission Products	Activation Products	Terrestrial Background
0.35			Pb-214
0.51			Annihilation
0.61			Bi-214
0.766			Bi-214
0.933			Bi-214
1.12			Bi-214
1.46			K-40
1.76			Bi-214
2.117			Bi-214
2.20			Bi-214
2.615			Tl-208

5. SUMMARY AND CONCLUSIONS

At the time of the survey, the Millstone reactor had not yet commenced operations; the survey therefore provided a background radiation map for the surrounding area. Exposure rates and radioactive isotopes revealed in the survey are consistent with normal terrestrial background.

The 3-foot level exposure rates mapped during the survey were mostly in the 4 to 12 $\mu\text{R/hr}$ range.

REFERENCES

1. "Aerial Radiological Measuring Systems (ARMS) - Systems and Procedures Employed Through FY 71," AEC Report No. ARMS-71.6, in preparation.
2. 1970 Census of Population, Advance Report PC(V1)-8, U. S. Dept. of Commerce, Bureau of Census, December, 1970.
3. Burson, Z. G., Boyns, P. K., and Fritzsche, A. E., "Technical Procedures for Characterizing the Terrestrial Gamma Radiation Environment by Aerial Surveys," EG&G/LVAO Report No. 1183-1559, 1972.