Reprint of a paper
presented at the
5th International Heat Transfer Conference

September 3 — September 7, 1974

at

Keidanrenkaikan Building, Tokyo

ISTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

HEAT TRANSFER IN POOL BOILING
AND CONDENSING SELENIUMLeonard Breitstein
NUS Corporation, Rockville, MarylandCharles F. Bonilla
Columbia University, New York, New York

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Abstract

Heat transfer data for the pool boiling and condensation of elemental selenium were obtained and correlated. The heat transfer surfaces consisted of a horizontal stainless steel 316 boiling plate and condensing tube. Heat transfer coefficients ranged from 681 to 6810 $W/m^2 \cdot ^\circ K$ (120 to 1200 $BTU/hr \cdot ft^2 \cdot ^\circ F$) in the case of boiling and from 454 to 1305 $W/m^2 \cdot ^\circ K$ (80 to 230 $BTU/hr \cdot ft^2 \cdot ^\circ F$) in the case of condensation, over a pressure range of 0.133 to 10.13 cm^2 (10 to 760 Torr), at 437 to 687°C, respectively. Corrosion of the apparatus, though heavy, was found to have insignificant effect on the heat transfer data. Results were interpreted qualitatively in terms of the complex molecular chain and ring structure of liquid and vapor selenium.

NOMENCLATURE

h : heat transfer coefficient, $W/m^2 \cdot ^\circ K$
 M : molecular weight
 P : pressure, N/cm^2
 q : heat flux, W/m^2
 R : perfect gas constant
 T : temperature $^\circ K$
 w : mass flow rate of condensate, $kg/m^2 \cdot s$
 y_2 : mole fraction of dimer in vapor
 c : molecular condensation coefficient

Subscripts

b : boiling
 c : condensing
 Nu : predicted by Nusselt equation for filmwise condensation on horizontal tubes
 o : at surface of test condenser
 sl : at surface of condensate film
 v : vapor
 w : at boiling surface

INTRODUCTION - At the present time, the principal use for selenium is as a semiconductor component in rectifiers. Possible future applications, which provided the motivation for this research, are as a high temperature heating or cooling fluid with liquid vapor phase change and as a thermodynamic working fluid in thermal energy conversion, especially for space power generation. Selenium has a high boiling point (686°C) and is much less costly than certain other substances, such as cesium and rubidium, which have similar boiling points and which have been considered as heat transfer and thermodynamic working fluids. The supply of selenium is

expected to remain ample in the future. Selenium's corrosiveness to most commercial metals would appear to be its principal drawback, though its toxicity and relatively high melting point (217°C) would also be disadvantageous. In view of its merits, the heat transfer properties of selenium in boiling and condensing were investigated.

CORROSION TESTS - A series of corrosion tests was carried out by the authors to identify suitable materials of construction for the heat transfer apparatus⁽¹⁾. Samples of several stainless and refractory metals were heated at 620°C for 6 weeks in liquid selenium contained in mullite tubes under argon as cover gas. In agreement with Cooper in other tests⁽²⁾, stainless steel 316 had the best corrosion resistance of the metals investigated, and was selected as the material of construction. The corrosion rate of stainless steel 316 at the conditions of these tests ranged between 0.16 and 0.25 millimeters (6.2 and 9.9 mils) per month.

APPARATUS AND EXPERIMENTAL PROCEDURE -

The boiling section of the heat transfer apparatus contained a solid copper cylinder, 7.6cm in diameter and 17.8cm high, with its bottom 2/3 heated electrically. The upper part of the cylinder served to diffuse heat to a stainless steel 316 boiling plate brazed to the top of the copper cylinder, as shown in Fig. 1. An electrical analogue study established that these dimensions would ensure a highly uniform heat flux to the boiling liquid. The wall thickness of the test chamber for 1cm immediately above the boiling plate

Figures 9 to 12 prove that for fins on a wall the fin base is never isothermal and never has a uniform heat flux. It is remarkable that the Q versus ΔT curves by 1-D and 2-D techniques are so little different. If the Biot number for a fin is defined as the average heat transfer coefficient over the fin surface multiplied by the fin thickness and divided by the thermal conductivity, we note that 1-D and 2-D solutions for Freon-113 are very similar when the Biot number is less than 1.0. For water, the upper limit is less than 0.6. A general conclusion is that the peak heat duty of a fin may nearly always be calculated satisfactorily by a 1-D method. However, the base temperature may not have adequate accuracy. To insure accuracy in that value, one must use a 2-D model.

ACKNOWLEDGMENT

This work was supported by the National Science Foundation.

REFERENCES

- [1] Irey, R. K.: J. Heat Transfer, **90**, 175 (1968)
- [2] Hennecke, D. K., and E. M. Sparrow: Int. J. Heat Mass Transfer, **13**, 287 (1970)
- [3] Sparrow, E. M., and D. K. Hennecke: J. Heat Transfer, **92**, 204 (1970)
- [4] Klett, D. E., and J. W. McCulloch: J. Heat Transfer, **94**, 333 (1972)
- [5] Barnett, P. G.: Int. J. Heat Mass Transfer, **15**, 1159 (1972)
- [6] Cump, M., S. Lopez, and G. C. Pinchera: Chem. Engng. Prog. Symp. Ser. **61**, No. 59, 225 (1965)
- [7] Kraus, A. D.: Proc. Third Intern. Heat Trans. Conf., **6**, 242 (1966)
- [8] Haley, K. W., and J. W. Westwater: Proc. Third Intern. Heat Trans. Conf., **3**, 245 (1966)
- [9] Klein, G. J., and J. W. Westwater: A.I.Ch.E. Journal **17**, 1050 (1971)
- [10] Bondurant, D. L., and J. W. Westwater: Chem. Engng. Prog. Symp. Ser. **67**, No. 113, 30 (1971)

- [11] Shih, C. C.: Ph.D. Thesis, University of Illinois, Urbana, Illinois (1973)
- [12] Shih, C. C., and J. W. Westwater: Int. J. Heat Mass Transfer, **15**, 1965 (1972)
- [13] Petukhov, B. S., S. A. Kovalev, V. M. Zhukov, and G. M. Kazakov: Teplofizika Visokikh Temperatur, **9**, 1260 (1971).

Fig. 11 Isotherms for stainless steel in water with nucleate boiling at the wall.

Fig. 10 Isotherms for copper in Freon-113.

Fig. 12 Isotherms for stainless steel in water with film boiling at the wall.

was reduced to 1.63 mm in thickness to minimize conduction of heat upwards along the wall.

Fig. 1 BOILING SECTION

Ultrasonic tests of the brazed joint showed that the copper and stainless steel surfaces were perfectly bonded, without voids. Six sheathed 1.02mm Chromel-Alumel thermocouples in 1.07mm holes and located in two vertical columns near the center and at mid-radius of the copper cylinder, were used to determine the boiling surface heat flux and temperature by extrapolation. The heater consisted of Kanthal A-1 resistance wire wound on an alumina core placed around the lower portion of the copper cylinder.

The test condenser, shown in Fig. 2, consisted of a horizontal, thin-walled, stainless steel 316 tube, brazed to an inner concentric silver tube.

Fig. 2 CONDENSING TUBE

Ultrasonic tests showed that bonding between the silver and stainless steel surfaces was excellent over the entire length of the brazed joint. Eight sheathed Chromel-Alumel thermocouples were located at mid-wall in the silver tube, four thermocouples being located 90° apart and 2.54cm deep from each end of the silver tube. Hole and couple diameters were as in the boiler. Due

to the high thermal conductivity of silver, errors in condensing-surface temperatures resulting from uncertainties in the radial locations of the thermocouple junctions were minimized. Compressed air was used as the coolant for the test condenser. The flow rate and temperature rise of the coolant were measured and used to calculate the condensing heat flux. An expansion chamber at the outlet of the test condenser reduced the air velocity sufficiently to eliminate kinetic energy effects on the exit temperature measurement. The average temperature of the condensing surface was obtained by computation from the observed temperatures in the silver. The condensing tube was welded into the walls of the boiling chamber. The silver tube had the same inner diameter as the air tubes, to maintain a uniform air boundary layer. The assembled heat transfer apparatus is shown schematically in Fig. 3, and permitted obtaining boiling and condensing heat transfer data simultaneously.

Fig. 3 ASSEMBLED APPARATUS

Argon cover gas was used to control the pressure in the test chamber. An auxiliary reflux ambient-cooled condenser was used to flush the argon from the test chamber on start-up, and keep it negligible during operation. It worked by setting the boiling rate above the test condenser condensing rate, the excess vapor flushing the inert gas into the space above the reflux condenser. A bellows welded to the top permitted raising and lowering two long thermocouples that passed through the reflux condenser into the boiling pool, thereby providing temperature profiles in the pool. A third thermocouple was fixed in the vapor space of the test chamber, above the test condenser.

Prior to the experiments with selenium, heat loss calibrations were made by supplying power to the heater with the test chamber evacuated. At each steady state, the total heat loss from the apparatus, equal to the power supplied to the heater, was evidently mainly from the heater. The ob-

served heat losses were then employed in energy balances to verify the boiling rate around the copper cylinder. Electrical meters and thermocouples were calibrated in place.

Boiling and condensing experiments were first carried out with water and with Dowtherm-A for general verification of the concept and equipment. The heat transfer data agreed closely with published data obtained under similar conditions and with prediction by standard correlations, thereby supporting the reliability of the heat transfer data later obtained on selenium with the assembled apparatus. The heat transfer apparatus and procedures are described in detail in ref. 1.

RESULTS. - Boiling and condensing experiments with selenium were carried out over a pressure range of 0.133 to 10.1 N/cm², but predominantly at approximately 0.133, 0.399, 1.33, 3.99, and 10.1 N/cm². All thermocouples were ungrounded, and were read connected in electrical opposition to the fixed vapor space thermocouple for greater accuracy in determining their relative temperatures. The vapor space temperature was then obtained from that thermocouple alone.

Boiling Heat Transfer. - The mid-radius thermocouples were always close to, but 1 or 2°C below, the near-axial thermocouples, and the latter were adopted for analysis. The 3 values for each run were first fitted with a parabola in distance from the copper surface. The vertical temperature gradient was next calculated at the copper/SS interface by differentiation. Multiplying by the thermal conductivity of the copper yielded the boiling heat flux q_b , in agreement with a σ of 6% with q_b obtained from a heat balance. The calculated ΔT of the copper/SS interface above the vapor temperature T_v , minus q_b times the thickness over the thermal conductivity of the SS plate, gave the boiling ΔT , $(T_w - T_v)$. The data points are shown in Fig. 4. Pool boiling data of several investigators and liquids show linear plots of $\log q_b$ vs $\log \Delta T$ over most of the nucleate boiling region, and little if any effect of pressure P on the slope. Experience with similar data for NaK (3), having a substantial range of pressure but only a moderate number and range of q_b points at some pressures, suggested that least squares correlation of all $\log q_b$ points at a single optimum slope vs $\log (T_w - T_v)$ by the method of Ergun (4) would best present the effect of ΔT . Subsequent correlation vs P can yield a single correlation that is also helpful for interpolation or extrapolation in P . Fig. 4 shows

the separate lines obtained for the principal test pressure groups, the slope being 1.981. The best simple overall correlation that was found including P is:

$$q_b = (T_w - T_v)^{1.981} (17.11P^{1/2} + 6.348P) \quad (1)$$

which has a probable error of $\pm 10\%$ of q_b , compared to the data points.

Fig. 4 HEAT FLUX VS. TEMPERATURE DIFFERENCE FOR BOILING SELENIUM

To test for any possible effects of wall corrosion or of selenium contamination on boiling heat transfer, two selenium charges were employed, and several runs were duplicated during the course of the experiments. Though considerable corrosion of the boiling plate and chamber walls occurred, the boiling heat transfer data were found to be fairly reproducible, and corrosion not to have a significant effect.

Temperature profiles in the boiling liquid pool were measured during several runs. Most of the temperature drop between the boiling surface and the top of the liquid pool occurred within 1 mm of the boiling surface. The rest of the boiling pool and vapor space were close to the saturation temperature at the measured pressure. Small erratic temperature fluctuations were recorded by the thermocouple closest to the top of the copper cylinder during the boiling runs at the lowest pressure. For boiling pressures above 0.133 N/cm², temperature fluctuations were negligible. In contrast, wide temperature fluctuations (up to 18°C) were observed during the only non-boiling run, at 0.399 N/cm².

The boiling heat transfer data were compared to predictions by six widely tested correlations for nucleate pool boiling. For data at 10.1 N/cm², heat fluxes predicted by the correlations of Forster and Zuber (5), Forster and Greif (6), and Levy (7)

were within 25% of experimental heat fluxes, while predictions by the equations of McNelly (8), Hughmark (9), and Chang and Snyder (10) generally agreed within a factor of two. However, for each of the six correlations agreement with experimental results became progressively worse as the pressure decreased. At the lowest pressure, predicted heat fluxes exceeded experimental values by approximately one to two orders of magnitude for each correlation.

To explain differences between experimental and predicted results at the lower pressures, a possible mechanism for bubble nucleation and growth was devised (1). Liquid selenium is composed of Se_8 (and possibly Se_6) rings, plus long chains of selenium atoms (11, 12). The proposed mechanism was based on the high relative volatility of the rings compared to the long polymer chains, and on the expected separation of these components in the vicinity of nucleation sites and growing bubbles. Due to their high relative volatility, liquid selenium surrounding nucleation sites and growing bubbles would become partially stripped of rings. Diffusional resistances and reaction kinetics in the liquid could thus have a significant effect on bubble nucleation and growth. Predicted heat fluxes were found to approach experimental heat fluxes as the average chain length of the liquid decreased, which was consistent with the proposed mechanism. Qualitative similarities are evident (1) between boiling heat transfer data for non-reacting binary mixtures of high relative volatility (13), such as water-ethylene glycol, and for selenium. However, a useful quantitative theory taking into account the predominant vaporization of the more volatile rings at the liquid-vapor interface, and their replacement at the interface by reaction from chains in the liquid film and diffusion to the interface seems out-of-reach at present.

Condensation Heat Transfer. - The average condensing heat flux, q_c , was computed by dividing the sensible heat gained by the air coolant in passing through the test condenser, minus the heat conducted from the wall of the test chamber to the test condenser by the outer surface of the test condenser. The end correction was computed as for two flat round fins of infinite diameter attached to the test condenser.

The condensing ΔT , $(T_v - T_o)$, was the average of the 8 separate opposed thermocouple observations of temperature difference from the vapor to the silver sleeve, after correction for the temperature drop through the outer half of the silver sleeve and the stainless steel condenser tube, due

to q_c . Since q_c and $T_v - T_o$ each affected the calculation of the other quantity, the total of 9 equations involved was solved iteratively by computer. The values of q_c and $T_v - T_o$ obtained are plotted in Fig. 5.

Fig. 5 HEAT FLUX VS. TEMPERATURE DIFFERENCE FOR CONDENSING SELENIUM (See note at end)

Since nearly identical data were obtained for several runs, many of the data points shown are multiple.

To test for the presence and effect of inerts on the condensing heat transfer data, the height of the condensing ring in the auxiliary reflux condenser was varied by changing the power to the heater or by adding thermal insulation around the lower portion of the auxiliary condenser, while all other parameters were held constant. The condensing ring height is the path length for backward diffusion of inert gas from condenser pressure into the test chamber. Since wide variations in the height of the condensing ring had insignificant effect on the heat transfer data, and the results were generally reproducible, non-condensables were effectively eliminated from the test chamber (1).

The condensing heat transfer data were compared to predictions by the Nusselt equation (14) for filmwise condensation on a horizontal cylinder. For film condensation of water and organic liquids, Nusselt predictions generally agree with experimental results within 10 to 15%. For liquid metals, however, Nusselt-predicted heat transfer coefficients often exceed experimental heat transfer coefficients by around an order of magnitude (15). In the case of selenium, h_c was generally 40 to 50% of h_{Nu} . Several

possible explanations for the discrepancy between h_c and h_{Nu} were considered (1), including a "contact" resistance at the solid-liquid interface, an unexpected thickening of the condensate film, and the effect of several simplifying assumptions made by Nusselt (14) on the calculated h_{Nu} . It was concluded that the most reasonable explanation was a liquid-vapor interfacial resistance.

The liquid-vapor interface was analyzed by means of the kinetic theory of condensation, developed by Schrage (16) by applying kinetic theory of gases to the motion of molecules striking and leaving a condensate surface. Condensation coefficients for selenium were calculated from the condensing heat transfer data by the following equation:

$$\frac{2w}{\sigma_c} = w + \left[\frac{2M}{wR} \right]^{1/2} \left[\frac{P_v}{T_v}^{1/2} - \frac{P_{sl}}{T_{sl}}^{1/2} \right] \quad (2)$$

The calculated σ_c for selenium (which ranged between 0.0025 and 0.070) and for other metals were correlated against P_{sl} . Log σ_c was found to decrease linearly with log P_{sl} . σ_c for selenium was generally one to two orders of magnitude smaller than for sodium, potassium, and mercury at the same P_{sl} . M, the effective average molecular weight of the vapor, was taken at T_{sl} . M varies linearly with T from 359 at 636 C to 436 at 329 C; even at T_v , σ_c agreed within 5% (1). To explain the relatively low σ_c for selenium, a qualitative mechanism was developed (1), based on the assumption that Se_2 in the vapor does not condense. A compilation of data on the composition of selenium vapor (1), indicates that saturated selenium vapor consists of all molecular species from Se_2 to Se_8 , with Se_2 and Se_6 as major components between 300 and 700°C. Since there is no evidence for the existence of Se_2 molecules in the liquid phase, the condensate surface might be reflective to Se_2 molecules. In this case, Se_2 molecules in the vapor adjacent to the condensate surface would present a diffusional resistance to other molecules that do condense, having an effect similar to that of a noncondensable gas and resulting in a reduced calculated σ_c . It was found that σ_c decreased with increasing dimer (y_2) for each element, forming a nearly continuous straight line with sodium and potassium (1).

Acknowledgement. - Sponsorship initially by the Selenium-Tellurium Development Association, Inc., and subsequently by the Division of Research, USAEC under contracts AT(30-1)-2660 and (11-1)-3027 made this study possible, and was much appreciated. Assistance

by Oak Ridge National Laboratory and by NUS Corporation in preparing illustrations were also helpful. This paper is designated AEC report number C00-3027-14.

REFERENCES

- (1) Breitstein, L., Dr. Eng. Sc. Dissertation in Chemical Engineering with C. F. Bonilla, Columbia University, 1972; available from University Microfilms, Ann Arbor, Michigan, and as C00-3027-6 from NTIS, Springfield, Va. - 22151.
- (2) Cooper, W. C., Personal Communication, Aug. 3, 1967.
- (3) Madsen, N. and Bonilla, C. F., Chem. E. Eng. Progress Symp. Series No. 18, pp. 7 - 21 (1957)
- (4) Ergun, S., Ind. Eng. Chem. 48, 2063-8, 1956.
- (5) Forster, H. K., and Zuber, N., A.I.Ch.E. Journal 1 (4), pp. 531-5, 1955.
- (6) Forster, H. K., and Greif, R., Journal of Heat Transfer, Trans. ASME 81C, pp. 43-53, 1959
- (7) Levy, S., Journal of Heat Transfer, Trans. ASME 81C, pp. 37-42, 1959.
- (8) McNelly, M. J., Journal of the Imperial College Chemical Engineering Soc. 2, pp. 18-34, 1953.
- (9) Hughmark, G. A., Int. Heat and Mass Transfer 5, pp. 667-72, July 1962.
- (10) Chang, Y. P. and Snyder, N. W., CEP Symposium Series No. 30, pp. 25-38, 1960.
- (11) Richter, H. et al, Z. Naturforsch., 13A, pp. 874-881, 1958.
- (12) Keezer, R. C. et al, Mat. Res. Bull. 2, pp. 185-92, 1967.
- (13) Sternling, C. V., and Tichacek, L. J., "Heat Transfer Coefficients for Boiling Mixtures", P-931, Shell Development Co., Emeryville, Calif., 1963.
- (14) Nusselt, W., Zeitsch. d. Ver. Deutsch. Ing. 60, p. 541, 1916.
- (15) Larrain, J. and Bonilla, C. F. Fifth International Heat Transfer Conference, Tokyo (1974).
- (16) Schrage, R. W., "A Theoretical Study of Interphase Mass Transfer", Columbia University Press, New York, 1953.

Note: Fig. 5 neglects the several initial points with each charge, which gave h_c 10 to 20% higher than the later points, and were presumed to be in dropwise condensation.