UNCLASSIFIED

MASTER

OAK RIDGE NATIONAL LABORATORY

Operated By

UNION CARBIDE NUCLEAR COMPANY

POST OFFICE BOX P
OAK RIDGE, TENNESSEEExternal Transmittal
AuthorizedORNL
CENTRAL FILES NUMBER

58-4-75

DATE: April 15, 1958

COPY NO. 57

SUBJECT: A CALCULATION OF THE ENERGY SPECTRUM AND ANGULAR DISTRIBUTION
OF GAMMA RAYS AT THE SURFACE OF THE BSF REACTOR

TO: Distribution

FROM: L. A. Bowman,* W. W. Dunn,** R. H. Lessig,** and D. K. Trubey

Abstract

The energy and angular distribution of the gamma rays leaking from the BSF reactor were computed by integrating the sources over the entire reactor and applying an attenuation kernel. The primary gamma-ray spectrum was grouped into six initial energy groups, E_0 , of 0.5, 1, 2, 4, 6, and 8 Mev. The uncollided flux in each energy group at a point on the center of the north face was computed as a function of direction given by θ and ϕ . The collided flux was determined for each initial energy group by including the term $[B(\mu R) - 1]$, where $B(\mu R)$ is the energy buildup factor, in the initial integrand and was divided into contributions to that particular energy group and each lower energy group by assuming that the collided flux had a differential energy spectrum of the type computed by NDA for a point source after passage through 1 mfp of water. The total gamma-ray spectrum compared favorably with previously calculated spectrum, but was in the usual disagreement with experimental results. The angular distribution was determined by assuming the collided and uncollided flux had the same angular distribution.

*On assignment from Wright Air Development Center.

**On assignment from U. S. Air Force.

NOTICE

This document contains information of a preliminary nature and was prepared primarily for internal use at the Oak Ridge National Laboratory. It is subject to revision or correction and therefore does not represent a final report.

The information is not to be abstracted, reprinted or otherwise given public dissemination without the approval of the ORNL patent branch, Legal and Information Control Department.

UNCLASSIFIED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

- A. Makes any warranty or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or
- B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission to the extent that such employee or contractor prepares, handles or distributes, or provides access to, any information pursuant to his employment or contract with the Commission.

Introduction

In the past it has not been possible to use directly the Monte Carlo shielding codes to check, or to predict, the experimental results of shielding experiments performed with the BSF reactor. While theoretical calculations of the energy spectrum have been performed¹ for comparison with the experimentally measured gamma-ray spectrum,² there is only limited information on the angular distribution at the reactor surface.³ The calculation reported here represents a new attempt to calculate the energy spectrum from primary gamma ray sources and, in addition, to determine the angular distribution of the gamma rays at the reactor surface.

Geometry

The reactor was divided into four quadrants, each containing one quarter of the reactor volume as shown in Fig. 1. The thermal-neutron flux in the second quadrant was used to perform an integration of the power and gamma-ray leakage out the center of the north face of the reactor. The integration was performed over the angles ϕ and θ so that an angular distribution of the gamma rays could be computed.

Thermal-Neutron Flux

Thermal-neutron flux measurements were available⁴ at points within the volume of the second quadrant of BSR loading 33 for a reactor power of 27.36 kw. Plotting and cross-plotting these measured values produced curves which could be used to determine the flux at any point in this volume. Integration over the reactor, i.e.,

-
1. G. deSaussure, "A Calculation of the Gamma-Ray Spectrum of the Bulk Shielding Reactor," ORNL-CF-57-7-105 (July 31, 1957).
 2. F. C. Maienschein and T. A. Love, Nucleonics 12, No. 5, 6-8 (1954).
 3. F. C. Maienschein, F. T. Bly, and T. A. Love, ORNL-1714, Parts I and II (Aug. 20, 1954) (classified).
 4. E. B. Johnson, "Power Calibration for BSR Loading 33," ORNL-CF-57-11-30.

Fig. 1. Assumed Geometry for the Calculation of the Gamma-Ray Spectrum of the BSF Reactor (Loading 33)

$$\begin{aligned}
 \text{Power} &= C \int_{\text{Reactor}} \phi_{\text{th}}(\vec{R}) d\vec{R} \\
 &= C \int_{\theta} \int_{\phi} \int_0^{R_{(\max)}} \phi_{\text{th}}(\theta, \phi, R) R^2 dR \sin\theta d\theta d\phi
 \end{aligned}$$

where

ϕ = thermal-neutron flux (taken from the plots),

$C = \Sigma_f(u)/K$,

$\Sigma_f(u)$ = macroscopic uranium fission cross section

= 0.0565 cm^{-1} ,

K = factor to convert from fission rate to power,

= $3.48 \times 10^{13} \text{ fissions/sec-kw}$,

yields a power of 29.48 kw or approximately 8% over the rated power of 27.36 kw. The 29.48-kw figure was used in the normalization for this calculation since both integrations over ϕ and θ (power and gamma-ray leakage) do not account for the corners properly. In order to enable the calculation for the second quadrant to apply equally to the other three quadrants, it was necessarily assumed that the reactor has flux symmetry in all quadrants.

Gamma-Ray Sources

The following primary gamma-ray sources were considered in this calculation: (1) prompt fission and capture gamma rays from uranium, (2) fission-product decay gamma rays, (3) capture and decay gamma rays from aluminum, and (4) capture gamma rays from water. These sources were grouped into six initial energy groups of 0.5, 1, 2, 4, 6, and 8 Mev and expressed in the following equation which gives the source for a particular energy group at a point:

$$(1) \quad S(E_0, \vec{R}) = \phi_{th}(\vec{R}) \left[N(p+c) \Sigma_f(u) + N(fp) \Sigma_f(u) + N(Al) \Sigma_a(Al) + N(H) \Sigma_a(H) \right]$$

where

$\phi_{th}(\vec{R})$ = thermal-neutron flux at $\vec{R}$,

$N(p+c)$ = number of prompt and capture gamma rays in the energy group about E_0 produced in uranium per fission (see Table 1),

$\Sigma_f(u)$ = macroscopic fission cross section of U^{235} (0.025 ev),

$N(fp)$ = number of fission-product gamma rays in the energy group about E_0 produced per fission (see Table 1 and Ref. 5),

$N(Al)$ = number of aluminum capture and decay gamma rays in the energy group about E_0 per capture (see Table 1 and Ref. 5),

$\Sigma_a(Al)$ = macroscopic absorption cross section for aluminum (0.025 ev) (see Ref. 6),

$N(H)$ = number of hydrogen capture gamma rays in the energy group about E_0 per capture (see Table 1 and Ref. 5),

$\Sigma_a(H)$ = macroscopic cross section of hydrogen per absorption (0.025 ev) (see Ref. 6).

Absorption Coefficients

The linear absorption coefficients, μ , for the core as a function of E_0 were determined by the following expression where f_i is the fractional density of the i^{th} material:

$$(2) \quad \mu_{E_0}(\text{core}) = \sum_i \left(\frac{\mu}{f} \right) f_i$$

$$f = \sum_i f_i$$

5. H. W. Bertini et al., ORNL-2113, pp. 9, 16 (Sept. 17, 1956) (classified).

6. H. C. Claiborne and T. B. Fowler, "The Calculation of Gamma Heating in Reactors of Rectanguloid Geometry," ORNL-CF-56-7-97, p. 20 (July, 1956).

Table 1. Equivalent Number of Gamma Rays in the Core
for Each Energy Group E_0

Energy Interval (Mev)	E_0 (Mev)	N(p+c) per Fission (a)	N(fp) per Fission (a)	N(H) per Capture (b)	N(Al) per Capture (b)
0 - 0.75	0.5	3.31	2.972	0	0
0.75 - 1.5	1.0	2.55	1.864	0	0.10
1.5 - 3.0	2.0	1.687	0.891	1.115	1.53
3.0 - 5.0	4.0	0.368	0.1165	0	0.77
5.0 - 7.0	6.0	0.050	0.0084	0	0.21
7.0 - 9.0	8.0	0.0067	0.0006	0	0.35

a. Taken from H. W. Bertini et al., ORNL-2113, pp. 9, 16 (Sept. 17, 1956)
(classified).

b. Taken from H. C. Claiborne and T. B. Fowler, The Calculation of Gamma Heating
in Reactors of Rectanguloid Geometry, ORNL-CF-56-7-97, p. 20 (July, 1956).

Buildup Factors

The energy buildup factors for each energy group were obtained by fitting curves between the NDA tabulated values⁷ for aluminum and water. Where possible, the curve was weighted by the ratio of the electron densities of aluminum and water.

Flux Computation

The uncollided and collided fluxes in a particular direction at the center of the north face for each initial energy group were computed by numerically integrating the standard point kernels over the volume, V , of the differential solid angle where $S(E_o, \vec{R})$ is the average source strength at $\vec{R}$:

$$(4a) \quad \phi_{\text{uncollided}}(\theta, \phi, E_o) = \int_V \frac{E_o S(E_o, R) e^{-\mu R}}{4\pi R^2} d\vec{R}$$

$$(4b) \quad \phi_{\text{collided}}(\theta, \phi, E_o) = \int_V \frac{E_o S(E_o, R) e^{-\mu R}}{4\pi R^2} [B(\mu R) - 1] d\vec{R}$$

where $B(\mu R)$ is the energy buildup factor.

The collided flux from each initial energy group was divided into effective contributions to the energy group under consideration and each lower energy group. For example, for the collided flux from the 4-Mev initial energy group:

$$(5) \quad \phi_{\text{collided}}(E_o = 4 \text{ Mev}) = \phi(4 \text{ Mev}) + \phi(2 \text{ Mev}) + \phi(1 \text{ Mev}) + \phi(0.5 \text{ Mev})$$

The contributions to each of the lower energy groups were obtained by comparing the areas in each energy group under the NDA differential energy spectrum for a point source after passage through 1 mfp (mean free path) of water for the initial energy group under consideration.⁷ The use of the energy spectrum after passage through 1 mfp of water was assumed since the spectrum is nearly independent of distance of penetration for a number of

7. H. Goldstein and J. E. Wilkins, Jr., "Calculations of the Penetration of Gamma Rays," NYO-3075 (June 30, 1954).

mean free paths. The total flux in a particular direction, $\phi(\theta, \phi, E)$, was the sum of the uncollided flux for that energy group and the collided contributions from each higher energy group. This total flux and the uncollided flux are given in Table 2. The total and uncollided flux for $\theta = 0$ was converted to an energy spectrum and plotted in Fig. 2 as a histogram. Also shown are the results of calculations by deSaussure¹ and the experimental results.³

Angular Distribution

The energy flux at the surface of the reactor, averaged over the azimuthal angle, ϕ , is shown in Fig. 3 as a function of the polar angle, θ . A typical plot of the variation of the flux with ϕ when $\theta = 30$ deg is shown in Fig. 4.

Conclusions

The gamma-ray energy spectrum normal to the reactor surface, as calculated in this study, is in good agreement with previous calculations by deSaussure.¹ The present calculation is an overestimation, particularly in the low-energy range, since it was assumed that the collided flux, as calculated by the energy buildup factors, is all travelling in the outward direction.

Table 2. Gamma-Ray Energy Flux as a Function of the Polar Angle, θ , the Azimuthal Angle, ϕ , and the Average Energy, E

E (Mev)	Gamma-Ray Energy Flux (Mev/cm ² -sec-watt-steradian)									
	$\theta = 0 \text{ deg}$		$\theta = 30 \text{ deg}$		$\theta = 45 \text{ deg}$		$\theta = 60 \text{ deg}$		$\theta = 90 \text{ deg}$	
	Total	Uncollided	Total	Uncollided	Total	Uncollided	Total	Uncollided	Total	Uncollided
$\phi = 0 \text{ deg}$										
8.0	2.47×10^5	2.38×10^5	2.24×10^5	2.16×10^5	1.92×10^5	1.85×10^5	1.58×10^5	1.54×10^5	1.40×10^5	1.36×10^5
6.0	3.66×10^5	3.33×10^5	3.30×10^5	2.30×10^5	2.83×10^5	2.59×10^5	2.34×10^5	2.18×10^5	2.08×10^5	1.95×10^5
4.0	1.59×10^6	1.39×10^6	1.43×10^6	1.24×10^6	1.24×10^6	1.09×10^6	1.04×10^6	9.41×10^5	9.31×10^5	8.48×10^5
2.0	3.43×10^6	2.70×10^6	3.08×10^6	2.42×10^6	2.72×10^6	2.20×10^6	2.37×10^6	1.98×10^6	2.15×10^6	1.83×10^6
1.0	2.52×10^6	1.38×10^6	2.26×10^6	1.25×10^6	2.00×10^6	1.17×10^6	1.75×10^6	1.10×10^6	1.60×10^6	1.04×10^6
0.5	4.51×10^6	6.69×10^5	3.98×10^6	6.20×10^5	3.46×10^6	5.94×10^5	2.93×10^6	5.75×10^5	2.63×10^6	5.51×10^5
$\phi = 30 \text{ deg}$										
8.0	2.47×10^5	2.38×10^5	2.12×10^5	2.04×10^5	1.92×10^5	1.86×10^5	1.64×10^5	1.59×10^5	1.34×10^5	1.31×10^5
6.0	3.66×10^5	3.33×10^5	3.12×10^5	2.85×10^5	2.84×10^5	2.60×10^5	2.43×10^5	2.25×10^5	1.99×10^5	1.88×10^5
4.0	1.59×10^6	1.39×10^6	1.36×10^6	1.19×10^6	1.24×10^6	1.10×10^6	1.08×10^6	9.66×10^5	8.96×10^5	8.18×10^5
2.0	3.43×10^6	2.70×10^6	2.90×10^6	2.37×10^6	2.73×10^6	2.19×10^6	2.43×10^6	2.01×10^6	2.08×10^6	1.77×10^6
1.0	2.52×10^6	1.38×10^6	2.10×10^6	1.24×10^6	2.01×10^6	1.18×10^6	1.79×10^6	1.11×10^6	1.54×10^6	1.02×10^6
0.5	4.51×10^6	6.69×10^5	3.70×10^6	6.20×10^5	3.46×10^6	5.98×10^5	3.01×10^6	5.78×10^5	2.50×10^6	5.45×10^5
$\phi = 50 \text{ deg}$										
8.0	2.47×10^5	2.38×10^5	2.08×10^5	2.01×10^5	1.76×10^5	1.71×10^5	1.46×10^5	1.43×10^5	1.19×10^5	1.17×10^5
6.0	3.66×10^5	3.33×10^5	3.06×10^5	2.81×10^5	2.60×10^5	2.41×10^5	2.17×10^5	2.04×10^5	1.77×10^5	1.68×10^5
4.0	1.59×10^6	1.39×10^6	1.34×10^6	1.18×10^6	1.15×10^6	1.04×10^6	9.75×10^5	8.88×10^5	8.04×10^5	7.45×10^5
2.0	3.43×10^6	2.70×10^6	2.94×10^6	2.36×10^6	2.60×10^6	2.14×10^6	2.26×10^6	1.92×10^6	1.91×10^6	1.66×10^6
1.0	2.52×10^6	1.38×10^6	2.16×10^6	1.24×10^6	1.92×10^6	1.17×10^6	1.62×10^6	1.08×10^6	1.42×10^6	9.83×10^5
0.5	4.51×10^6	6.69×10^5	3.78×10^6	6.23×10^5	3.27×10^6	5.98×10^5	2.76×10^6	5.71×10^5	2.25×10^6	5.37×10^5
$\phi = 65 \text{ deg}$										
8.0	2.47×10^5	2.38×10^5	2.05×10^5	1.98×10^5	1.65×10^5	1.61×10^5	1.36×10^5	1.33×10^5	1.12×10^5	1.10×10^5
6.0	3.66×10^5	3.33×10^5	3.03×10^5	2.78×10^5	2.45×10^5	2.29×10^5	2.02×10^5	1.91×10^5	1.66×10^5	1.58×10^5
4.0	1.59×10^6	1.39×10^6	1.33×10^6	1.18×10^6	1.09×10^6	9.89×10^5	9.16×10^5	8.42×10^5	7.57×10^5	7.07×10^5
2.0	3.43×10^6	2.70×10^6	2.96×10^6	2.41×10^6	2.50×10^6	2.09×10^6	2.15×10^6	1.85×10^6	1.82×10^6	1.61×10^6
1.0	2.52×10^6	1.38×10^6	2.15×10^6	1.25×10^6	1.85×10^6	1.16×10^6	1.59×10^6	1.07×10^6	1.36×10^6	9.64×10^5
0.5	4.51×10^6	6.69×10^5	3.75×10^6	6.28×10^5	3.12×10^6	6.00×10^5	2.59×10^6	5.71×10^5	2.09×10^6	5.34×10^5
$\phi = 90 \text{ deg}$										
8.0	2.47×10^5	2.38×10^5	2.05×10^5	1.98×10^5	1.62×10^5	1.58×10^5	1.33×10^5	1.30×10^5	1.08×10^5	1.07×10^5
6.0	3.66×10^5	3.33×10^5	3.03×10^5	2.79×10^5	2.39×10^5	2.25×10^5	1.97×10^5	1.87×10^5	1.61×10^5	1.55×10^5
4.0	1.59×10^6	1.39×10^6	1.33×10^6	1.18×10^6	1.07×10^6	9.77×10^5	8.93×10^5	8.25×10^5	7.40×10^5	6.93×10^5
2.0	3.43×10^6	2.70×10^6	2.96×10^6	2.39×10^6	3.47×10^6	2.08×10^6	2.11×10^6	1.83×10^6	1.79×10^6	1.59×10^6
1.0	2.52×10^6	1.38×10^6	2.17×10^6	1.27×10^6	1.83×10^6	1.16×10^6	1.56×10^6	1.06×10^6	1.33×10^6	9.60×10^5
0.5	4.51×10^6	6.69×10^5	3.80×10^6	6.35×10^5	3.08×10^6	6.05×10^5	2.52×10^6	5.73×10^5	2.03×10^6	5.35×10^5

Fig. 2. Comparison of Calculated and Experimental Spectra of Gamma Rays at the Surface of the Bulk Shielding Facility Reactor
Polar Angle, $\theta=0$ deg

Fig. 3. Total Calculated Gamma-Ray Energy Flux at the Surface of the BSF Reactor as a Function of the Polar Angle, θ , Averaged over the Azimuthal Angle, ϕ , for Various Energies E

($\times 10^6$)

UNCLASSIFIED
2-01-059-280

Fig. 4. Total Calculated Gamma-Ray Energy Flux at the Surface of the BSF as a Function of the Reactor Azimuthal Angle, ϕ , for Various Energies E when Polar Angle $\theta=30$ deg

INTERNAL DISTRIBUTION

1. E. P. Blizzard	23. F. J. Muckenthaler
2-5. L. A. Bowman	24. R. W. Peelle
6. V. R. Cain	25. S. K. Penny
7. A. D. Callihan	26. A. B. Reynolds
8. G. T. Chapman	27. A. Simon
9. R. A. Charpie	28. M. J. Skinner
10. C. E. Clifford	29-38. D. K. Trubey
11. G. deSaussure	39. A. M. Weinberg
12. E. B. Johnson	40. W. Zobel
13. F. L. Keller	41-44. Laboratory Records
14-21. F. C. Maienschein	45-46. C. R. Library
22. E. G. Silver	

EXTERNAL DISTRIBUTION

- 47. Atomics International (Attn: R. L. Ashley)
- 48. Convair, Ft. Worth (Attn: N. M. Schaeffer)
- 49-50. General Electric, Cincinnati (Attn: J. Carver, W. E. Edwards)
- 51. Lockheed, Marietta, Georgia (Attn: F. N. Watson)
- 52. The Martin Company, Baltimore (Attn: G. J. Rausa)
- 53. Nuclear Development Corporation of America (Attn: H. Goldstein)
- 54. R. K. Osborn, Univ. of Michigan, Ann Arbor, Michigan
- 55. Pratt and Whitney Aircraft (Attn: J. B. Dee)
- 56. Technical Research Group (Attn: R. Aronson)
- 57-71. TISE, AEC
- 72-73. Wright Air Development Center (Attn: W. W. Dunn, R. H. Lessig, WCLQE)
- 74. Wright Air Development Center (Attn: Capt. E. Zawalick, WCLJX)