BNWL-B-338

CRITICAL EXPERIMENTS TO MEASURE THE
NEUTRON POISONING EFFECTS
OF Cu AND Cu-Cd PLATES

S. R. Bierman and E. D. Clayton

Battelle

Pacific Northwest Laboratories
Richland, Washington 99352

JANUARY 1974

*This report is intended primarily for internal use
by the sponsoring organization and Battelle.*

MASTER

Prepared for the U.S. Atomic Energy
Commission under Contract AT(45-1):1830

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

BNWL-B-338

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

NOTICE

The report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

PACIFIC NORTHWEST LABORATORY
operated by
BATTELLE
for the
U.S. ATOMIC ENERGY COMMISSION
Under Contract AT(45-1)-1830

Printed in the United States of America
Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, Virginia 22151
Price: Printed Copy \$4.00; Microfiche \$1.45

CRITICAL EXPERIMENTS TO MEASURE THE
NEUTRON POISONING EFFECTS OF Cu AND Cu-Cd PLATES

by

S. R. Bierman
E. D. Clayton

January 1974

BATTELLE
PACIFIC NORTHWEST LABORATORIES
RICHLAND, WASHINGTON

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

LB

EXECUTIVE SUMMARY

There has been considerable interest in the use of fixed neutron absorbers (poisons) for criticality control, since their use would permit safely handling larger quantities of nuclear materials with reduced probability of criticality. The effectiveness of such absorbers as neutron poisons depends on self-shielding effects which in turn are determined by the magnitude of the absorption cross sections and their variation with energy, the thickness of material, and the neutron energy spectrum. For the fixed poisons to be considered as either a primary or secondary means of criticality control, their use must be based on a firm knowledge of these effects. To obtain experimental data in this area, the reactivity worth of two such materials, copper and copper containing 1 wt% cadmium, was recently measured in two different energy spectrums and at different thicknesses up to about 2.5 cm. The results of these measurements are presented in this paper and provide a set of clean, well defined, poisoned critical assemblies that can be used to check calculational techniques and cross section data.

In the relatively thermalized neutron energy spectrum, very little additional absorption was observed in the copper plate at thicknesses greater than about 2-1/2 cm or in the copper-cadmium plate at thicknesses greater than 1 cm. At thicknesses greater than these, self-shielding precluded any additional absorption and the change in reactivity was due almost entirely to the additional void being introduced in to the system by the poison plates.

In the relatively fast neutron energy spectrum, neutron absorption was observed to continually increase with plate thickness for both sets of plates. However, in this spectrum the void effects, caused by the presence of the poison plates, had a greater reactivity worth, over the thickness range covered, than the neutron absorption.

In either spectrum, the 1 wt% cadmium in the copper contributed significantly to the neutron absorption. Of course, the cadmium was found to be worth much more in the thermalized spectrum.

CONTENTS

EXECUTIVE SUMMARY	i
LIST OF FIGURES	iii
LIST OF TABLES	iii
INTRODUCTION	1
GENERAL DESCRIPTION OF EXPERIMENTS	1
DISCUSSION OF EXPERIMENTAL DATA	4
DETAILED DESCRIPTION OF EXPERIMENTAL ASSEMBLIES	15
COMPARISON BETWEEN CALCULATIONS AND EXPERIMENTS	18
REFERENCES	20

LIST OF FIGURES

1. Experimental Assembly With Part of the Reflector Removed	5
2. Physical Model of PuO ₂ -UO ₂ -Polystyrene Assemblies - Single Neutron Poison Plate	7
3. Physical Model of PuO ₂ -UO ₂ -Polystyrene Assemblies - Two Neutron Poison Plates	8
4. Effect of Al, Cu and Cu-Cd Plates on Critical Height	9
5. Effect of Al, Cu, and Cu-Cd Plates on Critical Height	10
6. Effect of Plate Position on Critical Height	11
7. Effect of Al, Cu, and Cu-Cd Plates on Critical Height	13
8. Changes in Critical Height due to Reduction of Core Density and to Increased Neutron Absorption - Plexiglas Reflected 9x9 Assemblies of PuO ₂ -UO ₂ -Polystyrene Compacts	14
9. Variation in k_{eff} Average With Neutron Histories	19

LIST OF TABLES

I. Description of Experimental Fuel and Reflector Material	2
II. Calculated 18-Energy Group Neutron Flux for PuO ₂ -UO ₂ -Polystyrene Fuels	3
III. Composition of Neutron Poison Plates	6
IV. Plexiglas Reflected 9x9 Assemblies of 30.6 H:Pu+U PuO ₂ -UO ₂ -Polystyrene Compacts	16
V. Plexiglas Reflected 9x9 Assemblies of 2.8 H:Pu+U PuO ₂ -UO ₂ -Polystyrene Compacts	17
VI. Comparison Between k_{eff} 's Calculated Using Experimental Geometries and Simplified Geometries	20

CRITICAL EXPERIMENTS TO MEASURE THE NEUTRON POISONING EFFECTS OF Cu AND Cu-Cd PLATES

S. R. Bierman
E. D. Clayton

INTRODUCTION

Shipping casks, storage facilities, and process vessels involved in handling fissile materials contain neutron absorbing materials - either for their neutron absorbing properties or for structural reasons. These types of systems can be fully utilized, safely, only if the neutron absorbers are properly accounted for in the criticality analyses. The reactivity worth of two such materials, copper and copper containing 1 wt% cadmium, was recently measured at the Battelle-Northwest operated Critical Mass Laboratory. The results of these measurements are presented in this paper and provide a set of clean, well defined, poisoned critical assemblies that can be used to check calculational techniques and cross section data.

GENERAL DESCRIPTION OF EXPERIMENTS

The relative worth of Cu and Cu-Cd plates was measured in two different sets of fuel to provide data on these neutron absorbers in widely differing neutron energy spectrums. Both sets of fuel were homogeneous mixtures of PuO_2 - UO_2 -polystyrene in the form of 5 x 5 cm compacts having different thicknesses. A complete description of each fuel, including cladding, composition and size, is shown in Table I. One set of fuel, having an atomic H:Pu+U ratio of 30.6 and containing 14.62 wt% PuO_2 in the oxide, had a relatively soft neutron energy spectrum. The second set of fuel contained 30.3 wt% PuO_2 in the oxide at an H:Pu+U atomic ratio of 2.8 and had a much harder spectrum. Calculated 18-energy group spectra, using the GAMTEC-II⁽¹⁾ code and ENDF/B-III cross section data, are shown in Table II for each of the fuels.

The critical assemblies consisted of rectangular parallelepipeds of fuel fully reflected with 15 cm of Plexiglas. All of the assemblies had a

TABLE I

DESCRIPTION OF EXPERIMENTAL FUEL AND REFLECTOR MATERIAL

	28 H: Pu + U FUELED EXPERIMENTS	30.6H: Pu + U FUELED EXPERIMENTS				
• CLADDING MATERIAL PER COMPACT, g	2.432	3.175				
• CLADDING DENSITY, g/cc	1.12	1.12				
• COMPOSITION OF CLADDING, ATOMS/BARN cm						
H	4.489×10^{-2}	4.489×10^{-2}				
C	3.110×10^{-2}	3.110×10^{-2}				
Cl	0.724×10^{-2}	0.724×10^{-2}				
• COMPOSITION OF REFLECTOR, atoms/barn cm						
H	5.712×10^{-2}	5.712×10^{-2}				
C	3.570×10^{-2}	3.570×10^{-2}				
O	1.428×10^{-2}	1.428×10^{-2}				
• COMPOSITION OF FUEL COMPACTS, atoms/barn cm						
²⁴¹ Am	1.017×10^{-5} (a)	4.036×10^{-7} (b)				
²³⁹ Pu	2.186×10^{-3}	1.954×10^{-4}				
²³⁸ Pu	2.288×10^{-6}	0.0				
²⁴⁰ Pu	2.927×10^{-4}	1.702×10^{-5}				
²⁴¹ Pu	5.875×10^{-5}	1.211×10^{-6}				
²⁴² Pu	6.751×10^{-6}	0.0				
O	1.864×10^{-2}	3.023×10^{-3}				
²³⁸ U	6.162×10^{-3}	1.252×10^{-3}				
²³⁵ U	9.269×10^{-6}	1.904×10^{-6}				
H	2.432×10^{-2}	4.489×10^{-2}				
C	2.660×10^{-2}	4.412×10^{-2}				
• PuO ₂ PARTICLE SIZE, μm						
95%	< 20	< 20				
50%	< 8	< 5				
5%	< 2	< 0.5				
• UC ₂ PARTICLE SIZE, μm						
95%	< 40	< 40				
50%	< 9	< 9				
5%	< 2	< 3				
• POLYSTYRENE PARTICLE SIZE, μm						
95%	< 225	< 225				
50%	< 150	< 150				
5%	< 50	< 50				
• URANIUM DENSITY, g/cm ³	2.438 ± 0.023	0.495 ± 0.005				
PLUTONIUM DENSITY, g/cm ³	1.012 ± 0.010	0.085 ± 0.001				
• FUEL COMPACT DENSITY, g/cm ³	4.520 ± 0.043	1.615 ± 0.017				
• DIMENSIONS OF FUEL COMPACTS, cm						
	LENGTH	WIDTH	THICKNESSES	LENGTH	WIDTH	THICKNESSES
UNCLAD COMPACTS	5.090 ± 0.005	5.083 ± 0.026	5.090 ± 0.005 ; 1.339 ± 0.026	5.090 ± 0.005	5.090 ± 0.025 (c)	5.090 ± 0.005 ; 3.400 ± 0.044 ; 1.384 ± 0.039
CLAD COMPACTS	5.114 ± 0.009	5.170 ± 0.026	5.114 ± 0.006 ; 1.363 ± 0.026	5.121 ± 0.005	5.137 ± 0.005 (d)	5.121 ± 0.005 ; 3.431 ± 0.044 ; 1.415 ± 0.039
CLAD COMPACTS + VOIDS	5.118 ± 0.015	5.174 ± 0.030	5.118 ± 0.015 ; 1.367 ± 0.026	5.130 ± 0.010	5.190 ± 0.025	5.130 ± 0.010 ; 3.440 ± 0.048 ; 1.424 ± 0.043

(a) ISOTOPIC ANALYSIS MADE ON 12-2-71. EXPERIMENTS PERFORMED JUNE 1973.

(b) ISOTOPIC ANALYSIS MADE ON 5-28-70. EXPERIMENTS PERFORMED MAY 1973.

(c) 5.095 ± 0.021 cm FOR THE 5.09 cm THICK COMPACTS.(d) 5.142 ± 0.021 cm FOR THE 5.121 cm THICK CLAD COMPACTS.

TABLE II

CALCULATED 18-ENERGY GROUP NEUTRON FLUX FOR PuO₂-UO₂-POLYSTYRENE FUELS

RELATIVE FLUX 30.6 H:Pu + U FUEL	LOWER ENERGY OF GROUP	RELATIVE FLUX 2.8 H:Pu + U FUEL
0.0024	7.79 MeV	0.0023
0.0069	6.07	0.0071
0.0155	4.72	0.0164
0.0253	3.68	0.0267
0.0337	2.87	0.0375
0.0958	1.74	0.1074
0.0475	1.35	0.0538
0.2419	183.00 keV	0.3212
0.0987	24.80	0.1404
0.0688	3.36	0.0912
0.0628	454.00 eV	0.0750
0.0447	101.00	0.0443
0.0284	37.30	0.0222
0.0264	13.70	0.0169
0.0245	5.04	0.0116
0.0250	1.86	0.0130
0.0220	0.683	0.0058
0.1297	0	0.0072

constant base of 9 fuel compacts on a side. The plates, having thicknesses up to about 2-1/2 cm and the same cross section dimensions as the assemblies, were positioned horizontally in the assemblies. Except for one series of experiments to measure the worth of a plate as a function of position in the assembly, the position of the plates, relative to the bottom of the assembly, was constant for each fuel. This distance from the bottom was such that the plates were approximately centered in the fuel for all the experiments. A portion of one experimental assembly is shown in Figure 1 with the remote operated split-table, used in the experiments, fully open and part of the reflector material removed.

In addition to the measurements with Cu or Cu-Cd plates, measurements were similarly made without any plates and with aluminum plates to provide a measure of the void effects relative to the poison effects caused by the plates being present in the assemblies. The compositions for each type plate are given in Table III.

DISCUSSION OF EXPERIMENTAL DATA

Critical heights were determined for the 30.6 H:Pu+U fueled assemblies both with and without poison regions in the fuel. The poisoned assemblies had either a single region of Al, Cu, or Cu-Cd plates or two regions separated by 5.09 cm of fuel. Except for one series of experiments, which will be covered later, the bottom plate, in either type assembly, was always located 10.32 cm from the bottom of the fuel. The geometries of these poisoned assemblies are shown graphically in Figures 2 and 3. The measurements with the Al and Cu plates were made with different thicknesses of plates up to about 2-1/2 cm. The measurements with the Cu-Cd plates were limited to a maximum thickness of about 2-1/4 cm for the single region experiments and to a single thickness of about 1/3 cm for the two-region experiments. The results of these experiments are shown graphically in Figures 4 and 5. Critical heights as a function of plate position in the 30.6 H:Pu+U fuel were also obtained for a single region of Al, Cu, or Cu-Cd about 1/3 cm thick. The results of these experiments are shown graphically in Figure 6.

FIGURE 1 - Experimental Assembly With
Part of the Reflector Removed

TABLE III

COMPOSITION OF NEUTRON POISON PLATES

ELEMENT	COPPER (8.913 g/cc)	COPPER CADMIUM (8.910 g/cc)	ALUMINUM (2.692 g/cc)
	WT%	WT%	WT%
Cu	99.960	98.685	0.14
Cd	-	0.989	-
Al	-	-	97.98
Zn	0.001	0.007	0.25
Sn	-	0.250	-
Ni	-	0.010	-
Fe	0.003	0.020	0.70
Cr	-	-	0.15
Mn	-	0.009	0.15
Mg	0.001	-	0.08
Ti	-	-	0.15
Si	0.001	0.004	0.40
O	0.030	0.019	-
C	0.004	0.002	-
B	-	0.005	-

ONE SIGMA LIMIT OF 0.003 WT% FOR CADMIUM.

IMPURITY ELEMENTS COULD BE OFF BY A FACTOR OF 3

FIGURE 2

PHYSICAL MODEL OF $\text{PuO}_2\text{-UO}_2$ -POLYSTYRENE ASSEMBLIES
SINGLE NEUTRON POISON PLATE

FIGURE 3

PHYSICAL MODEL OF PuO_2 - UO_2 -POLYSTYRENE ASSEMBLIES
TWO NEUTRON POISON PLATES

FIGURE 4

EFFECT OF Al, Cu AND Cu-Cd PLATES ON CRITICAL HEIGHT

FIGURE 5

EFFECT OF Al, Cu, AND Cu-Cd PLATES ON CRITICAL HEIGHT

FIGURE 6

EFFECT OF PLATE POSITION ON CRITICAL HEIGHT

Critical heights, both with and without plates of Al, Cu, or Cu-Cd, were similarly determined for the 2.8 H:Pu+U fueled assemblies. However, the measurements were limited to a single region of plates located 15.35 cm from the bottom of the fuel. The results of these experiments are shown in Figure 7.

It should be noted that the neutron importance in the vicinity of the plates is not the same in all of the assemblies. Consequently, the data as shown in Figures 4 through 7 are intended to show only approximately the relative effectiveness of the Cu and Cu-Cd plates as neutron absorbers in the two different fuels. From the data shown in these figures, however, the void and absorption effects, that the Cu and Cu-Cd plates have on the reactivity of each system, can be differentiated between and the relative effectiveness of each as an absorber can be obtained.

The changes in critical heights due to neutron absorption in different thicknesses of Cu and Cu-Cd plates in the 30.6 and the 2.8 H:Pu+U fuels are shown in Figure 8 along with the changes in critical heights due to the void these plates cause by their presence in each fuel. (The data, shown in Figure 8, was obtained from Figures 4 and 7.) As can be seen in Figure 8, the void (as represented by the Al + void data) introduced into the 2.8 H:Pu+U fueled assemblies by the Cu and Cu-Cd plates is worth more than neutron absorption in either of these plates over the thickness range covered in these experiments. In the more thermalized 30.6 H:Pu+U fuel the void effects are worth less than the neutron absorption in these plates. However, even in the 30.6 H:Pu+U fuel the continual increase in critical height, observed in the data shown in Figure 4, with increased thicknesses of Cu and Cu-Cd plates is due almost entirely to void effects above a given plate thickness. As can be seen in Figure 8, little, if any, additional neutron absorption occurs in the Cu plate at thicknesses greater than about 2-1/2 cm or in the Cu-Cd plate at thicknesses greater than about 1 cm. At thicknesses greater than these, self-shielding has precluded any additional absorption and the change in reactivity is due almost entirely to the additional void being introduced into the assemblies.

The experimental data as shown in Figure 8 also shows that significantly increased neutron absorption is obtained, even in the relatively fast neutron

FIGURE 7

EFFECT OF Al, Cu, AND Cu-Cd PLATES ON CRITICAL HEIGHT

FIGURE 8

CHANGES IN CRITICAL HEIGHT DUE TO REDUCTION OF
CORE DENSITY AND TO INCREASED NEUTRON ABSORPTION
PLEXIGLAS REFLECTED 9x9 ASSEMBLIES OF $\text{PuO}_2\text{-UO}_2\text{-POLYSTYRENE}$ COMPACTS

spectrum of the 2.8 H:Pu+U fuel, with 1 wt% Cd in the Cu-Cd plates. Of course, as shown in Figure 8, the Cd was found to be worth much more in the thermalized spectrum of the 30.6 H:Pu+U fuel.

DETAILED DESCRIPTION OF EXPERIMENTAL ASSEMBLIES

A detailed description is given in Table IV for each critical assembly fueled with the 30.6 H:Pu+U compacts. Each critical assembly of 2.8 H:Pu+U compacts is described in Table V. In both tables the layers of fuel above, below and between (when applicable) the poison plates are given. The dimensions associated with each type fuel layer are given in Table I along with the associated cladding thicknesses and stacking voids. The total number of fuel layers in terms of 5.09 cm thick compacts is also given for each assembly in Tables IV and V, and can be used to obtain a more simplified geometry description of each assembly.

The approach-to-critical for each of the assemblies shown in Tables IV and V was made by incrementally loading fuel compacts to the top face of each assembly in a symmetrical manner with respect to the neutron flux. Consequently, the fractional layers given in Tables IV and V should be treated as full layers of thinner fuel compacts having a thickness equal to the fractional layer times the full sized compact.

The effect of the cladding and stacking voids was experimentally determined⁽²⁾⁽³⁾ for each of these fuels. The fuel regions in each 30.6 H:Pu+U assembly can be expressed as homogeneous regions of PuO_2 - UO_2 -polystyrene fuel only, by reducing the critical mass of each assembly 3.92%. For the 2.8 H:Pu+U, corrections are not needed. The negative reactivity effects, caused by the stacking voids and the reduced fuel density due to the cladding being present, were compensated for by the positive worth of the additional hydrogen and carbon introduced into each assembly by the cladding material.

The total mass and thickness of Cu, Cu-Cd, or Al present in each poison region is also given in Tables IV and V for each critical assembly. In some of these assemblies the poison region actually is made up of several thinner plates stacked on top of one another to achieve the plate thickness that is indicated. The combined poison plate thickness and additional void space,

TABLE IV

PLEXIGLAS REFLECTED 9x9 ASSEMBLIES OF 30.6 H:Pu+U PuO₂-UO₂-POLYSTYRENE COMPACTS

LAYERS OF FUEL (a) (3.4cm)	TYPE	NEUTRON POISON PLATE					NEUTRON POISON PLATE					LAYERS OF FUEL (d)		TOTAL LAYERS OF FUEL (e)	KENO-11 k_{eff} (f)
		PLATE MASS (Kg)	PLATE THICKNESS (cm)	PLATE + VOID THICKNESS (cm)	REDUCED DENSITY (%)	LAYERS OF FUEL (c)	PLATE MASS (Kg)	PLATE THICKNESS (cm)	PLATE + VOID THICKNESS (cm)	REDUCED DENSITY (%)	LAYERS OF FUEL (c)	(5.09cm)	(1.384cm)		
3	NONE	0	0	0	-	2 1.276	-	-	-	-	-	-	-	4.351±0.004	1.018±0.005
3	1/8in. Cu	6.440±0.013	0.337±0.008	0.40±0.06	83.8	2 2.415	-	-	-	-	-	-	-	4.661±0.005	
3	1/4in. Cu	11.985±0.024	0.637±0.003	0.71±0.07	87.8	2 3.110	-	-	-	-	-	-	-	4.850±0.004	
3	1/2in. Cu	24.425±0.049	1.290±0.004	1.35±0.06	94.1	3 0.463	-	-	-	-	-	-	-	5.13 ±0.01	
3	3/4in. Cu	36.410±0.072	1.927±0.005	2.02±0.09	93.8	3 1.136	-	-	-	-	-	-	-	5.313±0.005	0.998 ± 0.006
3	1 in. Cu	48.785±0.096	2.580±0.006	2.70±0.10	94.0	3 1.746	-	-	-	-	-	-	-	5.479±0.001	
3	1/8in. Cu-Cd	6.905±0.014	0.368±0.005	0.43±0.06	83.6	3 0.757	-	-	-	-	-	-	-	5.210±0.003	
3	3/4in. Cu-Cd	40.635±0.081	2.160±0.006	2.30±0.10	91.9	3 2.698	-	-	-	-	-	-	-	5.738±0.006	
3	1/8in. Al	1.790±0.025	0.316±0.001	0.40±0.08	77.1	2 1.548	-	-	-	-	-	-	-	4.425±0.003	1.013±0.006
3	1/4in. Al	3.665±0.012	0.645±0.002	0.73±0.08	86.5	2 1.739	-	-	-	-	-	-	-	4.477±0.007	
3	3/4in. Al	11.270±0.049	1.983±0.004	2.06±0.07	94.2	2 2.713	-	-	-	-	-	-	-	4.742±0.004	1.020±0.007
3	1 in. Al	15.250±0.034	2.676±0.002	2.75±0.07	95.5	2 3.158	-	-	-	-	-	-	-	4.863±0.003	
(g)	1/8in. Cu	6.440±0.013	0.337±0.008	0.40±0.06	83.8	1 2.349	-	-	-	-	-	-	-	4.643±0.005	
(g)	1/8in. Cu-Cd	6.905±0.014	0.368±0.005	0.43±0.06	83.6	2 0.952	-	-	-	-	-	-	-	5.263±0.003	
(h)	1/8in. Cu-Cd	6.905±0.014	0.368±0.005	0.43±0.06	86.6	0 3.463	-	-	-	-	-	-	-	4.946±0.002	
3	1/8in. Cu	6.440±0.013	0.337±0.008	0.37±0.03	90.6	1 0	1/8in. Cu	6.415±0.013	0.337±0.008	0.37±0.03	90.2	1	3.603	4.984±0.005	
3	1/2in. Cu	24.425±0.049	1.290±0.004	1.33±0.04	95.5	1 0	1/2in. Cu	24.360±0.049	1.290±0.004	1.33±0.03	95.3	2	3.584	5.979±0.005	
3	3/4in. Cu	36.410±0.073	1.927±0.005	1.98±0.05	95.7	1 0	3/4in. Cu	36.450±0.072	1.927±0.005	1.98±0.05	95.3	3	1.129	6.311±0.003	1.020±0.005
3	1 in. Cu	48.470±0.096	2.565±0.006	2.68±0.06	94.1	1 0	1 in. Cu	48.450±0.096	2.565±0.006	2.68±0.06	94.1	3	2.092	6.573±0.003	
3	1/8in. Cu-Cd	6.905±0.014	0.368±0.005	0.41±0.04	87.6	1 0	1/8in. Cu-Cd	6.685±0.013	0.354±0.005	0.39±0.03	89.2	3	0.331	6.094±0.022	
3	1/8in. Al	1.790±0.025	0.316±0.001	0.34±0.02	90.7	1 0	1/8in. Al	1.790±0.025	0.317±0.002	0.34±0.02	90.7	1	1.812	4.497±0.002	
3	1 in. Al	14.940±0.056	2.628±0.004	2.68±0.05	96.0	1 0	1 in. Al	14.965±0.031	2.629±0.013	2.69±0.05	95.8	2	1.151	5.317±0.003	

(a) LAYERS OF 3.4cm THICK FUEL COMPACTS BELOW BOTTOM POISON PLATE UNLESS NOTED OTHERWISE

(b) PLATE MASS PER PLATE AND VOID VOLUME RELATIVE TO 8.913g Cu/cc, 8.910g Cu-Cd/cc, OR 2.692g Al/cc

(c) LAYERS OF 5.09cm AND 1.384cm THICK FUEL COMPACTS ABOVE OR BETWEEN POISON PLATES. FRACTIONAL LAYERS SHOULD BE TREATED AS FULL LAYERS HAVING THE INDICATED FRACTIONAL THICKNESS.

(d) LAYERS OF 5.09cm AND 1.384cm THICK FUEL COMPACTS ABOVE TOP POISON PLATE

(e) TOTAL LAYERS OF FUEL COMPACTS EXPRESSED AS EQUIVALENT 5.09cm THICK COMPACTS. MULTIPLY BY 0.9608 TO CORRECT FOR STACKING VOIDS AND CLADDING.

(f) 18-GROUP GAMTEC-II AVERAGED CROSS SECTIONS USING FLANGE-ETOG PROCESSED ENDF/B-3 DATA. 15000 HISTORIES AT 200 PER BATCH UNLESS NOTED OTHERWISE.

(g) THREE LAYERS OF 3.4cm PLUS ONE LAYER OF 5.09cm THICK FUEL COMPACTS BELOW POISON PLATE

(h) THREE LAYERS OF 3.4cm PLUS TWO LAYERS OF 5.09cm THICK FUEL COMPACTS BELOW POISON PLATE

TABLE V

PLEXIGLAS REFLECTED 9x9 ASSEMBLIES OF 2.8 H:Pu+U PuO₂-UO₂-POLYSTYRENE COMPACTS

LAYERS OF FUEL (a) (5.09cm)	NEUTRON POISON PLATE				REDUCED DENSITY (b) (%)	LAYERS OF FUEL (c)		TOTAL LAYERS OF FUEL (c)(d)	KENO-II k _{eff} (e)
	TYPE	PLATE MASS (Kg)	PLATE THICKNESS (cm)	PLATE + VOID THICKNESS (cm)		(5.09cm)	(1.339cm)		
-	NONE	0	0	0	-	4	4.207	4.997 ± 0.013	0.989 ± 0.006
3	1/8 in. Cu	6.440 ± 0.013	0.337 ± 0.008	0.41 ± 0.07	82.2	2	0.502	5.119 ± 0.010	0.988 ± 0.006
3	3/8 in. Cu	18.425 ± 0.037	0.974 ± 0.008	1.02 ± 0.07	94.5	2	1.321	5.313 ± 0.004	
3	3/4 in. Cu	37.280 ± 0.075	1.964 ± 0.012	2.06 ± 0.08	95.0	2	2.536	5.601 ± 0.013	0.976 ± 0.006
3	1/8 in. Cu-Cd	6.905 ± 0.014	0.386 ± 0.005	0.46 ± 0.07	78.5	2	0.738	5.175 ± 0.010	
3	3/8 in. Cu-Cd	20.419 ± 0.040	1.085 ± 0.005	1.18 ± 0.09	90.5	2	1.827	5.433 ± 0.003	
3	3/4 in. Cu-Cd	40.635 ± 0.081	2.160 ± 0.006	2.28 ± 0.09	93.2	2	3.468	5.822 ± 0.007	0.976 ± 0.006
3	1/8 in. Al	1.790 ± 0.025	0.316 ± 0.001	0.39 ± 0.07	79.5	2	0.342	5.081 ± 0.012	
3	3/8 in. Al	5.455 ± 0.044	0.961 ± 0.002	1.01 ± 0.05	93.5	2	0.873	5.207 ± 0.016	
3	3/4 in. Al	11.185 ± 0.083	1.971 ± 0.005	2.04 ± 0.08	95.0	2	1.688	5.400 ± 0.004	

(a) LAYERS OF 5.09 cm THICK FUEL COMPACTS BELOW POISON PLATE.

(b) PLATE MASS PER PLATE AND VOID VOLUME RELATIVE TO 8.913g Cu/cc, 8.910g Cu-Cd/cc, OR 2.692g Al/cc.

(c) LAYERS OF 5.09 cm AND 1.339 cm THICK FUEL COMPACTS ABOVE POISON PLATE. FRACTIONAL LAYERS SHOULD BE TREATED AS FULL LAYERS HAVING THE INDICATED FRACTIONAL THICKNESS.

(d) TOTAL LAYERS OF FUEL COMPACTS EXPRESSED AS EQUIVALENT 5.09 cm THICK COMPACTS.

(e) 18 GROUP GAMTEC-II AVERAGED CROSS SECTIONS USING FLANGE-ETOG PROCESSED ENDF/B-3 DATA. 15000 HISTORIES AT 200 PER BATCH UNLESS NOTED OTHERWISE.

caused by the neutron poison material being present, is shown for each poison region.

COMPARISON BETWEEN CALCULATIONS AND EXPERIMENTS

Effective multiplication constants were calculated for some of the experimental assemblies as indicated in Tables IV and V. The calculations were made with the Monte Carlo code KENO⁽⁴⁾ using 18-group GAMTEC-II⁽¹⁾ averaged cross sections that had been processed from the ENDF/B-III with FLANGE-II⁽⁵⁾ and ETOG-I⁽⁶⁾ codes. The geometries for each assembly were input to KENO as described in Tables IV and V and as shown in the applicable Figure 2 or 3. Stacking voids and cladding materials, as specified in Table I, were included in the calculational models. The mass of the Al, Cu or Cu-Cd plates was homogenized, at the reduced densities indicated in Tables IV and V, over the plate plus void space of the respective poison region. The KENO calculations were performed using 200 neutrons per generation and running for at least 75 generations. Additional generations were run if, after 15000 histories, k_{eff} had not attained a constant level as illustrated in Figure 9 for one of the critical assemblies.

As has been reported previously⁽²⁾⁽³⁾ for these two fuels, the calculated k_{eff} values are about 2% high for the 30.6 H:Pu+U fuel and 1 to 2% low for the 2.8 H:Pu+U fuel. However, as can be seen by comparing the poisoned with the unpoisoned k_{eff} values shown in Tables IV and V, the calculations reproduce the effects of the Al, Cu, and Cu-Cd plates with a reasonable degree of accuracy.

As indicated previously, the geometry of these assemblies can be simplified by describing the compacts in terms of a uniform set of compacts 5.09 cm thick. A further simplification can be accurately attained by applying the experimentally determined corrections previously discussed for the stacking voids and cladding materials. A calculational comparison was made between these simplified assemblies and the actual experimental assembly, and is shown in Table VII.

FIGURE 9

FIGURE 9 VARIATION IN k_{eff} AVERAGE WITH NEUTRON HISTORIES

TABLE VI

Comparison Between k_{eff} 's Calculated Using
Experimental Geometries and Simplified Geometries

<u>Critical Assembly</u>	<u>KENO-II k_{eff}</u>
30.6 H:Pu+U fuel as in experiment, including stacking voids and cladding material	1.018 $\pm$ 0.005
30.6 H:Pu+U fuel as uniform 5.09 cm thick compacts with stacking voids and cladding material	1.020 $\pm$ 0.006
30.6 H:Pu+U fuel as homogenized fuel corrected for stacking voids and cladding material	1.016 $\pm$ 0.009
2.8 H:Pu+U fuel as in experiment, including stacking voids and cladding material	0.989 $\pm$ 0.006
2.8 H:Pu+U fuel as homogenized fuel corrected for stacking voids and cladding material	0.989 $\pm$ 0.005

REFERENCES

1. L. L. CARTER, C. R. RICHIEY, and C. E. HUGHIEY, "GAMTEC-II: A Code for Generating Consistent Multigroup Constants Utilized in Diffusion and Transport Theory Calculations," BNWL-35, Pacific Northwest Laboratory (1965).
2. S. R. BIERMAN, E. D. CLAYTON, and L. E. HANSEN, "Critical Experiments With Homogeneous Mixtures of Plutonium and Uranium," Nucl. Sci. Eng., **50**, 115-126 (1973).
3. S. R. BIERMAN and E. D. CLAYTON, "Critical Experiments With Mixed Oxides of Pu and U Containing 8 and 30 wt% Plutonium," Trans. Am. Nucl. Soc., **15**, 1, 307 (1972).
4. G. E. WHITESIDES, "KENO - A Multigroup Monte Carlo Criticality Program," CTC-5, Computing Technology Center (September, 1969).

5. H. C. HONECK and D. R. FINCH, FLANGE-II (Version 71-1): A Code to Process Thermal Neutron Data From an ENDF/B Tape, DP-1278 (ENDF-152), Savannah River Laboratory, Aiken, South Carolina (1971).
6. D. E. KUSNER, R. A. DANIELS, and S. KELLMAN, ETOG-I: A FORTRAN-IV Program to Process Data from the ENDF/B File to the MUFT, GAM, and ANISN Formats, WCAP-3845-1 (ENDF-114), Westinghouse Electric Corporation (1969).

DISTRIBUTIONCopy
NumberOFF-SITE DISTRIBUTIONUSAEC, Washington-Office of Regulation

1-12 S. H. Smiley
13-14 R. H. Odegarden

USAEC, Washington-Division of Reactor Development and Technology

15 Philip B. Hemmig

ON-SITE DISTRIBUTIONUSAEC, Richland Operations Office

16 R. L. Ferguson
17 F. R. Standerfer
18 B. J. Melton

Battelle-Northwest

19 S. R. Bierman
20 C. L. Brown
21 N. E. Carter
22 D. L. Condotta
23 L. C. Davenport
24 S. W. Heaberlin
25 R. C. Lloyd
26 D. R. Oden
27-29 Technical Information Files