Progress Report
for
ERDA Contract AT(11-1) 2218
titled
CTR Plasma Engineering Studies*

for the period

1 September 1974 to 31 August 1975

by

George H. Miley
Principal Investigator

Nuclear Engineering Program
University of Illinois
Urbana, Illinois 61801

1 June, 1975

NOTICE
This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

MASTER

* Due to a consolidation of subtasks under this contract, the title has been modified accordingly.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Table of Contents

	<u>page</u>
1. Introduction	1
2. Mirror Injection and Plasma Build-Up Studies	1
3. Two-Component Plasma Calculations	2
a) Calculation in Support of TFTR Design	2
b) D-T Burn Simulation	3
c) Clamped Burns	4
4. Advanced Fuel Studies	4
a) Cross Sections and Reactivities	4
b) Cyclotron Emission	4
c) Wall Reflectivity	5
d) Optimized Catalyzed D-D Operation	5
5. Related Studies	6
6. Listing of Reports Issued During the Period	7

1. Introduction

During the past contract period this research was concerned with three main subtasks:

- a) Neutral beam injection and charge exchange losses for mirror systems
- b) Two-component plasma calculations and fusion burn simulation, and
- c) Studies of special problems such as cyclotron effects related to the use of advanced fusion fuels.

Each of these areas is discussed in more detail in following sections.

The year was extremely active with the result that a number of reports, papers, and talks were presented. For convenience a listing of reports issued during the period is presented in Section 6.

Since most of the details of the work under this contract are contained in these reports, the following sections will simply highlight the progress and refer back to the related report(s).

2. Mirror Injection and Plasma Build-Up Studies (R. L. Miller, M. Campbell)*

Work during this period has concentrated on the development of a Monte Carlo program that treats trapping and charge exchange of the injected beam in a realistic mirror geometry.

The first half of the period was consumed with the development of appropriate averaged cross-sections for ionization and charge exchange. The results, presented in C00-2218-26,** extend previous calculations by Riviere [Nuclear Fusion, 11, 363, (1971)] to include averages over a mirror energy dis-

*The graduate assistants involved in each task are indicated in each heading.

**Complete references to these reports are given in the listing in Section 5.

tribution with arbitrary ion or neutral energy and direction relative to the magnetic field. These results represent, in effect, a cross section library for the Monte Carlo code.

The code itself (called NUBIN), along with some first results, are described in COO-2218-38. It has been written in quite general terms to allow variations in injected beam geometry and intensity profile, direction relative to the mirror field, and density-temperature variation of the target plasma. Most of the numerical techniques employed are quite similar to those used in neutron transport codes. However, some relatively new methods, such as interactive sampling are employed.

Several test runs for simple cases where analytic solutions are known have been performed to verify the accuracy of the code. More realistic runs for a mirror-FERF reactor are now in progress. This will provide a detailed distribution for charge exchange neutrals hitting the first wall, a key aspect relative to both the heat load and wall erosion.

Work has begun on a companion build-up code which will be discussed further during the next contract period.

Both the injection and build-up work are being done in close collaboration with workers at the Lawrence Livermore Laboratory, and their continued encouragement and help are gratefully acknowledged.

3. Two-Component Plasma Calculations

a) Calculation in support of TFTR design (H. Towne and S. Justiss)

A variety of relatively specialized calculations were carried out in collaboration with PPPL staff in support of the TFTR design effort. Reports COO-2218-19 and 20 show that a finite background ion temperature can, in fact, provide a slight increase in energy multiplication for the lower injection

energies expected in earlier experiments. Likewise, energy dispersion during slowing of injected ions is shown to have a positive effect in this region (Report COO-2218-23). These results plus other cross section information were summarized in a review paper prepared for the Conference on Nuclear Cross Sections and Technology (Washington, D. C., March 1975) which was issued as COO-2218-28.

More recently, a study of the sensitivity of TFTR operation to changes in various parameters has been completed. As summarized in COO-2218-35, the injection performance appears to be the key element in the success of this project. If, for example, the injection energy could only reach 80% of the design value, the energy multiplication would fall off by a factor of 0.7. This is more than predicted in earlier studies, principally due to the changes in target heating which are handled in a self-consistent fashion in these calculations.

b) D-T Burn Simulation (T. Petrie)

The objective of this work is to find methods to simulate fusion product effects prior to actually burning D-T fuel in the TFTR. If successful, this would allow any necessary changes to be made before the TFTR is activated by D-T neutrons and contaminated with tritium.

One method under study last period is the injection of deuterium into a cold ^3He plasma. Such experiments are scheduled for TFTR anyway, but it has generally been thought that the fusion power density would be too low to be of interest. It is shown in COO-2218-27, however, that by reducing the background density, the ratio of fusion product to background pressure can be adjusted to simulate D-T burns fairly well. More recent calculations of fusion product energy deposition (COO-2218-36) indicate that under similar conditions, relative product heating will be about one-third of that expected for D-T. This should

be satisfactory provided other quantities such as the induced plasma rotation can also be held in a reasonable range, and this is now under study.

c) Clamped Burns (M. Rao, D. Driemeyer, B. Darnell)

Continued compression during the burn period can be used to clamp the superthermal ions near the optimum energy for fusion. This is considered as an alternate mode of operation for the TFTR, and appropriate magnet circuits and plasma volume are provided in the design. A point reactor code has been developed that includes a detailed development of the plasma energetics and dynamics during such burns. Preliminary results presented at the IEEE plasma sciences meeting in Ann Arbor (C00-2218-29) are encouraging in that reasonable cycle efficiencies are predicted. On the other hand some problems such as excessive heating of the target plasma suggest that a modified partial clamping may be desirable. Optimization of the cycle is, then, under continued study.

4. Advanced Fuel Studies

a) Cross Sections and Reactivities (H. Towner)

A comprehensive tabulation of cross sections and reactivities for both Maxwellian and two-component plasmas has been compiled and published as a "barn book" (C00-2218-17). Over 100 copies were originally distributed and due to continued requests a second printing was recently completed at ERDA headquarters. While similar compilations of Maxwellian reactivities have previously been available, this represents the first collection of reactivities for two-component operation. A number of advanced fuels are included in addition to D-T.

b) Cyclotron Emission (T. Chu)

Cyclotron emission is viewed as critical problem for advanced fuels. To better understand this, more accurate methods for evaluation of its transport and

emission from fusion plasmas are under development. In particular, in order to handle non-Maxwellian situations, a treatment using electron groups has been devised (see C00-2218-22). This technique is now being incorporated in a multigroup fusion plasma code at the Lawrence Livermore Laboratory.

In addition, the effect of cyclotron radiation on the operation of catalyzed D-D reactors has been studied in some detail. Results reported in C00-2218-32 and 37 for toroidal reactors are encouraging in the sense that reasonably high overall efficiencies can be obtained even with strong emission. However, this requires fairly high β (~ 0.1) or large recirculation powers to prevent excessive plasma cooling. Still, the fact that an operating region can be identified is encouraging and warrants further study.

c) Wall Reflectivity (G. Fenske)

The reflection of cyclotron radiation from the first wall of a reactor represents an important mechanism for reducing cyclotron losses. However, as blistering of the wall occurs during operation, the reflectivity may change drastically. Some very crude measurements described in Report C00-2218-34 indicate that indeed the reflectivity could be reduced by 50% or more. This could be a serious problem since the increased absorption could cause excessive local heating, hence rapid erosion and deterioration of the wall. Further studies appear warranted.

d) Optimized Catalyzed D-D Operation (W. Downum)

The use of two component operation and clamped burns in order to increase the power density of Cat. D-D reactors is discussed in Reports C00-2218-30 and 37. Improvements ranging from 5 to 20 in the power density relative to normal Maxwellian operation appear to be possible. The larger gains occur at a sacrifice in energy multiplication (Q_p), however. Thus the recirculation requirements offset some of the benefit in power density. Studies are now in

progress to find an optimum trade-off between these factors.

5. Related Studies

Techniques developed in this work are applied to the analysis of energy balances for fission-fusion hybrids in Reports C00-2218-25 and 33. While it is generally recognized that a fissionable blanket reduces confinement requirements for the fusion plasma, these reports provide a quantitative evaluation of the situation.

6. Listing of Reports Issued During the Period

7

AT(11-1)2218 Reports

<u>Report No.</u>	<u>Authors</u>	<u>Title & Publication</u>
19	H. Towner, G. Miley, D. Jassby, and F. Tenney	"Finite Ion Temperature Effects in Two Component Plasmas", <u>Bulletin APS</u> , <u>19</u> , 877 (1974).
20	M. Rao and G. Miley	"A Scheme for Achieving Ignition in Fusion Reactors," <u>Bulletin APS</u> , <u>19</u> , 878 (1974).
21	H. Towner and G. Miley	"Ion Temperature Effects in Two Component Systems", <u>Trans., Am.</u> <u>Nuc. Soc.</u> , <u>19</u> , 11 (1974).
22	T. Chu and G. Miley	"Evaluation of Cyclotron Radiation Using Monoenergetic Electron Groups," <u>Trans. Am. Nuc. Soc.</u> , <u>19</u> , 13 (1974).
23	G. Miley and S. Justiss	"Effect of Dispersion in Ion Slowing Down On Plasma Energy Multiplication Factors".
24	G. Miley and H. Towner	"Reactivities for Two-Component Fusion Calculations," <u>Conf. on Cross Section</u> <u>& Tech.</u>
25	G. H. Miley	"Energy Balances for Fusion-Fission Hybrids," AEC Mtg. on Hybrids, Dec. 1974.
26	R. Miller and G. Miley	"Ionization and Charge Exchange Rate Coefficients for CTR Calculations".
27	T. Petrie	"Simulation of a D-T Burn Using D ³ He in TCT. Part I. Superthermal Ion and Fusion Product Pressure Considerations."
28	G. Miley and H. Towner	"Reactivities for Two-Component Fusion Calculations," <u>Conf. on Nuclear Cross</u> <u>Sec. and Tech.</u> , Wash., D.C., March 1975.
29	G. H. Miley	"Compression-Expansion Cycles for Clamped Burns," 2nd IEEE Internat. Conf. Plasma Sci., Ann Arbor, Mich.
30	G. Miley and F. Southworth	"Two Component Catalyzed D-D Fusion," 2nd IEEE Internat. Conf. Plasma Sci., Ann Arbor, Mich.

- 31 R. Miller and G. Miley "Monte Carlo Simulation of Neutral Beam Injection Into Fusion Reactors," 2nd IEEE Internat. Conf. Plasma Sci., Ann Arbor, Mich.
- 32 G. Miley and T. Chu "Effect of Radiation Losses on Fusion Energy Balances," Trans. Am. Nuc. Soc., 20, 1975.
- 33 G. H. Miley "Plasma Requirements for Fusion-Fission Hybrids," Trans. Am. Nuc. Soc., 20, 1975.
- 34 G. Fenske "Preliminary Measurement of the Effect of Surface Blistering on the Reflectivity of a CTR First Wall"
- 35 H. H. Towner "Parameter Studies for a Two-Component Fusion Experiment"
- 36 T. Petrie and G. H. Miley "Simulation of a D-T Burn using D^3He in TCT: Part II-Superthermal Fusion Product Energy Deposition"
- 37 G. H. Miley "Energy Balances and Direct Conversion for Toroidal D-D Fusion Reactors." 7th European Meeting on Plasma Physics and Fusion (1975).
- 38 R. L. Miller "Monte Carlo Simulation of Neutral Beam Injection into Fusion Reactors"