SWPO-C 63-3719

CONFIDENTIAL
RESTRICTED DATA
Atomic Energy Act 1954

Westinghouse Electric Corporation
Astronuclear Laboratory

OK2

CONFIDENTIAL
RESTRICTED DATA
Atomic Energy Act 1954

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

23

10

RECORD COPY

Astronuclear

WANL-TNR-062

WESTINGHOUSE ELECTRIC CORPORATION
ASTRONUCLEAR LABORATORY

P. O. Box 10864

Pittsburgh 36, Pa.

May, 1962

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Classification cancelled (or changed to) _____
by authority of Doe
by H.F.C. 78-10 SEP 10 1973

Author:

E.A. DeZubay

LAMINAR FLOW
INSTABILITIES
PART 1

(Title Unclassified)

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

RECORD COPY

SPECIAL REVIEW FINAL DETERMINATION	Reviewed/	Class.	Date
	KAW	U	2-26-82
Class: <u>U</u>			

CONFIDENTIAL

UNCLASSIFIED DATA

CONFIDENTIAL
RESTRICTED

TABLE OF CONTENTS

and

LIST OF FIGURES

	<u>Page</u>
1.0 Summary	1
2.0 Introduction	2
3.0 Analysis of Model	3
4.0 Discussion	6
5.0 Conclusion	12
6.0 Recommendations	12
Figure 1 - Typical Temperature Responses	15
Figure 2 - Viscosity Integral	16
Figure 3 - Laminar Flow, Pressure Drop Relations	17
Table 1 - Solutions of Viscosity Integral	18
Appendix A - Calculation of Numerics	19
Appendix B - Nomenclature	20

CONFIDENTIAL
RESTRICTED

1.0 SUMMARY

The problem of laminar instability, defined as multivalued flow for a given pressure drop is considered from its basic derivations in this treatment of the problem. The conditions under which such flows can occur are determined and recommendations for future analytical and experimental work are suggested. The treatment of the problem as presented herein is to be considered as the introduction to subsequent reports which will cover the problem in greater depth.

2.0 INTRODUCTION

The problem of laminar flow instability in heated ducts has been the subject of considerable interest in nuclear devices. Abbreviated mathematical treatments are cited in a few references, and for this reason the development made in this report has gone into considerable detail in the formulation and solution of the mathematical models. The development used is to be considered as tentative and will be followed by more sophisticated treatments in the future. Several inherent simplifying assumptions will be evident and may be controversial. These are the assumption that the velocity distribution under conditions of laminar flow with heat transfer does not change appreciably from the conventional parabolic distribution obtained for Newtonian flow with no heat addition, and the assumption that the viscosity is a power function of the temperature under all conditions. Even with these simplifying assumptions, the closed form solution derived herein does clarify some of the controversial points of laminar flow instability.

3.0 ANALYSIS OF MODEL

The solution of laminar flow with heat transfer in a circular tube can be treated on the basis of the following model:

Let us establish a set of cylindrical coordinates and place a tube of radius R and length dx in this system as shown.

The pressure drop associated with the flow through the element dx can be considered as a combination of the pressure drop (dP_m) due to the momentum change and the pressure drop (dP_f) due to the shear at the wall. The former is directly expressible as:

$$dP_m = - \rho v dv$$

where:

ρ = density

v = velocity in x direction

The pressure drop due to the shear at the wall can be obtained from:

$$dF_s = \pi R^2 dP_f = -2 \pi R \tau_w dx$$

where:

F_s = shear force

τ_w = shear stress at tube wall where $r = R$.

The shear at any point in the stream is defined as:

$$\tau = -\mu \frac{dv}{dr}$$

which at the wall becomes:

$$\tau_w = -\mu \left. \frac{dv}{dr} \right|_{r=R}$$

where:

μ = viscosity

$\left. \frac{dv}{dr} \right|_{r=R}$ = the velocity gradient at the wall.

The sum of the pressure drops (dP) can be obtained as:

$$dP = dP_m + dP_f = -\rho v dv + 2 \mu \left. \frac{dv}{dr} \right|_{r=R} \cdot \frac{dx}{R}$$

From the continuity equation for a constant cross section tube $v = G/\rho$

where: G = mass velocity.

The differential form of the pressure drop then becomes:

$$dP = -G^2 d \left(\frac{1}{\rho} \right) + 2 \mu \frac{dx}{R} \left. \frac{dv}{dr} \right|_{r=R} \quad (1)$$

If the assumption is made that the laminar flow profile with heat addition remains parabolic⁽¹⁾ then:

$$v(r) = 2 \frac{G}{\rho} \cdot \left(1 - \left(\frac{r}{R} \right)^2 \right) \quad \text{or}$$

$$\frac{dv(r)}{dr} = -4 \frac{G}{\rho} \left(\frac{r}{R^2} \right)_{r=R} = -4 \frac{G}{\rho R} \quad (2)$$

Introducing the dimensionless length $\xi = x/L$ where L = tube length, the boundary conditions can be listed as:

Variable	P	ρ	μ	$\xi = x/L$	T
Entrance	P_1	ρ_1	μ_1	0	T_1
Exit	P_2	ρ_2	μ_2	1	T_2

The differential equation (1) with the appropriate substitution from (2) becomes:

$$\int_{P_1}^{P_2} dP = -G^2 \int_{\rho_1}^{\rho_2} d\left(\frac{1}{\rho}\right) - \frac{8GL}{R^2} \int_0^1 \frac{\mu}{\rho} d\xi \quad (3)$$

or on integration:

$$P_1 - P_2 = G^2 \left(\frac{1}{\rho_2} - \frac{1}{\rho_1} \right) + \frac{8GL}{R^2} \int_0^1 \frac{\mu}{\rho} d\xi \quad (4)$$

(1) Drew and Hoopes "Advances in Chemical Engineering", Vol. I, Academic Press, Inc. (1956) p. 78 - 118. (U)

Within limits, the viscosity can be expressed as $\mu = \mu_1 \left(\frac{T}{T_1} \right)^n$ $n < 1$ (actually about

0.73 for hydrogen) and $\rho = \rho_1 \left(\frac{T_1}{T} \right) \left(\frac{P}{P_1} \right)$ so that:

$$\frac{\mu}{\rho} = \frac{\mu_1}{\rho_1} \left(\frac{T}{T_1} \right)^{n+1} \left(\frac{P_1}{P} \right) \quad (5)$$

and equation (4) reduces to the general form of:

$$P_1 - P_2 = \frac{G^2}{\rho_1} \left(\frac{T_2}{T_1} \frac{P_1}{P_2} - 1 \right) + \frac{8G}{R^2} \frac{\mu_1 L}{\rho_1} \int_0^1 \left(\frac{T}{T_1} \right)^{n+1} \frac{P_1}{P} d\xi \quad (6)$$

4.0 DISCUSSION

Equation (6) is the general expression where the first term is attributable to the momentum change and the second term is attributable to the wall shear and requires the definition of pressure (P) and temperature (T) as a function of length. If P and T can be expressed as functions of the mass flow per unit area and the tube length, the closed form solution of ΔP , that is $(P_1 - P_2)$ can be obtained. For a given power input over the tube length, the energy equation can be used to define the temperature distribution axially in the tube. By equating power input from the origin to a point x, the enthalpy increase in the gas can be obtained as:

$$Q \frac{x}{L} = w (H - H_1) = w H_1 \left(\frac{H}{H_1} - 1 \right)$$

where:

- Q = power input into tube in length (L)
- w = mass flow through tube and equal to $G \frac{\pi D^2}{4}$
- c = mean specific heat at constant pressures
- H = enthalpy of gas at point x and equals c T
- H₁ = enthalpy of gas at inlet and equals c T₁

Therefore,

$$Q\xi = \frac{G \pi D^2 H_1}{4} \left(\frac{H}{H_1} - 1 \right) \quad (7)$$

which would be identical to:

$$Q\xi = \frac{G \pi D^2 H_1}{4} \left(\frac{T}{T_1} - 1 \right) \quad (7.1)$$

only if the mean specific heat applicable to T would be identical to the mean specific heat applicable to T_1 . In other words, equation (7) is generally valid while (7.1) is valid only if the mean specific heat in the temperature interval of $T_2 > T > T_1$ were constant. Letting

$$B = \frac{4Q}{\pi D^2 H_1} \quad \text{as a lumped constant reduces equation (7) to:}$$

$$\xi \frac{B}{G} = \left(\frac{H}{H_1} - 1 \right) \quad (8)$$

and similarly (7.1) to:

$$\xi \frac{B}{G} = \left(\frac{T}{T_1} - 1 \right) \quad (8.1)$$

This latter form of the flow-temperature equation would require an infinite temperature when the flow (G) became zero. From a physical viewpoint this condition becomes meaningless since the containing walls of the tube would melt and vaporize at some small but finite flow. The gases flowing through the tube would begin to deviate markedly from the linearity suggested by equation (8) due to the contributions of higher modes of molecular excitation (increased specific heat) as well as energy absorption by dissociation and ionization. As a result of these effects the temperature rise per unit energy addition would tend to become progressively less.

Equation (8.1) can be expressed in a limiting form which could be interpreted physically as a gas which would reach a limiting high temperature limit of T_m/T_1 . For such a representation the form

$$\xi \frac{B}{G} = \left(\frac{T_m}{T_1} - 1 \right) \tanh^{-1} \left(\frac{\left(\frac{T}{T_1} - 1 \right)}{\left(\frac{T_m}{T_1} - 1 \right)} \right) \quad (9)$$

would be useful since the above form behaves as

$$\xi \frac{B}{G} = \left(\frac{T}{T_1} - 1 \right) \text{ for } \frac{T}{T_1} \ll \frac{T_m}{T_1} \quad \text{and}$$

$\xi \frac{B}{G}$ approaches $\left(\frac{T_m}{T_1} - 1 \right)$ as $\frac{T}{T_1}$ approaches $\frac{T_m}{T_1}$. Solving equations (8) and

(9) for the temperature ratio yields:

$$\frac{T}{T_1} = 1 + \xi \frac{B}{G} \quad (10)$$

and

$$\frac{T}{T_1} = 1 + \left(\frac{T_m}{T_1} - 1 \right) \tanh \frac{\xi \frac{B}{G}}{\frac{T_m}{T_1} - 1} \quad (11)$$

The typical behavior of equations (10) and (11) is shown on Figure (1).

The temperature behavior depicted on Figure (1) can be considered as representative of a real gas with a progressively increasing specific heat which, in turn, can be attributed to contributions from molecular translation, rotation and vibration, and final electronic energy states (ionization). When the energy addition is small the linear behavior $\frac{T_2}{T_1} - 1$ with the energy addition $\frac{B}{G}$ or $\frac{H_2}{H_1} - 1$ implies a constant specific heat and as the slope is reduced a higher apparent specific heat is indicated which statistically accounts for contributions from all energy states over and above molecular translation.

Equation (6) can now be rearranged in the generalized form:

$$\frac{\rho_1 \Delta P}{B^2} = \left(\frac{G}{B} \right)^2 \left(\frac{T_2}{T_1} - 1 \right) + \frac{8 \mu_1 L}{BR^2} \int_0^{\xi=1} \left(\frac{G}{B} \right)^2 \left(\frac{T}{T_1} \right)^{n+1} d\left(\xi \frac{B}{G} \right) \quad (12)$$

if the usual assumption is made that $P_1 - P_2 = \Delta P$ and $\frac{P_1}{P_2} \approx 1$. For the temperature ratio as expressed by equation (10) the integral equation becomes:

$$\frac{\rho_1 \Delta P}{B^2} = \frac{G}{B} + \frac{8 \mu_1 L}{BR^2} \int_0^{\xi=1} \left(\frac{G}{B} \right)^2 \left(1 + \xi \frac{B}{G} \right)^{n+1} d\left(\xi \frac{B}{G} \right) \quad (13)$$

and for the temperature ratio as expressed by equation (11) a similar result as shown by equation (14) on the next page can be obtained.

$$\frac{\rho_1 \Delta P}{B^2} = \left(\frac{G}{B} \right)^2 \left(\frac{T_m}{T_1} - 1 \right) \tanh \frac{\frac{B}{G}}{\frac{T_m}{T_1} - 1} +$$

$$\frac{8 \mu_1 L}{BR^2} \int_0^{\xi=1} \left(\frac{G}{B} \right)^2 \left[1 + \left(\frac{T_m - T_1}{T_1} \right) \tanh \frac{\xi \frac{B}{G}}{\frac{T_m}{T_1} - 1} \right]^{n+1} d\left(\xi \frac{B}{G} \right) \quad (14)$$

The dimensionless pressure ratio $\Pi = \frac{\rho_1 \Delta P}{B^2}$ can now be discussed in terms of

two terms, the momentum pressure drop $\left(\frac{G}{B} \right)^2 \left(\frac{T_2}{T_1} - 1 \right)$ and the friction drop $\frac{8 \mu_1 L}{BR^2} \mathbf{I}$

where $\mathbf{I}$ is the viscosity integral as defined by:

$$\mathbf{I} = \int_0^{\xi=1} \left(\frac{G}{B} \right)^2 \left(\frac{T}{T_1} \right)^{n+1} d\left(\xi \frac{B}{G} \right)$$

The momentum term in both equations (13) and (14) simply approaches zero as $\frac{G}{B}$ becomes small. The expansion of the argument of the hyperbolic tangent as a series will quickly substantiate the preceding statement for (14). Furthermore, the hyperbolic tangent is a progressively increasing function of its argument for all positive values. Therefore both the linear and hyperbolic temperature expressions (equation 10 and 11) are single valued. The situation is more complex for the friction term and a detailed examination of the viscosity integral $\mathbf{I}$ is in order. Table I lists the solutions which can be obtained quickly for various assumptions of temperature and viscosity indices (n). These values are graphically

indicated on figure 2 for small values of $\frac{G}{B}$. The solid lines represent an unbounded temperature value (linear behavior, equation 10) and the dotted lines use bounded or limited temperature values (hyperbolic tangent behavior, equation 11). It can easily be established that for ($n > 0$) the viscosity integral for the unbounded behavior approaches infinity when the flow approaches

zero*. For the bounded behavior, $\frac{T_m}{T_1} = 31$, the value of the integral is zero for no flow as shown by the dotted curves which quickly approach the unbounded behavior for values of $\frac{G}{B}$ greater than one half. The steepness of the initial rise of the value of the viscosity integral in the vicinity of $\frac{G}{B}$ close to zero is by inspection of the forms of the solution on Table I dependent on the allowable temperature T_m . If this value were sufficiently low, the peak represented at

$\frac{G}{B} = .03$, $I = 8.55$ would progressively move to higher values of $\frac{G}{B}$ and lower values of I until it would be lost in the generally rising portion of the curve. Multivalued flows would be possible for given values of the viscosity integral in three of the five curves shown on figure 2. Such multivalued possibilities would in turn lead to the laminar instability of equation (6) where more than one flow can cause the identical value of the pressure drop. On figure 3, the dimensionless pressure drops are shown as a function of the dimensionless flow parameter for various limiting temperatures (for $n = 1$). The numerics for figure 3 are given in Appendix A, and correspond to typical values which could be expected in a reactor. It is of interest

*For small values of flow the viscosity integral (Table I) can be considered as

$$\text{Limit}_{G \rightarrow 0} \frac{\left(1 + \frac{B}{G}\right)^{n+2} - 1}{\left(\frac{B}{G}\right)^2} \quad \text{which by successive differential of numerator and denominator can be shown to be (L Hospital's rule):}$$

$$\text{Limit}_{G \rightarrow 0} \frac{(n+2)(n+1) \left(1 + \frac{B}{G}\right)^n}{2} = \infty \quad \text{for } n > 0.$$

[REDACTED]

to note that the pressure drops shown, follow the general form predicted by Bussard and DeLauer ⁽²⁾ only for the case of unlimited temperature rise. The general type of solution predicted by the temperature limited cases correspond to those predicted by the WANL program. ⁽³⁾

5.0 CONCLUSION

The calculations of the solutions of general pressure drop equation (6) obtained in this first report indicate the following conclusions:

1. The laminar instability condition is very sensitive to the high temperature transport and thermodynamic properties of the gas.
2. The hydrodynamic assumptions used in obtaining the classic solutions of laminar flow must be re-examined very critically in the light of the flow conditions existing in the range of the suspected instabilities.

6.0 RECOMMENDATIONS

On the basis of the results and conclusions obtained from this report, the following steps are recommended:

1. Analytic work must be continued in order to clearly define the instability behavior of an individual tube. This must include the pressure level effect assumed to be negligible in equation (12). A detailed derivation of laminar flow with heat transfer is also required. Such a treatment would require the extension

(2) Bussard and DeLauer "Nuclear Rocket Propulsion", McGraw Hill (1958) p. 129. (U)

(3) WANL-TNR-004 "Reactor Thermal Design", March 1962, Figure 4. 1. (C)

of the Graetz problem⁽⁴⁾, discussed in detail by Jakob⁽⁵⁾, to the conditions imposed by this problem. The Graetz problem considers the solution of the differential equation

$$\rho v c \frac{\partial T}{\partial x} = k \nabla^2 T \quad (15)$$

where

$$\nabla^2 = \frac{\partial^2}{\partial r^2} + \frac{1}{r} \frac{\partial}{\partial r} + \frac{\partial^2}{\partial x^2}$$

for an assumed parabolic velocity distribution and a uniform surface temperature. The boundary conditions were changed to constant heat flux by Sellars, et al⁽⁶⁾. The solutions of the Graetz problem using equation (15) neglect momentum considerations and imply the satisfaction of continuity by the use of a parabolic velocity distribution. Later treatments, of which Koppels solution can be considered representative⁽⁷⁾, consider the equation of continuity, fluid and thermal energy as

$$\frac{\partial}{\partial x} (\rho v) = 0 \quad (16)$$

(4) Graetz, L., *Annalen'd Physik* 18, 79, 1833; idem 25, 337; 1885

(5) Jakob, M., "Heat Transfer", Vol. I, 1949. Wiley & Sons, p. 451 - 469.

(6) Sellars, J. R., Tribus, J. R., Klein, J. S., "Heat Transfer to Laminar Flow in a Round Tube or Flat Conduit". *Trans. ASME*, Vol. 18, 1956.

(7) Koppel, L. B. and Smith, J. M., "Laminar Flow Heat Transfer for Variable Properties". *J. Heat Transfer* 18, C, 2, 1962.

$$\frac{1}{r} \frac{\partial}{\partial r} \left(r \mu \frac{\partial v}{\partial r} \right) = - \frac{\partial P}{\partial x} + \rho \quad (17)$$

$$\rho v c \frac{\partial T}{\partial x} = \frac{1}{r} \frac{\partial}{\partial r} \left(k r \frac{\partial T}{\partial r} \right) \quad (18)$$

Even these solutions neglect pressure forces, viscous dissipation and axial conduction in energy equation, as well as the equation of radial motion. (u , the radial component of velocity and all its derivatives are assumed zero.) The acceleration terms associated with the acceleration of a gas resulting from a reduced pressure and increased temperature (usually in the form of $v \frac{\partial v}{\partial x}$) are also missing from equation (17). A closed form solution incorporating as a minimum the variable properties of the gas implied in equation (16), (17) and (18) together with the missing acceleration terms would be very informative and helpful in establishing a more exact prediction of pressure drop vs flow behavior than that derived by the development in this report.

2. Experimental measurements of heated tubes simulating actual reactor conditions. Further investigations may permit fundamental investigations of this phenomenon at lower temperature levels where stainless steels or nickel tubes could be used with more readily dissociated cases such as NH_3 or NO_2 to establish fundamental behavior with more readily adaptable equipment.
3. Initiate the planning of high temperature experiments adaptable to the incorporation in the furnaces now being designed for fuel element corrosion studies.

[REDACTED]
 [REDACTED]
 [REDACTED]

FIGURE I
 TYPICAL TEMPERATURE RESPONSE TO HEAT ADDITION
 BY EQUATIONS 10 AND 11

[REDACTED]
 [REDACTED]
 [REDACTED]

FIGURE 2
VISCOSITY INTEGRAL FOR SMALL VALUES OF FLOW

FIGURE 3
LAMINAR FLOW PRESSURE DROP RELATIONS
 $B = 1.0 \text{ lb./ft}^2 \text{ sec.}$,
 $8\mu L / BR^2 = 3$

TABLE 1

SOLUTIONS OF VISCOSITY INTEGRAL I

$$I = \int_{\xi=0}^{\xi=1} \left(\frac{G}{B} \right)^2 \left(\frac{T}{T_1} \right)^{n+1} d \left(\xi \frac{B}{G} \right)$$

Type	n	$\frac{T}{T_1}$	I
1	0.00	$1 + \xi \frac{B}{G}$	$\frac{1}{2} + \frac{G}{B}$
2	0.73	$1 + \xi \frac{B}{G}$	$\left(\frac{G}{B} \right)^2 \left[\frac{\left(1 + \frac{B}{G} \right)^{2.73} - 1}{2.73} \right]$
3	1.00	$1 + \xi \frac{B}{G}$	$\frac{G}{B} + 1 + \frac{B}{3G}$
4	0.00	$1 + \left(\frac{T_m - T_1}{T_1} \right) \tanh \frac{\xi B T_1}{G (T_m - T_1)}$	$\frac{G}{B} + \left(\frac{G (T_m - T_1)}{B T_1} \right)^2 \log_e \cosh \frac{B T_1}{G (T_m - T_1)}$
5	1.00	$1 + \left(\frac{T_m - T_1}{T_1} \right) \tanh \frac{\xi B T_1}{G (T_m - T_1)}$	$\frac{G}{B} + 2 \left(\frac{G (T_m - T_1)}{B T_1} \right)^2 \log_e \cosh \frac{B T_1}{G (T_m - T_1)}$ $+ \frac{G}{B} \left(\frac{T_m - T_1}{T_1} \right)^2 \left[1 - \frac{G (T_m - T_1)}{B T_1} \tanh \frac{B T_1}{G (T_m - T_1)} \right]$

APPENDIX A

CALCULATION OF NUMERICS (BASED ON NERVA REACTOR DIMENSIONS)

1. Evaluation of $\frac{8 \mu L}{B R^2}$

Let

$$\begin{aligned} L &= 4 \text{ ft.} \\ R &= 0.1 \text{ inch} \approx 0.008 \text{ ft.} \\ &= 8 \times 10^{-3} \text{ ft.} \\ \mu &= 6 \times 10^{-6} \text{ lb/ft-sec.} \\ B &= 1 \text{ lb/ft}^2\text{-sec.} \end{aligned}$$

$$\text{therefore } \frac{8 \mu L}{B R^2} = \frac{8 \cdot 6 \cdot 10^{-6} \cdot 4}{1 \cdot (8 \cdot 10^{-3})^2} \approx 3.0 \text{ (dimensionless)}$$

2. For linear temperature behavior: ($n = 1$)

$$\frac{\rho \Delta P}{B^2} = \Pi = \frac{G}{B} + 3 I_3 = 4 \frac{G}{B} + 3 + \frac{B}{G}$$

3. For temperature limited behavior: ($n = 1$)

$$\frac{\rho \Delta P}{B^2} = \Pi = \left(\frac{G}{B} \right)^2 \frac{T_m - T_1}{T_1} \tanh \frac{B T_1}{G (T_m - T_1)} + 3 I_5$$

APPENDIX B

NOMENCLATURE

B	=	Lumped constant = $\frac{4 Q}{\pi D^2 H_1}$
c	=	Specific heat at constant pressure
D	=	Diameter of tube
F _s	=	Shear force
G	=	Mass velocity
H	=	Enthalpy
I	=	Viscosity integral
k	=	Thermal conductivity
L	=	Tube Length
n	=	Exponent for $\mu \sim T^n$
P	=	Total pressure
dP _f	=	Pressure drop due to the shear at the wall
dP _m	=	Pressure drop due to the momentum change
ΔP	=	Pressure drop (P ₁ - P ₂)
Q	=	Power input into the tube in length L
r	=	Radial distance from axis of tube.
R	=	Radius of tube
T	=	Temperature
T _m	=	Limiting high temperature

NOMENCLATURE (con't.)

v = Velocity in x direction

w = Mass flow through tube = $\frac{G \pi D^2}{4}$

x = Coordinate along length of tube

μ = Viscosity

ξ = Dimensionless length = x/L

ρ = Density

τ_w = Shear stress at tube wall

Π = Dimensionless pressure ratio = $\frac{\rho_1 \Delta P}{B^2}$