906
Printed

U of C-AUA-USAEC

TELEPHONE 312-739-7711
TWX 910-258-3285
WUX LB, ARGONNE, ILLINOIS

ARGONNE NATIONAL LABORATORY
9700 SOUTH CASS AVENUE, ARGONNE, ILLINOIS 60439
RDT STANDARDS TRANSMITTAL

DISTRIBUTION	DATE August 14, 1974	NO. ENG/QA0466	
List 1	RETURN COMMENTS TO	TYPE SUBMISSION	TYPE ACTION
	H. U. Ahmed	☐ 1. PRELIMINARY	☐ A. APPROVAL
		☐ 2. DRAFT	☒ B. INFORMATION
		☒ 3. TENTATIVE	☐ C. COMMENTS
		☐ 4. FINAL	☒ D. TRIAL USE
NOT LATER THAN	☐ 5.	☐ E.	
NUMBER	DESCRIPTION		ACTION
E 16-1T	Test Vehicles for Transient Reactor Test Facility (TREAT) Experiments Containing Sodium, August 1974		D
<div style="border: 1px solid black; padding: 5px; text-align: center;"><p>NOTICE</p><p>This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.</p></div>			
<p>Release for Announcement to Nuclear Science Abstracts</p>			

SIGNATURE

N. Balai

ANL RDT STANDARDS COORDINATOR

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

RDT Standard

TEST VEHICLES FOR TRANSIENT
REACTOR TEST FACILITY (TREAT)
EXPERIMENTS CONTAINING SODIUM

AUGUST 1974

Any further distribution by any holder of this document or of the data therein to third parties representing foreign interests, foreign governments, foreign companies, and foreign subsidiaries or foreign divisions of U.S. companies should be coordinated with the Director, Division of Reactor Research and Development, U.S. Atomic Energy Commission.

Division of Reactor Research and Development
United States Atomic Energy Commission

Send copy and distribution inquiries to:

RDT Standards Office
Oak Ridge National Laboratory
Building 1000, Room 120-C
P. O. Box X
Oak Ridge, TN 37830

Printed in the United States of America
USAEC Technical Information Center, Oak Ridge, Tennessee

RDT STANDARD

UNITED STATES ATOMIC ENERGY COMMISSION
DIVISION OF REACTOR RESEARCH AND DEVELOPMENT

RDT	E 16-1T	
DATE	August 1974	
PAGE	i	OF i

TEST VEHICLES FOR TRANSIENT REACTOR TEST FACILITY (TREAT) EXPERIMENTS CONTAINING SODIUM

TABLE OF CONTENTS

	<u>Page</u>
1. SCOPE	1
1.1 Purpose	1
1.2 Applicability	1
1.3 Definitions	1
2. APPLICABLE DOCUMENTS	2
2.1 RDT Standards	3
2.2 American National Standards Institute (ANSI)	4
2.3 American Society of Mechanical Engineers (ASME)	4
3. TECHNICAL REQUIREMENTS	5
3.1 General	5
3.2 Environmental Conditions	6
3.3 Design Analysis	6
3.4 Materials	10
3.5 Fabrication	10
3.6 Drawings	12
3.7 Installation and Field Services	13
4. QUALITY ASSURANCE REQUIREMENTS	13
4.1 Quality Assurance Program	13
4.2 Quality Verification and Certification	14
4.3 Records and Reports	14
4.4 Requirements for Nondestructive Examination	15
4.5 Pressure Test	16
4.6 Measuring and Test Equipment	17
5. PREPARATION FOR DELIVERY	17
5.1 Packing, Material Handling and Shipping Requirements	17
6. ORDERING DATA CHECKLIST	19
6.1 Ordering Data Checklist	19

RDT STANDARD

UNITED STATES ATOMIC ENERGY COMMISSION
DIVISION OF REACTOR RESEARCH AND DEVELOPMENT

RDT	E 16-1T
DATE	August 1974
PAGE	1 OF 22

TEST VEHICLES FOR TRANSIENT REACTOR TEST FACILITY EXPERIMENTS CONTAINING SODIUM

1. SCOPE

This standard delineates the requirements for the design, fabrication and quality assurance of the test vehicle for sodium cooled experiments which will be subjected to short term testing in the Transient Reactor Test Facility (TREAT).

1.1 Purpose. It is the purpose of this standard to define a set of rules for the procurement of the test vehicle by taking exceptions from the rules of ASME Boiler and Pressure Vessel Code, Section III (hereafter referred to as the Code), where necessary, in recognition to the short operating life of experiments. For instance, the design rules of this standard are outlined under only two conditions, Normal Conditions and Abnormal Conditions, redefined by this standard compared to five conditions of the Code.

1.2 Applicability. This standard establishes the requirements for test vehicles with a short operating life wherein long term high temperature creep and fatigue are not significant. Therefore, the rules pertinent to time - dependent behavior only as defined in Code and related Code Cases need not apply. However, during the short operating life of the experiment, if creep and fatigue is predicted then the analysis presented in the Code and the Code Cases, or any other method of analysis acceptable to the Purchaser, may be used in proving non-occurrence of damage to the test vehicle.

This standard shall only apply to test vehicles that will be loaded with nuclear fuel prior to installation in the TREAT and that will be removed from TREAT after a specified number of transient tests.

1.3 Definitions. The definitions of terms in this standard are consistent with those employed in the Code, except where given herein:

1.3.1 Test Vehicle. A vessel or assembly of vessels, piping pumps, heat exchanger, and valves, etc., containing a nuclear-fuel-bearing test sample and sodium as a coolant. The coolant may be recirculated passed once through the system, or be stagnant.

1.3.2 Normal Conditions. Those conditions of pressure, temperature and mechanical loading, etc., which can be sustained without degradation in the ability of the vehicle to meet the prescribed functional requirements.

1.3.3 Abnormal Conditions. Those conditions of temperature, pressure, mechanical loading, etc., which the test vehicle is designed to contain, but which may cause degradation in the continued ability of the vehicle to fulfill the prescribed functional requirements.

1.3.4 Normal Loads. Those loads associated with normal conditions, such as pressure, mechanical and thermal loads.

1.3.5 Abnormal Loads. Those loads associated with abnormal conditions, such as pressure, mechanical and thermal loads.

1.3.6 Mechanical Loads. Loads such as, but not be limited to:

a. Weight of components and normal contents including pressure due to static and dynamic head of sodium.

b. Superimposed loads such as insulation, electrical heaters, liners, etc.

c. Effects of differential thermal expansion.

d. Liquid impact.

1.3.7 System Analysis. As given in Fl322.1 of Appendix F of the Code.

1.3.8 Limit Analysis - Collapse Load. The methods of limit analysis are used to compute the maximum load or combination of loads that a structure made of ideally plastic (nonstrainhardening) material can carry. The deformations of an ideally plastic structure increase proportionately with energy input from the source of load until a failure mechanism defined by the lower bound theorem of limit analysis is reached in the primary structure. This load is above the elastic limit and is termed the "collapse load". An acceptable method used in limit analysis is a technique which assumes rigid perfectly plastic material behavior and a constant level of moment or force in those redundant structural elements in which membrane yield, plastic hinges or critical buckling load has been reached.

1.3.9 Plastic Analysis. As given in Fl321.1 of Appendix F of the Code.

1.3.10 Special Handling Devices. Those devices associated with the handling of the test vehicle which may be required for subsequent handling operations.

1.3.11 Special Tools. Those nonstandard tools which are required to carry out access, repair or replacement procedures, and inspection.

2. APPLICABLE DOCUMENTS

The following documents are a part of this standard to the extent specified herein and subject to applicability and purchaser approval. The issuance of a document in effect on the date of invitation to bid, including any amendments also in effect on the date, shall apply unless otherwise specified. Where the standard appears to conflict with the requirements of

a referenced document, such conflict shall be brought to the attention of the purchaser for resolution.

Where the materials, specifications or standards to be employed in the construction of any part are not identified in this standard or the documents referenced herein, the supplier shall submit for purchaser approval, the materials, specifications or standards he proposes to use.

2.1 RDT Standards.

RDT C 17-1T	High Temperature Electrical Connectors & Hermatic Seals
RDT C 18-1T	Ceramic Electrical Insulators
RDT E 1-18T	Class 1 Valves for Liquid Metal Service
RDT E 1-35T	Inert Gas Valves
RDT E 3-9T	E-M Pump for Liquid Metal Service
RDT E 4-13T	Freeze Vent for Na Service
RDT E 7-8T	Penetrations for Piping
RDT E 15-2T	Requirements for Nuclear Components (Supplement to ASME Boiler and Pressure Vessel Code, Section III)
RDT F 2-2	Quality Assurance Program Requirements
RDT F 3-2T	Calibration Program Requirements
RDT F 3-6T	Nondestructive Examination
RDT F 3-37T	Special Requirements for Metal Products
RDT F 4-20T	Operation and Maintenance Manuals
RDT F 5-1T	Cleaning and Cleanliness Requirements for Nuclear Components
RDT F 6-5T	Welding Qualifications (Supplement to ASME Boiler and Pressure Vessel Code, Section IX)
RDT F 6-10T	Repair of Materials by Welding
RDT F 7-2T	Preparations for Sealing, Packaging, Packing and Marking of Components for Shipment and Storage
RDT F 7-3T	Requirements for Identification Marking of Reactor Plant Components and Piping

RDT F 8-1T Preloading Threaded Fasteners and Closures

RDT F 8-6T Hoisting and Rigging of Critical Components and Related Equipment

RDT M 1-19T Nickel-Chromium-Molybdenum-Columbium Bare Welding Rods and Electrodes (ASME SFA-5.14 with Additional Requirements)

RDT M 2-5T Austenitic Stainless Steel Welding Fittings (ASME SA-403 with Additional Requirements)

RDT M 2-15T Nickel-Chromium Alloy Bars, Forgings, and Forging Stock (ASTM SA-637 with Additional Requirements)

RDT M 2-16T Tungsten Forgings (AMS 7897 with Additional Requirements)

RDT M 6-2T Mechanical Locking Devices

RDT M 7-7T Cobalt-Chromium Alloy Bars and Shapes

RDT M 12-1T Test Requirements for Thermal Insulating Materials for use on Austenitic Stainless Steel

RDT M 12-4T Reflective Insulation

RDT M 12-5T Thermal Insulation - Flexible or Molded, High Temperature Low Conductivity

RDT P 3-1T Electrical Penetration Assemblies for Nuclear Reactor Containment Structures

RDT P 4-3T Metal Sheathed, Mineral-Insulated Electrical Resistance Heater

2.2 American National Standards Institute (ANSI)

ANSI B46.1 Surface Texture

ANSI B16.25 Butt Welding Ends for Pipes, Valves, Flanges and Fittings

ANSI Y14 Drafting Manual

2.3 American Society of Mechanical Engineers (ASME)

ASME Boiler and Pressure Vessel Code, Section III, Nuclear Power Plant Components

ASME Boiler and Pressure Vessel Code, Section IX, Welding Qualifications

3. TECHNICAL REQUIREMENTS

3.1 General. The physical requirements, pressure, temperature, mechanical loads and operating conditions shall be as defined for both the normal and abnormal conditions in the Ordering Data.*

3.1.1 Functional Requirements. The functional requirements of the test vehicle shall be as specified in the Ordering Data.

3.1.2 Vessel. The vessel portions of the test vehicle shall be specified in the Ordering Data. The design analysis procedures shall be as given in Section 3.3 below.

3.1.3 Pipe. The pipe portions of the test vehicle shall be specified in the Ordering Data. The design analysis procedures shall be as given in Section 3.3 below.

3.1.4 Flanges and Fittings. The flanges and fittings shall be as specified in the Ordering Data. The design analysis procedures shall be as given in Section 3.3 below.

In flanged connections, the stress intensities in the vessel and flange shall be classified according to Table NB-3217-1 with corresponding footnote 4 of the Code.

*Special Consideration. Test vehicles for testing nuclear-fuel-bearing materials in TREAT may be subjected to conditions not encountered in out-of-reactor experiments, such as:

a. Relocation of fuel (solid, liquid or vapor) may occur within the test vehicle during the course of an experiment and provide an intense localized heat source.

b. Vaporization of fuel and sodium may effect coolant flow, heat exchanger, or pump characteristics.

c. Agglomeration of fuel material in portions of the test vehicle may occur during an experiment and be difficult to remove during maintenance or refitting operations.

The purchaser is responsible for evaluating the above mentioned and similar related special conditions and incorporating applicable requirements into the Ordering Data for the test vehicle. Current requirements for test vehicle design established by TREAT should be included in the evaluation of special conditions applicable to the design of a test vehicle for a specific test program.

3.1.5 Rupture Disc. Rupture discs shall be designed subject to following requirements and any other requirements specified in the Ordering Data.

- a. Burst pressure shall be less than the design pressure at design temperature.
- b. Rupture disc flow area shall be at least equal to flow area of inlet piping to rupture disc.
- c. Burst pressure of the disc shall be certified to be within $\pm 5\%$ of rupture disc rating.
- d. Material used shall be compatible with the working fluid (sodium).

3.1.6 Gaskets. Material used shall be compatible with the working fluid (sodium).

3.1.7 Specified Stress Values. The stress values such as S_m , S_a and S_y , as defined by the Code, shall be as specified in the Ordering Data. The Code material criteria and material properties shall be used except when otherwise justified by the designer for special cases and approved by the purchaser.

3.2 Environmental Conditions. The environmental conditions imposed upon the test vehicle shall be as specified in the Ordering Data.

3.3 Design Analysis.

3.3.1 Normal Condition Analysis. Elastic analysis shall be used with the stress intensity limits defined by Figures 1 and 2 subject to the following.

3.3.1.1 When the fatigue screening rules of NB-3222.4 (d) of the Code are satisfied, the limits indicated on Figure 1 shall be satisfied. For the piping portions of the test vehicle, the procedures of NB-3652 of the Code may be used.

3.3.1.2 When the fatigue screening rules of NB-3222.4 (d) of the Code are not satisfied, the limits indicated on Figure 2 shall be satisfied in addition to those of Figure 1. The procedure of NB-3653 of the Code may be used for the piping portions of the test vehicle, in satisfying equations (10), (11), or (12). If these equations are not satisfied then the limits indicated on Figure 2 shall be satisfied in addition to those of figure 1 of this document.

3.3.1.3 In addition to satisfying the above requirement, equation (9) in NB-3652 of the Code shall be evaluated, including the effects of bending moment which result from constraint of free-end displacement (see NB-3213.19 of the Code), using an allowable value of $2 S_m$. When considering

Stress Category	Primary		
	General Membrane	Local Membrane	Bending
	Average primary stress across solid section. Excludes discontinuities and concentrations. Produced only by mechanical loads.	Average stress across any solid section. Considers discontinuities but not concentrations. Produced only by mechanical loads.	Component of primary stress proportional to distance from centroid of solid section. Excludes discontinuities and concentrations. Produced only by mechanical loads. (Note 2)
Symbol (Note 1)	P_m	P_L	P_b
Combination of stress Components and Allowable Limits of Stress Intensities.	<pre> graph TD Pm[Pm] --> PL15Sm[PL 1.5 Sm] PL[PL] --> PL15Sm PL15Sm --> PLPb15Sm[PL + Pb 1.5 Sm] Pb[Pb] --> PLPb15Sm </pre> <p>— Use Normal Loads</p>		

NOTE 1: The symbols P_m , P_L , and P_b do not represent single quantities, but rather sets of six quantities representing the six stress components σ_r , σ_t , σ_θ , τ_{rt} , $\tau_{r\theta}$, and $\tau_{t\theta}$.

NOTE 2: Bending component of primary stress for piping shall be the stress proportional to the distance from centroid of pipe cross-section.

Figure 1

Figure 2

the vessel portions of the test vehicle, the effects of such moments shall be categorized in accordance with NB-3227.5 of the Code.

3.3.1.4 The fatigue screening rules of NB-3222.4 (d) of the Code may be applied to all temperatures of interest.

3.3.1.5 The following design capacities shall be calculated and documented in the stress report for both the test fuel element region and the weakest region of the test vehicle.

a. Allowable Design Pressure, P_N . The maximum static pressure which could be applied in the presence of the normal mechanical loads and still satisfy the requirements of this section.

3.3.2 Abnormal Condition Analysis. For the abnormal loadings, the test vehicle analysis shall consist of a complete system analysis and a component analysis. The evaluation of the primary stress shall be in accordance with F-1321 and F-1322 of Appendix F of the Code. (In the evaluation and meeting the design limits of the primary stress the abnormal conditions defined by this document shall be considered as the faulted condition of the Code.) The following design capacities shall be calculated and documented in the stress report for both the test fuel element region and the weakest region of the test vehicle.

a. Allowable Abnormal Static Pressure, P_{AS} . The maximum static pressure which could be applied in the presence of the normal mechanical loads and still satisfy the requirements of this section.

b. Maximum Allowable Dynamic Pressure, P_D . When required by the Ordering Data for certain pressure-time characteristics, the maximum allowable dynamic pressure, P_D , for that characteristic which could be applied in the presence of the normal mechanical loads and still satisfy the requirements of this section shall be calculated.

3.3.3 Stability Requirements. These requirements shall be as given by F-1325 of Appendix F of the Code.

3.3.4 Burst Tests. For complicated fittings the burst test procedure of NB-3649 of the Code may be used in lieu of an analysis to establish the pressure rating.

3.3.5 Stress Report. A stress report shall be required and shall include a complete set of stress analysis calculations establishing that the designs shown by the drawings, used or to be used for construction, comply with the requirements of this standard. Any computer programs used in the calculations shall be properly included or documentation referenced in the stress report with appropriate test problems where the computer program is new or proprietary.

All experimental testing performed to demonstrate the integrity of the structure shall be completely documented in the stress report.

Appendix C of the Code may be used as a general guide in the preparation of the stress report.

3.3.6 Design Report. If specified in the Ordering Data, a design report shall be required to establish that the design satisfies the thermal and hydraulic requirements specified in the Ordering Data.

3.4 Materials. Materials and material standards for the test vehicle are listed in RDT E 15-2. Additional specific material requirements and other materials shall be as specified in the Ordering Data.

3.4.1 Repair Welding. Where the applicable material standard and the Ordering Data allows the use of welding processes for repair of defects in the material, the repair welding shall be accomplished in accordance with the requirements of RDT F 6-10.

3.4.2 Archive Samples. Archive samples of the materials of construction shall be provided as specified in the Ordering Data.

3.5 Fabrication.

3.5.1 General Requirements. The test vehicle shall be fabricated and examined in accordance with Articles NB-4000 and NB-5000 of the Code as supplemented by RDT E 15-2, this standard and the Ordering Data.

3.5.2 Heat Treatment. The heat treatment which is to be applied to any part, subassembly, or the complete vehicle after welding shall be in accordance with the requirements as specified in the Ordering Data.

3.5.3 Sensitization. Austenitic stainless steel which has become sensitized during operations such as heat treating, welding, or forming shall be protected against corrosion and moisture during all subsequent manufacturing and storage operations.

3.5.4 Surface Finish. Surface finish shall be determined in accordance with ANSI B46.1.

a. The maximum surface roughness shall be specified in the Ordering Data.

b. Where tubular products shall not subsequently be machined or otherwise finished during fabrication, specific surface finish requirements will be as specified in the Ordering Data for the material.

3.5.5 Special Processes. Plating or clad materials shall not be permitted unless specifically authorized in the Ordering Data.

3.5.6 Closure. Threaded closures shall be in accordance with RDT F 8-1, Type 1. The use of threaded fasteners or the use of lubrication materials as permitted by RDT F 8-1 within a sodium or sodium vapor environment is prohibited unless approved by the purchaser.

3.5.7 End Connections. End connections to equipment, internal parts, or piping shall be prepared where possible for butt-welding and the preparation of the welding end shall be in accordance with the requirements of ANSI B16.25, unless otherwise specified in the Ordering Data.

3.5.8 Cleaning and Cleanliness. The fabrication of a part, combination of parts, subassembly, or completed test vehicle shall meet the cleaning and cleanliness requirements of RDT F 5-1.

3.5.9 Assembly Procedure. Component parts shall be assembled in accordance with written detailed procedures to meet assembly requirements and Ordering Data specifications. The supplier shall prepare the detailed assembly procedures. The procedures shall be complete and accepted by the purchaser for review and approval in accordance with the schedule established by the Ordering Data. The assembly procedures shall contain the following, if applicable:

- a. Assembly sequence.
- b. Cleaning and cleanliness procedures, sequence, and precautionary rules.
- c. Dated assembly log of procedure.
- d. Parts and material inventory control system.
- e. Any special machining or fitting-at-assembly instructions.
- f. Intermediate and final inspection criteria and hold points.
- g. Handling and storage methods, equipment and precautions.
- h. Procedures for the securing or locking devices or tack welding.
- i. Drawings or photographs as required to illustrate assembly problems or techniques.
- j. Lists and explanation of drawings, parts, jigs and fixtures.
- k. Special data, measurements, or observations to be recorded in quality control records.
- l. Check lists.
- m. Welder qualification and welding procedures.
- n. Heat treatment.
- o. Training requirements.

3.5.10 Identification and Traceability. Identification and traceability procedures shall conform with the following requirements:

3.5.10.1 Materials. All materials shall be identified in accordance with the requirements of the applicable material standard. When raw material is cut or sectioned, all identification shall be maintained.

3.5.10.2 Parts. During fabrication, all parts shall be identified in accordance with the requirements of RDT F 7-3. The identification of parts shall include order or contract number, drawing number and revision number and part number, if applicable, component identification and other special information necessary to clearly identify the part. The use of metal stamping is permitted only when approved by the purchaser.

3.5.10.3 Traceability. Traceability procedures shall be submitted to the purchaser for approval. All parts used in the fabrication of the test vehicle and for archive samples shall be traceable to materials and material certifications, heats, lots, processes, operators of special processes, inspectors and drawings per applicable RDT Standards for materials.

3.5.11 Precautionary Measures. Shop practices and restrictions on use of materials shall meet the requirements of RDT F 5-1 and the Ordering Data. The supplier shall include the appropriate instructions and restrictions in his fabrication procedures and other documents defining acceptable shop practices.

3.6 Drawings. Shop drawings shall be prepared in accordance with ANSI Y14. The time and approval requirements of submittals to the purchaser and the number of copies required shall be as specified in the Ordering Data.

3.6.1 Detail Drawings. Detail manufacturing and "as-built" drawings shall include, as appropriate, the following information:

- a. Tolerance block, including geometric tolerances.
- b. Detailed dimensions, tolerances and maximum roughness of each surface.
- c. Material specification and any special requirements including nondestructive examination, heat treatment and hardness.
- d. Fabrication instruction, including welding, hard surfacing, cleaning, inspection symbols, and references to assembly procedure requirements.
- e. Such additional information required to adequately describe equipment having special features or characteristics
- f. All "as-built" changes.

3.6.2 Drawing and Specification Lists. The supplier shall maintain a current listing of all drawings associated with the components supplied on

his contract in accordance with this standard. Each drawing number shall include the revision number.

The supplier shall maintain a current list of specifications to include as applicable, specifications for materials, fabrication, testing, inspection, assembly, maintenance, cleaning, packaging, shipping, storage, operation and quality assurance.

3.6.3 Parts List. The supplier shall provide a complete list of parts organized by assemblies. Each part shall be listed with the applicable drawing number and current revision number. The supplier shall provide a copy of the parts list (which shall serve as a baseline against which further changes may be monitored) as specified in the Ordering Data.

3.7 Installation and Field Services. The supplier shall provide technical advice and assistance and monitor quality assurance implementation during the installation and any subsequent repair, replacement, and alteration of equipment to the extent specified in the Ordering Data.

4. QUALITY ASSURANCE REQUIREMENTS

4.1 Quality Assurance Program. The supplier shall establish, implement and maintain a documented Quality Assurance Program in accordance with Sections 1, 2, 3, 4, 5 and 8 of RDT F 2-2 to the extent specified in the Ordering Data.

Prior to implementation, the supplier shall submit the following documents for approval by the purchaser. The schedule for submittal, approval requirements and number of copies required will be specified in the Ordering Data.

4.1.1 Quality Assurance Program Plan.

4.1.2 Inspection and Test Plan.

4.1.3 Special Process Control and Nondestructive Test Procedures.

4.1.4 Inspection and Test Procedures and Sampling Plans. These procedures shall include the details of all sampling plans proposed by the supplier and the basis for selection of the proposed sampling plan.

4.1.5 Handling, Preservation, Packaging and Storage Procedures.

4.1.6 Calibration Program Plan. The supplier shall prepare a calibration program plan and procedures for implementation. The calibration plan shall be in accordance with RDT F 3-2.

4.1.7 Identification and Traceability. Suppliers shall prepare identification and traceability control procedures to comply with the requirements of section 3.5.10 of this standard.

4.2 Quality Verification and Certification. As a minimum, the supplier shall submit the following documents to the purchaser for each test vehicle or deliverable subassembly or part. The supplier shall provide all documentation necessary to assure compliance of this standard at the time of delivery.

4.2.1 Parts List. List of Items by part number, drawing number and revision, part name, serial number, lot or heat number and weight.

4.2.2 Drawings. A reproducible set of assembly and part "as-built" drawings.

4.2.3 Special Processes and Nondestructive Test Qualification. Special processes and nondestructive examination procedures, equipment and personnel qualifications as specified in RDT F 3-6.

4.2.4 Initialed and dated checklists.

4.2.5 Assembly logs dated and signed.

4.2.6 Nonconformance records. A copy of each nonconformance and corrective action record including rework, repair and retest procedures.

4.2.7 Certification. Certification of conformance with this standard and contract requirements, including but not limited to the following:

a. Materials Certification. Chemical and physical test results, non-destructive examination results, heat treatment data and test results of material test coupons. This data shall be traceable from their related finished components to the mill heat numbers.

b. Nondestructive Examinations. Results of final nondestructive tests including logs, checklists, radiographic films, recordings and other test records for the test methods used.

c. Test Reports. Certified copies of test results, analysis of test results and conditions of test.

d. Final Inspection. A copy of final inspection results, including logs, checklists, etc.

4.3 Records and Reports

4.3.1 Progress Reports. Reports of progress in fabrication, inspection and testing, shall be made at regular intervals as specified in the Ordering Data. These reports shall relate the progress made since the preceding report with only enough repetition of previously reported events to frame the contents of the present report. The reports shall also include difficulties encountered (such as failures and malfunctions) and the corrective action taken or planned. Problems foreseen as possible disruptions of

the schedule shall be brought to the attention of the purchaser as early as possible.

4.3.2 Special Tool List. The supplier shall prepare and keep current a list of all special tools, including gages, required for the contract. The list shall identify each tool by name, drawing number, function, operation(s) for which it is required and whether it is an "in process" tool or a deliverable item.

4.3.3 Final Report. A final report is intended to be submitted to the purchaser. This report is intended to present the complete history of the fabrication, testing, inspection and shipping of the test vehicle and its auxiliary equipment. Proprietary information is neither sought nor desired. The final report shall include the following as a minimum:

- a. Copies of drawings specified in this standard of the "as-built" configuration reduced to convenient sizes for binding.
- b. Illustrations, sketches, schematic diagrams, and photographs of major stages of fabricating, assembling, inspecting, cleaning, testing, repairing, packing, and shipping.
- c. Full size reproducible copy of detail and assembly drawings specified in this standard of the "as-built" configuration.
- d. Certification of the test vehicle (Reference Section 4.2.7).
- e. Quality records (Reference Section 4.2).
- f. Assembly Procedures (Reference Section 3.5.9).

4.4 Requirements for Nondestructive Examination

4.4.1 General Requirements for Nondestructive Examination. Nondestructive examination of materials and fabricated components shall be in accordance with the Code as supplemented by RDT E 15-2 and the additional requirements specified herein. Calibration and examination methods and procedures shall be in accordance with RDT F 3-2 and RDT F 3-6. In addition, each written procedure shall specify, with approval by the purchaser, the certification levels (Level I, II, or III) required by personnel who:

- a. Perform the nondestructive examinations, and
- b. Interpret and evaluate the results.

Acceptance criteria shall be as specified in drawings, Ordering Data or RDT F 3-37.

Following each nondestructive examination, affected areas shall be thoroughly cleaned to the requirements of RDT F 5-1 before proceeding to the next weld pass, or the next fabrication step.

4.4.2 Examination of Materials. Prior to use in fabrication, all materials shall be examined:

- a. Visually, to assure specified cleanliness and detect obvious defects, and
- b. Nondestructively, in accordance with the requirements specified.

Repaired areas in materials shall be examined as required by RDT E 15-2 (welding not required), or RDT F 6-10 (welding required). For defects detected using methods other than liquid penetrant, magnetic particle or radiography, the repaired area shall also be re-examined by the method, and to the acceptance criteria which revealed the original defects.

4.4.3 Examination During Fabrication. During fabrication, or assembly, all items shall be subjected to visual and dimensional examination to verify compliance with applicable drawings and specifications.

Examination of welds shall be in accordance with the requirements of the Code as supplemented by RDT E 15-2 and as specified herein. Welds designated in the Ordering Data as critical shall be volumetrically examined by two (2) independent nondestructive methods.

If the welds cannot be satisfactorily examined by two independent non-destructive test methods this requirement shall be resolved with the purchaser before welds are made.

Welds which cannot be satisfactorily examined by either radiographic or ultrasonic methods shall be examined by a liquid penetrant or a magnetic particle method after each weld layer; or after the root pass and each successive 1/2 inch or (1/3)t (whichever is smaller) of deposited weld metal (where t is the thickness of the finished weld) as specified in the Code, as supplemented by RDT E 15-2.

4.4.4 Helium Leak Check. All pressure retaining welds shall be helium leak tested in accordance with RDT F 3-6. The leak rate limit and test method shall be as specified in the Ordering Data.

When a pneumatic or a hydrostatic strength test is used, the helium leak test shall be performed before and after the strength test is completed.

4.5 Pressure Test. A pneumatic, hydrostatic or any other pressure test shall be performed as specified by the Ordering Data. The supplier shall provide detailed procedures to the purchaser for approval. Any permanent deformation observed shall be reported to the purchaser for evaluation.

Prior to testing, the interior surfaces shall be cleaned to meet the cleanliness requirements of RDT F 5-1.

The studs, bolts, nuts, washers and other closure members furnished for the test vehicle shall not be used for pressure tests unless permitted by the Ordering Data.

The temperature of the test vehicle material and test fluid shall be continuously monitored during the test. Instruments used to monitor pressure and temperatures shall be calibrated in accordance with RDT F 3-2 for an overall system accuracy of ± 2 percent of full scale unless otherwise specified in the Ordering Data. Wherever possible, all primary vessel penetrations shall be pressure tested.

4.5.1 Pneumatic Strength Test Requirements. The pneumatic pressure test shall conform to article NB-6300 of the Code.

4.5.2 Hydrostatic Strength Test Requirements. Tests shall conform to the requirements of article NB-6200 of the Code and RDT E 15-2. The water used for hydrostatic pressure tests shall conform to the requirements of RDT F 5-1 for Grade A water. Drying requirements shall be in accordance with RDT F 5-1.

4.5.3 Proof Test. If specified in the Ordering Data, a proof test simulating design conditions for the test vehicle shall be performed.

4.6 Measuring and Test Equipment. Equipment used in measuring and testing the test vehicle and component parts shall comply with the following requirements:

a. No mercury or mercury-containing equipment shall be used during manufacturing or testing.

b. Soft metals, such as lead, copper, and aluminum shall not be brought in direct contact with the test vehicle parts.

c. Equipment shall be calibrated in accordance with RDT F 3-2.

5. PREPARATION FOR DELIVERY

5.1 Packing, Material Handling and Shipping Requirements. The supplier shall be responsible for the delivery of all items to be provided to the delivery point specified in the Ordering Data. The supplier shall submit for the purchaser's approval a packaging, material handling and shipment plan presenting the practices, procedures and instructions to be followed in meeting the requirements of 5.1.1, 5.1.2, 5.1.3, 5.1.4, and any additional requirements specified in the Ordering Data. Handling of items during preparation, packing, unpacking and shipping shall conform to RDT F 8-6.

5.1.1 Preparation. Upon completion of all shop testing and inspection, all items and components shall be prepared for delivery to the designated site. This shall include disassembly (as required), recleaning (if necessary), surface preparation, examinations, etc. Following preparation,

all deliverable components shall be packaged in accordance with the requirements of 5.1.2.

5.1.2 Packing. Items shall be packaged to prevent deterioration, corrosion or damage. All sealing, packing and identification marking shall be in accordance with RDT F 7-2. Packaging shall protect the item while at the supplier's facilities, during transportation to the designated site, and at the designated site.

5.1.3 Shipping. The supplier shall be responsible for the delivery of all items covered by this standard to the designated or destination point. These responsibilities include, but are not limited to the following:

5.1.3.1 Routing. The supplier shall recommend routing for all materials and components for which he is responsible. When approved, the supplier shall make all arrangements necessary to ship those materials and components in accordance with the requirements of this standard.

5.1.3.2 Shipping Instructions. The supplier shall prepare and forward instructions to the purchaser for approval for handling, shipping, in-transit storage and storing of all major items for which the supplier has delivery responsibility.

5.1.3.3 Loading. Required shipping position, supports and brazing shall be determined by the supplier. The supplier shall provide supervision for loading the components on a suitable vehicle. All handling equipment shall prevent any damage to components during handling and shipping operations in accordance with 5.1.4.

5.1.3.4 Unloading. The supplier shall provide written procedures for unloading items for which he has delivery responsibility, from the carrier at the designated site. The supplier shall also provide all special lifting devices, supports and fixtures necessary to unload the components from the carrier and to transport them to a designated storage area.

5.1.3.5 Unpacking. The supplier shall provide written procedures for removing all packaging from major items which he has supplied.

5.1.3.6 Storage. The purchaser will specify to the supplier which items will be stored at designated site for more than 30 days before use. The supplier shall provide written procedures for storage and storage inspection for all such items.

5.1.3.7 Documentation. The supplier shall identify all technical documentation, e.g., instructions, drawings, reports and manuals which are to accompany deliverable items during shipment.

5.1.4 Handling. All handling, lifting, supporting and shipping fixtures shall comply with RDT F 8-6 and the following requirements.

Each separate component weighing more than 50 pounds, that must be handled, shall be provided with a means of lifting and handling using standard crane equipment.

All special lifting or handling fixtures shall be designed for static load of five times normal anticipated static loads, based upon ultimate material strength.

Lifting, handling, and shipping fixtures (and lifting attachments provided with the components) fabricated from ferritic materials shall be sufficiently ductile to permit safe handling and shipment at an ambient temperature of -10°F . If shipment is scheduled for the winter months (October through March inclusive) and the anticipated ambient temperature may be less than -10°F , the supplier shall take special precautions to prevent brittle fracture of the material. All welds shall be heat treated as necessary to comply with the above requirements.

Lifting points shall be provided on all shipping devices which permit safe lifting of either the empty device or the device and the components as a single unit.

If the component to be handled required up-ending, points of attachments for chain falls, trunnions, or other features shall be provided so that up-ending can be done in a safe, controlled manner.

Use of cast iron, cast steel, or bronze load-bearing parts in any lifting or handling fixture is prohibited.

All handling equipment and shipping container fixtures shall be adequate to prevent any damage due to shock or vibration or both. Dynamic loadings for use as a reference basis are to be recommended by the supplier. Proof tests shall be performed on, and documented for, all critical lifting, handling, supporting and shipping fixtures prior to use on components to assure safe handling of these components.

6. ORDERING DATA CHECKLIST

6.1 Ordering Data Checklist. The detailed requirements and conditions necessary to design, fabricate, examine, test, and deliver a test vehicle in accordance with this standard are to be included in the Ordering Data. The Ordering Data is prepared by the purchaser in accordance with the following format.

Applicable paragraph numbers of the standard are used herein to identify information and its location. Any omission of a paragraph number indicates that the particular paragraph of the standard adequately specifies the requirement.

<u>Item</u>	<u>Applicable Section</u>
1. <u>Scope</u>	
a. Include a statement indicating that this document is the Ordering Data which supplements this standard.	1.0
b. A brief description of nature of application.	
c. The location of the installation site.	
d. Summary of the components and services to be furnished.	
2. <u>Miscellaneous Details</u>	
a. <u>Normal Conditions</u>	1.3.2
Steady State	
Pressure	
Temperature	
Mechanical Loads	
Coolant flow	
Transient	
Heatup (to pretest condition)	
Cooldown rate (after test)	
Pressure, change and rate	
Temperature, change and rate	
Mechanical Load, change and rate	
b. <u>Abnormal Conditions</u>	1.3.3
Pressure, change and rate	
Temperature, change and rate	
Mechanical Loads, change and rate	
Coolant flow, change and rate	
c. <u>Physical Characteristics</u>	
Geometry	
Weights	
Handling requirements	
Service Life	
Identification of Containment boundaries	
Support conditions	

<u>Item</u>	<u>Applicable Section</u>
3. <u>Applicable Documents</u>	2.0
List all documents which are specifically called out in Items 3 to 11 of the Ordering Data but do not appear in this standard.	
4. <u>Technical Requirements</u>	3.0
a. General	3.1
b. Functional Requirements	3.1.1
c. List vessel portions of test vehicle	3.1.2
d. List pipe portions of test vehicle	3.1.3
e. List flanges and fittings	3.1.4
f. List rupture discs	3.1.5
g. List gaskets	3.1.6
h. Specified stress values	3.1.7
S _m Material Temp. No. of Cycles	
S _a	
S _y	
5. <u>Design Analysis</u>	3.3
a. Normal Condition Analysis	3.3.1
b. Abnormal Condition Analysis	3.3.2
c. Maximum Allowable Dynamic Pressure	3.3.2
(for each specified operating temperature)	
d. Need for calculation	
e. Deformation Limit	
f. Design Report	3.3.6
6. <u>Materials</u>	3.4
a. Repair welding	3.4.1
b. Archive Samples	3.4.2
7. <u>Fabrication</u>	3.5
a. General	3.5.1
b. Heat Treatment	3.5.2
c. Surface Finish	3.5.4
d. Special Process	3.5.5
e. End Conditions	3.5.7
f. Assembly Procedure	3.5.9
g. Precautionary Measures	3.5.11
8. <u>Drawings</u>	3.6

<u>Item</u>	<u>Applicable Section</u>
9. <u>Installation and Field Service</u>	3.7
10. <u>Quality Assurance Requirements</u>	4.0
a. Quality Assurance Program	4.1
b. Progress Reports	4.3.1
c. General Requirements for Nondestructive Examination	4.4.1
d. Examination of Materials	4.4.2
e. Examination During Fabrication	4.4.3
f. Helium Leak Check	4.4.4
g. Pressure Test	4.5
Proof Test	4.5.3
11. <u>Preparation for Delivery</u>	5.0