~~CONFIDENTIAL~~
~~RESTRICTED DATA~~

~~Atomic Energy Act of 1954~~

Subcontract NP-1

399

NOTICE
This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Westinghouse Astronuclear Laboratory

NOTE

PORTIONS OF THIS REPORT ARE IN THE PUBLIC DOMAIN
has been removed from the report and the
copy to permit the broadest possible distribution
without

Classification cancelled (or changed to _____)

by authority of _____

by H. F. C. TIC, date SEP 11 1973

INFORMATION CATEGORY	
GROUP 1	
<u>W. J. Hill</u>	8-14-68
AUTHORIZED CLASSIFIER	DATE

GROUP - 1
EXCLUDED FROM AUTOMATIC DOWNGRADING AND DECLASSIFICATION

PREPARED BY:

Thermal and Nuclear Design
Department Staff

D. J. Hill

D. J. HILL

Technical Editor

SPECIAL REVIEW FOR DECLASSIFICATION	Class: <u>U</u>
	Reviewers <u>JRG</u>
Date <u>4-21-82</u>	

WANL-TME-1805

MASTER

XE-2 NUCLEAR SUBSYSTEM

THERMAL AND NUCLEAR

DESIGN DATA BOOK (U)

~~CONFIDENTIAL~~
~~RESTRICTED DATA~~

~~Atomic Energy Act of 1954~~

[DISTR. ...]

UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	D. J. H. 7-30-68	R. M. Cuthbert 7/4/68	

INTRODUCTION

(U) The purpose of this document is to present the design analysis* data from the Thermal and Nuclear Design Department for the XE-2 reactor. The scheduler objective is to publish the document before the first experimental plans to enhance its usefulness by WANL, Aerojet-General Corporation, and Government Agencies in their preparations for the test series. As a result, it represents the most recent design and "as built" data available at the time of publication. Specific data relative to the test series is covered in the XE-2 Test Prediction Report.

(U) The material in this Data Book includes reactor design goals, limitations, and nuclear, thermal, radiation, and corrosion data for the XE-2 reactor. The material is divided into the following sections and identified with tabs.

<u>SECTION</u>	<u>SUBJECT</u>
A	Introduction
B	Basic Design Requirements
C	Geometrical and Mass Data
D	Thermal Cycle Performance Data
E	Nuclear Data
F	Radiation and Shielding Data
G	Reflectors: Thermal-Hydraulic Data
H	Shield: Thermal-Hydraulic Data
I	Core: Thermal-Hydraulic Data
J	Corrosion Data

(U) Each section contains a general description of its scope in an introduction, and each has a detailed Table of Contents which gives the organization of the data in the section. Index numbers are used to identify the data pages.

(U) This Data Book is essentially complete in itself. Some data pages from the two previous Data Books, (WANL-TME-1565 for XE-1 and WANL-TME-1642 for NRX-A6), applicable to XE-2 have been reproduced in this document.

* Work performed under project numbers NE8010, NE8020, and NE8030 by the Thermal and Nuclear Design department

(U) DATA BOOK INTRODUCTION (U)	INDEX NO
	A

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	EJH 7/30/68	D.M. Gutzwiller 7/2/68	

DESIGN REQUIREMENTS

(U) The XE-2 reactor is designed to determine engine operating characteristics and to establish a technical basis for development of control concepts for future engine systems. Design changes from XE-1 are listed in Section C. 1.2. Limitations imposed on reactor operation are defined in Section D.2.

TEST OBJECTIVES

(U) The primary test objectives for the XE-2 reactors are:

1. Determine optimum XE startup characteristics.
2. Determine optimum XE shutdown and pulse cooling characteristics.
3. Evaluate candidate control systems to be used on the NERVA engine.
4. Demonstrate a flight-type operational cycle, beginning with automatic startup and progressing to full power followed by shutdown with pulse cooling.
5. Determine XE systems characteristics at selected operating points during steady-state operation.
6. Evaluate engine, subsystem, and component performance.

(U) These test objectives are discussed in detail in the XE-2 Test Specification, Report No. RN-S-0400.

(U) DESIGN REQUIREMENTS (U)	INDEX NO.
	B

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>Shippolee 8-2-68</i>	<i>AGH 8-2-68</i>	

THIS PAGE UNCLASSIFIED

SECTION C
GEOMETRICAL AND MASS DATA

(U) This section of the Data Book presents descriptive, dimensional and composition data related primarily to nuclear analysis requirements. Illustrations of the major reactor components and their assembly pertaining to the reactor are presented. Specifications of several major core components are provided together with their final "as built" weight and composition. Included in this description are such components as fueled and unfueled elements, nuclear shims, and core and reflector instrumentation.

(U) INTRODUCTION (U)	INDEX NO.
	C

XE-2

TABLE OF CONTENTS

*C.1

*C.1.1

C. 1. 1. 1 (CRD) Trimetric View of XE-2 Reactor (U)

C. 1. 1. 2 (CRD) XE-2 Core Subassembly (U)

C. 1. 1. 3 (CRD) Plan View of Reflector (U)

C.1.1.4 (CRD) Core Orientation and Cluster Identification (U)

C.1.1.5 (CRD) Element and Filler Strip Identification of Peripheral Clusters (U)

C. 1. 1.6 (CRD) Element Description and Identification (U)

C.1.1.7 (CRD) Radial Position of Fuel Elements in the Core (U)

C.1.1.8 (CRD) Fuel Element Cluster and Support Block Assembly (U)

C. 1. 1. 9 (CRD) Fuel Cluster Assembly - Dome End (U)

C.1.2 (CRD) Design Differences Between XE-2 and XE-1 (U)

ELEMENT DATA (U)

C.2.1 (CRD) Fuel Element Specifications (U)

C.2.2 (CRD) Unfueled Central Element Specifications (U)

C.2.3 (CRD) XE-2 "As-Built" Fueled and Unfueled Element Inventory (U)

C.2.4 (CRD) Average Axial Niobium Carbide Profiles by Loading Code (U)

C.2.5 (CRD) NbC Bore Coating Thickness as a Function of Axial Position (U)

C.2.6 (CRD) Average Axial Molybdenum Profiles by Loading Code (CRD)

C.2.7 (CRD) Molybdenum Mass Distribution as a Function of Axial Positions (CRD)

OVERALL DATA (U)

C.3.1 (CRD) XE-2 Uranium Loading Distribution (U)

C.3.2 (CRD) XE-2 Shimming Distribution and Instrumentation Placement (U)

C.3.3 (CRD) Core Instrumentation Summary (U)

C.3.4 (CRD) XE-2 "As-Built" Core Inventory (U)

REFLECTOR REGION DATA (U)

C.4.1 (CRD) Control Vane Data (U)

* There are no data pages corresponding to these index numbers.

INDEX NO.

C

Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>Simmons 7/2/65</i>	<i>D. M. G. 7/2/65</i>	

THIS PAGE UNCLASSIFIED
SECTION C

TABLE OF CONTENTS

Index No.

	C. 4. 2 (CRD)	Reflector Region "As-Built" Inventory (U)
	C. 4. 3 (CRD)	Reflector and Shield Instrumentation Summary (U)
*C. 5	THERMAL CAPSULES (U)	
	C. 5. 1 (U)	Thermal Capsule Specification
	C. 5. 2 (CRD)	XE-2 Thermal Capsule Distribution in Core (U)
	C. 5. 3 (CRD)	XE-2 Thermal Capsule Distribution in the Filler Strips (U)

* There are no data pages corresponding to these index numbers.

(CRD) TABLE OF CONTENTS (U)	INDEX NO.
	C Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Rittenberger 7/10/54	R. M. Peterson 7/10/54

(CRD) TRIMETRIC VIEW OF XE-2 REACTOR (U)	INDEX NO.
	C.1.1.1

REFERENCE WANL-TME-840A C 1.a.2	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Rittenberger 7/30/68	ROM Cutchner 7/4/68

(CRD) XE-2 CORE ASSEMBLY (U)	INDEX NO
	C.1.1.2

REFERENCE

DWG. 937J372

Astronuclear
Laboratory

* NOTE: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.

(CRD) PLAN VIEW OF REFLECTOR (U)

PREPARED BY

DJH 7/30/68

APPROVED BY

D.M. Fitch 7/30/68

INDEX NO.

C.1.1.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Rittenbayer 7/30/68	RLM Cutler 7/1/68

NOTE : THIS DRAWING SHOWS CORE CROSS SECTION AS VIEWED
IN THE DIRECTION OF CORE PROPELLANT FLOW

(CRD) CORE ORIENTATION AND CLUSTER IDENTIFICATION (U)	INDEX NO.
	C. 1. 1. 4

CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954

REFERENCE	PREPARED BY <i>J. J. J. 8/5/68</i>	APPROVED BY <i>28 J 8/5/68</i>	Astronautical Laboratory

- NOTES: 1) CORE VIEWED IN THE DIRECTION OF PROPELLANT FLOW.
2) ALL PARTIAL ELEMENTS IN XE-2 ARE UNFUELED.

(CRD) ELEMENT AND FILLER STRIP IDENTIFICATION OF XE-2 PERIPHERAL CLUSTERS (U)

INDEX NO.

C.1.1.5

CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Pittenger 7/30/64	Don Kitchin 7/3/64

FUELED ELEMENT CHANNEL IDENTIFICATION

NOTES:

1. Wedges indicate serial number face (a)
2. Within each sector all serial number faces are oriented in one direction. The exceptions are: (a) in the two large periphery clusters and (b) in the center cluster which has the elements with their serial numbers facing the center. This center cluster is adjacent to but not included in any sector.
3. These cross section drawings show identification as viewed in the direction of core propellant flow.

(CRD) ELEMENT DESCRIPTION AND IDENTIFICATION (U)	INDEX NO
	C. 1. 1. 6

CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. CORT 7/12/68	<i>Don M. Gatch</i> 7/14/68	

A = RADIUS OF NO. 10 CHANNEL (INCHES)*

B = POSITION

A	B	A	B	A	B	A	B	A	B
0.8	00 OF	6.9	1D 4G	10.9	1F 4D	13.8	1G 7E	15.1	1J 5G
2.0	1A 1F	6.4	1D 4B	11.1	1F 4E	14.4	1H 3F	14.8	1J 5B
1.3	1A 1G	6.8	1D 4C	10.9	1F 5F	13.8	1H 3G	15.4	1J 5C
1.5	1A 1B	7.5	1D 4D	10.2	1F 5G	13.7	1H 3B	16.1	1J 5D
2.3	1A 1C	7.9	1D 4E	9.8	1F 5B	14.4	1H 3C	17.0	1J 5J
2.7	1A 1D	9.9	1E 1F	10.2	1F 5C	15.0	1H 3D	16.8	1J 5H
2.6	1A 1E	9.3	1E 1G	10.9	1F 5D	15.1	1H 3E	16.5	1J 5K
3.9	1B 1F	9.4	1E 1B	11.3	1F 5E	14.1	1H 4F	15.9	1J 6F
3.3	1B 1G	10.1	1E 1C	11.6	1F 6F	13.4	1H 4G	15.1	1J 6G
3.5	1B 1B	10.7	1E 1D	10.9	1F 6G	13.2	1H 4B	14.8	1J 6B
4.2	1B 1C	10.6	1E 1E	10.4	1F 6B	13.8	1H 4C	15.3	1J 6C
4.7	1B 1D	9.2	1E 2F	10.6	1F 6C	14.5	1H 4D	16.0	1J 6D
4.6	1B 1E	8.5	1E 2G	11.4	1F 6D	14.7	1H 4E	16.8	1J 6H
3.8	1B 2F	8.5	1E 2B	11.8	1F 6E	14.1	1H 5F	16.6	1J 6K
3.0	1B 2G	9.2	1E 2C	13.8	1G 1F	13.3	1H 5G	16.2	1J 7F
2.7	1B 2B	9.8	1E 2D	13.2	1G 1G	13.1	1H 5B	15.5	1J 7G
3.3	1B 2C	9.8	1E 2E	13.4	1G 1B	13.6	1H 5C	15.1	1J 7B
4.0	1B 2D	8.9	1E 3F	14.1	1G 1C	14.3	1H 5D	15.5	1J 7C
4.2	1B 2E	8.2	1E 3G	14.7	1G 1D	14.6	1H 5E	16.2	1J 7D
5.9	1C 1F	8.0	1E 3B	14.5	1G 1E	14.3	1H 6F	17.0	1J 7H
5.3	1C 1G	8.6	1E 3C	13.1	1G 2F	13.6	1H 6G	17.0	1J 7K
5.4	1C 1B	9.3	1E 3D	12.4	1G 2G	13.2	1H 6B	16.8	1J 8F
6.2	1C 1C	9.4	1E 3E	12.5	1G 2B	13.6	1H 6C	16.0	1J 8G
6.7	1C 1D	9.0	1E 4F	13.1	1G 2C	14.4	1H 6D	15.6	1J 8B
6.6	1C 1E	8.3	1E 4G	13.8	1G 2D	14.7	1H 6E	15.9	1J 8C
5.4	1C 2F	7.9	1E 4B	13.7	1G 2E	14.8	1H 7F	16.6	1J 8D
4.7	1C 2G	8.4	1E 4C	12.5	1G 3F	14.1	1H 7G	17.0	1J 9H
4.6	1C 2B	9.1	1E 4D	11.8	1G 3G	13.6	1H 7B	16.5	1J 9K
5.2	1C 2C	9.4	1E 4E	11.8	1G 3B	14.0	1H 7C	16.8	1J 9P
5.9	1C 2D	9.6	1E 5F	12.4	1G 3C	14.7	1H 7D	15.6	1J 9F
6.0	1C 2E	8.9	1E 5G	13.1	1G 3D	15.1	1H 7E	14.8	1J 9G
5.7	1C 3F	8.4	1E 5B	13.1	1G 3E	15.0	1J 3F	14.3	1J 9B
4.9	1C 3G	8.7	1E 5C	12.3	1G 4F	14.4	1J 3G	14.6	1J 9C
4.5	1C 3B	9.4	1E 5D	11.6	1G 4G	14.4	1J 3B	15.3	1J 9D
4.9	1C 3C	9.9	1E 5E	11.4	1G 4B	15.1	1J 3C	15.8	1J 9E
5.7	1C 3D	11.8	1F 1F	12.0	1G 4C	15.7	1J 3D	15.8	1J 9V
6.0	1C 3E	11.3	1F 1G	12.7	1G 4D	15.7	1J 3E	15.2	1J 9W
7.9	1D 1F	11.4	1F 1B	12.9	1G 4E	17.0	1J 3H	15.4	1J 9R
7.3	1D 1G	12.1	1F 1C	12.5	1G 5F	16.4	1J 3J	16.1	1J 9S
7.4	1D 1B	12.7	1F 1D	11.7	1G 5G	17.0	1J 3N	16.7	1J 9T
8.2	1D 1C	12.5	1F 1E	11.4	1G 5B	16.4	1J 3V	16.5	1J 9U
8.7	1D 1D	11.1	1F 2F	11.8	1G 5C	15.7	1J 3W		
8.6	1D 1E	10.4	1F 2G	12.6	1G 5D	15.7	1J 3R		
7.3	1D 2F	10.5	1F 2B	12.9	1G 5E	16.3	1J 3S		
6.6	1D 2G	11.2	1F 2C	12.9	1G 6F	17.0	1J 3T		
6.5	1D 2B	11.8	1F 2D	12.1	1G 6G	17.0	1J 3U		
7.2	1D 2C	11.7	1F 2E	11.7	1G 6B	16.0	1J 4F		
7.8	1D 2D	10.7	1F 3F	12.1	1G 6C	15.2	1J 4G		
7.9	1D 2E	10.0	1F 3G	12.8	1G 6D	15.1	1J 4B		
7.2	1D 3F	9.9	1F 3B	13.2	1G 6E	15.7	1J 4C		
6.4	1D 3G	10.5	1F 3C	13.6	1G 7F	16.4	1J 4D		
6.2	1D 3B	11.2	1F 3D	12.9	1G 7G	17.1	1J 4H		
6.7	1D 3C	11.3	1F 3E	12.3	1G 7B	16.7	1J 4K		
7.4	1D 3D	10.6	1F 4F	12.6	1G 7C	17.0	1J 4M		
7.6	1D 3E	9.9	1F 4G	13.3	1G 7D	15.8	1J 5F		
7.6	1D 4F	9.6	1F 4B						
		10.1	1F 4C						

*Room Temperature Radius

(CRD) RADIAL POSITION OF FUEL ELEMENTS IN THE CORE (U)	INDEX NO.
	C.1.1.7

~~CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954~~

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>R. E. Thibault 7/24/62</i> <i>John M. Gault 7/24/62</i>

CUTAWAY VIEW OF SUPPORT BLOCK

(CRD) FUEL ELEMENT CLUSTER AND SUPPORT BLOCK ASSEMBLY (U)	INDEX NO.
	C.1.1.8

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Rittenberger 7/20/68	D. M. Litchner 7/26/68

(CRD) FUEL CLUSTER ASSEMBLY - DOME END (U)	INDEX NO
	C. 1. 1. 9

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	E. J. H. 7/30/68	DMC [signature]	

(U) The principal design differences between the XE-2 and XE-1 reactors which affect the nuclear, thermal, hydraulic and corrosion performance are listed using the XE-1 reactor as the basis for comparison. Differences stem from improvements made on the basis of previous reactor test experience and component testing. Similar tabulations are given in the NRX-A3, NRX/EST, NRX-A5, NRX-A6, and XE-1 Data Books (WANL-TME-840A, WANL-TME-1210, WANL-TME-1389, WANL-TME-1642, and WANL-TME-1565, respectively). The changes given here are for the "as-built" conditions.

(CRD) Design Changes (U)

A. (CRD) Fuel Elements (U)

(CRD) A summary of the fuel design conditions and placement of the XE-2 fuel elements is given in WANL-TME-1799, "XE-2 Element Placement and Orificing Summary".

1. The elements were manufactured by the Union Carbide Corporation Nuclear Division Y-12 and by the Westinghouse Astronuclear Core Operation.

2. The fuel element bore coatings are similar to those used in NRX-A6. They differ from those used in XE-1 in that the XE-2 coatings contain approximately 52 gms of niobium and 4 gms of molybdenum per element; whereas the XE-1 elements contained approximately 64 gms of niobium per element and no molybdenum.

3. All XE-2 fueled elements use a tapered tip at the aft end. The taper extends 0.75 inch from the end of the element and reaches a maximum depth of 0.0007 inch at the end of the element.

4. XE-2 elements in fueled loading codes 222, 179, and 133 are externally coated for a minimum of 30 inches from the aft end.

B. (CRD) Central Elements (U)

(CRD) Central elements are of the two types used in NRX/EST, NRX-A5, and XE-1, either solid graphite or TaC-dispersed in graphite. All central elements are externally NbC-coated for a minimum of 40 inches from the aft end.

(CRD) A total of 59 instrumented central elements were used in the XE-2 reactor. These elements are of the one-, two-, three-, or four-hole configurations which were tested in the NRX/EST and NRX-A5 reactors. No thirteen-hole central elements are used in XE-2.

C. (U) Partial Elements

(U) The partial elements in the XE-2 reactor have the same design as those used in the XE-1 reactor.

D. (CRD) Support Blocks (U)

(CRD) The support blocks in the XE-2 reactor are like those used in the XE-1 reactor, but with the following modifications:

1. The NbC-coating on the XE-2 support blocks was deposited at 1900°C and ranges from 2 to 4 mils in thickness; whereas the coating on the XE-1 support blocks was deposited at 2100°C and ranged from 2 to 5 mils in thickness.

2. The location of the flow holes and counter-bores in the XE-2 support blocks were slightly altered from the XE-1 configuration.

E. (U) Filler Strips

(U) The XE-2 filler strips are identical to the XE-1 filler strips.

F. (U) Liner Tube

(U) The XE-2 liner tubes are the same as the XE-1 liner tubes.

(CRD) DESIGN DIFFERENCES BETWEEN XE-2 AND XE-1 (U)	INDEX NO.
	C. 1.2 Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	DEZ 7/30/68	DEME 7/3/68	

- G. (U) Insulating Sleeve
- (U) The XE-2 central element insulating sleeves are "spigoted" as were the XE-1 insulating sleeves.
- H. (U) Inner Reflector
- (U) The inner reflector is identical to that of the XE-1, except for minor changes in instrumentation.
- J. (U) Particle Retainer
- (U) The XE-2 reactor contains a particle retainer above the filler strips, as did the XE-1 reactor.
- K. (U) Instrumentation
- (U) The XE-2 instrumentation is very similar to the XE-1 instrumentation; however, the following changes were made:
1. Five station 26 thermocouples were changed from a tungsten/tungsten-26 w/o rhenium thermocouple to a tungsten-5 w/o rhenium/tungsten-26 w/o rhenium thermocouple.
 2. The thermal capsule family distribution in XE-2 was changed from that used in XE-1 (see C.5.2 and C.5.3 for details).
 3. A pressure probe was added to seal chamber 11.
- L. (U) Core Pressure Drop
- (U) The design core pressure drop was decreased to 135 psi, versus 140 psi in the XE-1.
- M. (U) Initial Cold Critical Drum Position
- (U) The aim cold critical drum position for XE-2 was 96 degrees; whereas, the aim cold critical drum position for XE-1 was 90 degrees. The predicted cold critical drum position for XE-2 is 94.4 degrees (see E.3.1).

(CRD) DESIGN DIFFERENCES BETWEEN XE-2 AND XE-1 (U)	INDEX NO.
	C. 1.2 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>SLH 7/30/62</i>	<i>DAM Catch 7/4/62</i>	

Item	Units	Loading Code						
		431	366	315	256	222	179	133
1. Number of fueled elements.		1110	90	78	96	36	60	114
2. As-reamed coolant channel diameter.	mils	99	99	99	99	99	99	99
3. Enriched uranium loading per unit length of fueled graphite.	gms/inch	2.436	2.068	1.778	1.449	1.256	1.012	0.750
4. Enriched uranium loading per fueled graphite element ⁽¹⁾ ($\pm 2.5\%$ tolerance).	gms	124.2	105.5	90.7	73.9	64.0	51.6	38.2
5. Graphite loading per fueled element ($\pm 2.0\%$ tolerance).	gms	526	530	533	537	540	543	546
6. Niobium coating weight per fueled graphite element (bore and nozzle end). (± 10 gms tolerance)	gms	50	50	50	50	50	50	50
7. Maximum allowable external niobium coating weight gain per fueled graphite element.	gms	Not Applicable				16	16	16
8. Molybdenum coating weight per fueled graphite element.	gms	4.0	4.0	4.0	4.0	3.0	3.0	3.0
9. Molybdenum coating weight tolerances per fueled graphite element.	gms	± 1.0	± 1.0	± 1.0	± 1.0	± 1.5	± 1.5	± 1.5

(1) Uranium weight is for 51 inches because of the presence of the one-inch unfueled graphite tip; all other weights and tolerances are 52 inches.

(CRD) FUEL ELEMENT SPECIFICATION (U)	INDEX NO.
	C. 2. 1 Sheet 1

REFERENCE PDS 30093-1, 937J657	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>J. H. 7B968 EXM</i>	<i>Exm</i>	

Geometrical Specifications

Fuel Element Geometry

Hexagonal

Distance Across Flats

19 Hole Element	$0.754 \begin{smallmatrix} +.000 \\ -.002 \end{smallmatrix}$ inch
Overall Length, Including Graphite Tip	$52.000 \pm .005$ inch
Length of Graphite Tip	$1.000 \begin{smallmatrix} +.000 \\ -.125 \end{smallmatrix}$ inch
Reamed Hole Diameter	$0.0990 \pm .001$ inch

Computer Volumes

Element Envelope Volume (52 inches)	418.4 cc
Fueled Graphite Volume (Uncoated, 51 inches)	288.2 cc

(CRD) FUEL ELEMENT SPECIFICATIONS (U)

INDEX NO.

C. 2. 1
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>DDH 7/30/68</i>	<i>DAW [Signature]</i>	

Fuel Bead Specification

U-235 in Uranium	93.15 ± 0.15	Percent
U in UC_2	91	Weight Percent
Density of UC_2	$10.96 - 11.54$	gm/cc
Minimum U in Coated Particle	60	Weight Percent
Maximum Impurity Content	1000	ppm of U
Maximum Impurity Negative Reactivity Worth for the Core	30	cents
Particle Coating Thickness ⁽¹⁾	$\bar{X} - 1.6\sigma \geq 0.005$	mm
Coated Particle	0.130 ± 0.070	mm

⁽¹⁾ $\bar{X}$ is the average coating thickness and σ is the standard deviation on the coating thickness.

(CRD) FUEL ELEMENT SPECIFICATIONS (U)

INDEX NO.

C.2.1
Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>E. J. Jurenski 7/24/68</i>	<i>R. M. Galt 8/24/68</i>	

MASS SPECIFICATIONSReferenceGraphite Central Elements

PDS 30022-5

Graphite loading per unit volume of unfueled graphite	1.87 ± 0.05 g/cc
Graphite mass per single hole unfueled element	616.7 g
Graphite mass per unit volume tolerance	± 2.7 percent
Graphite mass per unfueled element tolerance; includes dimensional tolerance	± 2.9 percent
Quantity of H_2 in unfueled element	40 ppm maximum

TaC - Loaded Central Elements

PDS 30088-2

Density	2.00 g/cc
Ta mass per unit volume of element (approximate)	227 mg/cc
Ta mass per unfueled element	$75 \text{ g} \pm 2 \text{ g}$
Impurity concentration not to exceed	1500 ppm or -0.02% reactivity

GEOMETRICAL SPECIFICATIONS

Central Element Geometry	Hexagonal	PDS 30022-5
Distance Across Flats	$0.754 \begin{smallmatrix} + 0.000 \\ - 0.002 \end{smallmatrix}$ inch	938J192
Length	52.00 ± 0.005 inch	
Central Hole Diameter	0.364 ± 0.001 inch (BEFORE COATING)	
Number of holes in instrumented central elements	1, 2, 3, or 4	
Instrument hole diameter	0.100 ± 0.0005 inch	938J193

Component Specifications

Non-instrumented tie rod diameter	$0.110 \begin{smallmatrix} + 0.002 \\ - 0.001 \end{smallmatrix}$ inch	945C568
Stainless Steel Liner OD	$0.237 \begin{smallmatrix} + 0.000 \\ - 0.002 \end{smallmatrix}$ inch	978D347
Stainless Steel Liner Wall Thickness	0.005 ± 0.001 inch	
Pyrographite liner ID	0.246 ± 0.004 inch	
Pyrographite liner OD	0.357 ± 0.002 inch	

(CRD) UNFUELED CENTRAL ELEMENT SPECIFICATIONS (U)	INDEX NO.
	C.2.2 Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	D. Hill	<i>D. Hill</i> 7/31/54	

<u>Positive Shim Specifications*</u>	<u>Units</u>	<u>Value</u>	<u>Reference</u>
Graphite Pencil Shim Outer Diameter	inch	0.098 ± 0.001	946C173
	cm	0.249 ± 0.0025	
Graphite Pencil Shim Length	inch	$4.000 \begin{smallmatrix} + 0.100 \\ - 0.050 \end{smallmatrix}$	946C173
	cm	$10.16 \begin{smallmatrix} + 0.254 \\ - 0.127 \end{smallmatrix}$	
Graphite Pencil Shim Volume	cc	0.49	
Graphite Pencil Shim Density	g/cc	1.80 - 1.90	PDS 30039
Graphite Pencil Shim Weight	g	0.89 - 0.94	

* There are twelve 4-inch shim pencils and one 2.8 inch shim pencil per unused instrumentation hole. Positive shim pencils are no longer used for shimming, but only to fill unused instrumentation holes in central elements of XE-2.

Assembly and Component Volumes (Based on 52 inch length)

Unfueled element envelope volume	418.4 cc
Tie rod volume	8.10 cc
Stainless steel liner	3.10 cc
Pyrographite liner	45.12 cc
Graphite volume	
No instrument holes	330.8 cc
Void volumes	
Tie rod channel	31.3 cc

(CRD) UNFUELED CENTRAL ELEMENT SPECIFICATIONS (U)	INDEX NO.
	C.2.2 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>E. J. Jurenski 7/29/68</i>	<i>D. W. Matson 7/29/68</i>	

FUELED ELEMENT DATA BY LOADING CODE

Y-12 DATA						WNCO DATA			
LDG	T NO	NO	TOTAL	AVG	S DEV	NO	TOTAL	AVG	S DEV
REACTIVITY-WEIGHTED BORE NIOBIUM MASS, GRAMS ⁽¹⁾									
3	42	0	0.	0.000	0.000	42	0.	0.000	0.000
133	114	0	0.	0.000	0.000	114	5.591099E+03	49.045	3.205
179	60	0	0.	0.000	0.000	60	2.911159E+03	48.519	1.842
222	36	0	0.	0.000	0.000	36	1.769581E+03	49.155	1.963
256	96	96	5.297242E+03	55.180	2.720	0	0.	0.000	0.000
315	78	78	4.332107E+03	55.540	1.930	0	0.	0.000	0.000
366	90	90	5.045201E+03	56.058	4.710	0	0.	0.000	0.000
431	1110	667	3.600681E+04	53.983	3.790	443	2.176683E+04	49.135	3.994
TOTAL MASS, GRAMS									
3	42	0	0.	0.000	0.000	42	2.125780E+04	506.138	5.647
133	114	0	0.	0.000	0.000	114	7.327800E+04	642.789	3.392
179	60	0	0.	0.000	0.000	60	3.920130E+04	653.355	2.370
222	36	0	0.	0.000	0.000	36	2.391090E+04	664.192	2.335
256	96	96	6.455840E+04	672.483	2.766	0	0.	0.000	0.000
315	78	78	5.347220E+04	685.541	1.799	0	0.	0.000	0.000
366	90	90	6.285160E+04	698.351	3.724	0	0.	0.000	0.000
431	1110	667	4.746615E+05	711.636	4.522	443	3.139830E+05	708.765	3.737
EXTERNAL NIOBIUM MASS, GRAMS									
3	42	0	0.	0.000	0.000	42	6.193000E+02	14.745	0.854
133	114	0	0.	0.000	0.000	114	8.508000E+02	7.463	0.925
179	60	0	0.	0.000	0.000	60	4.143000E+02	6.905	0.883
222	36	0	0.	0.000	0.000	36	2.563000E+02	7.119	0.673
256	96	96	8.288000E+01	0.863	0.056	0	0.	0.000	0.000
315	78	78	6.805000E+01	0.872	0.037	0	0.	0.000	0.000
366	90	90	8.237000E+01	0.915	0.067	0	0.	0.000	0.000
431	1110	667	5.554300E+02	0.833	0.082	443	4.796668E+02	1.083	0.073

(1) The reactivity-weighted niobium weight reported is the mass of axially uniform niobium equivalent in reactivity to the actual niobium mass reported under the heading "niobium weight, grams".

(CRD) XE-2 "AS-BUILT" FUELED AND UNFUELED ELEMENT INVENTORY (U)	INDEX NO.
	C. 2.3 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>E. J. Jurek</i>	<i>R. M. Cuthbert</i>	

FUELED ELEMENT DATA BY LOADING CODE

Y-12 DATA						WNCO DATA			
LDG	T NO	NO	TOTAL	AVG	S DEV	NO	TOTAL	AVG	S DEV
UNFUELED TIP LENGTH, INCHES									
3	42	0	0.	0.000	0.000	42	0.	0.000	0.000
133	114	0	0.	0.000	0.000	114	1.100800E+02	0.966	0.020
179	60	0	0.	0.000	0.000	60	5.815000E+01	0.969	0.017
222	36	0	0.	0.000	0.000	36	3.509000E+01	0.975	0.014
256	96	96	9.127000E+01	0.951	0.005	0	0.	0.000	0.000
315	78	78	7.421000E+01	0.951	0.005	0	0.	0.000	0.000
366	90	90	8.525000E+01	0.947	0.011	0	0.	0.000	0.000
431	1110	667	6.312000E+02	0.946	0.009	443	4.302700E+02	0.971	0.013

MOLYBDENUM MASS, GRAMS

3	42	0	0.	0.000	0.000	42	0.	0.000	0.000
133	114	0	0.	0.000	0.000	114	3.936000E+02	3.453	0.362
179	60	0	0.	0.000	0.000	60	1.951000E+02	3.252	0.427
222	36	0	0.	0.000	0.000	36	1.267000E+02	3.519	0.261
256	96	96	2.947000E+02	3.070	0.252	0	0.	0.000	0.000
315	78	78	2.224000E+02	2.851	0.227	0	0.	0.000	0.000
366	90	90	2.598000E+02	2.887	0.353	0	0.	0.000	0.000
431	1110	667	1.897300E+03	2.845	0.416	443	1.599100E+03	3.610	0.396

REACTIVITY WEIGHTED MOLYBDENUM MASS, GRAMS⁽¹⁾

3	42	0	0.	0.000	0.000	42	0.	0.000	0.000
133	114	0	0.	0.000	0.000	114	4.245066E+02	3.724	0.400
179	60	0	0.	0.000	0.000	60	2.009750E+02	3.350	0.434
222	36	0	0.	0.000	0.000	36	1.281601E+02	3.560	0.340
256	96	96	3.515352E+02	3.662	0.363	0	0.	0.000	0.000
315	78	78	2.637753E+02	3.382	0.283	0	0.	0.000	0.000
366	90	90	3.013015E+02	3.348	0.297	0	0.	0.000	0.000
431	1110	667	2.240002E+03	3.358	0.491	443	1.760988E+03	3.975	0.499

(1) The reactivity-weighted molybdenum mass reported is the mass of axially uniform molybdenum equivalent in reactivity to the actual molybdenum mass reported under the heading "molybdenum mass, grams".

(CRD) XE-2 "AS-BUILT" FUELED AND UNFUELED ELEMENT INVENTORY (U)	INDEX NO.
	C. 2. 3 Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>J. J. J. J.</i>		

UNFUELED ELEMENT DATA

LOADING	TOTAL NO.	NO	TOTAL WEIGHT	AVG	S DEV
---------	-----------	----	--------------	-----	-------

TANTALUM MASS, GRAMS

00 ⁽¹⁾	36	42	3.140250E+03	74.768	0.319
01	212	206	0.	0.000	0.000
02	41	41	0.	0.000	0.000

BORE NIOBIUM MASS, GRAMS

00	36	42	2.902600E+02	6.911	0.379
01	212	206	1.594110E+03	7.738	0.413
02	41	41	3.112700E+02	7.592	0.424

CARBON MASS, GRAMS

00	36	42	2.547193E+04	606.475	1.731
01	212	206	1.260078E+05	611.688	2.005
02	41	41	2.433682E+04	593.581	11.446

REACTIVITY WEIGHTED BORE NIOBIUM MASS, GRAMS

00	36	42	2.870073E+02	6.834	0.573
01	212	206	1.561743E+03	7.581	0.382
02	41	41	2.993789E+02	7.302	0.474

TOTAL MASS, GRAMS

00	36	42	2.970134E+04	707.175	2.536
01	212	206	1.321002E+05	641.263	2.788
02	41	41	2.553770E+04	622.871	11.022

EXTERNAL NIOBIUM, GRAMS

00	36	42	7.989000E+02	19.021	1.509
01	212	206	4.498290E+03	21.836	1.498
02	41	41	8.896100E+02	21.698	1.964

- (1) 00 - Tantalum carbide shimmed central element.
01 - Graphite central element.
02 - Instrumented graphite central element.

(CRD) XE-2 "AS-BUILT" FUELED AND UNFUELED ELEMENT INVENTORY (U)	INDEX NO.
	C.2.3 Sheet 4

REFERENCE

AVERAGE BORE NbC PROFILE FOR WNCO FUEL ELEMENTS, MILS^(1,2)

AXIAL POSITION FROM INLET END OF FUEL ELEMENT, INCHES

Loading Code	1.0	4.0	7.0	10.0	13.0	16.0	19.0	22.0	25.0	28.0	31.0	34.0	37.0	40.0	43.0	46.0	49.0	Average Thickness
133	0.71	0.80	0.86	0.91	0.99	1.05	1.11	1.15	1.20	1.28	1.35	1.44	1.56	1.69	1.81	1.89	1.96	1.31
179	0.74	0.79	0.85	0.90	0.96	1.03	1.07	1.13	1.17	1.23	1.30	1.37	1.49	1.61	1.73	1.82	1.91	1.27
222	0.77	0.84	0.92	0.99	1.05	1.11	1.16	1.21	1.25	1.30	1.37	1.44	1.55	1.68	1.77	1.85	1.92	1.33
431	0.77	0.81	0.86	0.91	0.97	1.02	1.06	1.11	1.18	1.30	1.44	1.58	1.74	1.87	1.99	2.10	2.23	1.38

AVERAGE BORE NbC PROFILE FOR Y-12 FUEL ELEMENTS, MILS⁽¹⁾

AXIAL POSITION FROM INLET END OF FUEL ELEMENT, INCHES

Loading Code	3.4	8.3	13.2	18.0	22.9	27.7	32.6	37.6	42.3	47.2	Average Thickness
256	0.69	0.96	1.14	1.26	1.36	1.48	1.61	1.74	1.88	2.02	1.38
315	0.71	0.95	1.13	1.27	1.40	1.52	1.65	1.78	1.89	2.02	1.40
366	0.70	0.95	1.12	1.25	1.36	1.48	1.61	1.76	1.92	2.08	1.39
431	0.68	0.96	1.15	1.27	1.38	1.50	1.63	1.77	1.91	2.06	1.40

AVERAGE BORE NbC PROFILE FOR Y-12 UNFUELED ELEMENTS, MILS⁽¹⁾

AXIAL POSITION FROM INLET END OF FUEL ELEMENT, INCHES

Loading Code	11.8	37.0	49.0	51.9	Average Thickness
00	1.25	1.12	1.12	1.29	1.17
01	1.36	1.33	1.39	1.24	1.37
02	1.33	1.28	1.40	1.23	1.35

(1) Average external NbC profiles not available. Coating weights given on C.2.3. (2) Data on bore profiles for WNCO 03 unfueled elements are not available.

(CRD) AVERAGE AXIAL NIOBIUM CARBIDE PROFILES BY LOADING CODE (U)

PREPARED BY

APPROVED BY

Shumski 7/3/68 *DeMott 7/16/68*

CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954

C-24

C.2.4

INDEX NO.

REFERENCE

(CRD) NbC BORE COATING THICKNESS AS A FUNCTION OF AXIAL POSITION (1)

PREPARED BY

APPROVED BY

E. J. ...

INDEX NO

C.2.5

REFERENCE

AVERAGE MOLYBDENUM PROFILE FOR WNCO FUEL ELEMENTS, GM/5 INCHES

AXIAL DISTANCE FROM INLET END OF FUEL ELEMENT, INCHES

<u>Loading Code</u>	<u>2.5</u>	<u>7.5</u>	<u>12.5</u>	<u>17.5</u>	<u>22.5</u>	<u>27.5</u>	<u>32.5</u>	<u>37.5</u>	<u>42.5</u>	<u>47.5</u>	<u>Average Unit Mass</u>
133	0.23	0.37	0.41	0.42	0.40	0.37	0.34	0.31	0.31	0.30	0.34
179	0.26	0.41	0.43	0.39	0.35	0.31	0.29	0.28	0.27	0.28	0.32
222	0.31	0.45	0.47	0.42	0.37	0.32	0.30	0.29	0.29	0.30	0.35
431	0.17	0.37	0.47	0.46	0.41	0.37	0.36	0.35	0.33	0.31	0.36

AVERAGE MOLYBDENUM PROFILE FOR Y-12 FUEL ELEMENTS, GM/5 INCHES

AXIAL DISTANCE FROM INLET END OF FUEL ELEMENT, INCHES

<u>Loading Code</u>	<u>2.5</u>	<u>7.5</u>	<u>12.5</u>	<u>17.5</u>	<u>22.5</u>	<u>27.5</u>	<u>32.5</u>	<u>37.5</u>	<u>42.5</u>	<u>47.5</u>	<u>Average Unit Mass</u>
256	0.03	0.08	0.21	0.34	0.39	0.41	0.42	0.42	0.40	0.36	0.31
315	0.02	0.07	0.19	0.33	0.36	0.37	0.39	0.40	0.38	0.35	0.29
366	0.01	0.05	0.14	0.26	0.31	0.33	0.34	0.34	0.33	0.30	0.24
431	0.01	0.03	0.13	0.28	0.36	0.37	0.39	0.39	0.36	0.36	0.27

(CRD) AVERAGE AXIAL MOLYBDENUM PROFILES BY LOADING CODE (CRD)

PREPARED BY

APPROVED BY

E. L. ... *R. M. ...*

REFERENCE

(CRD) MOLYBDENUM MASS DISTRIBUTION AS A FUNCTION OF AXIAL POSITION (CRD)

PREPARED BY

APPROVED BY

E. J. ... 8-1-68

INDEX NO

C.2.7

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. R. Thompson 7/20/68	E. R. McArthur 7/24/68

* The loading code number represents the specification uranium loading of the fuel in mg/cc.

(CRD) XE-2 URANIUM LOADING DISTRIBUTION (U)	INDEX NO
	C.3.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. COURT 7/30/68	John F. Litch 7/30/68

- FILLER STRIP WITH THERMAL CAPSULE
- UNFUELED ELEMENT WITH THERMAL CAPSULE
- UNFUELED ELEMENT WITH THERMOCOUPLE
- UNFUELED ELEMENT WITH INTERSTITIAL PRESSURE PROBE
- TIE ROD STRAIN GAGE
- UNFUELED ELEMENT WITH TIE ROD MATERIAL THERMOCOUPLE
- EXIT GAS THERMOCOUPLE
- FUELED ELEMENTS WITH THERMOCOUPLES
- SHIMMED ELEMENTS

(CRD) XE-2 SHIMMING DISTRIBUTION AND INSTRUMENTATION PLACEMENT (U)

INDEX NO.

C. 3. 2
Sheet 1

CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E. COIT 7/30/69	<i>[Signature]</i> 7/30/69	

CLUSTER CENT	THERMO COUPLE	THERMAL CAPSULE	TE MOD WATER AL T/C	STRAIN GAGE	HYD STYL PRESSURE PROBE	STATION	CENTRAL ELEMENT HOLE NO	THERMOCOUPLE LOCAT ON
0 0 0 A	TE 608			MG 701 MG 702		200.6 200.6		
1 A1 A	TE 619	C 001				228.9	8 2 6 18 PLUGGED	UNFUELED ELEMENT
1 A1 G	TE 611					204.4		UNFUELED ELEMENT
1 B1 A	TE 609					258.7		UNFUELED ELEMENT
1 B2 A					PD 611	239.9	8	UNFUELED ELEMENT
C1 A	TE 655					258.7	6	UNFUELED ELEMENT
1 D A	TE 698					258.7		CLUSTER EXT GAS
D4 A	TE 648					229.9	9	UNFUELED ELEMENT
E A	TE 647					229.9	6	UNFUELED ELEMENT
F A	TE 699					258.7		CLUSTER EXT GAS
F2 A	TE 700				PD 67	237	2	CLUSTER EXT GAS
G A	TE 701					258.7		CLUSTER EXT GAS
G3 A	TE 668					200.6	6	UNFUELED ELEMENT
J9 Q				MG 708 MG 710		200.6		
2 B A	TE 685			MG 708		200.6		
2 D A				MG 706		200.6		
2 D4 A	TE 643			MG 706		200.6	6	UNFUELED ELEMENT
2 F1 A				MG 707		200.6		
2 G3 A	TE 644			MG 708		229.9	6	UNFUELED ELEMENT
2 H5 A	TE 708					258.7		CLUSTER EXT GAS
2 J9 Q	TE 672 TE 640	C 0	TE 77			223.9 233.9 257.8	2 8 0	UNFUELED ELEMENT UNFUELED ELEMENT
3 A A	TE 665 TE 646	C 03	TE 73			229.9 229.0 257.8	2 8 0	UNFUELED ELEMENT UNFUELED ELEMENT
3 B2 A			TE 73		PD 63	237	8	CLUSTER EXT GAS
3 C A	TE 670 TE 680 TE 690	C 007				229.9 235.9 258.7	2 8 0	UNFUELED ELEMENT UNFUELED ELEMENT CLUSTER EXT GAS
3 F2 A					PD 68	237	2	CLUSTER EXT GAS
3 F3 A	TE 661 TE 689	C 006				229.9 258.7	2 8 0	UNFUELED ELEMENT CLUSTER EXT GAS
3 G A	TE 649 TE 645	C 05	TE 75			229.9 229.9 257.8	2 8 0	UNFUELED ELEMENT UNFUELED ELEMENT CLUSTER EXT GAS
3 H3 A	TE 657 TE 677 TE 688	C 00				229.9 235.9 258.7	2 8 0	UNFUELED ELEMENT UNFUELED ELEMENT CLUSTER EXT GAS
3 J3 Q	TE 673	C 004	TE 7			229.9 25.8	2 8 0	UNFUELED ELEMENT CLUSTER EXT GAS
3 J9 Q	TE 706	C 005				258.7	2 8 0	UNFUELED ELEMENT CLUSTER EXT GAS
4 A A	TE 674 TE 674 TE 659					229.9 235.9 258.7	2 8 0	UNFUELED ELEMENT UNFUELED ELEMENT CLUSTER EXT GAS
4 C A A	TE 677					229.9	2	UNFUELED ELEMENT
4 D4 A	TE 653					229.9	6	UNFUELED ELEMENT
4 E A	TE 678					229.9	6	UNFUELED ELEMENT
4 G3 A	TE 663					229.9	6	UNFUELED ELEMENT
4 G6 A	TE 675					229.9	6	UNFUELED ELEMENT
4 H6 A	TE 707					258.7		CLUSTER EXT GAS
4 I E	TE 705					258.7		CLUSTER EXT GAS
5 B2 A					PD 66	237	8	CLUSTER EXT GAS
5 F2 A					PD 65	237	2	CLUSTER EXT GAS
5 J9 J			TE 76			257.8		
5 9 Q	TE 656 TE 657 TE 650 TE 652	C 06				229.9 229.9 204.9 204.4	2 8 0	UNFUELED ELEMENT UNFUELED ELEMENT UNFUELED ELEMENT UNFUELED ELEMENT
5 J9 T	TE 650 TE 650 TE 652	C 006				229.9 235.9 258.7	2 8 0	UNFUELED ELEMENT UNFUELED ELEMENT UNFUELED ELEMENT
6 A A	TE 650 TE 648 TE 692	C 04				229.9 235.9 258.7	2 8 0	UNFUELED ELEMENT UNFUELED ELEMENT UNFUELED ELEMENT
6 E A	TE 664 TE 642	C 008	TE 74			229.9 229.9 257.8	2 8 0	UNFUELED ELEMENT UNFUELED ELEMENT UNFUELED ELEMENT
6 F3 A	TE 676 TE 676 TE 694	C 009				229.9 235.9 258.7	2 8 0	UNFUELED ELEMENT UNFUELED ELEMENT UNFUELED ELEMENT
6 G A	TE 662 TE 65 TE 693					229.9 235.9 258.7	2 8 0	UNFUELED ELEMENT UNFUELED ELEMENT UNFUELED ELEMENT
6 G3 A	TE 658	C 003				229.9	2	UNFUELED ELEMENT
6 H3 A	TE 669 TE 695	C 002				229.9 257.8	2 8	UNFUELED ELEMENT UNFUELED ELEMENT
6 J								

CLUSTER DELT	THERMO COLUPLE	THERMAL CAPSULE	T.E. MOD MATERIAL TIC	STRAN GAGE	WTER ST T AL PRESSURE PROBE	STATION	CENTRAL ELEMENT MOLE DON	THERMOCOUPLE LOCAT ON
G 03 Q	TE 039 TE 041	C 019	TE 7 B			233 9 235 9 237 B	E O	MULTI ELEMENT MULTELEMENT
G 04 A		C 022 C 023 C 024 C 025					E B B	
G 04 H	TE 002 TE 0 3					204 8 204 4		MULTI ELEMENT MULTI ELEMENT
G 05 A		C 026 C 027 C 028 C 029					A O A	
G 05 E		C 030 C 031 C 032 C 033					E B O	
G 06 A		C 034 C 035 C 036 C 037					O A O	
G 07 E		C 038 C 039					O Z G	
G 08 A	TE 706	C 040				258 7		OP WATER, STERIL TGA
G 09 A	TE 702					250 7	B	CLUSTER 2 GAS
G 09 J	TE 703	C 041				258 7	B	CLUSTER 2 GAS
G 09 D						258 7		CLUSTER 2 GAS

[illegible]

CENTRAL CLUSTER

REGULAR CLUSTER

EX CPT AS NO
NOTCH IN PLATE 5 LOCATED IN RELATION
TO NOTCHES 4 ELEMENTS AS SHOWN
ARROW INDICATES FACE A

RAL NO FACE

CEN HA E ENL O SRE
HOLE CNG HA CLS
OCHLW ART
SEC HAR CHA A H E CATONS
SAEZI

NOTE

FACE F ROTATED TO A FACE F' IN
FOR ELEMENTS A A(4) A(4)
D USED HOLE NUMBERS REL. TO ELEMENT
HOLE NUMBER PRIOR TO ROTATION

	FILLER STRIP WITH THERMAL CAPSULE
	UNFUELED ELEMENT WITH THERMAL CAPSULE
	UNFUELED ELEMENT WITH THERMOCOUPLE
	UNFUELED ELEMENT WITH INTERSTITIAL PRESSURE PROBE
	THERMOCOUPLE ROD STRAIN GAGE
	UNFUELED ELEMENT WITH THERMOCOUPLE ROD MATERIAL THERMOCOUPLE
	EXHAUST GAS THERMOCOUPLE
	FILLED ELEMENTS WITH THERMOCOUPLES
	SHIMMED ELEMENTS

(CRD) XE-2 SHIMMING DISTRIBUTION AND INSTRUMENTATION PLACEMENT (U)

INDEX NO.

C.3.2
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. S. Langford	R. W. Fitch 7/3/58	

Type of Instrumentation	WANL Drawing No.	No. of Instruments	No. of Elements Used
I. Central Region (199 Regular Clusters)			
A. Unfueled Elements			
Thermal Capsules	978D675	12	12
Pressure Probes	980D608H01	6	6
Thermocouples			
a. Cluster Exit Gas	979D149H02	16	16
b. Station 52.6 Tie Rod Exit Material	978D186H02	3	3
c. Station 32 Material	978D270H03	6	6
d. Station 26 Material	978D270H02	16	14
e. Station 26 Material	914E072H02	5	4
f. Station 20 Material	978D270H01	6	6
Number of Central Unfueled Elements Containing In-Core Thermocouples			24
Number of Central Unfueled Elements Containing Instrumentation			35
B. Fueled Elements, Thermocouples			
a. Station 1.0 Material	978D186H03	1	1
b. Station 0.5 Material	978D186H03	1	1
Number of Central Fueled Elements Containing Thermocouples			1

(CRD) CORE INSTRUMENTATION SUMMARY (U)	INDEX NO.
	C. 3, 3 Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Bingham	G.M. [Signature] 7/4/8	

Type of Instrumentation	WANL Drawing No.	No. of Instruments	No. of Elements Used
II. Peripheral Region (90 Irregular Clusters)			
A. Unfueled Elements			
Thermal Capsules	978D675	26	17
Thermocouples			
a. Cluster Exit Gas	979D149H02	5	5
b. Station 52.6 Tie Rod Exit Material	978D186H02	4	4
c. Station 32 Material	978D270H03	2	2
d. Station 26 Material	978D270H02	3	2
e. Station 20 Material	978D270H01	2	2
Number of Peripheral Unfueled Elements Containing In-Core Thermocouples			4
Number of Peripheral Unfueled Elements Containing Instrumentation			21
B. Fueled Elements, Thermocouples			
a. Station 1.0 Material Temperature	978D186H03	2	2
b. Station 0.5 Material Temperature	978D186H03	2	2
Number of Peripheral Fueled Elements Containing Thermocouples			2
Total Number of Elements in Core Containing Instrumentation			59

(CRD) CORE INSTRUMENTATION SUMMARY (U)	INDEX NO
	C.3.3 Sheet 2

REFERENCE

XE-2 CORE INVENTORY, AS-BUILT

FUELED ELEMENTS

Loading Code	Manufacturer	No. of Elements	U Mass ⁽¹⁾ kg	C Mass kg	Nb Actual ⁽²⁾ Mass, kg	Nb Effective ⁽³⁾ Mass, kg	Molybdenum Mass, kg	Mo Effective ⁽⁵⁾ Mass, kg
133	WNCO	114	4.414	61.948	5.754	5.591	0.394	0.425
179	WNCO	60	3.162	32.483	3.006	2.911	0.195	0.201
222	WNCO	36	2.349	19.416	1.808	1.770	0.127	0.128
256	Y-12	96	7.187	51.928	5.196	5.297	0.295	0.352
315	Y-12	78	7.199	41.883	4.232	4.332	0.222	0.264
366	Y-12	90	9.629	48.065	4.990	5.045	0.260	0.301
431	WNCO	443	56.154	233.828	22.971	21.767	1.599	1.761
431	Y-12	667	84.290	354.178	35.275	36.007	1.897	2.240
TOTALS		1584	174.384	843.729	83.232	82.720	4.989	5.672

UNFUELED ELEMENTS

Loading Code ⁽⁴⁾	Manufacturer	No. of Elements	Ta Mass kg	C Mass kg	Nb Actual ⁽²⁾ Mass, kg	Nb Effective ⁽³⁾ Mass, kg
00	Y-12	42	3.140	25.472	0.290	0.287
01	Y-12	206	0.0	126.008	1.594	1.562
02	Y-12	41	0.0	24.337	0.311	0.299
03	WNCO	42	0.0	20.639	----	----
TOTALS		331	3.140	196.456	2.195	2.148

OTHER COMPONENTS

Component	Quantity	Material	Mass, kg
Pyrographite Sleeve	289	Carbon	26.832
Positive Shims	5	Carbon	0.056
Tie Rod	289	Inconel-718	23.648
Liner Tubes	289	Stainless Steel	8.044

- (1) Mass of uranium calculated on the basis of a 52-inch fueled length
 (2) Bore coating only. See C. 2.3 for external coating weights.
 (3) Mass of uniform Nb equivalent in reactivity to actual Nb mass.
 (4) Unfueled loading codes are defined in Figure E. 1. 4.
 (5) Mass of uniform Mo equivalent in reactivity to actual Mo mass.

(CRD) XE-2 "AS BUILT" CORE INVENTORY (U)

PREPARED

APPROVED BY

INDEX NO.

C. 3. 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>J. Jurek 1/3/61</i>	<i>R. M. G. 1/4/61</i>	

Specifications

			<u>Reference</u>
No. of Absorber Vanes	12		
No. of Control Plates (3/Vane)	36		
Inside Radius	$4.760^{+ .000}_{- .003}$	cm	977D791
Included Angle	120 degrees		
Thickness of Vane	$0.125 \pm .005$	cm	977D791
Volume of Vane Material (Net)	2010	cm ³	977D791
B-10 in Boron	92	Weight percent	PDS 30010
Weight of B/Vane	91.76	g	PDS 30010
Weight of B-10/Vane	84.42	g	
Weight of B-10 in 12 Vanes	1.013	kg	
Weight of B-10 in Aluminum	20 ± 2	Weight percent	PDS 30010
Volume of B in Al	22.4	Volume percent	

As-Built Data

B-10 in B	95.78	Weight percent
Weight of B/Vane	89.38	g
Weight of B-10/Vane	85.61	g
Weight of B-10 in 12 Vanes	1.027	kg
Weight of B-10 in Aluminum	19.94	Weight percent
Average Weight Per Control Plate	143.09	g
Average Density of Control Plate	2.57	g/cc

(CRD) CONTROL VANE DATA (U)

INDEX NO.

C.4.1
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>E. J. Smith 7/30/64</i>	<i>R. M. Litch 7/1/64</i>	

Sector	Location on Drum	Serial Number	Weight, Grams	w/o B-10	Weight B-10, Grams
1	D (dome)	A63633	142.77	19.89	28.40
	C (center)	A63653	142.51	19.70	28.27
	N (nozzle)	A63635	142.92	20.19	28.86
2	D	A63625	143.16	20.18	28.89
	C	A63624	143.18	20.32	29.09
	N	A63638	143.30	19.99	28.65
3	D	A63649	142.28	20.08	28.57
	C	A63619	142.34	20.39	29.02
	N	A63645	143.96	19.49	28.06
4	D	A63644	142.14	19.33	27.48
	C	A63648	143.65	19.90	28.59
	N	A63627	143.46	20.51	29.42
5	D	A63629	144.87	20.05	29.05
	C	A63622	143.46	20.34	29.18
	N	A63623	142.83	20.40	29.14
6	D	A63641	144.11	19.49	28.09
	C	A63647	143.73	19.69	28.30
	N	A63651	143.51	19.73	28.31
7	D	A63643	143.13	19.12	27.37
	C	A63639	143.37	20.01	28.69
	N	A63650	141.81	19.99	28.35
8	D	A63642	143.44	19.40	27.83
	C	A63654	143.06	19.57	28.00
	N	A63620	141.57	20.16	28.54
9	D	A63652	143.53	19.65	28.20
	C	A63632	142.88	19.93	28.48
	N	A63631	140.91	20.06	28.27
10	D	A63637	143.43	19.96	28.63
	C	A63636	140.66	20.38	28.67
	N	A63621	143.37	20.31	29.12
11	D	A63626	142.80	20.51	29.29
	C	A63634	142.79	19.80	28.27
	N	A63630	144.48	20.09	29.03
12	D	A63628	143.39	20.09	28.81
	C	A63646	144.60	19.42	28.08
	N	A63640	142.98	19.78	28.28
TOTAL			5151.38	AVERAGE 19.94	TOTAL 1027.28

(CRD) CONTROL VANE DATA (U)

INDEX NO.

C. 4, 1
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>JJA 7/30/68</i>	<i>R. M. Litch 7/27/68</i>	

REFLECTOR REGION WEIGHTS

Region	Material	Mass, kg
Filler Strip	Carbon ⁽¹⁾	94.011
	SS Retainer	0.5
Lateral Support	Carbon	
	a. Seal & Retainer Segments	43.279
	b. Barrel ⁽¹⁾	247.798
	c. Plungers	2.486
	Stainless Steel	11.836
	Aluminum	8.618
	Silica ⁽¹⁾	7.950
Beryllium Reflector	Beryllium	712.742
	Aluminum	1.545
	Titanium	29.143
Control Drums	Beryllium	199.856
	Aluminum	18.228
	B-10	1.0273
Support Blocks	Carbon	37.090

(1) Weight for active core length.

(CRD) REFLECTOR REGION "AS-BUILT" INVENTORY (U)	INDEX NO
	C. 4.2

~~CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954~~

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Burghardt <i>7/1/58</i>	<i>22 McClellan 7/4/58</i>	

REFLECTOR AND SHIELD INSTRUMENTATION SUMMARY

Measurement	Station *	Quantity	Transducer Drawing No.
I. Thermocouples			
A. Material Temperatures			
Outer Reflector Sector	8	1	963B363H01
	20	1	963B363H01
	32	1	963B363H01
	45	1	963B363H01
Outer Reflector Bolts	20	1	964B039H02
	32	1	964B039H02
Control Drum, No. 5	8	2	964B039H02
	32	2	964B039H02
Inner Reflector Cylinder	32.5	1	963B362H01
	32.7	1	963B362H01
	45	1	963B362H01
Core Support Plate	- 1.4	2	963B363H01
B. Gas Temperatures			
Reflector Inlet Plenum (RTT)	53.8	4	979D162G02
Shield Dome End Plenum	-23.1	6	945C906H01
Core Inlet Plenum	- 0.8	11	945C906H01
II. Pressure Probes			
Reflector Inlet Plenum	55.7	2	980D603H04
Outer Reflector Outlet Plenum	- 5.6	1	980D603H04
Shield Dome End Plenum	-22.6	1	980D603H04
Core Inlet Plenum	- 0.9	3	980D603H04
Seal Chamber 11	32.8	1	980D608H04

* Inches from forward face of core

(CRD) REFLECTOR AND SHIELD INSTRUMENTATION SUMMARY (U)	INDEX NO.
	C.4.3

~~CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954~~

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. B. Burghardt 7/25/68	D. M. Cutler 7/31/68	

THIS PAGE UNCLASSIFIED

CODE NO.	MELTING TEMPERATURE °R + 54°R	NOMINAL WIRE COMPOSITION ⁽²⁾
1	1680	100 aluminum
2	1887	28 copper - 72 silver
3	2139	20 copper - 80 gold
4	2238	100 silver
5	2463	82 silver - 18 palladium
6	2688	67 silver - 33 palladium
7	2832	50 silver - 50 palladium
8	3048	25 silver - 75 palladium
9	3120	15 silver - 85 palladium
10	3183	100 palladium
11	3187	90 palladium - 10 iridium
27	3354	85 platinum - 15 copper
26	3417	50 platinum - 50 palladium
12	3507	100 rhodium
13	3678	12 iridium - 88 platinum
14	3903	50 iridium - 50 rhodium
15	4110	60 iridium - 40 rhodium
16	4362	80 iridium - 20 rhodium
17	4443	100 molybdenum
18	4641	100 iridium
19*	4794	21 tantalum - 79 niobium
20	4956	100 rhenium
21*	5109	67 tantalum - 33 niobium
22*	5226	78 tantalum - 22 niobium
23	5361	100 tungsten
24*	5370	90 tantalum - 10 niobium
25*	5514	100 tantalum

* These codes have uncertain melting temperatures due to surface carburization.

- (1) Ref: WANL DWG 978D075, Wire Thermal Capsule
PDS 30058 Wire Spec
PDS 30059 Wire Spec
WANL DWG 910E085 Thermal Capsule Assembly

- (2) Numbers refer to weight percentages

(U) THERMAL CAPSULE SPECIFICATION

INDEX NO.

C.5.1

(CRD) XE-2 THERMAL CAPSULE DISTRIBUTION IN CORE (U)

PREPARED BY

R. Burghardt

APPROVED BY

R. M. Fitch 7/19/65

INDEX NO.

C.5.2

REFERENCE

(CRD) XE-2 THERMAL CAPSULE DISTRIBUTION IN THE FILLER STRIPS (U)

PREPARED BY

R. Burghardt 7/2/68

APPROVED BY

R. M. Cutler 7/2/68

INDEX NO.

C.5.3

C-40

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R.P.V. 7/31/68	KLR 7/31/68	

(U) INTRODUCTION (U)

(U) The purpose of this section is to describe the thermal performance of the XE-2 reactor. The information presented is:

1. A description of the thermal performance calculation method.
2. A summary of reactor test limits.
3. Steady State T-P (Chamber Temperature - Chamber Pressure) performance maps.
4. Typical performance data for maximum startup, maximum shutdown, and reactor emergency scram.

(U) In addition to illustrating the thermal performance of the XE-2 reactor, these data were also used as boundary conditions for detailed reactor component calculations which are presented in Section G, H, and I.

(U) This section is not intended to present thermal performance data for specific XE-2 test profiles. Such detailed data covering all XE-2 testing will be presented in the "XE-2 Test Prediction Report".

(U) INTRODUCTION (U)	INDEX NO.
	D

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68	

SECTION D

(U) THERMAL CYCLE PERFORMANCE TABLE OF CONTENTS (U)

<u>Index No.</u>		<u>Cross Reference</u> ⁽¹⁾ <u>Index No.</u>
*D.1		
D.1.1	(U) Thermal Performance Calculation Methods (U)	
D.1.2	(CRD) TNT Model of the XE-2 Reactor (10 sheets) (U)	
D.1.3	(U) TNT Calculational Uncertainties (U)	
D.2	(CRD) XE-2 Reactor Test Limits (3 sheets) (U)	
D.3	(U) Steady State T-P Performance Maps (2 sheets) (U)	
	Sheet 1 (U) Reactor Thermal Power (U)	
	Sheet 2 (U) Reflector Flow (U)	
	Sheet 3 (U) Core Flow (U)	
	Sheet 4 (U) Nozzle Chamber Flow (U)	
	Sheet 5 (CRD) Station 20 Core Unfueled Element Temperature (U)	
	Sheet 6 (CRD) Station 26 Core Unfueled Element Temperature (U)	
	Sheet 7 (CRD) Station 32 Core Unfueled Element Temperature (U)	
	Sheet 8 (CRD) Tie Rod Exit Material Temperature (U)	
	Sheet 9 (U) Core Inlet Plenum Temperature (U)	
	Sheet 10 (U) Shield Dome End Plenum Temperature (U)	
	Sheet 11 (U) Reflector Inlet Plenum Temperature (U)	
	Sheet 12 (U) Reflector Inlet Plenum Pressure (U)	
	Sheet 13 (U) Core Inlet Plenum Pressure (U)	
	Sheet 14 (U) Reflector Pressure Drop (U)	
	Sheet 15 (U) Core Pressure Drop (U)	
	Sheet 16 (U) Reflector Inlet/Core Exit Pressure Drop (U)	
	Sheet 17 (U) Control Drum Position (U)	
	Sheet 18 (CRD) Fuel Exit Gas Temperature (U)	
	Sheet 19 (U) Seal Exit Gas Temperature (U)	
	Sheet 20 (U) Seal Exit Flow Rate (U)	
D.4	(U) XE-2 Reactor Transient Performance (U)	
D.4.1	(U) 150°R/Sec Startup (U)	
	Sheet 1 (U) Power and Flow Rate (U)	
	Sheet 2 (CRD) Core Sensor Chamber and Fuel Exit Gas Temperature (U)	
	Sheet 3 (CRD) Plenum and Average Tie Rod Exit Material Temperature (U)	
	Sheet 4 (U) Plenum Pressures (U)	
	Sheet 5 (U) Component Pressure Drops (U)	
	Sheet 6 (U) Control Drum Position (U)	
	Sheet 7 (U) Reactivity Feedback (U)	
D.4.2	(U) 150°R/Sec Shutdown (U)	
	Sheet 1 (U) Power and Flow Rate (U)	
	Sheet 2 (CRD) Core Sensor Chamber and Fuel Exit Gas Temperature (U)	
	Sheet 3 (CRD) Plenum and Average Tie Rod Exit Material Temperature (U)	
	Sheet 4 (U) Plenum Pressures (U)	
	Sheet 5 (U) Component Pressure Drops (U)	
	Sheet 6 (U) Control Drum Position (U)	
	Sheet 7 (U) Reactivity Feedback (U)	

*There are no data sheets corresponding to these index numbers

(1) Data sheet will be found under Index No. entered in this column.

(U) TABLE OF CONTENTS (U)	INDEX NO
	D

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68	

SECTION D

(U) THERMAL CYCLE PERFORMANCE TABLE OF CONTENTS (U)

<u>Index No.</u>	<u>Cross Reference (1)</u> <u>Index No.</u>
* D,4,3	(U) XE-2 Emergency Shutdown (U)
	Sheet 1 (U) Power and Flow Rate (U)
	Sheet 2 (CRD) Core Sensor, Chamber and Tie Rod Material and Fuel Exit Gas Temperature (U)
	Sheet 3 (U) Plenum Temperatures (U)
	Sheet 4 (U) Plenum Pressures (U)
	Sheet 5 (U) Component Pressure Drops (U)
	Sheet 6 (U) Reactivity Feedback (U)
	Sheet 7 (U) Assumed Nozzle Torus Pressure Demand as a Function of Measured Chamber Temperature (U)
* D,4,4	(U) Pulse Cooldown (U)
	Sheet 1 (CRD) XE-2 Typical Pulse Cooldown Summary (U)
	Sheet 2 (U) XE-2 Decay Power (U)

*There are no data sheets corresponding to these index numbers.

(1) Data sheet will be found under Index No. entered in this column.

(U) TABLE OF CONTENTS (U)	INDEX NO.
	D

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	K L R 7/31/68	

- (U) This section presents the thermal performance calculation method by describing the TNT (Thermal and Nuclear Transient) code, the TNT model of the XE-2 reactor, and the TNT calculation uncertainties. The TNT code was used to generate all steady state and transient data that are presented in this section.
- (U) In general, TNT is used for (1) the thermal steady state and transient performance calculations required to define the boundary conditions for more detailed reactor component analysis, (2) test prediction calculations, and (3) the calculations that are required to develop emergency procedures for facility and reactor protection.
- (U) Previous reactor test data (A1, A2, A3, A4 and A5) has been used to modify both the TNT calculation procedure and the reactor model in order to improve the accuracy of TNT calculations.
- (U) The TNT computer program was written to obtain the thermal performance characteristics of NRX reactors during all phases of operation. Typical TNT calculations include normal startup and shutdown, steady state, cold flow transients, emergency shutdowns, continuous cooldown, and pulse cooldown.
- (U) The XE-2 model consists of the following channels:
- 1) Nozzle Tube
 - 2) Outer annulus (reflector)
 - 3) Outer reflector (reflector)
 - 4) Outer reflector tie bolt (reflector)
 - 5) Inner annulus (reflector)
 - 6) Inner reflector (reflector)
 - 7) Aluminum mockup shield and support plate
 - 8) Fuel element (core)
 - 9) Tie rod (core)
- (U) Inlet and exit loss coefficients are specified for each channel. Flow balancing is employed to attain the same overall pressure drop across the reflector channels and the core channels. Radiation heat transfer across all reflector annuli and between the core exit face and the nozzle is considered. Axial conduction is considered for all reflector components and fuel elements. The tie rod representation consists of five radial nodes at each axial station.
- (U) Steady state fluid flow momentum and energy equations are employed. Mass storage of coolant in the reactor is neglected. The actual calculation method can be considered as a series of short steady state calculations of the coolant flow conditions. With these coolant conditions the component temperature changes are calculated. Either the inlet coolant pressure or flow rate can be specified. The nozzle choked flow compatibility is always satisfied. Choking in the nozzle tubes and core orifices is also considered.
- (U) Hydrogen, nitrogen, and helium properties can be used. For each propellant a different thermodynamic property deck is required. The reactor material thermal properties are specified as a function of temperature.
- (U) The nuclear part of the TNT code is capable of simulating the following types of reactor operation:
- 1) Specified power profile
 - 2) Fixed control drums
 - 3) Control drums scrambled
- (U) Six delayed neutron groups are used to evaluate delayed fission power. The timewise power distribution of each reactor component is calculated as a function of the fission power history. At time of scram the fission product decay power may be calculated for times up to approximately one million seconds after scram.

(U) THERMAL PERFORMANCE CALCULATION METHOD (U)	INDEX NO.
	D.1.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR T/31/68	

(U) The TNT code simulates the reactor by nine channel types which are grouped into the following four sections:

- 1) Nozzle tube (one channel)
- 2) Reflector (five channels in parallel)
- 3) Shield and support plate (one channel)
- 4) Core (two channels in parallel)

The coolant flow passes through the reactor in the above sequence from nozzle manifold to nozzle chamber. This section will describe the input to the TNT code necessary to simulate the XE-1 reactor using the nine channel model.

(U) 1) Nozzle Tube

(U) The nozzle tube channels describe the flow passage from the nozzle manifold to the reflector inlet. The major source of heat input is convection from the core exhaust flow. Thermal radiation from the core exit face is a secondary source but is considered.

(U) The following table defines the general nozzle geometry and calculation constants used by TNT:

Number of coolant tubes	=	186
Wall thickness of each tube	=	0.014 in.
Inlet loss coefficient	=	2.4
Exit loss coefficient	=	0.5
Hot side heat transfer area multiplication factor	=	0.88
Friction pressure drop multiplication factor	=	1.11
Nozzle throat area (hot gas side)	=	58.195 in ²
Nozzle hot side choked flow coefficient at design condition		

$$\frac{W \sqrt{T}}{P} = 7.95 \frac{\text{in}^2 \text{ } \sigma_R^{1/2}}{\text{sec}}$$

(U) TNT MODEL OF THE XE-2 REACTOR (U)	INDEX NO.
	D.1.2 Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>RPN</i> 7/31/68	<i>KLR</i> 7/31/68	

(U) The following table describes the nozzle tube (one of 186 tubes) geometry at each of the 22 tube stations used in the calculation:

	AR	DIST	DE	AF	AS	TK3
1	10.00	0	0.462	0.197	0	0.500
2	8.090	4.620	0.421	0.172	2.546	0.500
3	6.140	10.00	0.378	0.143	2.609	0.500
4	4.650	14.72	0.339	0.117	1.982	0.500
5	3.370	19.38	0.300	0.092	1.654	0.500
6	2.220	24.41	0.258	0.064	1.459	0.500
7	1.590	27.74	0.230	0.047	0.792	0.500
8	1.120	30.51	0.208	0.037	0.543	0.500
9	1.000	31.68	0.195	0.035	0.199	0.500
10	1.070	32.78	0.189	0.036	0.198	0.500
11	1.400	34.36	0.202	0.040	0.348	0.500
12	2.580	37.13	0.229	0.055	0.864	0.530
13	4.260	39.96	0.256	0.071	1.019	0.600
14	6.540	43.02	0.287	0.087	1.346	0.680
15	8.890	45.67	0.311	0.102	1.365	0.750
16	10.31	47.08	0.319	0.109	0.804	0.780
17	11.84	48.49	0.325	0.117	0.853	0.820
18	15.20	51.31	0.340	0.133	1.875	0.900
19	17.04	54.47	0.355	0.140	2.354	0.900
20	17.04	57.65	0.360	0.141	2.445	0.400
21	17.04	60.65	0.367	0.144	2.307	0.400
22	17.04	63.65	0.371	0.147	2.307	0.400

where,

AR = hot gas side area ratio (total flow area divided by nozzle throat area)

DIST = tube length measured from nozzle manifold (coolant inlet) (in.)

DE = hydraulic diameter of tube flow area (in.)

AF = tube flow area (in.²)

AS = hot gas side heat transfer area for each axial increment (in.²)

TK3 = equivalent thickness of stainless steel sleeve which forms outside surface of nozzle (in.)

(U) TNT MODEL OF THE XE-2 REACTOR (U)	INDEX NO.
	D.1.2 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	K R 7/31/68	

(U) The following table describes heat transfer constants as a function of tube length from the nozzle manifold.

	AR	DIST	RADN	CG	DK
1	10.00	0	0	0.0260	0.258
2	8.090	4.620	0	0.0263	0.275
3	6.140	10.00	0	0.0268	0.288
4	4.650	14.72	0	0.0271	0.318
5	3.370	19.38	0	0.0275	0.314
6	2.220	24.41	0	0.0270	0.332
7	1.590	27.74	0	0.0265	0.333
8	1.120	30.51	0	0.0261	0.355
9	1.000	31.68	0.090	0.0263	0.387
10	1.070	32.78	0.170	0.0273	0.395
11	1.400	34.36	0.170	0.0288	0.354
12	2.580	37.13	0.170	0.0317	0.301
13	4.260	39.96	0.180	0.0344	0.260
14	6.540	43.02	0.180	0.0373	0.209
15	8.890	45.67	0.180	0.0400	0.185
16	10.31	47.08	0.180	0.0414	0.161
17	11.84	48.49	0.290	0.0428	0.140
18	15.20	51.31	0.380	0.0470	0.140
19	17.04	54.47	0.300	0.0517	0.140
20	17.04	57.65	0.350	0.0565	0.140
21	17.04	60.65	0.450	0.0633	0.140
22	17.04	63.65	0.500	0.0763	0.140

where,

AR	=	hot gas side area ratio
DIST	=	tube length measured from nozzle manifold (coolant inlet) (in.)
RADN	=	form factor for radiant heat transfer from reactor exit surface to nozzle.
CG	=	multiplication factor of hot gas side heat transfer equation
DK	=	thermal conduction distance from nozzle hot wall to cold wall at each axial location (in.)

(U) 2) Reflector

(CRD) The reflector is simulated by the following five components and channels.

<u>Reflector Component</u>	<u>Description</u>
Pressure vessel	That part of the pressure vessel located next to the outer reflector
Outer Reflector	All material within the borders of the outer reflector except the tie bolts. (includes drums)
Tie Bolt	Tie bolts only
Inner Reflector	All material within the boundaries of the inner reflector
Seal Segments and filler	All material between the inner reflector and the pyrographite insulation surrounding the core

(CRD) TNT MODEL OF THE XE-2 REACTOR (U)	INDEX NO
	D.1.2 Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KL 8/1/68	

Reflector Channel	Description
Outer Annulus	The flow passage between the outer reflector and pressure vessel
Outer Reflector	An equivalent channel type composed of all outer reflector flow passages except the tie bolt channels
Tie Bolt	The tie bolt channels
Inner Annulus	The flow passage between the inner and outer reflectors
Inner Reflector	The inner reflector flow passages

(CRD) The geometry of each equivalent reflector channel type is specified by the following table:

Channel Designation	Outer Annulus	Outer Reflector	Tie Bolt	Inner Annulus	Inner Reflector
No. of equivalent channels	1	1677	36	1	144
Hydraulic diameter (inches)	0.412	0.18408	0.25	0.1764	0.3125
Channel length (inches)	53.5	53.5	53.5	53.5	53.5
Flow area per channel (in ²)	32.06	0.0266	0.04906	11.12	0.07666
Heat transfer area per channel (in ²)	16653.	30.92	41.98	13470.	52.50
*Inlet loss coefficient	-1.5	-6.0	-1.5	-25.8	-1.84
*Exit loss coefficient	-81.0	-6.0	0.2	-3.71	-0.7

* A negative loss coefficient defines a pressure drop

(CRD) The following table describes the equivalent weights, the materials (required to define heat capacity and thermal conductivity), and the sizes of the five reflector components:

Reflector Component	Weight (lb)	Material	Average Inside Radius (in.)	Average Outside Radius (in.)
Pressure Vessel	751	Aluminum	24.886	25.8
Outer Reflector	2108	Beryllium	20.09	24.68
Tie Bolt	35	Titanium	----	----
Inner Reflector	865	Graphite	18.39	20.0018
Seal Segments and Filler Blocks	224	Graphite	17.86	18.35

(CRD) TNT MODEL OF THE XE-2 REACTOR (U)	INDEX NO.
	D.1.2 Sheet 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68	

(CRD) The following table defines the thermal radiation constants associated with the reflector components:

Radiation form factor between graphite sleeve and graphite reflector	=	0.7
Radiation form factor between graphite reflector and beryllium reflector	=	0.7
Radiation form factor between beryllium reflector and pressure vessel	=	0.7
Radiation form factor between pressure vessel and space	=	0.7
Fraction of power generated in graphite sleeve filler strips outside core pyrotils and seal segments to power generated in region between core pyrotils and inner annulus	=	0.05

(CRD) 3) Shield and Support Plate

(U) The aluminum shield first and second pass and support plate are simulated by 3 equivalent channels, all have the same hydraulic diameter.

Section No.	Description	Length (in.)	Weight (lbs.)	Hydraulic Diameter (in.)	Outside Radius of Material (in.)
1	Shield First Pass	12.5	2900	0.5	1.030
2	Shield Second Pass	15.0		0.5	0.865
3	Support Plate	5.0	325	0.5	0.836

Inlet and exit loss coefficient of the equivalent channel type = -0.8

(CRD) The power in the combined shield and support plate is given at each of 13 nodes along the length of the equivalent channel. The following table gives the axial power factor (normalized to an area equal to one) as a function of distance from the coolant entrance to the equivalent channel:

Distance From Coolant Entrance to Channel (in.)	Section	Axial Power Factor
1.25	Shield First Pass	0.882
3.75		0.441
6.25		0.221
8.75		0.110
11.25		0.055
13.75	Shield Second Pass	0.058
16.25		0.124
18.75		0.248
21.25		0.497
23.75		0.995
26.25	Support Plate	1.990
28.75		2.324
31.25		4.648

(CRD) TNT MODEL OF THE XE-2 REACTOR (U)	INDEX NO
	D.1.2 Sheet 5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/1/68	

(CRD) 4) Core

(CRD) The core is simulated by two average channels: a fuel channel and a tie rod channel. The following table defines the equivalent weights based on the principal component material.

<u>Component</u>	<u>Material</u>	<u>Weight (lbs)</u>
Fuel Elements	Graphite	1934
Unfueled elements, pyrographite and steel sleeves	Graphite	466
Tie rods (rods only)	Inconel - X	46

(CRD) The average fuel and tie rod channel geometries are defined in the following table:

<u>Channel Designation</u>	<u>Fuel</u>	<u>Tie Rod</u>
No. of equivalent channels	30096	289
Hydraulic diameter (in.)	0.096	0.116
Channel length (in.)	53.5	53.5
Exit Loss coefficient	+0.402	-1.92
Flow area of inlet orifice (in. ²)	0.000688	----

(U) The tie rod channel inlet loss coefficient and the pressure drop across the orifice at the core channel inlet are computed internal to the TNT code as follows:

Tie Rod Channel

$$\ln C_L = -.3425 \ln \frac{W_{TR}}{\mu} + 4.643$$

where

C_L = tie-rod channel inlet loss coefficient

W_{TR} = total tie-rod flow rate LB/SEC

μ = absolute viscosity LB/in.-SEC X 10^7

Core Channel

$$\frac{P_2}{P_o} = 1.00987 - 0.23283 FL + 1.38399 FL^4 - 6.34174 FL^5$$

$$FL = 6.212 \frac{W}{D_o^2 P_o} \sqrt{T_o}$$

(CRD) TNT MODEL OF THE XE-2 REACTOR (U)	INDEX NO
	D.1.2 Sheet 6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	KLR 7/31/68	

where

W = flow LB/SEC
 T_o = upstream total temperature $^{\circ}R$
 P_o = upstream total pressure PSIA
 A = flow area $IN.^2$
 D_o = orifice diameter in.
 P_2 = downstream static pressure PSIA

(CRD) The following table describes the material geometries used in TNT for the fuel and tie rod channel types:

		IN.
Outside radius of equivalent fuel element channel	=	0.112
Tie rod radius	=	0.055
Inside radius of steel sleeve (tie rod channel)	=	0.113
Outside radius of steel sleeve (tie rod channel)	=	0.1185
Inside radius of pyro-sleeve (tie rod channel)	=	0.1225
Outside radius of pyro-sleeve (tie rod channel)	=	0.178
Average outside radius of core	=	17.74
Average outside radius of pyro-tiles	=	17.86

(U) Thermal radiation constants associated with the core channels are:

Radiation form factor between tie rod and steel sleeve	=	0.3
Radiation form factor between steel sleeve and pyrographite sleeve	=	0.3
Radiation form factor between core and support plate	=	0.7

(CRD) TNT MODEL OF THE XE-2 REACTOR (U)	INDEX NO.
	D.1.2 Sheet 7

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>RPV 7/3/68</i>	<i>KLR 7/4/68</i>	

(CRD) The power generated in the fuel elements is given at each of 14 nodes along the length of the core. The following table gives the axial power factor (normalized to an area equal to one) as a function of the distance along the fuel channel from the dome end of the core:

<u>Distance from Dome End of Core (in.)</u>	<u>Axial Power Factor</u>
0	0.30
4.115	0.64
8.230	0.95
12.345	1.19
16.460	1.32
20.575	1.40
24.690	1.42
28.805	1.39
32.920	1.29
37.035	1.12
41.150	0.91
45.265	0.69
49.380	0.43
53.500	0.20

(U) This power distribution is also applied to the reflector. The diluent and hot bleed flow rates to the turbine are specified in TNT as a function of nozzle chamber temperature and pressure. These functions are shown in the figures of index number D. 1.2, Sheets 9 and 10, and were supplied by AGC.

(CRD) TNT MODEL OF THE XE-2 REACTOR (U)	INDEX NO.
	D. 1.2 Sheet 8

(U) XE-2 DILUENT FLOW RATE (U)

PREPARED BY

RPV 7/31/68

APPROVED BY

XLR 7/31/68

INDEX NO

D.1.2
SHEET 9

DATA SUPPLIED BY AGC

INDEX NO
D.1.2
SHEET 10

(U) XE-2 HOT BLEED FLOW RATE (U)

PREPARED BY

RPV 1/31/68

APPROVED BY

KSR 7/31/68

REFERENCE

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	KLR 7/31/68	

THIS PAGE UNCLASSIFIED

- (U) The TNT calculation uncertainties are based on the deviation of post-test TNT calculations from NRX/EST test data at 30 steady-state points on the operating map. The standard deviation of each parameter was calculated using the following equation:

$$\sigma = \sqrt{\frac{\sum_{i=1}^N \left(\frac{M-C}{M} \times 100 \right)^2}{N-1}}$$

where

σ = standard deviation in % of measured value
 M = measured value
 C = computed value
 N = number of points available for comparison

- (U) Since the XE-2 reflector design is similar to that of NRX-A5, reflector parameter uncertainties were also computed based on four NRX-A5 steady-state data points. These values agree with those computed from NRX/EST data.

The resulting TNT uncertainties are:

Parameter	3 σ Uncertainty, Percent Of Measured Value
Nozzle Inlet Pressure	$\pm 11.$
Nozzle Exit Pressure	± 6.1
Reflector Exit Pressure	± 4.5
Core Inlet Pressure	± 5.5
Core Exit Pressure (nozzle chamber)	± 7.1
Reflector Pressure Drop	$\pm 19.$
Core Pressure Drop	± 4.7
Reflector Inlet Temperature	$\pm 14.$
Reflector Exit Temperature	$\pm 25.$
Core Inlet Temperature	$\pm 21.$
Nozzle Chamber Temperature	± 1.3
Unfueled Element Temperatures:	
Station 20	$\pm 16.$
Station 26	± 6.6
Station 32	$\pm 13.$
Tie Rod Exit Temperature	$\pm 16.$

(U) TNT CALCULATIONAL UNCERTAINTIES (U)	INDEX NO.
	D. 1.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	XLR 7/31/68	

(CRD) XE-2 REACTOR TEST LIMITS (U)

TEST PARAMETERS (1, 2)	NUCLEAR EXPERIMENTS	FLOW TESTS	POWER TESTS	COOLDOWN AND EMERGENCY
(U) Fixed Power Factor	2 max.	2 max.	2 max.	----
(U) Floating Power Factor **	2 ($\frac{\text{measured}}{\text{demand}}$)	2 ($\frac{\text{measured}}{\text{demand}}$)	2 ($\frac{\text{measured}}{\text{demand}}$)	----
(U) Period **	0.25 sec. min.	0.25 sec. min.	0.25 sec. min.	----
(U) Average Drum Position	Equivalent to 2\$ shutdown margin min.	a) Equivalent to 2\$ shutdown margin, min. for GH ₂ tests b) 2\$ max. feedback for LH ₂	Equivalent to 2\$ shutdown margin, min.	----
(CRD) Sensor 26 Sensor Average Temperature (3)	800°R max. for air cooling	----	3945. max.	1400°R max. for nitrogen cooling
	645°R max. prior to poison wire removal -	----	----	800°R max. for air cooling
(CRD) Station 0.5 + 1.0 fuel Sensor Average Temperature	800°R max. for air cooling	----	----	800°R max. for air cooling
	900°R max. other coolants	----	----	900°R max. for other coolants
(CRD) Average Tie Rod Exit (4) Material Temperature *	1600°R max.	1200°R max.	1200°R max.	1600°R max.
(CRD) Lateral Support Spring Bracket Temp. (5) *	850°R max.	----	----	850°R max.
(CRD) Outer Reflector Tie Bolt Temperature (6) *	750°R max.	----	----	750°R max.
(U) Initial Outer Reflector Temperature *	----	540°R max.	540°R max.	----
(U) Rate of change (7) of avg. chamber temperature *	----	----	± 150 °R/sec.	± 300 °R/sec.
(U) Core Pressure Drop *	----	150 psid max.	150 psid max.	150 psid max.
(U) Reflector Inlet to Core Exit Pressure Drop *	----	225 psid max.	225 psid max.	225 psid max.
(U) Minimum Flow Rates	----	----	----	2 lb/sec LH ₂ 4 lb/sec LN ₂

* Stress Analysis XE-1, WANL-TME-1561.

** May be by-passed in excess of 100 MW during phase IV tests.

*** Acceptable only under emergency conditions. Not to exceed 900°R in any 3 second period.

(CRD) XE-2 REACTOR TEST LIMITS (U)

INDEX NO.

D.2
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	KLR/mk	

(U) NOTES: NUCLEAR EXPERIMENTS are those with powers up to 1 MW and no flow except as required by limits.

FLOW TESTS are the gas and liquid flow tests with very low power usually in the kilowatt range.

POWER TESTS are the ones with significant powers and flows such as power endurance, mapping, and bootstrap to medium power.

COOLDOWN AND EMERGENCY are the post power test conditions starting with scram of the drums.

(U) 1) These are operational limits

(U) 2) Additional limits exist for the nozzle, turbopump, and facility that are not presented in this table.

(U) 3) Station 26 Sensor Average Temperature and Temperature Limiter

These limits are based on the smallest practical margin above the 100 percent temperature set point to minimize corrosion and fission product release and maximize endurance capability. A 5 percent margin on the average of the 10 Station 26 sensor temperatures is considered the minimum practical for test observation. The limit is based on NRX-A3 results which are supported by analysis.

(U) 4) Average Tie Rod Material Temperature

The tie rod temperature limit is based on monitoring the average exit material temperature and relating this to stress limits for the maximum permitted core pressure differential (150 psid). Individual tie rod temperatures may be 300°R higher than the average.

(U) 5) Lateral Support Spring Bracket Temperature

This limit applies to the aluminum parts of the lateral system.

(U) 6) Previous cooldown experience indicates that the core temperature limits will be exceeded before the outer reflector limit of 750°R maximum or the support plate limit of 830°R maximum is exceeded.

(CRD) 7) Rate of Change of Average Chamber Temperature

Rapid changes in chamber temperature are accompanied by severe transient thermal stresses in the support blocks. The positive ramp causes high seat stresses and the negative ramp high web stresses in all support blocks. Both positive and negative ramps tend to cause high tangential stresses in the irregular blocks due to the temporary lags in the lobes of the peripheral blocks partial elements. The - 300°R/sec emergency shutdown would probably cause axial cracks in the lobes of the peripheral blocks under the unfueled elements. Immediate block failure following cracking should not occur, but subsequent deterioration would occur due to corrosion.

(CRD) XE-2 REACTOR TEST LIMITS (U)	INDEX NO.
	D.2 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>RPV 7/3/68</i>	<i>KLR 7/31/68</i>

(CRD) XE-2 PERFORMANCE LIMITS MAP (U)	INDEX NO.
	D. 2 Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/3/68	KLR 7/31/68	

(U) STEADY STATE T-P (CHAMBER TEMPERATURE-CHAMBER PRESSURE) PERFORMANCE MAPS (U)

The mapping predictions were based on steady state operation and all in-core temperatures and tie rod material temperatures are for average conditions (radial power factor of 1). All calculations except seal exit temperature and flow rate were performed with the TNT code as described in section D.1.2. The seal exit temperature and flow rate maps were calculated with the TRACK code.

(U) STEADY STATE T-P PERFORMANCE MAPS (U)	INDEX NO.
	D.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68

(U) XE-2 PREDICTED PERFORMANCE MAP - REACTOR POWER (U)	INDEX NO
	D.3 Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68

(U) XE-2 PREDICTED PERFORMANCE MAP - REFLECTOR FLOW (U)	INDEX NO.
	D.3 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>R.P.V. 7/31/68</i>	<i>K.L.R. 7/31/68</i>

(U) XE-2 PREDICTED PERFORMANCE MAP - CORE FLOW (U)	INDEX NO.
	D.3 Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/1/68	

THIS PAGE UNCLASSIFIED

(U) XE-2 PREDICTED PERFORMANCE MAP - NOZZLE CHAMBER FLOW (U)	INDEX NO
	D.3 Sheet 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	KLR 7/31/68

(CRD) XE-2 PREDICTED PERFORMANCE MAP - STATION 20 CORE UNFUELED ELEMENT TEMPERATURE (U)	INDEX NO.
	D.3
	Sheet 5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPR 7/31/64	KLR 7/21/64

(CRD) XE-2 PREDICTED PERFORMANCE MAP - STATION 26 CORE UNFUELED ELEMENT TEMPERATURE (U)	INDEX NO
	D.3 Sheet 6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KL 7/31/68

(CRD) XE-2 PREDICTED PERFORMANCE MAP - STATION 32 CORE UNFUELED ELEMENT TEMPERATURE (U)	INDEX NO
	D.3 Sheet 7

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLZ 7/31/68

(CRD) XE-2 PREDICTED PERFORMANCE MAP - TIE ROD EXIT MATERIAL TEMPERATURE (U)

INDEX NO

D.3
 Sheet 8

~~CONFIDENTIAL RESTRICTED DATA~~

Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	KLR 7/31/68	

THIS PAGE UNCLASSIFIED

(U) XE-2 PREDICTED PERFORMANCE MAP - CORE INLET TEMPERATURE (U)

INDEX NO

D.3
Sheet 9

~~CONFIDENTIAL RESTRICTED DATA~~

Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68

(U) XE-2 PREDICTED PERFORMANCE MAP - SHIELD DOME END PLENUM TEMPERATURE (U)	INDEX NO
	D.3 Sheet 10

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	KLR 7/31/68

(U) XE-2 PREDICTED PERFORMANCE MAP - REFLECTOR INLET TEMPERATURE (U)	INDEX NO.
	D.3 Sheet 11

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68

(U) XE-2 PREDICTED PERFORMANCE MAP - REFLECTOR INLET PRESSURE (U)	INDEX NO
	D.3 Sheet 12

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	KLR 7/31/68

(U) XE-2 PREDICTED PERFORMANCE MAP - CORE INLET PRESSURE (U)	INDEX NO.
	D.3 Sheet 13

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68

(U) XE-2 PREDICTED PERFORMANCE MAP - REFLECTOR PRESSURE DROP (U)	INDEX NO
	D.3 Sheet 14

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68

(U) XE-2 PREDICTED PERFORMANCE MAP - CORE PRESSURE DROP (U)

INDEX NO.

D.3
Sheet 15

REFERENCE

PREPARED BY

RPN 7/31/68

APPROVED BY

KLR 7/31/68

Astronuclear
Laboratory

(U) XE-2 PREDICTED PERFORMANCE MAP - REFLECTOR INLET/CORE EXIT PRESSURE DROP(U)

INDEX NO

D.3
Sheet 16

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RSK 7/31/68	KLR 7/31/68

(U) XE-2 PREDICTED PERFORMANCE MAP - CONTROL DRUM POSITION (U)	INDEX NO
	D.3 Sheet 17

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RYN 7/31/68	KLE 7/31/68

(CRD) XE-2 PREDICTED PERFORMANCE MAP - FUEL EXIT GAS TEMPERATURE (U)

INDEX NO

D.3
Sheet 18

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	MDW 7/27/68	KLR 7/31/68	

THIS PAGE UNCLASSIFIED

(U) XE-2 PREDICTED PERFORMANCE MAP - SEAL EXIT GAS TEMPERATURE (U)

INDEX NO

D.3
Sheet 19

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	MBW 7/29/68	KLR 7/31/68

(U) XE-2 PREDICTED PERFORMANCE MAP - SEAL EXIT FLOW RATE (U)	INDEX NO
	D.3 Sheet 20

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	XL 7/31/68	

(U) Thermal performance data for the following transients are presented in this section.

Index No.	
D.4.1	150°R/sec Startup
D.4.2	150°R/sec Shutdown
D.4.3	Emergency Shutdown
D.4.4	Pulse Cooldown

These calculations were made with the TNT digital code described in D.1.2. The results are shown here only to demonstrate expected maximum transient performance of the XE-2 reactor; the actual XE-2 test profiles will be specified in the XE-2 Test Specification and analyzed in the XE-2 Test Prediction Report.

(U) 150°R/sec Startup (U)

The flow rate for the first 13.5 seconds of the startup was estimated from NRX/EST data. The initial power is 1 MW and is then brought up on a 2.5 second period until the chamber temperature loop closes at 1100°R. From that point the chamber temperature and pressure follow the XE-2 normal operating line (see Figure D.2, Sheet 3) to design operating conditions.

(U) 150°R/sec Shutdown (U)

(U) The shutdown starts from design conditions and is performed by ramping chamber temperature at -150°F/sec following the normal operating line. The scram takes place at a chamber temperature of 2150°R.

(U) Emergency Shutdown (U)

(U) The emergency shutdown assumes that the demand nozzle torus pressure is controlled by chamber temperature as shown in Figure D.4.3, Sheet 7. Since the torus pressure (flow rate) is controlled by chamber temperature, this method is independent of run-time effects on decay powers. The method consists of the following steps:

- 1) Scram
- 2) Control nozzle torus pressure (see D.4.3, Sheet 7 where demand nozzle torus pressure is derived from measured chamber temperature).
- 3) Switch to Gaseous Flow - Initiate gaseous H₂ or He flow as soon after scram as the facility permits. Gaseous He would be used in case of fire.
- 4) Switch to liquid N₂ after the pipelines and components have warmed up (above the freezing temperature of nitrogen) and the flow requirements have dropped so that liquid N₂ can satisfy the cooling requirements.

(U) A shutdown from full power after a 20-minute run with this control mode is shown in Figures D.4.3, Sheets 1 to 6 for steps 1 and 2. This analysis assumes a step change in nozzle torus pressure upon scram (the flow tail-off depends on the dynamics of the system which are not known at this time). This shutdown produces a maximum absolute cooldown rate of chamber temperature of 190°R/sec, and the feedback reactivity does not rise above -0.5\$.

(U) XE-2 REACTOR TRANSIENT PERFORMANCE (U)	INDEX NO.
	D.4 Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	KPV 7/31/68	KLR 7/31/68	

(U) Pulse Cooldown (U)

(U) A summary of a typical XE-2 pulse cooldown and a decay power profile is given in D.4.4 for the following conditions:

- 1) During the initial period after scram chamber temperature is demanded as

$$[T_c]_D = (T_o - 1000) e^{-t/22} + 1000$$

where $T_o = T_c$ at time of scram ($^{\circ}\text{R}$) (1600 $^{\circ}\text{R}$ assumed)

$t =$ Time after scram (sec)

$[T_c]_D =$ Demand chamber temperature ($^{\circ}\text{R}$)

until chamber pressure is 30 psia. Then pulse cooling is initiated with nozzle torus inlet pressure of 35 psia for all pulses.

- 2) Pulses are terminated when $T_c \leq 800^{\circ}\text{R}$.
- 3) LH_2 is used for all pulses.
- 4) Engine back pressure is assumed to be 7.0 psia.
- 5) Reactor had been run for six minutes at full power.

(U) XE-2 REACTOR TRANSIENT PERFORMANCE (U)	INDEX NO.
	D.4 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>RPR 7/3/68</i>	<i>KLR 7/3/68</i>

(U) XE-2 150°K/SEC STARTUP - POWER AND FLOW RATE (U)	INDEX NO
	D.4.1 Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>RPN 7/31/68</i>	<i>KLR 7/8/68</i>

(CRD) XE-2 150°R/SEC STARTUP - CORE SENSOR AND CHAMBER TEMPERATURES (U)

INDEX NO.

D. 4. 1
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/1/68

(CRD) XE-2 150°R/SEC STARTUP - PLENUM AND AVERAGE TIE ROD EXIT MATERIAL TEMPERATURE (U)

INDEX NO

D. 4. 1
Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68

(U) XE-2 150°R/SEC STARTUP - PLENUM PRESSURES (U)	INDEX NO
	D. 4. 1 Sheet 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>RPV 7/3/68</i>	<i>KLR 7/1/68</i>

(U) XE-2 150°R/SEC STARTUP - COMPONENT PRESSURE DROPS (U)	INDEX NO
	D.4.1 Sheet 5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>RPV 7/3/68</i>	<i>KLR 7/1/68</i>

(U) XE-2 150°R/SEC STARTUP - CONTROL DRUM POSITION (U)	INDEX NO
	D. 4. 1 Sheet 6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68

(U) XE-2 150°/SEC STARTUP - REACTIVITY FEEDBACK (U)	INDEX NO
	D.4.1 Sheet 7

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	KLR 7/31/68	

THIS PAGE UNCLASSIFIED

(U) XE-2 150°R/SEC SHUTDOWN - POWER AND FLOW RATE (U)	INDEX NO
	D.4.2 Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>RPV 7/3/68</i>	<i>KLR 7/3/68</i>

(CRD) XE-2 150°R/SEC SHUTDOWN CORE SENSOR, CHAMBER AND FUEL EXIT GAS TEMPERATURE (U)

INDEX NO

D.4.2
SHEET 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	KLR 7/31/68

(CRD) XE-2 150°R/SEC SHUTDOWN - PLENUM AND AVERAGE TIE ROD MATERIAL TEMPERATURES (U)	INDEX NO
	D. 4. 2 Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	KLR 7/31/68	

THIS PAGE UNCLASSIFIED

(U) XE-2 150°R/SEC SHUTDOWN - PLENUM PRESSURES (U)	INDEX NO.
	D. 4. 2 Sheet 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLK 7/31/68

(U) XE-2 150°R/SEC SHUTDOWN - COMPONENT PRESSURE DROPS (U)

INDEX NO

D. 4. 2
Sheet 5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/3/68	KLR 7/1/68

(U) XE-2 150°R/SEC SHUTDOWN - CONTROL DRUM POSITION (U)	INDEX NO
	D.4.2 Sheet 6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>RPV 7/31/68</i>	<i>KLR 7/31/68</i>

(U) XE-2 150°R/SEC SHUTDOWN - REACTIVITY FEEDBACK (U)	INDEX NO
	D-4.2 Sheet 7

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68

(U) XE-2 EMERGENCY SHUTDOWN - POWER AND FLOW RATE (U)	INDEX NO
	D.4.3 Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/3/68	KLR 7/31/68

(CRD) XE-2 EMERGENCY SHUTDOWN CORE SENSOR, CHAMBER, TIE ROD MATERIAL AND FUEL EXIT GAS TEMPERATURE (U)

INDEX NO

D.4.3
SHEET 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68	

THIS PAGE UNCLASSIFIED

(U) XE-2 EMERGENCY SHUTDOWN - PLENUM TEMPERATURES (U)	INDEX NO
	D.4.3 Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	KLF 7/31/68

(U) XE-2 EMERGENCY SHUTDOWN - PLENUM PRESSURES (U)	INDEX NO
	D. 4. 3 Sheet 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPV 7/31/68	KLR 7/1/68

(U) XE-2 EMERGENCY SHUTDOWN - COMPONENT PRESSURE DROPS (U)	INDEX NO
	D.4.3 Sheet 5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68

(U) XE-2 EMERGENCY SHUTDOWN - REACTIVITY FEEDBACK (U)	INDEX NO
	D. 4. 3 Sheet 6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	RPN 7/31/68	KLR 7/31/68

(U) ASSUMED NOZZLE TORUS PRESSURE DEMAND AS A FUNCTION OF MEASURED CHAMBER TEMPERATURE (U)	INDEX NO.
	D. 4. 3 Sheet 7

REFERENCE

Astronuclear
Laboratory

Time After Scram, Seconds	Pulse No.	LH2 Usage, Lb _M	Flow On Interval, Seconds	Flow Off Interval, Seconds	Average Pulse Flow, Lb/Sec.	Average Chamber Temp., °R	At Start of Interval				
							Fueled Element, Station 1 Temp., °R	Unfueled Element Station 26 Temp., °R	Maximum Core Temp., °R	Maximum Tie Rod Temp., °R	Maximum Reflector Temp., °R
0	1	685	115	---	5.95	1177	259	1103	1726	610	208
115	--	---	---	63	----	----	162	473	841	542	238
178	2	236	50	---	4.71	1185	736	1352*	1383	1272	447
228	--	---	---	120	----	----	128	335	895	552	218
348	3	220	46	---	4.79	1144	796	1359*	1376	1322	463
394	--	---	---	200	----	----	128	263	836	502	187
594	4	190	40	---	4.75	1133	842	1352*	1367	1328	464
634	--	---	---	327	----	----	119	233	911	579	199
961	5	182	39	---	4.66	1148	892	1359*	1370	1342	483
1000	--	---	---	483	----	----	113	212	936	611	208
1483	6	174	37	---	4.70	1126	960*	1296	1313	1284	477
1520	--	---	---	575	----	----	108	197	919	614	207
2095	7	155	32	---	4.84	1031	956*	1161	1172	1153	433
2127	--	---	---	790	----	----	104	204	892	622	191
2917	8	162	33	---	4.90	994	952*	1115	1122	1110	423
2950	--	---	---	1088	----	----	114	205	847	574	167
4038	9	149	30	---	4.95	963	952*	1071	1077	1068	416
4068	--	---	---	1484	----	----	117	236	870	620	189
5552	10	145	28	---	5.18	944	950*	1043	1048	1042	429
5580	--	---	---	2039	----	----	116	227	844	595	233
7619	11	148	28	---	5.26	907	950*	1010	1016	1011	458
7647	--	---	---	2937	----	----	112	199	785	544	261
10584	12	137	26	---	5.26	887	950*	976	986	982	489
10610	--	---	---	4282	----	----	121	242	807	588	302
14892	13	135	26	---	5.20	882	950*	960	972	968	544
14918	--	---	---	6932	----	----	127	247	804	597	357
21850	14	132	26	---	5.08	882	950*	949	963	959	617
21876	--	---	---	12510	----	----	140	267	814	624	433
34386	15	145	32	---	4.54	889	950*	947	958	955	703
34418	--	---	---	14028	----	----	145	293	795	623	458
48446	Reactor Power		15 kw								
Total LH2 Usage		2995									

* Parameter Limit which initiated pulse flow.

(CRD) XE-2 TYPICAL PULSE COOLDOWN SUMMARY (U)

PREPARED BY

RPV 7/31/68

APPROVED BY

KLR 7/31/68

INDEX NO.

D-4.4
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>RPV 7/31/68</i>	<i>KLR 7/31/68</i>	

THIS PAGE UNCLASSIFIED

(U) XE-2 DECAY POWER (U)	INDEX NO
	D. 4. 4 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>P. Rittenberger 7/29/68</i>	<i>D. M. G. 1/1/68</i>	

SECTION E

This section presents data pertinent to the nuclear analysis of the XE-2 reactor. Seven major subsections are covered, as indicated in the Table of Contents.

A concise description of computer codes used in WANL nuclear calculations is given. One-and-two dimensional nuclear models are described in terms of region volumes, atom densities, and masses. Reactor characteristics are described in detail for both the ambient temperature condition and the full power condition.

One subsection covers the reactivity analysis of the XE-2 reactor and the specification of the shim inventory. Subsequent sections describe the shipping anticriticality system and list pertinent kinetics data, control drum worths, and operating reactivity changes. Finally, axial and radial power predictions are presented.

(U) INTRODUCTION (U)	INDEX NO.
	E

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>R. Rittenberger 7/29/66</i>	<i>D.M. Galt 7/29/66</i>	

SECTION E

XE-2
NUCLEAR DATA
TABLE OF CONTENTS

INDEX NO.

*E.1	(U)	Models	(U)
E.1.1	(U)	Standard Design Method (NSDM II) Computer Codes	(U)
E.1.2	(U)	Standard Design Method Flow Chart	(U)
E.1.3	(CRD)	XE-2 Configuration for Radiation and Nuclear Analysis at Room Temperature	(U)
E.1.4	(U)	Region Identification	(U)
E.1.5	(CRD)	Volumes by Detailed Region	(U)
E.1.6	(CRD)	Number of Components within Core by Radial Regions	(U)
E.1.7	(CRD)	"As Built" Weights by Core Radial Regions	(U)
E.1.8	(CRD)	Core Atom Densities and Bucklings for Room Temperature Radial Calculations	(U)
E.1.9	(CRD)	Atom Densities in Reflector Regions for Room Temperature Radial Calculations	(U)
*E.2		Limitations	
E.2.1	(CRD)	Nuclear Data Uncertainties	(U)
*E.3		Reactivity Analysis	
E.3.1	(CRD)	XE-2 Reactivity Analysis	(U)
E.3.2	(CRD)	Core Reactivity Differences Between XE-2 and NRX-A5	(U)
E.3.3	(CRD)	Non-Core Reactivity Differences Between XE-2 and NRX-A5	(U)
E.3.4	(CRD)	Summary of XE-2 and NRX-A5 Reactivity Differences	(U)
*E.3.5		Experimental Reactivity Coefficient Data	
E.3.5.1	(CRD)	Average Reactivity Coefficients for Core Regions	(U)
E.3.5.2	(CRD)	Average Reactivity Coefficients for Non-Core Regions	(U)
E.3.6	(CRD)	Results of the XE-2 Fuel Reactivity Check Experiment	(U)
*E.4		Anticriticality System Data	
E.4.1	(CRD)	B ₄ C Poison Wire Data	(U)
E.4.2	(CRD)	Radial Worth of XE-2 B ₄ C Poison Wires	(U)
E.4.3	(CRD)	Poison Wire Loading Pattern for XE-2	(U)
E.4.4	(U)	Predicted XE-2 Reactivity at Room Temperature	(U)

*There are no data pages corresponding to these index numbers.

(U) TABLE OF CONTENTS (U)	INDEX NO.
	E

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>R. Rittenberg 7/29/68</i>	<i>D. M. Kutcher 7/24/68</i>	

SECTION E

(Continued)

INDEX NO.

*E.5		Control and Kinetics Data	
E.5.1	(U)	Differential Single Control Drum Worth	(U)
E.5.2	(U)	Integral Control Drum Bank Worth	(U)
E.5.3	(U)	Delayed Neutron Data	(U)
E.5.4	(U)	Reactor Stable Period Versus Reactivity Insertion	(U)
*E.6		Operating Reactivity Changes	
E.6.1	(CRD)	Parameters for COHOT Reactivity Analysis	(U)
E.6.2	(CRD)	Iso-reactivity Feedback Map for Steady State Operation	(U)
*E.7		Operating Power Distribution	
E.7.1	(CRD)	Power Perturbation Adjacent to Unfueled Central Elements	(CRD)
E.7.2	(CRD)	Correlation Factors to Account for the Conduction of Heat from the Unfueled Element to Fueled Element	(CRD)
E.7.3	(CRD)	Midplane Power Distribution Correction for R-Z Non-Separability	(U)
E.7.4	(CRD)	Increase in Peripheral Fission Density due to the Removal of the Code 32 Fuel Elements	(CRD)
E.7.5	(CRD)	Gamma and Neutron Heating Rate Versus Radial Position	(U)
E.7.6	(CRD)	Effect of Gamma and Neutron Heating on Radial Power Distribution	(U)
E.7.7	(CRD)	Operating Channel Power Factors for a 115° Drum Bank Position (5 Sheets)	(U)
E.7.8	(CRD)	Calculated Average Element Power Factors at 100 Percent Power and Flow	(U)
E.7.9	(CRD)	Predicted Power Factor for Operation at Full Power, Channel Traverse 00F8 to J4M18	(CRD)
E.7.10	(CRD)	Predicted Power Factors for Operation at Full Power, Channel Traverse 00F9 to J5K18	(CRD)
E.7.11	(CRD)	Predicted Power Factors for Operation at Full Power, Channel Traverse 00F10 to J8D18	(CRD)
E.7.12	(CRD)	Predicted Power Factors for Operation at Full Power, Channel Traverse 00F12 to J9T18	(CRD)
E.7.13	(CRD)	Coolant Channel 10 Power Factors at 100 Percent Power Versus Drum Bank Position	(CRD)
E.7.14	(CRD)	Predicted Axial Power Distribution at 100 Percent Power and Flow	(U)

*There are no data pages corresponding to these index numbers.

(CRD) TABLE OF CONTENTS (U)	INDEX NO
	E

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>R. Littleberry - 7/29/68</i>	<i>Phil M. Linton - 7/29/68</i>	

THIS PAGE UNCLASSIFIED
NUCLEAR COMPUTER CODES

Listed below are the computer codes on which the nuclear standard design method (NSDM) is based.

A generalized flow chart appears on E.1.2. Depending on the type of calculation performed, the buckling and/or atom densities are entered either in the space-dependent neutron transport codes (ANISN, EXTERMINATOR, and ODD-K) or in the cross section code NSDM-3.

<u>Code</u>	<u>Description</u>	<u>Reference</u>
To Generate Nuclear Constants		
GAM	Calculates few group epithermal constants	GA 1850
TNS	Calculates few group thermal constants	WANL-TME-263
QUERY	Calculates resonance integrals	CEND-94
NSDM-3	Linkage of GAM-QUERY-TNS (See E.1.1.2)	WANL-TME-1091
To obtain Energy Spectra		
ANISN	Uses constants generated by GAM-QUERY-TNS to calculate fluxes and currents	K-1693
ANISIG	Uses ANISN output to yield flux and current input to SPECTRA for iterative spectrum weighting of nuclear constants	
SPECTRA	Stores fine group ANISIG spectra on magnetic tape	WANL-TME-1091
To Make Survey Calculations		
ANISN	One-dimensional transport theory code	K-1693
AIM-5	One-dimensional diffusion theory code	NAA-SR-4694
For Detailed Analysis		
ODD-K	Two-dimensional transport theory code	WANL-PR(LL)-010 - Vol. 6
PFENCE	Calculates individual channel power factors	WANL-TME-1091
COHOT	Calculates cold-to-hot reactivity change	WANL-TME-936
EXTERMINATOR	Two-dimensional diffusion theory code	ORNL-TM-842
R-101	Forward solution to nuclear kinetics equation	ANL-6132
R-102	Inverse solution to nuclear kinetics equation	ANL-6132

(U) STANDARD DESIGN METHOD (NSDM II) COMPUTER CODES (U)	INDEX NO.
	E.1.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>R. Pittenger 7/29/68</i>	<i>John G. Johnson 7/2/68</i>	

THIS PAGE UNCLASSIFIED

ABBREVIATIONS: f: FAST GROUPS
th: THERMAL GROUPS
"M" & "N" LIMITED BY COMPUTER CORE STORAGE

612128-308

(U) STANDARD DESIGN METHOD FLOW CHART (U)	INDEX NO.
	E. 1.2

REFERENCE

SEE FIGURE E.1.2, SHEET 2 FOR REGION IDENTIFICATION

- NOTE: 1. DRAWING NOT TO SCALE
2. ALL DIMENSIONS ARE IN CENTIMETERS

(CRD) XE-2 CONFIGURATION FOR RADIATION AND NUCLEAR ANALYSIS AT ROOM TEMPERATURE (U)

PREPARED BY

R. R. Thompson 7/29/62

APPROVED BY

D. M. G. L. L.

INDEX NO.

E.1.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Rittenberger 7/29/63	DM Lutch 7/31/63	

THIS PAGE UNCLASSIFIED

Region Number	Region Descriptive Name
1	Core Support Block & Fuel Element Tip
2 - 25	Core
26	Filler Strip
27	Nozzle End Lateral Support
28	Lateral Support
29	Nozzle End Beryllium Reflector
30A	Control Vane Annulus (Not Shown)
30B	Beryllium Reflector, Outside Vane Annulus
31	Cluster Plate
32	Aluminum Support Plate
33	Lateral Support-Dome End
34	Dome End Beryllium Reflector
35	Gap Between Pressure Vessel and Outer Reflector
36	Pressure Vessel
37	Dome End Support Ring
38	Drive Shaft
39	Plenum Between Core Support Plate and Shield
40	Aluminum Shield - Central Region
41	Aluminum Shield With Drum Shafts
42	Aluminum Shield - Outer Region
43	Hydrogen Plenum - Dome End - Between Shield and Pressure Vessel
44	Plenum Between Shield and Pressure Vessel With Drum Shafts
45	Pressure Vessel - Actuator Shaft
46	Dome End Pressure Vessel
47	Filler Block

(U) REGION IDENTIFICATION (U)	INDEX NO
	E. 1. 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>R. Rittenberg</i>	<i>J. M. C. 7/2/54</i>	

Region ⁽¹⁾	Volume ⁽²⁾	Region ⁽¹⁾	Volume ⁽²⁾	Region ⁽¹⁾	Volume ⁽²⁾
1	49,761.6	17	7,660.2	32	77,134.5
2	168,847.9	18	21,106.0	33	34,783.0
3	38,291.1	19	4,786.4	34	5,320.9
4	17,415.0	20	2,176.8	35	9,106.0
5	20,427.8	21	2,553.4	36	180,568.4
6	158,294.9	22	21,106.0	37	19,688.0
7	35,897.9	23	4,786.4	38	65,308.4
8	16,326.2	24	2,176.8	39	101,958.6
9	19,150.5	25	2,553.4	40	331,226.0
10	105,529.9	26	48,603.2	41	64,617.7
11	23,932.0	27	10,832.3	42	22,810.5
12	10,884.1	28	225,794.1	43	33,040.0
13	12,767.0	29	21,283.8	44	10,817.7
14	63,318.0	30A ⁽³⁾	3,688.1	45	8,160.0
15	14,359.1	30B ⁽⁴⁾	549,690.5	46	21,106.5
16	6,530.5	31	21,277.4	47	4,604.0

- (1) of E. 1.4
(2) Data in cm³
(3) Control vane annulus for use in (r, z) EXTERMINATOR problems
(4) Beryllium volume from EXTERMINATOR problems

(CRD) VOLUMES BY DETAILED REGION (U)	INDEX NO.
	E. 1.5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	E. Jurek 7/30/68	D. M. Gutch 7/3/68	

RADIAL REGION (OUTER RADIUS GIVEN IN CM)

		36.366	40.279	41.938	43.804	TOTAL
Region Identification		1	2	3	4	
FUEL ELEMENT						
Code	Manufacturer					
133	WNCO	0	0	0	114	114
179	WNCO	0	0	48	12	60
222	WNCO	0	6	30	0	36
256	Y-12	0	96	0	0	96
315	Y-12	0	78	0	0	78
366	Y-12	0	90	0	0	90
431	WNCO	437	6	0	0	443
	Y-12	661	6	0	0	667
TOTAL		1098	282	78	126	1584
UNFUELED ELEMENTS						
00 (1 hole TaC loaded)		36	6	0	0	42
01 (1 hole)		129	34	33	10	206
02 (multiholed)		22	8	9	2	41
03 (unfueled partial)		0	0	0	42	42
TOTAL		187	48	42	54	331
Number of Positive Shims		2	1	1	1	5

(1) See E.1.7, E.1.8 for core masses and atom densities.

(CRD) NUMBER OF COMPONENTS WITHIN CORE BY RADIAL REGION (U)	INDEX NO.
	E. 1.6

REFERENCE

MATERIAL WEIGHTS BY REGION, KG
(AT ROOM TEMPERATURE)

REGION IDENTIFICATION Radius, cm	2, 6, 10, 14, 18, 22 36.366	3, 7, 11, 15, 19, 23 40.279	4, 8, 12, 16, 20, 24 41.938	5, 9, 13, 17, 21, 25 43.804	TOTAL
<u>MATERIAL</u>					
Carbon					
Fueled Elements	581.652	151.466	42.166	68.444	843.728
Unfueled Elements	113.800	29.184	25.528	7.304	175.816
Pyrographite Sleeves	17.362	4.456	3.900	1.114	26.832
Positive Shims	0.023	0.011	0.011	0.011	0.056
Unfueled Partials	0.0	0.0	0.0	20.639	20.639
Total	712.837	185.117	71.605	97.512	1067.071
Uranium ⁽¹⁾	138.926	25.926	4.486	5.046	174.384
Niobium ⁽²⁾					
Fueled Bore	57.155	15.588	3.804	6.173	82.720
External	0.016	0.047	0.559	0.957	1.579
Unfueled Bore	1.385	0.357	0.316	0.090	2.148
External	4.078	1.056	0.939	0.903	6.976
Total	62.634	17.048	5.618	8.123	93.423
Tantalum	2.692	0.449	0.0	0.0	3.140
Stainless Steel ⁽³⁾	5.205	1.336	1.169	0.334	8.044
Inconel-718 ⁽⁴⁾	15.301	3.928	3.437	0.982	23.648
Hydrogen ⁽⁵⁾	0.0071	0.0019	0.0007	0.0010	0.0107
Molybdenum ⁽⁶⁾	3.957	0.982	0.268	0.465	5.672

(1) Uranium masses based on a 52 inch length.

(2) Niobium is reactivity weighted and includes both bore and external masses.

(3) Tube liner weights only; does not include orifice jets.

(4) Weight for entire length of tie rod.

(5) Hydrogen weight assumed to be 10 ppm of the total carbon weight.

(6) Molybdenum is reactivity weighted.

(CRD) AS-BUILT CORE MATERIAL WEIGHTS BY RADIAL REGION (U)

PREPARED BY

E. J. ...

APPROVED BY

D. M. ... 7/2/54

INDEX NO.

E. 1.7

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>James Lee</i> 7/14/54	<i>W. G. Adams</i> 7/14/54	

CORE ATOM DENSITIES 10^{24} ATOMS/CCCORE REGIONS⁽¹⁾

Element	2, 6, 10, 14, 18, 22	3, 7, 11, 15, 19, 23	4, 8, 12, 16, 20, 24	5, 9, 13, 17, 21, 25
Carbon	0.0651687	0.0746322	0.0634599	0.0736915
U235	0.0006043	0.0004973	0.0001892	0.0001815
U238	0.0000439	0.0000361	0.0000137	0.0000132
Niobium ⁽²⁾	0.0007477	0.0008969	0.0006647	0.0007966
Tantalum	0.0000163	0.0000120	0.0000000	0.0000000
Iron	0.0001225	0.0001386	0.0002667	0.0000650
Nickel	0.0001378	0.0001559	0.0003000	0.0000731
Chromium	0.0000742	0.0000840	0.0001616	0.0000394
Molybdenum	0.0000453	0.0000495	0.0000297	0.0000440
Hydrogen	0.0000078	0.0000089	0.0000076	0.0000088

Bucklings

Radial Buckling $0.0010076 \text{ cm}^{-2}$ Axial Buckling 0.000450 cm^{-2}

(1) See E.1.3 for region definition.

(2) Reactivity weighted.

(CRD) CORE ATOM DENSITIES AND BUCKLINGS FOR USE IN
RADIAL CALCULATIONS AT ROOM TEMPERATURE

INDEX NO.

E.1.8

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Rittenberger 7/30/68	R. M. Litchman 7/3/68	

<u>Region-Element</u>	<u>Region Outer Radius</u>	<u>Number Density</u> <u>10²⁴ Atoms per cc</u>
Filler Strip		
Carbon	45.244 cm	0.088592
Lateral Support	50.966 cm	
Carbon		0.063029
Iron		0.000399
Nickel		0.000051
Chromium		0.000114
Aluminum		0.000839
Silicon		0.000424
Oxygen		0.000849
Beryllium Reflector ⁽¹⁾ (including Control Drums)	62.699 cm	
Beryllium		0.110163
Aluminum		0.000798

(1) When a control vane is used in the reflector, these atom densities must be increased by the ratio of:

$$\left(\frac{\text{Reflector Volume}}{\text{Reflector Volume} - \text{Vane Volume}} \right).$$

(CRD) ATOM DENSITIES IN REFLECTOR REGIONS FOR USE IN RADIAL CALCULATIONS AT ROOM TEMPERATURE	INDEX NO.
	E. 1. 9

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	P. J. Spence 7/30/68	DeMott 7/3/68	

XE-2 NUCLEAR UNCERTAINTIES

A. Reactivity Data

Uncertainties are listed along with the applicable data.

- 1) The reactivity at room temperature is assigned a $\pm 10^\circ$ or $\pm 76\mu$ (3 σ) uncertainty.
- 2) The drum span of the reactor (8.2) is known to ± 0.2 (3 σ).
- 3) There is an uncertainty of ± 0.60 (3 σ value) in the reactivity change in going to any operating condition.

B. Power Factor Data

Uncertainty in the Predicted Power Per Element for XE-2 (Orificed Condition of 115° Drum Bank). These represent 3 σ values.

	Core Center (Percent)	Core Edge (Percent)
<u>At Constant Drum Angle</u>		
Error in Amount of Gamma and Neutron Heating Deposited in Core*	± 0.4	± 1.3
Error in the Gamma and Neutron Heating Distribution	± 3.1	± 1.3
Error Introduced by Basing XE-2 Fission Distribution on NRX-A3 Gross Ion Measurements Corrected by PAX Measurements for Loading Changes	± 1.5	± 3.0
Error in Gross Radial Fission Distribution Due to XE-2/NRX-A3 Shim Differences	± 1.0	± 1.0
Error in Uranium Assay of XE-2 Fuel	± 1.0	± 2.0
Statistical Sum	± 3.7	± 4.2
<u>Due to Drum Angle</u>		
Uncertainty in Cold Critical Drum Angle, 10° Drum Rotation	± 1.1	± 3.1
Error in Cold-to-Hot Reactivity, 6° Drum Rotation	± 1.1	± 2.9
Statistical Sum	± 1.6	± 4.2
Total Statistical Sum	± 4.1	± 5.9

*The predicted power includes fission product gamma heating for the fission product inventory at 20 minutes full power (this approximates the equilibrium inventory). At start-of-life operation, the edge power density will be 1.0% higher than predicted, while the centerline power density will be 0.35% lower than predicted.

(CRD) NUCLEAR DATA UNCERTAINTIES (U)	INDEX NO
	E.2.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>DDN</i> 7/31/68	<i>RM</i> 7/2/68	

The reactivity of the XE-2 reactor was determined relative to that of the NRX-A5 reactor, giving a predicted cold critical drum position of $94.4^{\circ} \pm 10^{\circ}$ ⁽¹⁾. The material inventories of the two reactors were determined by the Automated Materials Data System ⁽²⁾ (AMDS) computer program; the detailed XE-2 inventory is presented elsewhere in this report (See C.2.3, C.3.4, C.4.2 and E.1.7). The reactivity changes between XE-2 and NRX-A5 fueled and unfueled elements were determined on an element-by-element basis by interpolation of the radial reactivity worth curves ⁽³⁾; therefore, reactivity comparison given by E.3.2. The corresponding reactivity comparison for components outside the core is given by E.3.3, and the summary of the XE-2/NRX-A5 reactivity comparison is given by E.3.4.

As a check on the validity of the fuel composition data, substitution experiments ("FRC" experiments) were performed in the PAX mock-up of the NRX-A6 reactor (See E.3.6). From these experiments, it was found that the difference in the calculated and experimental reactivity change between XE-2 and NRX-A5 code 431 WNCO elements was 3.6¢. In a similar substitution of 126 XE-2 and NRX-A5 code 431 Y-12 elements into PAX, the difference between calculated and experimental reactivity change was found to be -1.3¢. It was concluded that the non-destructive analysis of the composition of the XE-2 elements had changed slightly relative to that used for the NRX-A5 elements. Therefore, the correction due to this change was determined by ratioing the differences by the respective number of WNCO and Y-12 code 431 elements in the XE-2 reactor and adjusting the results to XE-2 conditions. The correction for WNCO elements was found to be 9.8¢ while the correction for Y-12 elements was found to be -5.4¢. Therefore, the net correction to the XE-2 reactivity estimate is 4.4¢.

- (1) The $+10^{\circ}$ uncertainty was derived by considering the performance in predicting the cold critical drum position of previous reactors.
(2) WANL-TME-1355 for details of AMDS calculations.
(3) WANL-TME-878 and WANL-TME-1355 for the radial reactivity coefficient curves used.

(CRD) XE-2 REACTIVITY ANALYSIS (U)	INDEX NO.
	E.3.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	227 7/31/68	7/31/68	

<u>Material</u>	<u>XE-2 Mass, kg</u>	<u>NRX-A5 Mass, kg</u>	<u>Mass Difference kg</u>	<u>Reactivity Change, d XE-2 Minus NRX-A5</u>
Carbon				
Fueled Elements	864.367	864.926	-0.559	-4.7
Unfueled Elements	175.816	175.533	0.283	1.2
Positive Shims	0.056	0.056	0.00	0.0
Pyrographite Sleeves	26.832	26.957	-0.125	-0.7
Uranium	174.384	174.987	-0.603	-8.8
Niobium				
Fueled Elements				
Bore	82.720	97.088	-14.368	83.3
External	2.213	1.936	0.277	-1.1
Unfueled Elements				
Bore	2.148	2.758	-0.610	2.8
External	6.342	0.256	6.080	-33.6
Molybdenum	5.672	0.010	5.662	-80.5
Stainless Steel	8.044	8.044	0.0	0.0
Inconel-718	23.648	23.648	0.0	0.0
Hydrogen	0.011	0.011	0.0	0.0
Tantalum	3.140	4.014	-0.874	47.5
			<u>CORE SUBTOTAL I</u>	5.4

<u>Material</u>	<u>XE-2 Worth, d</u>	<u>NRX-A5 Worth, d</u>	<u>Reactivity Change, d, XE-2 Minus NRX-A5</u>
Thermocouples	-13.2	-15.7	2.5
Thermal Capsules	-6.4	-6.1	-0.3
Carbon Aft of T/C	1.3	2.0	-0.7
Carbon in Thermal Capsule	2.6	2.9	-0.3
Pressure Probes	-0.1	0.0	-0.1
Fueled Length	-4.7	-4.8	<u>0.1</u>
			CORE SUBTOTAL II
			1.2

(CRD) CORE REACTIVITY DIFFERENCES BETWEEN XE-2 AND NRX-A5 (U)	INDEX NO
	E.3.2

REFERENCE	PREPARED BY JST 7/31/68	APPROVED BY JST 8/4/68	Astronuclear Laboratory

Region	Material	XE-2 Mass, kg	NRX-A5 Mass, kg	Mass Difference kg	Reactivity Coefficient d/kg	Reactivity Change XE-2 Minus NRX-A5, d
Filler Strip	Carbon*	94.011	94.298	-0.287	3.42	-1.0
	Niobium	0.0	0.290	-0.290	-3.80	1.1
	SS Retainer	0.5	0.0	0.5	-0.23	-0.1
Lateral Support	Carbon					
	a. Seal & Retainer					
	Segments	43.279	43.230	0.049	2.8	0.1
	b. Barrel*	247.798	239.626	8.172	2.2	18.0
	c. Plungers	2.486	2.478	0.008	2.2	0.0
	Stainless Steel	11.836	11.830	0.006	-2.3	0.0
	Aluminum	8.618	8.598	0.020	0.26	0.0
	Silica*	7.950	8.613	-0.663	1.2	-0.8
Beryllium Reflector	Beryllium	712.742	712.492	0.250	2.2	0.6
	Aluminum	1.545	1.545	0.0	0.26	0.0
	Titanium	29.143	29.048	0.095	-0.45	0.0
Control Drums	Beryllium	199.856	199.743	0.113	2.2	0.2
	Aluminum	18.228	18.228	0.0	0.26	0.0
	B-10	1.0273	1.0324	-0.0051	----	-0.6
Support Blocks	Carbon	37.090	36.766	0.324	1.36	0.4
NON-CORE SUBTOTAL I						17.9
Reactivity Change, XE-2 Minus NRX-A5, d						
Material		XE-2 Worth, d	NRX-A5 Worth, d			
Instrumentation						
Thermocouples		-0.2	-0.2			0.0
Thermal Capsules		-0.7	-0.7			0.0
Pressure Probes		-0.2	-0.2			0.0
External Structures		7.0	0.0			7.0
NON-CORE SUBTOTAL II						7.0

*Mass adjusted to 52 inches.

(CRD) NON-CORE REACTIVITY DIFFERENCE BETWEEN XE-2 AND NRX-A5 (U)

INDEX NO.

E.3.3

~~CONFIDENTIAL RESTRICTED DATA~~ Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>ELH 7/31/68</i>	<i>R. G. H. Litch 7/31/68</i>	

DESCRIPTION OF DIFFERENCE	REACTIVITY DIFFERENCE (d) XE-2 MINUS NRX-A5
Subtotal I, Core Inventory Differences (E.3.2)	5.4
Reactivity Correction from FRC Experiment (E.3.6)	4.4
Subtotal II, Core Instrumentation Differences (E.3.2)	1.2
Subtotal I, Non-Core Inventory Differences (E.3.3)	17.9
Subtotal II, Non-Core Instrumentation and Shield Difference (E.3.3)	7.0
Net XE-2/NRX-A5 Reactivity Difference at the NRX-A5 Critical Drum Position of 99.3°	35.9
XE-2 Predicted Cold Critical Drum Position (Degrees)*	94.4
XE-2 Aim Cold Critical Drum Position (Degrees)*	96.0

*In the reactivity shimming procedure, it was not possible to specify an azimuthally uniform TaC shim pattern which would produce the desired 96° cold critical position. In addition, due to scheduler considerations, all of the XE-2 shims were specified before the final fuel inventory of the XE-2 was known. These two items resulted in a symmetrical shim pattern calculated to yield the indicated 94.4° drum position.

(CRD) SUMMARY OF XE-2 AND NRX-A5 REACTIVITY DIFFERENCES, d (U)	INDEX NO
	E.3.4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>DRH</i> 7/31/68	<i>DRM</i> 8/1	

REGION AVERAGE REACTIVITY COEFFICIENT (β/kg)⁽¹⁾

Region Radius, cm Region Identification ⁽²⁾	36.366 2, 6, 10, 14, 18, 22	40.279 3, 7, 11, 15, 19, 23	41.938 4, 8, 12, 16, 20, 24	43.804 5, 9, 13, 17, 21, 25	Core Average
Carbon ⁽¹⁾	6.20	4.65	4.15	3.80	5.62
Uranium ⁽¹⁾	14.39	10.26	11.08	12.20	13.33
Niobium ⁽¹⁾	-6.42	-3.47	-3.31	-3.37	-5.42
Tantalum ⁽¹⁾	-58.69	-43.05	-44.96	-47.59	-54.34
Molybdenum ⁽³⁾	-13.62	-11.78	-12.08	-12.73	-13.15
Stainless Steel	--	--	--	--	-0.08
Inconel-X 750	--	--	--	--	-0.39
Inconel - 718	--	--	--	--	-0.86
Hydrogen ⁽¹⁾	--	--	--	--	670.0
Iron ⁽²⁾	--	--	--	--	-0.08
Nickel ⁽¹⁾	--	--	--	--	-0.46
Chromium ⁽²⁾	--	--	--	--	0.11

(1) The coefficients for carbon, uranium, niobium, tantalum, nickel, and hydrogen are measured. The remainder are wholly or in part calculated. Other measured reactivity coefficients are given in WANL-TME-878, "NRX-A2 Reactivity and Shimming", July, 1964.

(2) Based on calculations.

(3) Based on measurements made in the PAX mockup of NRX-A6 and adjusted to XE-2 conditions by calculations.

(CRD) AVERAGE REACTIVITY COEFFICIENTS FOR CORE REGIONS (β/kg) (U)	INDEX NO
	E.3.5.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	D. Hill 8/1/68	R. M. Cutchner 9/1	

<u>Region</u>	<u>Material</u>	<u>Reactivity Coefficients (¢/kg)</u>
Filler Strip	Carbon ⁽¹⁾	3.42
	Niobium ⁽¹⁾	-3.80
Lateral Support	Carbon ⁽¹⁾	2.30
	Stainless Steel ⁽²⁾	-2.30
	Aluminum ⁽¹⁾	0.26
	Silica ⁽²⁾	1.20
Beryllium Reflector	Beryllium ^(1,2)	2.20
	Aluminum ⁽²⁾	0.26
	Titanium ⁽³⁾	-0.45
Core Support Block	Carbon ⁽¹⁾	1.36
	Molybdenum ⁽²⁾	0.50
	Stainless Steel ⁽²⁾	0.50
	Inconel - X ⁽²⁾	0.70
	Niobium ^(2,3)	0.40

- (1) Based on WANEF experimental data.
 (2) Based on LASL experimental data.
 (3) Based on calculations.

(CRD) AVERAGE REACTIVITY COEFFICIENTS FOR NON-CORE REGIONS (¢/kg) (U)	INDEX NO.
	E.3.5.2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	D. Hill 8/1/68	E. A. M. L. S. H.	

XE-2 WNCO/NRX-A5 WNCO COMPARISON (126 ELEMENTS)

Material	XE-2 WNCO Mass, kg	A5 WNCO Mass, kg	Mass Change, kg	Reactivity Change (Δ), XE-2 WNCO Minus A5 WNCO	
				Calculated	Experimental
C	66.600	66.485	0.115		+0.626
U	15.919	15.893	0.026		+0.420
Nb	6.205	8.452	-2.247		13.086
Mo	0.537	0.0	0.537		-7.209
		Unfueled Element Correction			-0.034
TOTAL				6.889	10.5 $\pm$ 1.0

WNCO Net Experiment/Calculation Difference Per Element = $(10.5 - 6.889)/126 = 0.029\%$

XE-2 Y-12/NRX-A5 Y-12 COMPARISON (126 ELEMENTS)

Material	XE-2 Y-12 Mass, kg	NRX-A5 Y-12 Mass, kg	Mass Change, kg	Reactivity Change (Δ), XE-2 Y-12 Minus NRX-A5 Y-12	
				Calculated	Experimental
C	66.835	67.264	-0.429		-2.367
U	15.905	16.076	-0.171		-2.519
Nb	6.661	8.273	-1.612		9.386
Mo	0.441	0.0	0.441		-5.917
		Unfueled Element Correction			0.034
TOTAL				-1.383	-2.7 $\pm$ 1.0

Y-12 Net Experiment/Calculation Difference Per Element = $(-2.7 + 1.383)/126 = -0.010\%$

Net Correction⁽¹⁾ for XE-2 = 4.4%

- (1) The correction is the product of the WNCO and Y-12 discrepancies times the respective number of WNCO and Y-12 code 431 elements in XE-2. Since the XE-2 FRC experiment was performed in the PAX mockup of NRX-A6, the preceding result is then adjusted to XE-2 conditions.

(CRD) RESULTS OF THE XE-2 FUEL REACTIVITY CHECK EXPERIMENT (U)	INDEX NO.
	E.3.6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Rittenberger 7/30/63	J. M. L. 7/30/63	

Specifications

Poison Material	B ₄ C powder in stainless steel tube with outer sheath of polyethylene	
Wire Length (Active)	52.0	inch
Wire Region Outer Diameters		
B ₄ C	0.048 ± .001	inch
Stainless Steel	0.067 ± .001	inch
Polyethylene Sheath	0.078 ± .004 - .000	inch
Density of B ₄ C	2.0	g/cc
Percent Theoretical Density	80	percent
Weight B in B ₄ C	78.5	weight percent
Weight B-10 in B (minimum)	17.11	weight percent
Weight B ₄ C in 52 inch length tube	3.10	g
Weight B in 52 inch length tube	2.42	g
Weight B-10 in 52 inch length tube	0.41	g
No. of wires present for shipping	6990	
Total B in core for shipping	16.92	kg
Total B-10 in core for shipping	2.87	kg

(CRD) B ₄ C POISON WIRE DATA (U)	INDEX NO.
	E.4.1

REFERENCE		Astronuclear Laboratory
-----------	--	---

(CRD) RADIAL WORTH OF XE-2 B ₄ C POISON WIRES (U)	PREPARED BY	APPROVED BY
	R. Ritterberger	<i>[Signature]</i>

INDEX NO.
E. 4.2

VIEWED IN DIRECTION OPPOSITE
TO CORE FLOW

(CRD) TYPICAL POISON WIRE LOADING PATTERN FOR XE-2 CORE SECTORS (U)

PREPARED BY

APPROVED BY

R. Ritterberger

DA/Kentchen 7/2/0

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	D. HILL 8/1/68	OKM Cutler 8/1/68	

THIS PAGE UNCLASSIFIED

ITEM	UNITS	VALUE
A. Reactivity of Unshimmed Reactor at Room Temperature; no H ₂ .		
Reactivity at 68°F (165° drum angle)*	dollars	5.44
(15° drum angle)	dollars	-2.48
Critical Drum Position Before Shimming	degrees	74
B. Reactivity of Shimmed Reactor at Room Temperature; no H ₂ .		
Reactivity of 42 TaC Loaded Unfueled Elements	dollars	-1.78
Shimmed Reactivity		
At 165° drum position	dollars	3.66
At 15° drum position	dollars	-4.26
Critical Drum Angle After Shimming	degrees	94.4° ± 10°
C. Shipping Reactivity		
Shutdown Reactivity for Core with 6990 Poison Wires		
Dry	dollars	66
Flooded	dollars	32

*During normal operation, the XE-2 control drums are limited to motion between 15° and 165° by design.

(U) PREDICTED XE-2 REACTIVITY AT ROOM TEMPERATURE (U)	INDEX NO.
	E. 4.4

DIFFERENTIAL DRUM WORTH - CENTS/DEGREE

DRUM POSITION - DEGREES

(U) DIFFERENTIAL SINGLE CONTROL DRUM WORTH (U)

PREPARED BY

R S K.

7/31/68

APPROVED BY

L. M. Entler 7/31/68

REFERENCE

 Astronautics
Laboratory

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>R. J. Kaiser 7/31/68</i>	<i>D. M. Ritchie 8/1/68</i>

(U) INTEGRAL CONTROL DRUM BANK WORTH (U)	INDEX NO
	E.5.2

REFERENCE "Physics of Nuclear Kinetics," G. Keepin	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. J. Keiser 7/5/68	Phil M. Fitch 7/5/68	

Kinetic Parameters

Inhour Equation

$$\rho(\$) = \frac{\rho}{\beta_{\text{eff}}} = \frac{\rho}{k_{\text{eff}} \beta_{\text{eff}} T} + \sum_{i=1} \frac{\alpha_i}{1 + \lambda_i T}$$

$\rho(\$)$	=	Reactivity, dollars
ρ	=	Reactivity, dimensionless
T	=	Stable Reactor Period in sec
β_{eff}	=	Effective Delayed Neutron Fraction = 0.0071
ℓ	=	Prompt Neutron Lifetime = 24×10^{-6} sec $\pm$ 5 percent
λ_i	=	Decay Constant of Group i
α_i	=	Fraction of Neutrons in Delayed Group i

Group	α_i	λ_i (sec ⁻¹)
1	0.033	0.0124
2	0.219	0.0305
3	0.196	0.111
4	0.395	0.301
5	0.115	1.14
6	0.042	3.01

(U) DELAYED NEUTRON DATA (U)	INDEX NO.
	E.5.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>R. J. Kaiser 7/31/68</i>	<i>W. M. Cutler 7/4/68</i>

(U) REACTOR STABLE PERIOD VERSUS REACTIVITY INSERTION (U)	INDEX NO
	E. 5. 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. J. Kassis 7/31/68	J. M. G. L. 8/1/68	

Reactivity Coefficients Changed for Differences between NRX-A2 and XE-2

Coefficients not appearing here remain unchanged from the values given in WANL-TME-936, Development of a Method for Computing the Cold-to-Hot Reactivity Change in the NRX-A Assemblies.

<u>Parameter</u>	<u>Symbolic Name</u> [*]	<u>NRX-A2 Value</u>	<u>XE-2 Value</u>
Hydrogen Worth Coefficient			
in Upper Plenum	C (7)	-0.672×10^{-1}	-0.672×10^{-1}
Niobium Doppler	CBCON	-0.833×10^{-4}	-1.066×10^{-4}
Uranium Doppler	UCON (1)	0.12	0.1221
	UCON (3)	-0.155	-0.1578
	UCON (4)	-0.26	-0.2646
	UCON (5)	-0.406	-0.4132
	UCON (6)	-0.45	-0.4580
Ta Shim Content	TASHIM	2.87	1.781

* Symbolic name as used in WANL-TME-936

(CRD) XE-2 PARAMETERS FOR COHOT REACTIVITY ANALYSIS (U)	INDEX NO.
	E.6.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. J. Kaiser 7/21/68	D. M. Patten 7/1/68

(CRD) ISO-REACTIVITY FEEDBACK MAP FOR STEADY STATE OPERATION (U)

INDEX NO

E.6.2

REFERENCE		
		Astronuclear Laboratory

(CRD) POWER PERTURBATION ADJACENT TO UNFUELED CENTRAL ELEMENTS (CRD)

PREPARED BY	APPROVED BY
R. Rittenberger 7/29/68	DA/Mentchen 7/31/68

INDEX NO.

E.7.1

REFERENCE

THESE FACTORS ARE ALSO MULTIPLIED BY A RADIAL CORRECTION FACTOR TO ACCOUNT FOR THE VARIATION IN GAMMA AND NEUTRON HEATING IN THE CENTRAL ELEMENTS; SEE FIGURE E.7.5

PREPARED BY

R. Rittenberger 7/30/68

APPROVED BY

D. M. Litch 7/30

(CRD) CORRECTION FACTORS TO ACCOUNT FOR THE CONDUCTION OF HEAT FROM THE UNFUELED ELEMENT TO FUELED ELEMENT (CRD)

INDEX NO.

E.7.2

REFERENCE

(CRD) MIDPLANE POWER DISTRIBUTION CORRECTION FOR R-Z NON-SEPARABILITY (U)

PREPARED BY

RR *Thy*

APPROVED BY

Devin G. G. 7/2/54

INDEX NO

E.7.3

~~CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954~~

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>B. Rittenberg et al.</i>

(CRD) INCREASE IN PERIPHERAL FISSION DENSITY DUE TO THE REMOVAL OF THE CODE 32 FUEL ELEMENTS (CRD)	INDEX NO.
	E.7.4

~~CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954~~

REFERENCE

(CRD) GAMMA AND NEUTRON HEATING RATE VERSUS RADIAL POSITION (U)

PREPARED BY

APPROVED BY

R. Rittenberger 7/30/68 DCM/Chh 8/1/68

INDEX NO.

E.7.5

REFERENCE

(CRD) EFFECT OF GAMMA AND NEUTRON HEATING ON RADIAL POWER DISTRIBUTION (U)

PREPARED BY

R. Rittenberger

APPROVED BY

D. M. Smith

INDEX NO.

E.7.6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Rittenberger 7/20/54	De Witt 7/20	

XE-2 POWER FACTORS

(U) Individual coolant channel power factors are presented in the following pages for the XE-2 reactor at a drum bank position of 115 degrees. Below is a sample to illustrate the format used.

10 OF 244 1230 1230 1219 1219 1219 1219 1208 1208 1208
 99 001 1208 1208 1197 1197 1197 1186 1186 1186

(CRD) Each fuel element is represented by two rows of information. The first two entries of the first row give the fuel element location (e.g., Row 1, Cluster OO, Element F). Next comes the nominal uranium weight in grams per inch of fueled element. The power factors for channels 1 to 10 complete the first row.

(CRD) The first entry of the second row is a two digit number; the first digit indicates the fuel loading (serial 9 is the 2.44 g/in. loading, etc.), while the second digit 9 indicates the element has 19 coolant channels. The next entry designates the applicable axial power profile. The power factors for the remaining coolant channels complete the second row. The succeeding pairs of rows give the above information for the remaining elements, moving radially outward from the core centerline. This loading designation has been superseded by a new three-digit system: the 2.44 g/in. fuel loading is now referred to as a Code 431 element, as shown in Figure No. C.2.1; the digits 8, 7, . . . 1 designate the range of decreasing loadings specified therein. The PFENCE computer code has not been altered to the new designation.

(CRD) OPERATING CHANNEL POWER FACTORS FOR A 115 DEGREE DRUM BANK POSITION (U)	INDEX NO.
	E. 7. 7
	Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Rittenberger	W. M. Litch	

POWER FACTORS FOR KE-2 DURING FULL POWER OPERATION
WITH GRID 32 FULLY ELEMENTS REMOVED
CONTROL DRUMS AT 115 DEGREES

1C 0F 124	1154	1195	1194	1173	1175	1175	1173	1155	1156	1157
55 001	1156	1155	1148	1145	1145	1148	1142	1145	1142	
1A 1F 124	1166	1166	1150	1186	1166	1145	1142	1185	1165	1148
55 001	1141	1175	1161	1146	1146	1134	1143	1138	1132	
1A 1C 124	1153	1147	1142	1169	1154	1147	1141	1186	1171	1154
55 001	1147	1141	1189	1176	1153	1146	1187	1167	1151	
1A 1E 124	1138	1140	1140	1143	1145	1146	1146	1148	1151	1152
55 001	1153	1155	1165	1168	1170	1169	1185	1181	1188	
1A 1C 124	1112	1135	1147	1136	1138	1147	1164	1128	1136	1146
55 001	1164	1184	1134	1144	1163	1184	1141	1159	1181	
1A 1C 124	1140	1158	1180	1111	1140	1159	1181	1123	1131	1141
55 001	1159	1175	1123	1111	1119	1156	1122	1136	1138	
1A 1E 124	1179	1164	1181	1157	1165	1161	1165	1156	1160	1142
55 001	1142	1142	1130	1132	1137	1133	1123	1125	1126	
1E 1F 124	1160	1142	1127	1159	1141	1125	1115	1153	1137	1122
55 001	1116	1112	1132	1115	1113	1109	1115	1110	1105	
1P 1E 124	1133	1126	1124	1147	1123	1127	1123	1164	1146	1132
55 001	1127	1122	1165	1147	1131	1125	1162	1144	1129	
1E 1E 124	1117	1116	1121	1120	1123	1125	1126	1124	1127	1130
55 001	1171	1112	1140	1144	1146	1146	1160	1163	1164	
1C 1E 124	1164	1112	1122	1112	1110	1119	1158	1099	1107	1117
55 001	1126	1157	1124	1114	1113	1155	1116	1129	1151	
1E 1E 124	1156	1147	1145	1159	1104	1126	1145	1096	1038	1106
55 001	1127	1147	1185	1147	1106	1124	1088	1096	1104	
1E 1E 124	1147	1151	1151	1124	1128	1130	1136	1105	1108	1110
55 001	1111	1112	1097	1100	1101	1113	1050	1092	1094	
1P 1F 124	1165	1145	1128	1164	1144	1127	1115	1166	1142	1125
55 001	1113	1111	1137	1122	1115	1105	1116	1112	1136	
1E 1E 124	1175	1112	1127	1134	1138	1111	1125	1171	1153	1156
55 001	1125	1126	1171	1151	1154	1126	1167	1147	1130	
1E 1E 124	1145	1117	1130	1135	1134	1135	1135	1138	1139	1141
55 001	1146	1140	1136	1158	1156	1154	1171	1175	1172	
1E 1C 124	1122	1128	1136	1115	1126	1135	1151	1116	1124	1132
55 001	1115	1116	1121	1129	1146	1168	1126	1143	1164	

1C 3E 124	1121	1120	1121	1099	1101	1101	1099	1079	1080	1081
55 001	1080	1079	1070	1071	1071	1070	1061	1062	1061	
1C 1F 124	1073	1057	1044	1070	1054	1041	1037	1064	1050	1037
55 001	1033	1030	1044	1032	1025	1025	1027	1023	1021	
1C 1C 124	1054	1050	1048	1065	1053	1049	1046	1075	1065	1052
55 001	1048	1045	1079	1063	1050	1046	1076	1066	1047	
1C 1E 124	1038	1041	1044	1039	1042	1045	1048	1041	1045	1048
55 001	1051	1053	1055	1060	1063	1064	1072	1077	1078	
1C 1C 124	1019	1026	1037	1015	1044	1034	1051	1011	1020	1033
55 001	1048	1068	1015	1025	1044	1065	1020	1038	1059	
1L 1C 124	1017	1035	1056	1006	1016	1035	1056	997	1006	1015
55 001	1024	1053	996	1004	1014	1031	994	1002	1011	
1C 1E 124	1054	1058	1060	1031	1036	1039	1040	1012	1016	1019
55 001	1022	1023	1004	1008	1010	1013	998	1000	1003	
1C 1F 124	1050	1073	1059	1087	1071	1056	1050	1081	1066	1052
55 001	1047	1042	1060	1047	1042	1038	1042	1038	1034	
1C 1E 124	1072	1066	1064	1084	1071	1066	1062	1099	1083	1069
55 001	1065	1056	1058	1081	1066	1060	1094	1077	1063	
1L 1E 124	1061	1063	1065	1062	1065	1067	108	1064	1067	1070
55 001	1071	1072	1078	1082	1084	1084	1095	1098	1099	
1C 1E 124	1045	1053	1061	1041	1049	1058	1075	1037	1045	1054
55 001	1072	1091	1040	1049	1068	1089	1044	1062	1082	
1L 1E 124	1041	1059	1079	1031	1040	1058	1078	1021	1029	1036
55 001	1056	1075	1019	1027	1035	1052	1017	1024	1032	
1E 1E 124	1074	1078	1078	1051	1055	1057	1057	1052	1035	1057
55 001	1058	1056	1023	1026	1029	1029	1016	1018	1019	
1C 1F 124	1054	1075	1060	1051	1073	1058	1051	1086	1069	1054
55 001	1048	1042	1064	1050	1044	1048	1045	1039	1034	
1C 1C 124	1077	1071	1066	1089	1075	1068	1063	1104	1087	1072
55 001	1065	1055	1102	1084	1068	1061	1097	1079	1064	
1L 1E 124	1071	1072	1072	1072	1073	1074	1075	1075	1077	1078
55 001	1078	1078	1088	1090	1091	1091	1103	1106	1105	
1C 1C 124	1058	1065	1072	1055	1061	1069	1085	1051	1058	1066
55 001	1083	1101	1053	1061	1075	1059	1063	1073	1093	
1C 1E 124	1053	1070	1089	1043	1051	1068	1068	1033	1040	1048
55 001	1065	1082	1031	1037	1045	1060	1027	1034	1041	
1C 1E 124	1082	1084	1083	1059	1062	1062	1061	1040	1042	1043
55 001	1043	1044	1040	1032	1032	1032	1023	1023	1023	

1C 4F 124	1083	1064	1048	1081	1062	1046	1038	1076	1059	1043
55 001	1035	1028	1054	1035	1032	1025	1035	1028	1022	
1L 4C 124	1067	1060	1054	1080	1064	1057	1051	1095	1078	1061
55 001	1053	1046	1093	1074	1057	1049	1087	1068	1052	
1C 4E 124	1066	1066	1065	1068	1068	1068	1067	1071	1072	1072
55 001	1071	1069	1083	1084	1084	1082	1098	1100	1097	
1C 4C 124	1058	1063	1069	1055	1060	1067	1081	1051	1057	1064
55 001	1080	1097	1053	1060	1076	1095	1055	1071	1089	
1F 4C 124	1051	1067	1085	1042	1045	1065	1083	1033	1039	1045
55 001	1061	1076	1025	1035	1041	1056	1052	1051	1036	
1C 4E 124	1075	1077	1075	1053	1055	1054	1052	1035	1035	1035
55 001	1040	1033	1025	1025	1024	1023	1015	1015	1015	
1E 1F 124	1016	1003	991	1013	958	987	983	1009	995	984
55 001	978	976	991	979	975	973	974	971	968	
1E 1E 124	1002	955	997	1011	1001	958	996	1023	1011	1000
55 001	956	954	1023	1009	997	994	1020	1005	994	
1E 1E 124	965	990	993	985	968	954	997	987	991	995
55 001	998	1001	1000	1005	1008	1013	1015	1021	1022	
1E 1C 124	947	974	984	964	972	980	997	962	969	975
55 001	994	1012	966	975	992	1011	970	968	1006	
1E 1C 124	965	965	1005	960	965	986	1005	945	959	968
55 001	980	1002	952	958	967	962	960	954	965	
1E 1E 124	1003	1007	1006	983	986	999	988	965	968	970
55 001	972	974	958	961	963	964	950	954	957	
1F 1F 124	1009	1020	1011	1005	1020	1017	1002	1028	1015	1002
55 001	958	954	1008	996	953	950	951	957	964	
1E 1C 124	1024	1021	1017	1035	1023	1019	1015	1048	1034	1021
55 001	1016	1012	1047	1031	1018	1013	1043	1027	1014	
1E 1E 124	1012	1015	1017	1013	1016	1015	1021	1014	1018	1021
55 001	1023	1024	1027	1031	1034	1035	1043	1047	1048	
1E 1C 124	954	1002	1011	950	958	1007	1023	984	993	1002
55 001	1020	1035	987	950	1015	1006	991	1008	1028	
1E 1C 124	987	1004	1024	978	980	1004	1024	968	975	985
55 001	1001	1020	967	974	981	957	967	972	979	
1E 1E 124	1000	1024	1024	957	1001	1004	1004	975	981	983
55 001	965	987	972	974	975	978	967	967	968	
1E 1F 124	1048	1032	1018	1045	1025	1014	1038	1024	1011	
55 001	1005	1000	1018	1005	1000	996	1000	995	991	

(CRD) OPERATING CHANNEL POWER FACTORS FOR A 115 DEGREE DRUM BANK POSITION (U)

INDEX NO.

E.7.7
Sheet 2

CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Rittenberger 7/20/58	D. M. Ratch 7/50	

1E 36 124 1035 1036 1026 1045 1032 1027 1023 1059 1044 1030	1F 4C 124 970 977 984 967 973 980 994 964 971 978
99 001 1024 1019 1057 1041 1026 1020 1053 1036 1022	99 001 993 1009 968 975 990 1007 970 986 1004
1E 38 124 1027 1029 1030 1029 1030 1032 1033 1030 1032 1034	1F 4D 124 968 983 1001 959 967 983 1000 950 955 963
99 001 1035 1036 1042 1045 1047 1046 1057 1060 1060	99 001 979 996 969 968 967 974 943 950 953
1E 3C 124 1012 1019 1027 1008 1015 1023 1039 1003 1010 1019	1F 4E 124 955 997 996 982 978 975 974 955 947 985
99 001 1036 1054 1005 1014 1031 1051 1009 1025 1044	99 001 980 974 957 940 947 948 939 936 951
1E 3D 124 1004 1021 1041 994 1002 1020 1039 983 991 1000	1F 5F 124 959 982 967 998 980 965 959 990 975 960
99 001 1016 1034 980 987 995 1011 978 984 991	99 001 955 952 995 983 958 946 952 946 931
1E 3E 124 1033 1036 1036 1010 1013 1015 1015 990 993 994	1F 5G 124 980 975 969 993 979 973 967 1008 992
99 001 995 996 982 984 985 985 973 975 976	99 001 949 964 1007 989 974 968 1002 984 970
1E 4F 124 1045 1027 1013 1043 1025 1010 1003 1037 1021 1006	1F 5H 124 980 980 980 981 982 982 981 984 985 978
99 001 999 994 1015 1001 995 990 995 990 985	99 001 985 984 994 995 995 994 1009 1010 1009
1E 4G 124 1032 1027 1021 1044 1030 1023 1018 1058 1041 1026	1F 5C 124 949 975 980 967 973 979 993 964 969 976
99 001 1019 1014 1055 1038 1022 1015 1049 1032 1017	99 001 992 1008 968 974 989 1007 970 984 1002
1E 4B 124 1030 1031 1031 1031 1032 1032 1032 1033 1034 1035	1F 5D 124 947 982 999 959 965 980 998 952 955 960
99 001 1035 1035 1044 1046 1047 1045 1059 1061 1059	99 001 975 990 946 958 983 995 931 946 952
1E 4C 124 1018 1024 1030 1014 1020 1027 1042 1010 1016 1023	1F 5E 124 959 1001 999 969 971 971 969 966 967 968
99 001 1039 1056 1011 1019 1035 1054 1013 1029 1047	99 001 967 966 946 946 946 946 946 946 946 946
1E 4D 124 1009 1025 1043 999 1007 1023 1041 990 996 1003	1F 6F 124 979 980 963 979 965 954 951 989 976 965
99 001 1019 1036 985 992 999 1013 981 987 993	99 001 941 931 954 961 937 944 949 941 934
1E 4E 124 1034 1036 1034 1011 1013 1014 1012 991 993 993	1F 6G 124 949 963 957 982 968 961 954 996 979 964
99 001 953 993 983 983 984 983 973 973 974	99 001 955 950 993 982 974 974 984 969 953
1E 5F 124 1029 1011 995 1026 1008 992 984 1021 1005 989	1F 6H 124 968 967 966 971 969 969 968 974 975 975
99 001 981 975 999 985 977 973 980 974 969	99 001 973 971 985 986 985 983 999 1000 998
1E 5G 124 1018 1011 1005 1029 1014 1007 1000 1043 1026 1010	1F 6C 124 963 968 973 961 965 971 984 958 963 969
99 001 1003 996 1040 1022 1005 998 1034 1015 1000	99 001 983 995 960 966 980 957 960 973 990
1E 5H 124 1019 1019 1018 1021 1021 1020 1019 1023 1024 1023	1F 6D 124 977 995 993 948 953 967 976 953 957
99 001 1022 1021 1034 1035 1034 1032 1047 1048 1046	99 001 943 986 945 952 959 974 933 936 939
1E 5C 124 1011 1016 1022 1008 1013 1019 1032 1004 1009 1015	1F 6E 124 988 992 993 958 957 981 970 953 955 962
99 001 1030 1046 1005 1011 1026 1044 1006 1021 1038	99 001 949 945 937 939 943 946 951 939 940
1E 5D 124 1002 1017 1034 992 998 1013 1030 982 987 993	1G 1F 124 1024 994 974 1047 1011 987 975 1067 1033 999
99 001 1008 1023 979 984 950 1003 974 978 983	99 001 967 975 1060 1026 1004 993 1055 1031 1009
1E 5E 124 1021 1022 1020 1000 1001 1000 997 983 981 981	1G 1G 124 963 955 952 1002 963 957 950 1023 1002 963
99 001 981 980 973 973 973 972 966 966 964	99 001 955 947 1037 1006 981 960 1047 1011 986
1F 1F 124 955 963 955 979 968 943 955 986 958 952	1G 1H 124 975 954 944 978 980 958 957 991 985
99 001 952 934 976 950 940 944 952 952 934	1G 1C 124 1010 1000 990 1054 1024 1014 1011 1123 1068 1039
1F 1G 124 944 965 949 980 955 975 953 984 977 952	99 001 1036 1035 1122 1069 1061 1061 1120 1118 1085
99 001 935 962 991 964 966 948 994 968 960	
1F 1B 124 956 944 967 948 957 947 949 945 958 948	1G 1D 105 1004 956 966 1014 1017 1009 1004 1048 1026 1029
99 001 957 955 954 977 967 978 987 980 987	99 001 1021 1013 1072 1050 1049 1039 1096 1070 1044
1F 1C 124 942 935 953 943 952 943 969 936 951 949	1G 1E 105 1002 960 936 1017 956 979 936 1010 1015
99 001 944 977 948 960 967 987 956 968 985	99 001 977 938 1020 1020 995 981 1029 1002 1000
1F 1D 124 962 972 986 958 951 964 973 950 965 957	1G 2F 124 952 984 959 993 977 961 964 1016 966 963
99 001 975 981 951 963 963 964 951 955 969	99 001 956 950 1009 984 945 949 985 989 973
1F 1E 124 984 992 984 962 969 962 971 966 954 956	1G 2G 124 956 944 944 968 962 950 939 979 966 956
99 001 952 961 965 955 944 944 950 958 944	99 001 955 944 987 979 953 934 996 968 962
1F 2F 124 951 978 965 1016 985 960 958 977 970 964	1G 2H 124 949 943 950 947 939 953 946 953 958 960
99 001 945 948 976 951 945 945 951 956 947	99 001 952 956 976 966 961 966 1002 991 980
1F 2G 124 974 971 966 985 974 969 966 999 985 972	1G 2C 124 951 955 970 940 944 1002 986 1008 1015
99 001 968 963 999 984 970 966 996 981 968	99 001 978 952 980 996 1000 1002 986 1008 1015
1F 2B 124 963 964 966 965 967 969 969 967 970 972	1G 2D 124 989 1000 1018 1005 1000 1002 1020 1003 1007 1011
99 001 974 974 980 983 985 985 995 995 999	99 001 1012 1018 1005 1008 1012 1022 1006 1009 1013
1F 2C 124 959 954 964 944 975 965 975 952 934 957	1G 2E 124 1018 1019 1026 1020 1008 1002 1000 1013 1012 1005
99 001 951 991 944 966 966 902 955 960 995	99 001 951 985 1009 1007 1005 997 1005 1003 1001
1F 2D 124 948 971 980 948 940 979 988 932 943 953	1G 3F 124 952 971 953 982 967 948 954 986 965 944
99 001 957 953 942 938 951 963 951 944 944	99 001 948 943 982 961 948 938 960 965 955
1F 2E 124 953 967 978 966 955 977 968 944 956 956	1G 3G 124 946 955 945 968 958 937 939 975 960 931
99 001 944 962 943 939 950 947 948 938 934	99 001 947 953 990 965 944 941 983 976 954
1F 3F 124 1002 987 974 1001 965 971 965 996 982 968	1G 3H 124 952 945 939 944 937 958 952 944 951 940
99 001 963 958 974 964 955 955 971 957 949	99 001 940 948 964 958 964 967 993 985 973
1F 3G 124 984 980 977 994 981 979 973 1009 954 980	1G 3C 124 944 944 955 929 955 956 964 951 947 939
99 001 975 970 1007 993 978 973 1005 988 974	99 001 976 987 948 964 966 986 965 969 979
1F 3H 124 976 975 980 978 978 981 983 979 981 982	1G 3D 124 940 986 993 951 962 976 1004 973 952 949
99 001 983 985 991 994 955 995 1006 1009 1009	99 001 977 952 983 978 967 974 974 988 983
1F 3C 124 963 969 977 961 968 975 989 957 964 972	1G 3E 124 952 1003 983 978 977 975 982 985 951
99 001 988 1005 961 968 965 1003 964 980 999	99 001 950 962 987 989 976 964 975 975 983
1F 3E 124 960 975 995 945 976 960 992 953 947 937	1G 4F 124 965 967 948 988 969 952 943 985 961 957
99 001 954 1001 936 960 940 968 945 944 962	99 001 954 947 957 950 951 941 954 946 938
1F 3E 124 1004 955 991 967 956 997 985 961 966 940	1G 4G 124 963 960 938 971 954 945 937 971 961 951
99 001 955 944 949 944 956 961 953 948 943	99 001 955 947 987 957 961 935 974 960 949
1F 4F 124 1005 986 974 1003 968 971 965 999 983 969	1G 4H 124 944 945 967 958 951 947 948 956 952 949
99 001 963 958 978 966 961 955 959 954 950	99 001 963 966 962 977 972 967 987 972 976
1F 4G 124 988 983 979 997 985 979 975 1011 996 982	1G 4C 124 947 936 948 935 945 954 971 947 945 943
99 001 975 972 1011 994 979 973 1006 991 977	99 001 961 960 947 949 973 982 959 970 983
1F 4H 124 984 985 986 984 986 987 987 985 988 949	1G 4E 124 950 955 986 945 960 964 990 959 957 956
99 001 950 990 998 999 1000 999 1011 1013 1012	99 001 966 954 950 963 971 978 951 956 961

(CRD) OPERATING CHANNEL POWER FACTORS FOR A 115 DEGREE DRUM BANK POSITION (U)

INDEX NO.

E.7.7
Sheet 3

CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>R. Rittenberg</i>	<i>Dr. M. R. Hutchins</i>	

1G 4E 124 981 993 977 983 978 973 960 961 961 966	1H 6G 124 967 960 953 996 975 972 966 1025 1005 988
99 C01 973 967 946 957 956 955 966 943 955	99 C01 982 977 1045 1025 1004 998 1064 1041 1020
1G 5F 124 981 964 949 993 975 960 953 985 972 951	1H 6E 124 955 947 938 960 955 951 957 965 965 964
99 C01 945 941 964 950 943 938 966 959 953	99 C01 970 976 1006 1006 1006 1012 1031 1030 1030
1G 5G 124 948 942 934 975 961 954 948 993 981 940	1H 6C 124 978 977 977 984 981 981 959 999 996 994
99 C01 935 931 981 965 951 950 947 948 949 948 942	99 C01 1012 1033 1015 1017 1027 1047 1046 1050 1062
1G 5H 124 952 970 967 939 947 947 948 949 948 942	1H 6D 105 877 887 899 902 901 912 924 946 946 946
99 C01 943 963 974 974 972 969 970 974 974 974	89 C01 958 971 972 972 972 983 999 999 999
1G 5C 124 951 954 957 946 960 942 958 935 943 949	1H 6E 105 951 986 981 1004 955 994 993 1021 1016 1010
99 C01 970 964 946 949 960 975 951 963 992	89 C01 1005 1005 1036 1031 1024 1023 1075 1068 1061
1G 5D 124 960 973 988 947 955 968 971 942 945 949	1H 7F 105 1023 1018 1066 1059 1046 1033 1039 1061 1049 1038
99 C01 975 974 958 959 962 972 950 955 966	85 C01 1044 1051 1090 1079 1082 1089 1119 1120 1121
1G 5E 124 979 996 991 980 975 977 973 961 961 962	1H 7G 124 953 994 995 1035 1015 1016 1018 1080 1057 1036
99 C01 968 968 955 957 957 956 968 959 950	99 C01 1039 1041 1106 1083 1067 1069 1158 1158 1121
1G 6F 124 951 978 948 992 977 964 960 1000 984 979	1H 7E 124 955 955 954 963 965 965 963 981 982 984
99 C01 955 950 976 963 957 950 961 963 968	99 C01 963 962 1030 1032 1015 1018 1082 1070 1057
1G 6G 124 954 950 940 956 944 940 938 990 976 964	1H 7C 124 965 976 989 986 985 1001 1022 1007 1010 1014
99 C01 944 941 989 973 955 954 986 967 950	99 C01 1035 1058 1031 1035 1062 1085 1058 1085 1114
1G 6H 124 934 937 937 953 954 955 955 941 941 969	1H 7D 105 961 981 1003 993 990 1010 1028 1027 1023 1020
99 C01 966 961 969 966 965 962 976 979 979	85 C01 1037 1055 1054 1051 1043 1059 1104 1096 1088
1G 6C 124 937 943 947 935 940 946 959 945 950 956	1H 7E 051 940 965 971 982 980 984 1004 1001 998
99 C01 970 986 948 954 969 986 950 964 981	75 C01 944 951 1036 1036 1033 1031 1078 1076 1074
1G 6D 124 948 962 979 948 954 969 986 961 967 973	1J 3F 051 946 911 902 991 943 911 902 985 986 942
99 C01 988 1003 951 954 962 975 960 966 971	75 C01 922 903 1020 981 965 947 1018 999 999
1G 6E 124 952 993 992 976 978 974 965 977 981 985	1J 3G 105 853 878 864 965 904 889 872 1011 972 935
99 C01 965 984 988 988 968 987 974 975 975	85 C01 857 881 1029 988 945 937 1046 1003 964
1G 7F 124 1016 1010 994 1028 1002 987 980 1018 1002 987	1J 3B 105 855 883 867 951 937 900 885 981 966 952
99 C01 967 988 1013 1005 1005 1000 1012 1007 1003	89 C01 942 904 1016 1001 981 971 1031 1033 1013
1G 7G 124 946 955 939 966 958 957 958 999 988 969	1J 3C 091 940 897 853 922 953 911 902 1019 990 964
99 C01 955 951 994 977 963 946 997 968 977	79 C01 955 953 1031 1001 965 991 1046 1028 1017
1G 7H 124 938 943 947 943 946 948 950 957 960 963	1J 3D 074 925 905 896 980 946 930 915 1038 1004 968
99 C01 947 954 966 972 965 957 979 984 985	65 C01 949 934 1084 1046 1014 950 1134 1095 1059
1G 7C 124 946 953 960 929 947 959 967 935 954 967	1J 3E 074 928 904 882 984 937 918 882 1053 1001 949
99 C01 965 973 953 962 986 1001 946 975 992	65 C01 917 886 1079 1027 978 943 1105 1053 1008
1G 7D 124 942 974 986 949 968 997 1018 971 989 995	1J 3M 036 856 856 818 999 932 888 844 1106 1035 966
99 C01 1010 1018 975 980 986 1000 978 986 996	39 C01 918 873 1153 1082 1021 971 1202 1138 1077
1G 7E 124 1018 1020 1018 1005 1012 1017 1020 1010 1012 1013	1J 3J 052 862 825 797 959 899 865 833 1061 1000 936
99 C01 1013 1013 1008 1009 1010 1010 1006 1007 1008	45 C01 902 870 1095 1031 982 948 1130 1078 1032
1H 3F 105 927 903 882 975 950 906 896 996 970 947	1J 3N 038 860 822 786 956 888 848 806 1059 988 919
85 C01 940 905 996 972 955 952 977 985 971	39 C01 873 829 1109 1036 976 929 1158 1096 1035
1H 3G 124 950 972 955 1020 955 977 964 1052 1025 1000	1J 3V 052 824 787 753 888 846 812 781 958 911 871
99 C01 966 973 1072 1045 1010 996 1093 1055 1020	1J 3W 051 840 810 984 942 903 871 1014 975 938
1H 3E 124 980 973 975 1000 985 982 972 1020 1009 998	1J 3X 074 866 850 835 945 896 879 849 1030 977 926
99 C01 968 977 1048 1037 1027 1017 1078 1068 1058	69 C01 854 863 1047 957 966 927 1069 1028 991
1H 3C 105 869 883 878 941 907 902 905 964 955 947	1J 3R 074 881 863 845 928 908 889 864 979 957 937
85 C01 929 935 979 970 970 980 945 994 995	69 C01 910 884 1032 1013 960 952 1091 1057 1027
1H 3D 091 904 903 927 941 925 924 921 969 960 945	1J 3S 052 849 806 765 918 818 826 805 991 938 888
75 C01 941 938 959 985 968 965 1023 1003 985	49 C01 867 848 1008 954 927 907 1024 996 969
1H 3E 091 944 928 936 968 947 932 914 983 969 952	1J 3I 038 830 602 776 934 669 839 810 1044 976 910
79 C01 934 916 1003 988 974 961 1026 1010 995	35 C01 877 846 1092 1023 967 932 1140 1082 1025
1H 4F 124 1047 1022 999 1068 1039 1017 1009 1091 1062 1034	1J 3U 038 840 805 772 927 872 836 790 1023 964 908
99 C01 1026 1019 1126 1071 1058 1051 1129 1118 1108	39 C01 859 811 1082 1022 968 918 1142 1086 1030
1H 4G 124 974 962 950 1003 974 962 956 1015 996 980	1J 4F 064 909 874 841 981 931 896 878 1060 1004 951
99 C01 960 974 1030 1011 989 981 1045 1021 998	95 C01 932 917 1097 1041 957 977 1134 1087 1044
1H 4E 124 951 947 943 963 960 956 956 989 986 965	1J 4G 074 716 767 758 830 803 796 781 885 854 826
99 C01 970 970 1003 1007 1008 1036 1036 1032 1028	65 C01 814 802 908 877 855 841 933 908 886
1H 4C 124 967 987 988 1009 1001 1001 1023 1030 1022 1014	1J 4B 051 918 906 894 959 945 934 931 989 980 970
99 C01 1036 1060 1050 1043 1054 1079 1072 1083 1097	75 C01 970 967 1042 1030 1019 1021 1099 1086 1073
1H 4D 105 918 925 942 966 955 969 957 991 979 968	1J 4C 074 868 860 853 925 905 896 900 982 964 943
85 C01 980 954 996 1008 1001 1013 1027 1019 1011	69 C01 946 951 1027 1006 1001 1006 1075 1066 1059
1H 4E 105 1009 1002 970 1033 1017 1010 1003 1036 1044 1028	1J 4D 052 815 813 812 880 858 856 866 950 925 903
85 C01 1021 1014 1064 1047 1038 1032 1091 1083 1074	49 C01 911 922 1000 976 966 973 1053 1039 1028
1H 5F 124 1032 1013 997 1061 1035 1019 1013 1090 1064	1J 4M 038 828 822 818 923 887 880 880 1024 986 949
99 C01 1034 1029 1111 1087 1065 1060 1158 1136 1115	39 C01 946 945 1110 1071 1041 1037 1200 1167 1135
1H 5G 124 940 951 943 983 969 960 952 1014 1006 991	1J 4K 038 744 712 683 808 775 742 724 875 839 805
99 C01 962 962 1028 1010 992 983 1041 1020 1001	39 C01 786 768 929 893 861 840 988 954 920
1H 5E 124 946 945 944 958 954 953 955 972 968 964	1J 4M 038 825 790 757 924 869 833 800 1028 971 915
99 C01 965 967 994 991 985 986 1025 1027 1021	39 C01 880 845 1097 1039 988 951 1169 1115 1063
1H 5C 124 970 977 971 977 976 982 1003 992 991 990	1J 5F 074 956 927 900 1021 974 946 935 1087 1041 994
99 C01 1004 1015 1002 1001 1021 1037 1012 1032 1053	65 C01 962 971 1123 1074 1044 1022 1160 1128 1098
1H 5D 124 1039 1041 1046 1060 1057 1059 1076 1103 1102 1073	1J 5G 091 856 881 887 949 929 913 899 1000 980 960
99 C01 1089 1107 1131 1130 1125 1143 1160 1154 1149	79 C01 946 933 1039 1018 987 975 1080 1045 1013
1H 5E 105 956 953 949 990 988 986 979 1001 998	1J 5B 091 887 880 873 906 912 905 900 948 932 917
85 C01 989 982 1002 1024 1025 1017 1040 1031 1031	79 C01 912 907 1002 986 969 964 1051 1037 1022
1H 6F 124 1039 1022 1007 1070 1051 1036 1032 1099 1081 1064	1J 5C 074 818 814 808 855 845 841 848 896 886 875
99 C01 1060 1057 1143 1126 1125 1121 1161 1160 1158	65 C01 882 890 935 924 923 930 975 973 974

(CRD) OPERATING CHANNEL POWER FACTORS FOR A 115 DEGREE DRUM BANK POSITION (U)

INDEX NO.

E.7.7
Sheet 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>R. Rittenberger</i>	<i>D. M. Cutler</i>	

1J 5C C52	764	764	762	807	756	796	808	853	843	834
49 CC1	845	855	905	895	895	908	958	958	959	
1J 5J C38	858	845	833	932	904	850	880	1013	984	954
39 CC1	943	932	1097	1066	1041	1029	1184	1157	1131	
1J 5F C38	780	773	766	850	820	818	809	927	901	876
39 CC1	864	853	991	964	942	929	1059	1055	1013	
1J 5K C52	914	875	847	979	948	914	904	1050	1017	987
49 CC1	974	964	1100	1074	1069	1058	1170	1164	1158	
1J 6F C64	901	878	858	972	933	911	895	1045	1003	964
59 CC1	948	935	1082	1041	1011	995	1122	1090	1061	
1J 6G C51	915	906	898	978	952	943	935	1038	1010	985
75 CC1	978	970	1076	1048	1010	1010	1119	1080	1055	
1J 6H C91	879	872	868	913	907	901	898	920	922	910
75 CC1	912	908	988	982	970	907	1046	1030	1026	
1J 6C C74	796	797	796	829	835	836	848	858	804	870
69 CC1	882	895	895	901	912	926	935	940	959	
1J 6C C64	887	900	914	935	941	955	993	988	994	1000
59 CC1	1034	1070	1065	1071	1082	1116	1144	1153	1165	
1J 6H C38	737	755	775	797	803	823	835	864	869	875
39 CC1	884	856	954	958	960	969	1048	1049	1050	
1J 6K C38	752	734	718	816	793	776	764	884	859	837
39 CC1	825	814	953	929	905	893	1029	1004	979	
1J 7F C52	818	800	785	887	861	844	841	959	931	906
49 CC1	902	895	1007	981	960	957	1047	1041	1021	
1J 7G C74	827	822	817	881	862	857	855	941	920	902
69 CC1	859	897	990	969	946	943	1041	1015	992	
1J 7H C51	855	854	893	933	935	934	932	970	972	975
75 CC1	972	970	1033	1035	1033	1030	1101	1098	1096	
1J 7C C74	820	831	837	861	865	871	886	900	904	908
69 CC1	923	940	952	950	970	987	1007	1020	1036	
1J 7L C52	785	795	814	848	845	859	864	892	899	900
49 CC1	930	957	952	959	980	1005	1018	1058	1046	
1J 7H C38	823	837	852	905	856	910	926	994	984	975
39 CC1	985	1006	1093	1083	1085	1100	1197	1198	1200	
1J 7K C38	850	835	822	929	911	898	901	1015	956	980
39 CC1	964	988	1109	1092	1091	1095	1208	1207	1207	
1J 8F C38	766	754	746	828	817	807	803	891	881	872
39 CC1	865	868	971	963	967	965	1060	1064	1069	
1J 8G C64	859	858	857	931	911	910	908	1003	984	907
59 CC1	966	965	1067	1048	1036	1015	1133	1119	1107	
1J 8E C74	845	840	846	884	850	851	888	926	932	935
69 CC1	936	932	1009	1010	1015	1010	1099	1098	1101	
1J 8C C64	823	827	831	872	864	859	911	923	932	945
59 CC1	968	993	981	994	1023	1000	1040	1070	1108	
1J 8D C38	711	729	749	758	771	790	812	807	821	835
39 CC1	855	878	892	906	919	941	965	998	1011	
1J 9H C38	807	827	848	853	865	851	920	904	921	939
39 CC1	969	1000	1005	1024	1047	1079	1112	1136	1160	
1J 9K C52	820	845	871	872	852	918	948	925	946	970
49 CC1	959	1031	1017	1038	1057	1089	1113	1133	1155	
1J 9P C38	744	752	759	788	800	809	838	833	846	862
39 CC1	854	926	908	925	962	996	992	1030	1069	
1J 9F C74	879	875	874	905	907	906	919	934	936	940
69 CC1	956	972	981	990	1011	1028	1045	1063	1084	
1J 9G C51	860	863	866	899	891	894	877	919	910	902
79 CC1	900	911	951	941	938	942	981	974	968	
1J 9B C38	857	858	859	872	881	882	888	888	896	905
89 CC1	932	937	955	962	972	976	999	1009	1019	
1J 9C C65	854	906	918	939	948	950	978	957	966	970
89 CC1	955	1016	986	990	1026	1023	994	1024	1056	
1J 9D C51	922	951	973	955	966	984	1000	969	981	994
79 CC1	1009	1028	1017	1030	1039	1055	1069	1078	1087	
1J 9E C74	916	925	943	932	953	967	957	951	972	994
69 CC1	1030	1064	1008	1033	1066	1104	1076	1109	1146	
1J 9V C64	897	852	810	955	898	854	822	1017	950	901
59 CC1	867	835	1023	963	921	890	1031	987	944	
1J 9W C74	826	798	768	877	840	815	784	934	892	855
69 CC1	829	800	949	907	862	835	965	916	869	
1J 9R C74	858	836	813	897	872	848	826	939	912	880
69 CC1	860	837	977	949	918	892	1018	985	953	
1J 9S C52	815	771	732	879	825	782	760	943	888	836
49 CC1	810	787	951	897	860	835	961	921	885	
1J 9T C38	772	742	715	851	802	771	738	930	883	832
39 CC1	757	762	979	922	869	832	1021	962	907	
1J 9U C38	755	716	678	813	769	730	687	875	829	787
39 CC1	741	698	931	884	806	760	989	905	820	

(CRD) OPERATING CHANNEL POWER FACTORS FOR A 115 DEGREE DRUM BANK POSITION (U)	INDEX NO.
	E.7.7 Sheet 5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Rittenberg 7/2/62	DCM Rittenberg 7/2/62

(CRD) CALCULATED AVERAGE ELEMENT POWER FACTORS (U) AT 100 PERCENT POWER AND FLOW	INDEX NO
	E.7.8

REFERENCE

(CRD) PREDICTED POWER FACTOR FOR OPERATION AT FULL POWER,
CHANNEL TRAVERSE OOF8 TO J4M18 (CRD)

PREPARED BY

R. Rittenbayer 7/13/68

APPROVED BY

K. M. Litch 1/2/68

REFERENCE

(CRD) PREDICTED POWER FACTORS FOR OPERATION AT FULL POWER,
CHANNEL TRAVERSE OOF9 TO J5K18 (CRD)

PREPARED BY

R. Littleberger 7/30/68

APPROVED BY

D. M. Little 7/30

INDEX NO

E.7.10

E-44

REFERENCE

(CRD) PREDICTED POWER FACTORS FOR OPERATION AT FULL POWER,
CHANNEL TRAVERSE OOF10 TO J8D18 (CRD)

PREPARED BY

R. Rittenberger 7/31/58

APPROVED BY

D. M. Galt 7/30

REFERENCE

(CRD) PREDICTED POWER FACTORS FOR OPERATION AT FULL POWER, CHANNEL OOF12 TO J9T18 (CRD)

PREPARED BY
R. Rittenberger 7/21/54

APPROVED BY
E. M. Kitchin 7/20

INDEX NO

E.7.12

REFERENCE

INDEX NO

E 7 13

(CRD) COOLANT CHANNEL 10 POWER FACTORS AT 100 PERCENT
POWER VERSUS DRUM BANK POSITION (CRD)

PREPARED BY

R. R. Hinchey 7/31/68

APPROVED BY

D. M. Hatcher 7/30

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	R. Rittenberger 7/31/68

(CRD) PREDICTED XE-2 AXIAL POWER DISTRIBUTION AT 100 PERCENT POWER AND FLOW (U)	INDEX NO.
	E. 7. 14

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>sjm</i> 7/31/68	<i>MAC</i> 8/8/68	

SECTION F

(CRD) RADIATION AND SHIELDING (U)

(U) INTRODUCTION (U)

(U) This section of the Data Book contains data pertaining to nuclear radiation and shielding effects applicable to the XE-2 reactor configuration.

(U) The specific data sub-sections contain the following types of data:

1. Radiation heating rate data, which include heating rate distributions by material and region; prompt, delayed and total heating by material and region, and transient heating rate data.
2. Gamma ray dose rates at locations within the pressure vessel.
3. Fast neutron and thermal fluxes at locations within the pressure vessel.
4. Maximum integrated neutron levels (nvt) for various neutron energy thresholds on reactor components and maximum integrated gamma radiation levels on reactor components.
5. Description and radiation environment of WANL components external to the reactor.

(U) This introduction gives the general type of data presented in this section. The following sub-section starts with a detailed Table of Contents, which if scanned, can lead one to specific data.

(U) INTRODUCTION (U)	INDEX NO.
	F

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>JPH</i> 7/5/68	<i>MAC</i> 8/8/68	

SUB-SECTION F

XE-2
(CRD) RADIATION AND SHIELDING (U)

TABLE OF CONTENTS

<u>INDEX NO.</u>		<u>CROSS REFERENCE⁽¹⁾</u> <u>INDEX NO.</u>
*F.1	(U) Radiation Heating Rates within XE-2	
F.1.1	(U) Analytical Techniques	
F.1.2	(U) How to Use Radiation Heating Rate Data	
F.1.3	(U) Heating Rate Uncertainties	
*F.2	(CRD) Region Integral Heating Rates (U)	
F.2.1	(CRD) XE-2 Heating Rate Regions (U)	
F.2.2	(CRD) XE-2 Prompt and Decay Heating Rate by Region and Material at Full Power (Sheets 1, 2, 3, & 4) (U)	
F.2.3	(CRD) Effect of Facility Shield on XE-2 Heating Rates (U)	
F.2.4	(U) Heat Distribution by Region	
F.2.5	(U) Gamma and Beta Decay Power Released Following Reactor Runs at Full Power	
F.2.6	(U) Effect of Drum Angle, α , on Radial Region Total Heating Rates	
F.2.7	(CRD) Maximum Increase in Reflector Heating Due to Carbon Loss in the Core (U)	
*F.3	(CRD) Heating Rate Distributions for XE-2 (U)	
F.3.1	(CRD) Radial Heating Rate Distribution - Region 1 - Core Support Block (U)	
F.3.2	(CRD) Average Axial Heating Rate Distribution - Region 1 - Core Support Block (U)	
F.3.3	(CRD) Radial Heating Rate Distribution - Region 2 - Reactor Core (U)	
F.3.4	(CRD) Average Axial Heating Rate Distribution - Region 2 - Reactor Core (Sheets 1 & 2) (U)	
F.3.5	(CRD) Radial Heating Rate Distribution - Region 3 - Filler Strip (U)	
F.3.6	(CRD) Average Axial Heating Rate Distribution - Region 3 - Filler Strip (U)	
F.3.7	(CRD) Radial Heating Rate Distribution - Region 4 - Lateral Support (U)	
F.3.8	(CRD) Average Axial Heating Rate Distribution - Region 4 - Lateral Support (U)	
F.3.9	(CRD) Radial Heating Rate Distribution - Region 5 - Beryllium Reflector (U)	
F.3.10	(CRD) Average Axial Heating Rate Distribution - Region 5 - Beryllium Reflector (Sheets 1 and 2) (U)	
F.3.11	(U) Azimuthal Heating Rate Distribution for Control Drum Vanes (Drums at 80°)	
F.3.12	(CRD) Radial Heating Rate Distribution - Region 6 - Pressure Vessel (U)	
F.3.13	(CRD) Average Axial Heating Rate Distribution - Region 6 - Pressure Vessel (U)	
F.3.14	(CRD) Radial Heating Rate Distribution - Region 7 - Lateral Support (Nozzle End) (U)	

* There are no data pages corresponding to these index numbers

(1) Data sheet will be found under Index No. entered in this column.

(U) TABLE OF CONTENTS (U)	INDEX NO.
	F

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>1jm</i> <i>7/31/68</i>	<i>MAC</i> <i>8/8/68</i>	

SUB-SECTION F

XE-2
(CRD) RADIATION AND SHIELDING (U)

TABLE OF CONTENTS

INDEX NO.

F.3.15	(CRD) Average Axial Heating Rate Distribution - Region 7 - Lateral Support (Nozzle End) (U)
F.3.16	(CRD) Radial Heating Rate Distribution - Region 8 - Reflector Support (Nozzle End) (U)
F.3.17	(CRD) Average Axial Heating Rate Distribution - Region 8 - Reflector Support (Nozzle End) (U)
F.3.18	(CRD) Radial Heating Rate Distribution - Region 9 - Reflector Support (Dome End) (U)
F.3.19	(CRD) Average Axial Heating Rate Distribution - Region 9 - Reflector Support (Dome End) (U)
F.3.20	(CRD) Radial Heating Rate Distribution - Region 10 - Actuator Shaft and Plenum Region (U)
F.3.21	(CRD) Average Axial Heating Rate Distribution - Region 10 - Actuator Shaft and Plenum Region (U)
F.3.22	(CRD) Radial Heating Rate Distribution - Region 11 - Suppressor Plate Region (U)
F.3.23	(CRD) Average Axial Heating Rate Distribution - Region 11 - Suppressor Plate Region (U)
F.3.24	(CRD) Radial Heating Rate Distribution - Region 12 - Support Plate (U)
F.3.25	(CRD) Average Axial Heating Rate Distribution - Region 12 - Support Plate (U)
F.3.26	(CRD) Radial Heating Rate Distribution - Region 13 - Support Plate (U)
F.3.27	(CRD) Average Axial Heating Rate Distribution - Region 13 - Support Plate (U)
F.3.28	(CRD) Radial Heating Rate Distribution - Region 14 - Support Plate (U)
F.3.29	(CRD) Average Axial Heating Rate Distribution - Region 14 - Support Plate (U)
F.3.30	(CRD) Radial Heating Rate Distribution - Region 15 - Support Plate (U)
F.3.31	(CRD) Average Axial Heating Rate Distribution - Region 15 - Support Plate (U)
F.3.32	(CRD) Radial Heating Rate Distribution - Region 16 - Core Axial Support Region (U)
F.3.33	(CRD) Average Axial Heating Rate Distribution - Region 16 - Core Axial Support Region (U)
F.3.34	(CRD) Radial Heating Rate Distribution - Region 17 - Aluminum Shield (U)
F.3.35	(CRD) Average Axial Heating Rate Distribution - Region 17 - Aluminum Shield (U)
F.3.36	(CRD) Radial Heating Rate Distribution - Region 18 - Aluminum Shield - Shaft Region (U)
F.3.37	(CRD) Average Axial Heating Rate Distribution - Region 18 - Aluminum Shield - Shaft Region (U)
F.3.38	(CRD) Radial Heating Rate Distribution - Region 19 - Dome End Support Ring to Flange Region (U)
F.3.39	(CRD) Average Axial Heating Rate Distribution - Region 19 - Dome End Support Ring to Flange Region (U)
F.3.40	(CRD) Average Radial Heating Rate Distribution - Region 20 - Pressure Vessel Dome (U)

(U) TABLE OF CONTENTS (U)	INDEX NO.
	F

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>8/8</i>	<i>1/31/68 MAC 8/8/68</i>	

SUB-SECTION F

XE-2
(CRD) RADIATION AND SHIELDING (U)

TABLE OF CONTENTS

INDEX NO.

F.3.41	(CRD) Axial Heating Rate Distribution - Region 20 - Pressure Vessel Dome (U)
F.3.42	(CRD) Average Radial Heating Rate Distribution - Region 21 - Flow Screen and Screen Support (U)
*F.4	(CRD) Neutron and Gamma Internal Radiation Environment (U)
F.4.1	(CRD) XE-2 Neutron Fluxes for $E > 2.87$ Mev for Various Radii (U)
F.4.2	(CRD) XE-2 Neutron Fluxes for $E > 1.0$ Mev for Various Radii (U)
F.4.3	(CRD) XE-2 Neutron Fluxes for $E > 0.1$ Mev for Various Radii (U)
F.4.4	(CRD) XE-2 Thermal Neutron Fluxes ($E < 1.86$ ev) for Various Radii (Sheets 1 and 2)(U)
F.4.5	(CRD) XE-2 Gamma Ray Dose Rates for Various Traverses Within the Pressure Vessel (U)
F.4.6	(CRD) Maximum Integrated Neutron Flux Levels on XE-2 Components (nvt) Per MW-SEC Sheets 1 through 2) (U)
F.4.7	(CRD) Maximum Integrated Neutron Flux Levels on XE-2 Components (nvt) (Full Power for 60 Minutes) (Sheets 1 through 3) (U)
F.4.8	(CRD) Maximum Integrated Gamma Radiation Levels on XE-2 Components (Sheets 1 through 3) (U)
*F.5	(U) External Radiation Environment
F.5.1	(U) Schematic Diagram of ETS-1 Facility Showing Location of WANL Components External to the Reactor
F.5.2	(U) XE-2 Maximum Radiation Environment at WANL Components for Full Power Conditions
F.5.3	(U) Uncertainty Factors for External Environment
*F.6	(U) Engine Mounted Neutron Detector System
F.6.1	(U) EMND Description and Radiation Environment
*F.7	(U) Neutronics Canister
F.7.1	(U) Neutronics Canister Description and Radiation Environment
F.7.2	(U) Startup Detector Response as a Function of Position in the ETS-1 Side Shield Neutronics Canister
F.7.3	(U) Startup Detector Response to a Neutron Check Source in the ETS-1 Side Shield Neutronics Canister
F.7.4	(U) Thermal Neutron Flux as a Function of Position in the ETS-1 Side Shield Neutronics Canister
F.7.5	(U) Gamma Ray Heating Rate as a Function of Position in the ETS-1 Side Shield Neutronics Canister
F.7.6	(U) WX-5362 Detector Response as a Function of Position in the ETS-1 Side Shield Neutronics Canister

(U) TABLE OF CONTENTS)	INDEX NO.
	F

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>MAC 8/8/68</i>	<i>MAC 8/8/68</i>	

<u>CODE</u>	<u>APPLICATION</u>	<u>REFERENCE</u>
NSDM-III	Neutron Cross Sections for ODD-K and TAPAT	WANL-TME-1091
TPXS	Photon Cross Sections for ODD-K and TAPAT	Unpublished
S-4 (Revised)	Fission Product Energy Release Code	Unpublished
ODD-K	Two-Dimensional Neutron and Photon Transport Code - Multigroup Neutron & Photon Fluxes	WANL-PR(LL)-010 Volume 6
NAGS	Neutron Flux and Gamma Ray Source Edit	WANL-PR(LL)-010 Volume 7
TAPAT	One-Dimensional Neutron and Photon Transport Code - Internal Heating Rates and External Environment	WANL-PR(LL)-010 Volume 3
FASTER	Solution of Transport Equation Using Random Sampling, External Environment	WANL-PR(LL)-010 Volume 9
EXPERIMENTAL DATA	External Environment	---

NOTE: Heating rates for the XE-2 were obtained by adjusting the heating rates for the NRX-A5 (WANL-TME-1389) using one-dimensional transport calculations to determine the effects of the facility shield. A general discussion of the techniques used can be found in WANL-TME-1466, Second Status Report, "Shielding Standard Design Method," 1 January 1967.

(U) ANALYTICAL TECHNIQUES FOR RADIATION ANALYSIS (U)	INDEX NO.
	F.1.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>dfm</i> <i>7/31/68</i>	<i>MAC 8/1/68</i>	

(U) The figure indexed F.2.1 illustrates 21 regions in the XE-2 for which heating rates are presented. For most of the regions two sets of curves are given. The first set presents the relative distribution of the heating rate in each important material in the region as a function of radial position in the region. The radial distributions have been normalized such that the area weighted average equals one. The second set of curves for each region shows the axial distribution of the heating rate in each important material in the Region. These curves give the radially averaged heating rate as a function of axial position in units of Btu/hr-in.³ where the in.³ refers to solid material with densities as shown on the figures.

(U) In order to compute the heating rate at any space point in a region, one simply multiplies the value from the axial distributions corresponding to the Z plane of interest by the value from the radial distributions for the values of interest.

(U) The total heating rate in any region can be calculated as follows:

$$H_T = \sum_m \frac{W_m \int_{Z_L}^{Z_U} H_m(Z) dZ}{\rho_m (Z_U - Z_L)}$$

where:

- H_T = total heat in a region in Btu/hr
 Z_U, Z_L = lower and upper axial boundaries of region in inches, respectively
 $H_m(Z)$ = radially averaged axial heating rate in material as given in Section F.3
 W_m = weight of material in lbs. given in F.2.2
 ρ_m = material density in lbs/in.³ given in the distribution figures

(U) Three exceptions should be noted: Region 20, the pressure vessel dome, Region 21, the flow screen and screen support, and the boral vane data in Region 5.

(U) Figures F.3.40 and F.3.41 present, respectively, for Region 20, the average radial heating rate distribution and relative axial heating rate distribution. The axial distribution presented here is for the pressure vessel centerline. Since the axial thickness of the pressure vessel dome is not constant, the total heat in Region 20 cannot be obtained from the distribution curves using the equation given above. However, the total heat for Region 20 was obtained from the computer code output data pertinent to the many regions required to describe the pressure vessel dome.

(U) Figure F.3.42 presents the average radial heating rate distribution in the flow screen and screen support region. No axial distribution is given for this region since the region is sufficiently thin in the axial direction to effect a negligible decrease in the axial heating rate.

(U) For the boral vane in Region 5, no radial distribution is given. Instead, the relative distribution of the heating in the vane as a function of azimuth angle is presented in Figure F.3.11.

(U) HOW TO USE RADIATION HEATING RATE DATA (U)	INDEX NO.
	F.1.2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	J/m 3/8/68	MAC 3/8/68	

THIS PAGE UNCLASSIFIED

It is difficult to assess the uncertainty in heating rates in the XE-2 for each particular region for several reasons:

1. These heating rate data were obtained by adjusting NRX-A5 data to add the contribution from the ETS-1 facility shield due to scattering and secondary radiation. The accuracy of the facility shield contribution is unknown since no verification of the analytical techniques by experimental data has been made.

2. As noted in WANL-TME-1389, the A5 heating rates in all regions (except the reactor core, filler strip, cluster plate, and support block) were multiplied by a factor of 1.235, thus adjusting the average heating rates in these regions to correspond to NRX-A2 measured data. The adjustment, however, is based on the total heating in all regions noted above and does not account for the fact that in a particular region, heating could be over-predicted, while in another region, the heating could be under-predicted.

3. The heating rate analysis for the NRX-A2, A3, and A5 reactors did not include the effects on reactor internal environment of the privy roof shield or external structure. This contribution may have accounted for part of the 23.5% discrepancy noted above for the NRX-A2 test.

Hence the present data, on a gross basis, are expected to be an over-prediction of reactor internal environment by as much as 10% in regions other than core, filler strip, cluster plate, and support block

(U) HEATING RATE UNCERTAINTIES (U)	INDEX NO.
	F.1.3

REFERENCE

Astronautical
Laboratory

605950-229A

NOTE: DIMENSIONS FOR THESE REGIONS ARE GIVEN ON
FIGURES F.3.1 THROUGH F.3.42. DIMENSIONS
APPLY TO FULL POWER CONDITIONS.

INDEX NO. F.2.1	(CRD) XE-2 HEATING RATE REGIONS (U)	PREPARED BY <i>o b n 7/31/68</i>	APPROVED BY <i>m e c 8/8/68</i>

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>JAH</i> 7/31/68	<i>MAC</i> 8/8/68	

Region Number (1)	Region Volume (2) (in ³)	Material	Material Weight (lbs)	HEATING RATE			
				Btu/hr			MW
				Prompt ⁽³⁾	Delayed ⁽⁴⁾	Total	Total
1	2.15 (3) ^α	Carbon	8.79 (1)	1.06 (6)	2.57 (5)	1.32 (6)	3.86 (-1)
		Niobium	2.09 (1)	1.76 (5)	6.57 (4)	2.42 (5)	7.08 (-2)
		Inconel-X	2.93 (0)	2.33 (4)	8.74 (3)	3.20 (4)	9.38 (-3)
		Steel	5.42 (-1)	4.30 (3)	1.62 (3)	5.94 (3)	1.74 (-3)
		Molybdenum	3.19 (0)	2.76 (4)	1.03 (4)	3.79 (4)	1.11 (-2)
		Hydrogen		4.03 (3) ^β		4.03 (3)	1.18 (-3)
		Total	1.15 (2)	1.30 (6)	3.43 (5)	1.64 (6)	4.80 (-1)
2	4.95 (4)	Fuel Element	2.41 (3)	3.49 (9)	1.70 (8)	3.66 (9)	1.073 (3)
		Unfueled Graphite	4.31 (2)	3.44 (7)	9.00 (6)	4.34 (7)	1.27 (1)
		Inconel-X	4.29 (1)	2.34 (6)	9.10 (5)	3.25 (6)	9.52 (-1)
		Steel	1.80 (1)	9.69 (5)	3.81 (5)	1.35 (6)	3.96 (-1)
		Tantalum Carbide	2.59 (1)	2.70 (6)	9.20 (5)	3.62 (6)	1.06 (0)
		Hydrogen		1.51 (6) ^β		1.51 (6)	4.40 (-1)
		Total	2.93 (3)	3.54 (9)	1.81 (8)	3.72 (9)	1.088 (3)
3	3.24 (3)	Carbon	2.24 (2)	8.16 (6)	1.94 (6)	1.01 (7)	2.96 (0)
4	1.31 (4)	Carbon ^δ	6.70 (2) ^δ	2.10 (7)	4.87 (6)	2.59 (7)	7.59 (0)
		Steel	2.57 (1)	5.60 (5)	2.04 (5)	7.64 (5)	2.24 (-1)
		Aluminum	2.23 (1)	4.96 (5)	1.61 (5)	6.57 (5)	1.92 (-1)
		Hydrogen		5.33 (5) ^β		5.33 (5)	1.56 (-1)
		Total	7.18 (2)	2.26 (7)	5.24 (6)	2.78 (7)	8.16 (0)
5	3.38 (4)	Beryllium	2.03 (3)	2.83 (7)	5.97 (6)	3.43 (7)	1.00 (1)
		Aluminum	4.40 (1)	4.67 (5)	1.48 (5)	6.15 (5)	1.80 (-1)
		Titanium	5.98 (1)	6.12 (5)	2.07 (5)	8.19 (5)	2.40 (-1)
		Boral	1.13 (1)	9.06 (6) ^ε	3.71 (4)	9.10 (6)	2.67 (0)
		Hydrogen		2.28 (5) ^β		2.28 (5)	6.67 (-2)
		Total	2.15 (3)	3.87 (7)	6.34 (6)	4.51 (7)	1.32 (1)

- (1) See figure F.2.1 for regions
(2) Volume is for full power conditions
(3) Energy released instantaneously with fission
(4) Based on a 13 minute run at full power

α Read 2.15 (3) as 2.15×10^3
β Refers to neutron heating in hydrogen

δ Includes Silica
ε Includes heating due to (n, α) reaction

(CRD) XE-2 PROMPT AND DECAY HEATING RATE BY REGION AND MATERIALS
AT FULL POWER (1120 MW THERMAL) (U)

INDEX NO.

F.2.2
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	SAF 7/31/68	mac 7/8/68	

Region Number (1)	Region Volume (2) (in. ³)	Material	Material Weight (lbs)	HEATING RATE			
				Btu/hr			MW
				Prompt ⁽³⁾	Delayed ⁽⁴⁾	Total	Total
6	7.37 (3)	Aluminum	7.51 (2)	3.82 (6)	1.09 (6)	4.91 (6)	1.44 (0)
7	7.10 (2)	Aluminum	1.99 (0)	1.09 (4)	2.93 (3)	1.39 (4)	4.06 (-3)
		Inconel-X	3.26 (0)	1.75 (4)	5.02 (3)	2.24 (4)	6.56 (-3)
		Carbon δ	2.84 (1)	2.05 (5)	4.32 (4)	2.48 (5)	7.28 (-3)
		Hydrogen		1.51 (4) β		1.51 (4)	4.43 (-3)
		Total	3.37 (1)	2.48 (5)	5.12 (4)	2.99 (5)	8.78 (-2)
8	1.47 (3)	Aluminum	5.00 (0)	1.88 (4)	4.87 (3)	2.37 (4)	6.92 (-3)
		Inconel-X	3.75 (0)	1.34 (4)	3.64 (3)	1.70 (4)	4.97 (-3)
		Steel	1.21 (1)	4.45 (4)	1.23 (4)	5.68 (4)	1.66 (-2)
		Titanium	3.55 (1)	1.51 (5)	3.60 (4)	1.87 (5)	5.53 (-2)
		Hydrogen		3.12 (4) β		3.12 (4)	9.13 (-3)
9	3.23 (2)	Total	5.62 (1)	2.59 (5)	5.68 (4)	3.16 (5)	9.29 (-2)
		Aluminum	2.18 (0)	1.84 (4)	3.04 (3)	2.15 (4)	6.31 (-3)
		Titanium	3.56 (1)	3.04 (5)	5.20 (4)	3.55 (5)	1.04 (-1)
		Hydrogen		2.33 (3) β		2.33 (3)	7.43 (-4)
		Total	3.78 (1)	3.25 (5)	5.50 (4)	3.79 (5)	1.11 (-1)
10	3.77 (3)	Aluminum	4.17 (0)	2.26 (4)	2.97 (3)	2.55 (4)	7.49 (-3)
		Titanium	1.11 (1)	6.26 (4)	8.49 (3)	7.11 (4)	2.08 (-2)
		Steel	3.86 (1)	2.12 (5)	2.97 (4)	2.41 (5)	7.07 (-2)
		Hydrogen		1.09 (5) β		1.09 (5)	3.20 (-2)
		Total	5.39 (1)	4.06 (5)	4.12 (4)	4.47 (5)	1.31 (-1)
11	1.04 (3)	Inconel-X	1.14 (0)	2.99 (4)	5.95 (3)	3.59 (4)	1.05 (-2)
		Steel	2.48 (1)	6.30 (5)	1.28 (5)	7.58 (5)	2.22 (-1)
		Aluminum	5.48 (0)	1.51 (5)	2.74 (4)	1.78 (5)	5.21 (-2)
		Ag-In-Cd	2.59 (1)	7.66 (5)	1.49 (5)	9.15 (5)	2.68 (-1)
		Hydrogen		1.52 (5) β		1.52 (5)	4.45 (-2)
		Total	5.73 (1)	1.73 (6)	3.10 (5)	2.04 (6)	5.97 (-1)

- (1) See figure F.2.1 for regions
 (2) Volume is for full power conditions
 (3) Energy released instantaneously with fission
 (4) Based on a 13 minute run at full power

β Refers to neutron heating in hydrogen
 δ Includes Silica

(CRD) XE-2 PROMPT AND DECAY HEATING RATE BY REGION AND MATERIALS AT FULL POWER (1120 MW THERMAL) (U)	INDEX NO.
	F.2.2
	Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>SAH</i> 7/31/68	<i>MEC</i> 8/8/68	

Region Number (1)	Region Volume (2) (in ³)	Material	Material Weight (lbs)	HEATING RATE			
				Btu/hr			MW
				Prompt (3)	Delayed (4)	Total	Total
12	5.55 (2)	Aluminum	3.02 (1)	4.93 (5)	9.95 (4)	5.93 (5)	1.73 (-1)
		Inconel-X	8.00 (-1)	1.23 (4)	2.74 (3)	1.51 (4)	4.42 (-3)
		Steel	7.18 (0)	1.11 (5)	2.44 (4)	1.35 (5)	3.95 (-2)
		Hydrogen		3.99 (4) ^β		3.99 (4)	1.17 (-2)
		Total	3.82 (1)	6.56 (5)	1.27 (5)	7.83 (5)	2.29 (-1)
13	1.46 (3)	Aluminum	7.94 (1)	1.20 (6)	2.31 (5)	1.43 (6)	4.19 (-1)
		Inconel-X	2.10 (0)	3.03 (4)	6.41 (3)	3.67 (4)	1.07 (-2)
		Steel	1.89 (1)	2.70 (5)	5.75 (4)	3.28 (5)	9.60 (-2)
		Hydrogen		9.56 (4) ^β		9.56 (4)	2.80 (-2)
		Total	1.00 (2)	1.59 (6)	2.95 (5)	1.89 (6)	5.54 (-1)
14	1.27 (3)	Aluminum	6.95 (1)	9.35 (5)	1.79 (5)	1.12 (6)	3.26 (-1)
		Inconel-X	1.84 (0)	2.34 (4)	4.88 (3)	2.83 (4)	8.29 (-3)
		Steel	1.65 (1)	2.10 (5)	4.38 (4)	2.54 (5)	7.45 (-2)
		Hydrogen		7.00 (4) ^β		7.00 (4)	2.05 (-2)
		Total	8.78 (1)	1.24 (6)	2.28 (5)	1.47 (6)	4.29 (-1)
15	1.43 (3)	Aluminum	7.82 (1)	8.82 (5)	1.48 (5)	1.03 (6)	3.03 (-1)
		Inconel-X	2.06 (0)	2.22 (4)	4.08 (3)	2.63 (4)	7.70 (-3)
		Steel	1.86 (1)	2.02 (5)	3.64 (4)	2.38 (5)	6.95 (-2)
		Hydrogen		5.54 (4) ^β		5.54 (4)	1.62 (-2)
		Total	9.89 (1)	1.16 (6)	1.88 (5)	1.35 (6)	3.96 (-1)
16	1.29 (3)	Aluminum	4.39 (1)	4.23 (5)	6.60 (4)	4.89 (5)	1.43 (-1)
		Steel	4.30 (1)	4.07 (5)	6.78 (4)	4.75 (5)	1.39 (-1)
		Titanium	1.90 (1)	1.83 (5)	3.01 (4)	2.13 (5)	6.27 (-2)
		Inconel-X	1.37 (0)	1.29 (4)	2.02 (3)	1.49 (4)	4.39 (-3)
		Hydrogen		4.49 (4) ^β		4.49 (4)	1.32 (-2)
		Total	1.07 (2)	1.07 (6)	1.66 (5)	1.24 (6)	3.62 (-1)

(1) See figure F.2.1 for regions

(2) Volume is for full power conditions

(3) Energy released instantaneously with fission

(4) Based on a 13 minute run at full power

β Refers to neutron heating in hydrogen

(CRD) XE-2 PROMPT AND DECAY HEATING RATE BY REGION AND MATERIALS
AT FULL POWER (1120 MW THERMAL) (U)

INDEX NO.

F.2.2

Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>SJM</i> 7/31/68	<i>mac</i> 8/8/68	

Region Number (1)	Region Volume (2) (in. ³)	Material	Material Weight (lbs)	HEATING RATE			
				Btu/hr			MW
				Prompt ⁽³⁾	Delayed ⁽⁴⁾	Total	Total
17	1.41 (4) ^θ	Aluminum	1.34 (3)	2.42 (6)	3.33 (5)	2.75 (6)	8.04 (-1)
		Hydrogen		1.77 (4) ^β		1.77 (4)	5.18 (-3)
		Total	1.34 (3)	2.44 (6)	3.33 (5)	2.77 (6)	8.09 (-1)
18	1.05 (4)	Aluminum	9.21 (2)	3.76 (6)	4.86 (5)	4.26 (6)	1.25 (0)
		Steel	5.10 (1)	1.85 (5)	2.46 (4)	2.09 (5)	6.14 (-2)
		Hydrogen		1.58 (4) ^β		1.58 (4)	4.59 (-3)
		Total	9.72 (2)	3.96 (6)	5.11 (5)	4.48 (6)	1.32 (0)
19	8.09 (2)	Titanium	9.75 (2)	5.54 (5)	7.83 (4)	6.34 (5)	1.85 (-1)
20		Aluminum		3.84 (4)	4.94 (3)	4.34 (4)	1.27 (-2)
21		Steel	3.15 (1)	2.00 (5)	3.68 (4)	2.37 (5)	6.95 (-2)
		Total	1.00 (4)	3.63 (9)	1.98 (8)	3.83 (9)	1.12 (3)

- (1) See figure F.2.1 for regions
 (2) Volume is for full power conditions
 (3) Energy released instantaneously with fission
 (4) Based on a 13 minute run at full power

β Refers to neutron heating in hydrogen
 θ Read 1.41 (4) as 1.41×10^4

(CRD) XE-2 PROMPT AND DECAY HEATING RATE BY REGION AND MATERIALS AT FULL POWER (1120 MW THERMAL) (U)	INDEX NO.
	F.2.2 Sheet 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>6/77 7/2/48</i>	<i>mac 8/8/68</i>	

EFFECT OF THE FACILITY SHIELD ON XE-2 HEATING RATES

Region Number (1)	HEATING RATE MW		Percent Change
	Shielded	Unshielded	
1	4.80 (-1)	4.80 (-1)	0
2	1.088 (3) ⁽²⁾	1.090 (3)	-0.2 ⁽²⁾
3	2.96 (0)	2.96 (0)	0
4	8.16 (0)	8.11 (0)	0.6
5	1.32 (1)	1.29 (1)	2.3
6	1.44 (0)	1.27 (0)	13.4
7	8.78 (-2)	8.63 (-2)	1.7
8	9.29 (-2)	8.97 (-2)	3.5
9	1.11 (-1)	1.01 (-1)	9.9
10	1.31 (-1)	1.22 (-1)	7.4
11	5.97 (-1)	5.97 (-1)	0
12	2.29 (-1)	2.29 (-1)	0
13	5.54 (-1)	5.54 (-1)	0
14	4.29 (-1)	4.29 (-1)	0
15	3.96 (-1)	3.96 (-1)	0
16	3.62 (-1)	3.02 (-1)	19.9
17	8.09 (-1)	7.82 (-1)	3.5
18	1.32 (0)	5.28 (-1)	150.0
19	1.85 (-1)	7.95 (-2)	133.0
20	1.27 (-2)	5.93 (-3)	114.0
21	6.95 (-2)	6.95 (-2)	0
Total - All Regions	1.120 (3)	1.120 (3)	
Total - Non Core Regions	31.74	30.09	5.5

(1) Refer to figure F.2.1 for region location.

(2) 2 MW removed from core region to adjust total to 1120 MW.

(CRD)EFFECT OF THE FACILITY SHIELD ON XE-2 HEATING RATES (U)	INDEX NO
	F.2.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>djm 7/3/68</i>	<i>mac 8/8/68</i>	

THIS PAGE UNCLASSIFIED

Region Number*	Percent of Power Generated	
	Prompt Power ⁽¹⁾	Delayed Power ⁽²⁾
1	0.036	0.169
2	96.854	88.992
3	0.223	0.954
4	0.618	2.567
5	1.060	3.117
6	0.104	0.025
7	0.007	0.536
8	0.007	0.028
9	0.009	0.027
10	0.011	0.020
11	0.048	0.152
12	0.018	0.062
13	0.044	0.145
14	0.034	0.112
15	0.032	0.092
16	0.029	0.082
17	0.067	0.164
18	0.108	0.251
19	0.015	0.039
20	0.001	0.002
21	0.006	0.018
LEAKAGE	0.671	2.437
TOTAL	100.00	100.00

*Refer to Figure F.2.1 for region location

(1) Prompt power is that due to energy released instantaneously with fission.

(2) Delayed power is that associated with energy released by decaying fission fragments.

(U) HEAT DISTRIBUTION BY REGION XE-2 (U)	INDEX NO.
	F.2.4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>adm 7/31/68</i>	<i>mac 8/8/68</i>	

DECAY POWER * (WATTS)

<u>Time After Shutdown (secs)</u>	<u>1 sec. Operation</u>	<u>10 sec. Operation</u>	<u>100 sec. Operation</u>	<u>1000 sec. Operation</u>
0	8.28 (6)	2.74 (7)	4.88 (7)	6.50 (7)
1	4.85 (6)	2.01 (7)	4.06 (7)	5.67 (7)
2	3.17 (6)	1.61 (7)	3.58 (7)	5.19 (7)
3	2.41 (6)	1.38 (7)	3.28 (7)	4.87 (7)
4	1.97 (6)	1.21 (7)	3.04 (7)	4.63 (7)
5	1.67 (6)	1.09 (7)	2.85 (7)	4.44 (7)
6	1.47 (6)	9.83 (6)	2.70 (7)	4.27 (7)
7	1.31 (6)	8.96 (6)	2.56 (7)	4.12 (7)
8	1.18 (6)	8.22 (6)	2.43 (7)	3.99 (7)
9	1.08 (6)	7.56 (6)	2.32 (7)	3.87 (7)
1.0 (1)	9.92 (5)	6.98 (6)	2.22 (7)	3.77 (7)
2.5 (1)	3.71 (5)	3.14 (6)	1.41 (7)	2.86 (7)
5.0 (1)	1.75 (5)	1.60 (6)	9.23 (6)	2.24 (7)
1.0 (2)	8.28 (4)	7.87 (5)	5.47 (6)	1.67 (7)
2.5 (2)	2.89 (4)	2.83 (5)	2.38 (6)	1.03 (7)
5.0 (2)	1.30 (4)	1.29 (5)	1.17 (6)	6.57 (6)
1.0 (3)	5.89 (3)	5.86 (4)	5.55 (5)	3.76 (6)
2.5 (3)	1.88 (3)	1.88 (4)	1.84 (5)	1.52 (6)
5.0 (3)	7.93 (2)	7.92 (3)	7.84 (4)	7.67 (5)
1.0 (4)	3.49 (2)	3.48 (3)	3.46 (4)	3.27 (5)
2.5 (4)	1.04 (2)	1.04 (3)	1.04 (4)	1.01 (5)
5.0 (4)	4.17 (1)	4.17 (2)	4.16 (3)	4.11 (4)
8.64 (4) (1 day)	1.98 (1)	1.98 (2)	1.98 (3)	1.97 (4)
1.0 (5)	1.67 (1)	1.67 (2)	1.67 (3)	1.66 (4)
2.5 (5)	5.01 (0)	5.01 (1)	5.00 (2)	4.99 (3)
5.0 (5)	2.15 (0)	2.15 (1)	2.15 (2)	2.14 (3)
6.05 (5) (1 week)	1.72 (0)	1.72 (1)	1.72 (2)	1.71 (3)
1.0 (6)	9.57 (-1)	9.57 (0)	9.57 (1)	9.56 (2)
2.5 (6)	3.32 (-1)	3.32 (0)	3.32 (1)	3.32 (2)
2.59 (6) (1 month)	3.00 (-1)	3.00 (0)	3.00 (1)	3.00 (2)
5.0 (6)	1.36 (-1)	1.36 (0)	1.36 (1)	1.36 (2)
1.0 (7)	5.28 (-2)	5.21 (-1)	5.20 (0)	5.20 (1)
2.5 (7)	1.18 (-2)	1.18 (-1)	1.18 (0)	1.18 (1)
5.0 (7)	3.85 (-3)	3.85 (-2)	3.85 (-1)	3.85 (0)

*This power includes only power generated by decay gammas and decay betas. It does not include power generated by delayed neutrons.

(U) GAMMA AND BETA DECAY POWER RELEASED FOLLOWING REACTOR RUNS AT FULL POWER (1120 THERMAL MEGAWATTS MAINTAINED OVER LENGTH OF RUN) (U)	INDEX NO.
	F. 2. 5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>sjm</i> 7/31/68	<i>mac</i> 8/8/68	

Relative Heating Rate Ratio* vs. Drum Angle α

Region	$\alpha = 60^\circ$	$\alpha = 90^\circ$	$\alpha = 115^\circ$	$\alpha = 150^\circ$
Unfueled Elements and Tie Rods	1.004	1.0	0.980	0.971
Filler Strips	0.959	1.0	1.021	1.044
Seal Segments	0.959	1.0	1.021	1.044
Be Reflector	0.963	1.0	1.018	1.048
Boron Vane (N-a)	1.139	1.0	0.867	0.715
Pressure Vessel	0.951	1.0	1.031	1.072

* Ratio of $\frac{\text{Heating rate at } \alpha}{\text{Heating rate at } \alpha = 90^\circ}$

Note: For a more detailed analysis of vane heating as a function of drum angle, see Figures F.3.10 and F.3.11.

(U) EFFECT OF DRUM ANGLE, α , ON RADIAL REGION TOTAL HEATING RATES (U)	INDEX NO.
	F. 2. 6

REFERENCE

F-17

INDEX NO
F.2.7

(CRD) MAXIMUM INCREASE IN REFLECTOR HEATING RATE DUE TO CARBON LOSS FROM THE CORE (U)

PREPARED BY

lfn 7/31/61

APPROVED BY

mac 8/8/68

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>JPM 7/31/68</i>	<i>MAC 8/8/68</i>

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 1 - CORE SUPPORT BLOCK - XE-2 (U)
(REFER TO FIGURE F.2.1 FOR REGION LOCATION)

INDEX NO.

F.3.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>SPM 7/3/68</i>	<i>MAC 8/8/68</i>

(U) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 1 - CORE SUPPORT BLOCK - XE-2 (U)
 (REFER TO FIGURE F.2.1 FOR REGION LOCATION)

INDEX NO

F.3.2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>dfm 7/31/68</i>	<i>MAC 8/8/68</i>

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 2 - REACTOR CORE - XE-2 (U)
(REFER TO FIGURE F.2.1 FOR REGION LOCATION)

INDEX NO

F.3.3

CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>sdm 7/3/68</i>	<i>mac 8/8/68</i>

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 2 - REACTOR CORE - XE-2 (U)
 (REFER TO FIGURE F 2.1 FOR REGION LOCATION)

INDEX NO

F 3.4
 Sheet 1

CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	1671 7/31/68	MGC 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 2 - REACTOR CORE - XE-2 (U)
(REFER TO FIGURE F.2.1 FOR REGION LOCATION)

INDEX NO

F 3.4
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	g & m 7/31/68	mac 8/8/68

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 3 - FILLER STRIP - XE-2 (U)
(REFER TO FIGURE F.2.1 FOR REGION LOCATION)

INDEX NO.

F.3.5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	6 J M 7/31/68	mac 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 3 - FILLER STRIP - XE-2 (U)
(REFER TO FIGURE F.2.1 FOR REGION LOCATION)

INDEX NO

F.3.6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	sgm 7/31/68	mac 7/8/68

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 4 - LATERAL SUPPORT - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.7

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	847 7/31/68	mac 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 4 - LATERAL SUPPORT - XE-2
(REFER TO FIGURE 2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.8

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>jam</i> 7/3/68	<i>mac</i> 8/2/68

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 5 - BERYLLIUM REFLECTOR - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO

F.3.9

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	SLM 7/31/68	MAC 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 5 - BERYLLIUM REFLECTOR XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)	INDEX NO
	F.3.10 SHEET 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	dfm 7/3/68	mac 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 5 - BERYLLIUM REFLECTOR - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO

F 3.10
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	sfm 7/31/68	mac 8/8/68	

THIS PAGE UNCLASSIFIED

(U) AZIMUTHAL HEATING RATE DISTRIBUTION FOR CONTROL DRUM VANES FOR A DRUM ANGLE OF 80 DEGREES (U)	INDEX NO
	F.3.11

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	lpm 7/31/68	mac 8/8/68

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 6 - PRESSURE VESSEL - XE-2 (U)
(REFER TO FIGURE F.2.1 FOR REGION LOCATION)

INDEX NO

F.3.12

REFERENCE		PREPARED BY	APPROVED BY	Astronautical Laboratory
		84-77 7/31/68	MCC 818/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 6 - PRESSURE VESSEL - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)	INDEX NO
	F.3.13

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>sfm</i> 7/31/68	<i>mac</i> 8/8/68

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 7 - LATERAL SUPPORT (NOZZLE END) - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION (U))

INDEX NO.

F.3.14

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>dfm</i> 7/31/68	<i>mac</i> 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 7 - LATERAL SUPPORT (NOZZLE END) - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO

F.3.15

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	lfn 7/31/68	mac 8/8/68

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 8 - REFLECTOR SUPPORT (NOZZLE END) - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)	INDEX NO.
	F.3.16

REFERENCE		Astronuclear Laboratory
-----------	--	---

APPROVED BY	mac 8/2/68
PREPARED BY	JM 7/31/68
(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 8 - REFLECTOR SUPPORT (NOZZLE END) - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)	

INDEX NO
F.3.17

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>jam</i> 7/31/68	<i>MAC</i> 8/8/68

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 9 - REFLECTOR SUPPORT (DOME END) - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.18

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	dfm 7/31/68	mac 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 9 - REFLECTOR SUPPORT (DOME END) - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)	INDEX NO.
	F.3.19

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>sfh</i> 7/21/68	<i>mac</i> 8/8/68

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 10 - ACTUATOR SHAFT AND PLENUM REGION - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.20

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	lfn 7/31/68	mac 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 10 - ACTUATOR SHAFT AND PLENUM
REGION XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO

F.3.21

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>sfm</i> 7/31/68	<i>mac</i> 8/13/68

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 11 - SUPPRESSOR PLATE REGION - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.22

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	dph 7/31/62	mgc 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 11 - SUPPRESSOR PLATE REGION - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.23

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	147 7/31/68	mac 8/3/68

(CRD) RADIAL HEATING RATE DISTRIBUTION — REGION 12 — SUPPORT PLATE — XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO

F.3.24

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	sfm 7/31/68	mac 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 12 - SUPPORT PLATE - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO

F.3.25

~~CONFIDENTIAL RESTRICTED DATA~~ Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	8pm 7/31/68	MGC 8/8/68

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 13 - SUPPORT PLATE - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.26

~~CONFIDENTIAL RESTRICTED DATA~~ Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>St M</i> 7/31/68	<i>mac</i> 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 13 - SUPPORT PLATE - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO

F.3.27

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	JFM 7/3/68	MGC 8/8/68

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 14 - SUPPORT PLATE - XE-2
REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.28

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	sfm 7/3/68	mac 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 14 - SUPPORT PLATE - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.29

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>dpm 7/31/68</i>	<i>MAC 8/3/68</i>

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 15 - SUPPORT PLATE - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.30

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>J. M. 7/31/68</i>	<i>MAC 8/8/68</i>

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 15 _ SUPPORT PLATE - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.31

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	SAH 7/31/68	MAC 8/8/68

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 16 - CORE AXIAL SUPPORT REGION - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO

F.3.32

REFERENCE	PREPARED BY <i>lfm 7/31/68</i>	APPROVED BY <i>mac 8/8/68</i>	Astronuclear Laboratory
-----------	-----------------------------------	----------------------------------	---

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 16 - CORE AXIAL SUPPORT REGION - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO

F.3.33

~~CONFIDENTIAL RESTRICTED DATA~~ Atomic Energy Act of 1954

REFERENCE

PREPARED BY

sgm 7/31/68

APPROVED BY

mac 8/8/68

Astronuclear
Laboratory

1 (CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 17 - ALUMINUM SHIELD - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION (U))

INDEX NO.

F.3.34

~~CONFIDENTIAL RESTRICTED DATA~~ Atomic Energy Act of 1954

REFERENCE	PREPARED BY <i>sdm 7/31/68</i>	APPROVED BY <i>mac 8/18/68</i>	Astronuclear Laboratory
-----------	-----------------------------------	-----------------------------------	--

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 17 - ALUMINUM SHIELD - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)	INDEX NO
	F.3.35

REFERENCE	PREPARED BY <i>SPM 7/31/68</i>	APPROVED BY <i>MGC 8/8/68</i>	Astronuclear Laboratory
-----------	-----------------------------------	----------------------------------	--

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 18 - ALUMINUM SHIELD - SHAFT REGION - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.36

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>SAH 7/31/68</i>	<i>MAC 8/8/68</i>

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 18 - ALUMINUM SHIELD - SHAFT REGION - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)	INDEX NO.
	F.3.37

REFERENCE	PREPARED BY JPM 7/3/68	APPROVED BY MAC 2/8/68	Astronuclear Laboratory

(CRD) RADIAL HEATING RATE DISTRIBUTION - REGION 19 - DOME END SUPPORT RING TO FLANGE
REGION - XE-2 (REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO.

F.3.38

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>8pm</i> 7/31/68	<i>MAC</i> 8/8/68

(CRD) AVERAGE AXIAL HEATING RATE DISTRIBUTION - REGION 19 - DOME END SUPPORT RING TO FLANGE REGION - XE-2 (REFER TO FIGURE F. 2.1 FOR REGION LOCATION) (U)	INDEX NO
	F. 3. 39

REFERENCE	PREPARED BY J & N 7/8/68	APPROVED BY MQC 8/8/68	Astronuclear Laboratory
-----------	-----------------------------	---------------------------	---

(CRD) AVERAGE RADIAL HEATING RATE DISTRIBUTION - REGION 20 - PRESSURE VESSEL DOME - XE-2
(REFER TO FIGURE F. 2.1 FOR REGION LOCATION) (U)

INDEX NO

F. 3. 40

REFERENCE	PREPARED BY JAM 7/31/68	APPROVED BY MAC 8/8/68	Astronuclear Laboratory

(CRD) AXIAL HEATING RATE DISTRIBUTION - REGION 20 - PRESSURE VESSEL DOME - XE-2
(REFER TO FIGURE F.2.1 FOR REGION LOCATION) (U)

INDEX NO

F.3.41

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	JLM 7/24/68	mac 8/8/68

(CRD) AVERAGE RADIAL HEATING RATE DISTRIBUTION - REGION 21 - FLOW SCREEN SUPPORT - XE-2 (REFER TO F. 2.1 FOR REGION LOCATION) (U)	INDEX NO
	F.3.42

REFERENCE

Astronuclear Laboratory

(CRD) XE-2 NEUTRON FLUXES FOR $E > 2.87$ MEX FOR VARIOUS RADII (U)

PREPARED BY	APPROVED BY
<i>h/h</i> 7/31/68	<i>mac</i> 8/8/68

INDEX NO.

F.4.1

(CRD) XE-2 NEUTRON FLUXES FOR E 1.0 MEV FOR VARIOUS RADII (U)

PREPARED BY	APPROVED BY
<i>4/3</i> <i>8/6/68</i>	<i>mac</i> <i>8/8/68</i>

REFERENCE

F-64

INDEX NO.
F.4.3

(CRD) XE-2 NEUTRON FLUXES FOR 0.1 MEV FOR VARIOUS RADII (U)

PREPARED BY	APPROVED BY
<i>1/1</i> <i>9/6/68</i>	<i>Mac</i> <i>8/8/68</i>

REFERENCE

(CRD) XE-2 THERMAL NEUTRON FLUXES FOR E 1.86 EV FOR VARIOUS RADII (U)

PREPARED BY

1/4

APPROVED BY

8/6/68

mac 8/8/68

INDEX NO.

F.4.4, Sheet 1

REFERENCE

NOTE: DATA ARE FOR FULL POWER CONDITIONS (1125 Mw THERMAL)

(CRD) XE-2 THERMAL NEUTRON FLUXES FOR E 1.86 EV FOR VARIOUS RADII

(U)

PREPARED BY

4/4 2/6/68

APPROVED BY

mac 2/8/68

INDEX NO.

F.4.4, Sheet 2

REFERENCE

(CRD) XE-2 GAMMA RAY DOSE RATES FOR VARIOUS RADIAL TRAVERSES WITHIN THE PRESSURE VESSEL (FULL POWER, 1120 MW THERMAL) (U)

PREPARED BY	APPROVED BY
<i>SLM</i> 7/3/68	<i>mac</i> 8/8/68

INDEX NO
F.4.5

~~CONFIDENTIAL RESTRICTED DATA~~ Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	JFM - 7/31/68	MAC 8/5/68	

Component	E>1.0 Mev	E>0.1 Mev	E>2.87 Mev	E<1.86 ev
1) Pressure Vessel	3.86 (10)	1.1 (11)	5.4 (9)	2.1 (11)
2) Dome	5.90 (9)	2.5 (10)	8.9 (8)	6.8 (10)
3) Shield	1.03 (11)	3.2 (11)	1.9 (10)	3.9 (11)
a) Shield Seal	1.03 (11)	3.0 (11)	1.7 (10)	2.4 (11)
4) Flow Screen	1.63 (11)	5.2 (11)	2.3 (10)	3.7 (11)
5) Outer Reflector				
a) Dome End Support Ring	1.29 (11)	4.1 (11)	2.0 (10)	2.3 (11)
b) Nozzle End Support Ring	8.6 (10)	2.6 (11)	1.6 (10)	1.8 (11)
c) Impedance Ring	8.6 (10)	2.6 (11)	1.6 (10)	1.8 (11)
d) Sector	5.68 (11)	1.7 (12)	8.5 (10)	1.6 (12)
e) Tie Bolt	1.29 (11)	4.1 (11)	1.7 (10)	5.9 (11)
6) Control Drum				
a) Beryllium Cylinder	4.90 (11)	1.6 (12)	7.4 (10)	1.5 (12)
b) Dome End Shaft Extension	1.29 (11)	4.1 (11)	2.0 (10)	2.3 (11)
c) Nozzle End Shaft Extension	8.6 (10)	2.6 (11)	1.6 (10)	1.8 (11)
d) Aluminum Housing	4.90 (11)	1.6 (12)	7.4 (10)	1.5 (12)
e) Spring	8.6 (10)	2.6 (11)	1.6 (10)	1.8 (11)
f) Plate Assembly	4.90 (11)	1.6 (12)	7.4 (10)	1.5 (12)
7) Bearing Housing				
a) Bearing	1.29 (11)	4.1 (11)	2.0 (10)	2.3 (11)
b) Coupling	1.29 (11)	4.1 (11)	2.0 (10)	2.3 (11)
c) Stop	1.29 (11)	4.1 (11)	2.0 (10)	2.3 (11)
d) Safety Spring	1.29 (11)	4.1 (11)	2.0 (10)	2.3 (11)
e) Drive Shaft	1.29 (11)	4.1 (11)	2.0 (10)	2.3 (11)
8) Core Assembly				
a) Support Plate	6.71 (11)	2.0 (12)	1.2 (11)	3.7 (11)
b) Dome End Seal	2.84 (11)	8.1 (11)	5.2 (10)	1.2 (11)
9) Clusters				
a) Liner Tube	3.70 (12)	1.0 (13)	7.8 (11)	1.2 (12)
b) Plate Assemblies	8.0 (11)	2.2 (12)	1.6 (11)	1.2 (11)
c) Preload Spring	6.71 (11)	2.0 (12)	1.2 (11)	9.2 (10)
d) Positioning Spring	9.46 (11)	2.6 (12)	1.9 (11)	1.5 (11)
e) Orifice Jets	8.43 (11)	2.4 (12)	1.7 (11)	1.3 (11)
f) Split Bushing	6.71 (11)	2.0 (12)	1.2 (11)	1.1 (11)
g) Tie Rod	3.70 (12)	1.0 (13)	7.8 (11)	1.2 (12)
h) Tie Rod Holder	5.42 (11)	1.6 (12)	9.3 (10)	1.9 (11)
i) Fuel Elements	3.70 (12)	1.0 (13)	7.8 (11)	8.1 (11)
j) Unfueled Elements	3.70 (12)	1.0 (13)	7.8 (11)	1.2 (12)
k) Keyed Elements	1.63 (12)	4.8 (12)	3.6 (11)	1.2 (12)
l) Support Blocks	5.42 (11)	1.5 (12)	1.1 (11)	1.5 (11)
m) Support Cone	3.18 (11)	8.9 (11)	6.3 (10)	8.2 (10)
n) Insulating Cup	3.18 (11)	8.9 (11)	6.3 (10)	8.2 (10)
o) Support Washer	3.18 (11)	8.9 (11)	6.3 (10)	8.2 (10)
p) Insulating and Countersunk Sleeves	3.70 (12)	1.1 (13)	7.8 (11)	1.2 (12)
q) Insulating Washer	3.18 (11)	8.9 (11)	6.3 (10)	8.2 (10)

Note: Numbers in parenthesis indicate powers of 10.

(CRD) MAXIMUM INTEGRATED NEUTRON FLUX LEVELS ON XE-2 COMPONENTS (nvt) (N/CM ² - MW - SEC) (U)	INDEX NO
	F.4.6
	- Sheet 1

~~CONFIDENTIAL RESTRICTED DATA~~ Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	J J M 7/31/68	Mac 8/8/68	

Component	E>1.0 Mev	E>0.1 Mev	E>2.87 Mev	E<1.86 ev
10) Filler Strip Assemblies				
a) Strips	1.38 (12)	4.1 (12)	2.9 (11)	1.4 (12)
b) Insulating Tiles	1.46 (12)	4.1 (12)	3.0 (11)	1.2 (12)
11) Filler Blocks	6.97 (11)	1.9 (12)	1.4 (11)	5.2 (11)
12) Fuel Cluster Nuts	3.18 (11)	1.0 (12)	5.2 (10)	2.9 (11)
13) Cluster Nut Locking Device	1.63 (11)	5.2 (11)	2.3 (10)	3.6 (11)
14) Core Band	6.71 (11)	1.8 (12)	1.3 (11)	5.6 (11)
15) Core Assembly Axial Support System				
a) Core Support Ring	1.29 (11)	4.4 (11)	1.9 (10)	2.1 (11)
b) Instrumentation Ring	1.03 (11)	3.1 (11)	1.7 (10)	2.1 (11)
c) Locking Devices	1.03 (11)	3.1 (11)	1.7 (10)	2.1 (11)
d) Spring Support Ring	1.29 (11)	4.4 (11)	1.9 (10)	1.9 (11)
e) Preload Springs and Retainers	2.75 (11)	7.8 (11)	4.8 (10)	1.5 (11)
f) Spring Bearing Ring	2.84 (11)	8.5 (11)	5.2 (10)	1.1 (11)
g) Tie Tube	2.84 (11)	8.5 (11)	5.2 (10)	2.1 (11)
16) Lateral Support System				
a) Graphite Cylinder	1.20 (12)	3.5 (12)	2.3 (11)	1.6 (12)
b) Seal and Retainer Segments	1.20 (12)	3.5 (12)	2.3 (11)	1.5 (12)
c) Plunger	1.20 (12)	3.5 (12)	2.3 (11)	1.5 (12)
d) Springs	6.36 (11)	2.0 (12)	1.0 (11)	1.6 (12)
e) Spring Bracket	6.36 (11)	2.0 (12)	1.0 (11)	1.6 (12)
f) Spring Retaining Screw	6.36 (11)	2.0 (12)	1.0 (11)	1.6 (12)
17) Nozzle Interface Seal	2.41 (11)	5.9 (11)	4.1 (10)	1.6 (11)

Note: Numbers in parenthesis indicate powers of 10.

(CRD) MAXIMUM INTEGRATED NEUTRON FLUX LEVELS ON XE-2 COMPONENTS (nvt) (N/CM ² - MW - SEC) (U)	INDEX NO.
	F. 4. 6 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>l j n</i> 7/31/68	<i>mac</i> 8/8/68	

Component		E>1.0 Mev	E>0.1 Mev	E>2.87 Mev	E<1.86 ev
1)	Pressure Vessel	1.58 (17)	4.4 (17)	2.3 (16)	8.2 (17)
2)	Dome	2.40 (16)	1.0 (17)	3.7 (15)	2.8 (17)
3)	Shield	4.30 (17)	1.3 (18)	7.7 (16)	1.6 (18)
a.	Shield Seal	4.13 (17)	1.2 (18)	6.8 (16)	8.4 (17)
4)	Flow Screen	6.19 (17)	2.1 (18)	9.5 (16)	1.5 (18)
5)	Outer Reflector				
a)	Dome End Support Ring	5.33 (17)	1.7 (18)	8.3 (16)	9.5 (17)
b)	Nozzle End Support Ring	3.61 (17)	1.0 (18)	6.3 (16)	7.2 (17)
c)	Impedance Ring	3.61 (17)	1.0 (18)	6.3 (16)	7.2 (17)
d)	Sector	2.32 (18)	7.1 (18)	3.5 (17)	6.5 (18)
e)	Tie Bolt	5.33 (17)	1.7 (18)	7.1 (16)	2.4 (18)
6)	Control Drum				
a)	Beryllium Cylinder	2.06 (18)	6.3 (18)	3.0 (17)	6.3 (18)
b)	Dome End Shaft Extension	5.33 (17)	1.7 (18)	8.1 (16)	9.5 (17)
c)	Nozzle End Shaft Extension	3.61 (17)	1.0 (18)	6.3 (16)	7.2 (17)
d)	Aluminum Housing	2.06 (18)	6.3 (18)	3.0 (17)	6.3 (18)
e)	Spring	3.61 (17)	1.0 (18)	6.3 (16)	7.2 (17)
f)	Plate Assembly	2.06 (18)	6.3 (18)	3.0 (17)	6.3 (18)
7)	Bearing Housing				
a)	Bearing	5.33 (17)	1.7 (18)	8.1 (16)	9.5 (17)
b)	Coupling	5.33 (17)	1.7 (18)	8.1 (16)	9.5 (17)
c)	Stop	5.33 (17)	1.7 (18)	8.1 (16)	9.5 (17)
d)	Safety Spring	5.33 (17)	1.7 (18)	8.1 (16)	9.5 (17)
e)	Drive Shaft	5.33 (17)	1.7 (18)	8.1 (16)	9.5 (17)

Note: Numbers in parenthesis indicate powers of 10.

(CRD) MAXIMUM INTEGRATED NEUTRON FLUX LEVELS ON XE-2 COMPONENTS (nvt)
(60 Minutes Equivalent Full Power) (U)

INDEX NO.

F.4.7
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	JFM 7/31/68	TM AC 8/8/68	

Component	$E > 1.0 \text{ Mev}$	$E > 0.1 \text{ Mev}$	$E > 2.87 \text{ Mev}$	$E < 1.86 \text{ ev}$
8) Core Assembly				
a) Support Plate	2.75 (18)	8.0 (18)	5.0 (17)	1.5 (18)
b) Dome End Seal	1.20 (18)	3.3 (18)	2.1 (17)	4.8 (17)
9) Clusters				
a) Liner Tube	1.55 (19)	4.2 (19)	3.2 (18)	4.8 (18)
b) Plate Assemblies	3.27 (18)	9.0 (18)	6.6 (17)	4.8 (17)
c) Preload Spring	2.75 (18)	8.0 (18)	5.0 (17)	3.8 (17)
d) Positioning Spring	3.87 (18)	1.1 (19)	7.8 (17)	6.0 (17)
e) Orifice Jets	3.53 (18)	9.6 (18)	6.9 (17)	5.3 (17)
f) Split Bushing	2.75 (18)	8.0 (18)	5.0 (17)	4.2 (17)
g) Tie Rod	1.55 (19)	4.2 (19)	3.2 (18)	4.8 (18)
h) Tie Rod Holder	2.24 (18)	6.6 (18)	3.8 (17)	7.5 (17)
i) Fuel Elements	1.55 (19)	4.2 (19)	3.2 (18)	3.3 (18)
j) Unfueled Elements	1.55 (19)	4.2 (19)	3.2 (18)	4.8 (18)
k) Keyed Elements	6.71 (18)	2.0 (19)	1.5 (18)	4.8 (18)
l) Support Blocks	2.24 (18)	6.2 (18)	4.4 (17)	6.2 (17)
m) Support Cone	1.29 (18)	3.6 (18)	2.6 (17)	3.3 (17)
n) Insulating Cup	1.29 (18)	3.6 (18)	2.6 (17)	3.3 (17)
o) Support Washer	1.29 (18)	3.6 (18)	2.6 (17)	3.3 (17)
p) Insulating and Countersunk Sleeves	1.55 (19)	4.4 (19)	3.2 (18)	4.8 (18)
q) Insulating Washer	1.29 (18)	3.6 (18)	2.6 (17)	3.3 (17)
10) Filler Strip Assemblies				
a) Strips	5.85 (18)	1.7 (19)	1.2 (18)	5.9 (18)
b) Insulating Tiles	5.93 (18)	1.7 (19)	1.2 (18)	4.8 (18)

Note: Numbers in parenthesis indicate powers of 10.

(CRD) MAXIMUM INTEGRATED NEUTRON FLUX LEVELS ON XE-2 COMPONENTS (nvt) (60 Minutes Equivalent Full Power) (U)	INDEX NO.
	F.4.7 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>dfm 7/21/68</i>	<i>mac 8/8/68</i>	

Components		<u>E > 1.0 Mev</u>	<u>E > 0.1 Mev</u>	<u>E > 2.87 Mev</u>	<u>E < 1.86 ev</u>
11)	Filler Blocks	2.84 (18)	7.8 (18)	5.7 (17)	2.1 (18)
12)	Fuel Cluster Nuts	1.29 (18)	4.2 (18)	2.1 (17)	1.5 (18)
13)	Cluster Nut Locking Device	6.71 (17)	2.1 (18)	9.5 (16)	1.5 (18)
14)	Core Band	2.75 (18)	7.5 (18)	5.3 (17)	2.3 (18)
15)	Core Assembly Axial Support System				
a)	Core Support Ring	5.33 (17)	1.7 (18)	8.1 (16)	8.4 (17)
b)	Instrumentation Ring	4.13 (17)	1.3 (18)	6.8 (16)	8.4 (17)
c)	Locking Devices	4.13 (17)	1.3 (18)	6.8 (16)	8.4 (17)
d)	Spring Support Ring	5.33 (17)	1.7 (18)	8.1 (16)	7.5 (17)
e)	Preload Springs and Retainers	1.12 (18)	3.2 (18)	2.0 (17)	6.0 (17)
f)	Spring Bearing Ring	1.20 (18)	3.5 (18)	2.1 (17)	4.5 (17)
g)	Tie Tube	1.20 (18)	3.5 (18)	2.1 (17)	8.4 (17)
16)	Lateral Support System				
a)	Graphite Cylinder	4.90 (18)	1.4 (19)	9.5 (17)	6.5 (18)
b)	Seal and Retainer Segments	4.90 (18)	1.4 (19)	9.5 (17)	6.0 (18)
c)	Plunger	4.90 (18)	1.4 (19)	9.5 (17)	6.0 (18)
d)	Springs	2.58 (18)	8.1 (18)	4.1 (17)	6.5 (18)
e)	Spring Bracket	2.58 (18)	8.1 (18)	4.1 (17)	6.5 (18)
f)	Spring Retaining Screw	2.58 (18)	8.1 (18)	4.1 (17)	6.5 (18)
17)	Nozzle Interface Seal	9.46 (17)	2.4 (18)	1.7 (17)	6.5 (17)

Note: Numbers in parenthesis indicate powers of 10.

(CRD) MAXIMUM INTEGRATED NEUTRON FLUX LEVELS ON XE-2 COMPONENTS (nvt) (60 Minutes Equivalent Full Power) (U)	INDEX NO.
	F.4.7 Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>1pm 7/5/68</i>	<i>mac 7/8/68</i>	

<u>Components</u>		<u>Ergs/Gm-C (XE-2 Run)*</u>	<u>Ergs/Gm-C per Mw-sec</u>
1)	Pressure Vessel	2.4 (11)	5.9 (4)
2)	Dome	1.5 (10)	3.8 (3)
3)	Shield	1.3 (11)	3.4 (4)
a)	Shield Seal	1.8 (11)	4.3 (4)
4)	Flow Screen	2.0 (11)	4.8 (4)
5)	Outer Reflector		
a)	Dome End Support Ring	2.0 (11)	4.9 (4)
b)	Nozzle End Support Ring	1.4 (11)	3.7 (4)
c)	Impedance Ring	1.4 (11)	3.7 (4)
d)	Sector	6.4 (11)	1.5 (5)
e)	Tie Bolt	2.7 (11)	6.5 (4)
6)	Control Drum		
a)	Beryllium Cylinder	5.7 (11)	1.4 (5)
b)	Dome End Shaft Extension	1.5 (11)	3.8 (4)
c)	Nozzle End Shaft Extension	1.2 (11)	3.0 (4)
d)	Aluminum Housing	5.7 (11)	1.4 (5)
e)	Spring	1.2 (11)	3.0 (4)
f)	Plate Assembly	5.7 (11)	1.4 (5)
7)	Bearing Housing		
a)	Bearing	2.0 (11)	4.8 (4)
b)	Coupling	2.0 (11)	4.8 (4)
c)	Stop	2.0 (11)	4.8 (4)
d)	Safety Spring	2.0 (11)	4.8 (4)
e)	Drive Shaft	2.0 (11)	4.8 (4)

* The proposed XE-2 Reactor run is 4.1×10^6 Mw-seconds, i.e., 60 minutes equivalent full power.

Note: Numbers in parenthesis indicate powers of 10.

(CRD) MAXIMUM INTEGRATED GAMMA RADIATION LEVELS ON XE-2 COMPONENTS (U)	INDEX NO.
	F.4.8 Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>JH 7/31/68</i>	<i>MAC 8/8/68</i>	

	Components	Ergs/Gm-C(XE-2 Run)*	Ergs/Gm-C per Mw-sec
8)	Core Assembly		
a)	Support Plate	6.2 (11)	1.5 (5)
b)	Dome End Seal	3.9 (11)	9.6 (4)
9)	Clusters		
a)	Liner Tube	3.3 (12)	8.2 (5)
b)	Plate Assemblies	6.2 (11)	1.5 (5)
c)	Preload Spring	6.0 (11)	1.5 (5)
d)	Positioning Spring	8.0 (11)	2.0 (5)
e)	Orifice Jets	6.5 (11)	1.6 (5)
f)	Split Bushing	6.0 (11)	1.5 (5)
g)	Tie Rod	3.3 (12)	8.2 (5)
h)	Tie Rod Holder	5.0 (11)	1.2 (5)
i)	Fuel Elements	3.3 (12)	8.2 (5)
j)	Unfueled Elements	3.3 (12)	8.2 (5)
k)	Keyed Elements	1.8 (12)	4.4 (5)
l)	Support Blocks	4.4 (11)	1.1 (5)
m)	Support Cone	2.4 (11)	5.9 (4)
n)	Insulating Cup	2.4 (11)	5.9 (4)
o)	Support Washer	2.4 (11)	5.9 (4)
p)	Insulating and Countersunk Sleeves	3.3 (12)	8.2 (5)
q)	Insulating Washer	2.4 (11)	5.9 (4)
10)	Filler Strip Assemblies		
a)	Strips	1.5 (12)	3.7 (5)
b)	Insulating Tiles	1.7 (12)	4.1 (5)

* The proposed XE-2 reactor run is 4.1×10^6 Mw-seconds, i.e., 60 minutes equivalent full power.

Note: Numbers in parenthesis indicate power of 10.

(CRD) MAXIMUM INTEGRATED GAMMA RADIATION LEVELS ON XE-2 COMPONENTS (U)	INDEX NO.
	F.4.8 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>S/m</i> 7/31/68	<i>MAC</i> 8/18/68	

Components	Ergs/Gm-C (XE-2 Run)*	Ergs/Gm-C per Mw-sec
11) Filler Blocks	6.9 (11)	1.7 (5)
12) Fuel Cluster Nuts	3.2 (11)	7.8 (4)
13) Cluster Nut Locking Device	2.0 (11)	4.8 (4)
14) Core Band	5.7 (11)	1.4 (5)
15) Core Assembly Axial Support System		
a) Core Support Ring	2.1 (11)	5.2 (4)
b) Instrumentation Ring	1.7 (11)	4.1 (4)
c) Locking Devices	1.7 (11)	4.1 (4)
d) Spring Support Ring	2.1 (11)	5.2 (4)
e) Preload Springs and Retainers	3.6 (11)	8.9 (4)
f) Spring Bearing Ring	4.2 (11)	1.0 (5)
g) Tie Tube	4.2 (11)	1.0 (5)
16) Lateral Support System		
a) Graphite Cylinder	1.2 (12)	3.0 (5)
b) Seal and Retainer Segments	1.2 (12)	3.0 (5)
c) Plunger	1.2 (12)	3.0 (5)
d) Springs	7.2 (11)	1.8 (5)
e) Spring Bracket	7.2 (11)	1.8 (5)
f) Spring Retaining Screw	7.2 (11)	1.8 (5)
17) Nozzle Interface Seal	1.8 (11)	4.4 (4)

* The proposed XE-2 reactor run is 4.1×10^6 Mw-seconds, i.e., 60 minutes equivalent full power.
Note: Numbers in parenthesis indicate powers of 10.

(CRD) MAXIMUM INTEGRATED GAMMA RADIATION LEVELS ON XE-2 COMPONENTS (U)

INDEX NO

F.4 .8
Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	dfm 7/31/68	mac 8/8/68	

THIS PAGE UNCLASSIFIED

*NOTE: REFER TO FIGURE F.6.2 FOR COORDINATES AND RADIATION ENVIRONMENT

(U) SCHEMATIC DIAGRAM OF ETS-1 FACILITY SHOWING LOCATION OF WANL COMPONENTS EXTERNAL TO THE REACTOR	INDEX NO.
	F.5.1

(U) XE-2 MAXIMUM RADIATION ENVIRONMENT AT WNL COMPONENTS FOR FULL POWER
CONDITIONS (1120 MW THERMAL, 60 MINUTE RUN)

INDEX NO.

F 5 2
SHEET 1

F-77

Location*	Component	Coordinates		Neutron Flux (Neutrons/cm ² -sec)			Gamma Ray Dose Rate (R/hr)	Gamma Ray Heating Rate (w/gm-Al)
		Radius (in.)	Station** (in.)	E>2.9 Mev	E>1.0 Mev	E>0.1 Mev		
1	Startup ⁺ Source	25.3	26	8.9 (3)	3.6 (4)	6.9 (4)	1.6 (0)	4.2 (-9)
2	Power Calibration System	13.0	71.7	1.4 (13)	5.8 (13)	1.2 (14)	5.0 (8)	1.4 (0)
3	EMND	13.8 to 21.7	-28.3	7.0 (11)	3.3 (12)	5.9 (12)	1.0 (8)	3.0 (-1)
4	Control Drum Actuator and Pressure Transducer	23.6 to 39.4	-67.7	3.0 (8)	6.5 (8)	1.1 (9)	1.4 (5)	3.9 (-4)
5	Surface of Neutronics Detector Canister	104.7	-8.0	9.0 (11)	8.0 (12)	2.4 (13)	1.4 (8)	3.9 (-1)

* Refer to figure F.5.1 for schematic diagram of component locations.

** Station 0 is located at the inlet end of the reactor core.

+ Radiation values are per Watt of reactor power, since the startup source will not be present during full power operation.

REFERENCE

PREPARED BY

8/11 7/31/68

APPROVED BY

MAC 8/21/68

Astronuclear
Laboratory

(U) XE-2 MAXIMUM RADIATION ENVIRONMENT AT WANU COMPONENTS FOR FULL POWER
CONDITIONS (1120 MW THERMAL, 60 MINUTE RUN)

INDEX NO.
F.5.2
SHEET 2

SOURCE OF DATA USED IN F.5.2

Location *	Component	Neutron Flux (Neutrons/cm ² -sec)			(R/Hr)	(W/gm-Al)
		E > 2.9 Mev	E > 1.0 Mev	E > 0.1 Mev	Gamma Ray Dose Rate	Gamma Ray Heating Rate
1	Startup Source	Experimental Data (NRX-A6)	Experimental*	Experimental*	Experimental Data (NRX-A6)	Experimental Data (NRX-A6)
2	Power Calibration System	Experimental Data (NRX-A6)	Experimental*	Experimental*	Experimental Data (NRX-A6)	Experimental Data (NRX-A6)
3	EMND	Experimental Data (NRX-A6)	Experimental*	Experimental*	Experimental Data (NRX-A6)	Experimental Data (NRX-A6)
4	Control Drum Actuator and Pressure Transducer	Calculated Data (FASTER Monte-Carlo)	Calculated Data (FASTER Monte-Carlo)	Calculated Data (FASTER Monte-Carlo)	Calculated Data (FASTER Monte-Carlo)	Calculated Data (FASTER Monte-Carlo)
5	Surface of Neutronics Detector Canister	Calculated Data (TAPAT)	Calculated Data (TAPAT)	Calculated Data (TAPAT)	Experimental Data (WANEF-PAX)	Experimental Data (WANEF-PAX)

* Experimental data obtained by ratioing the experimental (E > 2.9 Mev) flux using FASTER Monte-Carlo calculated flux ratios.

REFERENCE

PREPARED BY

AM 7/3/68

APPROVED BY

MAC 8/8/68

Astronuclear
Laboratory

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>SJM 7/31/68</i>	<i>mac 8/8/68</i>	

(U) Uncertainty factors vary with the geometrical complexity of the problem and the penetration depth between the source and detector. Therefore, an uncertainty factor for the radiation environment at each location shown in Figure F.5.1 and F.5.2 are given here.

<u>Location</u>	<u>Uncertainty Factor</u>
1	1.5
2	1.5
3	2.0
4	3.0
5	1.5

(U) The gamma radiation levels at locations 1, 3, and 5 are based on experimental data.

(U) UNCERTAINTY FACTORS FOR EXTERNAL ENVIRONMENT)	INDEX NO.
	F.5.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>JPH</i> 7/31/68	<i>MQC</i> 8/8/68	

(U) The Engine Mounted Neutron Detector (EMND) system is used to monitor reactor power level. This system consists of three neutron detectors mounted, independently, on the dome of the XE-2 reactor at the "milk stool" flange. The detectors are WX-5362, boron coated, compensated ion chambers filled with helium gas. The detectors respond to low energy neutrons and have a minimal response to gamma rays. A low power "calibration" constant provides the necessary correlation between the specific reactor nuclear power level and the ion chamber current output. Each detector is approximately three inches in diameter by five inches long and is enclosed in a beryllium sleeve. The beryllium sleeve is used to provide a "good" thermal path between the detector and the dome of the reactor in order to dissipate the nuclear heat deposited in the detector. This sleeve is approximately seven inches long with a wall thickness of one inch.

(U) This detector is being used in the ETS-1 neutronics canister and it has also been used extensively during testing of both NRX and Phoebe reactors.

(U) Measurements have been made on the dome of the PAX reactor assembly at WANEF with the EMND system. Based upon these measurements, supplemented by calculations, the following data for the EMND system have been obtained:

Gamma Ray Dose Rate (at 1120 MW Thermal Power):

$$1.0 \times 10^8 \text{ R/Hr} \pm 50\%$$

Heating Rate (at 1120 MW Thermal Power):

$$0.3 \text{ w/gm} - \text{Al} \pm 50\%$$

$$0.3 \text{ w/gm} - \text{Be} \pm 50\%$$

Detector Gain Constant, K, due to the effect of hydrogen in the reactor system:

$$1 < K < 2.5$$

(U) Previous use of the WX-5362 detectors during Phoebe and NRX Reactor tests have indicated that the detector system is linear over the operating range of the detector. Different detector gain constants must be used because of changes in the radiation environment due to the effect of various amounts of hydrogen in the reactor system. K = 1 is used for a 0% hydrogen flow condition while K = 2.5 is used for a 100% hydrogen flow condition.

(U) ENGINE MOUNTED NEUTRON DETECTOR SYSTEM DESCRIPTION AND RADIATION ENVIRONMENT	INDEX NO.
	F.6.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	8/4/78	MAC 8/8/78	

(U) The neutronics canister system provides a housing facility for the XE-2 startup chamber, a neutron check source used for chamber checkout, and two ion chambers for power range operation. There are three separate neutronics canisters which penetrate the water-filled side shield which surrounds the XE-2 reactor. The canisters are located at an axial location approximately 34 inches above core midplane and separated azimuthally by $\approx 60^\circ$. Each neutronics canister consists of four horizontal tubes, arranged in a diamond pattern. One tube (1 inch in diameter) contains the BF_3 startup chamber, one tube (also 1 inch in diameter) contains a movable neutron source for chamber checkout, and the remaining two tubes (3 inches in diameter) each contains a WX-5362, boron coated, compensated ion chamber.

(U) The BF_3 startup chamber is used to monitor the initial XE-2 reactor startup. This detector responds to low energy neutrons. A base counting level for the BF_3 startup chamber is provided by a 1 curie Pu-Be neutron source, located on the XE-2 pressure vessel at approximately the same station and diametrically opposed to the center BF_3 startup chamber. The minimum acceptable count rate from this neutron source is a 1 count per second with the reactor in a shutdown condition, as set forth in Nuclear Safety documentation.

(U) The data in Figure F.7.2 which shows the fall-off in chamber count rate as a function of position of the chamber in the canister from a 1 curie Pu-Be neutron source, was obtained from measurements made at WANEF using a mockup of the side shield and neutronic canister with the PAX reactor assembly shutdown by about \$3.85 (drums full-in). The data indicates that the minimum acceptable count rate (1 CPS) will not be obtained if the chamber is retracted more than 1.9 inches into the side shield.

(U) A movable Pu-Be neutron source is used to check the BF_3 startup chamber for proper operation in the neutronics canister system. The data in Figure F.7.3 which shows the fall-off in the BF_3 chamber count rate as a function of separation distance between the chamber and a 1 curie Pu-Be neutron source, has also been obtained from measurements made at WANEF in a mockup of the side shield and neutronics canister. The data indicate that count rates well above background are obtained when the neutron source is displaced as far as 24 inches from the chamber in an adjacent tube. Thus, insertion of the neutron source to the "full-in" position will provide a sufficient count rate at the chamber to indicate whether the chamber is operating correctly, at any chamber position within the canister tube.

(U) The two WX-5362 ion chambers are identical and respond to low energy neutrons with a minimal response to gamma rays. One chamber is used for general diagnostic instrumentation and is used with linear channel electronics. The other chamber is for signal to the power controller and override and is used on log channel electronics. Both ion chambers are required to be positioned in the neutronics canister tubes such that the chambers will respond over the full power range specified without chamber saturation at the upper power levels or poor signal to noise ratios at the lowest power levels. It is also required that some form of shielding material be placed in the canister tube between the chamber and the side shield liner material and also behind the chamber. This is required to eliminate radiation streaming through the large canister tubes and to assure that excessive heating rates do not occur in the chamber or its associated cabling.

(U) NEUTRONICS CANISTER SYSTEM DESCRIPTION AND RADIATION ENVIRONMENT	INDEX NO.
	F.7.1 Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	8/6/68	mac 8/9/68	

(U) At 1120 MW (thermal) power, i.e., full power conditions for the XE-2 reactor, the current output from the WX-5362, boron coated, compensated ion chambers should be 2×10^{-3} amperes for maximum performance. Measurements were also made at WANEF using the mockup of the side shield and neutronics canister and the PAX reactor assembly to evaluate the performance of, and recommend position for, the WX-5362 ion chambers. This information, obtained at WANEF, has been scaled up to the full power conditions to be expected from XE-2, i.e., 1120 MW (thermal) power. The data in Figure F.7.4 shows the fall-off of the scaled thermal neutron flux as a function of position of the chamber in the canister tube. Measurements were made with and without shielding material present in the canister tube. Dysprosium-aluminum activation foils were used to confirm the WX-5362 ion chambers response to thermal neutrons and this information is also shown in Figure F.7.4. The scaled gamma ray heating rate with various amounts of shielding material present is shown in Figure F.7.5 for various locations within the canister tube. Figure F.7.6 shows the scaled current output of the WX-5362 ion chamber as a function of the position of the ion chamber in the canister tube without any shielding material present in the tube. The desired full-power output current of 2×10^{-3} amperes is observed to occur at a nominal distance of 12 inches from the inner surface of the side shield. As shown in Figure F.7.4, the addition of shielding material reduces the radiation streaming through the canister tube. Therefore, the WX-5362 ion chambers will be located behind approximately 5 inches of aluminum shielding material placed adjacent to the inner surface of the side shield to obtain the desired full-power current output of 2×10^{-3} amperes. The five inches of aluminum shielding material in front of the ion chamber plus an additional 6 inches of borated polyethylene located behind the detector is sufficient to eliminate the radiation streaming and nuclear heating problems.

(U) NEUTRONICS CANISTER SYSTEM DESCRIPTION AND RADIATION ENVIRONMENT

INDEX NO.
F.7.1 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>sfm</i>	<i>7/31/68 MAC 7/7/68</i>

(U) STARTUP DETECTOR RESPONSE AS A FUNCTION OF POSITION IN THE ETS-1 SIDE SHIELD NEUTRONICS CANISTER (U)	INDEX NO.
	F.7.2

REFERENCE

PREPARED BY

4/m 7/31/68

APPROVED BY

mac 8/8/68

Astronuclear
Laboratory

(U) STARTUP DETECTOR RESPONSE TO A NEUTRON CHECK SOURCE IN
THE ETS-1 SIDE SHIELD NEUTRONICS CANISTER (U)

INDEX NO

F.7.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>Lf M</i> 8/6/68	<i>Mac</i> 8/8/68

(U) THERMAL NEUTRON FLUX AS A FUNCTION OF POSITION IN THE ETS-1 SIDE SHIELD NEUTRONICS CANISTER

INDEX NO.

F.7.4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>dfm</i>	<i>8/6/68 Mac 8/8/68</i>

(U) GAMMA RAY HEATING RATE AS A FUNCTION OF POSITION IN THE ETS-1 SIDE SHIELD NEUTRONICS CANISTER	INDEX NO
	F.7.5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	<i>slm</i> 7/3/68	Mac 8/8/68

(U) WX 5362 DETECTOR RESPONSE AS A FUNCTION OF POSITION IN THE ETS-1 SIDE SHIELD NEUTRONICS CANISTER

INDEX NO.

F.7.6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	QD 8/2/68	

SECTION G

REFLECTOR SYSTEM: THERMAL - HYDRAULIC DATA

INTRODUCTION

This section of the Data Book contains thermal and hydraulic data pertinent to the reflector system. The reflector system includes those components external to the core elements beginning with the pyrolytic graphite insulating tiles and filler strips but not including the shield and screen assembly. Only that portion of the pressure vessel which is adjacent to the reflector and reflector support rings is included.

The section is divided into models, limitations and data subdivisions related to the XE-2 reactor. Computational uncertainties are included in the limitations subdivision and are meant to apply to the data given in the subsequent subdivisions.

Detailed steady state thermal and hydraulic data for 100% power and flow are given in sub-division G.3 and consists of two main groups; system flow and energy balances, and component temperature distributions. The first group consists of fluid properties (temperatures, pressures, flow rates) and energy distribution in the reflector system. The second group includes radial and axial temperature distributions in individual components.

(CRD) INTRODUCTION (U)	INDEX NO.
	G

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	OS 8/2/68	

SUB-SECTION G.

XE-2 DATA
REFLECTORS: THERMAL-HYDRAULIC DATA

TABLE OF CONTENTS

<u>Index No.</u>			<u>Cross Reference⁽¹⁾</u> <u>Index No.</u>
*G.1	(U)	Reflector System Models (U)	
G.1.1	(U)	Computer Codes (U)	
G.1.2	(CRD)	Reflector Cross Section (U)	C.1.1.3
G.1.3	(CRD)	Reflector System Flow Pattern (U)	
G.1.4	(U)	Control Drum Flow Pattern (U)	
G.1.5	(CRD)	Lateral Support and Seal Flow Pattern (CRD)	
		(CRD) Sheet 1 - Flow Path Diagram (CRD)	
		(CRD) Sheet 2 - Dimensional Data (CRD)	
G.1.6	(U)	Reflector System Hydraulic Model (U)	
		(CRD) Sheet 1 - Sketch (U)	
		(CRD) Sheet 2 - Dimensional Data and Loss Coefficients (U)	
*G.2	(U)	Reflector System Limitations (U)	
G.2.1	(CRD)	Calculational Uncertainties (2 Sheets) (U)	
G.2.2	(CRD)	Design Criteria and Limitations (U)	
G.2.3	(U)	Beryllium Sector Maximum Average-to-Web Temperature Difference vs. Startup Ramp Rate (U)	
G.3	(U)	Nominal Design Point - 100% Power at 77.0 lb/sec Flow (U)	
G.3.1	(U)	Reflector System Flow and Energy Balance (U)	
		(CRD) Sheet 1 - Reflector Flow Schematic (U)	
		(CRD) Sheet 2 - Reflector Energy and Flow Balance (U)	
		(CRD) Sheet 3 - Reflector Axial Pressure Profiles (U)	
		(CRD) Sheet 4 - Reflector Coolant Temperature Distributions (U)	
		(CRD) Sheet 5 - Control Drum Annulus Coolant Temperature (U) Distributions	
		(CRD) Sheet 6 - Control Plate Annuli Coolant Temperature (U) Distributions	
		(CRD) Sheet 7 - Seal Coolant Temperature, Pressure and (CRD) Flow Rate Profiles	
G.3.2	(U)	Beryllium Sector Axial Temperature Profiles (U)	
		(CRD) Sheet 1 - Axial Temperature Distribution (U)	
		(CRD) Sheet 2 - Axial Temperature Distribution in Control Drum (U) Annulus	
		(CRD) Sheet 3 - Beryllium Sector Temperature Differences (U)	

*There are no data sheets corresponding to these index numbers.

(1) Data sheets will be found Index No. entered in this column.

(CRD) TABLE OF CONTENTS (U)	INDEX NO.
	G

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	OB 8/2/68	

SUB-SECTION G.

XE-2 DATA
REFLECTORS: THERMAL-HYDRAULIC DATA

TABLE OF CONTENTS

<u>Index No.</u>		<u>Cross Reference⁽¹⁾ Index No.</u>
*G.3.3	(U) Control Drum Temperature Distributions (U)	
G.3.3.1	(U) Control Drum Axial Temperature Profiles (U)	
	(CRD) Sheet 1 - Control Drum Axial Temperature Profiles (U)	
	(CRD) Sheet 2 - Control Plate Axial Temperature Profiles (U)	
G.3.3.2	(U) Control Plate Azimuthal Temperature (U)	
G.3.4	(CRD) Inner Reflector - Lateral Support Temperature Distributions (CRD)	
G.3.4.1	(U) Axial Temperature Profiles (U)	
	(CRD) Sheet 1 - Graphite Cylinder Axial Variation of Temperature (CRD) and Radial Pressure Drops	
	(CRD) Sheet 2 - Seal Segment Axial Temperature Profiles (CRD)	
	(CRD) Sheet 3 - Filler Strip Axial Temperature Profiles (CRD)	
	(CRD) Sheet 4 - Pyrographite Insulating Tile Axial Temperature (CRD) Profiles	
G.3.4.2	(CRD) Inner Reflector Radial Temperature Profiles (CRD)	
	(CRD) Sheet 1 - Seal No. 2 (CRD)	
	(CRD) Sheet 2 - Seal No. 9 (CRD)	
	(CRD) Sheet 3 - Seal No. 14 (CRD)	
	(CRD) Sheet 4 - Seal No. 18 (CRD)	
G.3.5	(CRD) Pressure Vessel Temperature Distributions (U)	
G.3.6	(CRD) Tie Bolt Temperature Distributions (U)	
G.3.7	(CRD) Core Band Temperature Distributions (U)	
G.3.8	(U) Control Drum Scram Spring Temperatures (U)	

*There are no data sheets corresponding to these index numbers.

(1) Data sheet will be found under Index No. entered in this column.

(CRD) TABLE OF CONTENTS (U)	INDEX NO.
	G.

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	L DH 7/26/68	OSD 8/2/68	

THIS PAGE UNCLASSIFIED

<u>Code</u>	<u>Description and Usage</u>
MCAP (multiple channel analysis program) WANL-TME-944	Hydraulic and convection heat transfer code which balances flow in parallel channels. Used to determine reflector flow balance and coolant temperatures and pressure when heat distribution is known.
TOSS (transient or steady state temperatures) WANL-TME-1108	Heat conduction code which determines the temperature distribution in a component for given surface boundary conditions (boundary temperatures and heat transfer coefficient).
TNT (thermal and nuclear transients) Section D.5.a	Hydraulic and convection heat transfer code programmed specifically for the NRX-A reactors. This code establishes the boundary conditions to be used in more detailed reflector system analyses.
CAT (component approximate transients)	Transient code which uses lumped node models and TNT boundary conditions to obtain component average temperature and pressure differences.
TRACK II (transient convection and conduction)	Transient and steady state code which combines hydraulic and convection heat transfer solutions with internal heat conduction solution obtained by the TOSS code. Used to determine the coolant flow temperature and pressure conditions, and the material and wall temperature distributions in the lateral support seal and reflector regions of the reactor. This program is the basic tool for determining the reflector system and lateral support-seal system flow and energy balances.

(U) COMPUTER CODES USED IN REFLECTOR THERMAL AND HYDRAULIC ANALYSIS (U)

INDEX NO.

G.1.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	OS 8/2/68

(CRD) REFLECTOR SYSTEM FLOW PATTERN (U)	INDEX NO.
	G.1.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 8/2/68	OS 8/2/68	

THIS PAGE UNCLASSIFIED

(U) CONTROL DRUM FLOW PATTERN (U)	INDEX NO.
	G.1.4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	GS 8/2/68

(CRD) LATERAL SUPPORT AND SEAL FLOW PATTERN, SKETCH (CRD)

INDEX NO

G.1.5
Sheet 1

REFERENCE CR: MDW 200	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	AS 8/2/68	

Seal Groove Width = 0.440" (162 grooves per seal row, except seal no. 1 - see G.3.7)

*Seal No.	Seal Location Core Station	Depth of Seal Grooves (Inches)	**Filler Strip Gap (Inches) 100% Power	Pin Leakage Area Square Inch
1 (dome end)	2.30 - 3.30	0.025	0.0022	-----
2	5.64 - 6.64	0.012	0.0023	0.01907
3	8.45 - 9.45	0.012	0.0024	0.01907
4	11.26 - 12.26	0.012	0.0024	0.01907
5	14.08 - 15.08	0.012	0.0025	0.01907
6	16.89 - 17.89	0.012	0.0026	0.01907
7	19.70 - 20.70	0.010	0.0027	0.01907
8	22.51 - 23.51	0.010	0.0028	0.01907
9	25.32 - 26.32	0.010	0.0032	0.01653
10	28.14 - 29.14	0.010	0.0036	0.01568
11	30.95 - 31.95	0.010	0.0038	0.01983
12	33.76 - 34.76	0.008	0.0045	0.01356
13	36.57 - 37.57	0.008	0.0050	0.01272
14	39.38 - 40.38	0.008	0.0058	0.01102
15	42.20 - 43.20	0.008	0.0062	0.00975
16	45.01 - 46.01	0.008	0.0066	0.01820
17	47.80 - 48.80	0.050	0.0068	0.01780
18 (nozzle end)	50.63 - 51.63	0.008	0.0070	0.01950

*These numbers were arbitrarily assigned for analyses.

**Applies to nominal sectors only.

(CRD) LATERAL SUPPORT AND SEAL SYSTEM DIMENSIONAL DATA (CRD)	INDEX NO.
	G.1.5 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 8/2/68	ASB 8/2/68

NUMBERS INDICATE
CHANNELS DESCRIBED
ON SHEET 2

CONTROL DRUM SHOWN IN 90° POSITION LOOKING AFT

(CRD) REFLECTOR SYSTEM HYDRAULIC MODEL - SKETCH (U)

INDEX NO.

G. 1. 6
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	AS 8/2/68	

Channel Identification	Hydraulic Diameter (in)	No. of Equivalent Holes	Heat Transfer Area (in ²)	Loss Coefficients CL ¹	
				Inlet	Outlet
1. Reflector Annulus	0.1764	455.0	13109.0	25.8	3.7 ₂
2. Pressure Vessel Annulus	0.4120	240.0	16151.2	1.5	81.0 ₂
3. Sector Cooling Holes (non-vane side)	0.1875	48.0	1470.3	4.3 ³	1.4
4. Sector Cooling Holes (non-vane side)	0.1875	48.0	1470.3	4.3	1.4
5. Sector Cooling Holes (non-vane side)	0.1875	48.0	1470.3	4.3	1.4
6. Sector Cooling Holes (non-vane side)	0.1875	48.0	1470.3	4.3	1.4
7. Control Drum Annulus (non-vane side)	0.1560	409.0	10423.2	18.1	125.4
8. Control Drum Annulus (6-10th cm)	0.1560	110.0	2803.3	18.0	125.4
9. Control Drum Annulus (3-5th cm)	0.1560	69.0	1745.7	18.1	125.4
10. Control Drum Annulus (1-2 nd cm)	0.1560	42.0	1062.7	18.1	125.4
11. Sector Cooling Holes (vane side)	0.1875	48.0	1470.3	4.3	1.4
12. Sector Cooling Holes (vane side)	0.1875	48.0	1470.3	4.3	1.4
13. Sector Cooling Holes (vane side)	0.1875	48.0	1470.3	4.3	1.4
14. Sector Cooling Holes (vane side)	0.1875	48.0	1470.3	4.3	1.4
15. Graphite Reflector Cooling Holes	0.3125	144.0	7351.3	1.8	0.6
16. Control Drum Cooling Holes (4 central holes)	0.1875	48.0	1470.3	2.5	5.5
17. Control Drum Cooling Holes (4 middle holes - vane side)	0.1875	48.0	1470.3	1.6	6.3
18. Control Drum Cooling Holes (4 middle holes - non vane side)	0.1875	48.0	1470.3	1.6	6.3
19. Control Drum Cooling Holes (3.5 outer holes)	0.1875	42.0	1337.5	1.6	7.8
20. Control Drum Slot	0.2300	125.0	4681.6	1.6	7.8
21. Control Vane Inner Annulus, 6-10th cm	0.2560	60.0	2513.5	4.2	1.1
22. Control Vane Inner Annulus, 3-5th cm	0.2560	36.0	1509.7	4.2	1.1
23. Control Vane Inner Annulus, 2nd cm	0.2560	12.0	506.0	4.2	1.1
24. Control Vane Inner Annulus, 1st cm	0.2560	12.0	506.0	4.2	1.1
25. Control Vane Outer Annulus, 1st cm	0.1580	20.0	526.6	4.6	1.8
26. Control Vane Outer Annulus, 3-5th cm	0.1580	61.0	1577.1	4.6	1.8
27. Control Vane Outer Annulus, 6-10th cm	0.1580	102.0	2632.7	4.6	1.8
28. Control Vane Outer Annulus, 2nd cm	0.1580	20.0	526.6	4.6	1.8
29. Control Drum Cooling Holes (3.5 outer holes)	0.1875	42.0	1337.5	1.6	7.8
30. Tie Bolt Cooling Holes	0.2500	36.0	1471.6	1.5	-0.2

1. $\Delta P = CL \frac{G^2 V}{2g}$, where, ΔP = Pressure Drop, G = Mass flow rate per unit area (based on flow area of channel), V = specific volume (hydrogen properties based on state point in channel)
2. Based on test results reported in WANL-TME-832.
3. Based on test results reported in WANL-TME-673.

(CRD) REFLECTOR SYSTEM HYDRAULIC MODEL - DIMENSIONAL DATA AND LOSS COEFFICIENTS (U)	INDEX NO.
	G.1.6 Sheet 2

REFERENCE LDH-500 CR: AYL-016, -020, AYL-03027, -03037	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	DB 8/2/68	

NOMINAL CASE: 131 °R Reflector Inlet Temperature

ITEM	NOMINAL	2σ UNCERTAINTY ⁽¹⁾ Percent of Nominal
1. Reflector Inlet Pressure	744.7 psia	+ 5.5 -
2. Reflector Pressure Drop	33.5 psia	+18 -10
3. Sector Avg. Temp. (at max. temp. level, Core Station 23)	297 °R	+32 -20
4. Pressure Vessel Avg. Temp. (at max. temp. level, Core Station 25)	270 °R	+24 -20
5. Control Drum Avg. Temp. (at max. temp. level, Core Station 16)	207 °R	+20 -14
6. Graphite Cylinder Avg. Temp. (at max. temp. level, Core Station 32)	600 °R	+42 -19
7. Control Vane Avg. Temp. (at max. temp. level, Core Station 23)	295 °R	+37 -42
8. Tie Bolt Avg. Temp. (at max. temp. level, Core Station 25)	242 °R	+ 15 -
9. Maximum Coolant Temperatures		
(a) Pressure Vessel Annulus	192 °R	+16 -17
(b) Reflector Annulus	248 °R	+21 -14
(c) Sector Holes	246 °R	+27 -15
(d) Control Drum Holes	204 °R	+20 -14
(e) Graphite Cylinder Holes	255 °R	+32 -17
(f) Control Drum Annulus	306 °R	+30 -13
(g) Control Vane Annulus	345 °R	+16 -18
(h) Tie Bolt Holes	142 °R	+ 14 -
10. Core Support Cone Avg. Temp. °R	336 °R	+25 -
11. Nozzle End Support Ring Avg. Temp., °R	225 °R	+ 50 % of (T _{avg} -T coolant bulk)
12. Dome End Support Ring Avg. Temp. °R		
(a) Horizontal Ring	329 °R	+ 24 -
(b) Vertical Barrel Section	273 °R	+ 20 -

(CRD) XE-2 REFLECTOR SYSTEM PRESSURE AND TEMPERATURE UNCERTAINTIES AT 100% POWER
AND 77.0 LB/SEC FLOW (U)

INDEX NO

G.2.1
Sheet 1

REFERENCE CR: AYL-016, -020, AYL-03027, -03037	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	CS 8/2/68	

THIS PAGE UNCLASSIFIED

NOTE:

- 1) The factors considered in the uncertainty analysis are listed below. The percentage of variation in each factor is also listed:

1) Heating rate	Be $\begin{smallmatrix} +67 \\ -33 \end{smallmatrix} \%$	Graphite $\begin{smallmatrix} +53 \\ -27 \end{smallmatrix} \%$	Boron Vane $\begin{smallmatrix} +41 \\ -50 \end{smallmatrix} \%$ (max.)
2) Azimuthal variation in inlet temperature	$\pm 15 \%$	(3 σ)	
3) Channel inlet and outlet loss coefficients	$\pm 30 \%$	(3 σ)	
4) Sector and drum cooling hole size	$\pm 30 \%$	(3 σ)	
5) Sector and drum holes mismatch .161"	0.161"	(3 σ)	

(U) XE-2 REFLECTOR SYSTEM PRESSURE AND TEMPERATURE UNCERTAINTIES AT 100% POWER AND 77.0 LB/SEC FLOW (U)

INDEX NO.

G.2.1
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	OB 8/2/68	

The general philosophy of the reflector thermal design has been to minimize temperature gradients and coolant temperature differences. Most of the components in the reflector system operate far below their maximum allowable material temperatures. Only a few limitations have been established for the reflector thermal and hydraulic design. These are given below along with the actual design values for operating conditions of 100% power and 100% flow. The seal system was designed to insure an inward pressure force on the core without causing excessive frictional forces between elements.

Item	Limitation	As Designed
		100% Power 100% Flow
Control Plate Maximum Temperature	900°R	660°R
Variation in Coolant Temperature at Reflector Exit	Minimize (Uniform coolant temperature necessary at core inlet)	202°R
Beryllium Reflector Radial Temperature Difference (Average-Minimum)	Minimize (High Stress in Web Region)	110°R
Control Drum Radial Temperature Difference	Minimize (Control Drum Bowing)	69°R
Graphite Reflector Radial Temperature Difference (Inner Wall-Outer Wall)	Minimize (Thermal Stress)	950°R
Filler Strip Radial Temperature Difference	Minimize	250°R (Avg. Strip)
Reflector Axial Pressure Drop	Minimize	31.3 psi
Graphite Reflector Axial Pressure Drop	Minimize (Lift-off from Nozzle)	31.3 psi
Graphite Reflector Radial Pressure Drop	Minimize (Pressure Stress)	160 psi
Nominal Filler Strip Maximum Temperature on Seals	Minimize (Corrosion)	2050°R
Nominal Filler Strip Maximum Temperature Between Seals	Minimize (Corrosion)	2750°R
Seal Maximum Temperature	Minimize (Corrosion)	1800°R

(CRD) REFLECTOR SYSTEM DESIGN CRITERIA AND LIMITATIONS (U)

INDEX NO.

G.2.2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	SS 8/2/68	

THIS PAGE UNCLASSIFIED

(U) XE-2 BERYLLIUM SECTOR AVERAGE TO WEB TEMPERATURE DIFFERENCE AS A FUNCTION OF AVERAGE FLOW RAMP RATE (U)	INDEX NO
	G.23

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	GB 8/2/68	

THIS PAGE UNCLASSIFIED

Heating Rates

The heating rates used in the thermal analyses of XE-2 reactor components are those given in Section F.

Reflector System Model

The reflector system configuration of the XE-2 reactor is the same as in the NRX-A5 reactor, and is described in detail in the NRX-A5 Data Book, WANL-TME-1389. The reflector system hydraulic model used in the thermal analysis of the reflector is described in Section G.1.6.

Beryllium and graphite thermal properties used in the analyses were taken from NERVA Materials Properties Data Book, AGC Report 2275, and do not include the effect of nuclear radiation on the material properties. The expected rates of temperature rise at Station 32 of the beryllium sector and graphite barrel due to irradiation effects are as follows: for beryllium $1.2^{\circ}\text{R}/\text{min.}$, and for the graphite barrel $7.2^{\circ}\text{R}/\text{min.}$ at $R = 19.2"$ and $18.5^{\circ}\text{R}/\text{min.}$ at $R = 18.2"$. These data are the average observed values obtained from NRX-A2 through NRX-A5 reactor tests.

Component Radial Temperature Distributions (Nodal Tabulations)

The detailed temperature distributions (nodal tabulations) in the reflector components are not included in the data for the XE-2 reactor, but are available upon request.

(U) NOMINAL DESIGN POINT-100 PERCENT POWER AT 77.0 LB/SEC FLOW (U)	INDEX NO.
	G.3

(CRD) XE-2 REACTOR FLOW SCHEMATIC AT 100 PERCENT POWER AND FLOW (U)

PREPARED BY LDH 7/26/68

APPROVED BY [Signature] 8/2/68

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	AS 8/2/68	

Radiation Heating of Components

Component	Power - MW	
	Thermal	Nuclear* (based on 13 min. run)
Beryllium sectors and control drums (including aluminum)	10.30	10.22
Control plates	2.79	2.67
Pressure vessel (dome end flange to core station 52)	1.40	1.44
Tie Bolts	.163	.24
Graphite reflector and seal segments	8.18	8.16
Filler strip and pyrographite	3.07	2.96
Power input from core	<u>-0.10**</u> 25.80	<u>-0.10**</u> 25.59

Convective Cooling of Components

Cooling Channel	Power MW	Flow Ratio
Reflector annulus	3.24	0.091
Pressure vessel annulus	2.33	0.151
Beryllium sector holes	4.79	0.150
Control drum holes (including slot)	1.83	0.152
Tie bolt cooling holes	0.17	0.048
Graphite cylinder holes	7.45	0.205
Control drum annulus	0.97	0.040
Control plate inner annulus	1.77	0.104
Control plate outer annulus	1.36	0.053
Lateral support seal	<u>2.09</u> 26.00	<u>0.006</u> 1.000

* The nuclear powers for the sector, drum, control plate, pressure vessel, tie bolt and inner reflector were obtained from sub-section F.

**Obtained from lateral support fluid flow and thermal analysis on heat transfer across I.D. of pyrographite.

(CRD) REFLECTOR ENERGY AND FLOW BALANCE AT 100% POWER AND 77.0 LB/SEC FLOW (U)

INDEX NO.

G.3.1
Sheet 2

REFERENCE

LDH-500

INDEX NO
G-3.1 Sheet 3

(CRD) XE-2 FULL POWER STEADY STATE REFLECTOR SYSTEM COOLANT PRESSURE DISTRIBUTIONS (U)	PREPARED BY	APPROVED BY
	LDH 8/2/68	AB 8/2/68

REFERENCE

LDH-500

(CRD) XE-2 FULL POWER STEADY STATE REFLECTOR SYSTEM COOLANT TEMPERATURE
DISTRIBUTION (U)

PREPARED BY

LDH 7/31/68

APPROVED BY

QJ 8/2/68

REFERENCE	LDH-500	PREPARED BY	APPROVED BY	Astronuclear Laboratory
		LDH 7/31/68	GB 8/2/68

(CRD) XE-2 FULL POWER STEADY STATE DRUM ANNULUS TEMPERATURE DISTRIBUTION (U)	INDEX NO
	G.3.1 Sheet 5

REFERENCE	PREPARED BY		APPROVED BY		Astronuclear Laboratory
	LDH-500	LDH 7/31/68	AS	8/2/68

(CRD) XE-2 FULL POWER STEADY STATE CONTROL PLANE ANNULI COOLANT TEMPERATURE (U) DISTRIBUTION	INDEX NO
	G.3.1 Sheet 6

REFERENCE LDH -500	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 8/1/68	AS 8/2/68

(CRD) XE-2 SEAL COOLANT AXIAL TEMPERATURES, PRESSURES AND FLOW RATES FOR 100 PERCENT POWER AND FLOW (CRD)

INDEX NO

G.3.1
Sheet 7

REFERENCE LDH-500	PREPARED BY LDH 8/2/68	APPROVED BY OB 8/2/68	Astronuclear Laboratory

(CRD) XE-2 FULL POWER STEADY STATE BERYLLIUM SECTOR AXIAL TEMPERATURES (U)

INDEX NO

G.3.2
Sheet 1

REFERENCE LDH-500	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/31/68	QB 8/2/68

(CRD) XE-2 FULL POWER STEADY STATE BERYLLIUM SECTOR WALL TEMPERATURE IN THE DRUM ANNULUS (U)

INDEX NO

G.3.2
Sheet 2

REFERENCE LDH-500	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/31/68	QSS 8/2/68

(CRD) XE-2 FULL POWER BERYLLIUM SECTOR TEMPERATURE DIFFERENCES (U)	INDEX NO
	G.3.2 Sheet 3

REFERENCE LDH -500	PREPARED BY LDH 8/1/68	APPROVED BY as 8/2/68	Astronuclear Laboratory

(CRD) XE-2 FULL POWER STEADY STATE CONTROL DRUM AXIAL WALL TEMPERATURES (U)

INDEX NO.

G.3.3.1
Sheet 1

REFERENCE LDH-500	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/31/68	OS 8/2/68

(CRD) XE-2 FULL POWER STEADY STATE CONTROL PLATE AXIAL MATERIAL TEMPERATURES (U)

INDEX NO

G.3.3.1
Sheet 2

REFERENCE LDH-500	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/31/68	CS 8/2/68	

THIS PAGE UNCLASSIFIED

(U) CONTROL PLATE AZIMUTH TEMPERATURES FOR 100 PERCENT POWER AND FLOW (U)	INDEX NO
	G.3.3.2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	GS 8/1/68	

The inner reflector and lateral support region temperature distributions are given in this section (G.3.4). In the core periphery region the pyrolytic tile strips are located between the fuel elements and the filler strips as in the NRX-A5 nominal periphery or as in reactors prior to NRX-A5. The design data are given in subsection G.3.4.1 and G.3.4.2.

During reactor operations, there is a change in the radial power profile primarily as a result of core corrosion. This results in variations in the radial temperature profiles. At the core periphery, the fuel element temperature increases with the test run duration. The data given in G.3.4 are for full power condition without considering corrosion effects. However, the variation in core temperature has a negligible effect on the components exterior to the insulation strips and is, therefore, applicable to the entire full power test run in these regions.

The effect of changes in thermal conductivity of the graphite reflector components resulting from gamma radiation has not been included in the present analysis.

(CRD) INNER REFLECTOR AND LATERAL SUPPORT REGION MATERIAL TEMPERATURES (U)	INDEX NO.
	G.3.4

REFERENCE LDH-500	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 8/2/68	ad 8/2/68

(CRD) XE-2 NOMINAL GRAPHITE CYLINDER AXIAL VARIATION OF TEMPERATURE AND RADIAL PRESSURE DROP AT 100 PERCENT POWER AND FLOW (CRD)

INDEX NO

G.3.4.1
Sheet 1

REFERENCE LDH-500	PREPARED BY LDH 8/2/68	APPROVED BY OS 8/2/68	Astronuclear Laboratory

(CRD) XE-2 NOMINAL SEAL SEGMENT AXIAL TEMPERATURE AT 100 PERCENT POWER AND FLOW (CRD)

INDEX NO.

G.3.4.1
Sheet 2

REFERENCE	PREPARED BY		APPROVED BY		Astronuclear Laboratory
	LDH-500	LDH 7/31/68	OS	8/2/68

(CRD) XE-2 NOMINAL FILLER STRIP AXIAL TEMPERATURES AT 100 PERCENT POWER AND FLOW (CRD)

INDEX NO

G. 3. 4. 1
Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/31/68	OS 8/2/68

(CRD) XE-2 NOMINAL PYROGRAPHITE INSULATING TILE TEMPERATURES AT 100 PERCENT POWER AND FLOW (CRD)

INDEX NO

G.3.4.1
Sheet 4

REFERENCE LDH - 500	PREPARED BY LDH 8/2/68	APPROVED BY AS 8/2/68	Astronuclear Laboratory

(CRD) XE-2 NOMINAL INNER REFLECTOR RADIAL TEMPERATURES AT SEAL 2
FOR 100 PERCENT POWER AND FLOW (CRD)

INDEX NO

G. 3. 4. 2

Sheet 1

REFERENCE LDH-500	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/31/68	amb 8/1/68

(CRD) XE-2 NOMINAL INNER REFLECTOR RADIAL TEMPERATURES AT SEAL 9
FOR 100 PERCENT POWER AND FLOW (CRD)

INDEX NO.

G.3.4.2
Sheet 2

REFERENCE LDH-500	PREPARED BY LDH 7/31/68	APPROVED BY QSS 8/2/68	Astronuclear Laboratory

(CRD) XE-2 NOMINAL INNER REFLECTOR RADIAL TEMPERATURES AT SEAL 12 FOR 100 PERCENT POWER AND FLOW (CRD)	INDEX NO
	G.3.4.2 Sheet 3

REFERENCE LDH-500	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/31/68	AS 8/2/68

XE-2 NOMINAL INNER REFLECTOR RADIAL TEMPERATURES AT SEAL (CRD) 18 FOR 100 PERCENT POWER AND FLOW (CRD)	INDEX NO
	G.3.4.2 Sheet 4

REFERENCE

LDH-500

Astronautics
Laboratory

(CRD) XE-2 PRESSURE VESSEL AXIAL TEMPERATURES AT 100 PERCENT POWER AND FLOW (U)

PREPARED BY

LDH 7/31/68

APPROVED BY

GS 8/2/68

INDEX NO.

G.3.5

REFERENCE

LDH-500

(CRD) XE-2 FULL POWER STEADY STATE TIE BOLT AXIAL TEMPERATURES (U)

PREPARED BY

LDH 7/31/68

APPROVED BY

GB 8/2/68

INDEX NO

G.3.6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	AS 8/2/68

Flow entering from reflector cooling holes 1.53 lb/sec

Flow past inlet band 1.205 lb/sec

Flow entering seal system 0.325 lb/sec

Pressure drop (static) through inner reflector bleed holes 3.1 psi

Pressure drop through core band cooling holes 1.6 psi

Pressure drop (static) through impedance inserts 3 psi

Average core band temperature 486°R

Average temperature of core under band
(Core Station 1.25 to 4.25 in.) 795°R

36 inner reflector bleed holes, 0.3125 in. diameter

36 impedance inserts, 0.187 in. ID, 1.0" minimum length

162 filler block cooling slots, 147 at 0.014 x 0.33 in., 15 irregular

150 retainer segment grooves, 0.025 deep, width variable to span spaces between
filler block slots

(CRD) CORE INLET BAND DATA AT 100 PERCENT POWER AND 77.0 LB/SEC FLOW (U)

INDEX NO.

G.3.7

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	AS 8/2/68	

The control drum scram springs are located in the Reflector exit plenum.

Spring Coil Thickness	.08 inches
Spring Height	.937 inches
Maximum spring heat generation rate	3600 Btu/hr in ³
Coolant Gas Temperature	220°R

Nominal Condition: Laminar Natural Convection Assumed in Interior Coil Gaps;
Turbulent Forced Convection Assumed on Exterior Faces.

Average Spring Temperature	526°R
Maximum Spring Temperature	578°R
Interior Coil Gap Film Coefficient	58 Btu/hr ft ² °R

Bundled Condition*: Turbulent Forced Convection Assumed on Exterior Faces.

Maximum Spring Temperature	680°R
Exterior Face Film Coefficient	360 Btu/hr ft ² °R

*This condition occurs when the spring coils contact each other and close the interior coil cooling gaps.

(U) XE-2 FULL POWER AND FLOW STEADY STATE CONTROL DRUM SCRAM SPRING TEMPERATURES(U)	INDEX NO.
	G.3.8

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	OS 7/26/68	

SECTION H

ALUMINUM REPLACEMENT SHIELD, HYDRAULIC AND THERMAL DATA

(U) This section presents the thermal and hydraulic data related to the XE-2 shield which consists of an aluminum replacement shield and the screen assembly. The data include the fluid conditions surrounding the shield and shield temperature distributions.

(U) INTRODUCTION (U)	INDEX NO.
	H

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	OS 7/26/68	

SECTION H

XE-2 DATA

SHIELD: THERMAL - HYDRAULIC DATA

TABLE OF CONTENTS

<u>Index No.</u>		<u>Cross Reference⁽¹⁾</u> <u>Index No.</u>
H.1	(CRD) Shield Flow Model (U)	
*H.2	(U) Shield Thermal Design Criteria, Limitations, and Uncertainties (U)	
H.2.1	(U) Design Criteria (U)	
*H.3	(U) Nominal Design Point - 1120 MW Power at 77.0 lb/sec Flow (U)	
H.3.1	(U) Tabulated Temperature Data (U)	
H.3.2	(CRD) Shield Flow Schematic (U)	
H.3.3	(CRD) Radial Temperature Distributions in the Shield (U)	
H.3.4	(U) Axial Temperature Distributions in the Shield (U)	
	(U) Sheet 1 - Shield Region 1 (Region Locations are given in H.3.3) (U)	
	(U) Sheet 2 - Shield Region 5 (U)	
	(U) Sheet 3 - Shield Region 9 (U)	
	(U) Sheet 4 - Shield Region 10 (U)	
	(U) Sheet 5 - Control Drum Drive Shaft (U)	
	(U) Sheet 6 - Instrumentation Ports (U)	

*There are no data sheets for these index numbers.

(1) Data sheet will be found under Index No. entered in this column.

(U) TABLE OF CONTENTS (U)	INDEX NO.
	H

REFERENCE	PREPARED BY	APPROVED BY
	LDH 7/26/68	OS 4/14/68

(C-RD) ALUMINUM REPLACEMENT SHIELD FLOW MODEL (U)

INDEX NO.

H.1

~~CONFIDENTIAL RESTRICTED DATA~~ Atomic Energy Act of 1954

REFERENCE	PREPARED BY LDH 7/26/68	APPROVED BY GS 7/26/68	Astronuclear Laboratory
-----------	----------------------------	---------------------------	--

THIS PAGE UNCLASSIFIED

(U) The object of the thermal design of the aluminum replacement shield was to simulate the hydraulic conditions expected for the radiation shield it replaces. Difficulties in temperature level or temperature gradients may be discounted.

(U) The screen was designed to keep foreign particles from entering and plugging the core orifices. Significant design criteria are listed below:

- 1) Simulate radiation shield pressure drop
- 2) Minimize temperature gradients and assure proper cooling of all components
- 3) Minimize coolant temperature and pressure maldistributions

(U) The heat generation rates of the shield material are obtained from Section F. The dashed lines in H.3.3 show the temperature distributions at the vicinity of the interface between Pass 1 and Pass 2 which reflect an average heating rate, from data in Section F, in this region of the shield.

(U) SHIELD THERMAL DESIGN CRITERIA AND LIMITATIONS (U)	INDEX NO.
	H.2.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
AYL-03017	LDH 7/26/68	as 7/26/68	

THIS PAGE UNCLASSIFIED

	$^{\circ}$ R
Maximum Radial H_2 Temperature Difference at the Pass 2 Outlet	0.4
Maximum Local Temperature in the Replacement Shield, Location - Centerline Nozzle End, T_{max}	333
Maximum Local Temperature Difference in the Replacement Shield, Location - Centerline, Nozzle End, $T_{max} - T_{wall}$	62
Maximum Axial Temperature Difference in the Replacement Shield, Location - Centerline, T_{avg} Nozzle End - T_{avg} Dome End	97
Maximum Radial Temperature Difference in the Replacement Shield, Location - $-T_{avg}$ Centerline - T_{avg} Port Radius	37
Maximum Local Temperature in the Seal Flange	460
Maximum Temperature Difference in the Seal Location - Flange Section Perpendicular to the Nozzle End of Seal	190
Maximum Local Temperature in the Seal Flange Attaching Capscrew Location - End of Head Opposite from Thread	370
Maximum Temperature Difference in the Head of the Seal Flange Attaching Capscrew	50
Maximum Temperature Difference in the Thread of the Seal Flange Attaching Capscrew	70
Maximum Local Temperature in the Shield Lifting Lug	235
Maximum Temperature Difference in the Shield Lifting Lug	16
Maximum Temperature in Screen Assembly	280
Maximum Temperature Difference in Screen Assembly	
Axial	25
Radial	10

(U) ALUMINUM REPLACEMENT SHIELD AND SCREEN ASSEMBLY TEMPERATURE DATA FOR 100 PERCENT POWER AND FLOW (U)

INDEX NO.

H.3.1

REFERENCE AYL-03017	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	as 7/26/68

SHIELD POWER GENERATION	
PASS 1 (INCLUDING CONTROL DRUM DRIVE SHAFTS AND INSTRUMENTATION STALKS)	1.25 MW
PASS 2	0.81 MW
SCREEN ASSEMBLY	NEGLECTIBLE
TOTAL	2.06 MW

(CRD) ALUMINUM REPLACEMENT SHIELD FLOW SCHEMATIC AT 100 PERCENT POWER AND FLOW (U)	INDEX NO
	H. 3, 2

REFERENCE AYL-03017	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	as 7/26/68

(CRD) RADIAL TEMPERATURE DISTRIBUTION IN SHIELD AT 100 PERCENT POWER AND FLOW (U)	INDEX NO
	H.3.3

REFERENCE AYL-03017	PREPARED BY LDH 7/26/68	APPROVED BY OB 7/26/68	Astronuclear Laboratory

THIS PAGE UNCLASSIFIED

(U) AXIAL TEMPERATURE DISTRIBUTIONS IN SHIELD AT 100 PERCENT POWER AND FLOW (U)

INDEX NO.

H.3.4
Sheet 1

REFERENCE AYL-03017	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	L.D.H. 7/26/68	OB 7/26/68

(U) AXIAL TEMPERATURE DISTRIBUTIONS IN SHIELD AT 100 PERCENT POWER AND FLOW (U)

INDEX NO

H. 3.4
Sheet 2

REFERENCE AYL-03017	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	GS 7/26/68

(U) AXIAL TEMPERATURE DISTRIBUTIONS IN SHIELD AT 100 PERCENT POWER AND FLOW (U)

INDEX NO.

H. 3.4
Sheet 3

REFERENCE AYL-03017	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	CS 7/26/68

(U) AXIAL TEMPERATURE DISTRIBUTIONS IN SHIELD AT 100 PERCENT POWER AND FLOW (U)

INDEX NO.

H. 3. 4
Sheet 4

REFERENCE AYL-03017	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	OS 7/26/68

(U) AXIAL TEMPERATURE DISTRIBUTION IN SHIELD AT 100 PERCENT POWER AND FLOW (U)	INDEX NO
	H. 3.4 Sheet 5

REFERENCE AYL-03017	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	LDH 7/26/68	OS 7/26/68

(U) AXIAL TEMPERATURE DISTRIBUTION IN SHIELD AT 100 PERCENT POWER AND FLOW (U)	INDEX NO
	H.3.4 Sheet 6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.L. 8/12/68	AS 8/14/68	

SECTION I

CORE: THERMAL - HYDRAULIC DATA

INTRODUCTION

This section of the Data Book includes data relative to the thermal-hydraulic analyses performed on the XE-2 core subassembly which consists of the core support plate, cluster plates, fuel element orifices, fueled and unfueled core elements, tie rod and support blocks. The data sub-divisions are arranged on a component basis and include mechanical, thermal and hydraulic data. Specific data may be located by reference to the detailed Table of Contents which follows this introduction.

(CRD) INTRODUCTION (U)	INDEX NO.
	I

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/7/68	GD 8/7/68	

SECTION I

XE-2
CORE: THERMAL - HYDRAULIC DATA

TABLE OF CONTENTS

<u>Index No.</u>		<u>Cross Reference Index No.¹</u>
*I.1	XE-2 Models (U)	
1.1.1	(CRD) Computer Codes (U)	
1.1.2	(CRD) Core Orientation and Cluster Identification (U)	C.1.1.4
1.1.3	(CRD) Element and Filler Strip Identification (CRD)	C.1.1.5
1.1.4	(CRD) Element Description and Identification (U)	C.1.1.6
1.1.5	(CRD) Element Radial Location (U)	C.1.1.7
1.1.6	(CRD) Fuel Cluster - Dome End (U)	C.1.1.9
1.1.7	(CRD) Fuel Cluster and Support Block - Nozzle End (U)	C.1.1.8
*I.2	Core Limitations (U)	
1.2.1	(CRD) Design Criteria (U)	D.2
*1.2.2	Uncertainties (U)	
1.2.2.1	(CRD) Fuel Element Hot Channel Data (U)	
	(CRD) Sheet 1 - Single Cause and Effects (U)	
	(CRD) Sheet 2 - Combined 3 Cause and Effects (U)	
	(CRD) Sheet 3 - Nominal and Statistical Maximum Radial Fuel Temperature Distribution (U)	
	(CRD) Sheet 4 - Total Elements Per Core Above The Indicated Exit Gas Temperature (U)	
	(CRD) Sheet 5 - Notes to XE-2 Hot Channel Factors (U)	
	(CRD) Sheet 6 - Change in Fuel Exit Gas Temperature Versus Control Drum Angle (U)	
1.2.2.2	(CRD) Sensor to Fuel Temperature Differences and Uncertainties (U)	
*1.2.3	Support Block Maximum Radial Temperature Difference During Transients (U)	
	(CRD) Sheet 1 - Startup (U)	
	(CRD) Sheet 2 - Shutdown (U)	
*I.3	XE-2 Core Data (U)	
1.3.1	(CRD) Core Mechanical Data (U)	
1.3.2	(CRD) Core Thermal Data (U)	
1.3.3	(CRD) Core Hydraulic Data, Full Power and Flow (U)	
1.3.4	(CRD) Sensor to Fuel Element Temperature Correlation (U)	
	(CRD) Sheet 1 - Sensor to Fuel Element Temperature Difference Versus Relative Local Power Factor in Unfueled Element (U)	
	(CRD) Sheet 2 - Normalized Axial and Radial Power Factors for Use in Sensor to Fuel Element Temperature Correlation (U)	

*There are no data sheets corresponding to these index numbers
(1) Data sheet will be found under Index No. entered in this column.

(CRD) TABLE OF CONTENTS (U)	INDEX NO.
	I

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/7/68	OS 8/7/68	

SECTION I

XE-2
CORE: THERMAL - HYDRAULIC DATA

TABLE OF CONTENTS

Index No.

1.4	(CRD)	Core Support Plate Data (U)
*1.5		Fuel Element Orifices (For Orifice Loss Coefficients and Acceptance Limits see NRX-A4 Data Book, WANL-TME-1210, Section 1.4 e) (U)
1.5.1	(CRD)	XE-2 Master Orifice Jet Loss Coefficients (U)
1.5.2	(CRD)	Orifice Loss Coefficient and Diameter Versus Power Factor (CRD)
1.5.3	(CRD)	XE-2 Fuel Element Orifice Summary (CRD)
*1.6		Fuel Element Steady State Data (U)
1.6.1	(CRD)	Fuel Element Mechanical Data (U)
1.6.2	(CRD)	Fuel Element Axial Conditions at Full Power and Flow (U)
	(CRD)	Sheet 1 - 1.2 Power Factor (CRD)
	(CRD)	Sheet 2 - 1.0 Power Factor (CRD)
	(CRD)	Sheet 3 - 0.8 Power Factor (CRD)
1.6.3	(CRD)	Effect of Core Inlet Temperature on Exit Gas Temperature and Core Pressure Drop (U)
1.6.4	(CRD)	Axial Temperatures for XE-2 Steady State Holds, As Orificed (CRD)
	(CRD)	Sheet 1 - Fuel Temperatures (U)
	(CRD)	Sheet 2 - Gas Temperatures (U)
*1.7		Unfueled Central Element and Tie Rod Steady State Data (U)
1.7.1	(CRD)	Unfueled Element and Tie Rod Channel Data (U)
1.7.2	(CRD)	Unfueled Central Element and Tie Rod Model Description (U)
1.7.3	(CRD)	Average Unfueled Central Element and Tie Rod Channel Axial Conditions (U)
1.7.4	(CRD)	Tie Rod Exit Gas Temperature Versus Tie Rod Power Factor and Core Radius (U)
1.8	(U)	Startup and Shutdown Profile Used in Section I Analysis (6 Sheets) (U)
1.8.1	(CRD)	Average Fuel Cluster During 150°R/sec Startup (U)
	(CRD)	Sheet 1 - Axial Variation of Fuel Element Average Temperature (U)
	(CRD)	Sheet 2 - Axial Variation of Unfueled Central Element Average Temperature (U)
	(CRD)	Sheet 3 - Axial Variation of Temperature Difference Between Fueled and Unfueled Elements (U)
1.8.2	(CRD)	Peripheral Fuel Cluster (J8) With Partial Unfueled Element During 150°R/sec Startup (CRD)
	(CRD)	Sheet 1 - Axial Variation of Fuel Element Average Temperature (Adjacent to Partial Element) (CRD)
	(CRD)	Sheet 2 - Axial Variation of Unfueled Partial Element Average Temperature (CRD)
	(CRD)	Sheet 3 - Axial Variation of Unfueled Central Element Average Temperature (U)
	(CRD)	Sheet 4 - Axial Variation of Temperature Difference Between Unfueled Partial Element and Adjacent Fuel Element (CRD)
	(CRD)	Sheet 5 - Coolant Exit Gas Temperature (U)

*There are no data sheets corresponding to these index numbers.

(1) Data Sheet will be found under Index No. entered in this column.

(CRD) TABLE OF CONTENTS (U)

INDEX NO.

I

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/7/68	ASB 8/7/68	

SECTION I

XE-2
CORE: THERMAL-HYDRAULIC DATA

TABLE OF CONTENTS

Index No.

*1.9		Core Support Block and Tie Rod End (U)
*1.9.1		Regular Support Block (U)
1.9.1.1	(CRD)	Full Power, Steady State Temperatures (U)
1.9.1.2	(CRD)	Summary of Radial Temperature Differences During 50, 100 and 150°R/sec Startups (U)
1.9.1.3	(CRD)	50°R/sec Startup (U)
	(CRD)	Sheet 1 - Radial Temperature Profiles (U)
	(CRD)	Sheet 2 - Temperature Distribution of Time of Maximum Radial Temperature Difference (U)
1.9.1.4	(CRD)	100°R/sec Startup (U)
	(CRD)	Sheet 1 - Radial Temperature Profiles (U)
	(CRD)	Sheet 2 - Temperature Distribution at Time of Maximum Radial Temperature Difference (U)
1.9.1.5	(CRD)	150°R/sec Startup (U)
	(CRD)	Sheet 1 - Radial Temperature Profiles (U)
	(CRD)	Sheet 2 - Temperature Distribution at Time of Maximum Radial Temperature Difference (U)
1.9.1.6	(CRD)	Summary of Radial Temperature Differences During 100 and 300°R/sec Shutdown (U)
1.9.1.7	(CRD)	100°R/sec Shutdown (U)
	(CRD)	Sheet 1 - Radial Temperature Profiles (U)
	(CRD)	Sheet 2 - Temperature Distribution at Time of Maximum Radial Temperature Difference (U)
1.9.1.8	(CRD)	300°R/sec Shutdown (U)
	(CRD)	Sheet 1 - Radial Temperature Profiles (U)
	(CRD)	Sheet 2 - Temperature Distribution at Time of Maximum Radial Temperature Difference (U)
*1.9.2		Peripheral Partial Support Block (J8) (U)
1.9.2.1	(CRD)	Summary of Radial Temperature Profiles During 150°R/sec Startup (U)
1.9.2.2	(CRD)	Summary of Radial Temperature Differences During 150°R/sec Startup (U)
1.9.2.3	(CRD)	Summary of Radial Temperature Difference During a 350°R/sec Scram (U) ✓
*1.9.3		Support Block and Tie Rod End for Hollow Tie Rod With Exit T/C (CRD)
1.9.3.1	(CRD)	Full power, Steady State Temperature Distribution (CRD)
1.9.3.2	(CRD)	Temperature Distribution of Exit Gas Thermocouple Assembly at 100% Power and Flow (U)
1.9.3.3	(CRD)	Exit Gas Temperature Versus Core Radius and Location of Exit Gas Thermocouples (U)

*There are no data sheets corresponding to these index numbers.
(1) Data sheet will be found under Index No. entered in this column.

(CRD) TABLE OF CONTENTS (U)	INDEX NO.
	I

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/7/68	ab 8/7/68	

SECTION I

XE-2
CORE: THERMAL-HYDRAULIC DATA

TABLE OF CONTENTS

Index No.

*I. 10		Core Interelement Pressure Distributions (U)
I. 10. 1	(CRD)	XE-2 Normalized Interelement Pressure Distribution For Full Power and Flow Conditions (U)
I. 10. 2	(CRD)	XE-2 Axial Variation of Normalized Interelement Pressure For Design and Part Power Conditions (U)
I. 10. 3	(CRD)	XE-2 Interelement Pressure Probe Predictions as a Function of Chamber Temperature (U)

*There are no data sheets corresponding to these index numbers.
(1) Data sheet will be found under Index No. entered in this column.

(CRD) TABLE OF CONTENTS (U)	INDEX NO.
	I

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	as 8/5/68	

Code

MCAP (Multiple Channel
Analysis Program)
WANL-TME-944

TOSS (Transient or Steady
State Temperatures)
WANL-TME-1108

Tie Rod
Thermal Design Computer
Code Manual (Internal)

EPOD
WANL-TME-871

TRACK (Transient
Convection and Conduction)
WANL-TME-1736

Description and Usage

Hydraulic and convective heat transfer code which balances
flow in parallel channels. Used to determine core flow
balance and coolant temperatures and pressures.

Heat conduction code which determines the temperature
distribution in a component for given surface boundary
conditions (boundary temperatures and heat transfer coefficient).

Hydraulic, conduction, convection, radiation heat transfer
code which includes flow balancing in parallel tie rod
channels and determines material temperatures when the
heat generation rates are known. Used in iterations with
MCAP to determine core flow balance, pressure drop and
temperatures when the total flow and plenum conditions
are known.

A combination of several codes using nuclear data, fuel
element inspection data, parameterized thermal and
hydraulic data from MCAP, and measured orifice
performance data to specify element locations in the
core and orifice sizes to be used.

A steady-state and transient code which combines hydraulic
and convective heat transfer solutions with internal heat
conduction solution which is obtained by TOSS code. This
program is the primary tool for determining fuel cluster
steady-state and transient behavior.

(CRD) COMPUTER CODES USED IN CORE THERMAL AND HYDRAULIC DESIGN (U)

INDEX NO.

1.1.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C. 8/2/68	OSB 8/5/68	

XE-2 FUEL ELEMENT EXIT GAS HOT CHANNEL DATA,
SINGLE CAUSE AND EFFECTS

Cause (3 σ)	Center PF=1.16	Effect, °R		Percent Contribution (Center)
		Trough PF=1.0	Edge PF=0.92	
<u>Regional Effects</u>				
1. Horizontal Power Prediction + 3.6%, center and trough + 3.7%, edge	189	170	161	28
2. Average Core Inlet Temperature + 46.1°R	134	0	35	14
3. Radial Variation in Core Inlet Temperature + 19°R	74	96	105	4
4. Axial Power Shape + 10%	24	22	21	*
<u>Element Effects</u>				
5. Gamma Scan Precision + 1%, center and trough + 2%, edge	52	47	88	2
6. Support Block Misalignment + 0.023 inches	44	31	25	2
7. Operating Channel Diameter + 0.002 inches	230	159	130	42
8. Orifice Mismatch + 200°R, single channel	46	72	66	2
<u>Channel Effects</u> ⁽¹⁾				
9. Fuel Homogeneity ⁽²⁾ + 17.3%	376	335	314	6
10. Orifice Coefficient + 50°R	50	50	50	2

* Less than 1%

(1) Single channel basis. The variance is divided by 19 to account for radial conduction within the element.

(2) Represents combined effect of: reamed channel diameter ± 0.001 inch, channel orientation ± 0.018 inch, fuel bead concentration $\pm 2.9\%$.

(CRD) SINGLE CAUSE AND EFFECTS (U)	INDEX NO.
	1.2.2.1 Sheet 1

REFERENCE

INDEX NO.
1.2.2.1 Sheet 2

(CRD) XE-2 HOT CHANNEL DATA COMBINED 3rd CAUSE AND EFFECTS (U)

PREPARED BY	APPROVED BY
G.E.C. 8/4/68	Q.S. 8/5/68

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	Q3 8/5/68

(CRD) NOMINAL AND STATISTICAL MAXIMUM RADIAL FUEL TEMPERATURE DISTRIBUTION (U)

INDEX NO

I.2.2.1
Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C.	OSD 8/5/68

(CRD) TOTAL ELEMENTS PER CORE ABOVE THE INDICATED EXIT GAS TEMPERATURE (CRD)	INDEX NO
	I.2.2.1 Sheet 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/7/68	QJ 8/7/68	

- Regional effects occur equally in all elements within the one-inch radial increment.
- Element effects occur equally in all channels within an element.
- Channel effects occur individually in a single coolant channel.
- To account for radial conduction within a fueled element, the channel hot channel effects are divided by $\sqrt{19}$ before adding to the regional and element effects.
- Temperature effects are added statistically, as the sum of squares to arrive at the combined hot channel temperature for an element, i.e.,

$$(\Delta T_{\text{total}})^2 = \sum_{i=1}^n (\Delta T_i)^2$$
- Separation into regional and element effects is for information purposes only. Both are treated identically in the analysis.
- All effects are assumed to be normally distributed according to the Gauss error function. Combining them tends to make the total hot channel effect follow the Gauss distribution because of the central limit theorem, even when all of the individual effects do not.
- All effects are assumed to be mutually independent; however, the regional effects tend to be less than nominal in the remaining regions to compensate for any one region being above nominal. The result is that each regional effect averages to zero over the entire core and introduces a conservatism in the analysis. This introduces a conservatism in the predicted number of elements above a given temperature.
- Factors which affect the entire core as a unit, control drum effects, a possible bias which may exist in the WNCO versus Y-12 reported uranium loadings, and the effects of uncertainties on the temperature difference from the gas to the channel wall are not included in the prior analysis and are discussed below.
 - The only significant hot channel factor affecting the entire core as a unit is the control point accuracy which is estimated to be $+150^\circ\text{R}$ (3σ) based on NRX-A6 results. The correct value for XE-2 will depend on the particular control mode selected for the full power run. It should be added directly (not statistically) to the hot channel temperatures given in 1.2.2.1, Sheets 2 and 3.
 - Control drum effects for the various radial regions are given on Figure 1.2.2.1, Sheet 6. The exit gas temperature change is given as a function of control drum angle. The temperature change for the operating drum angle should be directly added (not statistically) to the nominal or statistical maximum temperature for the radial region of interest.
 - All hot channel temperatures shown apply to the fuel exit gas temperature. Additional uncertainties apply to the temperature difference between the coolant channel wall and the fuel exit gas. These include the uncertainties in the local power prediction, the local fuel concentration, the heat transfer film coefficient, and the coolant flow rate. At core station 50 inches where the channel wall temperatures are at the maximum, the resulting uncertainty in wall to coolant bulk temperature is 16°R across the core. This increase, when added statistically to the uncertainty in gas temperature, is negligible.
- The method of computing the number of hot elements per radial region is to multiply the total number of elements per region by the integral of the Gauss error function.

$$N_{i_T} = N_{i_O} \frac{1}{2\pi} \int_T^\infty e^{-t^2/2} dt$$

where

N_{i_T} = Number of elements above selected temperature per radial region.

N_{i_O} = Total number of elements in the radial region.

T = Selected temperature expressed in standard deviations above nominal.

t = Pseudo-variable to be integrated.

(CRD) NOTES TO XE-2 HOT CHANNEL FACTORS (U)

INDEX NO.

1.2.2.1
Sheet 5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	QSD 8/5/68

(CRD) CHANGE IN FUEL EXIT GAS TEMPERATURE VERSUS CONTROL DRUM ANGLE (U)

INDEX NO

1.2.2.1
Sheet 6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	GD 8/5/68	

RESULTS OF CORE MATERIAL THERMOCOUPLE UNCERTAINTY ANALYSIS
FOR AVERAGE CONDITIONS AT FULL POWER

1 Core Station inches	2 Combined Effects of Uncertainties % Error in ΔT (3σ)	3 *Nominal Value of ΔT , $^{\circ}R$		6 3 σ Uncertainty in ΔT , $^{\circ}R$		
		Calculated by Track	Test Results	Calculated Using Track as Base ΔT Column 2 x 3	Calculated	
					Using Test Results as Base ΔT Columns 2 x 4	Using Multiple Regression Analysis on NRX-A6 Test Data
20	+46% -36%	326	310	+150 -117	+143 -112	+130
26	+39%	348	360	+136	+140	+169
32	+39%	302	340**	+118	+133**	+220**

* Temperature Difference between thermocouple and average temperature in adjacent fuel element

** Using Thermal capsule data

FACTORS AFFECTING CORE MATERIAL THERMOCOUPLE MEASUREMENTS

I. Systematic Effects (Affect all Thermocouples at Station Equally)

- 1) Axial Heating +20%
- 2) Hydrogen Conductivity +20%
- 3) Graphite Conductivity +30%
- 4) Average inter-element gap +50%

II. Random Effects (Affect Individual Thermocouples)

- 1) H Gap Between Thermocouple and Sleeve +0.001 in.
- 2) H Gap Between Tungsten Sleeve and Graphite 0.005 + 0.0005 (sta. 20)
- 0.0025
- 3) H Gap Between Elements 0.009 + 0.0005 (sta. 26, 32)
- 0.0065
- 4) Radial Power Factor in Unfueled Graphite 0.000 min.
0.003 max.

(CRD) SENSOR TO FUEL TEMPERATURE DIFFERENCES AND UNCERTAINTIES (U)	INDEX NO.
	1. 2. 2. 2

REFERENCE	PREPARED BY		APPROVED BY		Astronuclear Laboratory
	GEC	8/5/68	ASB	8/5/68

(CRD) SUPPORT BLOCK MAXIMUM TEMPERATURE DIFFERENCE AS A FUNCTION OF NOZZLE CHAMBER TEMPERATURE RAMP RATE DURING STARTUP (U)

INDEX NO

1.2.3
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	Q.B. 8/5/68

(CRD) SUPPORT BLOCK MAXIMUM RADIAL TEMPERATURE DIFFERENCE AS A FUNCTION OF NOZZLE CHAMBER TEMPERATURE COOLDOWN RATE FROM 100 PERCENT POWER AND FLOW (U)

INDEX NO.

1.2.3
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY		Astronuclear Laboratory
	G. E. C.	8/2/68	ojs 8/5/68	

MECHANICAL DATA

<u>Item</u>	<u>Units</u>	<u>Value</u>	<u>Reference</u>
Fuel Element Length ⁽¹⁾	inch	52.0 $\pm$.005	
Core Diameter, Nominal ⁽¹⁾ (Filler Strip O.D.)	inch	35.54 $\pm$ 0.01	
Axial Expansion of Core	inch	0.220	TME-1561
Thermal Coefficient of Expansion Fuel Temperature, 3000°R Parallel to Extrusion	inch/inch - °R	1.61 $\times 10^{-6}$	TME-1561
Radial Expansion of Core - Maximum	inch	0.17	TME-1561
Radial Expansion of Core - Average	inch	0.12	TME-1561
Thermal Coefficient of Expansion Fuel Temperature, 3000°R Perpendicular to Extrusion	inch/inch - °R	2.17 $\times 10^{-6}$	TME-1561
No. Regular Fueled Elements	(19 channels)	1584	
No. Partial Unfueled Elements		42	
No. Regular Clusters		199	
No. Irregular Clusters		42	
No. Fueled Elements Per Regular Cluster		6	
Total Coolant Channels - Fueled Elements		30,096	
Average Channel Diameter	inch	0.09527 ⁽²⁾	
Minimum Channel Diameter	inch	0.0929 ⁽²⁾	
Orifice Jet Machining Tolerances			
sizes $\geq$ 0.050	inch	$\pm$ 1 percent ID	
sizes $>$ 0.050	inch	$\pm$ 0.005	

All data are for design conditions (100 percent power and flow) except as noted.

(1) These data are at room temperature, as coated.

(2) For "as-built" conditions, after corrections for expected effects of moly overcoat at operating conditions, values below drawing tolerance were accepted by variation request on an individual basis considering core location and other factors.

(CRD) CORE MECHANICAL DATA (U)	INDEX NO.
	1.3.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C.	8/7/68 QSD 8/7/68	

<u>Item</u>	<u>Units</u>	<u>Value</u>	<u>Reference</u>
THERMAL DATA - Full Power			
Heat Transfer Area	inch ²	466,837	Based on 0.0950 In. Average Channel Diameter 30,096 Fueled Channels
Core Thermal Power (Fueled Elements)	MW	1083.2	inch
Core Thermal Power (Unfueled Elements)	MW	14.3	
Total Core Thermal Power	MW	1097.5	
Core Average Heat Flux	Btu/sec-inch ²	2.230	
Maximum Radial Power Factor (Nominal U Loading)		1.212	For 115° Drum Angle
Minimum Radial Power Factor (Nominal U Loading)		0.68	For 115° Drum Angle
Maximum to Average Axial Power		1.38	
Overall Maximum to Average Power		1.673	For 115° Drum Angle
Maximum Core Heat Flux	Btu/sec-inch ²	3.731	For 115° Drum Angle
Average Power Density Parameter ⁽¹⁾	MW/ft ³	39.04 ⁽²⁾	67.15 ⁽³⁾
	W/cc	1378.6 ⁽²⁾	2372.4 ⁽³⁾
<u>Core Inlet Conditions</u>			
Average Fluid Temperature	°R	220.8	
Pressure	psia	698	
Enthalpy	Btu/lb	596	WANL-TME-1478
Specific Volume	ft ³ /lb	1.723	WANL-TME-1478
<u>Fueled Element Outlet Conditions</u>			
Average Fluid Temperature	°R	4307	
Pressure	psia	563	
Enthalpy	Btu/lb	16,163	WANL-TME-1478
Specific Volume	ft ³ /lb	40.84	WANL-TME-1478
<u>Nozzle Chamber Conditions</u>			
Temperature	°R	4090	
Pressure	psia	563	
Enthalpy	Btu/lb	15,199	WANL-TME-1478
Specific Volume	ft ³ /lb	39.11	WANL-TME-1478

- (1) To obtain maximum, multiply values shown by overall maximum to average power (1.673).
 (2) Based on overall core volume including 1584 fuel elements, 42 graphite partial elements and 289 central elements. (Support blocks, filler strips and interstitial gap volume not included)
 (3) Based on fueled volume (1584 fueled elements with 0.099 inch reamed diameters 51 inches long)

(CRD) XE-2 CORE THERMAL DATA (U)	INDEX NO.
	1.3.2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	CS 8/5/67	

HYDRAULIC DATA - Full Power

Fueled Element Flow	lb/sec	66.137
Tie Rod Element Flow	lb/sec	4.73
Bypass Flow	lb/sec	0.683
Flow in Unfueled Partial Elements	lb/sec	0.05
Total Core Flow	lb/sec	71.6

Core Flow Areas

Fueled Elements	inch ²	213.33	(Based on 0.095 inch diameter channel as designed conditions)
Unfueled Elements	inch ²	8.34	
Core Pressure Drop	psid	135	
Percent of Total Core Flow for Tie Rods		6.6	

FRICITION FACTOR FOR CORE COOLANT CHANNELS

$$f = \left(\frac{T_B}{T_W} \right)^{0.5} \left[0.0014 + 0.125 / (N_{Re})^{0.32} \right]_S \times \left[(1.8 \times 10^{-5}) N_{Re} + 0.73 \right]_R^{0.5}$$

- where
- f = Friction factor
 - N_{Re} = Reynold's number based on channel wall temperature
 - T_B = Coolant bulk temperature
 - T_W = Channel wall temperature
 - Subscripts
 - S = Denoting smooth tube correlation
 - R = Roughness correction

(CRD) CORE HYDRAULIC DATA, FULL POWER AND FLOW (U)	INDEX NO
	1.3.3

REFERENCE

(CRD) SENSOR TO FUEL ELEMENT TEMPERATURE DIFFERENCE VERSUS RELATIVE LOCAL POWER FACTOR IN THE UNFUELED ELEMENT (U)

PREPARED BY
GEC 8/2/68

APPROVED BY
ASB 8/5/68

INDEX NO

1.3.4
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. CORT 8/5/68	GSD 8/5/68

(CRD) XE-2 NORMALIZED RADIAL AND AXIAL POWER FACTORS IN UNFUELED ELEMENTS FOR USE IN SENSOR TO FUEL ELEMENT TEMPERATURE CORRELATION (U)

INDEX NO

1.3.4
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C.	8/2/68	03 8/1/68

Item	Units	Value
MECHANICAL DATA		
Overall Diameter of Core Support Plate	inch	41.0
Thickness at Center	inch	6.0
Thickness at core periphery (35.562 diameter)	inch	4.125
No. of 0.375 inch Diameter Flow Holes		1629
No. of 0.312 inch Diameter Flow Holes		396
No. of 0.368 inch Diameter Flow Holes		225
No. Tie Rod Hanger Holes		289
No. of Flow Holes in Hanger Support		6
Dimensions of Flow Holes in Hanger Support Slot		
Length	inch	0.250 +.005 -.000
Width	inch	0.0937 +.003 -.000

THERMAL DATA

Maximum Heating Rate in Core Support Plate on Core Centerline	Btu/Hr-inch ³	3670
Maximum Metal Temperature at Core Centerline, Nozzle Side	°R	340
Maximum Metal Temperature at Core Centerline, Dome Side	°R	241
Maximum Metal Temperature at R = 8.0 inch, Nozzle Side	°R	321
Maximum Metal Temperature at R = 8.0 inch, Dome Side	°R	245
Maximum Metal Temperature at R = 17.0 inch, Nozzle Side	°R	284
Coolant Inlet Temperature	°R	215.8
Average Coolant Temperature Rise in Support Plate	°R	5
Average Coolant Exit Temperature from Support Plate	°R	220.8

(CRD) CORE SUPPORT PLATE MECHANICAL AND THERMAL DATA
AT FULL POWER AND FLOW (U)

INDEX NO.

I. 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/7/68	Q.B. 8/7/68

(CRD) XE-2 MASTER ORIFICE JET LOSS COEFFICIENTS (U)	INDEX NO.
	1.5.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C. 8/2/68	OS 8/5/68

(CRD) ORIFICE LOSS COEFFICIENT AND DIAMETER VERSUS POWER FACTOR (CRD)	INDEX NO
	1.5.2

REFERENCE

XE-2 Fuel Element Orifice Summary

Row	22.5	24.0	25.5	27.5	30.0	33.0	36.0	40.0	45.0	50.0	60.0	70.0	Average Channel Diameter	Channels Per Row
00								32	52	26	4		0.09520	114
A							279	280	96	22	4	3	0.09514	684
B						177	651	418	96	22	4		0.09501	1368
C					8	909	971	154	9	1			0.09531	2052
D					259	1698	763	16					0.09482	2736
E				3	2404	1000	13						0.09531	3420
F				496	3533	75							0.09527	4104
G				581	3787	384	34	2					0.09526	4788
H			1	332	1816	930	236	90	15				0.09510	3420
J	125	561	1207	2280	1937	848	298	128	26				0.09559	7410
Total	125	561	1208	3692	13744	6021	3245	1120	294	71	12	3	0.09527	30096

INDEX NO. 1.5.3	(CRD) XE-2 FUEL ELEMENT ORIFICE SUMMARY (CRD)	PREPARED BY	APPROVED BY
		G.E.C. 8/7/68	QJ 8/7/68

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C. 8/2/68	ojs 8/5/68	

<u>Item</u>	<u>Units</u>	<u>Value</u>
MECHANICAL DATA		
Maximum Twist	inch	0.008
Maximum Bow	inch/inch	0.005
Maximum Fuel Channel Misalignment with Support Block	inch	0.023
Channel Spacing (Equilateral Triangle)	inch	0.173
Unfueled Tip Length	inch	1.0 Ref
Distance Across Flats for Coated Elements	inch	0.754 ^{+0.000} -0.002
Distance Across Flats for Uncoated Elements	inch	0.7537 ^{+0.000} -0.0014
No. of Unfueled Partial Elements Used in Core		42
Air Impedance Diameter of Unfueled Partial Elements	inch	0.070 $\pm$ 0.005
Orifice Size Used in Unfueled Partial Elements	inch	0.0275 $\pm$ 0.0005

(CRD) FUEL ELEMENT MECHANICAL DATA (U)	INDEX NO
	1.6.1

REFERENCE

Diameter 0.0950 in.
Inlet Loss Coefficient 24.55
Power 0.04349 MW
Flow 0.002658 lb/sec

X	P	T	TS	TW	TF	Q	H	REB	V
0.000	698.200	220.80							
0.000	684.888	220.80	221.44	459.60	467.43	0.8044	1750	123464	3035.57
2.000	684.299	280.25	280.33	685.87	699.91	1.2736	1628	107156	3876.13
4.000	683.526	365.26	365.39	1003.15	1025.95	1.7161	1395	90670	5063.13
6.000	682.504	481.99	482.24	1390.71	1426.66	2.1317	1216	75981	6688.42
8.000	681.220	626.57	626.98	1726.29	1778.36	2.5069	1182	63980	8666.37
10.000	679.623	797.77	798.45	1911.50	1976.92	2.8153	1311	54719	11013.26
12.000	677.690	988.15	989.19	2042.69	2119.74	3.0701	1511	47361	13635.21
14.000	675.402	1191.83	1193.34	2185.60	2274.15	3.2551	1700	41436	16459.73
16.000	672.746	1405.75	1407.86	2386.35	2489.49	3.4106	1807	36383	19452.43
18.000	669.731	1625.23	1628.02	2551.00	2666.63	3.5340	1984	32847	22556.17
20.000	666.326	1850.24	1853.88	2723.66	2851.15	3.6197	2156	29872	25778.55
22.000	662.535	2076.89	2081.33	2897.66	3035.59	3.6734	2332	27432	29073.06
24.000	658.375	2299.42	2304.93	3067.76	3214.19	3.7002	2513	25492	32365.60
26.000	653.812	2522.58	2529.29	3240.71	3393.41	3.6948	2690	23804	35730.45
28.000	648.892	2736.28	2743.97	3414.53	3570.28	3.6413	2812	22423	39029.77
30.000	643.598	2944.34	2953.38	3580.10	3735.73	3.5473	2930	21244	42323.27
32.000	637.947	3142.86	3152.92	3734.85	3887.54	3.4160	3038	20229	45559.43
34.000	631.969	3327.51	3338.99	3869.39	4016.08	3.2389	3159	19390	48677.35
36.000	625.654	3501.32	3514.28	3991.88	4130.54	3.0299	3280	18670	51724.15
38.000	619.038	3659.56	3673.54	4098.39	4227.10	2.7886	3392	18059	54630.00
40.000	612.142	3801.15	3816.57	4187.46	4303.97	2.5069	3490	17545	57376.54
42.000	604.974	3927.99	3944.19	4264.04	4368.47	2.2334	3602	17119	59990.83
44.000	597.590	4034.13	4051.53	4320.37	4411.05	1.9306	3699	16778	62373.38
46.000	589.987	4124.52	4143.17	4364.08	4440.82	1.6276	3787	16498	64595.33
48.000	582.191	4198.71	4218.54	4392.13	4453.97	1.3085	3864	16275	66641.72
50.000	574.179	4263.27	4283.64	4411.54	4458.63	0.9947	3969	16088	68615.86
52.000	566.202	4284.99	4305.47	4303.43	4303.43	0.0000	4069	16026	69937.29
54.000	558.180	4284.10	4305.14	4303.04	4303.04	0.0000	4073	16029	70924.57
54.000	563.258	4303.80	4307.00						

X Channel axial distance from inlet, inches
P Channel pressure, psia
T Gas temperature, °R
TS Stagnation gas temperature, °R
TW Channel wall temperature, °R

TF Maximum fuel temperature, °R
Q Channel heat flux, Btu/Sec-In (Includes average conduction heat from central element)
H Channel heat transfer film coefficient, Btu/Hr-Ft²-°R
REB Bulk Reynolds' number in channel (Average for preceding 2-inch increment)
V Gas specific volume, in³/lb

(CRD) XE-2 FUEL CHANNEL AXIAL CONDITION AT FULL POWER, 1.2 POWER FACTOR (CRD)

PREPARED BY	APPROVED BY
G.E.C. 8/7/68	JS 8/7/68

INDEX NO.

1.6.2
Sheet 1

REFERENCE

Diameter 0.0950 in.
Inlet Loss Coefficient 124.50
Power 0.03624 MW
Flow 0.002215 lb/sec

X	P	T	TS	TW	TF	Q	H	REB	V
0.000	698.200	220.80							
0.000	651.324	220.80	221.29	451.67	458.32	0.6703	1508	103226	3186.95
2.000	650.895	280.21	280.26	670.89	682.49	1.0613	1408	89457	4067.82
4.000	650.330	365.31	365.40	974.20	992.87	1.4301	1218	75574	5314.33
6.000	649.579	482.12	482.31	1346.40	1375.54	1.7764	1066	63329	7018.97
8.000	648.635	626.81	627.12	1669.48	1711.37	2.0891	1039	53312	9094.29
10.000	647.458	798.10	798.62	1854.43	1907.11	2.3461	1152	45591	11554.01
12.000	646.033	988.58	989.38	1991.04	2053.34	2.5584	1324	39458	14298.35
14.000	644.349	1192.40	1193.55	2139.03	2210.94	2.7126	1487	34518	17249.77
16.000	642.395	1406.46	1408.07	2341.48	2425.49	2.8422	1578	30308	20370.48
18.000	640.178	1626.10	1628.22	2509.98	2604.54	2.9450	1731	27362	23598.90
20.000	637.678	1851.32	1854.08	2686.03	2790.67	3.0164	1879	24882	26941.34
22.000	634.897	2078.16	2081.52	2863.16	2976.75	3.0612	2029	22850	30346.49
24.000	631.849	2300.95	2305.10	3036.15	3157.08	3.0835	2185	21233	33736.40
26.000	628.511	2524.41	2529.45	3211.73	3338.15	3.0790	2338	19826	37185.77
28.000	624.916	2738.36	2744.12	3387.57	3516.74	3.0344	2443	18676	40548.45
30.000	621.054	2946.76	2953.52	3555.24	3684.49	2.9561	2544	17692	43886.68
32.000	616.941	3145.55	3153.03	3712.02	3838.94	2.8467	2636	16847	47142.65
34.000	612.597	3330.57	3339.07	3848.64	3970.66	2.6991	2741	16147	50255.11
36.000	608.020	3504.78	3514.33	3973.32	4088.71	2.5249	2846	15546	53269.98
38.000	603.237	3663.33	3673.58	4082.10	4189.21	2.3238	2942	15037	56112.59
40.000	598.266	3805.34	3816.58	4173.27	4270.26	2.0891	3027	14609	58766.93
42.000	593.116	3932.46	3944.11	4251.81	4338.75	1.8612	3124	14254	61255.74
44.000	587.829	4038.82	4051.33	4310.02	4385.53	1.6088	3208	13969	63479.94
46.000	582.404	4129.64	4142.96	4355.69	4419.59	1.3563	3285	13735	65515.88
48.000	576.864	4204.29	4218.36	4385.59	4437.10	1.0904	3352	13549	67346.23
50.000	571.194	4269.37	4283.52	4406.92	4446.15	0.8289	3443	13392	69074.02
52.000	565.574	4291.13	4305.43	4304.01	4304.01	0.0000	3527	13341	70117.36
54.000	559.049	4290.63	4305.20	4303.75	4303.75	0.0000	3529	13342	70811.25
54.000	563.480	4304.27	4307.00						

X Channel axial distance from inlet, inches
P Channel pressure, psia
T Gas temperature, °R
TS Stagnation gas temperature, °R
TW Channel wall temperature, °R

TF Maximum fuel temperature, °R
Q Channel heat flux, Btu/Sec-In² (Includes average conduction heat from central element)
H Channel heat transfer film coefficient, Btu/Hr-Ft² - °R
REB Bulk Reynolds' number in channel (Average for preceding 2-inch increment)
V Gas specific volume, in³/lb

(CRD) XE-2 FUEL CHANNEL AXIAL CONDITIONS AT FULL POWER, 1.0 POWER FACTOR (CRD)

PREPARED BY	APPROVED BY
G. E. C. 8/7/68	AJ 8/7/68

CONFIDENTIAL RESTRICTED DATA Atomic Energy Act of 1954

1-27

INDEX NO.

1.6.2

Sheet 2

REFERENCE

Astronautics
Laboratory

Diameter 0.0950 in.
Loss Coefficient 316.04
Power 0.02899 MW
Flow 0.001772 lbs/sec

X	P	T	TS	TW	TF	Q	H	REB	V
0.000	698.200	220.80							
0.000	622.043	220.80	221.15	441.94	447.38	0.5362	1259	82819	3332.46
2.000	621.755	280.17	280.21	652.69	661.88	0.8490	1182	71678	4252.10
4.000	621.374	365.35	365.42	940.57	955.21	1.1441	1031	60470	5555.47
6.000	620.867	482.24	482.37	1294.80	1317.38	1.4211	907	50670	7335.98
8.000	620.227	627.02	627.24	1604.13	1636.32	1.6713	887	42646	9504.18
10.000	619.427	798.40	798.77	1789.04	1829.55	1.8769	982	36467	12071.31
12.000	618.459	988.99	989.55	1931.76	1979.89	2.0467	1126	31559	14931.69
14.000	617.315	1192.92	1193.73	2084.93	2140.72	2.1701	1262	27606	18002.81
16.000	615.989	1407.13	1408.25	2289.82	2355.24	2.2738	1337	24239	21243.55
18.000	614.485	1626.92	1628.39	2462.65	2536.62	2.3560	1464	21882	24587.95
20.000	612.789	1852.33	1854.24	2642.13	2724.32	2.4131	1587	19898	28041.07
22.000	610.905	2079.36	2081.68	2823.20	2912.79	2.4490	1712	18273	31546.89
24.000	608.840	2302.39	2305.25	2999.48	3095.18	2.4668	1841	16979	35023.96
26.000	606.582	2526.12	2529.59	3178.08	3278.41	2.4632	1968	15852	38547.38
28.000	604.152	2740.30	2744.25	3355.91	3458.65	2.4275	2056	14933	41963.28
30.000	601.545	2949.02	2953.63	3526.32	3629.29	2.3649	2139	14146	45336.66
32.000	598.772	3148.04	3153.12	3685.43	3786.66	2.2774	2216	13469	48604.00
34.000	595.848	3333.38	3339.14	3824.52	3921.91	2.1593	2303	12910	51704.39
36.000	592.773	3507.93	3514.37	3951.76	4043.90	2.0199	2391	12429	54683.03
38.000	589.566	3666.69	3673.57	4063.10	4148.67	1.8590	2470	12021	57460.93
40.000	586.241	3809.00	3816.50	4156.69	4234.18	1.6713	2541	11679	60025.31
42.000	582.805	3936.25	3943.99	4237.51	4306.98	1.4890	2623	11395	62395.85
44.000	579.286	4042.90	4051.16	4297.90	4358.25	1.2870	2695	11167	64478.25
46.000	575.687	4134.04	4142.78	4345.93	4397.01	1.0850	2757	10979	66349.02
48.000	572.021	4209.02	4218.20	4377.95	4419.13	0.8723	2815	10830	67991.85
50.000	568.283	4274.40	4283.40	4401.46	4432.83	0.6631	2890	10704	69509.81
52.000	564.589	4296.17	4305.38	4304.46	4304.46	0.0000	2957	10663	70323.27
54.000	560.905	4295.91	4305.23	4304.30	4304.30	0.0000	2958	10664	70779.36
54.000	563.169	4304.63	4307.00						

X Channel axial distance from inlet, inches
P Channel pressure, psia
T Gas temperature, °R
TS Stagnation gas temperature, °R
TW Channel wall temperature, °R

TF Maximum fuel temperature, °R
Q Channel heat flux, Btu/Sec-In² (Includes average conduction heat from central element)
H Channel heat transfer film coefficient, Btu/Hr-Ft² - °R
REB Bulk Reynolds' number in channel (Average for preceding 2-inch increment)
V Gas specific volume, in³/lb

(CRD) XE-2 FUEL CHANNEL AXIAL CONDITIONS AT FULL POWER, 0.8 POWER FACTOR (CRD)

PREPARED BY

G.E.C. 8/7/68

APPROVED BY

ASB 8/17/68

INDEX NO.

1.6.2

Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C. 8/2/68	OSD 8/7/68

(CRD) EFFECT OF CORE INLET TEMPERATURE ON FUEL AND TIE ROD EXIT GAS TEMPERATURE AND CORE PRESSURE DROP, 100 PERCENT POWER AND FLOW (U)

INDEX NO

1.6.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	QJ 8/7/68

(CRD) AXIAL FUEL TEMPERATURES FOR PLANNED XE-2 STEADY STATE HOLDS, AS ORIFICED (U)

INDEX NO

1.6.4
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	00 8/5/68

(CRD) GAS TEMPERATURE FOR PLANNED XE-2 STEADY STATE HOLDS, AS ORIFICED (U)

INDEX NO.

1.6.4
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C. 8/7/68	QJS 8/7/68	

DIMENSIONAL DATA

Item	Units	Value
No. Tie Rods and Unfueled Central Elements used in Core		289
Diameter of Tie Rods	inch	0.110 $\begin{smallmatrix} +.002 \\ -.001 \end{smallmatrix}$ (261)
		0.124 $\begin{smallmatrix} +.000 \\ -.003 \end{smallmatrix}$ (28)
Distance Across Flats of Unfueled Graphite	inch	0.754 $\begin{smallmatrix} +.000 \\ -.002 \end{smallmatrix}$
ID of Unfueled Graphite	inch	0.3625 $\pm$.0015 as coated
OD of Pyrographite	inch	0.357 $\pm$.002
ID of Pyrographite	inch	0.246 $\pm$.004
OD of Stainless Steel Liner	inch	0.237 $\begin{smallmatrix} +.000 \\ -.002 \end{smallmatrix}$
ID of Stainless Steel Liner	inch	0.226 $\pm$.003
Centering Bushing Orifice Size	inch	0.0325 $\pm$.0005 ⁽¹⁾
No. of Orifices Per Bushing		4
End Support Cone Hole Size	inch	0.059 $\begin{smallmatrix} +.005 \\ -.000 \end{smallmatrix}$
No. of Holes in Support Cone		12 ⁽²⁾

THERMAL DATA

Total Heat Transferred to Tie Rod Channels	MW	6.8	CR: GEC 3/1
Total Heat Transferred to Fuel Elements	MW	7.5	CR: GEC 3/1
Total Heating (289 Tie Rods and Unfueled Elements)	MW	14.3	CR: GEC 3/1

(1) Note: 28 bushings used with hollow tie rods have 0.0370 $\pm$.0005 inch holes.

(2) Note: 28 threaded support cones used with hollow tie rods have 8 holes at 0.059 $\begin{smallmatrix} +.005 \\ -.000 \end{smallmatrix}$ and 4 holes at 0.040 $\begin{smallmatrix} +.005 \\ -.000 \end{smallmatrix}$ inch.

(CRD) UNFUELED ELEMENT AND TIE ROD CHANNEL DATA (U)	INDEX NO.
	1.7.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C. 8/2/68	DSS 8/5/68

Hardware Description	Node Designation*	Node Location
(1) Tie Rod	CL	Tie Rod Centerline
Tie Rod	W	Tie Rod Wall
(2) Flow Channel	T	Hydrogen Bulk Temperature
(3) Stainless Steel Liner	SS	Stainless Steel Liner
(4) Hydrogen Gap	None	
(5) Pyrographite Insulating Sleeve	PYRO 1	Surface of Sleeve I. D.
"	PYRO 2	Sleeve Midpoint
"	PYRO 3	Surface of Sleeve O. D.
(6) Hydrogen Gap	None	
(7) Unfueled Element	Graph 1	Surface of Element I. D.
"	Graph 2	Surface of Element O. D.

*See I. 7. 3

(CRD) UNFUELED CENTRAL ELEMENT AND TIE ROD MODEL DESCRIPTION (U)	INDEX NO.
	I. 7. 2

REFERENCE

Astronuclear
Laboratory

Flow 0.01591 lb/sec
Inlet Loss Coefficient 83.0
Tie Rod Diameter 0.110 inch

In. X	Psia P	Gas	Temperature - °R								Radial Heat Flux Btu/Sec - In		
			Tie Rod		SS	Pyro 1	Pyro 2	Pyro 3	Grap 1	Grap 2	SS	Tie	Fuel
			Center	Wall									
0.0	698.2	220.8											
0.0	597.0	220.8	249.4	237.1	244.2	647.7	864.3	1004.8	1023.1	1013.1	0.1288	0.0893	-0.1439
3.0	596.3	227.8	268.0	250.8	260.6	774.3	1149.3	1402.9	1423.9	1407.9	0.1782	0.1248	-0.1850
6.0	595.5	236.6	288.8	266.5	277.8	879.7	1427.0	1755.8	1776.6	1750.4	0.2231	0.1616	-0.2404
9.0	594.7	247.2	310.3	283.3	294.0	950.2	1614.0	1956.6	1975.7	1937.8	0.2543	0.1958	-0.2996
12.0	593.8	259.5	331.6	300.6	312.7	1027.6	1822.4	2184.4	2204.0	2154.6	0.2910	0.2247	-0.3439
15.0	592.9	273.4	352.0	318.1	334.3	1112.8	2044.9	2436.6	2458.9	2399.2	0.3346	0.2457	-0.3721
18.0	591.9	289.4	372.3	336.4	361.9	1230.2	2329.3	2777.0	2805.5	2739.8	0.4002	0.2596	-0.3777
21.0	590.7	307.6	392.8	356.0	391.1	1332.1	2548.6	3046.5	3080.2	3014.1	0.4603	0.2667	-0.3752
24.0	589.5	328.1	414.3	377.5	427.0	1447.2	2782.6	3346.6	3386.8	3329.2	0.5345	0.2667	-0.3530
27.0	588.2	350.9	435.3	399.5	464.0	1545.1	2973.3	3598.0	3643.6	3600.9	0.6018	0.2588	-0.3188
30.0	586.8	375.5	456.8	422.6	502.1	1632.1	3136.5	3814.9	3865.2	3840.5	0.6636	0.2470	-0.2786
33.0	585.2	402.2	478.1	446.3	540.3	1709.7	3279.1	4005.3	4059.5	4056.2	0.7200	0.2300	-0.2295
36.0	583.5	432.2	500.4	471.8	575.7	1763.7	3367.2	4154.0	4181.1	4198.0	0.7522	0.2076	-0.1780
39.0	581.7	462.5	521.2	496.4	607.5	1800.5	3417.5	4106.2	4255.2	4293.0	0.7667	0.1792	-0.1204
42.0	579.8	492.9	541.7	521.0	639.5	1837.1	3467.8	4267.9	4328.6	4388.6	0.7812	0.1499	-0.0600
45.0	577.8	522.9	560.6	544.5	668.1	1853.3	3485.0	4301.3	4363.6	4445.4	0.7806	0.1162	0.0041
48.0	575.6	552.0	579.0	567.4	691.4	1840.4	3452.5	4275.4	4339.0	4436.8	0.7582	0.0841	0.0588
51.0	573.4	579.2	596.0	588.7	707.8	1791.1	3358.2	4175.0	4239.8	4347.0	0.7095	0.0526	0.1039
54.0	571.1	604.1	610.8	607.9	722.7	1741.7	3263.6	4073.7	4138.9	4255.4	0.6621	0.0210	0.1494
54.0	563.3	604.1											

NOTE: See I.7.2 for definition of model

X Axial station from core inlet, inches

P Pressure, Psia

INDEX NO.

I.7.3

(CRD) XE-2 AVERAGE TIE ROD CHANNEL AND FUELED ELEMENT AXIAL CONDITIONS (U)

PREPARED BY

G.E.C.

8/7/68

APPROVED BY

QD

8/7/68

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.G. 8/2/68	G.S. 8/5/68

(CRD) XE-2 TIE ROD EXIT GAS TEMPERATURE VERSUS TIE ROD POWER FACTOR AND CORE RADIUS (U)

INDEX NO

1.7.4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	AS 8/5/68	

THIS PAGE UNCLASSIFIED

NOTE: The transient data presented in Section I were calculated using startup and shutdown profiles that are presented in the following pages. They are the 50, 100, and 150°R/Sec startups and the 100°R/Sec, flow, and scram shutdowns.

(U) 50°R/SEC STARTUP: POWER AND FLOW RATE (U)	INDEX NO
	1.8 Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C 8/2/68	AS 8/5/68

(U) 100°R/SEC STARTUP- POWER AND FLOW RATE (U)	INDEX NO
	1 8
	Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	OB 8/5/68

(U) 150°R/SEC STARTUP: POWER AND FLOW RATE (U)

INDEX NO.

1.8
 Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/66	QD 8/5/66

(U) 100°R/SEC SHUTDOWN: POWER AND FLOW RATE (U)	INDEX NO.
	1.8 Sheet 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	GEC 8/2/68	GB 8/5/68

(U) FLOW SHUTDOWN- POWER AND FLOW RATE (U)	INDEX NO
	1.8 Sheet 5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	QSD 8/5/68	

THIS PAGE UNCLASSIFIED

(U) SCRAM SHUTDOWN: POWER AND FLOW RATE (U)

INDEX NO

I. 8
Sheet 6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C. 8/2/68	AB 8/5/68

(CRD) AXIAL VARIATION OF FUEL ELEMENT AVERAGE TEMPERATURE FOR AVERAGE CLUSTER DURING 150°R/SEC STARTUP (U)

INDEX NO.

I. 8. 1
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	QD 8/5/68

(CRD) AXIAL VARIATION OF UNFUELED CENTRAL ELEMENT AVERAGE TEMPERATURE
FOR AVERAGE CLUSTER DURING 150°R/SEC STARTUP (U)

INDEX NO.

1.8.1
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	GEC 8/2/68	GS 8/5/68

(CRD) AXIAL VARIATION OF TEMPERATURE DIFFERENCE BETWEEN FUELED AND UNFUELED ELEMENTS FOR AVERAGE CLUSTER DURING 150°R/SEC STARTUP (U)

INDEX NO

1.8.1
Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	AS 8/5/68

(CRD) AXIAL VARIATION OF FUEL ELEMENT AVERAGE TEMPERATURE FOR A PERIPHERAL CLUSTER DURING 150°R/SEC STARTUP (U)

INDEX NO

I. 8. 2
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C. 8/2/68	ASD 8/5/68

(CRD) AXIAL VARIATION OF UNFUELED PARTIAL ELEMENT AVERAGE
 TEMPERATURE FOR PERIPHERAL CLUSTER DURING 150°R/SEC STARTUP (CRD)

INDEX NO.

I. 8. 2
 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C. 8/2/68	GO 8/5/68

(CRD) AXIAL VARIATION OF UNFUELED CENTRAL ELEMENT AVERAGE
TEMPERATURE FOR PERIPHERAL CLUSTER DURING 150°R/SEC STARTUP (U)

INDEX NO

I. 8. 2
Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	OS 8/5/68

(CRD) AXIAL VARIATION OF TEMPERATURE DIFFERENCE BETWEEN PARTIAL UNFUELED ELEMENT AND ADJACENT FUEL ELEMENT FOR PERIPHERAL CLUSTER DURING 150°R/SEC STARTUP (CRD)

INDEX NO.

I. 8. 2
Sheet 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	BSO 8/5/68

(CRD) J8 FUEL CLUSTER COOLANT EXIT TEMPERATURES DURING 150°R/SEC STARTUP (U)

INDEX NO.

I. 8. 2

Sheet 5

8/5/68

1. 9. 1. 1

REFERENCE

(CRD) RADIAL TEMPERATURE DIFFERENCES FOR A REGULAR SUPPORT BLOCK AT AVERAGE CONDITIONS WITH 50, 100 AND 150°R/SEC STARTUP RAMPS (U)

PREPARED BY

G.E.C. 8/2/68

APPROVED BY

OSB 8/5/68

INDEX NO.

1.9.1.2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C. 8/2/68	QSD 8/5/68

(CRD) RADIAL TEMPERATURE PROFILES OF A REGULAR AVERAGE SUPPORT BLOCK WITH 50°F/SEC STARTUP RAMP (U)

INDEX NO.

I. 9. 1. 3

Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	ab 8/5/68

Refer to C. 1. 1. 8 for Part Identification

(CRD) TEMPERATURES IN TIE ROD END AND SUPPORT BLOCK ASSEMBLY 75 SECONDS AFTER BEGINNING OF 50°R/SEC STARTUP WITH FLOW LAG (U)	INDEX NO.
	1. 9. 1. 3 Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. C. 8/2/68	ap 8/5/68

(CRD) RADIAL TEMPERATURE PROFILES OF A REGULAR AVERAGE SUPPORT
BLOCK WITH 100°R/SEC STARTUP RAMP (U)

INDEX NO.

I. 9. 1. 4

Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	OS 8/5/68

Refer to C. 1. 1. 8 for Part Identification

(CRD) TEMPERATURES IN TIE ROD END AND SUPPORT BLOCK ASSEMBLY
40 SECONDS AFTER BEGINNING OF 100°R/SEC STARTUP (U)

INDEX NO.

1.9.1.4
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/2/68	GB 8/5/68

(CRD) RADIAL TEMPERATURE PROFILES OF A REGULAR AVERAGE SUPPORT BLOCK WITH 150°R/SEC STARTUP RAMP (U)

INDEX NO.

1.9.1.5

Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. CORT 8/5/68	OS 8/5/68

(CRD) SUMMARY OF RADIAL TEMPERATURE DIFFERENCES IN REGULAR SUPPORT BLOCK DURING 100 AND 300 °R/SEC SHUTDOWNS (U)

INDEX NO

1.9.1.6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. COIT 8/5/68	ASD 8/5/68

(CRD) RADIAL TEMPERATURE PROFILES OF AN AVERAGE REGULAR SUPPORT BLOCK DURING $100^{\circ}\text{R}/\text{SEC}$ SHUTDOWN (U)

INDEX NO

1.9.1.7
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/5/68	GD 8/5/68

Refer to C. 1.1.8 for Part Identification

(CRD) TEMPERATURES IN THE TIE ROD END AND SUPPORT BLOCK ASSEMBLY FOR AN AVERAGE REGULAR SUPPORT BLOCK 20 SECONDS AFTER BEGINNING OF 100°R/SEC SHUTDOWN (U)	INDEX NO.
	1.9.1.7
	Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. CORT 8/5/68	DSB 8/5/68

(CRD) RADIAL TEMPERATURE PROFILES OF AN AVERAGE REGULAR SUPPORT BLOCK FOLLOWING SCRAM WITH A FAST SHUTDOWN (300°R/SEC) (U)

INDEX NO

1.9.1.8
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.E.C. 8/5/68	Q.B. 8/5/68

Refer to C. 1. 1. 8 for Part Identification

(CRD) TEMPERATURES IN TIE ROD END AND SUPPORT BLOCK ASSEMBLY FOR AN AVERAGE REGULAR SUPPORT BLOCK 10 SECONDS AFTER SCRAM WITH A FAST SHUTDOWN (300°R/SEC) (U)

INDEX NO.

1.9.1.8
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. CORT 8/5/68	GP 8/5/68

(CRD) RADIAL TEMPERATURE PROFILES OF PERIPHERAL PARTIAL SUPPORT BLOCK (J8) WITH 150°R/SEC STARTUP (U)

INDEX NO
1.9.2.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. CoRT 8/5/68	as 8/5/68

(CRD) RADIAL TEMPERATURE DIFFERENCES OF PERIPHERAL PARTIAL SUPPORT BLOCK (J8) WITH 150°R/SEC STARTUP (U)

INDEX NO

1.9.2.2

REFERENCE AYL-01027	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. COR7 8/5/68	OS 8/5/68

(CRD) XE-2 J8 TYPE SUPPORT BLOCK TEMPERATURE DIFFERENCE DURING EMERGENCY SCRAM FROM FULL POWER (U)

INDEX NO.

1.9.2.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. COET 8/5/68	QSD 8/5/68

(CRD) TEMPERATURE DISTRIBUTION IN SUPPORT BLOCK WITH HOLLOW TIE ROD AND EXIT GAS THERMOCOUPLE AT 100 PERCENT POWER AND FLOW (CRD)

INDEX NO

1.9.3.1

REFERENCE

(CRD) TEMPERATURE DISTRIBUTION OF EXIT GAS THERMOCOUPLE ASSEMBLY AT 100 PERCENT POWER AND FLOW (U)

PREPARED BY

G. CORT 8/5/68

APPROVED BY

ASB 8/5/68

INDEX NO.

1.9.3.2

REFERENCE

(CRD) XE-2 EXIT GAS TEMPERATURE VERSUS CORE RADIUS AND LOCATION OF EXIT GAS THERMOCOUPLES

PREPARED BY

G. CART 2/5/68

APPROVED BY

ASB 8/5/68

INDEX NO

1.9.3.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G.F.C. 8/2/68	G.D. 8/5/68	

$$P_{\text{NORMALIZED}} = (P_i - P_{\text{EXIT}}) / (P_{\text{INLET}} - P_{\text{EXIT}})$$

$P_{\text{inlet}} = 698 \text{ psia}$

CORE RADIUS (INCHES)

(CRD) XE-2 NORMALIZED INTERELEMENT PRESSURE DISTRIBUTION FOR FULL POWER AND FLOW CONDITIONS (U)

INDEX NO.

I. 10. 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	G. E. G. 8/2/68	AS 8/5/68

(CRD) XE-2 INTERELEMENT NORMALIZED AXIAL PRESSURE DISTRIBUTION FOR DESIGN AND PART POWER CONDITIONS (U)	INDEX NO.
	1.10.2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	MWH 7/31/68	QD 8/7/68

(CRD) XE-2 INTERELEMENT PRESSURE PROBE PREDICTIONS AS A FUNCTION OF CHAMBER TEMPERATURE (U)	INDEX NO
	1.10.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S. L. D. 8/12/68	JHB 8/12/68	

THIS PAGE UNCLASSIFIED

SECTION J

(U) This section of the XE-2 Data Book is a compilation of data pertinent to the corrosion performance of the XE-2 fuel elements, the filler strips and the support blocks. The NRX-A6 reactor test results and electric furnace single element corrosion test results were used to empirically determine the fuel element midband and hot end corrosion weight losses and to adjust these for cyclic operation. Corrosion calculations are also given for fuel element external surface corrosion and filler strip corrosion.

(U) Specific data may be located by reference to the Table of Contents which follow.

(U) CORROSION DATA (U)	INDEX NO.
	J

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S. L. D. 8-12-68	JHB 8/12/68	

SECTION J

XE-2
(CRD) CORE CORROSION (U)

TABLE OF CONTENTS

<u>Index No.</u>		
J.1	(CRD)	XE-2 Nuclear Subsystem Endurance Limit (U)
J.2	(CRD)	Fuel Elements (U)
J.2.1	(CRD)	Comparison of NbC Bore Coating Thickness Profiles for XE-2 and NRX-A6 Fuel Elements (U)
J.2.2	(CRD)	Fuel Element Bore Coating Data (U)
J.2.3	(CRD)	Estimate of Molybdenum Loss During NRX-A6 Run Time (CRD)
J.3	(CRD)	Fuel Element Electrical Furnace Acceptance (Q.C.) Test Results (U)
J.3.1	(CRD)	Measured Average Electrical Test Parameters (U)
J.3.2	(CRD)	Calculated Axial Temperature Distribution of XE-2 Acceptance (Q.C.) Test Results (U)
J.3.3	(CRD)	XE-2 Acceptance (Q.C.) Test Results (U)
J.3.4	(CRD)	XE-2 Acceptance (Q.C.) Test Incremental Weight Losses (U)
J.3.5	(CRD)	Comparison of XE-2 and NRX-A6 Acceptance (Q.C.) Test Incremental Weight Losses for WNCO Fuel Elements (U)
J.3.6	(CRD)	Comparison of XE-2 and NRX-A6 Acceptance (Q.C.) Test Incremental Weight Losses for Y-12 Fuel Elements (U)
J.3.7	(CRD)	Fuel Element Pinhole Performance Results (U)
*J.4		Fuel Element Bore Corrosion Analysis (U)
J.4.1	(CRD)	Method of Analysis for Calculating Fuel Element Bore Corrosion (3 sheets) (U)
J.4.2	(CRD)	Corrosion Factors Used in Fuel Element Bore Corrosion Calculation (U)
J.4.3	(CRD)	Development of Corrosion Factors for Hot End Bore Corrosion Equation (U)
J.4.4	(CRD)	Development of Corrosion Factors for Midband Bore Corrosion Equation (U)
J.5	(CRD)	Fuel Element Cyclic Performance (U)
J.5.1	(CRD)	Incremental Weight Losses for NRX-A6 Characterization Test (U)
J.5.2	(CRD)	Calculational Multiplier to Account for Cyclic Bore Corrosion Effects (U)
*J.6		Fuel Element Corrosion Calculations (U)
J.6.1	(CRD)	Fuel Element Bore Corrosion Calculation (U)
J.6.2	(CRD)	Preliminary Test Profile Requirements, XE-2 (U)
J.6.3	(CRD)	Fuel Element Average Weight Loss and Reactivity Loss Vs. Operating Time (U)
J.6.4	(CRD)	Calculated XE-2 Drum Position (U)
J.6.5	(CRD)	Calculated Incremental Weight Losses (U)
J.6.6	(CRD)	Fuel Element Surface Corrosion Calculation (U)
J.6.7	(CRD)	Axial Distribution of Fuel Element External Surface Corrosion (U)

* There are no data sheets for this index no.

(CRD) TABLE OF CONTENTS (U)	INDEX NO.
	J

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S. L. D 8-12-68	J. H. B 5/12/68	

THIS PAGE UNCLASSIFIED

SECTION J

XE-2
CORE CORROSION

TABLE OF CONTENTS

Index No.

*J.7	Filler Strip Corrosion (U)
J.7.1	(CRD) Axial Distribution of Filler Strip Radial Surface Corrosion (U)
J.8	(CRD) Support Block Corrosion (U)

* There are no data sheets for this index no.

(U) TABLE OF CONTENTS (U)	INDEX NO
	J

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S.L.D. 8-12-68	JHB 8/12/68	

(U) The XE-2 nuclear subsystem endurance limit involves the following considerations:

1. Necessity to obtain maximum information from the XE-2 test series.
2. Necessity of not violating any nuclear subsystem limits.
3. Necessity of not exceeding support block limits.
4. Necessity of maintaining fission product release to minimum values.

(CRD) Experience on the NRX/EST, NRX-A5, and NRX-A6 reactivity loss, and fission product release is as follows:

Reactor	Reactivity Loss (Hot - %)	Fission Product Release (Curies)
NRX/EST	2.7	$8.2 \times 10^{7(1)}$
NRX-A5	2.0	$4.0 \times 10^{7(2)}$
NRX-A6	0.64	$0.4 \times 10^{7(3)}$

The associated drum positions are as follows:

Reactor	Initial Cold Critical Drum Position	Start-of-Life Hot Drum Position	End-of-Life Hot Drum Position
NRX/EST	99°	109°	162°
NRX-A5	99°	109°	146°
NRX-A6	93°	104°	115°

(CRD) It is recommended that the limit on XE-2 subsystem performance be a reactivity loss of 2%. A conservatively safe operating time limit of 40 minutes at full power has been recommended.⁽⁴⁾ This limit is based on expected cracking and subsequent corrosion of the support blocks (See J.8), as well as the effects of the cold filler strip periphery design on peripheral fuel element surface corrosion (See J.6.6 and J.6.7). Corrosion calculations for the planned XE-2 run profile (Figure J.6.2) indicate the 2.0% reactivity loss limit is achieved during the 5th high power cycle (total operating time at 3400°R chamber temperature 20 mins., total operating time at 4090°R ~ 40 minutes.

⁽¹⁾WANL-TME-1476, "Effluent Studies on NRX/EST"

⁽²⁾WANL-TME-1540, "Measurement of Fission Product Loss During NRX-A5"

⁽³⁾WANL-TME-1810, "Radiochemical Measurements on NRX-A6"

⁽⁴⁾XE-2 Reactor Design, Definition, letter dated December 19, 1966, to Mr. J. L. Dooling from Mr. H. Faught

(CRD) XE-2 NUCLEAR SUBSYSTEM ENDURANCE LIMIT (U)

INDEX NO.

J.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S.L.D. 8-12-68	J.H.B. 8/12/68	

(CRD) The XE-2 core consists of 1584 fuel elements with the following inventory:

<u>Matrix Source</u>	<u>NbC Coating Source</u>	<u>Molybdenum Coating Source</u>	<u>Number of Elements</u>
Y-12	Y-12	Y-12	892
Y-12	Y-12	WNCO	29
WNCO	WNCO	Y-12	10
WNCO	WNCO	WNCO	653
CORE TOTAL			1584

(CRD) The total number of unfueled central elements is 289. "The XE-2 Element Placement and Orificing Summary Report", WANL-TME-1799, gives the location of the fuel and unfueled central elements.

(CRD) There are 210 WNCO externally coated fuel elements. These are located in the two outermost rows of the core periphery.

(CRD) The makeup of the XE-2 core was generally random with no specific consideration given to element manufacturer type or to physical properties with regard to the fuel matrix. However, NbC coating thickness afforded a convenient and rapid method of separating fuel elements into two grades. The station 20 coating thickness, 1.3 mils, was used to separate the XE-2 candidate elements into two groups. The fuel elements (Code 99 only) were graded and located as follows:

Grade A Thickness: < 1.3 mils

Grade B Thickness: $\geq$ 1.3 mils

Cluster rows O-D, in the center of core, contained only Grade A fuel elements, and Cluster rows E-J in the trough and periphery, contained both Grade A and Grade B fuel elements. This resulted in approximately 50% of the elements located in cluster rows O-D being Grade A WNCO, and 50% Grade A Y-12.

(CRD) Figure J.2.1 presents the XE-2 NbC bore coating thickness profiles with a comparison to the NRX-A6 profiles. Estimates of molybdenum weight remaining in the NRX-A6 fuel element during the reactor test have been made based on reactivity data and post-test chemistry. These data for a limited number of samples are given on Figure J.2.2. Figure J.2.3 is a summary of the pertinent bore coat and bore overcoat pre-test measured data.

(CRD) FUEL ELEMENTS (U)	INDEX NO.
	J.2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S.L.D. 8-12-68	JHB 8/12/68

(CRD) COMPARISON OF NbC BORE COATING THICKNESS PROFILES FOR XE-2 AND NRX-A6 FUEL ELEMENTS (U)

INDEX NO.

J.2.1

~~CONFIDENTIAL RESTRICTED DATA~~ Atomic Energy Act of 1954

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S.L.D. 8-12-68	JNB 8/14/68	

	XE-2		NRX-A6	
	WNCO	Y-12	WNCO	Y-12
Average NbC Coating Thickness - Mils*	1.28	1.40	1.33	1.38
Average Molybdenum Weight per Element After Ambient Blowdown - gms	3.43	2.81	3.64	3.08
Average Bore NbC Weight per Element - gms	51.36	53.38	50.60	51.33

* Measured by beta backscatter technique.

(CRD) FUEL ELEMENT BORE COATING DATA (U)	INDEX NO.
	J. 2. 2

~~CONFIDENTIAL RESTRICTED DATA~~ Atomic Energy Act of 1954

REFERENCE

((CRD) ESTIMATE OF MOLYBDENUM WEIGHT REMAINING IN NRX-A6 FUEL ELEMENT DURING TEST ((CRD)

PREPARED BY

S.L.D. 8-12-68

APPROVED BY

JHB 8/12/68

INDEX NO.

J.2.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S L D 8-12-68	JNB 8/12/68	

(CRD) This section of corrosion data presents the XE-2 acceptance (Q.C.) test conditions and corrosion weight losses. Since the XE-2 elements are similar to the NRX-A6 elements, for comparison, the NRX-A6 values are included.

The XE-2 specifications for the electrical test are as follows:

Power - kw	900 $\pm$ 25
Flow - scfm	592 $\pm$ 15
Temperature at station 37.6 - $^{\circ}$ R	4100 $\pm$ 100
Excess of average element bore pressure at station 20 over external helium pressure, psid	30 $\pm$ 5
No. of equal duration cycles	2
Total test time - minutes	60

(CRD) Requirements to Pass XE-2 Acceptance (Q.C.) Test

1. The upper limit of matrix weight loss less than 15 gm.
2. Pinholes in the first 48 inches not in excess of 5.
3. Bearing area remaining (bar) at least 75 percent.
4. The air impedance differences between the original bore values in the NbC coated condition and those measured after the first 30 minutes of the required test sequence should conform to the following:

- a. This difference shall be in the range of 0-2 mils.
- b. This difference for each channel shall be within the range $\pm$ 1 mil of the

measured average change for all measured channels in the element.

(U) XE-2 fuel element electrical furnace test results are summarized in the following figures:

Figure J.3.1 - Compares the measured average electrical test parameters in both the XE-2 acceptance (Q.C.) test and the NRX-A6 acceptance (Q.C.) test.

Figure J.3.2 - Presents the calculated temperature distribution of the fuel element channel walls in the XE-2 acceptance (Q.C.) test.

Figures J.3.3, Present the midband and hot end XE-2 acceptance (Q.C.) test results.
J.3.4, J.3.5,
J.3.6

(CRD) It was observed from axial split examinations that the XE-2 acceptance (Q.C.) tested fuel element illustrated characteristic midband ring type corrosion in the midband region of the number 10 hole. For WNCO fuel the rings were observed from core stations 20-35; for Y-12 fuel the rings were observed from core stations 32-38. Ring corrosion was not observed in the number 10 hole of the NRX-A6 fuel. This phenomenon is not expected to influence XE-2 operation.

(CRD) FUEL ELEMENT ELECTRICAL FURNACE ACCEPTANCE (Q.C.) TEST RESULTS (U)	INDEX NO.
	J.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S. L. D. 8-12-68	J. H. B. 8/12/68	

Type of Element	XE-2 Acceptance (Q. C.) Test				Power Kw	Flow H ₂ SCFM	Δp -psid
	15.1	26.3	37.6	48.6			
WNCO	2551	3397	4143	4743	884	603	119
Y-12	2650	3443	4207	4721	883	604	119

Type of Element	NRX-A6 Acceptance (Q. C.) Test				Power Kw	Flow H ₂ SCFM	Δp -psid
	15.1	26.3	37.6	48.6			
WNCO	2619	3477	4221	4716	880	604	123
Y-12	2693	3511	4244	4755	881	605	122

(CRD) MEASURED AVERAGE ELECTRICAL TEST PARAMETERS (U)	INDEX NO.
	J. 3. 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	SLD 8-12-68	JHB 8/12/68

(CRD) CALCULATED TEMPERATURE OF ACCEPTANCE (QC) TEST (U)	INDEX NO
	J.3.2

REFERENCE

XE-2 Acceptance (Q. C.) Test Results*

Matrix Source	WNCO (OD Coat)	WNCO (Non-OD Coat)	Y-12 (Non-OD Coat)
Coating and Overcoat Source	WNCO	WNCO	Y-12
Test Time - Minutes	60 (30 + 30)	60 (30 + 30)	60 (30 + 30)
Average Midband Weight Loss (gms)	0.88 (1.39)**	1.37 (1.63)	2.60 (1.70)
Average Hot End Weight Loss (gms)	9.49 (1.60)	8.90 (1.17)	7.74 (1.66)
Average Total Weight Loss (gms)	10.28	10.27	10.34
No. of Elements in Sample	29	21	78

NRX-A6 Acceptance (Q. C.) Test Results*

Matrix Source	WNCO (OD Coat)	WNCO (Non-O. D. Coat)	Y-12 (Non - OD Coat)
Coating and Overcoat Source	WNCO	WNCO	Y-12
Test Time - Minutes	60 (30 + 30)	60 (30 + 30)	60 (30 + 30)
Average Midband Weight Loss (gms)	1.2 (1.1)**	2.2 (1.6)	3.6 (1.8)
Average Hot End Weight Loss (gms)	10.8 (1.5)	9.2 (1.6)	9.1 (1.7)
Average Total Weight Loss (gms)	12.0	11.4	12.7
Number of Elements in Sample	20	46	78

* These results are for elements which passed the Q. C. test (NRX-A6 and XE-2 Q. C. tests specifications are identical).
** 1 σ standard deviation.

(CRD) XE-2 ACCEPTANCE (Q. C.) TEST RESULTS (U)

PREPARED BY

S. L. D. 8-12-68

APPROVED BY

JHP 8/12/68

INDEX NO.

J.3.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S L D 8-12-68	J H B 8/12/68

(CRD) XE-2 ACCEPTANCE (Q.C.) TEST INCREMENTAL WEIGHT LOSSES (U)	INDEX NO
	J. 3. 4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S.L.D. 8-12-68	J.H.B. 8/12/68

(CRD) COMPARISON OF XE-2 AND NRX-A6 ACCEPTANCE (Q.C.) TESTS INCREMENTAL WEIGHT LOSSES FOR WNCO FUEL ELEMENTS (U)

INDEX NO.

J.3.5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S L D. 8-12-68	JHB 8/14/69

(CRD) COMPARISON OF XE-2 AND NRX-A6 ACCEPTANCE (Q. C.) TESTS INCREMENTAL WEIGHT LOSSES FOR Y-12 FUEL ELEMENTS (U)	INDEX NO.
	J. 3. 6

REFERENCE

XE-2 Acceptance (Q. C.) Test Results *

Type of Element	No. of Cycles	Average Pinholes per Element	Average Pinholes per Element		No. of Elements
			0-35 in.	35-52 in.	
OD Coated WNCO	2	0.86	0.0	0.86	29
Non-OD Coated WNCO	2	0.31	0.1	0.31	29
Y-12	2	1.32	0.04	1.28	80

NRX-A6 Reactor

WNCO	1	1.79	0.245	1.545	278
Y-12	1	8.07	0.215	7.851	415

NRX-A6 Acceptance (Q. C.) Test Results *

WNCO	2	1.1	0.200	0.900	46
Y-12	2	1.40	0.100	1.30	63

NRX-A6 Characterization Test Results

			0-45 in.	48-52 in.	
WNCO	1	0.5	0.0	0.5	16
Y-12	1	0.5	0.0	0.5	16
WNCO	2	1.688	0.875	0.813	16
Y-12	2	0.125	0.0	0.125	16

* The results are for elements which passed the Q.C. test.

(CRD) FUEL ELEMENT PINHOLE PERFORMANCE RESULTS (U)

PREPARED BY

S. L. D. 8-12-68

APPROVED BY

JNB 8/12/68

INDEX NO.

J.3.7

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S.L.D. 8-12-68	J H B 8/12/68	

J.4(CRD) Fuel Element Bore Corrosion Analysis (U)

(U) Fuel element bore corrosion analyses were performed using a modified version of the LOWERE computer code previously described in WANL-TME-1344.

(CRD) The two major modes considered in calculating carbon weight loss in the fuel element bore are midband corrosion and hot end corrosion. The midband region is defined as the portion of fuel element where corrosion occurs because of thermal expansion cracks in the NbC, that is, the portion between 2000°R and the coating deposition temperature. The NbC cracks remain open at temperatures below the coating deposition temperatures and tend to close at temperatures above the coating deposition temperature. A molybdenum overcoat has been placed over the NbC to reduce the midband corrosion by partially covering the thermal expansion cracks in the NbC.

(CRD) Hot end corrosion weight loss calculations account for carbon diffusion through the bore coat. The hot end region is defined as that portion of the fuel element with bore temperatures above 3600°R.

(U) Empirical adjustments were made both to the midband and hot end relationships based on the NRX-A6 reactor test and electric tests.

(CRD) Hot End Bore Corrosion Analysis (U)

(CRD) The hot end bore corrosion was calculated with the expression describing diffusion of carbon through the NbC coating. The expression for hot end bore corrosion is:

$$\Delta W(Z) = DEK_2 \frac{1}{f(Z)} + \exp \left[\frac{-\beta}{T(Z)} \right]$$

where,

$\Delta W(Z)$	=	weight loss at time t (gms/in-element)
D	=	hot channel corrosion factor, ratio of hot end weight loss of fuel elements with a normal distribution of exit gas temperature to the hot end weight loss with nominal exit gas temperature.
E	=	Factor to account for hot end cyclic behavior (see Figure J.5.2)
$f(Z)$	=	NbC coating thickness - in (Values of NbC coating thickness are given in Figure J.2.1)
t	=	time - min
β	=	constant in carbon diffusivity term - °R
T(Z)	=	Bore surface temperature at axial position Z = °R (See Section I.6.2 for initial values used)
K_2	=	Factor for adjusting to observed NRX-A6 test results

(CRD) METHOD OF ANALYSIS FOR CALCULATING FUEL ELEMENT BORE CORROSION(U)

INDEX NO.

J.4.1
Sheet 1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S. L. D. 8-12-68	JH B 8/12/68	

(CRD) The assumptions in development and application of the hot end equation are:

1. Hot end corrosion occurs only for $T(Z) \geq 3600^{\circ}\text{R}$.
2. Only carbon weight loss from the fuel element bores is considered.
3. When $T(Z)$ is a function of time, the finite difference form of the equation can be applied.

(U) Corrosion factors used in the hot end corrosion equation for the XE-2 calculations are given in Figure J.4.2 and developed in Figure J.4.3.

(CRD) Midband Bore Corrosion Analysis (U)

(CRD) The midband bore corrosion was calculated with a semi-empirical expression describing carbon corrosion at thermal expansion cracks in the NbC coating. Empirical adjustments were based on the NRX-A6 reactor test results and electric test results. The bore midband expression formerly included in WANL-TME-1642 had an exponential time dependence of weight loss. The exponential characteristic of midband weight loss could not be confirmed from the NRX-A6 test results for one cycle operation of NRX-A6/XE-2 quality fuel and therefore, was replaced with a linear time dependence. However, the cyclic factors displayed on Figure J-5-2 incorporate an exponential effect and were included in the calculation.

(CRD) Likewise, the bore midband expression included the effect of hydrogen mass velocity on bore midband performance. The NRX-A6 characterization tests and the NRX-A6 test results showed no mass velocity effect on the midband corrosion weight loss for the type of fuel in XE-2. Therefore, the mass velocity effect was removed from the calculation.

(CRD) The expression applicable to the XE-2 midband is:

$$\Delta W(Z) = A K_1 \Delta \alpha (T_o - T(Z)) \exp(-E/RT(Z)) t$$

where,

$\Delta W(Z)$	=	weight loss at time t (gms/in.-element)
t	=	operating time (min)
$T(Z)$	=	bore surface temperature at axial position Z ($^{\circ}\text{R}$) (See Section I.6.2 for initial values used)
T_o	=	coating deposition temperature, 3480°R
$\Delta \alpha$	=	difference between NbC and fuel coefficients of thermal expansion (in/in $^{\circ}\text{R}$)
E	=	activation energy for hydrogen-carbon reaction, 30,000 cal/gm-mole
R	=	gas constant, 1.1038 cal/lb-mole- $^{\circ}\text{R}$
K_1	=	constant, evaluated from NRX-A6 reactor leads to the observed NRX-A6 weight losses (gm/in-element)
A	=	factor to account for midband cyclic behavior (see figure J.5.2)

(CRD) METHOD OF ANALYSIS FOR CALCULATING FUEL ELEMENT BORE CORROSION (U)

INDEX NO.

J.4.1
Sheet 2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S L D 8-12-68	J H B 5/12/68	

(CRD) Assumptions in development and application of the midband equation are:

1. Midband corrosion occurs only for $T \geq 2000^{\circ}\text{R}$
2. Only carbon weight loss from the fuel element bores is considered.
3. When $T(Z)$ is a function of time the finite difference form of the equation can be applied.

(U) Corrosion factors used in the midband corrosion equation for the XE-2 calculations are given in Figure J.4.2.

(U) The method of development of the midband factors is outlined in Figure J.4.3.

(CRD) METHOD OF ANALYSIS FOR CALCULATING FUEL ELEMENT BORE CORROSION (U)	INDEX NO.
	J.4.1 Sheet 3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S. L. D. 8-12-68	JHB 8/12/68	

(CRD) There are six radial regions used in the analysis

Radial Region	1	2	3	4	5	6
Radii (in)	0 - 5.25	5.25 - 10.45	10.45 - 13.65	13.65 - 15.15	15.15 - 16.15	16.15 - 17.3
Number of Elements in Each Region	152	447	423	234	166	162

(CRD) The following corrosion factors were assumed the same for all radial regions.

Hot End Bore Corrosion Factors

D	Hot channel corrosion factor	1.0875														
E	Cyclic factor (see Figure J.5.2)*	<table><tr><td>Cycle</td><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td></tr><tr><td>Factor</td><td>1</td><td>1.3</td><td>2.05</td><td>3.25</td><td>5.4</td><td>8.6</td></tr></table>	Cycle	1	2	3	4	5	6	Factor	1	1.3	2.05	3.25	5.4	8.6
Cycle	1	2	3	4	5	6										
Factor	1	1.3	2.05	3.25	5.4	8.6										
K ₂	Factor for adjusting to observed NRX-A6 test results	$633 \exp \left(\frac{3.31 \times 10^4}{T(Z)} \right)$ gms/ele-min														
β	Constant in carbon diffusivity term	$+ 7.99 \times 10^4 - ^\circ R$														

Midband Bore Corrosion Factors

K ₁	Constant evaluated from the NRX-A6 which leads to the observed NRX-A6 midband weight losses.	204 x 10 ² gm/in-ele														
A	Cyclic factor (see Figure J.5.2)*	<table><tr><td>Cycle</td><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td></tr><tr><td>Factor</td><td>1</td><td>3</td><td>5</td><td>7</td><td>9</td><td>11</td></tr></table>	Cycle	1	2	3	4	5	6	Factor	1	3	5	7	9	11
Cycle	1	2	3	4	5	6										
Factor	1	3	5	7	9	11										

* The hot end cyclic factor E and the midband cyclic factor A which apply to the rate of corrosion during each cycle are derived from Figure J.5.2, using the formula

$$E_n = nY_n - \sum_{i=1}^{n-1} E_i$$

where

n = number of cycles

Y_n = average corrosion value given in Figure J.5.2 for the nth cycle

E_n = cyclic factor for nth cycle

(CRD) CORROSION FACTORS USED IN FUEL ELEMENT BORE CORROSION CALCULATION (U)

INDEX NO.

J.4.2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S. L. D. 8-12-68	J. H. B. 8/12/68	

(CRD) HOT END BORE CORROSION FACTORS(U)

Hot Channel Corrosion Factor, D

Fuel element exit gas temperatures are distributed normally around the nominal temperature as given by the hot channel factor. This results in greater hot end weight loss than would occur if all elements were at nominal temperature. The factor D to account for this effect is:

$$D = \exp \left[\frac{1}{2} \left(\frac{\sigma_T}{240} \right)^2 \right] = 1.0875$$

where,

$3 \sigma_T$ = element-to-element hot channel factor, 295°R , based on calculation after orificing the core.

Cyclic Factor, E

See Figure J.5.2 for development of this factor.

Factor, K_2

This factor was used to adjust the hot end expression to give the incremental and total weight losses observed in the NRX-A6 test.

$$K_2 = 633 \exp \left(\frac{3.31 \times 10^{-4}}{T(Z)} \right) \text{ gms/ele-min}$$

Carbon Diffusivity Factor, β

This constant is a factor in the carbon diffusivity in the NbC coating. The factor was determined experimentally, WANL-TME-1370.

$$\beta = +7.99 \times 10^4 - ^\circ\text{R}$$

(CRD) DEVELOPMENT OF CORROSION FACTORS FOR HOT END BORE CORROSION EQUATION(U)	INDEX NO.
	J.4.3

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S. L. D. 8-12-68	JHB 8/12/68	

(CRD) MIDBAND BORE CORROSION FACTORS (U)

Cyclic Factor, A

See Figure J.5 for Development of this factor.

Corrosion Factor K_1

This factor was used to adjust the midband expression to give the measured NRX-A6 midband weight loss - 1.1 gms/element in 60 minutes.

$$K_1 = 204 \times 10^2 \text{ gm/in-ele}$$

(CRD) DEVELOPMENT OF CORROSION FACTORS FOR MIDBAND BORE CORROSION EQUATION (U)

INDEX NO.

J.4.4

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S L D. 8-12-68	JHB 8/12/68	

(CRD) The preliminary XE-2 test profile (Table J.6.2) involves considerable cyclic operation. Previous fuel element corrosion testing experience was reviewed for guidance as to the best method of incorporating cyclic effects into the bore corrosion calculations. The NRX-A6C, Part I,⁽¹⁾ and GP-72⁽²⁾ electrical test programs were found most useful as sources of cyclic effect information.

(CRD) It was concluded from A6C, Part I, one and two cycle investigations that: (1) in the midband (0 to 35 inches) region, two cycles gave about twice the bore weight loss suffered during one cycle for the same total operating time, and (2) in the element hot end (35 to 52 inches), two cycles gave about 15 per cent more weight loss than one cycle. Figure J.5.1 shows the A6C cyclic results. The GP 72 test program included significant data with standard matrix elements for up to four cycles of corrosion testing. These results indicated that midband corrosion was increased by four or five times (over one cycle for the same total time) for four cycles, and hot end corrosion was approximately doubled.

(U) A plot of cyclic multipliers as deduced from the A6C and GP 72 test results is given in Figure J.5.2.

⁽¹⁾ (CRD) NRX-A6 Characterization Test, Part I, was a program utilizing 64 NRX-A6 production quality fuel elements. Operating parameters studied were cycles (one and two), operating time (four levels), and power-flow combinations (four). The NRX-A6 elements were judged to be similar to XE-2 elements.

⁽²⁾ (CRD) GP-72 was primarily intended to test the effect of fuel element matrix additives on cyclic and endurance capability of high void fuel elements. Although the elements were high void, the bore coating matched the process and chemistry of the NRX-A6 and XE-2 bore coats. The data used were for the standard matrix elements in the test plan.

(CRD) FUEL ELEMENT CYCLIC PERFORMANCE (U)	INDEX NO.
	J.5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S.L.D. 8-12-68	JHB 8/12/68

(CRD) INCREMENTAL WEIGHT LOSSES FOR NRX-A6 CHARACTERIZATION TEST (U)	INDEX NO.
	J.5.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S.L.D. 8-12-68	JHB 6/2/68

(CRD) CALCULATIONAL MULTIPLIER TO ACCOUNT FOR CYCLIC BORE CORROSION EFFECTS (U)	INDEX NO.
	J.5.2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S. L. D. 8-12-65	JH / 8/12/65	

J.6 Fuel Element Corrosion Calculations (U)

(CRD) Calculation of the fuel element corrosion, the associated reactivity loss and control drum position was made with the LOWERE Computer Code. Six individual runs incorporating a multiplier for cyclic operation in the midband and hot end region were made to calculate the fuel element performance for the postulated 6 cycle XE-2 run profile given on Figure J.6.2. The reactivity loss limit of 2.0\$ which was established prohibited completion of the 5th cycle.

(CRD) XE-2 fuel element bore corrosion performance is summarized in the following figures:

Figure J.6.3 - Presents the total fuel element bore corrosion calculation.

Figure J.6.4 - Presents the control drum position with reactor operating time.

Figure J.6.5 - Presents the incremental weight losses for the core center and core periphery at approximately the completion of the 5th cycle (65 mins)

(CRD) It should be noted that the calculations given in Figures J.6.3, J.6.4, and J.6.5 are subject to the following limitations and assumptions.

1. Cyclic effects were extrapolated from the single element electric furnace NRX-A6 characterization tests (2 cycles) and GP-72 (4 cycles).
2. Single cycle fuel element performance was adjusted to that observed in the NRX-A6 reactor test.
3. All material loss from the fuel element bores is carbon.
4. The effect of planned low temperature cyclic operation at 2200°R chamber temperature on fuel element corrosion was neglected.
5. Fuel element external surface corrosion was assumed to equal that observed in the NRX-A6 reactor test, approximately, 1.0 gram/element, in 60 minutes (Assumed linear with time).

(CRD) FUEL ELEMENT BORE CORROSION CALCULATION (U)	INDEX NO.
	J.6.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S L. D. 8-12-68	J H B 8/12/68	

Cycles	Duration (Min.)	Chamber Temperature (°R)
4	6	2200
5	13	4 Min. at 3400 followed by 9 Min. at 4090
1	9	4090

NOTES:

1. Conservative interpretation of XE-2 operating requirements as received from A. Bermingham, AGC-NRO, June 27, 1968.
2. XE-2 test objectives may be revised to include any XE-1 objectives not accomplished during XE-1 test.
3. 3400/4090°R combination cycles to be accomplished without cooldown between 3400 and 4090°R portions.

(CRD) PRELIMINARY TEST PROFILE REQUIREMENTS, XE-2 (U)	INDEX NO.
	J.6.2

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S. L. D. 8-12-68	JHB 5/12/68

(CRD) FUEL ELEMENT AVERAGE WEIGHT LOSS AND REACTIVITY LOSS VERSUS OPERATING TIME (U)	INDEX NO.
	J.6.3

REFERENCE

J-29

INDEX NO.
J.6.4

(CRD) CALCULATED XE-2 DRUM POSITION (U)	PREPARED BY	APPROVED BY
	S L D 8-12-68	y H B 8/12/65

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S L D 8-12-68	8/13 8/12/68

(CRD) CALCULATED INCREMENTAL WEIGHT LOSSES (U)	INDEX NO
	J.6.5

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S. L. D. 8-12-68	JH B 8/12/68	

(CRD) The calculational method for predicting fuel element external surface corrosion is described on p. J-11, WANL-TME-1565. The interelement gaps are expected to be smaller than those in XE-1 but larger than those in NRX-A6. Based on this information and on the calculations for XE-1 and NRX-A6 surface corrosion (p. J-17, WANL-TME-1565, and p. I-19, WANL-TME-1642, respectively), XE-2 surface corrosion is predicted to occur in the distribution shown in Figure J.6.7. The data shown are for five 3400/4090°R chamber temperature operating cycles, the bulk of the preliminary XE-2 test profile described in Table J.6.2. Since total element corrosion calculations indicate that the 2S reactivity loss limit will be exceeded during the fifth cycle, the predictions do not include the last full power hold.

(CRD) The calculations are seen to predict maximum surface corrosion of the outermost uncoated elements to be about 19 mils on the average. It is, therefore, possible that corrosion through to the bore liners will occur at many locations, since the web thickness "on bores" is between 22 and 29 mils.

(CRD) The NRX-A6 calculations predicted an integrated surface weight loss of 0.5 grams per element. Based on a best interpretation of the NRX-A6 reactor test data, the actual corrosion was about one gram per element. Although there is a large per cent error between the two numbers, the difference in magnitude between the two values is small. The XE-2 reactor is expected to lose 1 to 1.5 grams per element, with almost all the loss in the midband region.

(CRD) The following important uncertainties in the calculations are to be noted:

1. Bore-induced surface corrosion, that is, surface corrosion caused by hydrogen originating in the bores and entering the interelement gaps through pinholes, is not incorporated. Although pinholes and the effects of pinholes made little contribution to the single-cycle NRX-A6 surface corrosion, the multi-cycle XE-2 reactor test is expected to result in an increased pinhole population. The extent of pinhole formation in a reactor cannot be assessed analytically and is not indicated by the single element electric furnace tests as shown in the pinhole comparison of Figure J.3.7.

2. Interelement gap size is an important variable in the surface corrosion calculations; the sensitivity of corrosion to change in gap size is demonstrated on pp. J-18 and J-19, WANL-TME-1565. The following parameters enter into calculations of interelement gap size. Each parameter has associated uncertainties which mutually contribute to uncertainties in the gap size.

- a. Fueled and central support element coefficients of thermal expansion.
- b. Fueled and central element temperatures, including changes in radial temperature distribution caused by drum motion.
- c. Element across-flats dimensions.
- d. Core radial pressure distribution.
- e. Core periphery mechanical and hydraulic bundling forces.

3. The analysis is based on average conditions, in particular, average interelement gaps (leading to average interelement flow) and average material temperatures. Locally more severe corrosion due to higher than average flows or temperatures is not taken into account.

4. The effect of hydrocarbon pyrolysis (resulting in carbon deposition, shown to exist in the NRX-A6 reactor by the interelement bonding) on interelement gap size is not included.

(CRD) FUEL ELEMENT SURFACE CORROSION CALCULATION (U)

INDEX NO.

J.6.6

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S.L.D. 8-12-68	JHB 8/12/68

(CRD) AXIAL DISTRIBUTION OF FUEL ELEMENT EXTERNAL SURFACE CORROSION (U)	INDEX NO.
	J.6.7

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S L D 8-12-68	JH/BS 9/12/68

(CRD) AXIAL DISTRIBUTION OF FILLER STRIP RADIAL SURFACE CORROSION (U)	INDEX NO
	J.7.1

REFERENCE	PREPARED BY	APPROVED BY	Astronuclear Laboratory
	S. L. D 8-12-68	JHB 8/12/68	

98

(CRD) A conservatively safe support block capability is judged to be about 40 minutes of full power operating time, as stated previously in a letter from H. F. Faught to J. L. Dooling, "XE-2 Reactor Design Definition", dated December 19, 1966. The additional operation at chamber temperatures of 3400°R and below, as listed in Table J.6.2, is also considered within the capability of the XE-2 blocks. Although deduced independently, this estimate of support block operating capability agrees generally with the time limit resulting from the fuel element corrosion calculations. As shown in Figure J.6.3, the \$2 reactivity loss limit is predicted to occur during the fifth high temperature cycle, after about 40 minutes of full power operation.

(CRD) This estimate of the XE-2 support block corrosion performance is based on NRX/EST and NRX-A5 reactor experience, and on previous structural and corrosion tests performed at WANL to verify the adequacy of the blocks. The support block aft end counterbore fillet radius was cracked during startup transients of NRX-A2, NRX-A3, and NRX/EST. Axial cracking at the outer perimeter walls of the peripheral support blocks also occurred during startup of all prior reactors, including NRX-A6, and is expected in XE-2. The resulting corrosion and undermining caused very little degradation in the ultimate strength of the blocks according to load tests carried out on a total of 37 blocks taken from NRX-A2, NRX-A3, and NRX/EST. This load test data can be extrapolated for an additional ten minutes beyond the results for 21 cracked and corroded NRX/EST blocks which operated for 30 minutes above 3700°R with multiple startup ramps. The extrapolation is justified by the consistency of results for the various reactors and the wide margin between measured ultimate strength and tie rod load. The support blocks used in NRX-A5 were improved with the addition of grafoil washers and increased fillet radius. As a result of these improvements and reduced startup ramp rates, no fillet cracking occurred in NRX-A5. The same support block design (but with a more adherent coating) is used in XE-2. These improvements, together with the removal of partial lobes from the J3, J5, and J9 blocks, the improved uniformity in fuel element corrosion performance, and the limitation of the first XE-2 startup ramp rates to 50°R/sec will provide additional performance margin.

OHIO, CLEVELAND, OHIO
0-0-0

1968 JUL 13 1968 (CRD) SUPPORT BLOCK CAPABILITY (U)	INDEX NO.
	J.8