P
0
AECU-2890

W.O. 43869

AECU-2890

Studies of the $\text{Li}^6(\text{n}, \alpha)\text{H}^3$ Reaction with Nuclear Emulsions

James H. Roberts
Department of Physics
Northwestern University
Evanston, Illinois

UNCLASSIFIED

Final Report

December 21, 1953

Work supported by A. E. C. Contract No. AT(11-1)-66

This report has been photostated to fill your request as our supply of copies was exhausted. If you should find that you do not need to retain this copy permanently in your files, we would greatly appreciate your returning it to TIS so that it may be used to fill future requests from other AEC installations.

7640-1

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

/ /

Studies of the $\text{Li}^6(\text{n},\alpha)\text{H}^3$ Reaction with Nuclear Emulsions

1. Introduction

Since Progress Report No. 3 (February 20, 1953) and its supplement (April 1, 1953) were issued the major effort in the study of $\text{Li}^6(\text{n},\alpha)$ in nuclear emulsions at Northwestern has been to improve the technique of loading emulsions with specks of Li glass and to study the neutron energy resolution obtainable with the speck-loaded plates. Glass containing lithium highly enriched in Li^6 has been obtained.

Measurements of the differential cross-section of $\text{Li}^6(\text{n},\alpha)$ have been completed at 1.1, 1.5, and 2.0 Mev neutron energies. This work will be reported in a paper soon to be submitted to the Physical Review. Similar studies at neutron energies of 0.1, 0.27 and 0.600 Mev are nearly complete and will be submitted for publication in a separate report.

2. Preparation of Emulsions Containing Specks of Lithium Glass.

A summary of the most recent technique used to prepare nuclear emulsions loaded with specks of lithium glass has been published.¹ One gram of the glass is ground in a porcelain ball mill for one hour after it is powdered with a mortar and pestle. About 15 mg. of the ground glass is put into 3 cc of absolute alcohol in a one dram bottle. The mixture is agitated vigorously for about two minutes and allowed to settle for two minutes. Most of the alcohol containing suspended glass is pipetted off. About 3 cc of absolute alcohol is then added to the glass that remains and the process repeated. After a few such processes, only a small percentage of the glass settles out. Most of the suspended glass has speck sizes from 1 to 5 microns in diameter.

7640-2

The alcohol-glass mixture is sprayed by an atomizer on a 1" x 3" 50 micron Ilford E1 plate. After the alcohol has dried, E1 gel emulsion mixed with water in a ratio of two parts of emulsion to one of water by volume is heated to about 55°C and poured over the top of the 50 micron plate. After the emulsion has gelled (about 30 minutes) the plate is put into a drying box held at a temperature of about 30°C. for four hours. The emulsion is then ready for use.

A sample of glass containing lithium enriched in Li^6 to 93.4% was prepared for Mr. Victor Krohn of the Argonne National Laboratory by H. P. Hood of the Corning Glass Works. 4.192 gm. of LiNO_3 were supplied to Corning. The first melt had the following composition:

SiO_2	36%
Al_2O_3	8%
B_2O_3	8%
Li_2O	30%
Co_2O_3	18%

This sample proved rather unstable, and after grinding in a porcelain ball mill was sent back to Corning, where 2.2 grams of it (probably containing some porcelain) was diluted with 0.44 gm of 71% SiO_2 and 29% B_2O_3 glass. This glass was still not as stable as an earlier sample made with 15% Li_2O and no Co_2O_3 , but plates prepared from it had better than 65% of the tracks originating in visible specks. (Better than 90% of the tracks in plates made with the 15% Li_2O glass originated in visible specks.) The tracks not coming from specks were distributed at all depths throughout the emulsion, indicating that the "migration length" was such as to leave an accumulation of lithium near the specks unlikely. The only apparent harm of loss of some

7640-3

lithium from the glass is to reduce the effective number of lithium atoms in the glass. It is recommended that glass made in the future not contain the Co_2O_3 which is believed to be the chief cause of the trouble. It was added to color the glass and improve its visibility. It did no good, however, and it now appears that the glass is adequately visible without it.

A batch of 1" x 3" plates 100 microns thick, made with E1 emulsion and about 50 micrograms of the Li^6 glass/ cm^2 at the central layer have been prepared by Ilford Limited on an experimental basis. They appear quite satisfactory except for some clumping of the glass specks.

3. Resolution Obtained for 265 kev. Neutrons Incident "Isotropically" on Speck Loaded Plates.

Plates loaded with specks of 15% Li_2O glass (normal lithium) were exposed by Victor Krohn and the Van de Graaff group at the Argonne National Laboratory to 265 kev neutrons from $\text{Li}^7(\text{p},\text{n})\text{Be}^7$, using a 7 kev lithium target. The plates were wrapped in cadmium, and those which have been scanned were in the "isotropic rotator."² The integrated neutron flux was about 4.5×10^8 neutrons/ cm^2 . Every track found was measured. Whereas the $\sim 1" \times 1"$ plates had about 100 tracks each, scanning was easily accomplished under low power, since scanning in only one plane was required.

Every track coming from a visible speck was measured, regardless of diving angle. Shrinkage of the plates had been prevented by the usual glycerine treatment. A total of 514 tracks were measured by three observers. The track data was reduced by the usual method.²

A plot of the number of tracks per two micron interval (overlapping) for $0^\circ \leq \theta_0 \leq 30^\circ$, $0^\circ \leq \theta_0 \leq 60^\circ$, and $0^\circ \leq \theta_0 \leq 90^\circ$ (see Fig. 2, Ref. 2)

7640-4

as a function of the triton range corrected to $\theta = 180^\circ$ (i.e., triton emitted in forward direction) is shown in Fig. 1. The resolution, as would be expected, is seen to improve as tracks are selected in the smaller ϕ_0 cones. In the three plates shown there are 56, 144, and 220 tracks respectively. The percentages of the total tracks measured are therefore 11%, 28%, and 43%.

A similar plot for the same ϕ_0 intervals was made in which the sum of ranges ($R_\alpha + R_T$) was used instead of the triton range. The uncertainty in the point of disintegration due to the glass speck size was, however, comparable to the alpha straggling, so that no significant difference in resolution was observed in the two methods.

Exposures have also been made in the "isotropic" rotator to neutrons of 100, 270, 400, and 600 kev. Ilford E1 plates loaded with specks of Li^6 glass were used. Very few tracks have been measured. The purpose of this data is to obtain correction factors for the determination of relative intensities, and to obtain further information on neutron energy resolution.

4. Angular Distribution and Cross-Section Measurements.

Results on the angular distribution and cross-section of $\text{Li}^6(n,\alpha)$ for neutron energies of 1.1, 1.5, 2.0, and 2.5 Mev have been previously reported.³ The angular distribution at 1.1, 1.5, and 2.0 Mev have now been fitted to spherical harmonics.

We assume that the yield function $Y(\phi_0)$ can be expanded into spherical harmonics:

* ϕ_0 is the neutron-triton angle in the center of mass system.

7640-5

$$Y(\theta_0) = \sum_{i=0}^{\infty} a_i P_i(\theta_0),$$

where $P_0(\theta_0) = 1$, $P_1 = \cos \theta_0$, and $P_2 = 3/2 \cos^2 \theta_0 - 1/2$. Since spherical harmonics are orthogonal the coefficients a_i are obtained by a numerical integration from:

$$a_i = (i + 1/2) \int_0^\pi 2 \pi Y(\theta_0) P_i(\theta_0) \sin \theta_0 d\theta_0,$$

or, if written as a summation,

$$a_i = 2 \pi (i + 1/2) \sum_{k=1}^n P_i(\theta_0)_k Y_k(\theta_0) (\Delta \cos \theta_0)_k.$$

Now in our measurements we have determined $Y_k(\theta_0) (\Delta \cos \theta_0)_k$ for each 10° interval.⁴ Table I gives the values of a_0 , a_1 , and a_2 as calculated from this equation for these neutron energies as well as for those previously studied.⁵ A plot of the differential cross-section for $E_n = 1.1$, 1.5 , and 2.0 is also given in Fig. 2. Fig. 3 shows a fit of the results to the data at 2.0 Mev. The agreement is satisfactory within the limits of accuracy of the data. These results will be reported in a paper by J. B. Weddell and J. H. Roberts soon to be submitted to the Physical Review.

Further studies of the angular distribution and cross-section at 0.1 , 0.27 , and 0.60 Mev are underway. The data is complete but the analysis is not. The results will be reported in the PhD thesis of W. O. Pardo.

7640-6

5. Critical Evaluation of the Li^6 Technique for the Study of Neutron Spectra.

Four different types of neutron sources are to be considered in discussing the value of the $\text{Li}^6(n,\alpha)$ reaction in nuclear emulsions for the study of neutron spectra. Since speck-loading promises to have advantages for all types of sources, the following discussion presupposes that speck loading is used.

a) Unidirectional neutrons in which the neutrons are primarily in the energy region from thermal to 2.0 Mev.

When the neutron direction is known E_n , the neutron energy, is best determined from measurements of $R_\alpha + R_T$ and ϕ , where ϕ is the neutron-triton angle, or from R_T and ϕ . If specks are used in which the uncertainty of the point of disintegration is of the order of one micron or less there is some advantage in using R_T and ϕ , since the effect of alpha straggling is eliminated; for larger specks, however, the two methods give about the same resolution. If tracks are selected for which $0^\circ \leq \phi \leq 30^\circ$ resolution at least as good as ± 100 kev. is obtained. The tracks are easy to measure, and little judgement is required to make correct interpretations. In the region from 0.4 to 2.0 Mev relative intensities at least as good as $\pm 10\%$ appear feasible with reasonable statistics although the present knowledge of the differential cross-section probably does not permit this for all energies in this region. Below 0.4 Mev even better energy resolution is possible, but the problem of measuring relative intensities is complicated by the resonance in the cross-section at 0.27 Mev. and by the high cross-section for thermal neutrons. The percentage accuracy will be greatly influenced by the shape of the neutron spectrum in this region. If

7640-7

the thermal background is low and if the ratio of neutron intensities at 0.27 and 0.10 Mev is not greater than about two, some worthwhile information can often be obtained in the region from 0.1 to 0.4 Mev. (The smaller this ratio, of course, the better). The only way to make good use of the resonance is for the detection of a group of neutrons about 0.27 Mev having low intensity, such as in neutron scattering experiments.

Histograms are readily constructed through the use of the Boas slide rule.⁶

b) Unidirectional Neutrons in which a considerable fraction of the neutron flux is contributed by neutrons above 2.0 Mev.

2 Mev protons have a range of about 40 microns in E1 emulsions. If the neutron spectrum contains many neutrons above 2 Mev the proton background introduces serious problems. It has been estimated that for a fission spectrum there are about as many proton tracks which accidentally go through a speck so as possibly to be interpreted as a triton-alpha pair as there are triton-alpha pairs. Thus the importance of good track discrimination, and some critical judgement is not entirely eliminated by the introduction of speck loading. Scanning speed is also reduced because of the proton tracks.

In such work there is a distinct advantage if the neutron direction is known, since the tracks accepted for good resolution ($0^\circ \leq \theta \leq 30^\circ$) have the alpha tracks toward the neutron source, at the same end as the beginning of the proton tracks.

Apart from these considerations the same remarks can be made here as under part (a). No experimental data has yet been obtained for this case.

7640-8

c) Isotropic or anisotropic extended neutron sources with most neutrons below 2 Mev.

Problems of measurement are much the same as for case (a) except that ϕ is unknown and θ must be determined. Neutron energies are determined from $R_T + R_a$ and θ , as discussed in Ref. 1, or from R_T and θ (See § 3). Neutron energy resolution is generally a little worse than for case (a), since the accuracy of determining θ is about $\pm 5^\circ$. The accuracy of determining relative intensities should be comparable to case (a), provided the empirical probability that $0^\circ < \phi_0 \leq 30^\circ$, etc., has been measured. This is now being undertaken at Northwestern.

d) Isotropic or anisotropic extended neutron sources with a considerable fraction of the neutron flux contributed by neutrons above 2.0 Mev.

This is the most difficult situation because of the proton recoil background and because of the necessity of examining all tracks which go through a speck within 10 microns or less from one end of the track. Through the use of plates loaded with mock-lithium glass specks possible confusion with proton tracks accidentally going through specks can be corrected for, if necessary. The technique will, at best, probably be rather hard to use for such measurements and is not to be recommended unless the importance of the data justifies the laborous techniques involved. No definite conclusions should be reached as yet, however, until further experimental evidence is obtained. It is planned to obtain this evidence through further work at Northwestern. The fact that there are practically no other techniques available to measure neutron spectra from such sources, at least for neutrons below 0.6 Mev, it appears that such tests are justified.

7640-9

6. Acknowledgement

The author of this report wishes to express his appreciation to the U. S. Atomic Energy Commission for making the research done on this project possible. Thanks is also expressed to Mr. Victor Krohn and to the Van de Graaff group at the Argonne National Laboratory for the plate exposures and for their continued interest.

Track measurements and calculations were done during the period of this particular report by Mr. Jerome Green, Mr. William Meltzer, and Mr. Miles Kline. Calculations were also made by Miss Lillian Darlington, and work on speck loading was done by Mr. Donald Wood and Mr. Jack Haugsnes.

References

1. J. H. Roberts, J. Haugsnes, and D. E. Wood, "Loading of Nuclear Emulsions with Li^6 Glass", Bulletin of American Physical Society, Chicago Meeting, November 1953.
2. J. H. Roberts, W. O. Solano, D. E. Wood, and H. B. Billington, Rev. Sci. Instr. 24, 920, Oct. 1953; LA-1526.
3. J. B. Weddell and J. H. Roberts, Bulletin of A.P.S., Chicago Meeting, November 1953.
4. J. H. Roberts, Supplement to Progress Report No. 3, April 1, 1953.
5. L. E. Darlington, J. Haugsnes, H. M. Mann, and J. H. Roberts, Phys. Rev. 90, 1049, June 1953.
6. M. L. Boas, Rev. Si. Instr. 24, 356, May 1953.

7640-10

Table I

Neutron Energy	a_0	a_1	a_2
0.20	0.167	0.102	0.156
0.40	0.095	0.049	0.078
0.60	0.040	0.012	0.019
1.10	0.022	0.022	0.006
1.50	0.025	0.016	0.003
2.00	0.021	0.008	0.001

2640-11

Figure 1

7640-122

Figure 2

UNCLASSIFIED

7640-13

UNCLASSIFIED

Figure 3

0-13-