71131

RECORD COPY
REON

SNPO-C

SACRAMENTO PLANT

REPORT NO. RN-S-0242

TO

AEC-NASA SPACE NUCLEAR PROPULSION OFFICE

SECONDARY EJECTOR STUDY

MASTER

NERVA PROGRAM

CONTRACT SNP-1

OCTOBER 1965

AEROJET-GENERAL CORPORATION

SACRAMENTO, CALIFORNIA

RECORD COPY

DISTRIBUTION OF THIS DOCUMENT UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

REPORT NO. RN-S-0242

SECONDARY EJECTOR STUDY

NERVA PROGRAM

OCTOBER 1965

CONTRACT SNP-1

ROCKET ENGINE OPERATIONS - NUCLEAR

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

CLASSIFICATION CATEGORY

UNCLASSIFIED

Harry O. Palmer 10/18/65
CLASSIFYING OFFICER DATE

AEROJET-GENERAL CORPORATION
A SUBSIDIARY OF THE GENERAL TIRE & RUBBER COMPANY

DISCONTINUED

San

BLANK

ABSTRACT

This report presents the analytical and experimental evaluation of the scale-model, annular-nozzle, secondary ejector test program of Contract Year 1965. Three annular nozzle ejectors were tested and evaluated to determine the effects of ejector nozzle area ratio, total pressure, primary and secondary fluid properties (temperature, pressure, and molecular weight), and primary inlet Mach number. The design procedure for a primary diffuser and a secondary ejector are defined and an illustrative example is included.

for
W. D. Stinnett
Program Manager
REON

TABLE OF CONTENTS

	<u>Page</u>
I. SUMMARY	1
II. INTRODUCTION	3
III. TEST FACILITY AND GENERAL APPARATUS	7
A. Test Facility	7
B. Secondary Ejectors	7
C. Miscellaneous Hardware	10
D. Instrumentation	10
IV. RESULTS AND DISCUSSION	19
A. Test Procedure	19
1. Phase I	19
2. Phase II	23
3. Phase III	23
B. Test Results	23
1. Phase I	23
2. Phase II	53
3. Phase III	57
V. DESIGN PROCEDURE FOR A SECONDARY EJECTOR	63
VI. CONCLUSIONS AND RECOMMENDATION	91
REFERENCES	92
APPENDIX A, Prediction of Ejector System Performance	93
BIBLIOGRAPHY OF EJECTOR SYSTEMS	
Non-Pumping	102
Pumping	105

LIST OF ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1	Test Stand	8
2	Tabulation of Pertinent Dimensions of Secondary System	9
3	Greyrad Calorimetric Probe	11
4	Greyrad Calorimetric Probe Installed in Duct	12
5	Sampling-Tube of Calorimetric Probe (Greyrad Model G-6 General Purpose Probe)	13
6	Location of Pressure Measurements	16
7	Schematic of Calorimetric Probe and Thermo- Conductivity Cell Setup	17
8	Test Program (Phase I) $\epsilon_s = 7.65$	20
9	Test Program (Phase I) $\epsilon_s = 3.97$	21
10	Test Program (Phase I) $\epsilon_s = 2.0$	22
11	Secondary Ejector Test Program (Phase I)	24
12	Test Program (Phase II)	25
13	Summary of Tests Performed (Sheet 1 of 4)	27
13	Summary of Tests Performed (Sheet 2 of 4)	28
13	Summary of Tests Performed (Sheet 3 of 4)	29
13	Summary of Tests Performed (Sheet 4 of 4)	30
14	Performance Map of Diffuser Exit Pressure vs X	31
15	Momentum Ratio of Primary and Secondary Stream at Break Off Point	32
16	Fabri One Dimensional Flow Model	34
17	Predicted Primary Exit Pressure Determined by Fabri ($A_{sec}^* = 2.334 \text{ in}^2$)	36
18	Predicted Primary Exit Pressure Determined by Fabri ($A_{sec}^* = 4.495 \text{ in}^2$)	37
19	Predicted Primary Exit Pressure Determined by Fabri ($A_{sec}^* = 8.93 \text{ in}^2$)	38
20	Model of Plane of Equal Velocities	40
21	Predicted Primary Exit Pressure Determined by Plane of Equal Velocities ($A_{sec}^* = 2.334 \text{ in}^2$)	42
22	Predicted Primary Exit Pressure Determined by Plane of Equal Velocities ($A_{sec}^* = 4.495 \text{ in}^2$)	43
23	Predicted Primary Exit Pressure Determined by Plane of Equal Velocities ($A_{sec}^* = 8.93 \text{ in}^2$)	44

LIST OF ILLUSTRATIONS (cont.)

<u>Figure</u>		<u>Page</u>
24	Typical 3-Dimensional Solution Surface M_{pe} vs P_{pet}/P_{sc} , P_a/P_{sc}	45
25	Typical 3-Dimensional Solution Surface $\dot{w}_p/\dot{w}_s$ vs P_{pet}/P_{sc} , P_a/P_{sc}	46
26	Typical 3-Dimensional Solution Surface on a Plane of Equal P_a/P_{sc} M_{pe} vs P_{pet}/P_{sc}	48
27	Typical 3-Dimensional Solution Surface on a Plane of Equal P_a/P_{sc} $\frac{\dot{w}_p}{\dot{w}_s}$ vs P_{pet}/P_{sc}	49
28	Total Pressure Ratio vs M_{pe} Solution Surface ($A_s^* = 2.334 \text{ in}^2$)	50
29	Total Pressure Ratio vs M_{pe} Solution Surface ($A_s^* = 4.495 \text{ in}^2$)	51
30	Total Pressure Ratio vs M_{pe} Solution Surface ($A_s^* = 8.98 \text{ in}^2$)	52
31	Results of Phase II (Sheet 1 of 2)	55
31	Results of Phase II (Sheet 2 of 2)	56
32	Mach No. Profile at Exit of Secondary Duct as Secondary Chamber Pressure is Increased	58
33	Diffuser Exit Pressure at Zero Flow as a Function of Secondary Ejector Chamber Pressure (Ambient Flow)	59
34	Diffuser Exit Pressure at Zero Flow as a Function of Secondary Ejector Chamber Pressure (Hot Flow)	60
35	Typical Exhaust System	64
36	Effect of Ejector Diffuser Area Ratio on Maximum Contraction Ratio	67
37	Ratio of Diffuser Throat to Primary Nozzle Throat Area	68
38	Effect of 2nd Throat L_T/D_T on Optimum System Performance	69
39	Secondary Ejector System Center Body	72
40	Secondary Ejector System Annular System	73
41	Typical Performance Map of Primary Duct Exit Pressure as a Function of Secondary Ejector Chamber Pressure	75
42	Cylindrical Ejector Performance as Effected by Ejector Area Ratio	77
43	Performance Map of Diffuser Exit Pressure vs X	78
44	Effect of Secondary Ejector Geometry on Performance - Primary and Secondary Flow Parameters are Constant	79

LIST OF ILLUSTRATIONS (cont.)

<u>Figure</u>		<u>Page</u>
45	Increase in Secondary Pressure Ratio Necessary to Improve Performance of Secondary Ejector as System Ω is Increased	81
46	Proposed NERVA II Test Facility	82
47	Proposed NERVA II Engine Performance P_c vs T_c	88
48	Flow Schematic of Ejector System	95
49	Pressure Ratio Across An Oblique Shock as a Function of Area Ratio	97
50	The effect of Exit Area Ratio on Ejector Performance	101

SymbolNomenclature

P_c	primary nozzle chamber pressure
T_{cp}	primary fluid total temperature
M_p	primary fluid molecular weight
ϵ_p	primary nozzle expansion ratio
A_e	primary nozzle exit area
A_p^*	primary nozzle throat area
A_d	diffuser inlet area
S_d	diffuser inlet spacing
δ	diffuser contraction angle
α	primary nozzle gimbal angle
β	diffuser expansion angle
A_t	second throat area
L_t	second throat length
A_l	turning elbow area
R_l	turning elbow radius
A_{pe}	exit area of diffuser duct
A_s^*	throat area of secondary ejector nozzle
A_{se}	exit area of secondary ejector nozzle
A_{sd}	area of secondary mixing duct
L_{sd}	length of secondary mixing duct
P_{sc}	chamber pressure of secondary ejector nozzle
T_{sc}	chamber temperature of secondary ejector nozzle
m_s	molecular weight of secondary fluid

I. SUMMARY

Three, supersonic, annular secondary ejector systems were evaluated experimentally to determine the effect of various parameters on the pumping phenomena to define a flow model that could be used to predict ejector performance for testing NERVA engines. The secondary ejector consists of a supersonic annular nozzle ejecting a subsonic primary stream.

The test program was divided into three phases.

The first phase consisted of twenty-seven performance runs on the three geometrically different secondary ejector systems to determine the effect of geometry and temperature on performance. All runs were conducted utilizing hydrogen gas as the primary fluid and nitrogen gas as the pumping media. The areas of diffuser exit duct and the mixing duct were kept constant for all phases.

The second phase consisted of 13 tests. A calorimetric probe and thermal conductivity cell were utilized to traverse the duct to define a pressure profile, hydrogen concentration and momentum profile at four longitudinal locations in the mixing duct.

The third phase was comprised of selecting the best performing system of Phase I and obtaining additional data. The additional data included utilizing nitrogen gas as the primary fluid, a 10% increase in the flow rate of the secondary ejector above the "pull in" point, and variety of Ω points. ("Pull in" point is that point where the primary duct exit pressure first reaches a minimum value for zero primary flow rate).

The four analytical methods utilized were:

A. Map of primary exit pressure vs epsilon function at various values of the omega (Ω) function.

B. FABRI ONE-DIMENSIONAL ANALYSIS

This method assumes that the secondary supersonic stream accelerates the primary subsonic stream to a sonic condition downstream of the diffuser duct exit; there is no mixing between the two streams and momentum is conserved.

C. PLANE OF EQUAL VELOCITIES

This method assumes that the secondary supersonic stream accelerates the subsonic primary stream to a point where the absolute velocity of the two streams are equal. The ratio of the increase in kinetic energy of the primary stream is then in direct proportion to the decrease in static pressure ratio (P_a/P_a) of the primary stream.

D. SOLUTION SURFACE

This method describes the performance of the ejector system utilizing a three dimensional plot.

A design procedure is included along with an illustrative example for a nuclear rocket application utilizing an annular secondary ejector system.

II. INTRODUCTION

The Secondary Ejector Study Program was composed of three parts. The first was to analyze data from previous test programs and arrive at a model or models whereby design and performance criteria for future systems could be determined. The second part of the program was to conduct a series of tests varying given parameters of the system to determine effects over a range consistent with foreseeable engines. The test results would be used to uprate and extend the range of the analytical model or models. Part three of the program was concerned with analyzing test data and preparing a design procedure whereby future ejector systems could be designed and their performance determined.

The purpose of Phase I was to determine why as Ω is increased, the secondary ejector chamber pressure must also be increased in order to prevent a degradation in performance. This phenomenon was first described in REON Report 2680 which stated that when Ω is equal to 1, the secondary ejector chamber pressure required for best pumping is that value where the engine compartment pressure is a minimum when there is no primary fluid. In other words, when the secondary ejector is operated by itself, it will exhibit a performance curve and start point similar to a primary system operated by itself. It is the secondary ejector chamber pressure at this start point that will provide optimum pumping for a primary-secondary system in which the Ω is unity. As Ω is increased, the secondary ejector chamber pressure must be increased to provide optimum pumping.

Two possible reasons for this necessary increase in secondary ejector chamber pressure are:

- (1) to provide additional momentum to the secondary fluid,
- (2) to stop flow separation in the secondary nozzle.

Expanding on the above explanations:

For (1) - As Ω is increased, for a given system, the primary engine chamber pressure required to start the ejector increases. As a result of this increase in primary engine pressure, the velocity of the primary fluid, when it contacts the secondary fluid, is greater than for a lower value of Ω . In order that the secondary fluid be able to efficiently pump out this primary fluid of increased velocity, the secondary fluid must have additional momentum. Hence, for our fixed system, the momentum of the secondary fluid could be increased by increasing the chamber pressure in the secondary nozzle.

For (2) - If it is assumed that for a given system, the secondary fluid will supply sufficient momentum to accelerate the primary fluid and cause a start condition no matter what the value of Ω , another interesting possibility arises to explain the need of increased secondary ejector chamber pressure. As pointed out above, when Ω is increased the primary chamber pressure required to start is increased. At the chamber pressure where a start condition is reached, the pressure ratio (primary engine/diffuser duct exit) is a constant value, dependent only on primary diffuser geometry. As Ω is increased, the chamber pressure to start is increased and therefore the pressure at the diffuser duct exit is increased. If this diffuser duct exit pressure is sufficiently large, it will induce flow separation in the secondary ejector. Once flow separation occurs, the pumping ability of the secondary fluid is decreased. One way to overcome this flow separation is to increase the secondary ejector chamber pressure.

Phase II of the study program was designed to yield information concerning the process whereby the secondary ejector fluid "accelerates" the primary fluid. This information was obtained with the use of a calorimetric probe and a thermo-conductivity cell. The calorimetric probe was such that its axial location could be changed during a run allowing a survey of the pressure across the duct to be made. During a test, when this pressure survey was being obtained, the probe was stopped at selected locations to allow a sample of the mixture of primary and secondary fluid to be taken. This gas sample did not only yield the degree of mixing of the two fluids but also gave the enthalpy of the mixture.

By making mixing, pressure, and enthalpy measurements at various locations across the secondary duct at selected locations along the secondary duct, the pumping process could be defined.

Comparison of the performance of the three systems tested in Phase I has shown which of the systems is the best. This best system was then tested over a wide range of variables for Phase III.

Analysis of results from Phase III enabled the design procedure, mentioned earlier, to be developed.

BLANK

III. TEST FACILITY AND GENERAL APPARATUS

A. TEST FACILITY

A photograph of the test facility is shown in Figure 1. The calorimetric probe is shown installed with the rectangular bosses along the duct indicating other possible positions for the probe.

The absence of a primary diffuser should be noted. It has been shown that a given primary diffuser system has a given ratio of engine chamber pressure to the diffuser exit pressure at which this system will start. This pressure ratio to start is a constant for a given system. Because the type of information desired must be applicable for many primary systems, it was decided that to obtain the best test data the primary diffuser should be eliminated altogether. The primary system would be composed of a plenum upstream of the secondary ejector where fluid with controlled properties could be introduced.

Nitrogen and hydrogen were used as test fluids. When heating of these fluids was required, it was accomplished with two stored energy heaters. These heaters are capable of heating the test fluids to 1600°R.

B. SECONDARY EJECTORS

After a careful analysis of all the variables involved in the pumping problem previously described, it was found that by varying only the throat area of a secondary ejector nozzle that the velocity of the secondary fluid could be changed without influencing other parameters. Limits of secondary throat sizes, which determine operating chamber pressure, were selected to be compatible with current or projected hot gas generating systems. Figure 2 tabulates the pertinent dimensions of the secondary systems that were built and tested.

Figure 1
Test Stand
8

SYSTEM	A_s^* in ²	A_{se} in ²	A_{pe} in ²	A_{sd} in ²	L_{sd} in	RUN NO. 284 -
1	2.334	17.9	27.8	45.7	61	1 → 8 41 → 52
2	4.495	17.9	27.8	45.7	61	9 → 17 28 → 40
3	8.93	17.9	27.8	45.7	61	18 → 27

Figure 2
Tabulation of Pertinent Dimensions
of Secondary System

C. MISCELLANEOUS HARDWARE

Figures 3 and 4 show the calorimetric probe as used during Phase II of the test program. Figure 5 shows the cross section of the probe. Construction of the probe itself is of copper, with stainless-steel supports. Cooling water from a high pressure source (500 psi) enters through the mounting block, passes up the front stainless-steel support, and through the outermost channel to the probe tip. It returns via the inner coolant channel. Sheathed, ungrounded thermocouple junctions are located at the probe coolant channel inlet and outlet. The central tube carries a steady flow of sample gas from the probe tip past a thermocouple junction located opposite the "water out" thermocouple and then through a gas sample tube to the thermal-conductivity cell where the gas mixture concentration is measured.

The probe is equipped with a variable speed control which enables variations in the speed at which the probe traverses the duct during a test.

D. INSTRUMENTATION

1. General

In order to obtain the best possible results from the secondary ejector test program, it was decided to use the ADDAS (Aerojet Digital Data Acquisition System) to record and reduce all test data. As a safety precaution, all data were simultaneously recorded on a 36 channel oscillograph. These oscillograph data are to be used only in case of a malfunction in one or more of the ADDAS channels. Some of the functions were also recorded on the LMV chart recorders in the test bay control room. The LMV recorders are used to give the test engineers instant visible knowledge of the control parameters in the system during a test.

Figure 3
Greyrad Calorimetric Probe
11

Figure 4
Greyrad Calorimetric Probe Installed in Duct
12

Figure 5
Sampling-Tube of Calorimetric Probe
(Greyrad Model G-6 General Purpose Probe)

The Aerojet Digital Data Acquisition System is an accurate, high speed, high capacity, data processing and recording system. It gathers and conditions test parameters in analog form, converts it to digital, and records it on magnetic tape. The tape is then processed through the IBM 709⁴ which tabulates and makes various calculations of the digitized data. The finalized data are ready for engineering analysis within one to two hours following a test.

The system's resolution is ± 1 count in 20,000 with an accuracy of 0.1% of the reading. End-to-end system accuracy can be 0.5% with proper selection of transducers.

For the secondary ejector studies 38 functions were sampled, each function being sampled and recorded every 0.4 second. Twenty separate calculations were performed on specific parts of the data and the results of these calculations along with the basic sampled data were presented in tabular form by the computer.

As well as printing out the data, the computer also punched cards for specific parameters. These cards were then fed into an automatic data plotter which yielded a graphical presentation of the data.

Figure 6 shows the locations where the pressure measurements were made and the nomenclature used.

2. Greyrad Calorimetric Probe and Gas Sampling System

For certain tests during this program, a Greyrad Calorimetric Probe was used in conjunction with a Gow-Mac thermal conductivity cell to obtain information about the mixture of primary and secondary fluids at various locations in the secondary duct. Figures 3 and 4 shows photographs of the probe assembly. Figure 5 is a cross-section of the probe showing flow passages, etc. Figure 7 is

a schematic showing the actual valving arrangement and test setup with the thermal conductivity cell.

A number of known mixtures of hydrogen and nitrogen were used to calibrate the thermoconductivity cell. From these points it was possible to derive a calibration equation which was stored in the computer. The concentration of hydrogen in nitrogen established as the digital characteristics of the unknown sample was matched to the calibration equation.

SECONDARY EJECTOR ANALYSIS TEST SYSTEM

SECONDARY EJECTOR NO	A_{PE}	A_{SD}	A_{SE}	A_s^*	ϵ
1	27 805	45 664	17 859	8 930	2.0
2	27 805	45 664	17 859	4 495	3.97
3	27 805	45 664	17 859	2 334	7.65

PRESSURE TAP	L/D	PRESSURE TAP	L/D
PsD-1	0.81	PsD-9	2.000
PsD-2	2.31	PsD-10	3.000
PsD-3	3.44	PsD-11	8.000
PsD-4	4.75	PsD-12	4.000
PsD-5	6.06	PsD-13	5.000
PsD-6	7.37	PsD-14	6.000
PsD-7	8.68	PsD-15	7.000
PsD-8	1.000

Figure 6
Location of Pressure Measurements

Figure 7
Schematic of Calorimetric Probe and
Thermo-Conductivity Cell Setup

BLANK

IV. RESULTS AND DISCUSSION

A. TEST PROCEDURE

1. Phase I

The test program for Phase I is shown in Figures 8, 9 and 10. Three secondary nozzle area ratios were each tested at two values of secondary fluid temperature. For each of these values of secondary fluid temperature, there was a test with two values of primary fluid temperature. The primary fluid flow rate was varied to give selected values of pressure at the primary exit.

The method for conducting Phase I tests is shown in Figure 11 and described below:

a. At time ① the secondary ejector chamber pressure is increased until P_{pe} reaches a minimum value, indicating a secondary ejector start condition. This provides the minimum possible value of $\dot{w}_s$ for pumping.

b. At time ② primary flow is initiated and increased until P_{pe} reaches a predetermined value at time ③ .

c. At time ③ the secondary ejector chamber pressure is increased until P_{pe} reaches its minimum value. P_{sc} is then held constant.

d. At time ④ the primary flow is decreased to zero.

e. At time ⑤ a short time for measuring P_{pe} at the increased level of P_{sc} is allowed.

f. At time ⑥ P_{sc} is shut down.

The above procedure was repeated for different values of desired P_{pe} and primary and secondary fluid conditions in accordance with the test program.

Figure 8
 Test Program (Phase I) $\epsilon_s = 7.65$
 20

Figure 9
 Test Program (Phase I) $\epsilon_s = 3.97$
 21

Figure 10
 Test Program (Phase I) $\epsilon_s = 2.0$

2. Phase II

The test program for Phase II is shown in Figure 12. Figure 7 shows the schematic of the calorimetric probe-thermo conductivity cell set up. For four longitudinal positions along the secondary duct, the probe was used to obtain data on the mixture of the primary and secondary gas. When the desired test conditions (prescribed value of P_{pe}) were arrived at, as described in Figure 11, a gas sample was taken. The probe then traversed to the next position and another sample was taken. Data were obtained at four locations from the centerline of the duct to the outer wall.

By running a series of mixtures with known concentrations of hydrogen and nitrogen through the system (Figure 7) prior to actually testing, a calibration curve was derived. An equation (fifth order polynomial) was then written for this curve and the equation was incorporated as part of the computer program. The printout of the data, therefore, yielded a direct reading of the percentage of hydrogen in nitrogen, by volume.

3. Phase III

Phase III utilized the best performer of the three secondary ejector systems tested to obtain a performance map for a variety of test conditions. The secondary ejector was set at its pull-in value and the primary flow was increased until the pressure at the primary duct exit was 10 psia. The primary flow was then decreased back to zero. Tests were conducted for seven values of Ω .

B. TEST RESULTS

1. Phase I

The purpose of Phase I is twofold. First, determine why as Ω is increased, the secondary ejector chamber pressure must also be increased in order to prevent a degradation in performance; second, the geometry of the secondary system was varied in order to determine its effect along with Ω .

RUN SEQUENCE

Figure 11
Secondary Ejector Test Program
Phase I
24

Figure 12
Test Program (Phase II)

Other effects that might influence ejector performance such as; a range of secondary chamber pressures above the designated optimum point at zero primary flow, various L/D of the secondary mixing duct. Economic and time restrictions were such that investigations in these areas were impossible in order to fully obtain the influence of the omega (Ω) function.

The test conditions for Phases I, II and III are present in Figure 13.

a. Ω Function

Figure 14 is a map of expected primary duct exit pressure as a function of ($x = \text{omega times the weight flow ratio}$) for various values of omega. It is shown that the lowest value of duct exit pressure is realized for low values of omega.

Also of note in this plot is that at some time during the run the slope of the curve breaks off abruptly (Run #50 $\epsilon = 0.22$ and $P_{pe/pa} = 0.3$). Coincident with this point, it was noted that the Mach number of the primary gas becomes constant, indicating the secondary ejector is not longer able to accelerate the primary gas; also, the duct pressure (Figure 6 $P_{sd}-1$ --- $P_{sd}-15$) undergoes a definite rise at this point, indicating a breakdown in the pumping efficiency. The two secondary ejector exit pressure taps ($P_{se}-1$ and $P_{se}-2$) located 180° apart, did not show signs of separation when the duct taps ($P_{sd}-1$ --- $P_{sd}-15$) experience a sharp rise.

The mach number being constant after some point in the run is attributed to some choking phenomena and it appears to be dependent on the omega function.

Figure 15 compiles the momentum ratio of the three systems determined at the point where M_{pe} becomes constant. At this "break off" point, it seems that it is possible to increase the momentum of the primary stream to a greater value as Ω is decreased.

SECONDARY EJECTOR PROGRAM
SUMMARY OF TESTS PERFORMED

RUN NO D-28a LQ-	DATE	PHASE	PURPOSE	PRIMARY SYSTEM			SECONDARY EJECTOR			OTHER TEST CONDITIONS	RESULTS	
				FLUID	W/sec	T ₁ °R	TYPE	FLUID	P _{sc} psia			T _{sc} °R
1	5/16/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles.	H ₂	303	606	III	H ₂	2.6	502	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value.	P _{FE} (min) 3.22 psia
2	5/16/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles.	H ₂	670	609	III	H ₂	3.8	500	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value.	P _{FE} (min) - 6.01 psia
3	5/16/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles.	H ₂	.220	1.0	III	N ₂	.7	477	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value.	P _{FE} (min) 3.4 psia
4	5/16/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles.	H ₂	-	-	III	N ₂	-	-	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value.	Test no good N ₂ supply low
5	5/16/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles.	H ₂	.234	1.311	III	H ₂	2.1	496	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value.	P _{FE} (min) 4.0 psia
6	5/17/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles.	H ₂	.38	1.5	III	N ₂	2.0	500	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value.	P _{FE} (min) 11.4 psia
7	5/17/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles.	H ₂	1.1	611	III	N ₂	2.5	107	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value.	P _{FE} (min) 2.0 psia
8	5/17/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles.	H ₂	-	-	III	N ₂	-	-	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value.	Test no good N ₂ supply low
9	5/24/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles.	H ₂	384	1212	II	H ₂	184	500	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value.	P _{FE} (min) 1.51 psia
10	5/24/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles.	H ₂	1.1	1100	III	N ₂	1.0	500	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value.	P _{FE} (min) 1.1 psia
11	5/24/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles.	H ₂	400	1420	III	N ₂	1.3	492	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value.	P _{FE} (min) 10.34 psia

Figure 13
Summary of Tests Performed
(Sheet 1 of 4)

SECONDARY EJECTOR PROGRAM
SUMMARY OF TESTS PERFORMED

RUN NO D-284 LQ-	DATE	PHASE	PURPOSE	PRIMARY SYSTEM			SECONDARY EJECTOR			OTHER TEST CONDITIONS	RESULTS	
				FLUID	ω lb/sec	T °R	TYPE	FLUID	P _{sc} psia			T _{sc} °R
12	3/24/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	228	1	5 97 L	H ₂	100	1357	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value	P _{FE} (min) 4.9 psia
13	3/24/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	229	011	5 97 L	H ₂	161	1357	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value	P _{FE} (min) 7.43 psia
14	3/24/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	191	0	5 97 L	H ₂	14	1400	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value	P _{FE} (min) 3.28 psia
15	3/25/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	701	1272	5 97 L	H ₂	134	1411	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value	P _{FE} (min) 7.20 psia
16	3/25/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	140	153	5 97 L	H ₂	12	1400	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value	P _{FE} (min) 2.94 psia
17	3/26/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	701	5	2 00 L	H ₂	16	1400	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value	P _{FE} (min) 6.01 psia
18	4/5/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	241	1151	2 00 L	H ₂	80	1400	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value	P _{FE} (min) 7.80 psia
19	4/5/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	-	0	2 00 L	H ₂	-	-	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value	Test not good N ₂ supply low
20	4/5/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	183	1218	2 00 L	H ₂	77	01	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value	P _{FE} (min) 5.41 psia
21	4/5/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	192	124	2 00 L	H ₂	70	03	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value	P _{FE} (min) 5.58 psia
22	4/5/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	080	1070	2 00 L	H ₂	72	433	Secondary was set at its nominal pull in value, primary was initiated and increased until a preselected value of primary exit pressure was achieved, secondary was then increased until primary exit pressure reached a minimum value	P _{FE} (min) 3.91 psia

Figure 13
Summary of Tests Performed
(Sheet 2 of 4)

SECONDARY EJECTOR PROGRAM
SUMMARY OF TESTS PERFORMED

RUN NO D-284-LG	DATE	PHASE	PURPOSE	PRIMARY SYSTEM			SECONDARY EJECTOR			OTHER TEST CONDITIONS	RESULTS
				FLUID	ω lb/sec	T_1 °R	TYPE	FLUID	P_{sc} psia	T_{sc} °R	
23	4/6/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	1	200	1				1.2 (3) 18.4
24	4/16/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	1	200	1				(0.1) 1.1
25	4/6/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	1	200	1				P (m) 1.1
26	4/6/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	1	200	1				(7) 1.1
27	4/7/65	I	To find the relationship between pumping ability and secondary chamber pressure for 3 secondary nozzles	H ₂	1	200	1				(1) 1 ps
28	5/26/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	1	200	1				
29	5/26/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	1	200	1				
30	5/26/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	1	200	1				
31	5/28/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	1	200	1				
32	5/28/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	1	200	1				
33	5/28/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	1	200	1				
34	5/28/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	1	200	1				
35	5/28/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	1	200	1				
36	6/1/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	1	200	1				
37	6/2/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	1	200	1				

Figure 13
Summary of Tests Performed
(Sheet 3 of 4)

SECONDARY EJECTOR PROGRAM
SUMMARY OF TESTS PERFORMED

RUN NO D-284-LQ-	DATE	PHASE	PURPOSE	PRIMARY SYSTEM			SECONDARY EJECTOR				OTHER TEST CONDITIONS	RESULTS
				FLUID	ω	$T, ^\circ R$	TYPE	FLUID	P_{sc} psia	$T_{sc}, ^\circ R$		
38	6/2/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	463	1435	c 5 97 1	N ₂	181	1454	Probe tip at 6 125 in from primary exit	
39	6/2/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	153	1249	e 5 97 1	N ₂	179	1462	Probe tip at 44 25 in from primary exit	
40	6/2/65	II	To determine the degree of mixing of the primary and secondary fluid at various axial and longitudinal locations in the secondary duct	H ₂	498	1435	e 5 97 1	N ₂	181	1510	Probe tip at 44 25 in from primary exit	
41	6/7/65	III	To obtain a complete operating and performance map of the best of the three secondary ejectors	H ₂	-	-	e 5 97 1	N ₂	14 → 471	10	Secondary only operating	
42	6/8/65	III	To obtain a complete operating and performance map of the best of the three secondary ejectors	H ₂	0 → 1 409	109	e 5 97 1	N ₂	152	101		
43	6/8/65	III	To obtain a complete operating and performance map of the best of the three secondary ejectors	H ₂	0 → 3 251	119	e 5 97 1	N ₂	204	1048		
44	6/8/65	III	To obtain a complete operating and performance map of the best of the three secondary ejectors	H ₂	0 → 2 922	113	e 5 97 1	N ₂	221	1041		
45	6/8/65	III	To obtain a complete operating and performance map of the best of the three secondary ejectors	H ₂	0 → 2 926	117	e 5 97 1	N ₂	167	1400		
46	6/8/65	III	To obtain a complete operating and performance map of the best of the three secondary ejectors	H ₂	-	-	e 5 97 1	N ₂	14 → 478	1482	Secondary only operating	
47	6/9/65	III	To obtain a complete operating and performance map of the best of the three secondary ejectors	H ₂	0 → 1 132	1309	e 5 97 1	N ₂	247	1067		
48	6/9/65	III	To obtain a complete operating and performance map of the best of the three secondary ejectors	H ₂	0 → 1	1402	e 5 97 1	N ₂	238	1040		
49	6/9/65	III	To obtain a complete operating and performance map of the best of the three secondary ejectors	H ₂	0 → 703	1432	e 5 97 1	N ₂	220	1042		
50	6/9/65	III	To obtain a complete operating and performance map of the best of the three secondary ejectors	H ₂	0 → 9 7	1400	e 5 97 1	N ₂	240	1000		
51	6/9/65	III	To obtain a complete operating and performance map of the best of the three secondary ejectors	N ₂	-	-	e 5 97 1	N ₂	-	-	High frequency data was scrambled no usable results	
52	6/9/65	III	To obtain a complete operating and performance map of the best of the three secondary ejectors	H ₂	0 → 3 280	100	e 5 97 1	N ₂	150	1040		

Figure 13
Summary of Tests Performed
(Sheet 4 of 4)

LEGEND

	RUN NO	Ω
○	42	3.8 → 3.7
□	44	2.3 → 2.1
◇	47	3.9 → 5.4
△	48	4.4 → 5.8
◊	49	3.2 → 4.2
○	50	2.7 → 3.5
◇	52	1.1 → 1.4

NOTES -

$$A^*_S = 2.334 \text{ in}^2$$

$$A_{pe} = 27.8 \text{ in}^2$$

$$A_{SD} = 45.7 \text{ in}^2$$

PRIMARY FLUID - H_2 & N_2 (RUN 52) - 500 → 1600 °R

SECONDARY FLUID - N_2 - 500 → 1600 °R

Figure 14
Performance Map of Diffuser Exit
Pressure vs X

NOTES.

1. SYSTEM NO. 1.
SYSTEM NO. 2.
SYSTEM NO. 3.
2. SECONDARY FLUID N_2 AT 520 — 1600°R
3. PRIMARY FLUID H_2 AT 520 — 1600°R
4. m_{pe} BECOMES CONSTANT AS A FUNCTION OF Ω .

Figure 15
Momentum Ratio of Primary and Secondary
Stream at Break Off Point

b. Fabri Analysis

The model employs the same theory as given by "Theory and Experiments on Supersonic Air to Air Ejectors by J. Fabri and J. Paulon, NACA TM 1410. The test program employed the following conditions:

(1) Secondary

- (a) Nitrogen as pumping media
- (b) Vary gas temperature from 520°R to 1600°R
- (c) Secondary throat areas of 2.33 in.², 4.495 in.² and 8.93 in.²
- (d) Secondary expansion ratios, A_{se}/A_s^* , of 7.65, 3.97 and 2.0

(2) Primary

- (a) Nitrogen and hydrogen gas
- (b) Vary gas temperature from 520° to 1600°R
- (c) Primary exit area of $A_{pe} = 27.8 \text{ in.}^2$

Refer to Figure 16 for a schematic of the model. At Station 1, it is assumed that the primary stream attains a sonic condition (referred to as the "supersonic regime" by Fabri). There is no mixing between the two streams until after Station 1 and isentropic flow is assumed for both the primary and secondary streams.

An iteration technique is employed to solve P_{pe} and M_{pe} utilizing the continuity, momentum balance between Stations e and 1 and isentropic relationships.

Figure 16
 Fabri One Dimensional Flow Model
 34

Continuity

$$\frac{W_{\text{prim}}}{P_{\text{pe}}} = A_{\text{pe}} M_{\text{pe}} \sqrt{\frac{(\text{mol wgt}) \gamma g}{1545 T_{\text{pe}}} \left[1 + \frac{\gamma - 1}{2} M_{\text{pe}}^2 \right]}$$

Momentum

$$P_{\text{pe}} A_{\text{pe}} (1 + \gamma M_{\text{pe}}^2) + P_{\text{se}} A_{\text{se}} (1 + \gamma M_{\text{se}}^2) = P_{\text{pi}} A_{\text{pi}} (1 + \gamma M_{\text{pi}}^2) + P_{\text{si}} A_{\text{si}} (1 + \gamma M_{\text{si}}^2)$$

Isentropic Relationship

$$\frac{P_t}{P} = \left(1 + \frac{\gamma - 1}{2} M^2 \right)^{\frac{\gamma}{\gamma - 1}}$$

$$\frac{A}{A^*} = \frac{1}{M} \left[\frac{2}{\gamma + 1} \left(1 + \frac{\gamma - 1}{2} M^2 \right) \right]^{\frac{\gamma + 1}{2(\gamma - 1)}}$$

The Fabri, one-dimensional approach was performed and the results are presented in Figures 17 through 19.

It is considered that leaving out the wall shearing force in the momentum balance accounts for the lower-than-actual predicted values. The number one system has the highest secondary ejector velocity; therefore, the higher shear at the wall. This system also predicts the lowest values of duct exit pressure.

The Fabri tests were conducted with the supersonic stream buried in the subsonic stream, which is just the reverse of this test program.

c. Plane of Equal Velocities

Another flow model evaluated for this test program assumed that there is a point where the absolute velocity of the two streams are equal.

NOTES.

1. $A_{sc}^* = 2.334 \text{ in}^2$; $A_{SD} / A_s^* = 19.6$
 $A_{pe} = 27.8 \text{ in}^2$; $A_{SD} = 45.7 \text{ in}^2$
2. PRIMARY FLUID — H_2 (500 — 1600°R)
 SECONDARY FLUID — N_2 (500 — 1600°R)
3. $\circ$ — 284 LQ-2 $\Omega = 3.8/4.1$
 $\square$ — 284 LQ-5 $\Omega = 4.1/5.4$
 $\diamond$ — 284 LQ-7 $\Omega = 2.37$

Figure 17
 Predicted Primary Exit Pressure
 Determined by Fabri ($A_{sec}^* = 2.334 \text{ in}^2$)

NOTES.

1. $A_{sec}^* = 4.495 \text{ in}^2$; $A_{SD}/A_s^* = 10.5$
 $A_{pe} = 27.8 \text{ in}^2$; $A_{SD} = 45.7 \text{ in}^2$
2. PRIMARY FLUID - H_2 (500 — 1600°R)
 SECONDARY FLUID - N_2 (500 — 1600°R)
3. $\circ$ — 284 LQ — 11 $\Omega = 3.9/4.9$
 $\square$ — 284 LQ — 12 $\Omega = 2.6$
 $\diamond$ — 284 LQ — 15 $\Omega = 2.2/2.7$
 $\square$ — 284 LQ — 17 $\Omega = 3.8/3.9$

Figure 18
 Predicted Primary Exit Pressure
 Determined by Fabri ($A_{sec}^* = 4.495 \text{ in}^2$)

NOTES.

1. $A_{sec}^* = 8.93 \text{ in}^2$; $A_{SD}/A_s^* = 5.11$
 $A_{pe} = 27.8 \text{ in}^2$; $A_{SD} = 45.7 \text{ in}^2$
2. PRIMARY FLUID — H_2 (500 — 1600 °R)
 SECONDARY FLUID — N_2 (500 — 1600 °R)
3. $\odot$ — 284 LQ -18 $\Omega = 3.9/4.4$
 $\square$ — 284 LQ -20 $\Omega = 4.2/5.2$
 $\diamond$ — 284 LQ -23 $\Omega = 2.3$
 $\triangle$ — 284 LQ -24 $\Omega = 2.3$
 ∇ — 284 LQ -26 $\Omega = 3.4$
 $\hexagon$ — 284 LQ -27 $\Omega = 3.9$

Figure 19
 Predicted Primary Exit Pressure
 Determined by Fabri ($A_{sec}^* = 8.93 \text{ in}^2$)

Refer to Figure 20 for a schematic of the flow model. The kinetic energy ratio of the primary stream is assumed to be in a direct ratio to the decrease in primary pressure ratio across the duct.

An iterative technique was used to solve the following equations:

(1) Assume a value of primary Mach number at station e and from continuity solve P_{pe}

$$P_{pe} = \frac{\dot{w}_p \sqrt{1545} \sqrt{T_{cp}/\text{mol wgt}}}{A_{pe} \sqrt{g} M_{pe} \sqrt{1 + \frac{\gamma-1}{2} M_{pe}^2}}$$

(2) Calculate a value of M_{pe}^*

$$M_{pe}^* = \frac{\sqrt{\frac{\gamma+1}{2}}}{\sqrt{1 + \frac{\gamma-1}{2} M_{pe}^2}} M_{pe}$$

(3) From isentropic relationships

$$(a) \quad \left(\frac{A_{pi}}{A_{pe}} \right) = \frac{M_{pe}^*}{M_{pi}^*} \left[\frac{1 - \frac{\gamma-1}{\gamma+1} M_{pe}^{*2}}{1 - \frac{\gamma-1}{\gamma+1} M_{pi}^{*2}} \right]^{\frac{1}{\gamma-1}}$$

$$(b) \quad \frac{A_{si}}{A_{se}} = \frac{M_{se}^*}{M_{si}^*} \left[\frac{1 - \frac{\gamma-1}{\gamma+1} M_{se}^{*2}}{1 - \frac{\gamma-1}{\gamma+1} M_{si}^{*2}} \right]^{\frac{1}{\gamma-1}}$$

NOTES

- I. AT STATION I. — THE ABSOLUTE VELOCITY OF THE PRIMARY STREAM EQUALS THE ABSOLUTE VELOCITY OF THE SECONDARY STREAM

Figure 20
Model of Plane of Equal Velocities
40

(4) From geometry

$$A_{si} + A_{pi} = 45.7 \text{ in.}^2$$

(5) From plane of equal velocities

$$M_{si}^* = \Omega M_{pi}^*$$

(6) Solve M_{pi}^*

(7) Compute kinetic energy ratio of primary stream

$$\frac{K_{pi}}{K_{pe}} = \frac{A_{pe}}{A_{pi}} \left(\frac{M_{pi}^*}{M_{pe}^*} \right) = \frac{P_a}{P_{pe}},$$

Iterate until P_{pe} from Step (1) equals P_{pe} , calculated from Step (7).

The results of the plane of equal velocities model is presented in Figures 21 through 23. It appears to apply for $\Omega > 2$. From the physical aspect it would seem, based on Equation 5, that for a low value of Ω it would be impossible to accelerate the gas to some supersonic value.

d. Solution Surface

The approach taken was to assume that the ejector system can be represented by a "solution surfaces" defined in Reference 2. This study (Reference 7) is for the supersonic stream buried in the sub-sonic stream which is opposite to the NES configuration. A "solution surface" of similar form used in Reference (7) was assumed to apply to the present configuration and is used as a guide for evaluating ejector performance. In ejector operation, the stagnation pressure ratio (subsonic to supersonic stream, P_{pe_t}/P_{sc}) and the ambient pressure ratio (P_a/P_{sc}) are the main controlling variables for a given ejector configuration. Typical 3-dimensional solution surfaces are shown in Figures 24 and 25.

NOTES.

1. $A_{sec}^* = 2.334 \text{ in}^2$; $A_{SD} / A_s^* = 19.6$
 $A_{pe} = 27.8 \text{ in}^2$; $A_{SD} = 45.7 \text{ in}^2$
2. PRIMARY FLUID — H_2 & N_2 (Run 52) (500 — 1600°R)
 SECONDARY FLUID — N_2 (500 — 1600°R)
3. $\circ$ — 284 LQ - 2 $\Omega = 3.8/4.1$
 $\square$ — 284 LQ - 6 $\Omega = 4.1/5.4$
 $\diamond$ — 284 LQ - 7 $\Omega = 2.37$
 $\hexagon$ — 284 LQ - 43 $\Omega = 2.21$
 $\square$ — 284 LQ - 52 $\Omega = 1.0$

Figure 21
 Predicted Primary Exit Pressure
 Determined by Plane of Equal Velocities
 ($A_{sec}^* = 2.334 \text{ in}^2$)

NOTES.

1. $A_{sec}^* = 4.495 \text{ in}^2$; $A_{SD}/A_s^* = 10.15$
 $A_{pe} = 27.8 \text{ in}^2$; $A_{SD} = 45.7 \text{ in}^2$
2. PRIMARY FLUID — H_2 (500 — 1600 °R)
 SECONDARY FLUID — N (500 — 1600 °R)
3. $\circ$ — 284 LQ -11 $\Omega = 3.9/4.9$
 $\square$ — 284 LQ -13 $\Omega = 2.6$
 $\diamond$ — 284 LQ -15 $\Omega = 2.2/2.7$
 $\triangle$ — 284 LQ -17 $\Omega = 3.8/3.9$

Figure 22
 Predicted Primary Exit Pressure
 Determined by Plane of Equal Velocities
 ($A_{sec}^* = 4.495 \text{ in}^2$)

NOTES.

1. $A_{sec}^* = 8.93 \text{ in}^2$; $A_{SD}/A_s^* = 5.11$
 $A_{pe} = 27.8 \text{ in}^2$; $A_{SD} = 45.7 \text{ in}^2$
2. PRIMARY FLUID — H_2 (500 — 1600 °R)
 SECONDARY FLUID — N_2 (500 — 1600 °R)
3. $\circ$ — 284 LQ - 18 $\Omega = 3.9/4.4$
 $\square$ — 284 LQ - 24 $\Omega = 2.33$
 $\diamond$ — 284 LQ - 26 $\Omega = 3.4$
 $\triangle$ — 284 LQ - 27 $\Omega = 3.9$

Figure 23
 Predicted Primary Exit Pressure
 Determined by Plane of Equal Velocities
 ($A_{sec}^* = 8.93 \text{ in}^2$)

Figure 24
 Typical 3-Dimensional Solution Surface
 M_{pe} vs P_{peT}/P_{sc} , P_A/P_{sc}

Figure 25
 Typical 3-Dimensional Solution Surface
 $\dot{w}_p / \dot{w}_s$ vs P_{pe_T} / P_{sc} , P_A / P_{sc}

The intersection of the solution surface (Figure 24) with the base plane ($M_{lp} = 0$) describes the base pressure solution. Point ① is termed the "start" pressure ratio (P_a/P_{sc}) and was determined for each test. The majority of the tests were run at the ambient pressure ratio described as Point ①.

Figures 26 and 27 show schematics of the intersection of the solution surface with the plane of constant but sufficiently low ambient pressure ratio ($P_a/P_{sc} \leq \text{Point ①}$).

Runs 3, 5 and 6 were plotted as shown in Figures 26 and 27. The data followed the general shape of the curves except that M_{lp} became constant at a value lower than 1.0 and the $\dot{w}_p/\dot{w}_s$ at that point changed slope. This indicates that the choking point lies downstream (assumed to be the exit plane) of the mixing plane instead of at the primary exit, thereby restricting the theoretically attainable performance. This follows from the fact that the duct wall "sees" the supersonic stream and therefore the friction losses will be high. A theoretical mixing calculation was made for one point of Run 6 which showed that, after mixing, the total and static pressures were above exit pressure required for choking at the exit, indicating that this is probably the case. A look at Run 7 (hot secondary, cold primary) shows that Mach 1.0 was attained at the primary exit prior to choking at the mixing duct exit. Several runs showed a decrease in P_{peT} with an increase in P_{sc} . This would indicate that a "start" condition had not been realized prior to increasing P_{sc} . Mass flow plots show that the large secondary area ratio nozzle gives the best performance for the duct configuration tested.

Figures 28 through 30 present the results of M_{pe} vs. P_{pet}/P_{sc} for the three ejector systems tested. It is noted that the primary stream Mach number stabilizes at some value less than 1.0. This was noted in the P_{pe} vs. χ plots, this breakoff point is attributed to secondary duct choking.

Figure 26
 Typical 3-Dimensional Solution Surface
 on a Plane of Equal P_a/P_{sc}
 M_{pe} vs P_{pe_t}/P_{sc}

Figure 27
Typical 3-Dimensional Solution Surface
on a Plane of Equal P_a/P_{sc}

$\frac{\dot{w}_p}{\dot{w}_s}$ vs P_{pe_T}/P_{sc}

NOTES.

1. $A_s^* = 2.334 \text{ in}^2$; $A_{SD}/A^* = 19.6$
 $A_{pe} = 27.8 \text{ in}^2$; $A_{SD} = 45.7 \text{ in}^2$
2. PRIMARY FLUID — H_2 & N_2 (Run 52) (500 — 1600°R)
 SECONDARY FLUID — N_2 (500 — 1600°R)
3. $\circ$ — 284 LQ-2 $\Omega = 3.8/4.1$
 $\square$ — 284 LQ-6 $\Omega = 4.1/5.4$
 $\diamond$ — 284 LQ-7 $\Omega = 2.37$
 $\triangle$ — 284 LQ-43 $\Omega = 2.21$
 $\square$ — 284 LQ-52 $\Omega = 1.0$

Figure 28
 Total Pressure Ratio vs M_{pe}
 Solution Surface ($A_s^* = 2.334 \text{ in}^2$)

NOTES.

1. $A_s^* = 4.495 \text{ in}^2$; $A_{SD}/A_s^* = 10.15$
 $A_{pe} = 27.8 \text{ in}^2$; $A_{SD} = 45.7 \text{ in}^2$
2. PRIMARY FLUID — H_2 (500 — 1600°R)
 SECONDARY FLUID — N_2 (500 — 1600°R)
3. ○ — 284 LQ -11 $\Omega = 3.9/4.5$
 □ — 284 LQ -13 $\Omega = 2.6$
 ◇ — 284 LQ -15 $\Omega = 2.2/2.7$
 △ — 284 LQ -17 $\Omega = 3.8/3.9$

Figure 29
 Total Pressure Ratio vs M_{pe}
 Solution Surface ($A_s^* = 4.495 \text{ in}^2$)

NOTES.

1. $A_s^* = 8.98 \text{ in}^2$; $A_{SD} / A_s^* = 5.11$
 $A_{pe} = 27.8 \text{ in}^2$; $A_{SD} = 45.7 \text{ in}^2$
2. PRIMARY FLUID — H_2 (500 — 1600°R)
 SECONDARY FLUID — N_2 (500 — 1600°R)
3. — 284 LQ — 18 $\Omega = 3.9 / 4.4$
 — 284 LQ — 24 $\Omega = 2.3$
 — 284 LQ — 26 $\Omega = 3.4$
 — 284 LQ — 27 $\Omega = 3.9$

Figure 30
 Total Pressure Ratio vs M_{pe}
 Solution Surface ($A_s^* = 8.98 \text{ in}^2$)

e. Quasi One-Dimensional Analysis Utilizing Wall Friction

Reference 5 presents a generalized quasi one-dimensional analysis utilizing wall friction to calculate the pressure recovery in the ejector system. This program was formulated by Greyrad Corp. consultant to REON.

Reference 5 presents a computer program which for this analysis may be coupled with any primary diffuser calculation and used to predict diffuser duct exit pressure for any desired ejector system over any range of operating conditions.

2. Phase II

The purpose of Phase II was to determine the pressure profile, specie concentration, momentum profile and temperature profile at various longitudinal locations in the mixing duct.

Thirteen tests were conducted utilizing System 2 ($A_s^* = 4.495$, in.²; $\frac{A_{se}}{A^*} = 3.97$).

Figure 7 schematically presents the test set up.

The test procedure was as follows:

- a. Set the secondary system at its "pull in" value.
- b. Increase the primary flow rate to a set value of primary duct exit pressure (3.0 psia or 6.0 psia).
- c. Take gas sample at first station approximately 1/2 inch from mixing duct wall, allow the output from the thermal conductivity cell to stabilize. Repeat this procedure at various locations until a survey is completed from the mixing duct wall to the centerline of the duct.

d. The primary gas temperature was always heated (1000°R to 1400°R). Five tests were performed with the secondary gas temperature at ambient. The remaining eight tests were performed with the secondary at approximately 1600°R.

e. The location of the thermal probe was at 1 1/8-, 6 1/8-, 13 3/4-, and 36 5/8-inches from the exit plane of the primary duct.

The results are presented in tabular form (Figure 31).

Following is a list of average test conditions for Phase II:

Run No.	$\dot{W}_{\text{prim}}$ (lb/sec)	T_{cp} (°R)	Ω	T_{sc} (°R)	P_{pE} (psia)	Long Dist.
28	.100	900	5.0	520	3.0	Loc B
29	.08	900	5.0	520	3.0	Loc B
30	.311	1300	6.0	520	7.3	Loc B
31	.07	800	5.0	560	3.0	Loc A
32	.3	1300	6.0	520	6.0	Loc A
33	.10	900	3.0	1600	3.0	Loc A
34	.42	1000	3.5	1500	6.0	Loc A
35	.15	900	3.5	1300	3.0	Loc C
36	.42	1200	3.5	1400	6.0	Loc C
37	.18	1000	3.0	1600	3.0	Loc B
38	.43	1400	3.0	1400	6.0	Loc B
39	.14	1200	3.0	1400	3.0	Loc D
40	.53	1400	3.0	1500	6.0	Loc D

RUN NO.	X IN.	L IN.	% H ₂ (VOL)	PROBE		PRIM			SEC	
				P _{PT} PSIA	P _{PS} PSIA	T _{cp} °R	W _p LB/SEC	P _{pe} PSIA	T _{sc} °R	W _{sec} LB/SEC
28 - 60.4	6.13	1.03	3.4	30.0	1.0	898	.095	2.8	511	16.0
88.8	6.13	2.04	7.8	23.0	4.1	983	.092	3.9	507	12.11*
29 - 23.2	6.13	1.37	3.1	38.7	1.8	836	.091	2.6	502	15.87
46.8	6.13	2.27	5.36	29.1	3.3	961	.087	2.7	504	16.15
52.8	6.13	3.25	5.87	25.3	4.7	978	.087	2.7	505	16.21
30 - 38.8	6.13	1.07	1.51	64.1	5.1	1309	.336	7.4	504	16.72
62.0	6.13	2.96	3.96	51.9	9.7	1387	.329	8.7	505	14.80
69.8	6.13	3.76	3.3	30.5	9.6	1407	.328	9.4	506	13.88
31 - 20.8	1.125	.45	2.7	44.2	4.2	762	.077	2.6	568	15.49
33.2	1.125	1.39	10.1	5.4	3.5	814	.074	2.7	562	15.81
43.2	1.125	2.32	8.8	5.7	3.0	840	.075	2.9	560	15.86
52.4		3.07	8.7	4.8	3.1	861	.074	3.0	553	15.97
32 - 37.2	1.125	.46	1.4	38.4	7.0	1174	.32	6.5	540	15.82
49.2	1.125	1.37	2.0	9.5	7.4	1234	.33	7.4	540	15.94
64.8		2.33	4.9	10.3	8.4	1279	.32	8.3	532	14.03
72.0		3.29	5.1	9.8	8.4	1390	.31	8.8	529	13.36
33 - 28.0	1.125	1.09	0*	50.5	4.5	886	.116	3.0	1582	10.05
44.0	1.125	1.99	0*	5.4	3.9	1162	.113	3.2	1551	10.61
56.0	1.125	3.01	0*	5.6	3.4	1014	.122	3.5	1501	10.98
62.4	1.125	3.86	0*	5.7	3.5	1030	.111	3.5	1454	11.15
34 - 36.0	1.125	1.04	2.07	51.6	8.0	1279	.461	5.7	1577	10.12
50.0	1.125	1.96	100.0	9.7	6.3	1447	.453	6.5	1548	10.59
62.0	1.125	2.95	100.0	9.7	6.8	1478	.449	6.9	1482	10.97
68.4		3.95	100.0	9.7	6.8	1492	.449	7.0	1414	11.18
35 - 20.0	13.75	.97	4.94	35.3	3.2	1059	.158	3.5	1544	10.01
32.0	13.75	1.45	5.90	32.0	3.0	1104	.152	3.5	1575	10.31
52.0	13.75	1.90	6.09	30.6	2.4	1155	.148	3.6	1506	11.05
64.0	13.75	2.34	6.31	28.1	2.4	1182	.146	3.6	1417	11.50
78.0	13.75	2.79	6.30	27.4	2.6	1208	.145	3.7	1286	12.24
90.0	13.75	3.29	6.40	27.8	2.9	1235	.146	3.5	1161	12.36
95.6	13.75	3.81	6.4	28.5	3.2	1245	.144	3.8	1107	12.02

* DATA QUESTIONABLE

Figure 31
Results of Phase II
(Sheet 1 of 2)

RUN NO.	X	L	% H ₂ (VOL)	PROBE		PRIM			SEC	
				P _{PT}	P _{PS}	T _{cp}	$\dot{W}_p$	P _{pe}	T _{sc}	$\dot{W}_{sec}$
				PSIA	PSIA	°R	LB/SEC	PSIA	°R	LB/SEC
36 - 30.0	13.75	1.0	4.5	42.4	5.4	1358	.450	5.7	1423	10.79
44.0	13.75	1.93	22.6	19.0	5.6	1411	.443	6.1	1388	11.22
56.0	13.75	2.42	32.0	19.9	7.6	1447	.443	6.6	1315	11.83
66.4	13.75	2.98	34.0	20.4	8.3	1471	.439	7.0	1232	12.21
79.2	13.75	3.56	32.6	21.7	8.7	1494	.437	7.4	1115	12.95
37 - 21.2	6.13	1.03	0	37.7	1.8	1087	.167	3.7	1671	9.83
30.0	6.13	1.44	0	43.7	2.5	1122	.166	3.9	1694	10.12
42.0	6.13	1.94	4.6	46.6	2.7	1162	.163	3.8	1674	10.41
62.0	6.13	2.42	7.0	38.8	3.1	1212	.161	3.9	1415	11.30
73.2	6.13	2.84	7.93	39.3	4.5	1232	.160	4.3	1314	11.76
94.0		3.34	13.40	24.4	5.7	1270	.158	4.2	1180	12.43
38 - 28.4	6.13	1.02	2.04	49.7	7.0	1385	.471	6.6	1606	9.92
36.0	6.13	1.38	2.40	43.7	7.0	1415	.465	6.7	1602	10.11
46.8	6.13	1.87	2.48	37.6	6.9	1448	.462	6.9	1562	10.52
55.2	6.13	2.35	2.47	25.9	6.9	1473	.460	6.9	1509	10.81
68.4	6.13	2.86	2.72	12.8	7.3	1504	.458	7.1	1399	11.41
80.0	6.13	3.42	2.74	10.5	7.9	1522	.456	7.5	1281	11.94
86.1	6.13	3.76	2.60	10.8	8.3	1533	.455	7.9	1216	12.29
39 - 20.0	36.63	.98	6.8	32.2	3.4	1219	.159	3.5	1557	9.85
32.0	36.63	1.46	8.4	27.5	3.1	1253	.153	3.7	1585	10.12
45.6	36.63	1.89	10.24	28.5	3.2	1286	.150	3.7	1542	10.58
50.0	36.63	2.38	11.66	28.8	3.2	1312	.149	3.7	1454	11.02
68.0		2.88	11.49	28.9	3.7	1324	.148	4.1	1372	11.43
77.2		3.36	11.0	29.0	4.1	1341	.146	4.1	1286	11.95
40 - 32	36.63	1.00	17.0	28.2	6.8	1456	.501	6.7	1665	9.79
46	36.63	1.41	23.5	25.4	7.0	1501	.497	6.8	1609	10.25
60	36.63	1.88	34.6	22.5	14.0	1530	.492	6.9	1539	10.79
72	36.63	2.36	47.1	20.9	15.4	1549	.489	7.2	1433	11.24
84	36.63	2.98	46.0	21.3	15.8	1566	.488	7.8	1305	11.90
94	36.63	3.45	43.5	21.9	16.1	1578	.487	8.5	1193	12.18
100		3.88	43.4	22.0	15.5	1558	.423	7.8	1132	11.93

Figure 31
Results of Phase II
(Sheet 2 of 2)

3. Phase III

Phase III consisted of 12 performance tests utilizing the best performance system based on the results of Phase I.

The system chosen for Phase III was System 1 ($A_s^* = 2.334 \text{ in.}^2$, $\frac{A_{se}}{A_s^*} = 7.65$).

A total of 12 performance tests was conducted during this phase.

Two tests were performed with the secondary ejector system operating alone. First, at a high chamber temperature (1600°R) and then at an ambient chamber temperature. The flow rate of the secondary system was increased to a point approximately 100% greater than the "pull in" value. The purpose of these two runs was to (a) define a Mach number profile at the exit of the mixing duct as a function of secondary chamber pressure (refer to Figure 32), (b) define the primary duct exit pressure at zero primary flow (refer to Figures 33 and 34), and (c) obtain some insight to possible duct choking as a function of flow rate. The duct did not realize a sonic condition at the mixing duct exit until the value of secondary chamber pressure reached 330 psia (normal operating point - 230 psia). (Refer to Figure 32).

Two off-design secondary chamber pressure tests were conducted. The first consisted of lowering the chamber pressure 10% below the normal operating point; this resulted in very poor performance. The second test consisted of increasing the secondary chamber pressure 10%. The higher chamber pressure test was designated 284-43; the test conditions were: $T_{sc} = 1400^\circ\text{R}$, $T_{cp} = \text{ambient}$, $P_{sc} = 266 \text{ psia}$ and $\Omega = 2.3$. This run compares, Ω wise, to 284-7. The test conditions for 284-7 are: $T_{sc} = 1400^\circ\text{R}$, $T_{cp} = \text{ambient}$, $P_{sc} = 230 \text{ psia}$ and $\Omega = 2.3$. Referring to Figure 28, Run 7 attains a Mach number at the primary exit of 0.58 and remains constant. Run 43, with the increased secondary chamber pressure, it was possible to accelerate the primary gas Mach number to 1.0. This infers that the choking

NOTES.

1. MACH NO. AT STATION 15 - 1 L/D FROM EXIT OF SECONDARY DUCT
2. SECONDARY SYSTEM FLOW - N_2 AT $1600^\circ R$

Figure 32
Mach No. Profile at Exit of Secondary
Duct as Secondary Chamber Pressure is Increased

NOTES.

1. TYPICAL START CURVE OF SECONDARY SYSTEM
2. SECONDARY FLUID - N_2 AT $520^\circ R$
3. SYSTEM NO. 1

$$A_s^* = 2.334 \text{ in}^2$$

$$A_{pe} = 27.8 \text{ in}^2$$

$$A_{sd} = 45.7 \text{ in}^2$$

Figure 33
Diffuser Exit Pressure at Zero Flow
as a Function of Secondary Ejector Chamber Pressure
(Ambient Flow)

NOTES.

1. TYPICAL START CURVE OF SECONDARY SYSTEM
2. SECONDARY FLUID — N_2 AT $1600^\circ R$
3. SYSTEM NO. 1

$$A_s^* = 2.334 \text{ in}^2$$

$$A_{pe} = 27.8 \text{ in}^2$$

$$A_{SD} = 45.7 \text{ in}^2$$

Figure 34
Diffuser Exit Pressure at Zero Flow
as a Function of Secondary Ejector Chamber Pressure
(Hot Flow)

phenomena that was experienced during the test program is not a function of the flow rate, for in Run 43 it is possible to pump additional primary flow at a lower exit pressure utilizing increased secondary flow rate above that used for pumping during Run 7. It would be of interest to investigate the additional amount of secondary flow rate needed to increase the performance of an ejector system utilizing high values of Ω . Increased performance is being able to accelerate the primary gas to a value of 1.0 before choking occurs.

Eight remaining tests were conducted to obtain further information concerning the effects of the Ω function. The secondary ejector system was set at its "pull in" value. Two of the eight tests were conducted utilizing nitrogen as the primary fluid to verify Ω as the scaling factor.

BLANK

V. DESIGN PROCEDURE FOR A SECONDARY EJECTOR

In order to test various rocket engine systems at simulated altitude conditions, it is necessary to utilize a self-pumping diffuser system. In some instances, it is necessary to utilize a secondary ejector system to augment the performance of the primary self-pumping system. The rocket engine systems that require a secondary ejector system are the subject of this section.

One system is an upper stage chemical engine which employs low chamber pressures and a high expansion-ratio nozzle. A second system of concern is a nuclear rocket engine which, inherent in its design, has a slow chamber pressure rise rate and therefore a low engine back pressure throughout the start-up and shut-down is highly desirable.

This section will present a procedure to design a diffuser-ejector system as required by the geometry and propellant properties of a particular rocket engine system.

The design procedure is divided into three parts. The first will deal with the diffuser and determine the overall pressure ratio required to "start" the engine system. The second will deal with augmenting the diffuser with an ejector. The third part is an exemplified diffuser-ejector design calculation.

A. DIFFUSER

Refer to Figure 35 for a schematic of the diffuser. The following sections will outline the steps to determine:

Diffuser Inlet Area (A_d)
Diffuser Inlet Spacing (S_d)
Diffuser Contraction Ratio (A_d/A_t)
Length of Second Throat (L_t)

Figure 35
Typical Exhaust System
64

The following is the engine parameters necessary to design the diffuser-ejector system:

Primary Nozzle Throat Area (A_p^*)
Engine Expansion Ratio - ϵ
Engine Chamber Pressure - P_c
Engine Chamber Temperature - T_c
Engine Fluid Molecular Weight - M_p
Engine Fluid Ratio of Specific Heat - γ

1. Diffuser Inlet Area (A_d)

The inlet area is determined by the outside dimensions of the nozzle assembly and if there are any gimbaling requirements.

The excursion of the engine during gimbaling dictates the diffuser-duct inlet area. The area should be just large enough to insure the proper clearances. During the NERVA subscale test program, engine gimbal angles of $\pm 4^\circ$ were conducted without any apparent increase in the chamber pressure necessary to obtain a start condition.

If gimbaling is not required, the diffuser duct inlet area should be just large enough to allow clearance of the engine assembly inside of the diffuser inlet.

2. Inlet to Diffuser Spacing (S_d)

During the NERVA subscale testing the inlet spacing was varied from $S_d/D_d = 0$ to 0.5 with no degradation in performance. It was noted that the heat transfer rates on the diffuser walls were slightly higher for the low spacing and therefore, if space allows, it is recommended that the larger spacing $S_d/D_d = 0.5$ be used.

3. Contraction Ratio (A_d/A_t)

The maximum diffuser contraction ratio for starting, as a function of the diffuser inlet area ratio, is shown on Figure 36. Experimental data from conical and bell-shaped nozzles are compared to a theoretical curve based on normal shock theory. Normal shock theory assumes that the subsonic stream downstream of the shock at A_d is accelerated to a sonic condition at A_t .

It can be seen from the data that values predicted by this normal shock theory are very conservative.

The maximum contraction angle (δ) of the diffuser, based on past test programs, is 10° .

Figure 37 presents the minimum starting (operating) chamber pressure (for the NERVA configurations tested at Aerojet the minimum operating and the starting pressures were the same) that can be realized utilizing a second throat diffuser as a function of the diffuser throat-to-nozzle throat area ratio (A_t/A_p^*).

4. Length of Second Throat (L_t)

An important parameter that will modify the minimum starting pressure of the diffuser is the length of the second throat. In order to maintain the minimum starting chamber pressure ratio as predicted by Figure 37, the L_t/D_t of the second throat must be at least 8.

If construction limitations are such that it is not possible to fabricate the second throat with this optimum L/D , Figure 38 presents the decrease in diffuser performance as the length of the second throat is decreased.

For example, if the L_t/D_t is decreased to 4, the starting pressure ratio will increase by 30%.

Figure 36
Effect of Ejector Diffuser Area Ratio
on Maximum Contraction Ratio

LEGEND

—— EMPIRICAL

----- NORMAL SHOCK (Total to Static Pressure Ratio)

- · - · - NORMAL SHOCK (Total to Total Pressure Ratio)

REF. - TN.-D - 298 (Fig. 16.)

Figure 37
Ratio of Diffuser Throat to
Primary Nozzle Throat Area

Figure 38
Effect of 2nd Throat L_T/D_T on
Optimum System Performance

5. 90° Turn Ejector

When the exhaust products are toxic or radioactive and vertical-down engine tests are required, a 90° turn is required for disposal away from the test stand. Past heat transfer results have shown that the gas should be turned gradually ($R/D > 5$) or if a sharper turn is desired a low subsonic condition should exist during the turn. It is recommended that a diffuser section be attached downstream of the second throat. The maximum diffuser angle is 8° to prevent flow separation. Attached to the diffuser is a 90° elbow with a turning radius of 1.5 elbow diameters.

The maximum heating rate to the diffuser will probably be located at the outside (impingement side) of the elbow between 40° and 50° of the 90° turn. An elbow diameter, D_1 , of 1.5 to 2 D_t and a turning radius, R_1 , between 1 and 2 D_1 should be sufficient to obtain a reasonably low heating rate. The maximum heat transfer coefficient, providing the flow does not separate and result in a direct impingement on the elbow, can be determined from the equation. (Reference R.N. DR-0038.)

$$\frac{h_{\max}}{h_{\text{ref}}} = 5.0e^{2.15 D_1/R_1} \quad (1)$$

where

$$h_{\text{ref}} = 0.026 (\text{Pr})_f^{.4} (\text{Re})_f^{.8} \frac{\gamma f}{D_1} \quad (2)$$

(assuming one-dimensional, shockless, supersonic flow)

The value of $h_{\max}/h_{\text{ref}}$ for D_1/R_1 of 0.5 is 14.7. This is not 14.7 times the one-dimensional subsonic heating rate. The reference heat transfer coefficient, h_{ref} , will be quite large because of the assumed high supersonic Mach number (isentropic flow from the nozzle throat to the elbow). Equation (1) can be

used to estimate the maximum heating rate at the first shock attachment point located near the diffuser entrance. In this case, D_1/R_1 equals 0 and $h = 5 h_{ref}$. This is the h just upstream of the first shock. Determine the change of the flow conditions across the shock and compute this maximum heat transfer coefficient. To compute the maximum heat transfer coefficient, determine the change of the flow conditions across the shock and use Equations 2 and 1.

The elbow diameter, D_1 , and the turning radius, R_1 , consistent with a reasonable heating rate can thus be determined from Equations (1) and (2).

If the diffuser starting pressure is considerably lower than the nozzle operating pressure, the flow must be restricted (choked) downstream of the elbow. As the nozzle chamber pressure increases past the diffuser starting pressure, the shock structure inside the diffuser increases in length. The growth of this shock structure into the elbow and flow separation can be prevented by contracting the subsonic flow in the elbow to an area sufficiently small to choke the flow at a nozzle chamber pressure greater than that required to start but less than that required to extend the shock structure into the elbow.

B. EJECTOR

The pressure ratio to "start" is now fixed for a particular system, utilizing empirical data and normal shock theory. A refinement over the normal shock theory to predict the "starting" pressure ratio across the diffuser is presented in Appendix A of this report.

In order to lower the starting chamber pressure it is necessary to lower the static pressure at the exit of the diffuser. This is accomplished by means of a secondary pumping ejector system (refer to Figure 39 and 40). Two types of ejectors are possible - the centerbody pumping system and the annular pumping system.

If it is possible to utilize a centerbody pumping system, it would be more desirable in that the supersonic secondary stream would be internal to the subsonic annular stream of the primary (diffuser). The decrease in the wall friction would account for better performance from the centerbody ejector over the annular ejector. Reference 1, 2 and 3 by Fabri, (Princeton report), and Chow & Addy present a model to predict performance for this type of system.

Figure 39
 Secondary Ejector System Center Body
 72

Figure 40
Secondary Ejector System Annular System
73

This section will present a method to determine the reduction in the diffuser exit pressure utilizing an annular supersonic secondary ejector.

The restrictions for an ejector are imposed by the availability of fluid flow and available head. Therefore, the parameters necessary to design the secondary system are:

Fluid flow rate - $\dot{w}_s$
 Maximum fluid temperature - T_{sc}
 Maximum fluid pressure - P_{sc}
 Fluid molecular weight - M_s
 Ratio of specific heat - γ_s

1. Secondary Duct to Primary Duct Area Ratio $\frac{A_{sd}}{A_{pe}}$

Various area ratio configurations were tested during a previous test program (refer to NERVA Report No. 2403).

The range tested varied from $\frac{A_{sd}}{A_{pe}} = 1.46$ to 2.82

In the range tested, the minor benefits in performance obtained by increasing $\frac{A_{md}}{A_{pe}}$ (holding throat area constant) were more than offset by the necessary increase in secondary flow rate.

It was decided that the most desirable "trade off" in performance and secondary flow rate is at an $\frac{A_{sd}}{A_{pe}} = 1.6$.

2. Secondary Nozzle Area Ratio

Figure 41 presents the "operation point" for an ejector. The "operation point" is defined, as ejector nozzle chamber pressure is increased from zero, as the point where an additional increase in P_{sc} will not reduce the diffuser exit pressure (refer to Figure 41).

Figure 41
 Typical Performance Map of Primary
 Duct Exit Pressure as a Function of
 Secondary Ejector Chamber Pressure

Figure 42 presents empirical data as compared to normal shock theory for $\gamma = 1.2$ and $\gamma = 1.4$.

3. Length of Mixing Duct $\frac{L_{sd}}{D_{sd}}$

A previous test program (refer to NERVA Report 2403) has shown that the optimum $\frac{L_{md}}{D_{md}}$ for a secondary ejector system is 8.0.

4. Diffuser Exit Pressure Determination P_{pe}

Figure 43 presents empirical diffuser exit pressure as a function of omega ($\omega = \frac{T_{cp}/m_p}{T_{sc}/m_s}$) and chi ($\chi = \Omega \frac{\dot{w}_p}{\dot{w}_s}$).

These exit pressures were obtained for one particular geometry secondary ejector system. This system consisted of the following:

$$\frac{A_{se}}{A_s^*} = 7.65$$

$$\frac{A_{sd}}{A_s^*} = 19.6$$

$$\frac{A_{sd}}{A_{pe}} = 1.65$$

If the design area ratio is determined by Section V B.2 of the report is other than $\frac{A_{sd}}{A_s^*} = 19.6$, it is necessary to obtain the diffuser exit pressure as a function of secondary geometry.

Figure 44 presents faired empirical results of the diffuser duct exit pressure change that may be realized by varying secondary geometry. Therefore, it is possible for a given ω and ϵ for a system to utilize P_{pe} data from Figure 43 and convert this pressure to a corresponding value for any secondary ejector geometry.

LEGEND.

- EMPIRICAL
- NORMAL SHOCK (Total to Static Pressure Ratio)
- · - · - NORMAL SHOCK (Total to Total Pressure Ratio)

Figure 42
Cylindrical Ejector Performance
As Effected by Ejector Area Ratio

NOTES -

$$A^*_S = 2.334 \text{ in}^2$$

$$A_{pe} = 27.8 \text{ in}^2$$

$$A_{SD} = 45.7 \text{ in}^2$$

PRIMARY FLUID - H_2 & N_2 (RUN 52) - $500 \rightarrow 1600^\circ\text{R}$

SECONDARY FLUID - N_2 - $500 \rightarrow 1600^\circ\text{R}$

Figure 43
Performance Map of Diffuser Exit
Pressure vs X

Figure 44
Effect of Secondary Ejector Geometry
on Performance - Primary and
Secondary Flow Parameters are Constant

The data of Figure 44 can be represented by the following:

$$P_{pe} = P_{pe} \text{ (Figure 43)} \left[\frac{19.6}{\frac{A_{sd}}{A_s^*}} \right]^{1/3}$$

Referring to Figure 44, it is noted that it is not possible to realize much decrease in diffuser exit pressure by increasing the ejector nozzle area ratio above 20.

Figure 45 presents a design curve that shows a possible increase in performance may be realized by increasing the secondary chamber pressure as Ω is increased. It also points out the importance in designing the system with as low a value of Ω as possible.

The nozzle chamber pressure at which the Diffuser-Ejector System will start can now be determined. A typical diffuser-ejector design following the above procedures is presented in detail in the following section.

C. EXAMPLE OF DIFFUSER-EJECTOR DESIGN CALCULATIONS

The following presents the calculations required to arrive at the diffuser-ejector system dimensions necessary to test, at simulated altitude conditions, a 40/1 NERVA II nuclear engine utilizing a self-pumping primary diffuser and an annular secondary pumping ejector.

Figure 46 shows the proposed overall system.

1. Primary Self-pumping Diffuser

a. Area of Diffuser Inlet (A_d)

Based on the engine nozzle geometry and the need for engine gimballing requirements of $\pm 1^\circ$, it will be necessary to have a minimum inlet diameter of 135 inches.

Figure 45
 Increase in Secondary Pressure Ratio
 Necessary to Improve Performance
 of Secondary Ejector as System Ω is Increased

NOZZLE DIMENSIONS

$$A^* = 246 \text{ in}^2 - D^* = 17.7 \text{ in}$$

$$A_0 = 9850 \text{ in}^2 - D_0 = 112 \text{ in}$$

$$\epsilon = 40:1$$

CONTOURED NOZZLE

$$m_p = 2.01$$

$$\gamma = 1.4$$

$\pm 1^\circ$ GIMBALLING

ENGINE P_c vs T_c (REFER TO FIGURE B-2)

$$\frac{L_T}{D_T} = \frac{416}{104} = 4$$

$$\frac{L_{SD}}{D_{SD}} = \frac{1050}{175} = 6$$

$$\frac{A_{SD}}{A_{pe}} = 1.8$$

Figure 46
Proposed NERVA II Test Facility
82

$$A_d = 14350 \text{ in.}^2$$

b. Inlet to Diffuser Spacing S_d

Because of the need to restrict the height of the primary duct to a minimum, it was decided to begin the second throat contraction with no inlet straight section ($S_d = 0$).

c. Contraction Ratio $\frac{A_d}{A_t}$

(1) The diffuser inlet area ratio is

$$\frac{A_d}{A_p^*} = \frac{14350}{246} = 58.3$$

(2) From Figure 36 for $\frac{A_d}{A_p^*} = 58.3$ and a bell nozzle, the maximum contraction ratio equals 1.72.

$$(3) A_t = \frac{A_d}{1.72}$$

$$A_t = \frac{14350}{1.72} = 8350 \text{ in.}^2$$

$$D_t = 104 \text{ in.}$$

(4) The diffuser-throat to nozzle throat area ratio is

$$\frac{A_t}{A_p^*} = \frac{8350}{246} = 33.8.$$

(5) From Figure 37, $\frac{A_t}{A_p^*} = 33.8$, the minimum starting pressure is 27 atm.

(6) Because of height restrictions, the maximum contraction angle of 10° is utilized.

d. Length of Second Throat L_t

(1) The necessary height to allow an optimum length of the second throat would be 832 inches. This height plus the diffuser section and 90° turn would prove to be uneconomical. A compromise length of 416 inches was chosen. This would increase the starting chamber pressure ratio by 30%.

$$(2) \text{ Figure 38, at } \frac{L_t}{D_t} \text{ of } 4 \left(\frac{P_c/P_a}{P_c/P_a} \right)_{\text{start}} = 1.3$$

optimum

(3) The actual starting pressure ratio for the proposed system = $(1.3)(27) = 35 \text{ atm.}$

e. 90° Turn

The maximum elbow diffuser angle of $\beta = 8^\circ$ is utilized in order to maintain the total height of the duct at a minimum.

The elbow diffuser area ratio $\left(\frac{A_1}{A_t} \right)$ of 2.5 is selected in order to maintain a maximum Mach number of approximately 0.3 in the elbow.

$$D_1 = \sqrt{2.5 D_t}$$

$$D_1 = 165''$$

A restriction section, $D = 115$ inches, is utilized prior to the primary duct exit area. The gas attains a sonic condition at the restriction and prevents the shock structure located in the second throat from extending into the elbow when the nozzle chamber pressure is increased past the starting pressure.

A value of 1.5 is selected for the elbow-radius to elbow-diameter

$$\left(\frac{R_1}{D_1}\right)$$

$$R_1 = 1.5 D_1$$

$$R_1 = 1.5(165) = 245"$$

2. Secondary Ejector System

Following are the limitations on the secondary system

$$T_{sc} = 1650^\circ R$$

$$\text{Max } P_{sc} = 150 \text{ psia}$$

$$\text{Mol. Wgt} = 20.2$$

$$\gamma = 1.2$$

- a. Secondary Duct to Primary Duct Area Ratio, $\frac{A_{sd}}{A_{pe}}$

A value of secondary duct area to primary duct area of 1.82 is selected.

The reason for selecting a value slightly higher than recommended in the previous design section is to offset the slight degradation in performance that will be realized by shortening the length of the secondary mixing duct to $\frac{L_{sd}}{D_{sd}} = 6.0$.

$$\frac{A_{sd}}{A_{pe}} = 1.8$$

$$D_{ds} = D_{pe} (\sqrt{1.8})$$

$$D_{sd} = 130 (1.34)$$

$$D_{sd} = 175 \text{ in.}$$

b. Secondary Area Ratio

(1) From Figure 42 at, $\frac{P_{sc}}{P_a} = \frac{150}{12.8} = 11.7 \text{ atm}$, the necessary secondary area ratio $\frac{A_{sd}}{A^*_s} = 18.5$; this value is from curve, total to static normal shock theory of $\gamma = 1.2$.

$$(2) A_{sd} = \frac{\pi D^2}{4} = \frac{3.14(175)^2}{4} = 2.4 \times 10^4 \text{ in.}^2$$

$$(3) A^*_s = \frac{2.4 \times 10^4}{18.5} = 1300 \text{ in.}^2$$

(4) Flow Rate of Secondary from Choked Flow

$$\frac{\dot{w} \sqrt{T_{sc}}}{A^*_s P_{sc}} = \sqrt{\frac{\gamma g_m}{1545} \left(\frac{2}{\gamma+1} \right) \frac{\gamma+1}{\gamma-1}}$$

$$\frac{\dot{w}_s \sqrt{1650}}{(1300)(150)} = \sqrt{\frac{(1.2)(32.2)(20.2)}{1545} \left[\frac{2}{2.2} \right]^{\frac{2.2}{.2}}}$$

$$\dot{w}_s = 2050 \text{ */sec}$$

$$c. \quad \frac{L_{sd}}{D_{sd}}$$

A value of 1050 inches was selected for the length of the mixing duct. The $\frac{L_{sd}}{D_{sd}} = 6$ will cause a slight degradation in performance which is offset by the slightly larger value of $\frac{A_{md}}{A^*_s}$ as selected in the previous Section a.

d. Primary Duct Exit Pressure Determination (P_{pe})

(1) Choose a value of P_c from engine map. (Figure 47)

$$(a) \quad P_c = 50 \text{ psia}$$

$$T_c = 700^\circ R$$

$$(b) \quad \frac{\dot{w}_{prim} \sqrt{T_c}}{A^*_p P_c} = \frac{\gamma_g M_p}{1545} \left(\frac{2}{\gamma+1} \right)^{\frac{\gamma+1}{\gamma-1}}$$

$$\frac{\dot{w}_{prim} \sqrt{700}}{(246)(50)} = \sqrt{\frac{(1.4)(32.2)(2.01)}{1545}} \left(\frac{2}{2.4} \right)^{\frac{2.4}{.4}}$$

$$\frac{\dot{w}_{prim} \sqrt{700}}{(246)(50)} = 0.1405$$

$$\dot{w}_{prim} = 65.2 \text{ lb/sec}$$

$$(c) \quad \Omega = \sqrt{\frac{T_{cp}}{M_p} \frac{T_{sc}}{M_s}} = \sqrt{\frac{700}{2.01} \frac{1650}{20.2}} = 2.07$$

Figure 47
Proposed NERVA II Engine Performance
 P_c vs T_c
88

$$(d) \quad \chi = \frac{\dot{w}_p}{\dot{w}_s} = 2.07 \left(\frac{65.2}{2050} \right) = 0.0658$$

$$(e) \quad \text{From Figure 43} \quad \frac{P_{pe}}{P_a} = 0.16$$

$$P_{pe} = (.16)(12.8) = 2.05$$

$$(f) \quad \text{This would be the exit pressure if the system } \frac{A_{sd}}{A_s^*} = 20.$$

$$\text{From Figure 44, the equivalent pressure for } \frac{A_{sd}}{A_s^*} = 15.5.$$

$$P_{pe} = 2.05 \left(\frac{20.0}{15.5} \right)^{1/3} = 2.10 \text{ psia}$$

$$(g) \quad \frac{P_c}{P_{pe}} = \frac{50}{2.1} = 23.8 < 35$$

$\therefore$ system has not started

(2) Choose higher value of P_c

$$(a) \quad P_c = 100 \text{ psia}$$

$$T_c = 1300^\circ\text{R}$$

$$(b) \quad \frac{\dot{w}_{\text{prim}} \sqrt{T_c}}{A_p^* P_c} = .1405$$

$$\dot{w}_{\text{prim}} = \frac{.1405 (246)(100)}{\sqrt{1300}} = 96 \text{ lb/sec}$$

$$(c) \quad \Omega = \sqrt{\frac{T_{cp}/M_p}{T_{cs}/M_s}} = \sqrt{\frac{1300/2}{1650/20.2}} = 2.82$$

$$(d) \quad \chi = \Omega \frac{\dot{w}_p}{\dot{w}_s} = 2.82 \frac{96}{2050} = 0.132$$

$$(e) \quad \text{From Figure 43} \quad \frac{P_{pe}}{P_a} = 0.21$$

$$P_{pe} = (.21)(12.8) = 2.68 \text{ psia}$$

(f) From Figure 44, the equivalent pressure of a system with an area ratio = 18.5

$$P_{pe} = 2.68 \left(\frac{20}{18.5}\right)^{1/3} = 2.75$$

$$(g) \quad \frac{P_c}{P_{pe}} = \frac{100}{2.75} = 36.3 > 35 \quad \begin{array}{l} \text{the engine system is} \\ \text{started at approximately} \\ P_c = 100 \text{ psia} \end{array}$$

VI. CONCLUSIONS AND RECOMMENDATION

Two basic types of secondary ejectors have been studied to determine their relative merits and to predict their performance. The centerbody nozzle ejector and the annular nozzle ejector were the two types studied.

It is recommended that whenever possible, consistent with the structural integrity of the proposed system that the centerbody nozzle ejector be utilized. The supersonic stream is buried in the subsonic stream from the diffuser and not along the duct wall as is the case of the annular ejector. This provides lower shearing losses for the centerbody system and subsequent gains in performance. The reports by Fabri, Chow and Addy and the Princeton report (Ref 1, 2 and 3) present methods to predict performance which are relatively straightforward because of the applicability of the one-dimensional flow assumptions.

However, in the case of Nuclear Exhaust Systems where heat transfer, plate out and high reliability problems prevent the use of a centerbody nozzle ejector, it is necessary to use an annular nozzle secondary system. With the method, as presented in the Design Section and Quasi one-dimensional ejector theory by Princeton (Report No. AG-14), it is possible to predict the performance of an annular ejector system.

References

1. Fabri, J. and Paulon, J. "Theory and Experiments on Supersonic Air to Air Ejectors NACA TM-1410, September 1958.
2. Chow, W. L. and Addy, A. L. "Interaction Between Primary and Secondary Streams of Supersonic Ejector Systems and Their Performance Characteristics" AIAA - Journal Volume 2, No. 4, April 1964
3. Theoretical and Experimental Investigations of the Mixing of a Supersonic Stream With an Induced Secondary Stream as Applied to Ducted Propulsive Devices, Project SQUID Technical Report No. 25, Princeton University 1950, Part I.
4. REON Report No. RN-DR-0038 "A Heat Transfer Investigation of Ejector Systems With 90° Turns"
5. Grey, J. "Analytical Evaluation of Generalized NES Ejector Characteristics Based on Scale Model Tests." Report No. AG-14, Princeton, September 1965.
6. Layton, J. P. "Quasi-One-Dimensional Primary Ejector Analysis with Wall Pressure, Friction and Heat Transfer Effects." Contract SNP-1 Report, Princeton, September 1965.

APPENDIX A

PREDICTION OF EJECTOR SYSTEM PERFORMANCE

I. INTRODUCTION

Prediction of the performance of ejector systems has largely been done through the use of "rule of thumb" methods where a normal shock is assumed to exist somewhere in the ejector system. These "rule of thumb" methods leave much to be desired in evaluating ejector performance since they do not consider the actual ejector geometry, nor the actual shock structure that exists within the ejector. The complicated shock structure within the ejector is extremely difficult to analyze, but the behavior of the ejector system near the "start" point of the system depends only on the shock structure near the nozzle and consequently is simpler to analyze. The analysis presented in the first section of this appendix will deal with this region where the importance of the shock structure has been minimized to the point that only the first shock needs to be considered.

When an ejector has just "started" (i.e. the rocket nozzle is flowing full) and supersonic flow exists only near the ejector inlet with subsonic flow existing throughout the rest of the ejector system, the shock structure exists for only a portion of the ejector length. The remaining portion of the flow process is therefore in the subsonic region and can be easily analyzed. Under these conditions, the ejector system can be analyzed on the basis of a mass and momentum balance, and the system losses used to predict the behavior of the ejector system. In this way, the effects of the rocket nozzle performance, ejector contraction ratio, ejector area ratio, and the ejector exit area ratio are incorporated directly into the analysis. Because of a simplified treatment of the subsonic flow process, the effects of the length-to-diameter ratio of the ejector system are valid for lengths beyond the optimum.

II. ANALYSIS

This analysis will consider a generalized ejector system as illustrated in Figure 48. This ejector system is characterized by a nozzle of area ratio ϵ_{pe} (all area ratios are referenced to the nozzle throat), an ejector inlet area ratio ϵ_{di} , a contraction section of angle b , an ejector second throat area ratio ϵ_{ds} , and an ejector exit area ratio ϵ_{de} . The pressures of interest for this analysis are the nozzle compartment pressure P_v , the pressure that exists after the first shock in the ejector P_s , and the ejector system exit ambient pressure P_{de} . The nozzle compartment pressure and the ejector exit ambient pressure define the pressure ratio across the ejector, and consequently define the work requirements of the system, while the pressure after the first shock defines one part of the losses in the ejector system.

When the ejector system shown in Figure 48 has just started, the gas flow fills the nozzle and ejector inlet and reduces the nozzle compartment pressure to a value slightly less than the expanding of the gas to the ejector inlet area ratio. Since this pressure need only be known approximately, in the analysis of the ejector system it will be assumed that the nozzle compartment pressure is the pressure corresponding to the ejector inlet area ratio, ϵ_{di} .

$$\epsilon_v = \epsilon_{di} \quad (1)$$

Since the nozzle is assumed to be flowing full, the thrust of the nozzle can be exposed in terms of the vacuum thrust of the nozzle as follows:

$$F = P_{pc} A_p^* (C_{f \text{ vac}} - \epsilon_{pe} \frac{P_v}{P_{pc}}) \quad (2)$$

Figure 48
Flow Schematic of Ejector System
95

where

F	=	thrust
P_{pc}	=	engine chamber pressure
A_p^*	=	nozzle throat area
$C_{f_{vac}}$	=	nozzle thrust coefficient referenced to vacuum
ϵ_{pe}	=	nozzle area ratio
P_v	=	engine compartment pressure

The majority of the frictional losses at this point of ejector operation will occur in the second throat region so that the appropriate locations for a momentum balance are the ejector inlet (Station 1) and the second throat exit (Station 2). Some losses will occur between the second throat exit and the ejector exit (Station 3), but these losses will generally be quite small (owing to the low Mach number conditions through this region) and will be neglected in this analysis. The losses in the ejector can be separated into two parts; the first being the frictional losses which will be based on the flow conditions at the second throat exit, and the second being the pressure force on the contraction section of the ejector which will be based on the pressure ratio across an oblique shock.

At the ejector inlet the nozzle exhaust gases impinge on the ejector wall and are turned through a deflection angle approximately equal to the nozzle exit divergence angle plus the ejector contraction angle. This causes a shock to occur at a wave angle d , and produces the corresponding pressure rise in the exhaust gases. To estimate this effect, this analysis assumes that the flow is equivalent to flow over a wedge and that the deflection angle is the sum of the nozzle exit divergence angle and the ejector contraction angle. The pressure on the wall in the contraction section of the ejector is then constant and equal to the pressure downstream of an oblique shock of wave angle d . The angle d is found from the ejector inlet Mach number and turning angle. These relationships have been combined in Figure 49 to show the pressure ratio, C_p , across the shock as a function of area ratio for several turning angles for a gas with a specific heat ratio (γ) of 1.4.

Figure 49
Pressure Ratio Across an Oblique Shock
as a Function of Area Ratio

A momentum balance can now be written between the ejector inlet and the second throat exit.

$$F + P_v(A_{di} - A_{pe}) = 4C_f \frac{L}{D}_{ds} A_{ds} \frac{\gamma}{2} P_{ds} M_{ds}^2 + C_r P_{di} (A_{di} - A_{ds}) + P_{ds} A_{ds} (1 + \gamma M_{ds}^2) \quad (3)$$

where

- A_{di} = ejector inlet area
- A_{pe} = nozzle exit area
- C_f = coefficient of friction
- $(L/D)_{ds}$ = second throat length to diameter ratio
- A_{ds} = second throat area
- P_{ds} = static pressures at second throat exit
- M_{ds} = Mach number at second throat exit
- P_{di} = static pressures at ejector inlet

The pressure and Mach number at the second throat exit are unknown but can be determined by reference to the ejector exit conditions. At the start point of the ejector system, the Mach number at the ejector exit M_{de} will be small and the static pressure of the gases can be assumed to be equal to the ambient pressure surrounding the ejector. The ejector exit Mach number can, therefore, be determined directly from a mass balance, and can be stated as follows

$$\gamma M_{de}^2 = \frac{\gamma}{\gamma-1} \left\{ \left[1 + \frac{2(\gamma-1)}{\epsilon_{de}^2} \left(\frac{2}{\gamma+1} \right)^{\frac{\gamma+1}{\gamma-1}} \left(\frac{P_{pc}}{P_{de}} \right)^2 \right]^{1/2} - 1 \right\} \quad (4)$$

where

- ϵ_{de} = ejector exit area ratio
- P_{de} = static pressure at ejector exit

Once the exit Mach number has been computed, the assumption of zero losses between the second throat exit and the ejector exit allows the Mach number at the second throat exit to be computed from the isentropic relationship between the stream Mach number and the flow area ratio.

$$\frac{\gamma_{ds} M_{ds}^2}{\left(1 + \frac{\gamma-1}{2} M_{ds}^2\right)^{\frac{\gamma+1}{\gamma-1}}} = \frac{\epsilon_{de}^2}{\epsilon_{ds}^2} \frac{\gamma_{de} M_{de}^2}{\left(1 + \frac{\gamma-1}{2} M_{de}^2\right)^{\frac{\gamma+1}{\gamma-1}}} \quad (5)$$

The pressure at the second throat exit can be estimated from the known exit pressure, P_{de} , and the Mach numbers at the two stations, again using the assumption of zero losses between the two points. The equation for P_{ds} is stated as follows:

$$P_{ds} = \frac{\left(\frac{P_{ds}}{P_{ds_t}}\right)}{\left(\frac{P_{de}}{P_{de_i}}\right)} P_{de} = P_{de} \frac{\left(1 + \frac{\gamma-1}{2} M_{de}^2\right)^{\frac{\gamma}{\gamma-1}}}{\left(1 + \frac{\gamma-1}{2} M_{ds}^2\right)^{\frac{\gamma}{\gamma-1}}} \quad (6)$$

All the terms in the momentum balance between Stations 1 and 2 have not been defined and can be substituted into Equation 3. A convenient way to express the terms is as functions of area ratios, so that Equation 3 is divided by the product $P_{pc} A_p^*$ before substitution of the terms. The method of solution will be to solve for the coefficient of friction, C_f , in terms of the ejector variables. This leads to the following equation.

$$C_{f_{vac}} = \frac{-\frac{P_v}{P_{pc}} (2 \epsilon_{pe} - \epsilon_{di}) - C_r \frac{P_{di}}{P_{pc}} (\epsilon_{di} - \epsilon_{ds}) - \frac{P_{de}}{P_{pc}} \epsilon_{ds} \left(1 + \gamma M_{ds}^2\right) \frac{\left(1 + \frac{\gamma-1}{2} M_{dc}^2\right)^{\frac{\gamma}{\gamma-1}}}{\left(1 + \frac{\gamma-1}{2} M_{dc}^2\right)^{\frac{\gamma}{\gamma-1}}}}{2 \gamma \epsilon_{ds} \frac{L}{D} ds \frac{P_{de}}{P_{pc}} M_{ds}^2 \frac{\left(1 + \frac{\gamma-1}{2} M_{de}^2\right)^{\frac{\gamma}{\gamma-1}}}{\left(1 + \frac{\gamma-1}{2} M_{ds}^2\right)^{\frac{\gamma}{\gamma-1}}}} \quad (7)$$

The predicted performance of the subsonic turn configuration is shown in Figure 50 as a function of the exit area ratio. It can be seen that a definite penalty is incurred for values of $\epsilon_{de} < 20$, which is in good agreement with the observed performance.

Equation 7 gives the value of the coefficient of friction required to conserve momentum through the ejector system and is the basic tool developed by this analysis for evaluating the performance of an ejector system. Equation 7 is used to compute curves of C_f versus the pressure ratio P_{pc}/P_{de} , and the point of agreement with the conventional C_f relationships, found graphically or by inspection, establishes the starting pressure ratio P_{pc}/P_{de} . For values of C_f greater than this value, the ejector system has started, while for values less than this value the system cannot maintain the pressure ratio and separated flow will occur in the ejector system.

NOTES:

1. NOZZLE = 25:1 CONICAL
2. INLET TO NOZZLE THROAT AREA RATIO = 33.2:1
3. CONTRACTION RATIO = 1.66
4. $C_f = 0.010$; $\frac{P_v}{P_{pc}} = 0.0015$; $\frac{L}{D} = 8.09$

5.

Symbol	Remarks
⊙	Subscale Testing
X	Analysis

Figure 50
The Effect of Exit Area Ratio on Ejector Performance
101

BIBLIOGRAPHY OF EJECTOR SYSTEMS

NON-PUMPING EJECTOR SYSTEMS

1. Boorady, F. A., Experimental Results from Simulated Altitude Testing of the Bell-Agena Rocket Engine, ARS Paper 1665-61, March 1961.
2. Chamberlain, John and Robert Olsen, Development of an Exhaust Diffuser for Ground Testing Rocket Engines, Progress in Astronautics and Rocketry, Vol. 2, Academic Press, New York, 1960.
3. Deleo, R. V., R. F. Rose, R. S. Dart, An Experimental Investigation of the Use of Supersonic Driving Jets for Ejector Pumps, ASME Paper 61-Hyd-15, 1961.
4. Fabri, J. and J. Paulon, Theory and Experiments on Supersonics Air to Air Ejectors, NACA TM 1410, 1958.
5. Fortini, Anthony, Performance Investigation of a Non-Pumping Rocket Ejector System for Altitude Simulation, NASA TN-D-275, 1960.
6. German, R., Zero Secondary Flow Ejector Diffuser Performance Using Annular Nozzles, Arnold Engineering Development Center Report A-28-RW-2141, January 1963.
7. German, R. C. and R. C. Bauer, Effects of Diffuser Length on the Performance of Ejectors Without Induced Flow, AEDC TN-61-89, 1961.
8. Goethert, Bernard H., High Altitude and Space Simulation Testing, ARS Journal, June 1962.
9. Holzman, Allan, Sanford Tick and Ernest Hink, Summary of Experience in the Use of Exhaust Diffusers for Rocket Testing, Progress in Aeronautics and Rocketry, Vol. 2, Academic Press, New York, 1960.
10. Howell, R. T., Experimental Operating Performance of a Single Stage Annular Air Ejector, NASA TN-D 23, 1959.
11. Ilsen, V., A Large Rocket Ejector System, Progress in Astronautics and Rocketry, Vol. 2, Academic Press, New York, 1960.
12. Ilsen, V., Experimental Simulation of High Altitude by Cylindrical Ejector Systems, AGC Report TCR 185, 10 June 1960.
13. Johanneson, N. H., Ejector Theory and Experiments, ATS No. 1, Trans. Danish Academy of Technical Sciences (Copenhagen), 1951.
14. Jones, William Harold Price and Carl Lorenzo, Experimental Study of Zero-Flow Ejectors Using Gaseous Nitrogen, NASA TN-D 203, 1960.

15. Kumm, E. L., J. Friedman, I. A. Kanarek, Ejector Performance, Report AL-793, North American Aviation, Aerophysics Laboratory, 1949.
16. Lightner, I. C., Altitude Facility Rocket Testing, ARS Paper No. 996-59, 1959.
17. Mandell, Bernard, Gary O. Patmor, Cold Flow Testing Program for Test Cell "D" Exhaust System, Aerojet-General Report No. 2129, November 1961.
18. Mandell, Bernard, B. L. McFarland, R. E. Nelson, G. O. Patmor, Theoretical and Experimental Evaluation of Test Cell "D" Ejector Systems, Aerojet-General Report No. 2309, August 1962.
19. Marshall, J. W., R. H. Mickola, System Design Considerations for Testing of Rocket Engine Altitude, ARS Paper 1664-61, March 1961.
20. Massier, Paul F., and E. John Roschke, Experimental Investigation of Exhaust Diffusers for Rocket Engines, Progress in Astronautics and Rocketry, Vol. 2, Academic Press, New York, 1960.
21. q Nelson, R. E., G. O. Patmor, B. L. McFarland, B. Mandell, Scale Model Testing of 90° Supersonic Turn Ejector Systems for Altitude Simulation, AIAA Report No. 63-174, 1963.
22. Nelson, R. E., G. O. Patmor, B. L. McFarland, B. Mandell, Scale Model Testing of 90° Supersonic Turn Ejector Systems for Altitude Simulation, Journal of Spacecraft and Rockets, January 1964.
23. Povolney, John H., Use of Choked Nozzle Technique and Exhaust Jet Diffuser for Extending Operable Range of Jet Engine Research Facilities, NASA TM E-52 E12, 1952.
24. Rao, G. V. R., Short Diffuser for Testing Rocket Nozzles, Progress in Astronautics and Rocketry, Vol. 2, Academic Press, New York, 1960.
25. Roschke, E. J., P. F. Mussier, H. L. Gier, Experimental Investigation of Exhaust Diffusers for Rocket Engines, Technical Report No. 32-210, Jet Propulsion Laboratory, Cal Tech, Pasadena, California, 1962.
26. Siva, Joseph N., Carol L. Meyer, Daniel J. Peters, Experimental Evaluation of Rocket Exhaust Diffusers for Altitude Simulation, NASA TN-D 298, 1960.
27. Smith, L. P., L. A. Joy, High Altitude Simulation Testing, American Rocket Society Report, 1663-61.
28. Smith, R. E., D. Taylor, Performance of Single-Stage and Two-Stage Exhaust Ejector-Diffusers at Steady-State Conditions, Symposium Proceedings Vol. II, June 28-29, 1961, Rocket Testing in Simulated Space and High Altitude Environments (Confidential)

29. Syoberg, T., C. Kastner, S. Tuck, Altitude Simulation for Rocket Power-plant Testing, Report RMD 352-F, Thiokol Chemical Corporation, Reaction Motors Division, 1960.
30. Taylor, D., D. L. Barton, M. Simmons, An Investigation of Cylindrical Ejectors Equipped with Truncated Conical Inlets, Arnold Engineering Development Center, Report TN 60-221, March 1961.
31. Waitman, B. A., L. R. Reneau, S. J. Kline, Effects of Inlet Conditions on Performance of Two-Dimensional Subsonic Diffusers, ASME Paper 60-WA-143, 1960.
32. Wilcox, F. A., H. E. Bloomer, Handling Rocket Exhaust Products in Altitude Facilities, Symposium Proceedings (Rocket Testing in Simulated Space and High Altitude Environments), Arnold Engineering Development Center, October 1961 (Confidential).
33. Wood, Richard, Theoretical Ejector Performance and Comparison with Experimental Results, TR 54-556, WADC, 1954.
34. Analytical and Experimental Evaluation of Ejectors with 90° Turn for Use in Engine Test Stand No. 1, Aerojet-General Report No. 2403, November 1962.
35. Analytical and Experimental Evaluation of 90° Subsonic Turn Ejector Systems for Use at ETS-1, Aerojet-General Report No. 2679, October 1963.
36. AEDC Test Facilities Handbook, Supplement No. 1, Arnold Engineering Development Center, Tullahoma, Tennessee, 1959.
37. An Investigation of Ejectors Without Induced Flow, Phase I, AEDC Technical Note 59-145, 1949.

BIBLIOGRAPHY OF EJECTOR SYSTEMS

PUMPING EJECTOR SYSTEMS

1. Analytical and Experimental Evaluation of Ejectors with 90° Turn for Use in Engine Test Stand No. 1, Aerojet-General Report No. 2403, November 1962.
2. Constant Area Mixing of Non-Isoenergetic Coaxial Compressible Streams, C. E. Peters and S. Wehofer, U. S. Air Force, Arnold Engineering Development Center, January 1962.
3. Mixing of Compressible Fluids, General Applied Sciences Laboratory, ASME Paper 61-APMW-3 1960.
4. Momentum and Mass Transfer in Coaxial Gas Jets, W. Forstall Jr., and A. H. Shapiro, Massachusetts Institute of Technology, 1949.
5. Operating Characteristics of Jet Pump Using Gaseous Primary and Secondary Streams, Arnberg, B. T., University of Colorado, Boulder, Colorado, Engineering Experiment Station, 1958.
6. Theoretical and Experimental Investigations of the Mixing of Supersonic Stream With an Induced Secondary Stream As Applied to Ducted Propulsive Devices, Project SQUID Technical Report No. 25, Princeton University 1950 Part I.