01A

BNWL-1856
Special
Distribution

SNS SOURCE TERM EVALUATION PROGRAM

Battelle

Pacific Northwest Laboratories
Richland, Washington 99352

AUGUST 1974

Prepared for the U.S. Atomic Energy
Commission under Contract AT(45-1):1830

BNWL-1856

NOTICE

The report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

PACIFIC NORTHWEST LABORATORY
operated by
BATTELLE
for the
U.S. ATOMIC ENERGY COMMISSION
Under Contract AT(45-1)-1830

Printed in the United States of America
Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, Virginia 22151
Price: Printed Copy \$4.00; Microfiche \$1.45

3 3679 00062 2300

BNWL-1856
Special
Distribution

SNS SOURCE TERM EVALUATION PROGRAM

Annual Report

D. K. Craig, W. C. Cannon, R. E. Filipy, D. D. Mahlum and V. H. Smith

August 1974

Battelle
Pacific Northwest Laboratories
Richland, WA 99352

CONTENTS

SUMMARY	1
INTRODUCTION.	2
PROGRESS DURING FY 1974 AND PLANS FOR FY 1975	5
SPECIAL DISTRIBUTION.	28

LIST OF FIGURES

1. Rate of Soil Deposition for Soil #1	12
2. Rate of Soil Deposition for Soil #2	13
3. Rate of Plutonium Activity Deposition for Soil #1	15
4. Rate of Plutonium Activity Deposition for Soil #2	16

LIST OF TABLES

1.	$^{238}\text{PuO}_2$ Suspended in Air at 125 cm from the Generator	11
2.	Mass Ratio ($\times 10^{-4}$) of Soil to $^{238}\text{PuO}_2$	11
3.	Alpha Activity in Organs of Sea Cucumbers After Exposure to PPO in Sea Water ¹	20
4.	Relationships Between ^{238}Pu Activity in Selected Samples. . . .	22
5.	Alpha Activity in Sand Samples Taken from the Center and Periphery of Each of the PPO Solubility Test Vessels	24

SUMMARY

Work on the SNS Source Term Evaluation Program during FY 1974 has included the following:

Task 1 - Aerosol Experimental Studies

- Generation and characterization of aerosols of soil, $^{238}\text{PuO}_2$, and soil + $^{238}\text{PuO}_2$.
- Development of aerosol sampling techniques.
- Study of the effects of wind speed upon aerosol properties.

Task 2 - Marine Animal Studies

- Marine organisms caged with $^{238}\text{PuO}_2$ fuel pellets 60 feet under the ocean surface radiochemically analyzed and plutonium isotope ratios determined.
- Experiment designed to determine ultrafilterability of $^{238}\text{PuO}_2$ as a function of concentration, temperature, solvent pH and time following preparation of suspension.

Task 3 - Hot Particle Studies

- Calculated values of skin and respiratory deposition of plutonium aerosols compared to experimentally determined values.
- Computer program tested for application to estimating thermal characteristics of ^{238}Pu oxide deposition on skin.

Task 4 - Mathematical Modeling

- Tissue analysis of data for plutonium oxide-exposed dogs is being evaluated to determine applicability of $^{239}\text{PuO}_2$ data to $^{238}\text{PuO}_2$ retention parameters.

INTRODUCTION

^{238}Pu is currently being used in the form of a pure refractory oxide as a power source on a number of space vehicles that have already been or will be launched during the next few years. Although the sources are designed and built to withstand re-entry into the earth's atmosphere and impact with the earth's surface without releasing any plutonium, the possibility of such an event can never be absolutely excluded. Should the capsule fall into the ocean, the corrosive effect of salt waters must be considered. On land, in addition to the possibility of an immediate release from a fractured capsule, the long-term effects of thermal and humidity cycling must be considered. Should $^{238}\text{PuO}_2$ become mixed in a finely divided form with soil, the resuspension characteristics of the plutonium in conjunction with the soil and the subsequent aerodynamic behavior of the aerosols will be major factors in determination of the fate of the plutonium in the environment.

Thus a range of factors is involved in air analysis of the hazards of plutonium-238 released from SNS power sources. The work to be described in this report was undertaken primarily because of the long experience of the Biology Department of the Pacific Northwest Laboratories in the conduct of biological experiments with plutonium compounds. These included the conduct of plutonium aerosol inhalation exposures of animals involving aerosol generation, sampling and characterization, followed by the radiochemical, autoradiographic and other analysis of biological and other samples for plutonium. In addition, a facility was available which permitted study of interactions between plutonium aerosols and aerosols

derived from soil samples. Also available was a large body of biological data from small and large animals exposed to $^{238}\text{PuO}_2$ and $^{239}\text{PuO}_2$ aerosols over a number of years. These data serve as the base for the computer modeling work that has been conducted for the purpose of developing predictive dose and hazard estimates for possible future exposure of humans to plutonium aerosols.

The objectives of the present study are confined to four specific tasks:

Task 1 - Aerosol Experimental Studies, which concern interactions between soils and $^{238}\text{PuO}_2$ aerosols which might be created in a space launch abort environment. The specific problem to be solved, analytically and experimentally, is the degree to which the plutonium aerosol source term might be modified in a terrestrial environment and, also, determination of feasibility of using soil-plutonium aggregates in animal inhalation studies;

Task 2 - Marine Animal Studies, which concern support activities for the SNS underwater experiments at the Navy Undersea Center, including assistance with their technical planning. In vitro solubility tests of $^{238}\text{PuO}_2$ as a function of time, temperature, suspension concentration and molality of solvent are also included in this task, but have not progressed beyond the planning stage;

Task 3 - Hot Particle Studies, which concern development of a plan in consultation with SNS for possible animal experiments in cooperation with DBER, to evaluate $^{238}\text{PuO}_2$ hot particle effects;

Task 4 - Mathematical Modeling, which concerns support of the SNS safety effort to standardize analytical techniques for system risk analysis. This task includes a commitment to review and comment upon the Overall Safety

Manual (OSM) expected to be available during FY 1975.

This report describes the progress made during FY 1974, the first year of this project, on each of the above tasks. Plans for FY 1975 are also discussed where appropriate.

PROGRESS DURING FY 1974 AND PLANS FOR FY 1975Task 1 - Aerosol Experimental Studies

The scope of the work on this task during FY 1974 has been to co-generate soil aerosols and $^{238}\text{PuO}_2$ aerosols in a low-speed wind tunnel facility, and to study the effects of interaction of the two aerosols upon the transport of $^{238}\text{PuO}_2$ at various wind speeds. A section of this report will be devoted to a discussion of the materials generated and the aerosol generation methods used. Certain special sampling systems have been used and are discussed. A series of tests have been performed with a combination of $^{238}\text{PuO}_2$ aerosols and aerosols of four different soil types. The conducting of these tests, the analytical methods used and some experimental results are also presented. Finally, a brief outline of the plans for FY 1975 will be presented.

Section 1 - Materials Handling and Aerosols Generation

$^{238}\text{PuO}_2$, Pure Plutonium Oxide (PPO), supplied by Los Alamos Scientific Laboratories, was screened to a maximum size of 10 μm before packing into a steel container and sealed for shipment. The material was removed from the container, portions weighed, and mixed with distilled water in a dry-filmed generator jar approximately one hour before beginning aerosol generation. The generator jar containing the water-PPO mixture was placed in an ultrasonic cleaner for one-half hour just prior to generation.

Aerosol generation of the $^{238}\text{PuO}_2$ was accomplished by nebulization of the aqueous suspension using a Retec PN 7002 aerosol generator. The particles were dried by passing them through a heated tube before injection

into the wind tunnel. The suspension was magnetically stirred in the generator jar during generation.

This treatment of the suspension does not appear to have been adequate for this material since much of the material soon settled to the bottom of the generator jar. Suspensions appeared cloudy immediately following ultrasonic treatment but within approximately one-half hour they were noticeably clearer even with continuous stirring. The activity injected into the wind tunnel appears to have been 10% or less of the activity which should have been generated. The intended soil-to- $^{238}\text{PuO}_2$ mass ratio was 1000:1 but the actual ratio was from 50,000:1 to 125,000:1.

A surfactant (sodium lignin sulphonate) was added to the suspensions but did not appear to be effective in keeping the particles in suspension.

Further work is required on the $^{238}\text{PuO}_2$ generation to improve the efficiency and to achieve the desired concentrations. Even more important than the actual value of aerosol concentration is that it be steady and predictable. Several methods are being considered to achieve this:

1. Prolonging ultrasonic treatment and continuation of treatment during generation may help to break up agglomerates and prevent agglomerate formation.
2. A non-aqueous suspension of $^{238}\text{PuO}_2$ may allow longer ultrasonic treatment (the tendency of the material to react with water is more pronounced with $^{238}\text{PuO}_2$ than with $^{239}\text{PuO}_2$).
3. Surfactants other than sodium lignin sulphonate may prove more effective.
4. Another type of liquid generator may be more effective with this material.

5. Dry aerosol generation is also a possible approach.

The soil aerosols were all generated by means of the Wright Dust Feed Mechanism, using the same gear ratio for all soils. The pressure used to pack soil into the dust container and the generator air flow was varied to accommodate the different soil types. The generator mass output rate varied from 73 mg/min to 86 mg/min for the different soils.

The soils were untreated except for breaking up larger pieces and screening through a 0.8 mm screen.

Section 2 - Instrumentation and Sample Collection

Four types of samples were collected in these studies:

1. Filter paper samples for determination of aerosol concentration and for autoradiographic observation.
2. Cascade impactor samples for determining aerosol particle size distributions.
3. Sedimentation samples for determining the deposition pattern of materials on the tunnel floor.
4. Electron microscope grids containing particles deposited by thermal precipitation used for visualization and possible particle size analysis.

Samplers of types 1 and 2 have been modified to provide isokinetic sampling, i.e., the air velocity at the sampler inlet must match that of the wind tunnel in magnitude and direction so that the particles are representative of those in the wind tunnel aerosols. In the filter paper samplers the size of the inlet opening and the sample air flow were arranged to make the inlet velocity equal the wind tunnel velocity. In order to achieve the proper isokinetic inlet velocity for the cascade

impactors, dilution air was added to the sample air. It is necessary to keep the total cascade impactor air flow constant in order to maintain the proper operation of the instrument. The close regulation of air flows required to maintain the proper balance between dilution air and sample air will necessitate modifications to the present air supply systems.

Sedimentation samples were collected on specially cut Whatman 41 filter disks which were placed in disposable plastic cups on the wind tunnel floor. The filter disks were predampened to enhance particle adhesion. Eleven such samplers were distributed along the longitudinal centerline of the tunnel floor to determine the deposition pattern. Lateral distributions will also be determined by future sedimentation sampler arrays. A special apparatus has been devised to collect short-term sedimentation samples for autoradiography because the regular samples were too heavily coated with particles for this purpose. Autoradiographic examinations were carried out by LFE Corporation of Richmond, CA.

There was no modification of the thermal precipitator to make it isokinetic because there is already an inherent small-particle bias in the instrument.

Section 3 - Sample Analysis

The two cascade impactors used for sample collection were:

1. Mercer Cascade impactor which collects small samples on filter disks and glass slides, which, although too small for soil analysis are useful for $^{238}\text{PuO}_2$ determination by gamma counting techniques;
and

2. Andersen 2000 Model 20-000 impactor, which collects fairly large samples which hopefully, can be used for soil analyses as well as $^{238}\text{PuO}_2$ determination.

The samples from the Andersen impactor, the filter paper samples and the sedimentation samples were subjected to the standard process of ashing away organic material and chemically digesting the remaining minerals. Aliquots of these samples were alpha-counted by scintillation in terphenyl for content, and examined for Fe and Al content by atomic absorption spectrophotometry (AA). Fe and Al content of the four soils had been previously determined for calibration. Background levels of Fe and Al in blank samples were higher than anticipated -- too high for acceptable analyses of filter paper and Andersen impactor samples. Only the sedimentation samples contained enough material to make the results of the AA analyses acceptable. The high background levels were traced, at least in part, to improper handling of the samples during the unloading and ashing processes. Steps have been taken to correct these handling errors.

Section 4 - Description of the Experiment and Discussion of Results

Tests were conducted with each type of soil without $^{238}\text{PuO}_2$ cogeneration at each of the wind speeds 0.4, 0.9, 4.5 and 22.4 cm/sec. Since we were not yet aware of the importance of sedimentation samples, only three samples were taken at the upper end of the tunnel. These were insufficient to define the deposition pattern. The one useful result of these tests was to establish that re-entrainment of activity from the tunnel walls would not seriously affect the results of tests of the combined aerosols.

Subsequent to expansion of sedimentation sampling to eleven positions, tests were conducted with $^{238}\text{PuO}_2$ aerosols, alone and in combination with

each soil type. In the most recent test, runs with $^{238}\text{PuO}_2$ alone were alternated with Soil 4 (Composite Soil) + $^{238}\text{PuO}_2$ runs, hoping to enable us to make better comparisons.

Since the $^{238}\text{PuO}_2$ generation was not consistent from day to day, nor even during a given day, it was not meaningful to compare aerosol concentrations or amounts of material deposited on the tunnel floor in tests conducted with and without soil generation. Instead the data were analyzed as follows:

1. Using sedimentation data, curves were constructed of the amounts of $^{238}\text{PuO}_2$ and of soil deposited per centimeter of tunnel bottom downstream from the generator outlets.
2. Assuming the deposition to be uniform across the tunnel floor and neglecting deposition on walls and the top of the tunnel, the total depositions per minute between the generators and the 125 cm mark were computed by graphic integration of these curves.
3. The $^{238}\text{PuO}_2$ aerosol concentrations were determined at 125 cm and were multiplied by the tunnel flow to determine the total amount of suspended $^{238}\text{PuO}_2$ at that point. (Soil aerosol concentration data were not obtained because sample results were not sufficiently above background levels).
4. The total $^{238}\text{PuO}_2$ input was taken to be the sum of suspended material at 125 cm and the floor deposition up to 125 cm.
5. The percentage of input still suspended at 125 cm was computed.

The total bottom deposition of soil agreed quite well with the known average generator output rates. The total $^{238}\text{PuO}_2$ activity was between

2% and 10% of the product of suspension concentration and generator volume output rate.

Table 1 presents the percentage of plutonium-238 activity still suspended at 125 cm downstream from the generators for each type of soil at each windspeed. Table 2 shows the actual value of soil-to- $^{238}\text{PuO}_2$ mass ratio.

TABLE 1. $^{238}\text{PuO}_2$ Suspended in Air at 125 cm from the Generator.

Test No.	Soil No.	Percent $^{238}\text{PuO}_2$ Suspended at 125 cm			
		22 ℓ /min 0.4 cm/sec	50 ℓ /min 0.9 cm/sec	250 ℓ /min 4.5 cm/sec	1250 ℓ /min 22.4 cm/sec
9	No Soil	65	92	97	99+
10	1	69	84	92	96
11	2	77	85	94	95
12	3	66	87	93	95
13	4	78	90	96	90
13A	No Soil	85	96	96	98

Soil #1 - Los Alamos Humus

Soil #2 - Coarse, Sandy

Soil #3 - Fine Clay

Soil #4 - Composite

TABLE 2. Mass Ratio ($\times 10^{-4}$) of Soil to $^{238}\text{PuO}_2$

Test No.	Soil No.	22 ℓ /min 0.4 cm/sec	50 ℓ /min 0.9 cm/sec	250 ℓ /min 4.5 cm/sec	1250 ℓ /min 22.4 cm/sec
10	1	5.9	6.4	12.8	7.1
11	2	5.3	4.2	7.3	8.6
12	3	7.6	12.2	27.9	12.8
13	4	6.3	8.0	8.6	15.6

Soil #1 - Los Alamos Humus

Soil #2 - Coarse, Sandy

Soil #3 - Fine Clay

Soil #4 - Composite

Figures 1 and 2 are graphs of the rate of soil deposition per cm^2 at the tunnel centerline as a function of distance downstream from the

FIGURE 1. Rate of Soil Deposition for Soil #1

FIGURE 2. Rate of Soil Deposition for Soil #2

generators. The data are shown for the lowest and highest windspeed in each case. Figure 1 is for Soil #1 (Los Alamos Humus Soil) and Figure 2 is for Soil #2 (Coarse Texture Sandy Soil). Note the small shift downstream of the peak in Figure 1 and the lack of such a shift in Figure 2.

Figures 3 and 4 display the sedimentation data for $^{238}\text{PuO}_2$ obtained from the same sets of samples.

It is difficult from these results to state definitely that less $^{238}\text{PuO}_2$ remains suspended at 125 cm when soil is cogenerated than when it is not; although this was the case at the lower windspeeds in test 13, where the best comparisons between soil and no-soil conditions could be made. Since the interaction time is considerably reduced at the higher windspeeds, it is not surprising that soil and no-soil runs should yield the same results.

The $^{238}\text{PuO}_2$ aerosol particle size distributions as measured at more than 60 cm downstream from the generators were usually characterized by an activity median aerodynamic equivalent diameter (AMAD) of between 2.0 and 3.0 μm , with a geometric standard deviation (GSD) of between 2.0 and 2.5 (assuming a log normal distribution). In the original PPO powder 50% of the particles and much more than 50% of the mass has an aerodynamic equivalent diameter of 3.2 μm . Further, if the generated aerosol were representative of the original material, a considerable fraction of the activity would have been deposited on the tunnel floor near the generator outlet.

There doesn't appear to have been an effect of the soil generation upon the $^{238}\text{PuO}_2$ particle size distribution - a further indication that little interaction took place between soil and $^{238}\text{PuO}_2$ particles.

FIGURE 3. Rate of Plutonium Activity Deposition for Soil #1

FIGURE 4. Rate of Plutonium Activity Deposition for Soil #2

Section 5 - Work in FY 1975

Top priority must be given to work on the $^{238}\text{PuO}_2$ aerosolization. Ways will be sought to maintain a higher degree of dispersion of the $^{238}\text{PuO}_2$ particles in the liquid suspension. The first approach will be to employ ultrasonic agitation of the aqueous suspensions during generation and for several hours prior to generation. Second, the results of adding other materials (surfactants, etc.) to the suspension will be investigated. The third approach will be to use nonaqueous liquids in which to suspend the particles. A fourth alternative might employ a different type of spray production apparatus, and, as a fifth choice, a Wright Dust Feed Mechanism or another dry dust generator will be evaluated for use with $^{238}\text{PuO}_2$ powder.

The goal is to generate $^{238}\text{PuO}_2$ at a steady and repeatable rate, with a particle size distribution approximately that of the original $^{238}\text{PuO}_2$ powder, and to characterize the behavior of the aerosol in the wind tunnel. This characterization of $^{238}\text{PuO}_2$ aerosols will be necessary to evaluate the effects of interaction with soil aerosols.

High priority will also be given to improved characterization of the soil aerosols. The results of the soil analyses carried out at Washington State University should soon be available. Also, tests will be performed on soil-only aerosols in which efforts will be made to collect aerosol samples large enough for gravimetric and/or chemical analysis. Improvement will be effected in sample handling to reduce the background levels of the trace elements Fe and Al.

Collection of much larger soil samples without a significant reduction in the $^{238}\text{PuO}_2$ generation may present serious problems in sample handling

due to the large $^{238}\text{PuO}_2$ activity in the samples. It may therefore be necessary to characterize the soil aerosol during the soil-only tests, and to assume that the properties of the soil aerosol will be essentially the same with and without the $^{238}\text{PuO}_2$ aerosol.

It is suggested that one soil be selected first for a thorough study of the soil - $^{238}\text{PuO}_2$ interaction. This experience may enable us to perform the work on the other soils with greater speed and efficiency, and may result in an overall saving of time and money.

The first set of tests will be made on generation of soil mixed with $^{238}\text{PuO}_2$, probably using the same soil-to- $^{238}\text{PuO}_2$ mass ratio as in aerosol interaction tests. The effects of "aging" will be studied by subjecting the mixtures to different periods of temperature and humidity cycling.

Ways will be sought to observe photographically the mixing and interaction of the aerosols.

In order to study the effects of aerosol particle charge, static electric charge neutralizers will be designed for removal of the electric charge from the aerosols, and ways to increase the electric charge will also be investigated.

A study will be made of a method for exposing animals to agglomerates of soil and $^{238}\text{PuO}_2$, considering both conventional exposure facilities and exposure in the wind tunnel.

Task 2 - Marine Animal Studies

Section 1 - *In Vivo* Studies

With the cooperation of Dr. Frank Kawahara of the Navy Undersea Center, San Diego, CA, sea cucumbers and other small marine organisms from the

Pure Plutonium Oxide (PPO) solubility test site off San Clemente Island were radiochemically analyzed. These specimens include eight sea cucumbers and three marine snails which were confined within the test vessels for 30- to 99-day time periods. A small fish and some fairy shrimp which had invaded the vessels during the period of submersion were also analyzed.

The total alpha activity of selected organs of the sea cucumbers is given in Table 3. In some cases, atrophy of some internal organs had occurred so that values for these organs are not available. The reasons for the atrophied organs in animals 2, 3, 4, and 5 are not known. There are no apparent relationships between atrophy and organ plutonium content or length of confinement in the test vessel. Some possible explanations are (a) atrophy may be related to the reproductive cycle of the organism, or (b) it may be a seasonal occurrence. Animals 3, 4, and 5 were collected in July and October of 1973.

Most of the activity appears to be concentrated in the digestive tracts and the body walls of the animals. The body wall values in Table 3 appear low in comparison to those of other organs because the values given are per gram wet weight. When it is considered that the body wall comprised 90-95% or more of the total body weight, these values become more significant.

Great inconsistencies in the data are noted: for example, Animal 2 had a higher body burden of plutonium than did Animals 3 and 4, even though the latter were confined within a test vessel for 30 days and the former was collected outside the vessels. It appears, however, that the plutonium content of the stomach is responsible for the discrepancy, or, Animal 2 may have ingested the plutonium immediately prior to its capture.

TABLE 3. Alpha Activity in Organs of Sea Cucumbers After Exposure to PPO in Sea Water¹

<u>Animal No.</u>	<u>Time Period</u>	<u>Location</u>	<u>Mouth & Stomach</u>	<u>Gut</u>	<u>Respiratory Tree</u>	<u>Gonads</u>	<u>Body Wall</u>	<u>Total dpm/gm</u>	<u>Total dpm/animal</u>
1	--	< 15 ft outside vessel	0.79	7.28	0.42	0.35	0.15	1.42	151
2	--	< 15 ft outside vessel	8410	--	86	< Bkgd	116	219	17,549
3	30 days	cage 5	3950	--	--	--	153	175.8	14,499
4	30 days	cage 6	2110	--	--	--	51.9	56.8	7,064
5	43 days	cage 5	1696	--	--	< Bkgd	1093	1098	71,676
6	99 days	cage 5	10779	109819	39350	4440	1499	4963	404,480
7	99 days	cage 5	1355	2025	1450	150	218	265	31,466
8	99 days	cage 6	37015	268266	2164	12720	1235	3611	341,203

¹ All values are in disintegrations per minute (dpm) per gram wet weight except in last column.

Further, it might be assumed that Animals 3 and 4 were not feeding during their confinement in the test vessels due to the atrophic state of their intestinal tracts. The same explanation could account for the discrepancy in values between Animals 6 and 7 which, although confined in the same cage for the same period of time, exhibited more than a ten-fold difference in plutonium content.

The determination of the physical form of $^{238}\text{PuO}_2$ taken up by the animals may lead to another explanation for the inconsistent data. Radiochemical analysis indicates the presence and amount of radioactivity but not its dispersal within the organism. If the plutonium is taken up as a relatively large particle or aggregate of particles from the original PPO pellet, a large amount of activity would be recorded even though the activity might be concentrated in a single site within the animal. Forthcoming autoradiographs of tissue samples taken from the animals should reveal whether or not that is the case.

After radiochemical analysis of Animal 1 it was noted that the ratio of ^{238}Pu to ^{239}Pu in the organ was considerably lower than would be expected (see Table 4), were the PPO fuel the sole source of plutonium, since this contains isotopes in a ratio of approximately 1500:1 by weight. Further analysis was performed with selected samples from animals confined with the PPO pellet for 99 days and, although a higher isotopic ratio was found, it was still lower than the expected ratio (Table 4). Two possible reasons for the reduced ratio are suggested: (1) selective uptake or retention of $^{239}\text{PuO}_2$ by the animal and/or (2) contamination of the test area with $^{239}\text{PuO}_2$ from atmospheric fallout.

TABLE 4. Relationships Between ^{238}Pu Activity in Selected Samples

Animal No.	Organ	Total dpm/gm	^{238}Pu dpm/gm	^{239}Pu dpm/gm	Ratio ^{238}Pu to ^{239}Pu
1	Mouth & Ring Canal	0.341	0.255	0.086	2.965
	Stomach	3.373	3.225	0.148	21.791
	Gut	7.282	7.134	0.148	48.204
	Respiratory Tree	0.419	0.303	0.116	2.608
	Gonads	0.345	0.225	0.120	1.875
	Body Wall	0.153	0.144	0.008	18.0
*6	Mouth & Stomach	8139.0	8106.0	31.0	261.5
	Gut	187326.0	186300.0	1001.0	186.1
	Respiratory Tree	4477.0	4470.0	6.0	745.0
*8	Mouth & Stomach	32226.0	32094.0	130.0	246.9
	Gut	156450.0	155892.0	561.0	277.9
	Gonads	1247.0	1238.0	7.0	176.9

*Values given represent total activity per sample.

On a recent trip to the test site (June, 1974) samples were taken of the bottom sand at varying distances from the cages: 5, 10, 15, 20, and 100 ft from the test vessels. No plutonium activity was found in the samples due either to inadequate sample size or to the detection limits of our analytical procedure. Samples were collected in a 4 oz glass jar by a diver and did not, therefore, incorporate a very large area of the sea bottom (probably a maximum of about 9 cm^2). If ^{239}Pu fallout contamination of the ocean floor is 3000 dpm/m^2 , as has been suggested by a member of the Battelle-Northwest Radiological Science Division, the area sampled would contain only enough radioactivity to reach the lower detection limits of our procedure (2-5 dpm).

Although our sampling did not show any plutonium radioactivity, incorporation of sand from a larger area in each sample would be more likely to indicate its presence. Sea cucumbers probably cover a large area of the ocean floor during their lifetimes and ingest considerable amounts of sand. There may also be systemic retention of plutonium from the sand, however, so that accumulation within the organisms could occur. Otherwise, the plutonium would be excreted at the same rate that it is ingested. Two more sea cucumbers were collected near the test site on the last collecting trip and these animals will be analyzed for both ^{238}Pu and ^{239}Pu in an attempt to establish a reliable background level of plutonium in the organisms.

In April, 1974 two new test vessels with new sand floors and new PPO pellets were put into use. Pretest sand samples were not taken, but samples were collected from the center and periphery of each vessel in June, 1974. Those values are presented in Table 5.

TABLE 5. Alpha Activity in Sand Samples Taken from the Center and Periphery of Each of the PPO Solubility Test Vessels.

<u>Vessel No.</u>	<u>Center (dpm/sample)</u>	<u>Periphery (dpm/sample)</u>	<u>Date</u>
3	2964 $\pm$ 177	5025 $\pm$ 225	June 1974
4	16627 $\pm$ 403	905 $\pm$ 105	June 1974

It is noted that more alpha activity was found at the periphery of Vessel 3 than at the center. A probable explanation is that the sand was shifted due to water turbulence as the vessel was raised from the ocean floor. Similar samples will be taken during each inspection tour.

An unsuccessful attempt was also made to withdraw water samples from the vessels before they were disturbed. With perfection of that technique and with periodic sand samples, it is hoped that the levels of plutonium to which the test animals are exposed can be more closely monitored.

Three sea cucumbers confined in these vessels for a two-month period were also collected and are being analyzed for plutonium content.

Section 2 - In Vitro Studies

Aged suspensions of "insoluble" ^{238}Pu display a greater biological availability than expected from solubility data. Ultrafiltration of a plutonium oxide suspension provides a measure of plutonium that is mobile and generally available to enter biological processes. To estimate the effect of such aging to help in the analysis of possible release of these materials, an experiment was devised having an orthogonal factorial design with four sets of factors: logarithmic plutonium concentrations of 100 pCi, 100 nCi, and 100 $\mu\text{Ci/ml}$ solvent; temperatures representative of the

ocean, 4-10°C, and of body, 37°C; solvents, sea water, simulated lung fluid and citric acid in a pH 6 phosphate buffer; and time following preparation of the suspension. A pilot study is being undertaken because of a prohibitively large number of samples (8000) requiring plutonium analyses under this design. To decrease the number of samples required it is necessary to identify the sources of error and decrease the variation by improved or altered techniques. The major error is in determining the suspension concentration prior to each ultrafiltration. The coefficient of variations for 8 samples is sometimes 40%, usually 25%, and must be brought down to about 5%. The CV has been brought to about 10% by sampling the suspensions while under the influence of ultrasonic agitation. Another source of error in preparation of solutions for counting can be avoided for high (μCi) level plutonium samples by direct counting of the X-ray component which brings the CV for 10 samples of the high-level suspension to about the desired 5% level.

Another factor influencing design is pH. In a 50 ml suspension at a concentration of 100 μCi $^{238}\text{PuO}_2/\text{ml}$ distilled water, pH changed from 6 at 1 hour following preparation of the suspension to 4.5 in 1 day and 3.5 in 10 days. At a concentration 100X higher, pH was 3 in 30 hours and stabilized at approximately 1.5 after 60 hours. One way of partially compensating for this appears to be by taking a small amount of the master suspension, and creating a new suspension just prior to the ultrafiltration test. If a series of controlled pH suspensions had to be maintained with pH-stats the experiment would be unmanageably large. Progress in these studies has been delayed pending the acquisition of equipment.

Task 3 - Hot Particle Studies

Questions have been raised concerning the relative importance of airborne plutonium deposited within the respiratory tract and that deposited on the skin. In the absence of data, skin deposition has generally been ignored in deference to deposition within the respiratory tract. In order to test the validity of calculated values for skin and respiratory tract deposition, we decided to compare them to values obtained experimentally. Our experimentally measured values were obtained by exposing rats which had the hair removed to an aerosol of $^{238}\text{Pu}(\text{NO}_3)_4$ in the wind tunnel. Immediately after exposure, the rats were killed and the ^{238}Pu content of the skin, lungs, GI tract and head determined. The experimentally determined values for initial deposition in the respiratory tract were within 20% of the calculated values, while the quantity deposited on skin was approximately half that calculated. We therefore conclude that both skin and respiratory tract deposition can be reasonably estimated for varying conditions of exposure and that skin deposition is unlikely to greatly exceed the initial deposition in the respiratory tract.

A computer program which was designed to evaluate the thermal profile for implantable heat sources containing $^{238}\text{PuO}_2$ is being tested for its application to estimating the thermal characteristics of ^{238}Pu and ^{244}Cm oxide particles which might be deposited on skin. Use of this program should facilitate assessment of the influence of a number of parameters, such as depth of penetration of a particle, vascularity and blood flow, cell death, etc. on heat dissipation. Preliminary calculations indicate that the temperatures of $^{238}\text{PuO}_2$ particles between 200 and 1000 μm in diameter do not differ greatly from the ambient air temperature ($< 140^\circ \text{F}$

difference). The observations in the laboratory that ^{238}Pu particles can penetrate lucite and glass (Pers. comm., D. H. Willard) give some indication that a higher differential would be expected. The calculations are therefore being reexamined to determine if a transient high temperature spike does occur.

Task 4 - Mathematical Modeling

Data on all dogs exposed to ^{238}Pu oxides over the past 8 years is being assembled for input to our computer model derived from $^{239}\text{PuO}_2$ dog exposure data to see what modifications are necessary.

No. of Copies

OFFSITE

- 1 AEC Chicago Patent Group
U. S. Atomic Energy Commission
9800 South Cass Avenue
Argonne, IL 60439

A. A. Churm
- 3 AEC Technical Information Center
- 13 AEC Space Nuclear Systems
U. S. Atomic Energy Commission
Washington, D.C. 20545

G. P. Dix (2)
T. J. Dobry Jr. (10)
D. S. Gabriel
- 4 AEC Division of Biomedical Environmental Research
U. S. Atomic Energy Commission
Washington, D.C. 20545

N. F. Barr
C. W. Edington
J. L. Liverman
B. O. Stuart
- 2 Los Alamos Scientific Laboratories

R. N. Mulford
G. R. Waterbury
- 1 Lovelace Foundation

B. B. Boecker
- 1 Oak Ridge National Laboratory

J. A. Auxier

No. of Copies

ONSITE

- 1 AEC Richland Operations Office

P. F. X. Dunigan Jr./
B. J. Melton
- 26 Battelle-Northwest

E. L. Alpen
W. J. Bair
W. C. Cannon (2)
D. K. Craig (5)
R. E. Filipy (2)
E. L. Klepper
D. D. Mahlum (2)
E. J. Rossignol
G. A. Sehmel
V. H. Smith
R. C. Thompson
R. E. Wildung
Biology Library (2)
Technical Information Files (5)