JAN 22 1968

September 15, 1967

SC-R-67-1100

MASTER

ENVIRONMENTAL ENGINEERING ABSTRACTS

Prepared By
Simulated Environments Information Center
Sandia Laboratory Library

SANDIA LABORATORIES

OPERATED FOR THE U. S. ATOMIC ENERGY COMMISSION BY SANDIA CORPORATION

ALBUQUERQUE, NEW MEXICO; LIVERMORE, CALIFORNIA

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

ENVIRONMENTAL ENGINEERING ABSTRACTS

Prepared for

THE ENVIRONMENTAL TESTING LABORATORY

Organization 7300

By

The Simulated Environments Information Center
Sandia Laboratory Library

September 15, 1967

SANDIA CORPORATION

Albuquerque, New Mexico

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

INTRODUCTION

The intent of this bulletin is to abstract information in the field of environmental engineering. Selection of material, abstracting, subject coding, and editing are the responsibility of the Simulated Environments Information Center. The SEIC is located in the Environmental Test Library, Building 860, Rm. 208, telephone 264-7568. Inquiries should be directed to this Center.

The code number, appearing to the right of each entry, is a unique identification number used for machine subject retrieval. The final letter of the code indicates the major subject of the article and determines the order of listing in this bulletin.

<u>Major Subject</u>	<u>Code</u>
ACCELERATION	A
ACOUSTIC	B
ATMOSPHERIC	C
CLIMATIC	D
ELECTRICAL	E
GASEOUS	F
GENERAL	G
HYGRO-ENVIRONMENT	H
INDUCED	I
STATIC	J
MEASUREMENT/INSTRUMENTATION	K
NATURAL	L
PRESSURE	M
RADIATION	N
MECHANICAL SHOCK	O
SPACE	P
SPECIFICATIONS	Q
HI-TEMP AND UNSPECIFIED TEMP	R
LOW-TEMP AND TEMP SHOCK	S
RANDOM VIBR AND UNSPECIFIED VIBR	T
SINUSOIDAL	U
BIOLOGICAL	V
MISCELLANEOUS	W
UNRELATED	X
RELIABILITY	Y
ENGINEERING PRACTICES	Z

ACCELERATION ENVIRONMENTS

VOSS K TECHNOLOGY WEEK
GE FACILITY TO STUDY ZERO-G PERFORMANCE
TECH.WEEK VOL.20,P.17 JAN.2,1967 1FIG

VOS7001A

1.INFORMATION 2.FACILITY 3.SPACE 4.NOMINAL 5.SINGLE 7.HUMAN,
FACILITY 9.SUB-GRAVITAL

IN ORDER TO ALLOW SCIENTISTS TO STUDY HUMAN WORK OUTPUT IN EXTENDED PERIODS OF WEIGHTLESSNESS, GENERAL ELECTRIC HAS SET UP AN UNDERWATER CAGE THE SIZE AND SHAPE OF A SATURN S-IVB HYDROGEN TANK IN 31 FT OF WATER NEAR ST THOMAS IN THE VIRGIN ISLANDS. THE TANK IS BEING USED IN CONJUNCTION WITH A UNIQUE BACK-PACK LIFE-SUPPORT SYSTEM.

ACOUSTIC ENVIRONMENTS

BOST RB AEROSPACE CORP
PREDICTION OF FLIGHT VIBRATION LEVELS FOR THE SCOUT LAUNCH
VEHICLE

BOS6001B

US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVIRONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.5,P.85-95 6REF 9FIG

1.STUDY 2.METHOD 3.INDUCED 4.NOMINAL 5.SINGLE 7.SCOUT 8.ENVIRO-MEAS 9.ACOUSTIC

THE PREDICTION PROCEDURE WAS DESIGNED TO DEFINE THE ACOUSTICALLY INDUCED RANDOM VIBRATION ENVIRONMENT THROUGHOUT THE SCOUT VEHICLE BY USING THE LIMITED DATA SAMPLE FROM SIX VEHICLES. A TRANSFER FUNCTION RELATING THE INTERNAL VIBRATION LEVEL TO THE EXTERNAL NOISE LEVEL WAS ESTABLISHED BY USE OF THE MEASURED VIBRATION DATA AND THE CALCULATED EXTERNAL NOISE LEVELS AT THE POINT OF MEASUREMENT. THIS TRANSFER FUNCTION WAS THEN USED TO CALCULATE THE EXPECTED VIBRATION LEVELS IN EACH AREA OF THE VEHICLE FROM THE NOISE LEVEL AT EACH LOCATION. STATISTICAL METHODS WERE USED TO ESTABLISH CONFIDENCE LEVELS FOR THESE CALCULATIONS. THE SUCCESS OF THE PREDICTION PROCEDURE IS DEMONSTRATED BY COMPARISON OF THE PREDICTED VIBRATION LEVELS WITH MEASURED DATA OBTAINED ON SUBSEQUENT SCOUT FLIGHTS. THE APPLICABILITY TO OTHER VEHICLES IS DEMONSTRATED BY COMPARISON OF PREDICTED AND MEASURED VIBRATION LEVELS FOR THE ATLAS-LAUNCHED FIRE VELOCITY PACKAGE.

BOWEN AJ ASSOC ELEC IND

BOW7001B

AN INVESTIGATION OF THE NOISE FIELD PRODUCED NEAR A HALF-INCH
DIAMETER STEAM JET
=JL.SOUND AND VIBR VOL.5,P.113-128 JAN.1967 21REF 10FIG

1.STUDY 2.MEASUREMENT 3.INDUCED 4.NOMINAL 5.SINGLE 7.CHAMBER,
PRESSURE-SYSTEM,MICROPHONE 8.ENVIRO-MEAS 9.ACOUSTIC

THE OVERALL SOUND FIELD (25 TO 40,000 C/S) AND THE SOUND FIELDS FOR THREE REPRESENTATIVE FREQUENCIES (1/3-OCTAVE BANDWIDTH) WERE PLOTTED AS CONTOURS OF CONSTANT SOUND PRESSURE LEVEL WITHIN 60 DIAMETERS OF THE JET NOZZLE EXIT. THESE NOISE FIELDS FORMED THE BASIS FOR DISCUSSION OF THE JET NOISE SOUND FIELDS AND, IN PARTICULAR, THE DIRECTIONAL TRENDS OF THE NOISE FIELDS AT VARIOUS FREQUENCIES WERE INVESTIGATED. THE NOISE RADIATION DECAY RATES IN DIFFERENT DIRECTIONS WERE ESTIMATED AND AN APPROXIMATE RADIAL LIMIT FOR THE BEGINNING OF THE INVERSE SQUARE LAW WAS FIXED. TO FIND THE VARIATION OF SOUND PRESSURE LEVEL WITH JET MACH NUMBER, THE DISTRIBUTION OF THE VELOCITY EXPONENT WAS PLOTTED AS A CONTOUR MAP. THE CHARACTERISTICS OF EACH SOUND FIELD WERE COMPARED WITH PREVIOUS WORK BY OTHER INVESTIGATORS. PARTICULAR ATTENTION WAS PAID TO THE DIFFERENT MEDIA USED. ALL THE CHARACTERISTICS OF THE SOUND FIELDS INVESTIGATED WERE COMPATIBLE WITH BOTH THE QUADRUPOLE AND SIMPLE SOURCE THEORIES FOR THE GENERATION OF SOUND, ALTHOUGH SOME OF THE RESULTS WERE CONTRADICTORY TO STATEMENTS MADE IN OTHER REPORTS.

CHANDIRAMANI KL BOLT BERANEK

CHA6003B

RESPONSE OF STRUCTURAL COMPONENTS OF A LAUNCH VEHICLE TO IN-
FLIGHT ACOUSTIC AND AERODYNAMIC ENVIRONMENTS
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS, SYMPOSIUM, 36TH, OCT. 1966 PT. 5, P. 97-106 9REF 6FIG
=1TABLE

1.THEORY 2.EFFECTS 3.INDUCED 4.NOMINAL 5.SINGLE 7.MODEL,
STRUCTURE 8.ENVIRO-EFFECTS 9.ACOUSTIC

A UNIFIED SYSTEM OF PROCEDURES IS DEVELOPED FOR ESTIMATING SOME IMPORTANT CLASSES OF IN-FLIGHT NOISE ENVIRONMENTS AND THE RESULTING SURFACE VIBRATION ON A TYPICAL LAUNCH VEHICLE. NOISE ENVIRONMENTS ARE CLASSIFIED ACCORDING TO THE NATURE OF THE SPATIAL AND TEMPORAL CORRELATIONS OF THE ASSOCIATED FLUCTUATING PRESSURE FIELDS. THE STRUCTURAL ELEMENTS CONSIDERED ARE A CYLINDER AND A FLAT PLATE. THE PRESENTATION IS GENERAL ENOUGH TO APPLY TO ORTHOTROPIC AND LIQUID-LOADED STRUCTURES. SOME NUMERICAL EXAMPLES ARE PRESENTED FOR ESTIMATES OF FREQUENCY SPECTRA OF ACCELERATION ON THE VIBRATING STRUCTURES.

INDUCED ENVIRONMENTS

- BRAY A INST DINAMOMETRICO ITAL BRA60021
VACUUM DEPOSITED FILMS AT HIGH TEMPERATURE
=INSTR.AND CONT.SYS VOL.39,P.121-125 NOV.1966 11REF 9FIG
1.STUDY 2.INSTRUMENT 3.INDUCED 4.NOMINAL 5.COMBINED 7.GAGE-
STRAIN,PLATING 8.ENVIRO-MEAS 9.HI-TEMP,VH-TEMP,STRAIN
THE RESULTS OBTAINED FOR CHROMIUM-SILICON AND PLATINUM FILMS
DEPOSITED ON AN INSULATING SUBSTRATE AND USED AS STRAIN GAGES
AT HIGH TEMPERATURE ARE ENCOURAGING.THEY SHOW THAT IN THE
ABSENCE OF AN ADHESIVE,RESISTANCE DRIFT AT HIGH TEMPERA-
TURE CAN BE REDUCED TO VERY LOW VALUES,AND THAT THE TEMPERA-
TURE EFFECT ON GAGE FACTOR IS SMALL(LESS THAN + OR -5 PERCENT
FOR ALL TESTED FILMS WITHIN THE TEMPERATURE RANGE OF 20 DEG TO
400 DEG C).
- BUTLER RI SANDIA CORP BUT70011
CURRENT PRACTICES IN SHOCK AND VIBRATION SENSORS
=INSTR.TECH VOL.14,P.41-48 MAR.1967 8REF 11FIG
1.EVALUATION 2.INSTRUMENT 3.INDUCED 4.NOMINAL 5.SINGLE
7.ACCELEROMETER,GAGE-STRAIN,TRANSDUCER,PIEZO-ELECTRIC
8.ENVIRO-MEAS 9.VIBR,SHOCK
AN EXCELLENT REVIEW ARTICLE ON SHOCK AND VIBRATION SENSORS
DISCUSSED ACCORDING TO THE FUNCTION TO BE MEASURED--STRAIN,
DISPLACEMENT,ACCELERATION,VELOCITY,AND PRESSURE OR FORCE.
IN ADDITION TO AN EXPLANATION OF THE OPERATING PRINCIPLES,
PRACTICAL CONSIDERATIONS OF VALUE IN THE USE OF THESE SENSORS
ARE INCLUDED.
- LICARI JJ NORTH AM AV LIC70011
PLASTICS FOR PACKAGING--HANDLE WITH CARE
=ELECTRONICS VOL.40,P.101-108 APR.17,1967 10REF 3FIG
=8TABLES
1.EVALUATION 2.PROTECTION 3.INDUCED 4.LIFE 5.SINGLE 7.PLASTIC,
ENCAPSULATE,MINUTEMAN,SEMICONDUCTOR 8.ENVIRO-EFFECTS 9.CON-
TAMINANTS,MOISTURE,HI-TEMP,VH-TEMP
PRELIMINARY TESTS OF THE INTERACTION OF EPOXY,PHENOLIC,SILI-
CONE,AND FLUOROCARBON PLASTICS WITH SEMICONDUCTOR DEVICES UN-
DER VARIOUS ENVIRONMENTS HAVE INDICATED THAT CONTAMINANTS IN-
HERENT IN OR GENERATED BY THE PLASTICS CAN AFFECT DEVICE PER-
FORMANCE. THEREFORE PLASTICS MUST BE CLASSIFIED WITH RESPECT
TO CONTAMINANTS IN RESINS,HARDENERS,AND FORMULATION INGREDI-
ENTS,AND IN TERMS OF THEIR PROBABLE EFFECTS ON SEMICONDUCTORS.

OWENS FS AF MATERIALS LAB

OWE6001I

ELASTOMERS FOR DAMPING OVER WIDE TEMPERATURE RANGES
=US DIRECTOR OF DEFENSE, SHOCK, VIBRATION AND ASSOCIATED ENVI-
=RONMENTS, SYMPOSIUM, 36TH, OCT. 1966 PT. 4, P. 25-35 10 REF 11 FIG
=1 TABLE

1. EVALUATION 2. MITIGATION 3. INDUCED 4. NOMINAL 5. COMBINED
7. ISOLATOR, ELASTOMER 8. ENVIRO-EFFECTS 9. HI-TEMP, LO-TEMP,
DAMPING

THE APPROACH IS BASED ON THE PHENOMENON THAT VISCOELASTIC POLYMERS EXHIBIT A HIGH LEVEL OF DAMPING ONLY WITHIN A FEW DEGREES OF THEIR GLASS TRANSITION TEMPERATURES AND THAT CERTAIN TYPES OF POLYMER BLENDS EXHIBIT MORE THAN ONE GLASS TRANSITION TEMPERATURE. THE DYNAMIC RESPONSE OF BLENDS OF POLYVINYL ACETATE AND POLYSTYRENE WITH A STYRENE-BUTADIENE AND A NITRILE-BUTADIENE RUBBER WERE INVESTIGATED OVER TEMPERATURE RANGES INCLUDING ALL THE GLASS TRANSITIONS OF THE POLYMERS USED IN THE BLENDS. THE POLYVINYL ACETATE-POLYSTYRENE-NITRILE RUBBER BLEND AND THE POLYSTYRENE-NITRILE RUBBER BLEND BOTH MET THE TARGET PROPERTIES OF HAVING A LOSS FACTOR OF 0.1 OR MORE AND A MODULUS OF 10 TO THE 4TH POWER PSI OVER A 200 DEG F RANGE. THE THREE POLYMER BLENDS HAD A HIGHER LEVEL OF DAMPING OVER A WIDER TEMPERATURE RANGE THAN THE TWO POLYMER BLENDS, AND THE TWO POLYMER BLENDS WERE BETTER THAN THE BASE ELASTOMERS.

REESE DR WYLE LAB

REE6001I

DYNAMIC-TESTING SECTIONS OF APOLLOS SATURN
=ENVIR. QUAR VOL. 12, P. 19-20+ DEC. 1966 6 FIG

1. ORGANIZATION 2. FACILITY 3. INDUCED 4. NOMINAL 5. SINGLE 7. CHAM-
BER, SHAKER, DATA-SYSTEM, SATURN 8. ENVIRO-CONTROL 9. ACOUSTIC,
LF-VIBR, HF-VIBR, RDM-VIBR

THE MISSION OF WYLE-HUNTSVILLE FACILITY WAS TO SIMULATE THE EFFECT OF THE 7.5 MILLION-LB THRUST OF THE S-1CS FIVE F-1 ENGINES ON THREE MAJOR SECTIONS OF THE S-II STAGE. TEST REQUIREMENTS INCLUDED--ACOUSTIC EXCITATION FROM 10 TO 10,000 CPS AT 160 DB OVER-ALL, RANDOM VIBRATION FROM 10 TO 300 CPS IN EACH OF 5 AXES, AND SINUSOIDAL VIBRATION FROM 5 TO 300 CPS IN EACH OF 5 AXES. THE SYSTEMS DESIGNED TO MEET THESE REQUIREMENTS ARE DESCRIBED.

SHARMA MG PENN STATE UNIV

SHA6001I

DYNAMIC MECHANICAL STUDIES OF A COMPOSITE MATERIAL
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.4,P.95-106 10REF 9FIG
=1TABLE

1.STUDY 2.MITIGATION,METHOD 3.INDUCED 4.NOMINAL 5.COMBINED
7.ISOLATOR,ELASTOMER,TEST-EQUIP 8.ENVIRO-EFFECTS 9.HF-VIBR,
LO-TEMP,HI-TEMP

AN APPARATUS WHICH WAS DEVELOPED FOR THE DETERMINATION OF THE DYNAMIC MECHANICAL BEHAVIOR OF SOFT SUBSTANCES FOR THE FREQUENCY RANGE 300-3000 CPS INCLUDING A THERMAL CABINET FOR THE STUDY OF TEMPERATURE EFFECTS IS DESCRIBED. A THEORY THAT CONSIDERS THE COMPOSITE MATERIAL SYSTEM TO BE MADE UP OF AN ELASTIC FILLER(ALUMINUM)RANDOMLY DISPERSED IN A MATRIX OF A VISCOELASTIC MATERIAL(SOFT MATERIAL)HAS BEEN DEVELOPED. THE THEORY PREDICTS THE DYNAMIC BEHAVIOR OF THE MATERIAL IN TERMS OF THE CREEP PROPERTIES OF THE CONSTITUENT MATERIALS FOR UNI-AXIAL AND VOLUMETRIC COMPRESSION LOADING. AN EXAMINATION OF THE EXPERIMENTAL DATA SHOWS THAT THE DYNAMIC MODULUS AND THE DAMPING PROPERTIES OF THE MATERIAL ARE CONSIDERABLY AFFECTED BY THE VOLUME FRACTION OF THE FILLER SUBSTANCE IN THE BULK MATERIAL. BY USING THE TIME-TEMPERATURE SHIFT PRINCIPLE, ONE REDUCED CURVE CAN BE CONSTRUCTED FOR THE COMPLEX DYNAMIC MODULUS VARYING WITH THE FREQUENCIES.

STATIC ENVIRONMENTS

DAVIDSE PD IBM

DAV6001J

THEORY AND PRACTICE OF RF SPUTTERING
=JL.ENVIR.SCI VOL.9,P.28-33 DEC.1966 21REF 17FIG 3TABLES

1.EVALUATION 2.PROTECTION 3.GENERAL 4.NOMINAL 7.GLASS,SEMICON-
DUCTOR,METALS,PLATING 9.SEAL-PROP

HIGH QUALITY INSULATOR FILMS,EG,FILMS USED TO PASSIVATE SEMI-
CONDUCTOR DEVICES AND CIRCUITS,CAN BE DEPOSITED AT REASONABLY
HIGH RATES THROUGH RF SPUTTERING. THIS ARTICLE DESCRIBES THE
EQUIPMENT,PROCEDURES AND PROPERTIES OF THIS PROCESS.

PRESSURE ENVIRONMENTS

ENVIRONMENTAL QUARTERLY

ENV6003M

LOCKHEED IS FINDING OUT WHAT ITS LIKE TO WORK ON THE MOON
=ENVIR.QUAR VOL.12,P.48 DEC.1966 1FIG

1.INFORMATION 2.FACILITY 3.PLANETARY 4.NOMINAL 5.SINGLE
7.CHAMBER 9.VL-PRESS

A NEWS REPORT OF A NEW,MAN-RATED ALTITUDE CHAMBER INSTALLED IN
LOCKHEEDS BIOTECHNICAL LABORATORIES. THE MAIN CHAMBER,
18X18X36 FT,CAN REACH THE PRESSURE EQUIVALENT OF 300,000 FT
IN 42 MINUTES,THE ENTRY LOCK,A 10-FT CUBE,250,000 FT
IN HALF AN HOUR.

FALOR K VEECO INSTR
VACUUM GAUGE CALIBRATION

FAL6001M

=INSTR.AND CONT.SYS VOL.39,P.93-97 DEC.1966 9FIG

1.EVALUATION 2.INSTRUMENT 3.GENERAL 4.NOMINAL 5.SINGLE 7.CALIBRATION-EQUIP,GAGE 8.CALIBRATION 9.HI-VAC

FOR TOTAL PRESSURE CALIBRATION,THE VEECO CS-775 IS DESCRIBED. IT UTILIZES RATE-OF-PRESSURE RISE AND LEAK-RATE MEASUREMENTS AND WILL CALIBRATE GAGES TO AN ACCURACY OF + OR - 5 PERCENT FROM 2×10^{-10} TO THE MINUS 4 TO 4×10^{-10} TO THE MINUS 7 TORR. PARTIAL-PRESSURE CALIBRATION USING RESIDUAL GAS ANALYZERS IS ALSO EXPLAINED.

RADIATION ENVIRONMENTS

BOBCO RP HUGHES AIRCRAFT

BOB7001N

SOLAR INCIDENCE FACTORS FOR THERMAL ANALYSIS OF IMPERFECTLY COLLIMATED RADIATION IN SOLAR SIMULATORS
=JL.SPACECRAFT AND ROCKETS VOL.4,P.236-242 FEB.1967 6REF
=6FIG 3TABLES.

1.STUDY 2.METHOD 3.SPACE 4.NOMINAL 5.SINGLE 7.RADIATION-SOURCE,OPTICS 8.ENVIRO-CONTROL 9.SOLAR

THE COMPUTATION OF SOLAR INCIDENCE FACTORS FOR USE IN ESTIMATING THE EFFECTS OF IMPERFECTLY COLLIMATED SOLAR SIMULATOR BEAMS IS SHOWN TO BE RELATED TO ALL ALGORITHMS FOR OBTAINING CONVENTIONAL SHAPE FACTORS USED IN DIFFUSE RADIANT EXCHANGE. SUPERPOSITION TECHNIQUES ARE USED AT THREE ANALYTICAL LEVELS TO REDUCE TO SIMPLER PROBLEMS THE COMPLEX PROBLEM OF FINDING SOLAR SIMULATOR INCIDENCE FACTORS. FIRST,SUPERPOSITION IS USED TO FIND THE ENERGY INCIDENT AT ANY LOCATION IN A TEST ZONE WHICH IS IRRADIATED BY DIRECTIONAL,VARIABLE-INTENSITY BEAMS FROM SEVERAL DISCRETE SOURCE REGIONS. SECOND,IT IS SHOWN HOW COMPLEX SOURCE INTENSITY DISTRIBUTIONS MAY BE DECOMPOSED INTO A SUM OF ANALYTICALLY TRACTABLE FUNCTIONS. THIRD,CONVENTIONAL SHAPE FACTORS,WHICH MAY BE INTRODUCED AS ELEMENTS OF THE SOLAR INCIDENCE FACTOR,ARE EXPRESSED IN TERMS OF COMPONENTS IN THREE MUTUALLY ORTHOGONAL DIRECTIONS. WITH THESE TECHNIQUES,IT IS POSSIBLE TO ESTIMATE THE IRRADIATION ON INCLINED SURFACES AND IN PENUMBRAL REGIONS WITHOUT RECOURSE TO SOPHISTICATED ANALYSIS. NUMERICAL RESULTS ARE PRESENTED FOR AN ARRAY OF HEXAGONAL SOURCE ZONES IN A COLLIMATOR TYPE OF SOLAR SIMULATOR.

EVANS AS ELLIOTT FLT AUTOMATION
RADIO FREQUENCY INTERFERENCE CONTROL
=ENVIR.ENG NO.18,P.11-16 JAN.1966 4FIG

EVA6001N

1.DESIGN 2.MEASUREMENT,PROTECTION 3.INDUCED 4.NOMINAL 5.SINGLE 6.EL-1716,BS-2G-100,MIL-I-26600,MIL-I-6181D 7.CAPACITOR,CONNECTOR,INDUCTOR,TEST-EQUIP 8.ENVIRO-MEAS 9.RF

THE AUTHORS INTENDED THIS PAPER TO BE A GUIDE TO THE BASIC ASPECTS OF RFI AND TO PROVIDE SOME ASSISTANCE TO ANY ORGANIZATION STARTING WORK IN THIS FIELD. THE FIRST PART DEALS WITH MEASUREMENT AND THE LAST PART WITH CONTROL AND SUPPRESSION.

HARRINGTON RE UNION CARBIDE
 THE CARBON ARC SOURCE
 =ENVIR.QUAR VOL.13,P.32-33 MAR.1967 3FIG

HAR7001N

1.EVALUATION 2.FACILITY 3.SPACE 4.NOMINAL 5.SINGLE 7.ARC-LAMP
 8.ENVIRO-MEAS 9.SOLAR

THE FIRST OF A SERIES OF ARTICLES ON LIGHT SOURCES. ANALYZES THE DIFFERENCES PRODUCED WHEN RARE-EARTH SALTS ARE USED TO CORE THE CARBONS, PRODUCING HIGH-INTENSITY ARCS.

THOMPSON RK BOEING
 ANALYSES AND TESTS OF THERMAL SCALE MODELS OF A SIMULATED SPACECRAFT
 =JL.SPACECRAFT AND ROCKETS VOL.4,P.486-491 APR.1967 15REF
 =9FIG 5TABLES

TH07001N

1.STUDY 2.FACILITY,METHOD 3.SPACE 4.NOMINAL 5.COMBINED
 7.MODEL,RADIATION-SOURCE 8.ENVIRO-MEAS 9.SOLAR,HI-VAC

THIS INVESTIGATION OF THE FEASIBILITY OF THERMAL SCALE MODELING OF SPACECRAFT INCLUDED ANALYSES AND TESTS OF 0.285-, HALF-, AND FULL-SCALE MODELS OF A SIMULATED, DOUBLE-WALLED CYLINDRICAL SPACECRAFT. THE DESIGN OF THE SCALED MODELS WAS BASED ON THE TEMPERATURE PRESERVATION TECHNIQUE. BOTH STEADY-STATE AND TRANSIENT DATA WERE OBTAINED FROM TESTS PERFORMED IN THE BOEING 10-FT-DIAM THERMAL-VACUUM CHAMBER EQUIPPED WITH A 4-FT SOLAR SIMULATOR. THE RESULTS HAVE DEMONSTRATED THE FEASIBILITY OF USING SUBSCALE MODELS, DESIGNED ACCORDING TO THE TEMPERATURE PRESERVATION TECHNIQUE, TO PREDICT SPACECRAFT TEMPERATURES UNDER BOTH STEADY-STATE AND TRANSIENT CONDITIONS. THE MAJORITY OF THE MODEL-PREDICTED PROTOTYPE TEMPERATURES AGREED WITHIN 2 PERCENT FOR THE HALF-SCALE MODEL AND 3 PERCENT FOR THE 0.285-SCALE MODEL. ALL SIGNIFICANT DEVIATIONS IN THE MODEL-PREDICTED PROTOTYPE TEMPERATURES ARE ACCOUNTED FOR THROUGH THE ACCURACY OF THE THERMAL SIMULATION, THE MODEL DESIGN, AND THE INSTRUMENTATION.

MECHANICAL SHOCK ENVIRONMENTS

CARLSON AD GENERAL DYNAMICS
 TRANSDUCER SHOCK STUDY
 =US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVIRONMENTS, SYMPOSIUM, 36TH, OCT.1966 PT.2,P.31-51 7REF 23FIG
 =4TABLES

CAR60030

1.STUDY 2.EFFECTS 3.INDUCED 4.NOMINAL 5.SINGLE 7.TRANSDUCER,
 MODEL,CERAMICS,SHIP 8.ENVIRO-EFFECTS 9.BLAST-SHOCK

A SONAR TRANSDUCER WAS ANALYZED TO DETERMINE THE STRESSES INDUCED IN THE CERAMIC DRIVE ELEMENT BY AN UNDERWATER EXPLOSION. TWO EXPLOSIVE FORCES WERE CONSIDERED--A HYDRAULIC SHOCK ALONG THE AXIS OF THE TRANSDUCER, AND A MECHANICAL SHOCK NORMAL TO THIS AXIS. IT WAS DETERMINED FROM THE ANALYSIS THAT THE PEAK STRESSES CAUSED BY THESE TWO LOADINGS OCCUR IN DIFFERENT TIME PERIODS AND, THEREFORE, THE TWO TYPES OF SHOCK MOTION ARE ESSENTIALLY INDEPENDENT OF EACH OTHER. FURTHER ANALYSIS REVEALED THAT HYDRAULIC SHOCK IS MORE DAMAGING TO THE CERAMIC ELEMENT THAN MECHANICAL SHOCK FOR A GIVEN STANDOFF. THE RESULTS OF THE ANALYSIS COMPARED FAVORABLY WITH PREVIOUSLY CONDUCTED EXPERIMENTS. A PARAMETRIC STUDY WAS CONDUCTED TO IMPROVE THE TRANSDUCERS RESISTANCE TO BOTH HYDRAULIC AND MECHANICAL SHOCK. THE STUDY SHOWED THAT A SIGNIFICANT INCREASE IN SHOCK RESISTANCE IS POSSIBLE BY MINOR REDESIGN OF THE TRANSDUCER.

FAGAN JR RCA

FAG60010

SHOCK SPECTRA OF PRACTICAL SHAKER SHOCK PULSES
=US DIRECTOR OF DEFENSE SHOCK, VIBRATION AND ASSOCIATED ENVI-
=RONMENTS, SYMPOSIUM, 36TH, OCT. 1966 PT. 2, P. 17-29 5REF 16FIG
=2TABLES

1.XPER-RESULTS 2.SIMULATION 3.INDUCED 4.NOMINAL 5.SINGLE
7.SPECTRUM-ANALYZER, DATA-SYSTEM, SHAKER, PULSE 8. ENVIRO-CONTROL
9.SHOCK

SHAKER SHOCK DATA ARE ACQUIRED USING PIEZOELECTRIC ACCELEROMETERS AND A WIDEBAND FM MAGNETIC TAPE SYSTEM FOR RECORDING THE PULSES. DATA REDUCTION IS ACCOMPLISHED WITH SIX RELATIVELY UN-DAMPED GALVANOMETERS AND TAPE SPEED TRANSLATIONS EFFECTIVELY TO PRODUCE A 1/3-OCTAVE SHOCK SPECTRUM ANALYSIS TO 5 KHZ. A METHOD FOR SELECTING THE FOUR SHOCK SPECTRA (PLUS AND MINUS INITIAL, PLUS AND MINUS RESIDUAL) FROM A PARTICULAR SHOCK PULSE IS DETERMINED. SOME CONSIDERATION IS GIVEN TO EXPANDING THE SYSTEM FOR ON-LINE ANALYSIS. THE SPECTRA OF SHOCK PULSES USED IN SHAKER TESTS ARE COMPARED TO THE SPECIFICATION PULSE SPECTRA. THE SPECTRA OF TRANSIENT INPUTS TO TEST ITEMS DUE TO FIX-TURING PARAMETERS ARE DETERMINED, AND THEIR EFFECTS ARE DISCUSSED. TRANSIENTS OCCURRING DURING FACILITY MALFUNCTIONS OR PROTECTIVE DEVICE OPERATIONS ARE DEFINED SPECTRALLY, AND THEIR EFFECTS ON TEST ITEMS ARE DETERMINED.

FOLEY JT SANDIA CORP

FOL70010

AN ENVIRONMENTAL RESEARCH STUDY
=IES PROC. 1967, P. 363-373 8REF 4FIG 5TABLES

1.STUDY 2.DATA 3.INDUCED 4.NOMINAL 5.SINGLE 7.TRUCK, DATA-
SYSTEM 8. ENVIRO-MEAS 9.TRANSPORT

AUTOMATED METHODS OF APPLYING ENVIRONMENTAL DATA TO TEST LEVEL DERIVATION ARE BEING DEVELOPED BY THE SANDIA CORP ENVIRONMENTAL OPERATIONS ANALYSIS GROUP. THE GOAL IS TO DEVISE A SERIES OF METHODS WHEREBY DATA FROM AN ENVIRONMENTAL DATA BANK AND FROM SPECIFICALLY DESIGNED ENVIRONMENTAL RESEARCH TESTS CAN BE INTEGRATED IN A COMPUTERIZED SYSTEM WHICH PERMITS AN ALMOST CONTINUOUS, REAL TIME UPDATING OF RECOMMENDED TEST LEVELS. THIS PAPER REPORTS ON THE PROGRESS WHICH HAS BEEN MADE IN DEVELOPING SUCH A TECHNIQUE FOR DESCRIBING THE DYNAMIC ENVIRONMENT EXPECTED FOR CARGO IN TRUCK TRANSPORTATION.

HOWLETT JT NASA LANGLEY
NEW APPROACH FOR EVALUATING TRANSIENT LOADS FOR ENVIRONMENTAL TESTING OF SPACECRAFT
=US DIRECTOR OF DEFENSE SHOCK, VIBRATION AND ASSOCIATED ENVIRONMENTS, SYMPOSIUM, 36TH, OCT. 1966 PT. 2, P. 97-106 3REF 6FIG
=1TABLE

HOW60020

1. THEORY 2. SIMULATION, METHOD 3. INDUCED 4. NOMINAL 5. SINGLE
7. PULSE, MODEL, COMPONENT, SPACECRAFT 8. ENVIRO-CONTROL 9. SHOCK

A RIGOROUS DERIVATION IS PRESENTED OF A METHOD FOR DETERMINING SYSTEM RESPONSE TO TRANSIENT INPUTS USING NORMAL COORDINATES TO REPRESENT THE MULTI-DEGREE-OF-FREEDOM SPACECRAFT SYSTEM. COMPARISON OF THE ENVELOPES OF THE AMPLITUDES OF THE NORMAL COORDINATES AT ANY TIME SHOWS THE AMOUNT OF PARTICIPATION OF THAT COORDINATE AND THE CONTRIBUTION OF A PARTICULAR NORMAL MODE OF VIBRATION TO THE TOTAL SYSTEM RESPONSE. THE PROPOSED PROCEDURE FOR EVALUATING TRANSIENT ENVIRONMENTAL TESTING IS ILLUSTRATED WITH SEVERAL EXAMPLES. THE RESULTS SHOW THE EFFICACY OF MULTI-DEGREE-OF-FREEDOM ANALYTICAL MODELS OF SPACECRAFT FOR DETERMINING SYSTEM RESPONSE AND THE ADEQUACY OF PROPOSED INPUT TRANSIENTS FOR ENVIRONMENTAL TESTS, THUS PROVIDING A MORE RELIABLE MEANS OF SELECTING APPROPRIATE TEST TRANSIENT INPUTS.

HUFFINGTON NJ MARTIN CO
SIMULATION OF HEAT SHIELD PYROTECHNIC SHOCK IMPEDANCE
=US DIRECTOR OF DEFENSE SHOCK, VIBRATION AND ASSOCIATED ENVIRONMENTS, SYMPOSIUM, 36TH, OCT. 1966 PT. 2, P. 63-70 3REF 3FIG
=1TABLE

HUF60010

1. DESIGN 2. SIMULATION 3. INDUCED 4. NOMINAL 5. SINGLE 7. MODEL,
SHIELD 8. ENVIRO-EFFECTS 9. BLAST-SHOCK

PYROTECHNIC SHOCK TESTS HAD TO BE MADE ON A REENTRY VEHICLE BEFORE THE PRODUCTION HEAT SHIELD BECAME AVAILABLE. IT WAS NECESSARY TO ASSESS IN ADVANCE WHETHER DYNAMIC SIMULATION OF AN ACTUAL HEAT SHIELD WAS FEASIBLE AND WHETHER TESTS PERFORMED WITH SUCH A SIMULATION COULD BE USED TO DEVELOP PROTOTYPE DESIGN CRITERIA. THESE OBJECTIVES WERE SATISFIED BY FORMULATING A THEORY FOR THE MOTION OF A STRIP OF TWO-LAYERED SURFACE AND USING THIS THEORY TO COMPARE THE WAVE PROPAGATION CHARACTERISTICS OF A SIMULATED HEAT SHIELD WITH THOSE OF THE ACTUAL HEAT SHIELD. THE FEASIBILITY OF ACCOMPLISHING A PRACTICAL MATCH OF PHASE VELOCITIES AND ATTENUATION FACTORS OVER A WIDE RANGE OF FREQUENCIES WAS EXPLORED IN DETAIL BEFORE CONCLUDING THAT AN ADEQUATE SIMULATION COULD BE ACHIEVED.

JOURNAL OF ENVIRONMENTAL SCIENCES
MOON LANDING MEASUREMENTS
=JL. ENVIR. SCI VOL. 9, P. 20-21 DEC. 1966 4FIG

JOU60030

1. INFORMATION 2. MEASUREMENT 3. PLANETARY 4. NOMINAL 5. SINGLE
7. SURVEYOR, GAGE-STRAIN 8. ENVIRO-MEAS 9. IMPACT-SOFT

SHOCK ABSORBER-MOUNTED STRAIN GAGES MEASURED STRUCTURAL LOADING ON THE SURVEYOR SPACECRAFT AT TOUCHDOWN AND YIELDED VALUABLE FORCE-TIME DATA THAT VERIFIED A SOFT LANDING ON THE MOON.

MCWHIRTER M. SANDIA CORP

MCW60010

SPECIFICATION OF SHOCK TESTS--PANEL SESSION
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.2,P.107-119

1.PHILOSOPHY 2.SIMULATION 3.INDUCED 4.NOMINAL 5.SINGLE 6.GEN-
ERALIZED 7.PULSE,SHAKER 8.ENVIRO-CONTROL 9.SHOCK

THE DISCUSSION CENTERS ABOUT THE ADVANTAGES AND DISADVANTAGES
OF THE PULSE-TYPE SPECIFICATION AND THE SHOCK SPECTRUM METHOD.

MENTZER WR BOWLES ENG CORP

MEN60010

YIELDING EFFECTS ON SHOCK SPECTRA
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.2,P.9-16 8REF 5FIG
=1TABLE

1.XPER-RESULTS 2.EFFECTS 3.INDUCED 4.NOMINAL 5.SINGLE
7.MODEL,STRUCTURE,COMPUTER 8.ENVIRO-EFFECTS 9.SHOCK

AN UNDAMPED TWO-DEGREE-OF-FREEDOM SPRING-MASS SYSTEM, REPRESENTING AN EQUIPMENT ATTACHED TO A NONRIGID FOUNDATION SUBJECTED TO SHOCK, IS ANALYZED TO DETERMINE THE SHAPE OF THE SHOCK SPECTRUM CURVE WHEN THE EQUIPMENT SPRING IS ALLOWED TO YIELD. ANALYTICAL SOLUTIONS FOR THE EQUATIONS OF MOTION ARE PRESENTED FOR THE SYSTEM RESPONSE AS A PERFECTLY ELASTIC SYSTEM AND AS A SYSTEM YIELDING UNDER A CONSTANT FORCE. THE SYSTEM BASE MASS RESPONSE IS USED TO OBTAIN THE SHOCK SPECTRUM DATA BY HIGH-SPEED DIGITAL COMPUTER. THE SHOCK SPECTRUM CURVES FOR THE YIELDING SYSTEMS AND FOR THE PERFECTLY ELASTIC SYSTEMS, WITH EQUIVALENT DESIGN PARAMETERS AND SHOCK LOADING, ARE COMPARED. THE RESULTS INDICATE THAT CERTAIN DIFFICULTIES EXIST FOR PROPER INTERPRETATION OF FIELD DATA WHEN THE EQUIPMENT HAS YIELDED, PARTICULARLY IF THE ANALYST, UNAWARE THAT YIELDING HAS TAKEN PLACE, WISHES TO COMPILER DATA FOR A DESIGN SHOCK SPECTRUM CURVE.

SEAMONS LO SANDIA CORP

SEA60010

SHOCK TESTING WITH SOLID-PROPELLANT-POWERED GUNS
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.2,P.83-88 3REF 5FIG

1.EVALUATION 2.FACILITY 3.INDUCED 4.NOMINAL 5.SINGLE 7.SHOCK-
TESTERS,PULSE,PROPELLANT-SOLID 8.ENVIRO-MEAS 9.VH-G

A GENERAL DESCRIPTION IS GIVEN OF THE USE TO WHICH SOLID-PROPELLANT-POWERED GUNS CAN BE PUT IN THE FIELD OF ENVIRONMENTAL TESTING. EMPHASIS IS PLACED ON THE INHERENT FLEXIBILITY OF THE SHOCK TESTING OF PROJECTILES IN THE TIME INTERVAL BETWEEN IGNITION OF THE PROPELLANT CHARGE AND EXIT OF THE PROJECTILE FROM THE GUN MUZZLE. A METHOD OF COMPUTING THE SHOCK PULSE IN THIS CASE HAS BEEN DESCRIBED BRIEFLY. PROJECTILE RECOVERY AND INSTRUMENTATION PROBLEMS HAVE BEEN CURSORILY EXAMINED.

SPANG K SAAB AKTIEBOLAG, SWEDEN SPA60010
THE ADVANTAGES OF USING INITIAL-PEAK SAWTOOTH PULSE SHAPES IN
SHOCK TESTING
=ENVIR.ENG NO.23,P.14-17 NOV.1966 1REF 6FIG

1.EVALUATION 2.SIMULATION 3.INDUCED 4.NOMINAL 5.SINGLE
7.SHOCK-TESTERS 8.ENVIRO-CONTROL 9.SHOCK

THE REASONS WHY THE INITIAL-PEAK SAWTOOTH PULSE SHAPE SHOULD
BE USED IN SHOCK TESTING ARE PRESENTED--1.IT IS UNSYMMETRICAL,
2.EXPERIENCE HAS SHOWN THAT IT IS ABLE TO COVER THE EFFECTS OF
THE MOST PART OF MEASURED SHOCKS WITHOUT CONSIDERABLE OVER-
TESTING, AND 3.IT GENERATES HIGH OSCILLATIONS SUPERIMPOSED ON
HIGH ACCELERATIONS IN MECHANICAL SYSTEMS.

TEST ENGINEERING TES60150
ROAD SIMULATOR AT DANA FATIGUE-TESTS CARS
=TEST ENG VOL.16,P.32-33 DEC.1966 4FIG

1.INFORMATION 2.FACILITY 3.INDUCED 4.NOMINAL 5.SINGLE 7.VE-
HICLE, DATA-SYSTEM, FACILITY 8.ENVIRO-CONTROL 9.TRANSPORT

A HYDRAULIC ROAD SIMULATOR BUILT FOR THE PARISH DIV OF THE
DANA CORP IN DETROIT BY MB ELECTRONICS WILL PRODUCE BOUNCE,
TORSION, PITCH AND ROLL MODES OF A VEHICLE THROUGH INTERNAL
FUNCTION GENERATORS IN CONTROL CONSOLE. EACH ACTUATOR CAN BE
INDEPENDENTLY CONTROLLED AS TO RESPONSE AND PHASE RELATION-
SHIP. RIDING CONDITIONS OF ANY ROAD OR TEST TRACK CAN BE DU-
PLICATED BY PLAYING BACK TAPES RECORDED UNDER ACTUAL DRIVING
CONDITIONS. FREQUENCY RANGE OF THE EXCITERS IS DC TO 400 CPS.

SPACE ENVIRONMENTS

BABER S BOEING BAB7001P
TEST SYSTEMS FOR SIMULATING SPACE THERMAL MISSIONS
=TEST ENG VOL.17,P.40-42 APR.1967 4FIG

1.INFORMATION 2.FACILITY 3.SPACE 4.NOMINAL 5.COMBINED 7.CHAM-
BER, RADIATION-SOURCE 8.ENVIRO-MEAS 9.SOLAR, HI-VAC, HI-TEMP, LO-
TEMP, VL-TEMP, UL-TEMP

A TEST SYSTEM, WHICH WAS USED FOR FOURTEEN DAYS, WAS DESIGNED AT
BOEING TO REPRODUCE THE COMBINED THERMAL ENVIRONMENTS PRE-
DICTED FOR A TEST ITEM MOUNTED EXTERNAL TO A SPACECRAFT DUR-
ING A LUNAR MISSION. THE FACILITY AND TEST SEQUENCE ARE
BRIEFLY DESCRIBED.

CUNNINGHAM BE NASA AMES CUN7001P
SPACE ENVIRONMENT SIMULATOR FOR MATERIALS STUDIES AT NASA AMES
=JL. SPACECRAFT AND ROCKETS VOL.4,P.280-282 FEB.1967 4REF
=3FIG 1TABLE

1.ORGANIZATION 2.FACILITY 3.SPACE 4.NOMINAL 5.COMBINED 7.ARC-
LAMP, CHAMBER, MATERIALS 9.HI-VAC, SOLAR, METEOROIDS, VH-TEMP

THE SES WAS DESIGNED AND BUILT TO NASA SPECIFICATIONS BY RCA
SERVICE CO. THIS FACILITY IS DESIGNED TO SIMULATE VACUUM (AS
LOW AS 10^{-10} TO THE MINUS 10 TORR), PHOTON AND CHARGED PARTICLE
RADIATION, MICROMETEOROID BOMBARDMENT, AND TEMPERATURE FOR
STUDIES OF THE FUNDAMENTAL PHYSICAL AND CHEMICAL MECHANISMS
AND KINETICS, WHEREBY MATERIAL PROPERTIES ARE INFLUENCED BY EX-
POSURE TO THE SPACE ENVIRONMENT. ANOTHER OBJECTIVE IS THE DE-
VELOPMENT OF SIMULATION PARAMETERS AND TECHNIQUES LEADING TO
THE SIMPLIFICATION OF TEST PROCEDURES FOR SPACECRAFT MATERIALS
RESEARCH.

GILES S. ATOMICS INTERNATL
VACUUM PUMPING TECHNIQUES FOR NUCLEAR EXPERIMENTS
=TEST ENG VOL.16,P.25-26 DEC.1966 1FIG

GIL6009P

1.EVALUATION 2.FACILITY 3.SPACE 4.NOMINAL 5.COMBINED 7.PUMP,
REACTORS 8.ENVIRO-CONTROL 9.HI-VAC,NUCLEAR

IN A VACUUM SYSTEM SHOWN IN THE ILLUSTRATION,THE DIFFUSION
PUMP SYSTEM WAS REPLACED BY 2 GETTER-ION PUMPS AND A TITANIUM
SUBLIMATOR. TEST CHAMBER PRESSURE WAS IMPROVED BY A DECADE AND
UTILITY FAILURES CEASED TO BE A PROBLEM. CONTAMINATION PROB-
LEMS WERE ALSO ELIMINATED. EXPERIENCE AT AI INDICATES THAT THE
SYSTEM IS PRACTICAL FOR A LESS THAN 10 TO THE MINUS 6 TORR,
10,000-HR TEST PROGRAM.

OUTMAN V. MCDONNELL CO
SIMULATION TESTING IN A SPACE ENVIRONMENT--AN ASSESSMENT
=JL.SPACECRAFT AND ROCKETS VOL.3,P.1697-1710 DEC.1966 105REF
=14FIG 4TABLES

OUT6002P

1.STUDY 2.SIMULATION,FACILITY 3.SPACE 4.NOMINAL 5.SINGLE
7.CHAMBER,PRESSURE-SYSTEM,GAGE,RADIATION-SOURCE,OPTICS 8.ENVI-
RO-MEAS 9.HI-VAC,CONTAMIN,SOLAR,ALBEDO,UL-TEMP

AN EXCELLENT SURVEY WHICH DISCUSSES TECHNIQUES,SUMMARIZES EX-
ISTING CAPABILITIES,AND REVIEWS PROJECTED IMPROVEMENTS IN
SPACE ENVIRONMENTAL TESTING. THE STATE-OF-THE-ART IS REFLECTED
IN A TABLE WHICH DESCRIBES 45 LARGE,OPERATIONAL SPACE SIMULA-
TION FACILITIES IN THE U.S.

SCHRUMPF LC. MCDONNELL
COMBINED ENVIRONMENTS ACHIEVED WITH EXCITER-SUPPORTED TEST
CHAMBER
=TEST ENG VOL.17,P.12-16 MAY 1967 8FIG

SCH7002P

1.DESIGN 2.FACILITY 3.SPACE 4.NOMINAL 5.COMBINED 7.CHAMBER,
HEATERS 8.ENVIRO-MEAS 9.VH-TEMP,VL-PRESS,RDM-VIBR

MCDONNELL LABORATORIES HAS DESIGNED A FACILITY COMBINING IN
ONE ENVELOPE THE COMBINED MAXIMUM CONDITIONS OF 25.9 G-RMS
RANDOM VIBRATION,2100 DEG F TEMPERATURE,AND 1.6MM HG PRES-
SURE. THIS INVOLVED THE FABRICATION OF A SPECIAL CHAMBER TO
INCLOSE THE MOVING ELEMENT OF THE EXCITER.

HIGH TEMPERATURE AND UNSPECIFIED TEMPERATURE

METZGER JW GENERAL ELEC
OXIDATION AND SUBLIMATION OF GRAPHITE IN SIMULATED RE-ENTRY
ENVIRONMENTS

MET7001R

=AIAA JL VOL.5,P.451-460 MAR.1967 12REF 14FIG 1TABLE

1.STUDY 2.PROTECTION 3.INDUCED 4.NOMINAL 5.SINGLE 7.SHIELD,
MATERIALS 8.ENVIRO-EFFECTS 9.REENTRY

INTEREST IN THE APPLICABILITY OF GRAPHITE AS A THERMAL SHIELD MATERIAL LED TO A DETAILED INVESTIGATION OF ITS THERMOCHEMICAL RESPONSE TO HYPERSONIC FLIGHT. AN EXPERIMENTAL PROGRAM WAS CONDUCTED USING ELECTRIC ARC FACILITIES TO GENERATE APPROPRIATE SIMULATION ENVIRONMENTS. DATA WERE OBTAINED OVER A BROAD RANGE OF MATERIAL SURFACE TEMPERATURES FROM 1200 DEG K UP TO THE SUBLIMATION VALUE. THE MATERIALS SELECTED FOR STUDY WERE ATJ GRAPHITE AND VAPOR-DEPOSITED PYROLYTIC GRAPHITE. BY VARYING THE TEST GAS(AIR) STAGNATION ENTHALPY IN A HYPERSONIC ARC TUNNEL FROM APPROX 5400 TO 13,000 BTU/LB OVER A SIGNIFICANT RANGE OF MODEL PRESSURE, MATERIAL DEGRADATION UNDERWENT A CHANGE FROM PREDOMINANTLY RATE-CONTROLLED OXIDATION TO DIFFUSION-CONTROLLED OXIDATION. PERFORMING TESTS IN AN ATMOSPHERIC FREE-JET ARC PLASMA FACILITY A STAGNATION ENTHALPY VALUES IN EXCESS OF 17,000 BTU/LB EXTENDED THE DEGRADATION PROCESS INTO THE SUBLIMATION REGIME. THE EXPERIMENTAL RESULTS ARE CORRELATED FOR THE RATE-CONTROLLED, DIFFUSION-CONTROLLED, AND SUBLIMATION REGIMES AS PROPOSED BY THE THEORIES OF SCALA AND SCALA-GILBERT. IN ADDITION TO IDENTIFYING THE DATA IN THE VARIOUS MASS-TRANSFER REGIMES, IT WAS NECESSARY TO INTERPRET THE NONCONTINUUM NATURE OF SOME OF THE TEST ENVIRONMENTS IN TERMS OF LOW REYNOLDS NUMBER CRITERIA. A CORRELATION TECHNIQUE IS DESCRIBED WHICH PROVIDES A MECHANISM FOR COMPARISON OF THE EXPERIMENTAL RESULTS WITH THE CONTINUUM THEORIES REFERRED TO PREVIOUSLY. CLOSE AGREEMENT IS SHOWN TO EXIST.

VARWIG RL AEROSPACE CORP
A 7-FT-DIAM SHOCK TUBE FOR TRANSONIC AND SUPERSONIC AERO-
DYNAMIC TESTING
=JL SPACECRAFT AND ROCKETS VOL.3,P.1809-1811 DEC.1966 4REF
=2FIG

VAR6001R

1.DESIGN 2.FACILITY 3.INDUCED 4.NOMINAL 5.SINGLE 7.SHOCK-TUBE
8.ENVIRO-MEAS 9.AERODYNAMIC

DESCRIBES THE LARGE DIAMETER SHOCK TUBE WHICH PROVIDES A SHORT-DURATION FACILITY TO PRODUCE SUBSONIC, TRANSONIC, AND LOW SUPERSONIC FLOWS WHEREIN THE INSTRUMENTATION SYSTEMS AND MODELS DESIGNED FOR A HYPERSONIC SHOCK TUNNEL COULD BE SHIFTED FOR TESTING IN THE LOW-SPEED RANGE. THE BASIS FOR PREDICTING THE SHOCK MACH NUMBER, FLOW CONDITIONS, AND TESTING TIME AND THE EXPERIMENTS FOR CONFIRMING THESE PREDICTIONS ARE PRESENTED.

ZYSK ED ENGLEHARD INDUS

ZYS7001R

THERMOCOUPLE CALIBRATION--METHODS ABOVE 1500 DEG C
=INSTR.TECH VOL.14,P.49-54 JAN.1967 15REF 3FIG 1TABLE

1.DESIGN 2.INSTRUMENT 3.GENERAL 4.NOMINAL 5.SINGLE 7.SENSOR-
TEMP,CALIBR-EQUIP 8.CALIBRATION 9.UH-TEMP

THE CALIBRATION OF HIGH TEMPERATURE THERMOCOUPLES IN TERMS OF
THE INTERNATIONAL PRACTICAL TEMPERATURE SCALE CAN BE DONE IN
SEVERAL WAYS--1.DETERMINATION OF EMF AT DEFINED POINTS OF MET-
ALS,2.COMPARISON CALIBRATION AGAINST INTERPOLATION INSTRUMENTS
SPECIFIED IN THE IPTS,3.COMPARISON CALIBRATION OF A THERMO-
COUPLE WITH A STANDARD THERMOCOUPLE OF THE SAME MATERIAL.

RANDOM VIBRATION AND UNSPECIFIED VIBRATION

ARONE RA WYLE LAB

ARO6001T

CONTROL TECHNIQUES FOR MULTI-SHAKER VIBRATION SYSTEMS
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.3,P.147-155 5FIG

1.EVALUATION 2.METHOD 3.INDUCED 4.NOMINAL 5.SINGLE 7.SHAKER,
CNTRL-SYSTEM 8.ENVIRO-CONTROL 9.VIBR,RDM-VIBR

THE PROBLEMS ASSOCIATED WITH THE CONTROL OF A MULTI-SHAKER OP-
ERATION DURING SINUSOIDAL AND RANDOM VIBRATION TESTING ARE
COMPLEX BECAUSE OF THE SEVERE,UNPREDICTABLE,AND SOMETIMES NON-
LINEAR EFFECTS OF LARGE STRUCTURES UNDER TEST,AS WELL AS POS-
SIBLE DIFFERENCES IN THE INDIVIDUAL SHAKER SERVO COMPONENTS.
THIS PAPER DISCUSSES POSSIBLE METHODS FOR PERFORMING THESE
TESTS AND OUTLINES REQUIREMENTS FOR EQUIPMENT AND BASIC OPER-
ATING CHARACTERISTICS OF AN AUTOMATIC VIBRATION CONTROL SYSTEM
USED FOR AN EIGHT-SHAKER VIBRATION TEST PROGRAM.

FRANKEN PA BOLT BERANEK

FRA6002T

COMPARISON OF MARINER ASSEMBLY-LEVEL AND SPACECRAFT-LEVEL
VIBRATION TESTS

=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.3,P.27-38 6REF 9FIG
=1TABLE

1.EVALUATION 2.METHOD 3.INDUCED 4.NOMINAL 5.SINGLE 7.MARINER,
ELECTRONIC,SHAKER 8.ENVIRO-CONTROL 9.VIBR,RDM-VIBR

RESULTS ARE PRESENTED OF A STUDY OF VIBRATION DATA OBTAINED BY
JPL IN TWO SERIES OF TESTS OF AN ELECTRONIC ASSEMBLY FROM THE
MARINER C SPACECRAFT. IN ONE SERIES,THE ASSEMBLY WAS MOUNTED
IN A CONVENTIONAL VIBRATION TEST FIXTURE. IN THE OTHER,THE AS-
SEMBLY WAS MOUNTED IN THE SPACECRAFT. THE RESULTS OF THE STUDY
CAN BE DIVIDED INTO TWO CATEGORIES--THOSE REGARDING THE AVER-
AGING OF LARGE COLLECTIONS OF VIBRATION DATA,AND THOSE CON-
CERNING THE DIFFERENCES BETWEEN ASSEMBLY-LEVEL AND SPACECRAFT-
LEVEL VIBRATION TESTS. SOME RECOMMENDATIONS ARE ALSO GIVEN FOR
FUTURE RANDOM VIBRATION TESTS OF AEROSPACE STRUCTURES.

MCCAA R MARTIN CO

MCC6001T

FLIGHT LEVEL VIBRATION TESTING OF A LIFTING BODY REENTRY
VEHICLE
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS.SYMPOSIUM,36TH,OCT.1966 PT.3,P.113-118 8FIG

1.DESIGN 2.METHOD 3.INDUCED 4.NOMINAL 5.SINGLE 7.STRUCTURE,
SHIELD,TRANSDUCER,SHAKER,SATURN 8.ENVIRO-CONTROL 9.RDM-VIBR

VIBRATION TESTING OF SPACECRAFT TO THE LEVELS OF THE BOOSTER
INTERFACE SPECTRUM WHILE SUPPORTED BY RIGID FIXTURES IS DEEMED
UNREALISTIC IN THAT STRUCTURAL FAILURES MAY BE INDUCED WHICH
WOULD NOT OCCUR ON THE MORE COMPLIANT SUPPORT OF THE BOOSTER.
LIMITING OF THE SHAKER INPUT FORCES AT THE VEHICLE SUPPORT
POINTS TO DESIGN LIMIT LOADS PRECLUDES THIS TYPE OF FAILURE.
RANDOM VIBRATION TESTS CONDUCTED ON THE PRIME SV-5D LIFTING
BODY UTILIZED THIS FORCE LIMITING APPROACH AND THE TECHNIQUES
EMPLOYED ARE DESCRIBED.

PATRICK TJ UNIV COLLEGE, LONDON

PAT7001T

SWEEP SINE WAVE SIMULATION OF RANDOM VIBRATION AND ITS EFFECT
ON DESIGN WITH PARTICULAR REFERENCE TO SPACE ROCKETS
=JL.SOUND AND VIBR VOL.5,P.37-41 JAN.1967 5REF 2FIG

1.THEORY 2.SIMULATION 3.INDUCED 4.NOMINAL 5.SINGLE 7.ROCKET
8.ENVIRO-CONTROL 9.RDM-VIBR

DISCUSSES FORMULAE FOR THE LEVEL AND DURATION OF A SINE WAVE
TEST AND HOW THE UNCERTAINTIES SURROUNDING THE ASSUMPTIONS
MADE WILL LEAD TO WEIGHT PENALTIES IF RANDOM VIBRATION IS NOT
USED FOR PROOF OF DESIGN.

TUSTIN W TUSTIN INST OF TECH

TUS7004T

THE PLANNING OF AEROSPACE VIBRATION TESTS AND PROGRAMS
=TEST ENG VOL.17,P.18-19+ MAY 1967 19REF

1.ORGANIZATION 2.ENGR-PRACTICE 3.INDUCED 4.NOMINAL 5.SINGLE
6.MIL-STD-810 9.VIBR,RDM-VIBR

EXCERPTS FROM A PAPER OF THE SAME TITLE PRESENTED BY ROY W.
MUSTAIN AT THE 1965 MEETING OF THE INSTITUTE OF ENVIRONMENTAL
SCIENCES. IT OUTLINES THE VIBRATION TEST PROGRAMS THAT WILL BE
REQUIRED BY AN AEROSPACE PROGRAM SUCH AS THE MANNED MARS
MISSION.

UNGAR EE BOLT BERANEK

UNG6001T

ANALYSIS OF VIBRATION DISTRIBUTIONS IN COMPLEX STRUCTURES
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS.SYMPOSIUM,36TH,OCT.1966 PT.5,P.41-53 14REF 6FIG
=1TABLE

1.THEORY 2.METHOD 3.INDUCED 4.NOMINAL 5.SINGLE 7.STRUCTURE
8.ENVIRO-EFFECTS 9.RDM-VIBR

AN INTRODUCTION TO THE STATISTICAL ENERGY ANALYSIS APPROACH
WHICH PROVIDES A RELATIVELY SIMPLE MEANS FOR UNDERSTANDING AND
ESTIMATING THE MOST SIGNIFICANT PROPERTIES OF MULTI-MODAL RAN-
DOM VIBRATIONS OF COMPLEX STRUCTURES. THE THEORETICAL BASIS
FOR THIS APPROACH IS SUMMARIZED,SOME INSIGHTS RESULTING FROM
ITS USE ARE PRESENTED,AND SOME APPLICATIONS TO SPACECRAFT VI-
BRATION ANALYSIS AND TESTING ARE DISCUSSED.

SINUSOIDAL VIBRATION

BAKER WE ROCKETDYNE
DYNAMIC ANALYSIS OF CONTINUUM BODIES BY DIRECT STIFFNESS
METHOD
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.5,P.55-68 11REF 10FIG
=6TABLES

BAK6001U

1.STUDY 2.METHOD 3.INDUCED 4.NOMINAL 5.SINGLE 7.STRUCTURE
8.ENVIRO-EFFECTS 9.VIBR

AXISYMMETRIC AND PLANE STRESS-STRAIN FORMULATIONS,WITH THE ASSOCIATED COMPUTER PROGRAMS,HAVE BEEN DEVELOPED. THE ANALYSIS WAS DEVELOPED USING VISCOUS DAMPING AND THE ASSUMPTION THAT CLASSICAL MODES EXIST. THE UNDAMPED FREQUENCIES AND MODE SHAPES ARE FIRST CALCULATED,THEN USED TO UNCOUPLE THE DAMPED EQUATIONS OF MOTION BY DIAGONALIZATION OF THE MASS, DAMPING AND STIFFNESS MATRICES. THUS,SINGLE-DEGREE-OF-FREEDOM MODAL RESPONSE EQUATIONS ARE FORMED AND SOLVED FOR THE RESPONSE CONTRIBUTION OF EACH MODE. THROUGH SUPERPOSITION OF EACH MODAL CONTRIBUTION COUPLED WITH A TRANSFORMATION BACK TO THE ORIGINAL COORDINATE SYSTEM,THE RESPONSE TO AN ARBITRARY FORCING FUNCTION IS DETERMINED. THEORETICAL DEVELOPMENT,CORRELATION STUDIES, APPLICATIONS AND SOME OF THE LIMITATIONS OF THE ANALYSIS ARE DISCUSSED.

BLASINGAME W. NAVY MARINE ENG LAB
DEVELOPMENT OF DAMPED MACHINERY FOUNDATIONS
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.4,P.81-94 11REF 12FIG
=1TABLE

BLA6002U

1.DESIGN 2.MITIGATION,MEASUREMENT 3.INDUCED 4.NOMINAL 5.SINGLE
7.ISOLATOR,ELASTOMER,SHIP 8.ENVIRO-EFFECTS 9.DAMPING

TO OBTAIN A REDUCTION IN RADIATED NOISE,IT IS PROPOSED THAT FOUNDATIONS BE FABRICATED FROM HIGHLY DAMPED LAMINATED PLATES AND A PIPE-WITHIN-A-PIPE CONFIGURATION SEPARATED BY A VISCO-ELASTIC MATERIAL. THE PROGRAM HAS LED TO A GENERAL SPECIFICATION OF TEST SAMPLES FOR DAMPING EVALUATION,ANALYTICAL MEANS FOR PREDICTING DAMPING AND DETERMINING COMPOSITE BEHAVIOR,DEVELOPMENT OF A METHOD FOR REASONABLY DETERMINING THE DYNAMIC PROPERTIES OF A PARTICULAR VISCOELASTIC MATERIAL,AND THE DESIGN AND EVALUATION OF LAMINATED FOUNDATIONS FOR EFFECTIVENESS IN REDUCING VIBRATION TRANSMISSION.

CINELLI G. ARGONNE

CIN6001U

DYNAMIC VIBRATIONS OF THICK-WALLED ELASTIC ANISOTROPIC CYLINDERS AND SPHERES WITH INTERNAL DAMPING
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVIRONMENTALS, SYMPOSIUM, 36TH, OCT. 1966 PT. 5, P. 107-118 20REF

1. THEORY 2. EFFECTS, MEASUREMENT 3. INDUCED 4. NOMINAL 5. SINGLE
7. STRUCTURE-SHELL 8. ENVIRO-EFFECTS 9. VIBR, TORSIONAL-VIBR

A NEW FINITE HANKEL TRANSFORM IS USED TO FIND THE TRANSIENT DISPLACEMENT AND STRESSES IN THICK ELASTIC CYLINDERS AND SPHERES COMPOSED OF MATERIAL WITH TRANSVERSE CURVILINEAR ISOTROPY AND INTERNAL VISCOUS DAMPING FOR THE FOLLOWING PROBLEMS--(A) PLANE STRAIN MOTION OF AN INFINITELY LONG CIRCULAR CYLINDRICAL SHELL, (B) TORSIONAL MOTION OF A FINITE CIRCULAR CYLINDRICAL SHELL, AND (C) RADIALLY SYMMETRIC MOTION OF A SPHERICAL SHELL. THE DYNAMIC LOADS ON THE SURFACES ARE TAKEN AS ARBITRARY FUNCTIONS OF SPACE (TORSIONAL CASE ONLY) AND TIME. IT IS SHOWN THAT THE PROBLEMS OF THE SOLID BODY, THE THIN SHELL, AND CAVITY IN AN INFINITE MEDIUM CAN BE OBTAINED FROM THE THICK SHELL SOLUTION AS LIMITING CASES. SPECIALIZING THE SURFACE TRACTION TO STANDARD FORMS SUCH AS AN IMPULSE OR A SINUSOID, THE FREE, HARMONIC, AND STATIC MOTIONS ARE RECOVERED. PHYSICAL QUANTITIES SUCH AS RESONANCE AND MECHANICAL IMPEDANCE ARE DERIVED AND STUDIED. USING THE DISPLACEMENT EQUATIONS, IT IS SHOWN THAT THE RADIALLY SYMMETRIC MOTION IS ANALOGOUS TO THE PLANE-STRAIN MOTION OF THE CYLINDER. THE RESULTS FOR ISOTROPIC BODIES ARE FOUND BY SPECIFYING CERTAIN VALUES FOR THE ELASTIC CONSTANTS. AN EXTENDED WEBER TRANSFORM IS ALSO INTRODUCED, PERMITTING SOLUTION OF INFINITE MEDIA PROBLEMS IN A MANNER WHICH IS MORE DIRECT THAN EXISTING TECHNIQUES.

FOGELSON S. MARQUARDT CORP

FOG6001U

DIGITAL ANALYSIS OF FATIGUE DAMAGE TO A MULTI-MODAL SYSTEM
SUBJECTED TO LOGARITHMICALLY SWEPT SINUSOIDAL VIBRATION
SPECTRA
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVIRONMENTALS, SYMPOSIUM, 36TH, OCT. 1966 PT. 5, P. 17-40 3REF 12FIG
=3 TABLES

1. THEORY 2. METHOD, EFFECTS 3. INDUCED 4. AGING 5. SINGLE 7. STRUCTURE, COMPUTER 8. ENVIRO-EFFECTS 9. VIBR

IT IS ASSUMED THAT THE STRUCTURE IS A DAMPED SPRING-MASS SYSTEM WITH EACH MASS HAVING THREE TRANSLATIONAL AND THREE ROTATIONAL DEGREES OF FREEDOM. ONLY LUMPED MASS STRUCTURES ARE CONSIDERED. IT IS FURTHER ASSUMED THAT THE RESONANT AMPLIFICATION FACTORS AND THE OVERALL DAMPING RATIO OF THE STRUCTURE ARE KNOWN. BASED ON THIS ANALYSIS, THE RESULTING DIGITAL COMPUTER PROGRAM YIELDS THE DAMAGE ACCUMULATED IN EACH MODE OF RESPONSE FOR EACH AXIS OF APPLIED EXCITATION, THE TOTAL DAMAGE ACCRUING FOR EACH INPUT AXIS, AND THE TOTAL DAMAGE CAUSED BY SWEEPING THE SPECTRUM A GIVEN NUMBER OF TIMES.

JONES DIG AF MATERIALS LAB

JON6001U

DAMPING OF STRUCTURES BY VISCOELASTIC LINKS
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.4,P.9-24 3REF 18FIG

1.STUDY 2.MITIGATION 3.INDUCED 4.NOMINAL 5.SINGLE 7.STRUCTURE
8.ENVIRO-EFFECTS 9.DAMPING

INVESTIGATIONS HAVE BEEN MADE OF THE RESPONSE OF PARALLEL BEAMS OF DIFFERENT FLEXURAL RIGIDITIES AND WEIGHTS JOINED BY VISCOELASTIC LINKS. ATTENTION HAS BEEN CONCENTRATED ON A PAIR OF PARALLEL CLAMPED-CLAMPED BEAMS WITH A VISCOELASTIC LINK JOINING THE CENTERS. A THEORY OF THE RESPONSE OF THE SYSTEM IS DEVELOPED AND IT IS SHOWN THAT SUBSTANTIAL AMOUNTS OF DAMPING CAN BE INTRODUCED INTO THE BEAMS BY PROPER CHOICE OF THE LINK STIFFNESS, PROVIDED THAT A NATURAL FREQUENCY OF ONE BEAM IS NOT IDENTICAL TO (OR CLOSE TO) ANY NATURAL FREQUENCY OF THE OTHER BEAM, IN WHICH CASE NO DAMPING CAN BE ACHIEVED NO MATTER WHAT THE EXCITATION MAY BE. AN EXPERIMENTAL INVESTIGATION IS DESCRIBED IN WHICH THE THEORY IS VERIFIED FOR LINKS MADE OF ONE COMMERCIALY AVAILABLE VISCOELASTIC MATERIAL.

JONES E NBS

JON7001U

IMPROVED TRANSFER STANDARD FOR VIBRATION PICKUPS
=ACoust.SOC.AM.JL VOL.41,P.354-357 FEB.1967 7REF 2FIG
=3TABLES

1.DESIGN 2.INSTRUMENT 3.INDUCED 4.NOMINAL 5.SINGLE 7.CALIBR-
EQUIP 8.CALIBRATION 9.LF-VIBR,HF-VIBR,VHF-VIBR

DESCRIBES A VIBRATION TRANSFER STANDARD DESIGNED TO PROVIDE COMPARISON CALIBRATIONS OF PICKUPS WITH MINIMUM DEGRADATION. FEATURES OF THE DESIGN ARE THE USE OF A CERAMIC HOUSING OF A STIFF,LIGHT,GLOSSY MATERIAL,PROVISION OF A MEANS FOR EVALUATING THE QUALITY OF THE MOTION BY THE USE OF THREE INTEGRAL ACCELEROMETERS ORIENTED PARALLEL TO THE NOMINAL DIRECTION OF MOTION,AND DESIGN OF THE GEOMETRY TO MINIMIZE DIFFERENCES IN MOTION BETWEEN THE PICKUP BEING CALIBRATED AND THE STANDARD. THE USEFUL FREQUENCY RANGE IS 10-10000 HZ.

KERFOOT RE SPECTRAL DYNAMICS CORP

KER6003U

A SYSTEM THAT WORKS--MECHANICAL IMPEDANCE,PART 2
=ENVIR.QUAR VOL.12,P.36-39 DEC.1966 7FIG

1.DESIGN 2.MEASUREMENT 3.INDUCED 4.NOMINAL 5.SINGLE 7.COMPUT-
ER,TEST-EQUIP 8.ENVIRO-MEAS 9.IMPEDANCE

THIS CONCLUDING ARTICLE OF A TWO-PART SERIES DESCRIBES THE DEVELOPMENT OF A SYSTEM THAT OVERCOMES THE TREMENDOUS PROBLEMS OF DETECTION AND ANALYSIS THAT HAS STOOD IN THE WAY OF WIDER UTILIZATION OF THE VERY USEFUL MECHANICAL IMPEDANCE TECHNIQUE. THE KEY CONCEPTS--AUTOMATIC,CONTINUOUS.

MCCANN RF BOEING

MCC6002U

THE HOW OF HELICOPTER VIBRATION TESTING
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.3,P.71-82 3REF 14FIG
=1TABLE

1.DESIGN 2.SIMULATION 3.INDUCED 4.NOMINAL 5.SINGLE 7.DATA-
SYSTEM,AIRCRAFT,SHAKER 8.ENVIRO-EFFECTS 9.LF-VIBR,HF-VIBR

WITH THE AIRCRAFT SUSPENDED BY STEEL SPRINGS,FREQUENCY SWEEPS
ARE MADE FROM 6 TO 20 CPS AND RESONANT POINTS ARE LOCATED.
INSTRUMENTATION ALLOWS DIRECT X-Y PLOTTING OF PHASE AND AMPLI-
TITUDE VS FREQUENCY WITH IBM CARD PUNCH RECORDING OF SHAKER LO-
CATIONS,INPUT FORCE,PERIOD OF FREQUENCY,AIRCRAFT CONFIGURA-
TION,PHASE ANGLE AND AMPLITUDES OF DISPLACEMENT. IT IS NOT
THE INTENT IN THIS PAPER TO BE ALL-INCLUSIVE BUT RATHER TO
PRESENT THE HISTORY AND CONTEMPORARY APPROACH TO GROUND VIBRA-
TION TESTING OF HELICOPTERS AT THE BOEING COMPANYS VERTOL
DIVISION.

MCGREGOR HM HONEYWELL

MCG7001U

MECHANICAL IMPEDANCE,III--IMPEDANCE MEASUREMENT TECHNIQUES
=ENVIR.QUAR VOL.13,P.40-44 MAR.1967 5FIG 1TABLE

1.EVALUATION 2.MEASUREMENT 3.INDUCED 4.NOMINAL 5.SINGLE
7.GAGE-STRAIN,TRANSDUCER,ACCELEROMETER 8.ENVIRO-EFFECTS
9.IMPEDANCE

AN UNDERSTANDING OF THE BASIC CHARACTERISTICS AND LIMITATIONS
OF TRANSDUCERS AND ANALYSIS EQUIPMENT IS NECESSARY FOR RELI-
ABLE IMPEDANCE MEASUREMENTS--SPECIFICALLY,DEVICES FOR MEAS-
URING FORCE,VELOCITY AND PHASE. THE INHERENT ERRORS IN THESE
DEVICES AND THEIR CONTRIBUTION TO THE OVER-ALL SYSTEM ERROR,
WHICH MUST BE DETERMINED FOR PROPER INTERPRETATION OF THE
RESULTING IMPEDANCE PLOT ARE EXAMINED IN THIS THIRD ARTICLE
DEALING WITH MECHANICAL IMPEDANCE.

NORTH RG NORTH AM AV

NOR6001U

MULTIPLE SHAKER GROUND VIBRATION TEST SYSTEM DESIGNED FOR
XB-70A
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
=RONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.3,P.55-70 7REF 16FIG

1.DESIGN 2.SIMULATION 3.INDUCED 4.NOMINAL 5.SINGLE 7.AIRCRAFT,
SHAKER,DATA-SYSTEM 8.ENVIRO-EFFECTS 9.LF-VIBR

EQUIPMENT DEVELOPED FOR AND EMPLOYED IN THE XB-70A GROUND VI-
BRATION TEST,INCLUDING THE 24-SHAKER VIBRATION EXCITATION SYS-
TEM,THE 100-CHANNEL DATA ACQUISITION SYSTEM CAPABLE OF AUTO-
MATIC RECORDING ON IBM PUNCHED CARDS,AND THE LOW-FREQUENCY AIR
VEHICLE SUSPENSION SYSTEM,ARE BRIEFLY DESCRIBED. SPECIAL OPER-
ATING PROCEDURES ARE ALSO DESCRIBED.

SALTER JP RARDE

SAL5004U

THE INTERPRETATION OF VIBRATION PHENOMENA--THE PRACTICE
=ENVIR.ENG NO.17,P.23+ NOV.1965 5FIG

1.THEORY 2.MEASUREMENT 3.INDUCED 4.NOMINAL 5.SINGLE 8.ENVIRO-EFFECTS 9.VIBR

THE FOURTH AND LAST IN A SERIES OF ARTICLES. PARTS 2 AND 3 DEALT WITH POINT MEASUREMENTS. PART 4 CONSIDERS THE SIMPLER CASES OF TRANSFER MEASUREMENTS, THOSE IN WHICH THE FORCE ACTING AT ONE POINT IN A SYSTEM ARE RELATED TO THE RESULTING MOTION AT ANOTHER POINT, THAT IS, TRANSFER IMPEDANCES AND TRANSFER MOBILITIES.

SCHLOSS F WILCOXON RES

SCH7001U

OBTAINING PURE LINEAL MOTION OVER AN EXTENDED FREQUENCY RANGE WITH CONVENTIONAL VIBRATION GENERATORS
=ENVIR.QUAR VOL.13,P.55 MAR.1967 1FIG

1.DESIGN 2.METHOD 3.INDUCED 4.NOMINAL 5.SINGLE 7.SHAKER, TRANSDUCER 8.ENVIRO-CONTROL 9.VIBR

TRANSVERSE SENSITIVITY OF TRANSDUCERS, WHICH ARE OFTEN TESTED AT A VERY LOW FREQUENCY, GENERALLY IS STATED WITHOUT REFERENCE TO FREQUENCY. IT HAS BEEN FOUND THAT THE TRANSVERSE SENSITIVITY USUALLY IS FREQUENCY DEPENDENT, AND THAT A TRANSDUCER WITH A SPECIFIED LOWER TRANSVERSE SENSITIVITY MAY NOT NECESSARILY BE THE BETTER CHOICE.

SHURTLEFF WW SANDIA CORP

SHU6001U

AVERAGING FUNDAMENTAL VIBRATION CONTROL SIGNALS--A THEORETICAL STUDY
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVIRONMENTS, SYMPOSIUM, 36TH, OCT.1966 PT.3,P.139-146 3REF 9FIG
=1TABLE

1.STUDY 2.METHOD 3.INDUCED 4.NOMINAL 5.SINGLE 7.FILTER,AMPLIFIER,SHAKER 8.ENVIRO-CONTROL 9.VIBR

PRESENTS A THEORETICAL EVALUATION OF THREE METHODS OF VIBRATION FEEDBACK CONTROL SIGNAL AVERAGING. THE EVALUATION CRITERIA EMPLOYED ARE PHASE SENSITIVITY, FUNDAMENTAL AVERAGING, AND ACCURACY AND LINEARITY OF AVERAGE. EXPERIMENTAL RESULTS CONFIRM THE THEORETICAL SUPERIORITY OF THE TRACKING FILTER AND OPERATIONAL AMPLIFIER AVERAGING TECHNIQUE OVER RESISTIVE AND TIME-SHARING AVERAGING TECHNIQUES.

STEIN P ARIZONA STATE UNIV

STE6002U

VIBRATION ANALYSIS
=INSTR.AND CONT.SYS VOL.39,P.124-129 DEC.1966 5FIG 3TABLES

1.THEORY 2.MEASUREMENT 3.INDUCED 4.NOMINAL 5.SINGLE 7.MODEL 8.ENVIRO-EFFECTS 9.VIBR

VIBRATION HAS BEEN DEFINED IN VERY SPECIFIC TERMS. METHODS OF INTERPRETING DATA WERE DERIVED FROM THE CONSIDERATION OF A SIMPLE SYSTEM ON PURELY THEORETICAL BASES. THESE METHODS WERE EXTENDED TO THE GENERAL CASE THROUGH A BRIEF DISCUSSION OF EXPERIMENTAL MECHANICAL IMPEDANCE TECHNIQUES. A SIMPLE APPLICATION OF THESE CONCEPTS TO A LINEARITY VIBRATING SYSTEM EXCITED BY A ROTATING UNBALANCE WAS TREATED. THIS TREATMENT BROUGHT TOGETHER A NUMBER OF SECTIONS IN THE TEXT TO PROVIDE A COMPLETE SOLUTION TO THE PROBLEM.

TAUSCHER RC TEAM CORP

TAU7001U

AIR BEARINGS FOR VIBRATION EXCITERS
=SOUND AND VIBR VOL.1,P.23-25 JAN.1967 4REF 6FIG

1.EVALUATION 2.INSTRUMENT 3.INDUCED 4.NOMINAL 5.SINGLE
7.ACCELEROMETER,CALIBR-EQUIP,BEARINGS 8.CALIBRATION 9.HF-
VIBR,LF-VIBR,CROSS-TALK

TRANSVERSE MOTION CAN BE REDUCED TO A MINIMUM ON VIBRATION EX-
CITERS FOR CALIBRATING ACCELEROMETERS BY THE USE OF AIR BEAR-
INGS ON THE MOVING ELEMENT OF THE EXCITER. CONVENTIONAL EX-
CITERS CAN BE IMPROVED BY SUCH A MODIFICATION.

TOLLETH FC NORTH AM AV

TOL6002U

DESIGN TECHNIQUES FOR HORIZONTAL DRIVERS
=US DIRECTOR OF DEFENSE SHOCK,VIBRATION AND ASSOCIATED ENVI-
RONMENTS,SYMPOSIUM,36TH,OCT.1966 PT.3,P.101-112 7REF 13FIG

1.DESIGN 2.FACILITY 3.INDUCED 4.NOMINAL 5.SINGLE 7.SHAKER
8.ENVIRO-CONTROL 9.LF-VIBR,HF-VIBR

DESIGN REQUIREMENTS, ANALYSIS FOR A LARGE CAST HORIZONTAL
DRIVER USED WITH A LING-249 VIBRATION EXCITER, AND PERTINENT
DATA FOR USE WITH THE DESIGN ARE PRESENTED. THE REASONING BE-
HIND COMPROMISES IN DESIGN IS EXAMINED SO THAT A PARTICULAR
DESIGN MAY BE USED FOR APPLICATION TO OTHER PROBLEMS. A PRAC-
TICAL ANALYSIS IS OFFERED FOR A SINGLE- AND TWO-DEGREE-OF-
FREEDOM DRIVER AND SHAKER SYSTEM WHERE THE STRUCTURAL MEMBERS,
AS INDIVIDUAL UNITS AND AS A WHOLE, EMPLOY CONCLUSIONS DE-
RIVED FROM UNIT ANALYSIS. DATA RECORDED DURING THE DYNAMIC
EVALUATION OF THE DRIVER AND SHAKER UNITS INDICATE THE STRONG
POINTS AND SHORTCOMINGS OF DESIGN. THE DATA OBTAINED ARE IN
THE FORM OF GS VS FREQUENCY PLOTS THAT REVEAL VARIOUS FORCE
LEVELS AND STRUCTURAL MEMBERS OF THE DRIVER IN A LOADED AND
UNLOADED CONDITION.

TUSTIN W TUSTIN INST OF TECH

TUS6011U

ENFORCING VIBRATION TESTING STANDARDS
=TEST ENG VOL.16,P.28-29 NOV.1966

1.ORGANIZATION 2.ENGR-PRACTICE 3.INDUCED 4.NOMINAL 5.SINGLE
6.SC-4452 7.TEST-LAB,QUALITY-CNTRL 9.VIBR

SANDIA CORPORATION IS USED AS AN EXAMPLE OF AN ORGANIZATION
WHICH CORRECTED A LACK OF STANDARDIZATION AMONG ITS SUPPLIERS.
THIS WAS ACCOMPLISHED THROUGH USE OF SC-4452(SANDIA CORPOR-
ATION STANDARD ENVIRONMENTAL TEST METHODS), COMPREHENSIVE
SURVEYS OF LABORATORIES SEEKING APPROVAL, AND INSPECTIONS
AFTER CERTIFICATION.

TUSTIN W TUSTIN INST TECH

TUS7002U

MODIFYING SHAKER SERVOS FOR NEWER SINE TEST SPECIFICATIONS
=TEST ENG VOL.17,P.24-27 MAR.1967 3REF 4FIG

1.INFORMATION 2.FACILITY 3.INDUCED 4.NOMINAL 5.SINGLE
7.SHAKER,CONTRL-SYSTEM 8.ENVIRO-CONTROL 9.VIBR

A BRIEF DESCRIPTION OF A SYSTEM USED BY C.A.PIPPIN,DOW CHEMI-
CAL CO,GOLDEN,COLO, FOR MODIFYING A SHAKER SERVO. VOLTAGE
DIVIDERS SWITCHED INTO THE ACCELEROMETER SIGNAL PATH AT AP-
PROPRIATE FREQUENCIES ENABLE THE VIBRATION LEVEL TO FOLLOW A
COMPLEX GRAPH.

WAMBSGANSS MW ARGONNE

WAM6001U

METHOD FOR IDENTIFYING AND EVALUATING LINEAR DAMPING MODELS
IN BEAM VIBRATIONS
=US DIRECTOR OF DEFENSE SHOCK, VIBRATION AND ASSOCIATED ENVI-
=RONMENTS, SYMPOSIUM, 36TH, OCT. 1966 PT. 4, P. 65-74 2REF 6FIG

1. STUDY 2. MITIGATION, METHOD 3. INDUCED 4. NOMINAL 5. SINGLE
7. STRUCTURE, MODEL, REACTORS 8. ENVIRO-EFFECTS 9. DAMPING

THE TECHNIQUE INVOLVES A COMPARISON OF THE EXPERIMENTALLY DE-
TERMINED RATIO OF FIRST TO SECOND MODE MAGNIFICATION FACTORS,
RELATED TO A COMMON POINT ON THE BEAM, WITH THE CONSTANT VAL-
UES OF THIS RATIO CORRESPONDING TO PURE FORMS OF THE PROPOSED
DAMPING. THIS METHOD IS ILLUSTRATED BY APPLICATION TO THE MOD-
ELING OF THE RESPONSE OF A CLUSTER OF CANTILEVERED BEAMS
CLAMPED TOGETHER AT THE BASE. THIS MODEL IS BEING EMPLOYED IN
THE PRELIMINARY ANALYSIS OF THE INTERACTION EFFECTS OF VIBRA-
TING FUEL RODS IN A NUCLEAR REACTOR CORE. DAMPING MODELS ARE
IDENTIFIED AND CURVES OF DAMPING COEFFICIENTS AS A FUNCTION OF
CLUSTER SIZE ARE PRESENTED.

MISCELLANEOUS ENVIRONMENTS

HERTZLER RG MCDONNELL CO

HER7001W

MARTIAN SAND AND DUST STORM EXPERIMENTATION
=JL. SPACECRAFT AND ROCKETS VOL. 4, P. 284-286 FEB. 1967 4REF
=4FIG 1TABLE

1. STUDY 2. SIMULATION, EFFECTS 3. PLANETARY 4. NOMINAL 5. COMBINED
6. MIL-STD-810A 7. CHAMBER, PLATING 8. ENVIRO-EFFECTS 9. DUST, WIND,
LO-PRESS, VL-TEMP

THE SIMULATION FACILITY, CAPABLE OF SIMULATING THE GAS, THERMAL,
DUST STORM, WIND AND PRESSURE ENVIRONMENTS OF MARS, WAS DEVEL-
OPED BY MODIFYING AN EXISTING CHAMBER WITH A 14X14X35 FT
WORKING SPACE. A SERIES OF EXPERIMENTS WAS DIRECTED TOWARD OB-
TAINING THE THRESHOLD VELOCITY AT WHICH SAND AND DUST PARTI-
CLES WOULD BECOME AIRBORNE. THE FACILITY WAS THEN USED TO
EVALUATE THE ABRASIVENESS OF THE STORMS ON CANDIDATE THERMAL
CONTROL COATINGS FOR MARTIAN LANDERS.

RELIABILITY

GRIFFIN NB SIG R AND D ESTAB

GRI7001Y

ENGINEERING FOR RELIABILITY
=ENVIR. ENG NO. 24, P. 11-20 JAN. 1967 9REF 6FIG 12TABLES

1. PHILOSOPHY 2. ENGR-PRACTICE 3. GENERAL 4. LIFE 5. SINGLE
7. ELECTRONIC, COMPONENT, RELIABILITY 8. ENVIRO-EFFECTS

A REVIEW ARTICLE ON THE CURRENT THINKING ON RELIABILITY OF
ELECTRONIC COMPONENTS AND MICROELECTRONIC UNITS, BOTH IN
GREAT BRITAIN AND THE U.S.

ENGINEERING PRACTICES

GILLARD LF RAF GIL6008Z
THE CORRELATION OF SERVICE DEFECTS AND DEVELOPMENT EXPERIENCE
=ENVIR.ENG NO.18,P.21-24 JAN.1966

1.PHILOSOPHY 2.ENGR-PRACTICE 3.GENERAL 7.AIRCRAFT

THE FIRST PART OF THIS PAPER CONSIDERS BRIEFLY THE CASE OF THE RAF CURRENT ALL-WEATHER FIGHTER TO SHOW WHAT HAPPENED DURING DEVELOPMENT AND IN RAF USAGE. THE SECOND DESCRIBES GENERALLY THE METHODS OF OBTAINING INFORMATION ON DEFECTS, AND THE THIRD PART THE WAYS IN WHICH THE RAF PASSES THE IMPORTANT CONCLUSIONS BACK TO INDUSTRY.

WYLE FS WYLE LAB WYL7001Z
IN TESTING--A NEW ERA
=TEST ENG VOL.17,P.12-17+ JAN.1967 5FIG

1.PHILOSOPHY 2.ENGR-PRACTICE 3.SPACE 4.NOMINAL 5.SINGLE 7.FACILITY,PERSONNEL,MODEL

A SURVEY OF THE MAJOR DEVELOPMENTS IN THE TESTING INDUSTRY DURING THE PAST FIFTEEN YEARS USING MANY OF THE FACILITIES DEVELOPED BY WYLE LABORATORIES AS EXAMPLES. THE ARTICLE CONCLUDES WITH THE OUTLOOK FOR THE FUTURE OF ENVIRONMENTAL ENGINEERING.