365
MASTER

ORNL-2753
Reactors-General

DAREX PROCESSING OF APPR FUEL: EFFECT OF
ACIDITY AND GAS SPARGING ON RATE OF
CHLORIDE REMOVAL FROM DISSOLVER
PRODUCT DURING REFLUXING

B. C. Finney
F. G. Kitts

OAK RIDGE NATIONAL LABORATORY

operated by

UNION CARBIDE CORPORATION

for the

U.S. ATOMIC ENERGY COMMISSION

Printed in USA. Price \$0.50. Available from the

Office of Technical Services
Department of Commerce
Washington 25, D.C.

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

- A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or
- B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

ORNL-2753

Contract No. W-7405-eng-26

CHEMICAL TECHNOLOGY DIVISION

Unit Operations Section

DAREX PROCESSING OF APPR FUEL: EFFECT OF ACIDITY AND GAS
SPARGING ON RATE OF CHLORIDE REMOVAL FROM DISSOLVER PRODUCT
DURING REFLUXING

B. C. Finney
F. G. Kitts

DATE ISSUED

AUG 7 1959

OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee
Operated by
UNION CARBIDE CORPORATION
for the
U. S. ATOMIC ENERGY COMMISSION

ABSTRACT

The rate of chloride removal varied directly with HNO_3 concentration in an APPR-type Darex dissolver product containing 100 g/liter metal loading, 0.58 M initial chloride, and initial HNO_3 concentrations of 8, 9, 10, 12, and 14 M . The removal rate with 8 and 9 M HNO_3 was very low. After 6 hr refluxing, the chloride content decreased to 0.50 and 0.36 M , respectively. After refluxing for the same time with 10 to 14 M HNO_3 , the product contained 0.064 to 0.0007 M (2270 to 25 ppm) chloride. The effect of air sparging was approximately equivalent to refluxing without sparging at a HNO_3 concentration 2 M higher. After 6 hr sparging and refluxing the chloride content varied from 0.034 to < 0.00014 M (1200 to < 5 ppm) for initial HNO_3 concentrations from 8 to 14 M .

CONTENTS

	<u>Page</u>
1.0 Introduction	4
2.0 Variables Affecting Chloride Removal	6
2.1 Nitric Acid Concentration and Refluxing Time	6
2.2 Sparging	6
3.0 References	11
4.0 Appendix	11
4.1 Procedure	11
4.2 Summary of Data and Calculated Values	11

1.0 INTRODUCTION

The Darex head-end process is a means of converting stainless steel-uranium and stainless steel- UO_2 fuels to chloride-free nitrate solutions suitable for processing in existing solvent extraction equipment.^{1,2} Chloride is necessary to effect dissolution of stainless steel in nitric acid but it must be removed to avoid corrosion of feed adjustment, solvent extraction, and waste handling equipment fabricated of stainless steel.

Small-scale chloride removal studies were made to determine the effect of nitric acid concentration and sparging on the rate of chloride removal from the dissolver product and to obtain data for use in designing larger scale feed adjustment experiments and in pilot plant installations. All results reported are strongly influenced by the scale of operation and must be verified on a larger scale, but they indicate the feasibility of the proposed techniques.

The Darex head-end process consists basically of three steps: (1) dissolution, (2) chloride removal, and (3) adjustment of the resulting solution to solvent extraction feed concentrations. These steps may be accomplished continuously, semicontinuously, or batchwise with nitric acid solutions from 61 to 95 wt % HNO_3 to volatilize and/or decompose the chloride. To remove chloride to the desired concentration of < 350 ppm in the solvent extraction feed, it may be desirable at some point in the various flowsheets to incorporate a reflux step.

In the ORNL reference flowsheet (Fig. 1) for APPR fuel reprocessing, provision is made for a refluxing step and an air sparge following the recovery of mixed acid (dilute aqua regia for the preparation of the next batch of dissolvent) and the batch addition of fresh 13.3 M HNO_3 .^{3,4} Excess nitric acid is removed after the reflux step by distillation, and the acidity in the solvent extraction feed is decreased to 2-3 M by dilution with water. The ultimate chloride content therefore cannot be specified for any run, but for acidities greater than 11 M there would probably be a further decrease in the reported values by a factor of at least 10.

Fig.1. Darex Process: Reference Flowsheet for Batch Operation with 61 wt % HNO₃ (Data from Run APPR-52).

2.0 VARIABLES AFFECTING CHLORIDE REMOVAL

2.1 Nitric Acid Concentration and Refluxing Time

For a given reflux time the chloride concentration in the dissolver product varied inversely with the initial nitric acid concentration (Fig. 2). Very low chloride concentrations were reached (< 100 ppm) by decomposition during 6 hr of reflux with initial nitric acid concentrations of 12 M or greater. Below an initial HNO_3 concentration of 10 M there was only a very slow change in the chloride concentration with reflux time.

Higher nitric acid concentrations increased the chloride decomposition rate and decreased the chloride in equilibrium with the liquid phase. Initially, chloride removal rates were high for acidities above 10 M , but the lower slopes of the removal curves indicated either the approach to an equilibrium chloride concentration or a gradual decrease in acidity and total removal rate. However, the experimental data (Table 1, Appendix) indicate that the nitric acid concentration did not decrease significantly in any run, so that a pseudo-equilibrium chloride content which varies with acidity is probably approached in the refluxing step.

Five runs were made with an arbitrarily selected dissolver product containing 100 g of APPR metal per liter, 0.58 M initial chloride, and initial HNO_3 concentrations of 8, 9, 10, 12, and 14 M .

2.2 Sparging

Air sparging increased both the rate of chloride removal and the total amount removed (Fig. 3). For example, after 2 hr refluxing and sparging of a solution with an initial HNO_3 concentration of 10 M , the chloride concentration was approximately 0.01 M (355 ppm) as compared to 0.3 M without sparging.

Use of the sparge was approximately equivalent to an additional 2 moles of HNO_3 per liter without sparging. With an initial dissolver product HNO_3 concentration of 8 M , the chloride concentration after 6 hr was 0.034 M as compared to 0.064 M with an initial HNO_3 concentration of 10 M without air sparging. With initial HNO_3 concentrations of 12 and 14 M it was possible to obtain chloride concentrations of less than 10 ppm with

Fig. 2. Darex Dissolver Product Chloride Concentration as a Function of Reflux Time for Various Initial Nitric Acid Strengths.

Fig. 3. Darex Dissolver Product Chloride Concentration as a Function of Reflux Time for Various Initial Nitric Acid Concentrations Using an Air Sparge.

sparging. These five runs were made with the same type of Darex dissolver product used previously (Sec. 2.1) containing 100 g of APPR metal per liter, 0.58 M initially in chloride and 8, 9, 10, 12, and 14 M in HNO_3 .

One run was also made to determine the rate of chloride removal from a dissolver product at room temperature ($\sim 25^\circ\text{C}$) using an air sparge (Fig. 4). There was a very slow reduction in the chloride concentration (0.65 M to 0.41 M) after 12 hr refluxing. Room temperature sparging with 12.7 M HNO_3 was approximately as effective as refluxing with 8 M HNO_3 with no sparging (Fig. 2).

In one scouting run, refluxing with nitrogen as a sparge gas was more effective than refluxing with no sparge but was not so effective initially as refluxing with air (Fig. 5). The over-all rates for chloride removal with air and nitrogen were approximately equal after 6 hr.

It was concluded that refluxing and sparging is a useful and effective method of removal of chloride from the dissolver product of the Darex process for APPR fuel. The use of an air sparge made it possible to remove chloride rapidly when the acidity was over 9 M. With refluxing alone, chloride was removed very slowly from 9 M HNO_3 . It is recommended that provisions for refluxing and sparging be incorporated in the final pilot plant design for APPR fuel processing. The use of reflux and sparge would increase the flexibility of any flowsheet which depended on distillation alone for chloride removal.

Fig. 4 Chloride Concentration in Darex Dissolver Product as a Function of Air Sparging Time

Fig. 5. Chloride Concentration in Darex Dissolver Product as a Function of Refluxing Time

3.0 REFERENCES

1. F. G. Kitts and J. J. Perona, "Pre-Solvent Extraction Treatment of Stainless Steel Uranium Fuels with Dilute Aqua Regia," ORNL-CF-57-6-125 (June 10, 1957).
2. F. G. Kitts, B. C. Finney, and J. H. Goode, "The Darex Process: Progress Since the 1958 Geneva Conference," ORNL-CF-58-11-82 (Nov. 28, 1958).
3. F. R. Bruce, R. E. Blanco, and J. C. Bresee, "Recent Developments in Feed Preparation and Solvent Extraction," ORNL-CF-58-11-91 (March 20, 1959); presented at 5th Nuclear Congress, Cleveland, Ohio, April 7, 1959.
4. W. E. Clark, J. R. Flanary, and F. G. Kitts, "The Darex Process: The Treatment of Stainless Steel Reactor Fuels with Dilute Aqua Regia," ORNL-2712 (in preparation).

4.0 APPENDIX

4.1 Procedure

The test solutions were prepared by concentrating a single batch of product from chloride removal and feed adjustment runs made in the 4-in.-i.d. Pyrex feed adjustment tank using 61 wt % HNO_3 with a reflux flowsheet.³ Hydrochloric acid, nitric acid, and water were added to obtain solutions with 100 g of APPR metal per liter and the various chloride and nitric acid concentrations indicated. A run was made by charging 900 ml of adjusted dissolver product to a 2-liter distillation flask and boiling the solution at total reflux using an updraft condenser. Constant boil-up was maintained at a boil-up/liquid volume ratio of approximately 1/150 per minute. The sparging rate was also maintained constant at a sparging rate/liquid volume ratio of approximately 8.5 per hour. The sparge gas was dispersed by a 1-in.-dia glass frit mounted horizontally and centered about 2 in. below the undisturbed surface level.

4.2 Summary of Data and Calculated Values

In Table 1 are shown the experimental results of all chloride removal runs. Most of the data are presented graphically in Figs. 2-5.

Table 1. Comparison of Chloride Concentration in APPR Darex Dissolver Product as a Function of Reflux Time and Various HNO₃ Concentrations, with and without Air Sparging

Dissolver product: 100 g APPR metal per liter, 0.58 M initial Cl⁻, and 8-14 M initial HNO₃

Condenser: updraft with total reflux

$$\frac{\text{Boil Up Rate}}{\text{Liquid Volume}} = \frac{1}{150} \text{ min}^{-1}$$

$$\frac{\text{Air Sparge Rate}}{\text{Liquid Volume}} = \frac{8.5}{1} \text{ hr}^{-1}$$

Reflux Time, hr	8 M Initial HNO ₃				9 M Initial HNO ₃				10 M Initial HNO ₃				12 M Initial HNO ₃				14 M Initial HNO ₃			
	HNO ₃ Content, M		Cl Content, M		HNO ₃ Content, M		Cl Content, M		HNO ₃ Content, M		Cl Content, M		HNO ₃ Content, M		Cl Content, M		HNO ₃ Content, M		Cl Content, M	
	Sparge	No Sparge	Sparge	No Sparge	Sparge	No Sparge	Sparge	No Sparge	Sparge	No Sparge	Sparge	No Sparge	Sparge	No Sparge	Sparge	No Sparge	Sparge	No Sparge	Sparge	No Sparge
1	7.60	7.79	0.15	0.57	8.73	8.9	0.062	0.50	9.69	10.0	0.0215	0.31	11.34	11.16	0.0013	0.14	13.01	13.19	0.0008	0.022
2	7.61	8.03	0.08	0.54	8.90	8.9	0.03	0.42	9.71	10.0	0.0093	0.20	10.96	11.22	0.0007	0.04	13.19	12.9	0.00035	0.012
3	7.71	8.03	0.062	0.54	8.83	9.0	0.0176	0.38	9.78	9.79	0.0047	0.15	11.55	11.18	0.00051	0.0146	13.16	12.62	<0.00028	0.0037
4	7.65	8.01	0.048	0.54	8.87	8.89	0.0124	0.34	9.74	9.81	0.0024	0.11	11.60	11.03	0.00037	0.006	13.41	12.71	<0.00014	0.0018
5	7.63	8.09	0.0415	0.53	8.82	8.95	0.0095	0.31	9.51	9.71	0.0018	0.092	11.74	11.08	0.00034	0.004	13.57	12.75	<0.00014	0.0012
6	7.62	8.07	0.034	0.50	8.90	8.92	0.0072	0.30	9.53	9.70	0.0013	0.064	11.66	11.00	0.00028	0.0025	13.36	12.95	<0.00014	0.0007

INTERNAL DISTRIBUTION

1. C. E. Center	62. G. E. Boyd
2. Biology Library	63. W. E. Unger
3. Health Physics Library	64. R. R. Dickison
4-5. Central Research Library	65. A. T. Gresky
6. Reactor Experimental
Engineering Library	66. E. D. Arnold
7-26. Laboratory Records Department	67. C. E. Guthrie
27. Laboratory Records, ORNL R.C.	68. J. W. Ullmann
28. A. M. Weinberg	69. K. B. Brown
29. L. B. Emlet (K-25)	70. K. O. Johnsson
30. J. P. Murray (Y-12)	71. J. C. Bresee
31. J. A. Swartout	72. J. B. Adams
32. E. H. Taylor	73. R. E. Brooksbank
33. E. D. Shipley	74. W. E. Clark
34-35. F. L. Culler	75. L. M. Ferris
36. M. L. Nelson	76-77. B. C. Finney
37. W. H. Jordan	78. J. R. Flanary
38. C. P. Keim	79. A. E. Goldman
39. J. H. Frye, Jr.	80. J. H. Goode
40. S. C. Lind	81. P. A. Haas
41. A. H. Snell	82. J. M. Holmes
42. A. Hollaender	83. R. W. Horton
43. K. Z. Morgan	84. A. R. Irvine
44. M. T. Kelley	85. H. F. Johnson
45. T. A. Lincoln	86-87. F. G. Kitts
46. R. S. Livingston	88. E. Lamb
47. A. S. Householder	89. W. H. Lewis
48. C. S. Harrill	90. J. T. Long
49. C. E. Winters	91. A. C. Schafer
50. H. E. Seagren	92. E. M. Shank
51. D. Phillips	93. C. D. Watson
52. W. K. Eister	94. M. E. Whatley
53. F. R. Bruce	95. P. M. Reyling
54. D. E. Ferguson	96. D. L. Katz (consultant)
55. R. B. Lindauer	97. I. Perlman (consultant)
56. H. E. Goeller	98. M. Benedict (consultant)
57. C. W. Hancher	99. C. E. Larson (consultant)
58. R. A. Charpie	100. H. Worthington (consultant)
59. J. A. Lane	101. J. H. Rushton (consultant)
60. M. J. Skinner	102. ORNL - Y-12 Technical Library,
Document Reference Section
61. R. E. Blanco	

EXTERNAL DISTRIBUTION

- 103. A. M. Platt, Hanford Operations Office
- 104. C. E. Stevenson, Idaho Chemical Processing Plant
- 105. Division of Research and Development, AEC, ORO
- 106-693. Given distribution as shown in TID-4500 (14th ed.) under Reactors-General category (75 copies - OTS)