MAY 4 1965

BNWL-SA-125
~~BNSA-125~~

CONF-650529-1

MASTER

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:
A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or
B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.
As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

ENVIRONMENTAL MONITORING

LECTURE NOTES

March, 1965

by

J. K. Soldat

Environmental Studies and Evaluation
Section

Radiation Protection Department
Pacific Northwest Laboratories
Battelle Memorial Institute
P. O. Box 999
Richland, Washington

PATENT CLEARANCE OBTAINED. RELEASE TO
THE PUBLIC IS APPROVED. PROCEDURES
ARE ON FILE IN THE RECEIVING SECTION.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

TABLE OF CONTENTS

- I. INTRODUCTION
- II. CRITERIA FOR ENVIRONMENTAL MONITORING PROGRAMS
 - A. Standards for Public Exposure
 - B. Specific Requirements
 - C. Basis for MPC's
- III. ENVIRONMENTAL MONITORING PROGRAMS
 - A. Pre-operational Surveys
 - B. Emergency Surveys
 - C. Operation Surveys
- IV. HANFORD'S ENVIRONMENTAL MONITORING PROGRAM
 - A. Organization
 - B. Sources of Exposure
 - C. River Water
 - D. Airborne Materials
 - E. Miscellaneous Measurements
 - F. Composite Dose
- V. BIBLIOGRAPHY
 - A. Standards and Guides
 - B. Sampling Theory and Statistics
 - C. Radiochemical Analysis
 - D. General Considerations
 - E. Sampling Devices
 - F. Ground Contamination and Food Chains
 - G. Surveys at Specific Sites
 - H. Hanford Reports

Appendix A Sources of Environmental Radiation Exposure

Appendix B Natural Background Radiation

Appendix C Medical Radiation Exposure

Appendix D Problems

ENVIRONMENTAL MONITORINGI. INTRODUCTION

It must be conceded from experience that some radioactive material will always be released from a nuclear installation. The ultimate fate of these materials, even if rates and concentrations at the point of release are known to be low, can be determined without reservation only by measurements in the environment. Although meteorologists may be able to predict wind direction, deposition velocities, fallout patterns, etc., and biologists may know the paths of isotopes in food chains, their predictions will not replace the direct measurement of isotopes in the environment of man, and in man himself. Every installation must provide the necessary monitoring surveys to assure that contamination levels on vegetation, in soil, water, fish and animals consumed as food are below levels of concern. These measurements of radioactive materials at the point of release, in the environment, and in the ultimate receptor, are important features of a well designed radiation protection program.

In recent years the presence of world-wide fallout from weapons tests has complicated environmental measurements. A nuclear plant should not be credited with and penalized for release of material which may be ascribed to fallout from weapons tests. The contribution of fallout to the total hazard picture must nevertheless be assessed. This requires extremely careful sampling, and sensitive radiochemical analytical methods to properly interpret environmental samples. Pre-operational surveys, discussed briefly in the ensuing paragraphs, are necessary to establish the background above which nuclear operation contributions must be identified, and evaluated.

II. CRITERIA FOR ENVIRONMENTAL MONITORING PROGRAMS

A. Standards for Public Exposure

The translation, by an operator of a nuclear facility, from existing regulations into a practical environmental monitoring program is not always a straight-forward task. The difficulty arises from the multitude of agencies, international, national, and state, which have issued radiation standards and guides. In addition, none of these agencies specifies the exact monitoring program required to protect the general public, but they do require control measures which can only be verified by effluent and environmental monitoring.

Until March 1962, the federal government was the sole control authority for the use of radioactive materials in the U. S. A. Activities carried out under licenses issued by the U. S. Atomic Energy Commission were subject to the regulations published as Title 10 code of Federal Regulations Part 20. Operations of the AEC or its contractors were subject to appropriate chapters of the AEC Manual. Since March 1962, the radiation protection regulatory responsibility for licensees in the states of Kentucky, Mississippi, California, New York, Arkansas, and Texas have been turned over to the governments of those states.

1. ICRP-NCRP

The radiation protection requirements of the federal and state governments are nearly identical and are derived from the recommendations of the National Committee on Radiation Protection and Measurements (NCRP). The recommendations of the NCRP have been developed primarily for the protection of occupationally exposed persons. Recent recommendations of this Committee do, however, include statements applicable to persons outside of controlled

areas. In general, the recommendations for persons outside of controlled areas specify a maximum radiation dose (or rate of intake) equivalent to one-tenth of that permitted for occupational exposure. These recommendations include maximum permissible concentrations (MPC's) of radioactive contamination in air and water which agree closely with the MPC's suggested by the International Commission on Radiological Protection (ICRP).

Neither of these two advisory groups has given specific guidance with respect to the contamination of food or environmental materials other than air and water. However, several general comments relating to environmental and food contamination do appear in the main ICRP recommendations and in the 1959 Report of Committee II on Permissible Dose for Internal Radiation.

"Members of the population at large may be exposed to radiation that cannot be related to any specific controlled area ----. As such exposure is not easily controlled, it will be impossible to ensure that a recommended maximum permissible individual dose is not exceeded in any single case. Where large numbers are involved, it will not be possible to examine the habits of every individual. A reasonable procedure would be to study a sample of the group involved and to set the environmental level so that no individual in the sample receives any excessive exposure. There will always remain the possibility that someone of grossly different habits from those in the observed sample may receive a higher dose than the maximum in the sample."

While this statement is more applicable to the establishment of maximum permissible levels than to a monitoring program, it does indicate that the habits and customs of people do affect the degree of exposure to radioactive materials in the environment. It also recognizes that the radiation exposure of a population can be determined by measuring the exposure of a representative sample of that population.

2. FRC

The Federal Radiation Council (FRC), a regulatory organization formed in 1959, has given more attention to the need for environmental surveillance than have either the ICRP or the NCRP. The first staff report of the FRC introduced the term "Radiation Protection Guide" (RPG) viz.,

"Radiation Protection Guide (RPG) is the radiation dose which should not be exceeded without careful consideration of the reasons for doing so; every effort should be made to encourage the maintenance of radiation doses as far below this guide as practicable."

It also suggests an operational technique for assuring that the RPG for the annual whole body dose to the individual in the population is not exceeded when the actual dose received by each individual is not measured. The technique is to measure the dose received by a suitable sample of the population and to impose an RPG on the average of the sample which is one-third of the RPG imposed on individuals in the general population.

Further guidance on the control of environmental radioactivity is given by the second report of the Federal Radiation Council which discusses that subject in more detail than have any previous advisory or regulatory reports, viz.,

"The objective of the control of population exposure from radionuclides occurring in the environment is to assure that appropriate RPG's are not exceeded. This control is accomplished in general either by restrictions on the entry of radioactive materials into the environment or through measures designed to limit the intake of such materials by members of the population. The most direct means of evaluating the effectiveness of control measures is the determination of the amount of radioactive material in the bodies of the members of exposed population groups. Although the determination of such body burdens may at times be indicated, in routine practice potential

exposures will generally be assessed on the basis of either one or a combination of two general approaches: (1) calculations based upon known amounts of radioactive material released to the environment, and assumptions as to the fraction of this material reaching exposed population groups, or (2) environmental media."

The second report also recommended a graded series of radiation protection actions which are related to ranges of intake of radioactive materials by exposed population groups, viz.,

Ranges of transient rates of daily intake	Graded scale of action
Range I	Periodic confirmatory surveillance as necessary
Range II	Quantitative surveillance and routine control
Range III	Evaluation and application of additional control measures as necessary

B. Specific Requirements

1. Licensees

Since 1954, the U. S. Atomic Energy Commission has been authorized by the Atomic Energy Act to license the use of nuclear and radioactive by-product materials by qualified applicants pursuant to such safety standards as are established by rule of the Commission to protect health and to minimize danger to life or property.

Accordingly the Commission has promulgated the radiation protection regulations which are published as Title 10 Part 20 of the Code of Federal Regulations (10-CFR-20).

Three sections of these regulations are concerned with the release of radioactive materials.

20.106 Concentrations in effluents to unrestricted areas

(a) There may be included in any application for a license or for amendment of a license proposed limits upon concentrations of licensed and other radioactive material released into air or water in unrestricted areas as a result of the applicant's proposed activities. Such applications should include information as to anticipated occupancy times for each unrestricted area involved. The Commission will approve the proposed limits if the applicant demonstrates that it is not likely that any individual will be exposed to concentrations in excess of the limits specified in Appendix B, Table II, of this part.* For purposes of this paragraph, concentrations may be averaged over periods not greater than one year.

(b) Except as authorized by the Commission pursuant to 20.302 or paragraph (a) of this section, no licensee shall possess, use or transfer licensed material in such a manner as to release into air or water in any unrestricted area any concentration of radioactive material in excess of the limits specified in Appendix B, Table II, of this part. For purposes of this paragraph, concentrations may be averaged over periods not greater than one year.

(c) For purposes of this section, determinations as to the concentration of radioactive material shall be made with respect to the point where such material leaves the restricted area. Where the radioactive material is discharged through a stack, tube, pipe, or similar conduit, the determination may be made with respect to the point where the material leaves such conduit.

(d) The provisions of this section do not apply to disposal of radioactive material into sanitary sewerage systems (see 20.303).

20.302 Method for obtaining approval of proposed disposal procedures.

Any licensee or applicant for license may apply to the Commission for approval of proposed procedures to dispose of licensed material in a manner not otherwise authorized in the regulations in this chapter. Each application should include a description of the licensed material and any other radioactive material involved, including the quantities and kinds of such material and the levels of radioactivity involved, and the proposed manner and conditions of disposal. The application should also include an analysis and evaluation of pertinent information as to the nature or the environment, including topographical, geological, meteorological, and

*Note: These concentrations are one-tenth of the 168 Hour Occupational MPC's determined by the NCRP.

hydrological characteristics; usage of ground and surface waters in the general area; the nature and location of other potentially affected facilities; and procedures to be observed to minimize the risk of unexpected or hazardous exposures. The Commission will not approve any application for a license to receive licensed material from other persons for disposal on land not owned by the Federal government or by a State government.

20.303 Disposal by release into sanitary sewerage systems.

No licensee shall discharge licensed material into a sanitary sewerage system unless:

- (a) It is readily soluble or dispersible in water; and
- (b) The quantity of any licensed or other radioactive material released into the system by the licensee in any one day does not exceed the larger of subparagraphs (1) or (2) of this paragraph:
 - (1) The quantity which, if diluted by the average daily quantity of sewage released into the sewer by the licensee, will result in an average concentration equal to the limits specified in Appendix B, Table I, Column 2 of this part;* or
 - (2) Ten times the quantity of such material specified in Appendix C of this part; and
- (c) The quantity of any licensed or other radioactive material released in any one month, if diluted by the average monthly quantity of water released by the licensee, will not result in an average concentration exceeding the limits specified in Appendix B, Table I, Column 2 of this part; and
- (d) The gross quantity of licensed and other radioactive material released into the sewerage system by the licensee does not exceed one curie per year.

Excreta from individuals undergoing medical diagnosis or therapy with radioactive material shall be exempt from any limitations contained in this section.

2. Contractors

Nuclear facilities operated by AEC contractors are not governed by 10-CFR-20, but rather by appropriate AEC Manual chapters,

*Note: These concentrations are equal to the 40 Hour Occupational MPC_w determined by the NCRP.

principally chapter 0524. Whereas the licensee must control concentrations of effluent air and water to MPC values at the point of release, the contractor is regularly permitted to discharge effluents with concentrations greater than specified by the MPC's. The contractor is required, however, to control his operations so that radiation doses and concentrations in "uncontrolled areas" do not exceed certain standards, viz.,

RADIATION PROTECTION STANDARDS FOR INDIVIDUALS
AND POPULATION GROUPS IN UNCONTROLLED AREAS

A. Radiation dose standards for external and internal exposure

<u>Type of Exposure</u>	<u>Dose (rem/year)</u>	
	<u>Based on exposure to individuals</u>	<u>Based on an average exposure to a suitable population sample</u>
Whole body, Gonads, or Bone Marrow	0.5	0.17
Thyroid or Bone	1.5	0.5
Bone (alternate standard)	Body burden of 0.003 μg of radium 226 or its biological equivalent	Body burden of 0.001 μg of radium 226 or its biological equivalent

B. Radioactivity in effluents released to uncontrolled areas.

1. Except as provided in paragraph 2 below of this section, radioactivity in effluents released to uncontrolled areas shall not exceed the radiation protection standards specified in Table II of annex 1 of this appendix. The point of release of such effluents shall be considered to be the point at which the effluents pass beyond the site boundary. Where such effluents are discharged through a conduit such as a stack or pipe, the point of release may be considered to be the conduit discharge. For the purpose of applying these standards, radioactivity concentrations in effluents may be averaged over periods up to one year.
2. Radioactivity in effluents may be released to uncontrolled areas in excess of the radiation protection standards specified in

table II of annex 1 of this appendix provided it is reasonably demonstrated that in uncontrolled areas:

- (a) individuals are not exposed in excess of the standards specified in paragraph A above,
- (b) individuals are not exposed in excess of table II of annex 1 standards, or
- (c) the average exposure of a suitable sample of an exposed population group is not in excess of one-third of table II of annex 1 standards. Radioactivity concentrations in the environment may be averaged over periods up to one year.

The local office (RLOO) of the AEC has issued an appendix to 0524 call 0524-053, dated February 28, 1964. The purpose of the appendix is to clarify the intent of chapter 0524. Only two items are concerned with non-occupational exposure. First, a firm statement is made that control in the environment (rather than in the pipe line) is the prime consideration. Second, another alternative is given for demonstrating compliance with the environmental exposure criteria. This alternative is limiting of radiation doses received by an average of a suitable sample of an exposed population to the standards tabulated for such an average. Originally, 0524 referred only to the standards for the individual radiation doses when discussing alternatives for demonstrating compliance.

C. Basis of MFC's

All of regulations cited above are based on the desire to limit the radiation exposure to the general public or to people in the vicinity of the nuclear facility, to levels which are below some specified amount. This applies to whole body external radiation as well as to internal radiation exposure of specific body organs. External exposure can be measured directly while internal exposures can only be evaluated

indirectly. The best indirect measure of internal doses is determination of the body burden of the environmental resident by means of a whole body counter. This is expensive and time consuming. Therefore, the various advisory agencies have defined secondary standards in terms of the maximum permissible concentration (MPC) of a radionuclide in air or water. The MPC is calculated from the "permissible" internal radiation doses, assuming certain sustained rates of air and water consumption over the entire adult life, and assuming certain biologically behavior of the radionuclides. The methods used and the calculations involved are discussed in the Report of ICRP Committee II on Permissible Dose for Internal Radiation (1959) (See Health Physics, Vol. 3, June 1960).

The derivations of the MPC's and the calculations for doses from internally deposited nuclides are discussed in some detail below, because of the relative importance of this subject to the estimation of radiation exposures received by residents in the plant environs of a nuclear facility.

1. Behavior of Ingested Materials

When an element enters the body through food or drink, its fate depends upon the manner in which the body utilizes the particular element. Some elements may be firmly fixed in a given organ and reside there with little turnover. If a diet is followed which contains a given amount I of element A taken in per day, and the body eliminates the element at a constant fraction, λ_B , of the amount, N , at any time t ,

then $\frac{dN}{dt} = I - \lambda_B N$ (1)

$$N = I \frac{(1 - e^{-\lambda_B t})}{(\lambda_B)} \quad (2)$$

at equilibrium, t is large, $1 - e^{-\lambda t} \approx 1$

and $N = \frac{I}{\lambda_B}$

$$I = N \lambda_B$$

but

$$\lambda_B = \frac{.693}{T_B}$$

where

T_B = half life (biological)

$$T_B = \frac{.693 N}{I} \quad (3)$$

If f = fraction of the element deposited in a particular organ in question, then

$$T_B = \frac{0.693 N}{I f} \quad (4)$$

The effective half life, $t_{eff.}$, is the time for the radioisotope to be reduced to half its original value from both radioactive decay and biological elimination:

$$\frac{N}{N_0} = (e^{-\lambda_B t}) (e^{-\lambda_R t}) \quad (5)$$

$$= e^{-(\lambda_B + \lambda_R)t} = e^{-\lambda_{eff} t}$$

$$= e^{-\left(\frac{0.693}{T_B} + \frac{0.693}{T_R}\right) t}$$

$$\frac{N}{N_0} = e^{-0.693t \left(\frac{T_B + T_R}{T_B T_R}\right)} = e^{-(0.693t) \div \left(\frac{T_B T_R}{T_B + T_R}\right)}$$

$$\frac{(T_B)(T_R)}{T_B + T_R} = \text{Effective half-life} = t_{eff.} \quad (6)$$

$$(0.6932) \div \left(\frac{T_B T_R}{T_B + T_R}\right) = \frac{0.6932}{t_{eff.}} = \lambda_{eff.}$$

Non-radioactive Element,
biological removal only.

Radioactive Isotope
with biological removal.

Note that the assumption was made that removal is exponential.

This assumption is not necessarily the most accurate, but it permits a reasonable analysis of uptake, retention and elimination in many cases.

2. The Standard Man

Because of the many variables entering into the calculation of MFC's, and the uncertainty in many of the metabolic constants it is first necessary to establish ground rules which will be uniformly applied. Among these are the attributes of the "standard man". The International Commission on Radiation Protection tabulated the characteristics of the so called "standard man" as defined in the following tables.

Table I

AVERAGE CHEMICAL COMPOSITION OF THE ADULT HUMAN BODY

<u>Element</u>		<u>Per cent by Weight</u>	<u>Approximate amount in a 70 kg man (g)</u>
Oxygen	O	65.0	45,500
Carbon	C	18.0	12,600
Hydrogen	H	10.0	7,000
Nitrogen	N	3.0	2,100
Calcium	Ca	1.5	1,050
Phosphorous	P	1.0	700
Sulphur	S	0.25	175
Potassium	K	0.2	140
Sodium	Na	0.15	105
Chlorine	Cl	0.15	105
Magnesium	Mg	0.05	35
Iron	Fe	0.006	4
Copper	Cu	0.0002	0.1
Manganese	Mn	0.00003	0.02
Iodine	I	0.00004	0.03

Table II

MASS AND EFFECTIVE RADIUS OF ORGANS OF THE ADULT HUMAN BODY***

	<u>Mass, m, (g)</u>	<u>Per cent of total body*</u>	<u>Effective Radius, X(cm)</u>
Total Body*	70,000	100	30
Muscle	30,000	43	30
Skin and Subcutaneous Tissue**	6,100	8.7	0.1
Fat	10,000	14	20
Skeleton: Without bone marrow	7,000	10	5
Red marrow	1,500	2.1	
Yellow marrow	1,500	2.1	
Blood	5,400	7.7	
Gastrointestinal Tract*	2,000	2.9	30
Contents of G. I. tract -			
Lower large intestine	155		
Stomach	250		
Small intestine	1,100		
Upper large intestine	135		
Liver	1,700	2.4	10
Brain	1,500	2.1	
Lungs (2)	1,000	1.4	30
Lymphoid tissue	700	1.0	
Kidneys (2)	300	0.43	7
Heart	300	0.43	
Spleen	150	0.21	7
Urinary bladder	150	0.21	
Pancreas	70	0.10	
Salivary glands (6)	50	0.071	
Testes (2)	40	0.057	
Spinal cord	30	0.043	
Eyes (2)	30	0.043	
Thyroid gland	20	0.029	3
Teeth	20	0.029	
Prostrate gland	20	0.029	
Adrenal glands or suprarenal (2)	20	0.029	
Thymus	10	0.014	
Miscellaneous (blood vessels, cartilage, nerves, etc.)	390	0.56	

*Does not include contents of gastrointestinal tract.

**The mass of the skin alone is taken as 2000 g.

***The reports, "The Standard Man", by Hermann Lisco, ANL-4253, November 1948-February, 1949, p. 96; and "A Survey Report of the Characteristics of the Standard Man", September 1948, by M. J. Cook, were used as the principal sources of reference in the original selection of values given in this table.

Table IIICHARACTERISTICS OF THE STANDARD MAN

	<u>cc/day</u>
Water intake in food	700
Water intake as fluids	1500
	—
Water intake in food and fluids	2200
Water of oxidation	300
	—
Total water consumption per day	2500
Water excretion as sweat	500
Water excretion from lungs	400
Water excretion by faeces	100
Water excretion by urine	1500
	—
Total water excretion per day	2500
Air inhaled during 8-hour work day	10^7
Air inhaled during 16 hours not at work	10^7
	—
Total air inhaled per day	2×10^7
CO ₂ in alveolar air - 5.5%	
Interchange area of lungs	50 sq. metres
Area of upper respiratory tract, trachea, bronchials	20 sq. metres
	—
Total surface area of respiratory tract	70 sq. metres
Total water in body - 50 kg	
Average life span of man - 70 years	
Occupational exposure of man: 8 hours/day, 40 hours/week, and 50 weeks/year	
Minimum thickness of epidermis - 0.07 mm, and depth of blood- forming organs - 5 cm	

3. The Body Burden

As indicated earlier, when a radioactive material is ingested, some fraction finds its way to a particular organ, a sizeable fraction is immediately eliminated, and perhaps a fraction goes to some other tissue or body fluid. As ingestion continues, various equilibria are established and eventually one organ may be "critical". Thus, for a given mode of intake of a particular isotope, an amount of the isotope will accumulate in a given organ, to such an extent that this organ receives a greater insult than any other tissue, fluid, or organ in the body. In some cases the whole body may be the critical organ, in others it will be the bone, thyroid, liver, etc. Hence, we need to know something of the metabolism of an isotope before we can determine its maximum permissible concentration in the food, air, or water entering the body.

It is also important to know the nature of the radiation emitted, (beta, gamma, alpha), and what energies will be absorbed per disintegration. The approximate relative biological effectiveness (RBE) can then be selected. Other variables such as non-uniformity of deposition must also be recognized and accounted for.

To estimate permissible intake even after we have knowledge of the metabolic variables, requires that we somehow determine the "permissible body burden". This is defined as that amount (generally deposited in a critical organ) such that the tissue receives ~~at~~ no more than the "permissible" dose during the lifetime of the individual. The "permissible" dose can be obtained from toxicity studies, from intercomparison with known toxic isotopes, or by assuming that

a given dose rate to an organ is "permissible". A discussion of these methods follows.

Direct toxicity studies in man would, of course, give the best value of the permissible body burden, and simultaneously the permissible drinking, or breathing limit. In general, this has been morally infeasible. Some data have been obtained from accidental ingestion of isotopes, or through administration of certain isotopes to terminal cases. The historical, careful study of radium workers has been used to establish body burden limits for radium and, through animal experiment intercomparison, the limit for other bone-seeking isotopes.

A study of many cases strongly suggested that 0.1 μg of radium in the body would not result in damage. This was established as the body burden for radium.

Now if we could compare the toxicity of some other bone seeking isotope with that of radium, we could proceed to set a body burden limit for this other isotope. This has been done in the case of plutonium. It was determined from many small-animal experiments that the same damaging effects could be produced by feeding the animals about 1/15 as much plutonium as radium in terms μc per kg. The criteria of damage were dose to (1) cause 50 per cent deaths in 30 days, (2) reduce survival by 50 per cent, (3) spontaneous fractures, and (4) bone tumors. The 1/15 was not a firm figure but represented a reasonable average. About half the energy per radium disintegration is released in the small animal as in many due to a greater removal of the radium daughter, radon, from

from small animals. Thus, we would expect the toxicity to be about twice that in man as in the small animal. This alone would reduce the relative toxicity of radium to about $\frac{1}{7.5}$ that of plutonium.

About $1/3$ as much radium as plutonium is retained in the animal, so that a body burden of about $\frac{1}{7.5} \times 3 \times 0.1 = 0.04 \mu\text{c}$ plutonium will give equal effect (and be "permissible") to that of $0.1 \mu\text{g}$ of radium.

Similar comparisons of Sr^{89} toxicity with radium and comparison of the energy released of Sr^{89} with that of Sr^{90} leads to a permissible body burden of Sr^{90} of $1 \mu\text{c}$.

Most often permissible body burdens are calculated using the best metabolic data available and a knowledge of the decay scheme and energy release of the isotope in question. It is also necessary to know the fraction of the element in the various organs so that the "critical" organ may be identified. Although the critical organ was previously defined as that organ receiving the greatest "insult", this may not always be true. Because complete information is not available on the radiosensitivity of all organs and their relative importance in the body system, the critical organ for permissible body burden considerations is assumed to be that organ which receives the greatest dose in rem.

The fraction of the total body content of a given element, f_a , going to a particular organ has actually been determined for a number of elements, but is only estimated in other cases. These fractions are listed in the 1959 ICRP Committee II report.

For alpha and beta particles the energy released is almost totally absorbed in the tissue, but the surface tissue may be more lightly irradiated than deeper tissue.

Alpha particles from a pure emitter are of a single energy, hence the effective energy is equal to the tabled energy. The RBE for most alpha particles is 10.

The effective energy of a beta particle is about 1/3 the maximum beta energy. More ^{or} exact expressions are available for determining the average energy. The RBE for beta particles is taken as one. Some data suggests a somewhat higher RBE should be used for very soft emitters such as tritium.

For gamma rays the energy released in tissue is dependent on the absorption coefficient. The organ containing the gamma emitter is assumed to be a sphere and the isotope uniformly distributed. The fraction of energy absorbed is given by

$$b_g = 1 - e^{-(\mu - \sigma_s)x} \quad (7)$$

where x is the radius of the sphere, μ = total linear absorption coefficient and σ_s = the Compton scattering coefficient. The RBE = 1

A correction to the gamma energy absorbed due to internal conversion must sometimes be made. When a gamma ray is internally converted, an outer shell electron is emitted with the energy of the photon minus the binding energy. The number of photons "converted" to electrons per photon escaping is the internal conversion coefficient, α . The fraction of the photons emitted which are

converted = $\frac{1}{1 + \alpha}$, and the fraction which escape and are absorbed in the tissue is

$$1 - \frac{1}{1 + \alpha} = \frac{\alpha}{1 + \alpha} \quad (8)$$

so that

$$\gamma_{\text{eff.}} = \gamma_{\text{total}} \left(\frac{\alpha}{1 + \alpha} \right)$$

The conversion electrons are absorbed as monoenergetic betas, and the energy release in the organ per photon from conversion electrons is then

$$E_{e^-} = \left(\frac{1}{1 + \alpha} \right) (E_{\gamma} - E_{\text{binding}}) \quad (9)$$

Since the binding energy appears as low energy X-rays which are effectively absorbed in the organ,

$$E_{e^-} = \frac{E_{\gamma}}{1 + \alpha} \quad (10)$$

In evaluating the energy released in an organ from an isotope it is, of course, necessary to sum all emissions from the disintegration. It is necessary to weight the energy release for each type of emitter before summing.

$$\Sigma E(\text{RBE}) = \Sigma (f_{\gamma} E_{\gamma} b_{\gamma} + \bar{E}_{\beta} f_{\beta} + 10 E_{\alpha} f_{\alpha} + 20 E_R f_R + E_{e^-} f_{e^-}) \quad (11)$$

where f_{γ} , f_{β} , f_{α} , f_R , etc., are the fractions of the total disintegrations leading to γ , β , α emission and recoil nuclei.

One other factor which must be accounted for is the non-uniform distribution of the isotope in the organ. This is of particular importance in bone seekers, since it is found that localization of the isotope gives rise to greater damage than would otherwise be

expected. It has been determined that a factor of five would account for this increased sensitivity for bone seekers. Thus, for bone seekers

$$\Sigma E(RBE)N = \Sigma(f_{\gamma} E_{\gamma} b_{\gamma} + NE_{\beta}f_{\beta} + 10 NE_{\alpha}f_{\alpha} + 20 NE_Rf_R + NE_e-f_e-) \quad (12)$$

where N = the localization factor.

4. Calculation of Dosage Rate

$$D = \frac{qf_2(3.7 \times 10^4)(60)(1440)[\Sigma E(RBE)N](10^6)(1.6 \times 10^{-12})}{m \times 100} \quad (13)$$

D = dose in rem/day

q = μ c in the body

f_2 = fraction of isotope in organ

3.7×10^4 = disintegrations per sec. per μ c.

(60)(1440) = seconds/day

E(RBE)N = Mev per disintegration absorbed in organ

10^6 = to convert Mev to ev

1.6×10^{-12} = ergs per ev.

m = mass of organ in grams

100 = ergs per rad.

This reduces to

$$D = \frac{51qf_2[\Sigma E(RBE) N]}{m} \quad (14)$$

If D = 0.30 rem/week. (0.043 rem/day)

$$q = \frac{8.4 \times 10^{-4} m}{f_2[\Sigma E(RBE) N]} \quad (15)$$

q = Body burden in μ c to deliver 0.3 rem per week to critical organ.

qf_2 = Organ burden

For isotopes such as tritium and cesium for which the total body is the critical organ the permissible dose is limited to 0.100 rem per week. Gonad dose is also limited to 0.100 rem per week.

The foregoing formulas permit the dose to an organ to be computed if the energy and total body burden are known, or if a permissible dose is specified, to calculate the body burden. What remains is to calculate the daily intake which just permits the body burden to be reached in a lifetime exposure, presently considered to be fifty years.

Assume that a steady intake of $S \mu\text{c}$ per day is taken orally, of which f_w reaches the critical organ. This rate of intake will eventually raise the quantity of isotope in the critical organ to qf_2 .

The differential equation which describes this process is as follows

change in organ = Input - output

$$d(qf_2) = [Sf_w - \lambda_R (qf_2) - \lambda_B (qf_2)]dt \quad (16)$$

in which

λ_R = radioactive decay constant
(fraction per day)

λ_B = biological removal constant
(fraction per day)

from which

$$qf_2 = \frac{Sf_w (1 - e^{-\lambda_{eff}t})}{\lambda_{eff}} \quad (17)$$

where

$$\lambda_{eff} = \lambda_R + \lambda_B$$

$$\lambda_{\text{eff}} = 0.693 \frac{T_R + T_B}{T_R T_B}$$

$$T_{\text{eff}} = \frac{(T_R)(T_B)}{T_R + T_B}$$

[See (6)]

T_{eff} = Effective half-life

From Equation (17)

$$S = \frac{\lambda_{\text{eff}} q f_2}{f_w (1 - e^{-\lambda t})} \quad (18)$$

$$S = (\text{MPC})_w \times 2200$$

2200 = average water consumed per day

$$\text{MPC}_w = \frac{4.6 \times 10^{-4} \lambda_{\text{eff}} q f_2}{f_a (1 - e^{-\lambda_{\text{eff}} t})} \quad (19)$$

also

$$\text{MPC}_{\text{air}} = \frac{S}{2 \times 10^7} = \frac{5 \times 10^{-8} \lambda_{\text{eff}} q f_2}{f_a (1 - e^{-\lambda_{\text{eff}} t})} \quad (20)$$

The values of the constants λ_{eff} (or T_{eff}), f_2 , and f_a are determined experimentally by administering the isotope to animals and measuring the excretion and retention. Human experimental results are far superior and in some cases these have been obtained.

It should be noted that exponential decay and biological elimination were assumed in the foregoing calculations. Actual experiments show this assumption to be only very approximately true and for this reason (and others) the MPC calculations are only approximations.

III. ENVIRONMENTAL MONITORING PROGRAMS

The selection of a suitable survey design is determined by the objectives of the survey and the means which are available to execute it. The objectives of the survey prescribe the nature and precision of the information required. When the only objective of a survey is to compare the existing levels with those considered acceptable, the precision is governed by the magnitude of the acceptable levels. When, however, it is desired to investigate variations in dietary levels from place to place or in time, the precision required is likely to be greater and will depend on the actual or estimated magnitude of the variation.

A. Preoperational Surveys

Preoperational surveys, aimed at obtaining samples before a nuclear facility comes into operation for comparison with others taken later may be needed for regulatory or legal reasons. They may serve also to familiarize personnel with suitable sampling sites and with methods of collection and analysis. They are otherwise justifiable only if the preoperational values for radionuclides relevant to the local surveys are likely to be an appreciable fraction of the levels set by competent authorities. Such pre-existing values might be due to neighboring installations, weapons fallout, or to natural radioactivity.

When a preoperational survey is made, samples of air, water, soil, and plant and animal life may be collected and analyzed for those radionuclides which will be of interest when the facility becomes operational. In preoperational surveys around reactors, it may be sufficient to measure external gamma dose rates, gross beta or gamma activity in air, water, soil and biological materials. A few measurements for Sr^{90} might be made to determine the contribution from fallout.

A preoperational survey around a complex nuclear facility operated by an AEC contractor should include all of the kinds of measurements that will be made after operations begin. Also included should be measurements of meteorological and hydrological parameters likely to effect the dispersal of released effluents. The survey should extend over a period of 12 to 18 months, and include two growing seasons. By the time the facility is operational, the particular vegetation, animals, water locations, etc., likely to concentrate released nuclides should have been indicated. Routine operational surveys can be designed on the basis of this information.

B. Emergency Surveys

These have to be carried out in situations where accidental releases of radioactive materials lead to significant contamination of the environs and/or high external dose rates. They are generally designed to define the area and extent of the contamination spread.

Detection of an accident will normally depend upon the usual procedures for discerning abnormal conditions within the establishment and its environs. Should an emergency occur the immediate aim must be to bring it under control, and to reduce to a minimum injury to people and damage to property. For this reason each installation should promulgate, in detail, specific standing arrangements appropriate to all conceivable accidents for which it is reasonable to plan. Clear lines of responsibility should be defined for immediate control of an accident at its source and for initiating appropriate emergency action.

The emergency arrangements should provide for the most effective use of the resources available by providing for allocation of key personnel

and facilities for emergency duty and for the effective co-ordination of all the site services. They should also contain provision for assistance from outside the region affected. It is essential that emergency permissible levels should have been established.

C. Operational Survey

1. Effluent Monitoring

The effectiveness of radioactive waste control practices must be evaluated in terms of the amount and kind of isotopes released to the environment. Repeated, or continuous measurements of the isotopes present in effluent streams at the point of release are necessary to insure that excessive radioactive materials are not introduced into the environment. These measurements can be used to identify off-standard releases and may also assist in determining the corrective action required. Another important function of such measurements is to reinforce other historical evidence that the plant was not creating a significant hazard in the environment either during short time emissions or in the long range view.

Liquid Streams

Liquid effluent streams to be sampled and analyzed are those flowing in closed pipes or in open ponds, flumes, and ditches. Certain devices have been developed for sampling both kinds of streams. Whether in open or closed conduits the problem resolves itself into: (1) getting a representative sample, and (2) providing an adequate measurement of the radioactive material present. In many applications it is found impractical to provide continuous monitors because of the very low concentrations which must be measured. In these cases grab samples or integrated proportional

samples must be obtained and taken to a laboratory for analysis. Non-uniform flow conditions may make it virtually impossible to obtain a representative, proportional sample. The quality of the sample required is dictated by the general level of active material in the waste, and the consequences of a failure to estimate the level of radioactive material accurately.

Most release limits permit averaging over a significant period of time. This is true of the Code of Federal Regulations, Title 10, Part 20, which permits averaging of concentrations at the point of release over a period of one year. This implies that the operation should be evaluated not on the basis of a particular sample, but on a long term basis involving many samples. This averaging process will minimize the consequences of occasional non-representative samples. Serious effort should be made, however, to obtain the most representative sample without exorbitant cost.

Sampling from a closed conduit, such as a pipe can be as simple as turning on a faucet manually at the required time and collecting the sample. This is the same as a grab sample taken from an open flume or ditch. Some assurance of representativeness is obtained if the line is flushed with the liquid for a period before collecting the sample. The objection to this kind of sampling is that the sample can be only representative of the stream passing the sampling point at the time of sampling. A frequency of sampling must be selected which gives a valid average. This can be determined in statistical tests of the results of sampling over a long period of time.

The manual valve can be replaced with a solenoid valve and timer which opens the valve momentarily at pre-selected times, or at a fixed frequency. If adequate head is not available, a pump may be used to circulate a portion of the stream to the level of the sampling point and collector. An integrated sample can thus be obtained automatically which will be more representative than an infrequent grab sample.

Gaseous Effluents

Methods of air sampling have been described in a separate lecture. Application of these methods to sampling gaseous effluents from a duct or stack involve, (1) careful sampler design to insure that a representative sample is presented to the sampling media, (2) selection of sampling media to match the chemical and physical forms of the nuclides being sampled, and (3) for constant monitoring devices, selection of the detector to match the radiations given off by the nuclides to be monitored.

Specific applications include the use of filter paper for collecting particulates; caustic scrubbing columns for collecting iodine, ruthenium, and oxides of carbon and sulfur; charcoal cartridges or charcoal impregnated filter paper for collecting iodines; and cartridges of silica gel for collecting tritium oxide.

Direct in-line monitoring of gaseous effluent streams is usually impractical for the low concentrations being routinely discharged to the environs. However, such monitoring might be used to signal off-standard conditions requiring emergency shut down of the facility.

2. Environs Monitoring

If the nuclear facility is a power reactor operated under an AEC license, the monitoring performed in the environs will only be used to confirm that the effluent concentrations are under control and to guard against any reconcentration in the environs.

Air monitoring can be accomplished by four to six permanent stations located around the reactor in a pattern which will permit comparison of up wind and down wind results. An air filter sample should be operated at each station. Filter samples should be counted for gross beta and occasionally for gross alpha. Analysis for specific nuclides will normally be prohibited by the low concentrations encountered. Ion chambers should be used to measure gamma dose rates at each station. At least one of the chambers located in the direction of the prevailing wind should be connected to an automatic recording device. Film badge dosimeters make an inexpensive back-up device to record gamma radiation doses which might exist during an emergency situation.

Spot samples of water, soil, and biological materials can be collected approximately monthly. Normally, only gross measurements are required with an occasional analysis for a specific nuclide likely to be released from the plant. These samples should be collected from all compass points around the reactor to provide comparative data from areas not being affected by the reactor. Complete definition of the behavior of all effluents is not specifically required of a licensee, and effluent concentrations will normally be low enough so that the environmental behavior could not be determined anyway.

The environs monitoring program of an AEC contractor is likely to be complicated by the necessity to evaluate all possible pathways of environmental exposure. The following section describes Hanford's Environmental Monitoring program as an example of the type required of an AEC contractor at a site where both reactors and fuel processing plants are being operated.

IV. HANFORD'S ENVIRONMENTAL MONITORING PROGRAM

A. Organization and Functions of ES&ES

The Environmental Studies and Evaluation Section is a part of the Radiation Protection Department of Pacific Northwest Laboratories.

The ES&ES organization structure is shown in the chart on page IV-2.

The functions of the group are to:

1. detect, measure, and follow trends of environmental contamination;
2. evaluate and report findings in terms of radiation doses to people in the environs of Hanford;
3. perform R&D on the effects of Hanford on the environs including the Columbia River, and on mechanisms of environmental exposure in general.

Sources of radiation exposure in the Hanford environs are listed in Appendices A, B, and C.

B. Radioactive Materials in the Columbia River

1. Sources

a. Production Reactors

The main contributor of radioactive materials to the Columbia River is the cooling water from the Production Reactors. This water is derived from the river, put through filtration processes and then passed once through the reactors, before being returned to the river. The effluent water contains radioactive materials from fission of natural uranium in the river water, from ruptures in fuel elements, and from neutron activation of stable elements in the cooling water and structural materials.

ENVIRONMENTAL STUDIES AND EVALUATION

Grab samples of reactor cooling water effluent are collected at these reactors by IPD personnel. Environmental Monitoring (EMU) collects a continuously composited sample once per week from these effluent streams just before they enter the river.

The 100-N production reactor employs recirculating primary cooling water and as a result negligible amounts of radioactive material are released to the river from this facility.

b. PRTR

The Plutonium Recycle Test Reactor (PRTR) located at 300 Area uses recirculating Heavy Water cooling and as a result contributes negligible amounts of radioactive material to the Columbia River. The effluents of highest potential radionuclide concentrations are sampled prior to release by PRTR operating personnel. If the concentration exceeds 5×10^{-5} $\mu\text{c } \beta/\text{cc}$ these effluents are routed to the 340 waste handling facility in the 300 Area.

c. 200 Area Liquid Wastes

Liquid wastes from the Chemical Separations Plants are discharged to the ground at the 200 Areas. These gradually migrate to the Columbia River in a time period currently estimated at 6 to 7 years. Insignificant amounts of H^3 and Ru^{106} are now thought to be entering the river from these waste sources. The quantities are so low that no increased river concentrations of these nuclides are detectable.

d. Fallout

In addition to the plant contributions, river water contains some small amounts of fallout radionuclides principally Sr^{90} ($\sim 10^{-9} \mu\text{c/cc}$) and H^3 ($\sim 10^{-6} \mu\text{c/cc}$).

2. Exposure Pathways

a. External Radiation

People using the Columbia River for water skiing, swimming, or boating receive some small increment of external gamma radiation exposure from the radioactive materials in the water (principally Na^{24}). EMU measures this potential radiation exposure by placing pocket type ionization chambers in plastic bottles which are then submerged in the river at selected locations. The dosimeters are replaced weekly and brought to 300 Area where they are read on the Hanford Pencil Reader. Such measurements have indicated average dose rates of 3 mr/day in the vicinity of 300 Area, 2 mr/day at Richland, and 1.5 mr/day at Pasco. For purposes of dose estimation it is assumed that the ardent water sport fan spends 240 hours (10 days equivalent) on the river.

Dose rate measurements made over mud at the Columbia River shoreline in the vicinity of Richland during 1964 were about 0.1 mr/hr. For purposes of dose estimation, the assumption is made that an ardent fisherman might spend up to six hours per week, 35 weeks of the year fishing from the Columbia River shore.

Recent attempts at improvement of evaluation of external doses received via water borne nuclides includes tests of waterproof containers for film badges and the use of the 40 liter low background ion chamber to measure shoreline dose rates. The use

of badges in place of pocket dosimeters for immersion dose measurements would permit longer periods between dosimeter exchange and would yield improved results at reduced cost.

b. River and Drinking Water

River water samples are collected on weekly to monthly schedules from Vernita Ferry, Hanford Ferry, Ringold, 300 Area, Richland, Pasco, McNary Dam, the Dalles Dam, and Bonneville Dam. Analyses range from gross alpha and beta measurements to detailed radioisotopic measurements.

Sanitary water supplies are sampled weekly to monthly at 100-F, 200-West and 300 Areas, Richland, Pasco, and Kennewick. Radioisotopic analyses are performed in sufficient detail to define annual internal radiation exposure to the whole body, bone, thyroid, and GI tract for an "average" Tri-City resident and a hypothetical "maximum individual".

c. Irrigation with Columbia River Water

Irrigation is a negligible source of crop contamination compared to direct deposition of airborne materials. Cattle grazed on river irrigated pasture will yield beef with detectable Zn^{65} but no P^{32} . Milk from such cattle contains small amounts of both Zn^{65} and P^{32} . Milk from six local dairy farms are sampled weekly, three commercial brands of milk are purchased twice per month from local stores and two separate milk shed composites are collected from a local creamery twice per month. Meat, eggs, and produce in season are sampled at frequent intervals to measure plant and fallout radionuclides contributed via the river, and via atmospheric deposition.

d. Fish and Waterfowl

Fish and ducks will pick up some P^{32} and Zn^{65} in the Columbia River below the reactors. Migratory ducks can also pick up some fission product radionuclides from the surface ponds used for low level liquid waste disposal in the 200 Areas. EMU personnel sample ducks by hunting during the regular season. Analyses show that only ~ 30% of the ducks collected contained detectable radioactivity in the flesh during 1964.

Fish are collected by rod and reel or gill net. Whitefish are the species with the highest concentrations of P^{32} in the flesh. During 1964 the average and maximum P^{32} concentrations in flesh of whitefish caught below the reactor areas were 400 and 4,900 pc/gram, respectively. Average and maximum Zn^{65} concentrations were 30 and 100 pc per gram of flesh.

Evaluation of the radiation exposure of consumers involves not only measurement of the radionuclides in the food but also an estimate of the quantities eaten fresh and the quantities preserved by smoking or freezing. The latter data is important in the instance of P^{32} which is a relatively short-lived nuclide (~ 2 weeks half-life). For the past few years the state game department has conducted under contract to RL00, a creel census among local river fishermen. Data collected includes amounts caught, methods of preservation and number of persons consuming the fish.

These data indicate that even though whitefish are the species with the highest P^{32} concentrations, other species, such as

bass and crappies, are eaten in sufficiently large quantities by a few people to represent a rate of intake of P^{32} comparable to that via whitefish.

A few whole body counts have been obtained on fishermen to check their uptake of Zn^{65} versus the data they supplied to the creel census. Body burdens measured to date are lower than expected. This indicates that either the fishermen overestimate their catch and consumption, or that Zn^{65} is taken up less readily than predicted by the "standard man" parameters. The latter possibility seems unlikely based on the results of a fish eating experiment performed two years ago. In this test, a volunteer consumed 1 meal per week of whitefish of known Zn^{65} content and had his body burden of Zn^{65} measured frequently in the whole body monitor. His uptake of Zn^{65} appeared to be ~ 4 times higher than expected on the basis of "standard man" parameters.

Until recently no means of directly measuring human body burdens of P^{32} was possible. The difficulty arose from the fact that P^{32} emits only beta radiation. A P^{32} counter developed by Radiological Physics is now available for use in counting local fishermen and in a controlled fish eating experiment being conducted by John Honstead of ES&ES.

From these P^{32} counts and from additional Zn^{65} measurements, we hope to learn more about the actual behavior of P^{32} and Zn^{65} in the human body and also how to relate the creel census and analytical data to intake rates of these two nuclides.

e. Oysters

Zinc-64 and some P^{32} persist in the Columbia River to the Ocean and are accumulated by aquatic organisms especially shellfish. Samples of oysters are sent to EMU two times per month from commercial oyster beds. The annual average oyster content in 1964 was 30 pc Zn^{65} /gram and 5 pc P^{32} /gram.

D. Radioactive Materials in the Air1. Sourcesa. CPD Stacks

The CPD stacks are the main Hanford contributors of radioactive materials to the atmosphere. Redox and Purex Separations Plant stacks release I^{131} at the rate of 2 c/week, annual average, the current stack release guide set by BNW. Strontium semiworks and "B" Plant stacks contribute some small amounts of Sr^{89} , Sr^{90} , and other long-lived nuclides during fission product recovery work. The emission of Sr^{90} is well below the current release guide of 10^{-2} c/week. CPD personnel assumed responsibility for monitoring their own process stacks on January 4, 1965. EMU previously performed this service.

Reactor Stacks

No releases of any significance to the environs outside of the immediate area have ever occurred from a reactor stack at Hanford. Some small amounts of noble gases, tritium C^{14} , S^{35} , and radioactive particulate materials are currently released from these stacks. The reactor stacks are sampled because of the potential for a significant release during a major accident. IPD personnel assumed responsibility for monitoring their own process stacks on

January 4, 1965. EMU previously performed this service.

c. Other Hanford Sources

Research facilities are capable of releasing short-lived fission products during handling of irradiated specimens or long-lived fission products during studies on waste recovery. Stacks from these facilities including Radiometallurgy (327 Building), Radiochemistry (325 Building), and Critical Mass Laboratory (209-E Building), are also sampled by EMU. Facilities of lesser potential are monitored by the operating department (such as 234-5, 233-S, 231-Z) or by RMU (Biology Laboratory vents, 306 Building thorium facilities).

In addition to plant sources, radioactive contamination of the atmosphere also results from fallout of debris from weapons testing. Fresh fallout contains I^{131} and $Ba-La^{140}$, while older materials contain $Zr-Nb^{95}$, Sr^{89} , Sr^{90} , Cs^{137} , and $Ce^{144}-Pr^{141}$.

2. Exposure Pathways

a. Inhalation

Iodine-131 is the only measurable, but still insignificant, source of human radiation exposure via inhalation of Hanford originated materials. Concentrations of I^{131} in the atmosphere are measured on and off-project by means of caustic scrubbers. Each plant area has at least one permanent atmospheric monitoring station ("614 Building") where air samples are collected for measurement of radioactive particulates, gaseous I^{131} , and where ambient gamma radiation dose rates are monitored and recorded. Each of the Tri-Cities and Benton City are also equipped with a "614-Building".

Smaller, transportable structures, referred to as "dog houses", are used in more remote areas on and off the plant to house the air sampling equipment. A film badge dosimeter is placed in each "dog house" for measurement of gamma dose in the event of a major plant accident.

During 1964 the annual average I^{131} concentration in the air of the Tri-Cities was at or below the detection limit of 1×10^{-14} $\mu\text{c/cc}$. During 1963 the average had been 2×10^{-14} $\mu\text{c/cc}$.

b. Milk

Radionuclides detected in local milk are mainly I^{131} plus some Sr^{90} from fallout. Some P^{32} and Zn^{65} can be detected in milk when the cows are on a pasture that has been irrigated with Columbia River water drawn from below reactors. EMU samples milk and pasture grass from six local dairy farms weekly; collects two milk shed composites, twice per month; and three commercial brands of milk are purchased from a local store twice per month. Iodine-131 content of local milk averaged 3 to 5 pc/l during 1964.

A small contribution to this average was made by the influx of I^{131} with small amounts of fallout materials from the Chinese nuclear test of October 16, 1964. During late October and early November I^{131} concentrations in local milk reached a peak value of 36 pc/l at one farm. During the remainder of the year all concentrations were at or below 10 pc/l.

During September, 1963 unplanned release of ~ 65 curies of I^{131} from a CPD stack gave ES&ES an opportunity to investigate the relationships between amounts of I^{131} released and the subsequent concentrations appearing in air, pasture grass and milk. A peak milk concentration of 140 pc/l and an extrapolated peak of 450 pc/l were determined in the local environs. Maximum dose from this release was estimated to be 0.03 rem to the thyroid of a four year old child residing on the farm where the maximum concentrations of I^{131} in milk were determined.

Strontium-90 in local milk ranged from 3 to 16 pc/l in 1964 and averaged 6 pc/l, typical of measurements made by USPHS and Washington State Department of Health for this part of the country. Sr^{89} in milk was usually below the detection level of 4 pc Sr^{89} /l. Levels of Cs^{137} were about 100 pc/l milk in early 1964, and steadily decreased to about 70 pc/l by the end of the year.

c. Contamination in Crops

Very small concentrations of I^{131} are found on leafy vegetable as a result of Hanford operations. Some I^{131} and Sr^{90} are present from fallout. The closest farming areas to the CPD stacks are ~ 13 miles away. Under most meteorological conditions this distance affords adequate dilution before radioactive effluents reach the farming areas. The I^{131} content of the majority of the crop sampled during 1964 was at or below the detection level of 50 pc/Kg. Iodine-131 intake can be calculated directly from our numerous measurements for this isotope in leafy

vegetables by assuming typical dietary habits.

Crop samples collected by EMU are periodically analyzed for Sr^{89} and Sr^{90} content. These measurements indicate that the Sr^{90} content of local crops is typical of that expected from fallout alone, but sufficient data is not obtained from our measurements to accurately calculate the Sr^{90} intake of local residents. The Health and Safety Laboratory of the AEC has measured the Sr^{90} content of typical diets. Their data indicates that about 40% of the total intake of this nuclide is from milk and 60% is from other foodstuffs. Locally produced milk contained an average of 6 pc Sr^{90} /l in 1964, and if a person consumes 1 liter per day of milk, then milk should provide 6 pc Sr^{90} /day intake. Other foods should therefore have provided about 9 pc Sr^{90} /day intake for a total of 15 pc/day during 1964. This estimate of Sr^{90} intake is about one-half of the estimate for 1963 (33 pc/day).

d. Beef Thyroids

Cattle thyroids are sampled at five slaughterhouses several times per month by local veterinarians and shipped to EMU. These samples are then analyzed for I^{131} by gamma-scan.

Concentrations of I^{131} are 10^2 to 10^3 higher in beef thyroids than in milk and pasture grass, so thyroids are a good trend index when I^{131} in the others is too low to measure.

E. Miscellaneous Measurements

1. External Gamma Dose

Stray Radiation Chambers are used near the Y-Barricade and at the 747 Building in Richland to measure gamma radiation dose rate. During 1964 the average gamma dose rate was ~ 0.5 mr/day, nearly all due to fallout plus natural background radiation.

2. Ground Surveys

Small areas of ground (100 ft^2) called "control plots" are surveyed repetitively for a trend indicator and to detect releases of radioactive materials which might otherwise be missed.

Plots are established around Purex and Redox stacks and others are located on Wahluke Slope. These are surveyed monthly to quarterly and the number of radioactive particles plus survey instrument readings are recorded.

Solid waste burial grounds are surveyed twice a year to check on contamination, status of fences and signs, and housekeeping.

In addition to direct ground surveys, quarterly flights are made with aerial survey equipment over the project, down river, and over the local environs to measure background and check for unsuspected contamination. These periodic flights also ensure that the equipment is in good working order for use in an emergency.

F. Composite Dose (See Annual Reports such as HW-80991 for 1963, for details)1. Exposure Limits for Various Critical Organsa. GI Tract

1. NCRP - 1500 mrem/year
2. FRC - Maximum Individual 1500 mrem/year
3. FRC - Average of suitable sample, 500 mrem/year

b. Total Body

1. NCRP - 500 mrem/year
2. FRC - Maximum Individual 500 mrem/year
3. FRC - Average of suitable sample, 170 mrem/year

c. Thyroid

1. NCRP - 300 mrem/year
2. FRC - Maximum Individual, 1500 mrem/year
3. FRC - Average of suitable sample, 500 mrem/year
4. FRC - Annual Average intake of 100 pc of I^{131} per day
 $\approx$ 500 mrem/year to thyroid of small child.

d. Bone

1. FRC - Maximum Individual, 1500 mrem/year
2. FRC - Average of suitable sample, 500 mrem/year
3. FRC - Specific Nuclides expressed as permissible daily
 intakes on an annual average basis.

Sr^{89}	-	2000 pc/day
Sr^{90}	-	200 pc/day
Ra^{226}	-	20 pc/day

2. Biological Parameters

- a. ICRP standard man parameters for uptake and retention and dose versus organ burden.
- b. 2 gram thyroid size used for child in place of 20 gram size for standard man.

3. Maximum Individual's Diet

- a. Lives in Pasco and drinks city water at the rate of 2 ℓ /day (730 ℓ /yr).
- b. Buys meat, produce and milk from Riverview farms irrigated with Columbia River water.

Meat	227 g/d	(80 Kg/yr)
Milk	1.05 ℓ /d	(380 ℓ /yr)
Fresh Leafy Vegetables	200 g/d	(30 Kg/yr)*
Other Vegetables and Fruit	1430 g/d	(215 Kg/yr)*

- c. Eats 200 meals per year of bass, perch, crappie and whitefish caught in Columbia River below the reactors. (40 Kg/yr)

4. Average Adult Diet

- a. Lives in Richland and drinks city water at 1.2 ℓ /d (440 ℓ /yr)
- b. Buys all meat, sea food, produce and milk in local grocery store.

meat	227 g/d (80 Kg/yr)
sea food	15 g/d (5.5 Kg/yr - 10% from Pacific Coast)
milk	0.85 ℓ /d (310 ℓ /yr)
leafy vegetables	100 g/d (36.5 Kg/yr)

*This produce is for the 5 months local growing season. During the remaining 7 months, the produce eaten is assumed to contain no radionuclides of Hanford origin, except Zn^{65} in "Other Vegetables and Fruit" at a total consumption of 520 Kg/year.

5. Modification for Children's Thyroid Dose

- a. The "maximum" child is a Pasco resident drinking 290 l/year of city water, 365 l/year of Riverview milk and eating 18 Kg/year of fresh leafy vegetables from the Riverview area.
- b. The "average" child is a Pasco resident drinking 145 l/year of city water, 220 l/^{year} of Riverview milk, and eating 9 Kg/year of fresh leafy Riverview vegetables.

6. Modification of Sr⁹⁰ Intake

- a. The Health and Safety Lab of AEC studies U.S. Diets and calculates Sr⁹⁰ intake rates. Their results indicate that 40% of the Sr⁹⁰ intake with foods is from milk and 60% from other foods. They consider water as a separate source of Sr⁹⁰.
- b. Total Sr⁹⁰ intake with food for local residents should be about 2.5 times the Sr⁹⁰ intake from local milk alone. Columbia River water is a negligible source of Sr⁹⁰ (≤ 1 pc/l),

7. 1964 Composite Doses

Type of Person	Organ	mrem/year	% of Applicable FRC Guide
Hypothetical)	GI Tract	140	9
Maximum)	Total Body	100	20
Adult)	Thyroid	16	1
	Bone	-	30
Average)	GI Tract	50	10
Richland)	Total Body	12	7
Resident)	Thyroid	13	3
	Bone	-	8
Maximum Child	Thyroid	75	5
Average Child	Thyroid	28	6

V. BIBLIOGRAPHY

A. Standards and Guides

1. Advisory Committee on X-ray and Radium Protection (later renamed the National Committee on Radiation Protection) "X-Ray Protection" U. S. Department of Commerce, National Bureau of Standards, Handbook 15, Washington, D. C. (1931)
2. National Committee on Radiation Protection, "Permissible Dose from External Sources of Ionizing Radiation". U. S. Department of Commerce, National Bureau of Standards, Handbook 59, Washington, D. C. (1954)
3. National Committee on Radiation Protection and Measurement, "Maximum Permissible Body Burdens and Maximum Permissible Concentrations of Radionuclides in Air and Water for Occupational Exposure". U. S. Department of Commerce, National Bureau of Standards, Handbook 69, Washington, D. C. (1959)
4. U. S. Atomic Energy Commission, "Permissible Levels of Radiation Exposure", AEC Manual Chapter 0524, Washington, D. C. (1958)
5. U. S. Atomic Energy Commission, "Codes and Standards for Health, Safety and Fire Protection", AEC Manual Chapter 0550, Washington, D. C. (1961)
6. International Commission on Radiological Protection, "Recommendations of the International Commission on Radiation Protection, (Revised December 1, 1954)" British Journal of Radiology, Sup. No. 6 (1955)
7. U. S. Atomic Energy Commission, "Standards for Protection Against Radiation", Code of Federal Regulations, Title 10 - Atomic Energy, Chapter 1 - Atomic Energy Commission, Part 20 - Federal Register, Document 58-5775, Washington, D. C. (July 30, 1958)
8. International Commission on Radiological Protection, "Recommendations of the International Commission on Radiation Protection, (Adopted September 9, 1958)
9. International Commission on Radiological Protection, "Report of Committee II on Permissible Dose for Internal Radiation", Health Physics, Vol. 3, (1959)
10. Federal Radiation Council, "Radiation Protection Guidance for Federal Agencies (Report No. 1)", Federal Register Document 60-4539, Washington, D. C. (May 18, 1960)
11. Federal Radiation Council, "Radiation Protection for Federal Agencies (Report No. 2)", Federal Register Document 61-9204, Washington, D. C. (September 26, 1961)

12. Federal Radiation Council, "Health Implications of Fallout from Nuclear Weapons Testing through 1961 (Report No. 3)", (May 1962)
13. Federal Radiation Council, "Estimates and Evaluation of Fallout in the United States from Nuclear Weapons Testing Conducted through 1962 (Report No. 4)", (May 1963)
14. U. S. Public Health Service, "Drinking Water Standards 1962", P.H.S. Publication No. 956, U. S. Government Printing Office, (1962)
15. Tsivoglou, Ernest C. and Burte, George W., Jr., "Radioactivity Standards for Water", Journal American Water Works Association, Vol. 55, No. 6, (June 1963) pp. 668-676.
16. Morgan, G. W., "AEC Program for State Regulation of Certain Phases of Atomic Energy", Health Physics, Vol. 9, No. 2, pp. 239-241, (February 1963)
17. Harwell, W. L., Glennin, F. N., and Smith, J. L., "Atomic Regulation by States", Nuclear Safety, Vol. 4, No. 2 (December 1962), pp. 14-26.

B. Sampling Theory and Statistics

1. Hansen, M. H., Hurwitz, W. N. and Madow, W. G., "Sampling Survey Methods and Theory", Vol. I and II, John Wiley and Sons Inc., New York, (1953)
2. Sukhatme, P. V., "Sampling Theory of Surveys with Applications", Iowa State College Press, Ames, Iowa. (1954)
3. Yates, F., "Sampling Theory for Censuses and Surveys", Charles Griffin and Co. Ltd., London, (1949)
4. Kerr, Gerald W. (Pratt & Whitney), "Statistical Treatment of Environmental Radioassay Data", Health Physics, 6:152-62 (October 1961)

C. Radiochemical Analysis

1. Boni, A. L., "Improved Techniques for Environmental Sample Analysis", Health Physics, Vol. 9, No. 11, pp. 1035-1046, (November 1963)
2. Goldin, A. S., Straub, C. P., "Radiochemical Analysis for Preoperational Surveillance", Analytical Chemistry in Nuclear Reactor Technology Part 2 Instrumentation, Remote Control Techniques and Nucleonics, Second Conference, Gatlinburg, Tennessee. September 29 - October 1, 1958. Oak Ridge National Laboratory, TID-7568. (1959)
3. "Standard Practices Radiochemical Procedures for Off-Site Environmental Samples", HW-81277 (Unclassified) Rough Draft, (April 1964)

D. General Considerations

1. Sax, N. Irving; and Gabay, Jack J., "Public Health Aspects of Environmental Radiation", NP-11641
2. Harris, W. B., Dunster, H. S., "Examining the Value of Reactor-Site Environmental Surveys", A United States View; A United Kingdom View. Nucleonics 18, pp. 67-68. (1960)
3. Goldman, M. I., McCullough, D. R., and Witzig, W. F., "Environmental Monitoring at Nuclear Facilities", Preprint No. 73, New York, (Nuclear Utility Services, Inc., Washington, D. C.) Engineers Joint Council, (1962)
4. Pelletier, Charles A., "Environmental Surveys for Nuclear Facilities", Nucleonics 17, No. 1, (January 1959)
5. Palmer, G. H., "Environmental Survey Around an Atomic Energy Site", U. K. A.E.A. Report AERE HP/R 2742.
6. Whipple, G. Hoyt, "Surveying for Environmental Radioactivity", Proceedings of the Thirteenth International Congress on Occupational Health, New York, U. S. Executive Committee of the Thirteenth International Congress on Occupational Health, 1961, pp. 171-178.
7. Straub, Conrad P., "Types and Objectives of General and Local Monitoring Programs", FAO/WHO/IAEA Seminar on the Agriculture and Public Health Aspects of Radioactive Contamination in Normal and Emergency Situations. The Hague, Netherlands, (Dec. 11-15, 1961)
8. Fish, B. R., and Abee, H. H., "Selection of Samples for Area Monitoring", Nuclear Safety, Vol. 4, No. 4, pp. 112-116, (June 1963)
9. Farmer, F. R., (U.K. A.E.A.), "The Evaluation of Power Reactor Sites", Preprint Paper No. 77, 1962 Nuclear Congress June 4-7, New York, New York. Engineers Joint Council.
10. Grummitt, W. E., "Environmental Surveys for Nuclear Power Stations", AECL-1656, December 1962, (CRER-1120).
11. Barry, P. J., "Planning an Environmental Survey for a Nuclear Power Plant", J. Air Pollution Control Association, 11(1):14 (January 1961)
12. Abott, John D., and Lakey, J. R. A., "Environmental Radiation Survey Around a Nuclear Power Station", Atomic Energy Review, Vol. 2 pp. 200-204, (1960)
13. Whipple, G. H., "Preoperational Environmental Survey for a Power Reactor", American Industrial Hygiene Association Journal, Vol. 18, No. 4, pp. 315-318, (December 1957)

14. A. S. A., "Current Practices in Disposal of Waste Radioactive Gases from Nuclear Reactors", (Draft No. 5 June 1963), Sectional Committee No. 5 Nuclear Fuel Cycle Engineering Working Group No. 4, Review of Current Practices, Subcommittee No. 5.2 on Radioactive Waste Disposal, C. E. Stevenson-Leader, C. S. Abrams, R. G. Beverly, I. B. Dick, F. Fack, and C. F. Stolzenbach.

E. Sampling Devices

1. Saxby, W. N. (U.K. A.E.A., Aldermaston, Berks, Eng.), "Air Sampling: Some Problems", Annals of Occupational Hygiene, Vol. 4, pp. 152-8, (December 1961)
2. Schwendiman, L. D., Reick, H. G., and Harvey, R. A., "Automatic In-Line Analyzers for Radioactive Constituents in Liquid and Gaseous Waste Streams", P/394. Proceedings of Second U. N. International Conference on the Peaceful Uses of Atomic Energy, Vol. 23, pp. 414-18. (1958)
3. Merrit, W. F., and Parsons, P. J., "Sampling Devices for Water and Soil", Disposal of Radioactive Wastes, Conference Proceedings, Monaco, November 1959, Vol. 2, pp 329-338.

F. Ground Contamination and Food Chains

1. Chamberlain, Gower and William, "Environmental Monitoring After Accidental Deposition of Radioactivity", J. Nuclear Engineering Parts A/B, Vol. 14, pp. 156-67, (1961)
2. Garner, R. J., "An Assessment of the Quantities of Fission Products Likely to be found in Milk in the Event of Aerial Contamination of Agricultural Land", Nature 186, (1960)
3. Garner, R. J., "Environmental Contamination and Grazing Animals", Health Physics, Vol. 9, pp. 567-605, (June, 1963)
4. Russel, F. Scott., "Radioisotopes and Environmental Circumstances: The Passage of Fission Products Through Food Chains", Radioisotopes in the Biosphere, University of Minnesota, pp. 269-292, (1960)
5. Subcommittee of the Food Protection Committee, NAS-NRC, "Radio-nuclides in Foods", Health Physics, Vol. 9, No. 6, pp 569-596, (June, 1963)
6. Food and Agriculture Organization of the United Nations, Organization of Surveys for Radionuclides in Food and Agriculture", FAO Atomic Energy Series, No. 4, (1961) (Also has good review of EM programs at specific sites)

G. Surveys at Specific Sites

1. Garner, R. J., (AHSB(RP)R-26), "Environmental Monitoring in Relation to Gaseous Discharges from UK AEA Establishments", August, 1963.

2. "Radiation Hygiene in and Around a Nuclear Power Station", J. H. Martin (UK AEA, Annan, Scotland), Atom, No. 81, pp. 219-28, (July 1963) (The operation of Chapelcross is presented in relation to its experiences in radiation safety.)
3. Davies, Sherwood, "Protecting the Environment around a Nuclear Power Reactor - A State Health Department Acts", American Journal of Public Health, Vol. 52, pp. 1993-2000, (December 1962) (Monitoring program for Indian Point Reactor Environs.)
4. Westinghouse Electric Corp., "Preoperational Radiation Survey of the Shippingport Atomic Power Station Site and Surrounding Area", WAPD-CTA(IH)-208, 1958.
5. Long, F. J., "Radiation Monitoring at the Shippingport Atomic Power Station", WAPD-T-624 (REV).
6. Manneschildt, J. F., and Witkowski, E. J., "The Disposal of Radioactive Liquid and Gaseous Waste at Oak Ridge National Laboratory", ORNL-TM-282, Paper presented at Conference on Light-Water-Moderated, Research Reactors, June 1962. Gatlinburg, Tennessee.
7. Friend, Albert G. and Porcella, Donald B., (US Public Health), "Studies on the Distribution of Radionuclides in the Clinch and Tennessee Rivers Below Oak Ridge", Preprint Paper No. 75, 1962 Nuclear Congress, New York, N. Y., June 4-7, Engineers Joint Council.
8. Abee, H. H. and Cottrell, W. D., "Contamination Resulting from the Release of Radioactive Liquid Wastes to the Tennessee River System", AIHA Journal, Vol. 21, No. 2, pp. 156-161, (April 1960)
9. Manneschildt, J. F., "Equipment and Procedures for Stack Gas Monitoring at ORNL", ORNL-TM-141, February 13, 1962.
10. Kennedy, M. R., "Health Physics Manual of Environmental Monitoring, Knolls Atomic Power Lab.", KAFL-A-HP-6, 1960.
11. Washington State Department of Health, Air, Sanitation and Radiation Control Section, "Environmental Radiation Surveillance, Second Annual Report", August 1963.
12. Nehemias, John V., Whipple, G. Hoyt., "The Preoperational Environmental Survey for the Enrico Fermi Reactor - 1958", AIHA Journal, Vol. 21, No. 2, pp. 144-150, (April 1960)
13. Hughes, J. H., "The Environs Monitoring Program for the Dresden Nuclear Power Station", Paper presented at Fifth Annual Meeting Health Physics Society, June 29-July 1, 1960, Boston, Mass. Health Physics, Vol. 4, p. 198, (1960)
14. Selby, J. M., Willis, C. A., Bowen, B. M., and Edgerton, J. H., "Radiation Effects of a 10-MW Reactor on Environs of AFP 67", Health Physics 4 (1960) 199 (Abstract only), Health Physics, Vol. 6, pp. 126-135, (October 1961)

15. Selby, J. M., et. al., "Environmental Monitoring at Georgia Nuclear Laboratories" - AFP 67.
16. Selby, J. M., et. al., "A Proportional Continuous River and Stream Water Sampler at Georgia Nuclear Laboratories", Health Physics, Vol. 6, No. 3/4, pp. 149-151, (October 1961)
17. Hoy, J. E., and Landon, L. F., (Du Pont de Nemours), "Background Radiation Measurements in the Environs of the Savannah River Plant", 1952-1963, DPSPU-63-30-8, March 1963.
18. Reinig, W. C., "The 1951 Preoperational Environmental Survey for the Savannah River Plant - In Retrospect", Health Physics, Vol. 9, No. 1, pp. 83-85, (January 1963)
19. Singlevich, W., et. al., "Natural Radioactive Materials at the ARCO Reactor Test Site", HW-21221, May 28, 1951, (Declassified).
20. Junod, T. L. "Stack and Water Effluent Monitor Systems at Plum Brook Reactor Facility", Abstract of paper presented to 1960 Annual Health Physics Society Meeting, Health Physics, Vol. 4, No. 2, p. 192, (December 1960)

H. Hanford Reports

1. Foster, R. F., "Radiological Aspects of Hanford Land Utilization", HW-76772, February 26, 1963.
2. Foster, R. F., Junkins, R. L., and Lindereth, C. E., "Waste Control at the Hanford Plutonium Production Plant", Journal Water Pollution Control Federation, Washington, D. C., May 1961.
3. McConnon, D., "Radioiodine Sampling with Activated Charcoal Cartridges", HW-77126, April 19, 1963.
4. McConnon, D., "The Status of Gaseous Effluent Monitoring at HAP0", December 1961, HW-69205, August 27, 1962.
5. Soldat, J. K., "Monitoring for Air-Borne Radioactive Materials at Hanford Atomic Products Operation", HWSA-38, 1959.
6. Soldat, J. K., "Management of Radioactive Effluent Gases of HAP0", HWSA-2629 REV, October 1962, (Unclassified).
7. Bustad, L. K., "Radioisotopes and Environmental Circumstances: Significance of Nuclear Industry Effluents in Animal Populations", Radioisotopes in the Biosphere, University of Minnesota, 1960, pp. 234-254.
8. Wilson, R. H., "The Columbia River Environmental Monitoring Program", HW-75076, October 1, 1963 (Unclassified).

9. Stringer, J. L., "Radiological Monitor for the Columbia River", HW-79186, October 1963, (Unclassified).
10. Hall, R. B. and Wilson, R. H., "Evaluation of Discharging Radioactive Wastes into Fresh Water Systems", HWSA-2748, October 1962.
11. Foster, R. F., and Junkins, R. L., "Off-Project Exposure from Hanford Reactor Effluent", HW-63654 REV, February 1, 1960.
12. Backman, G. E., "Dispersion of 300 Area Liquid Effluent in the Columbia River", HW-73672, May 25, 1962.
13. Foster, R. F., Backman, G. E., Wittenbrock, N. G., and Skarpelos, J. M., "Factors Establishing Limits for Release of Effluents from the Plutonium Recycle Test Reactor", J. of Sanitary Engineer Division, ASCE, Vol. 89, No. SA6, Proc. paper 3733, pp. 17-35, (December 1963).
14. Backman, G. E., "Design Limits for Radioactive Waste Disposal from the Fuels Recycle Pilot Plant", HW-69988 REV2, September 14, 1962.
15. McConnon, D., "Dose Rate Measurements of Beaches and Islands on the Columbia River Between Ringold and Richland", HW-72229 REV. August 10, 1962.
16. Foster, R. F., "Accumulation of Zn^{65} from Prolonged Consumption of Columbia River Fish", HWSA-3060, 1963.
17. Healy, J. W., et al., "Radiation Exposure to People in the Vicinity of a Major Production Atomic Energy Plant" - P/743, Proceedings of Second U. N. International Conference on Peaceful Uses of Atomic Energy, Vol. 18, pp. 309-18, (1958). (Discusses 1957 environs data and evaluates it in terms of radiation exposure in the neighborhood of the plant).
18. Andersen, B. V., HW-61676, (Unclassified), "Hanford Environmental Monitoring Annual Report - 1958", August 27, 1959.
19. Junkins, R. L., et al., HW-64371, (Unclassified), "Evaluation of Radiological Conditions in the Vicinity of Hanford for 1960", June 1, 1961.
20. Environmental Studies & Evaluation Staff, HW-68435, (Unclassified), "Evaluations of Radiological Conditions in the Vicinity of Hanford for 1960", June 1, 1961.
21. Environmental Studies & Evaluation Staff, HW-71999, (Unclassified), "Evaluation of Radiological Conditions in the Vicinity of Hanford for 1961", March 1, 1962.
22. Environmental Studies & Evaluation Staff, HW-76526, (Unclassified), "Evaluation of Radiological Conditions in the Vicinity of Hanford for 1962", February 25, 1963.
23. Environmental Studies & Evaluation Staff, HW-80991, (Unclassified), "Evaluations of Radiological Conditions in the Vicinity of Hanford for 1963", February 24, 1964.

APPENDIX ASOURCES OF ENVIRONMENTAL RADIATION EXPOSUREI. EXTERNALA. Plant Sources

1. Airborne
 - (a) Gaseous and Particulate
2. Deposited on Vegetation and Ground or in Water
3. Water - Liquid Waste Disposal
 - (a) Swimming
 - (b) Boating

B. Fallout

1. Airborne Material
2. Deposited on Vegetation, Ground, or in Water

C. Natural Background Radiation

1. Cosmic Rays
2. Radon, Thoron, and their Decay Products
3. Radioactive Substances in Soil, Rocks, Water, Building Materials, etc.

D. Medical Exposures

1. Diagnostic X-Rays - Chest, GI Tract, etc.
2. Dental X-Rays
3. Treatments for Cancer and Dermatitis

II. INTERNALA. Plant Sources

1. Breathing Airborne Materials
 - (a) Gaseous - I^{131} , Noble Gases
 - (b) Particulate - F.P.'s., U, and Pu

2. Drinking Water-borne Materials
 - (a) Reactor Cooling Water Radioactivity
 - (b) Fallout of Airborne Materials
3. Eating Vegetation Contaminated by:
 - (a) Water-borne Materials through Irrigation
 - (b) Fallout of Airborne Materials onto Vegetation
4. Eating Meat From:
 - (a) Grazing Animal fed on Irrigated Vegetation
 - (b) Fish caught near the project

B. Fallout

1. Breathing airborne materials
2. Eating vegetation and meat directly or indirectly contaminated
3. Drinking water containing fallout

C. Natural Background Radiation

1. Radon and Thoron and decay products breathed into lungs
2. Eating foods and drinking water containing naturally radioactive materials
3. Natural H^3 , C^{14} , K^{40} , and Ra^{226} in body

D. Medical Treatments

1. Treatments with Isotopes
 - (a) I^{131} - Thyroid
 - (b) P^{32} - Cancer
2. Radioactive Tracer Tests
 - (a) Na^{24} - Blood Circulation Study

APPENDIX BNATURAL BACKGROUND RADIATIONI. EXTERNAL EXPOSURESA. Cosmic Rays

1. 0.1 mr/day at sea level
2. 0.2 mr/day at 5000 feet above sea level

B. Naturally Occurring Radioactive Materials in:

1. Soil, rocks, air, water, and building materials add up to
0.2 mr/day

C. Total Whole Body Exposure

1. 0.3 mrad/day
2. 3 to 4 rad per 30 years

II. INTERNAL EXPOSURESA. Lungs

1. Radon and Thoron and their Decay Products, inhaled
2. One (1) to 50 mrem/day

B. Bone

1. Ra^{226} and K^{40} in bone and tissues
2. 0.15 mrem/day

C. Gonads

1. C^{14} , K^{40} , Ra^{226} , and Decay Products of Ra^{226}
2. 0.07 mrem/day

D. Body Concentrations

1. H^3 - 3×10^{-5} μc
2. C^{14} - 9×10^{-3} μc
3. K^{40} - 1×10^{-2} μc
4. Ra^{226} - 2×10^{-4} μc (variable)

III. MISCELLANEOUS DATAA. Radium Springs

1. World Maximum - 7×10^{-4} $\mu\text{c Ra/cc}$ at Masutomi, Japan
2. U. S. Maximum - 3×10^{-4} $\mu\text{c Ra/cc}$ at Boulder, Colorado
3. Generally - Few above 3×10^{-5} $\mu\text{c Ra/cc}$

B. Radium in Tap Water

1. U. S. Generally - 0 to 1×10^{-10} $\mu\text{c Ra/cc}$
2. Joliet, Illinois - 6×10^{-9} $\mu\text{c Ra/cc}$

C. Radon in Air

1. Normally in room air - 10^{-10} to 10^{-11} $\mu\text{c/cc}$
2. In Colorado, uranium mines - 10^{-8} to 10^{-5} $\mu\text{c/cc}$ of air
3. Normally in air of Pacific Northwest - 1 to 5×10^{-11} $\mu\text{c/cc}$

D. Thoron in Air

1. Thoron is normally 0.1 percent to 5 percent of Radon concentrations

E. Uranium

1. In Earth's crust - 10^{15} Tons
2. In oceans - 10^{10} Tons
3. Average in surface soil - 1 to 2 ppm
4. Normally in Columbia, Snake, and Yakima River water - 10^{-9} $\mu\text{c/cc}$
5. Normally in Benton City well water - 10^{-8} $\mu\text{c/cc}$

F. Tritium

1. Total in atmosphere - 2/3 ounce
2. Total in oceans - 2 pounds
3. Total in inland waters - 1/3 ounce

APPENDIX CRADIATION EXPOSURES FROM SOME MEDICAL TREATMENTS AND EXAMINATIONS

<u>Procedure</u>	<u>Exposure</u>
Dental X-Ray	1 to 15 R/film
Chest X-Ray	50 mr/film
Fluorscopy	10 to 20 R/min
Barium Contrast Studies	1 to 2 R/series
G. I. Series	1 to 8 R/series
Pregnancy X-Ray Examinations	20 to 65 R Total
Thymus Treatment	75 to 350 R Total
Acne Treatment	500 to 1000 R Total
Tumor Treatment	3000 to 7000 R Total

APPENDIX DPROBLEMSI. RELEASE TO RIVERA. Problem

Compute the maximum sustained release rate of P^{32} per month from an atomic energy plant into a river using the "water $\rightarrow$ fish $\rightarrow$ human" pathway and the following assumptions:

1. Averaging over a 12 month period is permissible
2. The MPC of P^{32} in drinking water for non-occupational workers is $2 \times 10^{-5} \mu\text{c/cc}$.
3. A person drinks 2200 cc/day
4. The concentration factor $\frac{\mu\text{c/g fish}}{\mu\text{c/cc water}}$ for P^{32} between fish and water is:

Jan.	2,000	May	10,000	Sept.	100,000
Feb.	1,000	June	25,000	Oct.	50,000
Mar.	2,000	July	50,000	Nov.	10,000
Apr.	5,000	Aug.	100,000	Dec.	5,000

5. The flow rate of the river is 80,000 cubic feet per sec.
6. The consumption rate of fish is 200 grams per week but only one fish in ten comes from the contaminated river.

B. Solution

1. Average the 12 concentration factors given in the problem and find the annual average factor to be $30,000 \mu\text{c } P^{32}/\text{g}$ of fish per $\mu\text{c } P^{32}/\text{cc}$ of water.

2. Calculate the river flow rate in terms of cc/month

$$\text{Flow} = 8 \times 10^4 \frac{\text{ft}^3}{\text{sec}} \times 2.83 \times 10^4 \text{ cc/ft}^3 \times 30 \text{ d/month} \times 8.64 \times 10^4 \frac{\text{sec}}{\text{day}}$$

$$\text{Flow} = 5.87 \times 10^{15} \text{ cc/month}$$

3. Assume allowable intake in $\mu\text{c } P^{32}/\text{day}$ is the product of MPC_w and $2.2 \times 10^3 \text{ cc/day}$.

$$2 \times 10^{-5} \mu\text{c/cc} \times 2.2 \times 10^3 \text{ cc/day} = 4.4 \times 10^{-2} \mu\text{c/day}$$

4. Calculate the average number of grams of fish from contaminated river which are actually eaten per day.

$$\begin{aligned}\text{Consumption} &= \frac{200 \text{ g fish/week}}{7 \text{ days/week}} \times \frac{1 \text{ contaminated fish}}{10 \text{ total fish}} \\ &= 2.86 \text{ g/day of contaminated fish eaten}\end{aligned}$$

5. Calculate the P^{32} content of the river and of the fish if one curie of P^{32} per month were discharged to the river.

$$\begin{aligned}\text{Water content} &= 1 \text{ curie} \times 10^6 \frac{\mu\text{C}}{\text{C}} \times \frac{1}{5.87 \times 10^{15} \text{ cc/month}} \\ &= 1.7 \times 10^{-10} \mu\text{C/cc water}\end{aligned}$$

$$\begin{aligned}\text{Fish content} &= 30,000 \times \text{water content} \\ &= 3 \times 10^4 \times 1.7 \times 10^{-10} = 5.1 \times 10^{-6} \mu\text{C/gram fish}\end{aligned}$$

6. Calculate total daily P^{32} intake if 1 c/month were released.

$$\begin{aligned}\text{Intake} &= (1.7 \times 10^{-10} \mu\text{C/cc} \times 2.2 \times 10^3 \text{ cc/d}) + (5.1 \times 10^{-6} \mu\text{C/g} \times 2.86 \text{ g/day}) \\ &= (3.74 \times 10^{-7} \mu\text{C/day}) + (1.46 \times 10^{-5} \mu\text{C/day}) \\ \text{Intake} &= 1.50 \times 10^{-5} \mu\text{C/day}\end{aligned}$$

7. Find ratio of MPRI and intake from one curie per month released.

This ratio is the permissible release rate.

$$\text{Permissible Release Rate} = \frac{(4.4 \times 10^{-2} \mu\text{C/day})}{1.5 \times 10^{-5} \mu\text{C/day/c released/month}}$$

Permissible Release	= $2.9 \times 10^3 \text{ c/month*}$
---------------------	--------------------------------------

*Note: This release limit would be reduced to $\sim 1.5 \times 10^3 \text{ c/month}$ if it were calculated on the basis of the FRC's recommendation of 1.5 mrem/year to the bone of the maximum individual.

II. RELEASE TO ATMOSPHERE

A. Problem

Compute the maximum permissible concentration of I^{131} in the atmosphere outside of an atomic energy plant on the basis of the atmosphere vegetation cow milk human pathway. Use the following assumptions:

1. The maximum permissible rate of intake is 100 $\mu\mu\text{c/day}$
2. Consumption rate for milk is 1 liter/day
3. A cow produces 10 liters of milk/day
4. A cow eats 40 kg of vegetation/day
5. One $\mu\text{c } I^{131}/\text{cc}$ of air leads to $10^{+7} \mu\text{c/g}$ of vegetation
6. 3 percent of the I^{131} eaten by the cow appears in the milk

B. Solution

1. Find intake of cow if air has 1 $\mu\text{c/cc}$.

1 $\mu\text{c/cc}$ in air yields $10^7 \mu\text{c/g}$ vegetation

so cow eats $10^7 \mu\text{c/g} \times 4 \times 10^4 \text{ g/day} = 4 \times 10^{11} \mu\text{c/day}$

2. Find content of milk when 3% goes to milk.

$$\frac{4 \times 10^{11} \mu\text{c/day} \times 0.03}{10 \text{ liters/day}} = 1.2 \times 10^9 \mu\text{c/liter}$$

or milk contains $1.2 \times 10^{15} \mu\mu\text{c/liter}$ when air has 1 $\mu\text{c/cc}$

3. Find ratio of answer in (2) and allowable milk concentration of 100 $\mu\mu\text{c/liter}$.

This ratio is the permissible air concentration

$$\text{Permissible Concentration} = \frac{100 \mu\mu\text{c/liter}}{1.2 \times 10^{15} \mu\mu\text{c/liter per } \mu\text{c/cc of air}}$$

Permissible Concentration = $8.3 \times 10^{-14} \mu\text{c } I^{131}/\text{cc air}$
--

III. STACK SAMPLING

A. Problem

A stack sampler, which had a flow rate of 3 cfm, was operated continuously for one week. The stack discharge rate was 6,000 cfm; the activity released from the stack was Fe^{59} . The net activity (background subtracted) found on the filter paper was 1,000 counts per minute. Assuming the collection efficiency is 85 percent and the counter efficiency is 12 percent, and neglecting the decay of Fe^{59} , calculate the total number of microcuries released to the atmosphere, via the stack, during the week. Calculate the average Fe^{59} concentration ($\mu\text{c}/\text{cc}$) in stack air during the week. (1 cu. ft. = 28,000 cc)

B. Solution

$$\begin{aligned} \text{Total Activity } (\mu\text{c}) &= \frac{1000 \frac{\text{c/m}}{\frac{\text{c/m}}{\text{d/m}}}}{0.12 \frac{\text{c/m}}{\text{d/m}}} \times \frac{1}{2.22 \times 10^5 \frac{\text{d/m}}{\mu\text{c}}} \times \frac{1}{0.85} \times \frac{6000 \text{ CFM}}{3 \text{ CFM}} \\ &= 8.84 \mu\text{c} \end{aligned}$$

$$\begin{aligned} \text{Avg. Conc. } (\mu\text{c}/\text{cc}) &= \frac{(\mu\text{c})}{\text{flow } (\text{ft}^3/\text{m}) \times \text{time } (\text{m}) \times 2.8 \times 10^4 (\text{cc}/\text{ft}^3)} \\ &= \frac{8.84}{6000 \times 7 \times 24 \times 60 \times 2.8 \times 10^4} \\ &= \frac{8.84}{1.69 \times 10^{12}} \\ &= \boxed{5.2 \times 10^{-12} \mu\text{c}/\text{cc}} \end{aligned}$$

IV. ENVIRONMENTAL EVALUATION

A. Problem

1. A reactor is delivering radioactive waste to a public stream.

The effluent contains a known concentration of each of several isotopes. How would you evaluate the practice in terms of

safety to downstream users of the water? Give the steps and additional data which would be required, or at least desirable for a proper assessment.

2. How would your assessment differ if the reactor were a government-operated reactor not subject to licensing requirements?

B. Solution

1. As a licensee, the reactor operator is required to control the concentrations of radionuclides in the liquid effluent to the MPC_w for 168 hours public exposure. Where a mixture of nuclides is present, the combined effect must be evaluated for all organs of concern.

$$\sum \frac{c_i}{MPC_i} \leq 1$$

where c_i is concentration of nuclide (i) and MPC_i is 168 hour public MPC_w for nuclide (i) for the organ being considered.

If the licensee wishes to discharge concentrations higher than permitted by the MPC's, he can appeal to the AEC for special permission. He must first evaluate the proposed increased discharge in a manner similar to that required for an AEC contractor. He must then convince the AEC that no one will be consuming water at concentrations over MPC_w or that they will be exposed to external radiation exceeding the allowable public rates.

2. As a contractor, the operator need not restrict the effluent concentrations to MPC_w at the point of release, but may use the point of water use as the place to evaluate the safety of the disposal practices.

He must, however, still use the formula -

$$\sum \frac{C_i}{MPC_i} \leq 1$$

at the point of water use by the general public. He must also consider all organs of the body.

In addition, he must evaluate other possible modes of exposure either by calculation or direct sampling and/or monitoring.

These modes include:

- (a) Accumulation of radioactive materials in municipal water plant
- (b) Reconcentration of nuclides in fish and ducks
- (c) Contamination of produce irrigated by the receiving stream
- (d) Contamination of irrigated pasture and subsequent contamination of meat or milk products
- (e) External exposure to people who use the stream for recreation.

This evaluation must also include the combined effects of all the above items on all possible body organs.

ENVIRONMENTAL MONITORING QUIZ

- A. Explain (define) the terms in the following expression:

$$D = \frac{q f_2 (3.7 \times 10^4)(60)(1440) \Sigma E(RBE)(N)(10^6)(1.6 \times 10^{-12})}{m \times 100}$$

(define numerical as well as alphabetical terms)

- B. Due to the inadvertent processing of short-cooled fuel elements, a large quantity of Iodine-131 was released in a few hours from a radiochemical separations plant stack. Within a few days, the average concentration of Iodine-131 in milk from dairies (over a 600 square mile area) was 7,000 $\mu\mu$ /l and the maximum was 22,000 $\mu\mu$ /l. Discuss in detail the radiological surveillance and public health controls that are warranted.

Federal Radiation Council's Guidance on I^{131} intake

Range I	0 to 10 $\mu\mu$ /day
Range II	10 to 100 $\mu\mu$ /day
Range III	100 to 1000 $\mu\mu$ /day

- C. Answer one of the following two.

1. Discuss the basic considerations that should guide a staff health physicist in recommending the scope of the pre-operational environmental survey that should be made for a site where a nuclear reactor and radiochemical separations plant are to be constructed.
2. For a large power reactor, give your recommendation on the environmental monitoring program with regard to area to be covered, types of measurements to be made and reasons for each type of measurement.

- D. According to the ICRP and NCRP, what fraction of the continuous occupational exposure limit should be permitted to

- (1) People in the vicinity of a controlled area.
- (2) Population at large.

Explain why these two limits are different if they are.