233
25-77

LA-5289-MS

INFORMAL REPORT

33440

LA 209

Geothermal Energy

los alamos
scientific laboratory

of the University of California

LOS ALAMOS, NEW MEXICO 87544

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED.

UNITED STATES
ATOMIC ENERGY COMMISSION
CONTRACT W-7405-ENG. 36

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

In the interest of prompt distribution, this LAMS report was not edited by the Technical Information staff.

Printed in the United States of America. Available from
National Technical Information Service
U. S. Department of Commerce
5285 Port Royal Road
Springfield, Virginia 22151

Price: Printed Copy ~~\$3.00~~; Microfiche \$0.95

4.00

LA-5289-MS

Informal Report

UC-34

ISSUED: May 1973

Geothermal Energy

by

Morton C. Smith

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

This report presents an introduction to geothermal energy and discusses its present and projected uses in terms of economics, current technology, and environmental impact. Both the advantages and disadvantages of geothermal energy and its conversion to electricity are presented briefly.

GEO THERMAL ENERGY

1.0 INTRODUCTION

The total volume of the earth is about 260 billion cubic miles, and all but a thin crust at its outermost surface is very hot. Exactly how hot is uncertain, but the evidence from lava flows -- and, less spectacularly, from hot springs and geysers and fumaroles -- is that it is certainly hot enough to supply most of mankind's needs for energy. In fact, when the volume of the earth's interior and the specific heat of rock are taken into account, it becomes evident that this geothermal heat is by far the largest reservoir of energy that is now available to man. Further, the energy which it contains is inherently clean energy. It already exists as heat, and it is therefore not necessary to burn a fuel or operate a reactor to produce that heat.

In a few fortunate places nature delivers geothermal energy to the earth's surface in the form of steam or of superheated water that flashes to steam, and this natural steam can be used directly to generate electricity. Elsewhere the water from springs or wells is at least hot enough to heat homes and greenhouses, and to supply energy for low-temperature chemical processes. In general however, and particularly considering the magnitude of the resource that it represents, the present worldwide usage of geothermal energy is in fact very small.

The ideas and most of the technology required to correct this now exist. It appears quite possible that within a few years geothermal energy can be made broadly available at a cost in money, effort, and environmental deterioration that men can afford. If so, this oldest form of energy will contribute significantly to solving two of the world's newest problems: a vanishing fuel supply, and an overwhelming burden of pollution.

2.0 APPLICATIONS

Where natural steam or superheated water that flashes to steam is produced, the steam is simply passed through a screen to remove entrained particles, fed to a turbine, and thus used directly to generate electricity. The "fuel cost" of such a power plant is represented by the capital charges against the production wells and steam-collection

system, and is low. The generating plant is also relatively inexpensive, since it requires no fuel-handling facilities, boiler-plant, or smokestack. Accordingly, in this convenient natural form, geothermal energy is a very economical source of electricity. It is unfortunate that occurrences of natural steam, or of water sufficiently superheated to produce it in useful amounts, so far appear to be relatively rare.

Much more common are natural reservoirs of hot water at temperatures below boiling, which are the sources of most of the world's many hot springs. These have been used for thousands of years for recreational and religious and medicinal purposes, and for domestic heating. They are still used, very economically, for heating homes, greenhouses, resort hotels, and occasionally factories, mines, and even whole cities. In general they are an inexpensive source of low-grade heat, and their use has the great advantages of conserving higher-grade energy sources for more demanding uses, and of minimizing pollution locally.

Natural hot water at intermediate temperatures -- significantly above boiling, but not quite hot enough to be used economically as a steam source for a conventional generating plant -- occurs in large amounts in several parts of the world, notably in the Imperial Valley of California. The technology required to utilize this large geothermal resource is now developing rapidly, and demonstration plants which will desalinate brines and generate electricity in turbines driven by the vapors of low-boiling organic liquids will soon be operating in California. To this point, however, natural hot water in the intermediate temperature range is in general used only locally, and again principally for space-heating.

No demonstrated system yet exists for extracting energy from the hot "dry" rock which composes so much of the earth's crust but which -- for lack either of permeability or of a ground-water supply -- does not spontaneously yield useful amounts of either steam or hot water. However this energy reservoir is so vast, so broadly distributed and in many accessible places so hot, that it is now at last being given the serious technical attention that it deserves.

3.0 HISTORICAL BACKGROUND

Local use of natural geothermal water for various heating purposes is older than history, but has expanded notably in recent years -- particularly in Iceland, Hungary, and the U.S.S.R.

The first large-scale commercial use of natural steam was at Larderello, Italy, where it has been used to generate electricity since 1904. Development of the Wairakei geothermal area in New Zealand, where natural superheated water is flashed to steam, began in about 1950. In the United States the only commercial production of geothermal power is at The Geysers in California, where generation of electricity from natural steam began in 1960 and has since expanded steadily. A major geothermal power plant based on superheated water is now being constructed at Cerro Prieto in northwest Mexico, and there are very small geothermal generating plants operating elsewhere in Mexico, New Zealand, and Italy, and in Japan, the U.S.S.R., and Iceland. At this time, however, the total installed generating capacity of the world deriving its energy from geothermal sources is less than 1000 MW electrical¹, and thus is less than the capacity of one large fuel-fired or nuclear power plant. All but a minute fraction of this capacity is based on the use either of natural "dry" steam or of "wet" steam flashed from naturally superheated water.

There is now active exploration for or development of natural steam or superheated water fields in many parts of the world², and there is no real doubt that new geothermal sources of this type will be found and developed over the years. When they are, they will be economical sources of energy, and, locally, they may be of great importance. However, there is no evident reason to suppose that they will ever be found in very large numbers or that, individually, they will be much larger than are the similar fields now being exploited. Accordingly, if only "existing technology" is considered, there is an honest basis for the commonly stated conclusion that geothermal sources can never satisfy a significantly large fraction of the country's or the world's total energy requirement. If, on the other hand, consideration is given to applications of present technology to new kinds of geothermal energy developments and to the probability that entirely new technologies may soon appear, then the forecast of geothermal energy's future contribution becomes much more optimistic.

4.0 SYSTEM CHARACTERISTICS

There are still mysteries about "wet" geothermal reservoirs related, for example, to the natural flow of water into them, convective circulation within them, and many details of their geology and heat-flow. However, their general nature is reasonably well understood, and is illustrated schematically in Fig. 1.

Apparently three lithologic features must exist together to create and maintain a wet geothermal field: (1) A large supply of usefully hot rock at depth, which of course is the major heat source; (2) An aquifer or permeable formation above it, through which ground-water reaches the hot rock, and within which the heated fluid -- steam, hot water, or a mixture of the two -- circulates convectively and transports heat to a higher level; (3) An impermeable cap above the aquifer, to prevent the large-scale loss of fluid at the surface which otherwise, over the millenia, would have cooled the system sufficiently to make it uninteresting as an energy source. This cap appears often to have formed spontaneously through plugging of an initially permeable formation by minerals dissolved at depth and reprecipitated in cooler rock near the surface.

When the fluid circulating in at least the upper part of the aquifer is steam, the natural system is now generally described as a "vapor-dominated" geothermal reservoir³. When temperatures are lower, pressures higher, or the concentration of dissolved minerals greater, so that the circulating fluid is water or brine, then it is a "liquid-dominated" reservoir³.

The surface evidence that a wet geothermal reservoir exists at depth is usually the natural occurrence of hot springs, geysers, or fumaroles. However, it is now believed that many such reservoirs may exist with no evidence at the surface that they are present. Prospecting for these hidden reservoirs will evidently be difficult.

It is apparent that thermal energy is present in the hot rock even when no permeable reservoir or circulating fluid exists above it to transport the heat to the earth's surface. Frequently -- e.g., in Hawaii and other regions of recent vulcanism -- extremely hot rock is quite close to the earth's surface, and its energy content is impressive. Thus, as is suggested by Fig. 2, cooling 40 cubic miles of rock by 360°F would release 0.07Q of energy, which was just the energy requirement of the United States for all purposes

Fig. 1. Schematic diagram of a "wet" geothermal reservoir.

Fig. 2. The energy extracted from 40 cubic miles of rock cooled 200°C (360°F).

in 1970. In this form the energy would of course not be suitable for many purposes, such as smelting iron ores and powering aircraft. It could, however, be used for many purposes, to conserve higher-grade energy sources for uses that geothermal energy itself cannot serve. And, while 40 cubic miles is a lot of rock, it is infinitesimal compared to the total volume of the earth's interior, or even to that relatively small fraction of the earth's interior that can now be reached by conventional drilling methods.

The technology for producing and using either wet or dry steam for generating electricity is already highly developed, and is still improving steadily. That for lower-temperature waters and for concentrated brines is now being developed actively, and the use of this large resource for such other purposes as desalination will soon be demonstrated. The investigation of methods for extracting useful energy from the much more abundant "dry" geothermal reservoirs has just begun.

4.1 GENERAL

Economically, the most attractive geothermal reservoirs are the vapor dominated ones, which produce "dry" steam -- i.e., superheated steam, carrying with it minor amounts of other gases, but little or no water. Aside from mechanical removal of any dirt and rock carried out of the well by the steam, no treatment of it is ordinarily required, and in general the steam is piped directly to a turbine and used to generate electricity. Larderello in Italy, The Geysers in California, and Matsukawa in Japan are the principal dry-steam fields now being exploited commercially. Two small dry-steam fields in the Monte Amiata region of Italy are marginally commercial⁴, and several areas in Africa and in Central and South America now being investigated by the United Nations may be of this type. As new dry-steam fields are discovered, industry and/or government will be anxious to develop and manage them.

Considerably more common than dry-steam fields are the liquid-dominated or superheated-water fields, from which "wet steam" is produced. In these the temperature at depth is above the normal boiling point of water, but the water or brine in the reservoir is kept from boiling by the pressure on it, which is greater than atmospheric. As the fluid is brought out of the reservoir its pressure is reduced, boiling occurs,

and a mixture of steam and hot water is produced from the well. Normally about 20% of the fluid is converted to saturated ("wet") steam, and only this steam is used to generate electricity. The other 80% of the fluid, hot water at the boiling point, is usually wasted. Wet-steam fields of this type are now being exploited at Wairakei and Broadlands in New Zealand and in smaller plants in Japan, Mexico, the U.S.S.R., and Iceland. Much of the hot brine in the Imperial Valley of California is in this class, and a major plant now being completed at Cerro Prieto in northwestern Mexico will soon demonstrate commercial-scale generation of electricity from such brines.

Still more common are natural reservoirs of hot water at temperatures below the boiling point. One small power plant on the Kamchatka peninsula is now generating electricity by using natural hot water at only 178°F to vaporize freon, and using the freon vapor to drive a turbine. A similar "two-fluid" system, using isobutane instead of freon, will soon be demonstrated in the Imperial Valley. Otherwise, natural hot water at temperatures below boiling has so far been used only for space-heating and low-grade process heat.

Most common of all are "dry" geothermal reservoirs, which yield no steam or hot water either because they are relatively impermeable to water or because the ground-water circulation does not reach them. In principle, dry hot rock at a temperature high enough to be useful as an energy source could be reached from any point on the earth's surface simply by drilling a deep enough hole. In practice, the difficulty and expense of drilling increase exponentially with hole depth. In most types of geology, holes are now drilled more or less routinely to depths of the order of 20,000 feet, but each increment of depth below this becomes more of an adventure. Practically, then, with existing drilling technology, the dry geothermal reservoirs of interest are those within about 20,000 feet of the earth's surface. These vary widely in temperature and accessibility, the extremes being hot lava pools essentially at the surface with temperatures above 2000°F, and regions of extensive, geologically recent glaciation, where even at 20,000 feet the rock temperature may be less than 300°F.

No demonstrated method exists for extracting energy economically from hot dry rock in the earth's crust. Several proposed systems for doing so are discussed below.

4.2 AVAILABILITY

Dry steam fields with reserves sufficient to justify commercial development are now known to exist in less than a dozen places in the world, generally in regions of recent vulcanism. Systematic prospecting may discover a few dozen more, but the geological and thermal situation that produces a vapor-dominated geothermal reservoir is evidently rare, and the individual vapor-dominated reservoirs in general do not appear to be large.

Liquid-dominated systems capable of producing wet steam in commercial amounts appear to be both larger and more common than vapor-dominated systems. They occur in many parts of the world, and represent a very large and relatively accessible energy resource.

Natural hot water at lower temperatures is of course still more common and more readily available, and dry hot rock is the most common and accessible geothermal resource of all.

4.3 ENERGY SOURCE

Estimates of the amount of energy potentially available from vapor-dominated and liquid-dominated geothermal reservoirs of types now being exploited commercially vary widely with the degree of optimism of the person extrapolating the boundaries and long-term productivities of existing fields, predicting discoveries of new ones, and anticipating technologies which may make them more broadly useful. One probably conservative estimate¹ is that -- with present technology -- the identified, recoverable resource of natural steam in the United States is sufficient to support only 1000 MWe of generating capacity for 50 years, but that discoveries of new steam fields will probably make it possible eventually to support another 3000 to 6000 MWe of generating capacity, again for 50 years. Other estimates can be found which would increase the probably magnitude of the nation's immediately useful reservoirs of natural steam by factors as large as 5 to 10. However, even the most optimistic of these estimates suggests that -- if only existing technology is used to exploit it -- the geothermal resource is indeed small relative to the total energy needs of the United States.

The degree to which the magnitude of this resource can be increased simply by improvements in technology is the subject of much speculation. To most specialists in the field, it would probably seem reasonable to assume that, during the next 5 to 10 years, there will be:

- (1) Significant improvements in techniques of prospecting for immediately usable geothermal reservoirs, so that more of them will be discovered than are now believed to exist;
- (2) Development of improved drilling equipment and of totally new drilling systems so that exploration, development, and production costs will decrease for reservoirs at normal depths, and much deeper reservoirs will become accessible and economical energy sources.
- (3) The chemical problems associated with relatively concentrated hot brines, such as those of the Imperial Valley, will be brought under control, vastly increasing the supply of superheated water that is directly useful for generating electricity;
- (4) Two-fluid generating systems, involving transfer of heat from natural hot water to a lower-boiling organic liquid, will have been demonstrated convincingly, making lower-temperature geothermal reservoirs valuable for generating electricity;
- (5) Non-electrical uses of the heat from natural hot water (and from power-plant coolants and condensates) will increase in such applications as domestic and industrial heating and air-conditioning, desalination of water, distillation of domestic and industrial wastes, recovery of minerals, and physical and chemical processing;
- (6) Increased understanding of the geology, hydrology, heat- and fluid-flow, chemical and mechanical behavior, and artificial stimulation of geothermal reservoirs of all types will significantly increase their productivity.

The magnitude of the useful geothermal resource will increase with the degree to which any of these technological advances is achieved, and a resulting total increase in the resource by a factor of 20 in the next 10 years would not be unexpected. Thus

Peck et al.¹ estimate that such advances may increase the geothermal resource of the United States sufficiently so that it can support a generating capacity of about 440,000 MWe for 50 years, in addition to its nonelectrical uses. Again, estimates 5 to 10 times this large can be found elsewhere in the literature, but the Peck estimate alone exceeds the total presently installed generating capacity of the U.S.

The further technological developments required to make possible the economical extraction of energy from dry hot rock would enormously increase the magnitude of the geothermal resource. The extent of the projected increase depends principally upon the assumptions made concerning the types and extents of geological structures in which suitable energy systems can be created, the minimum rock temperature that would be useful, the maximum depth to which the system might economically be extended, the costs associated with geochemical and other systems problems, and the anticipated life of the system. It seems probable that rock temperatures as low as 300°F will be useful, that depths to about 20,000 feet can be reached more or less routinely, that systems problems and costs will be no greater than for the utilization of hot brines, and that systems can be developed having lifetimes not less than 20 years. With such assumptions, the estimated generating capacity that might be supported by dry geothermal reservoirs in the United States becomes many millions of megawatts for at least a century. If even a fraction of one percent of this energy can in fact be extracted economically, it will satisfy a major part of the nation's total energy requirements. The incentive to develop the required technology is therefore very great.

4.4 OUTPUT FORM

The direct output of any geothermal energy system is heat, normally contained in steam or hot water. If its temperature level is high enough, this heat can be used to drive a turbine, a screw-expander, or some other type of heat-engine, producing mechanical energy that can be used to generate electricity or do other useful work. At similar or lower temperatures the heat can be used directly for space-heating, air-conditioning, distillation and chemical processes, and a multitude of other uses. Multiple-use systems, in which the higher-temperature heat is used to generate electricity and the rest is used directly as domestic or industrial heat, are particularly attractive.

4.5 EFFICIENCY RANGE

While the temperatures of natural geothermal fluids vary over wide limits, in general they are below 400°F. This is relatively low for driving a steam turbine, and normal generating efficiency is correspondingly low. Power-conversion efficiency may be in the vicinity of 20% for dry steam, but is likely to be 15% or less for a hot-water system. Efficiencies will be increased significantly if economical two-fluid generating systems are developed, to be used either alone or as a "bottoming cycle" in conjunction with a steam "topping cycle." Efficiencies will also be higher if water temperatures can be increased, which appears possible with man-made dry-rock systems.

In applications other than the generation of electricity, where part or all of the geothermal energy is used directly as heat, much higher efficiencies are possible than when the heat is used only for generating electricity.

4.6 SIZE LIMITATION

With existing technology, the natural unit size of a geothermal power plant is small -- of the order of 50 to 400 MW of electrical generating capacity. Principally this is because of the costs and inefficiencies associated with piping low-temperature steam over long distances. Typically the power plant is built to handle the steam production of about 10 to 30 wells in its immediate vicinity. Then, instead of extending the collection system and enlarging the existing plant, another small generating plant is built to use the steam from the next group of wells that is developed. However, the disadvantages associated with small plant size are less for geothermal power than for most other energy systems. Because of the low temperature and pressure of the steam used, turbines are large relative to generating capacity, and their most economical individual size probably corresponds to about 50 MW electrical or less. The associated plant equipment is small and simple, since no fuel or ash handling, combustion system, or smokestacks are required. Accordingly, the cost of constructing a new, small plant is not much greater than that of enlarging an old one, and -- above a plant capacity of perhaps 100 to 150 Mwe -- the advantage of scaling up

in plant size is not likely to balance the increased costs and heat losses of an extended piping system.

This picture may change somewhat as hot-water and pressurized dry-rock systems are developed. Energy output per well may be much larger when hot water instead of steam is produced because, for a given pressure drop and temperature, a much greater mass of liquid than of vapor is brought up the pipe, delivering a correspondingly greater amount of energy to the surface. Further, unlike steam, hot water at moderate pressure and temperature can be piped economically and efficiently over distances of many miles. Finally, because the organic vapors produced in a two-fluid system are much more dense than steam, the turbines required for a given generating capacity are much smaller. Therefore, as the technology of hot-water and dry-rock systems is developed, it may prove economical to use larger collection systems than are now used for natural steam. Combined with greater thermal output per well, this would result in fewer power plants and larger generating capacity per plant, although if two-fluid systems are used the physical size of the plant may not increase.

4.7 UNIT SIZE

The output of a single geothermal well varies widely with the nature, temperature, and quantity of fluid produced from it, and -- for geologic reasons that are not usually understood -- may differ greatly between adjacent wells in the same field. In general, a single steam well capable of supporting 20 Mw of generating capacity is unusual, and the average production per well corresponds to less than 10 Mwe. Because of the greater mass flow possible when hot water is produced instead of steam, the average energy output per well may be significantly higher for hot-water and dry-rock systems than for natural steam. This, however, obviously depends upon the temperature at which the water can be delivered to the surface plant.

4.8 POLLUTION PRODUCTS

Natural steam brings with it to the surface a proportion of noncondensable gas that varies usually between about 0.5 and about 5%. Usually this gas is principally carbon dioxide, which is inoffensive. However, it also usually contains some

proportion of hydrogen sulfide, in particular, and minor amounts of such other species as methane and ammonia. The gas is commonly discharged to the atmosphere either directly or upon release from the condensate used in wet cooling towers. Hydrogen sulfide has a very offensive odor and, if permitted to collect in low spots or confined areas, can be dangerous to human and animal life. Trace amounts of boron, arsenic, and other volatile compounds are commonly found in steam condensates which, if discharged into surface waters or permitted to escape as wind-blown droplets, can be damaging to plant life and may enter the food chain. If, as has been common, the condensate is discharged at an elevated temperature, then it also is a source of thermal pollution.

In the production of wet steam from liquid-dominated geothermal reservoirs, usually about 20% of the mass-flow from the well is steam, which carries with it normal amounts of the pollutants discussed above. The other approximately 80% is hot water which may contain higher concentrations of trace elements than does the steam, and typically has much higher contents of various dissolved minerals -- especially carbonates and silica. If discharged into surface waters, this geothermal water can be damaging to fish, animal, and plant life, and because of its larger volume it is a much more serious source of both chemical and thermal pollution than is the steam condensate.

In two-fluid systems, the primary fluid produced by the well will in general be passed through a heat exchanger and then reinjected into the underground reservoir through a second well. Since this circulation can be completely contained, such a system can in principle be completely nonpolluting. There will, however, be dissolved gases and minerals which will come out of solution as the pressure and temperature of the fluid are reduced, and these will present a disposal problem that may not always be solved by reinjection. Nevertheless, pollution problems should be much easier to control in hot-water and dry-rock systems than in natural steam systems.

Natural steam systems also have an acoustic-pollution problem which is difficult to control. Superheated water flashing to steam produces an intense noise which can be muffled only by causing the flashing to occur in an acoustically designed chamber. Because shutting in a well or changing the production rate from it suddenly or drastically

is very likely to damage the well, it is common to vent either wet or dry steam to the atmosphere continuously over quite long periods -- during testing of the well and its associated equipment, shut-downs elsewhere in the system, and the drilling of enough adjacent wells to supply a new power plant. This too produces an ear-splitting roar. Noise-suppressers capable of reducing the sound level to an acceptable value are available, but those which are effective are also expensive and are likely to wear out rapidly from abrasion by dirt, rocks, water drops, and precipitated minerals carried by the steam. Acoustic pollution is a continuing problem in natural steam fields.

Because geothermal energy is normally produced at relatively low temperature, its use in heat machines is relatively inefficient. Therefore, a geothermal power plant has a major waste-heat problem, which of course it shares with all other low-temperature power systems. The typically small size of a geothermal plant permits thermal pollution to be distributed, which mitigates the problem to some degree but of course does not solve it.

Geothermal energy, then, presents a variety of pollution problems, some of which it shares with other power systems. In general the problems of geothermal systems appear to be small compared with those of fuel-fired and nuclear plants, and to have straightforward engineering solutions. From an environmental standpoint, geothermal energy systems are probably the least objectionable of any power systems in existence or so far proposed. It is also worth noting that geothermal energy is usually developed in regions where there already is abundant surface evidence of the presence of an underground thermal reservoir -- in the form of fumaroles, geysers, mineral hot springs, and the odors, noises, mineral deposits, and stream contamination associated with them. Aside from its visual impact, controlled development of a well-engineered geothermal energy system is in fact very likely to reduce the level of local pollution to below its original, natural value.

4.9 PROBLEMS

The problems of locating and evaluating wet natural steam fields are similar to those of prospecting for oil and natural gas, and are being attacked with similar geological and geophysical methods supplemented by geochemical, hydrologic, and

heat-flow studies. However natural steam and hot-water reservoirs are even less well understood than are oil and gas reservoirs, and the correlation of geological structure and of any ground or aerial observation with the presence of underground steam or hot water remains very uncertain. Drilling is still the final and conclusive prospecting method and is still very expensive. The initial prospect drilling is commonly to depths of only a few hundred feet, to examine the local geothermal gradient, hydrology, and lithology. The sites for this drilling are usually selected on the basis of surface evidence of hydrothermal activity, supplemented by geochemical studies of natural waters and condensates, deep electrical resistivity measurements, microseismic observations, and other geophysical techniques. Exploration methods for geothermal energy are developing rapidly, but further development is needed.

Drilling is still essential in prospecting for geothermal energy, evaluating discoveries, and developing and producing the field. Except that high temperatures and hot fluids may be encountered, prospect drilling is now relatively routine, and would benefit principally from development of equipment and techniques that would reduce the costs of small-diameter exploration holes and permit them to be used without casings. Drilling of production wells has special problems associated with generally incompetent formations, high temperatures and pressures, and large flows of corrosive fluids. Production wells are now drilled more or less routinely in existing steam and hot-water fields, but the drilling is difficult, expensive, and dangerous, and more often than not the final hole depth is decided by an equipment failure rather than by a development plan. New drilling techniques and improved equipment could contribute greatly to geothermal exploration, development, and production.

Down-hole geologic, geophysical, and hydrologic investigations are an essential part of a sound exploration and development program. Much of the existing hole-logging equipment was developed for oil-field use, and is not designed for the temperatures encountered in geothermal wells. This severely limits the down-hole observations that can be made and the reservoir information that can be collected. Improved high-temperature logging equipment and techniques are now being developed, and it is important that this development continue.

Since wet geothermal reservoirs are not yet well understood, the analyses and models that are the bases of sound reservoir engineering are not yet fully developed. Well spacings and arrangements, drilling sequences, production rates, and reinjection procedures are still guided more by intuition and local experience than by real understanding, and are probably not optimum. Good reservoir models, and methods of producing them, are still lacking in the geothermal industry, and must be developed.

Geochemical problems and the pollutants involved in them have been considered above. An important trend in the industry is to dispose of steam condensates and excess water, together with as much as possible of their dissolved gases and minerals, by reinjecting them into the producing formation through unproductive wells or holes drilled specifically for that purpose. This returns most of the chemical pollutants to their source, avoids thermal pollution of surface waters, replenishes the fluid supply in the reservoir, and reduces the danger of surface subsidence caused by fluid withdrawal from the reservoir. However it is expensive, and involves the risk of plugging the formation in the vicinity of the injection hole with particles or precipitates from the injected water. Corrosion, scaling and plugging of drilling equipment, borehole casing, and surface plumbing are often serious problems with the hot, mineral-laden solutions produced from geothermal reservoirs. Until chemical methods of controlling these problems are developed, they will be handled principally by using expensive corrosion-resistant materials for surface-plant construction and by shutting down occasionally to rework wells and to clean out or replace surface plumbing.

Man-made, dry-rock geothermal-energy systems, as they are developed, will involve several of the problems of wet systems plus some peculiar ones of their own. Prospecting for them should be relatively simple, since only high temperature and a desirable lithology are required. Exploratory, development, and production drilling should also be generally less difficult than in wet geothermal reservoirs, since only high temperature -- which can be controlled by circulation of adequate coolant -- will normally be encountered, and not strong flows of hot, high-pressure, corrosive water or steam. The major problems will be the engineering ones associated with extraction of energy from hot dry rock in a useful form, at a usefully high rate, and

at a cost competitive with other energy systems. The principal basis for these problems is the fact that rocks in general are very poor conductors of heat.

Unless heat is carried into a drill hole by the mass flow of water or steam, it must be brought in by conduction through the rock, and this is very slow. The common idea of simply drilling a hole and lowering a heat-exchanger into it to extract energy from the earth is impractical except in the rare places where there is a strong horizontal flow of hot water through the formation containing the hole. In general, when heat enters the hole only by conduction through the rock, it does so at a rate so low that -- even if it could be brought out of the hole at perfect efficiency and zero cost -- its value would not be sufficient to amortize the cost of drilling the well. Drilling a larger hole would not materially change this situation, since drilling cost increases with hole diameter at about the same rate as does the surface area of the hole produced. To extract energy economically and at a usefully high rate from hot, dry rock evidently requires that a large heat-transfer area be created in the rock by some means less expensive than drilling a large number of holes, and that a large volume of fluid be circulated over this new surface to extract energy from it. The fluid with its contained heat must then be recovered and brought to the surface, where in general the thermal energy will be extracted in a heat-exchanger, and the cool fluid returned to the underground circulation system to extract more heat. There have been several suggestions for developing energy systems of this general type.

In arid regions or where porous or fractured formations are overlain by impermeable strata, there is undoubtedly hot rock which does not produce hot water or steam simply because no water reaches it. Here it may not be necessary to produce new surface, but only to introduce water, permit it to percolate through the formation, and then recover it as superheated water or steam. A water-flooding technique, such as that used in secondary recovery of petroleum, should permit very large amounts of heat to be recovered from such a formation. This would involve drilling a systematic array of holes, injecting cool water into some of them, and recovering hot water or steam from the others. Since hot water is less viscous than cold water, the cool water should sweep essentially all of the heated water ahead of it toward the recovery holes,

and energy extraction should be very efficient. Such a system would involve a high drilling cost and a long development period, but in suitable geology could produce very large amounts of energy for a very long time.

More generally, in hot dry rock, it will be necessary to produce new heat-transfer surface as well as to introduce, circulate, and recover a heat-transfer fluid. A method frequently suggested for accomplishing this is to detonate high explosive in the borehole in order to fragment the rock around it, and then to introduce cool water either through the borehole or through an insulated pipe down its center. The water would circulate convectively through the rubble, and would be recovered as either hot water or steam through a second hole or through the annulus around the insulated pipe. Unfortunately, to produce a usefully large volume of broken rock would require an intolerably and uneconomically large amount of explosive. Accordingly, the use of nuclear rather than conventional explosives has frequently been suggested. An excellent Plowshare study⁵ concludes that the use of nuclear explosives for this purpose would become economical only if a rather large number of very high-yield nuclear devices were detonated sequentially in a systematic, three-dimensional array. In addition to the difficulty of permanently containing the radioactive debris from these explosions, the ground-shock produced would be so intense that it could not be tolerated in most parts of the world. However, there may be solutions to these problems, and the Plowshare geothermal concept has not been abandoned.

An alternative method now being investigated is the use of hydraulic fracturing to produce the connected permeability and heat-transfer surface required to extract energy at a high rate from hot, dry rock. This is a standard technique of well-completion in oil and gas fields, used to increase the permeability of the producing formations around the well. It involves the use of a high-pressure pump at the surface to develop fluid pressure in the borehole sufficient to crack the rock and then to open and extend the crack. As is illustrated schematically in Fig. 3, the proposed method would involve drilling a hole to the depth required to penetrate usefully hot rock, and then producing a very large, pancake-shaped hydraulic fracture extending outward from this hole. The underground circulation system would be completed

Fig. 3. A dry-rock geothermal-energy system developed by hydraulic fracturing.

either by inserting an insulated pipe in the original hole or, as shown in the sketch, by drilling a second hole that intersects the crack system. Cool water injected through the deeper hole would be heated in its passage through the fracture and, because of its reduced density, would rise buoyantly through the second hole (or through the annulus around the insulated pipe) -- so that circulation could probably be maintained continuously without pumping. The possibility exists that cooling of the rock near the bottom of the injection hole will develop tensile stresses sufficient to cause new cracks to form, extending the circulation system outward and downward in three dimensions. If this occurs, new surface may be developed in the hot rock at a rate sufficient to compensate for cooling of the original crack surfaces, in which case the energy-extraction system will be self-perpetuating.

There are obvious problems associated with the creation and operation of such a system. Very large hydraulic fracturing has not been demonstrated in hot crystalline rock, and represents a significant extrapolation of the state of the art. Creating and maintaining interconnected circulation channels of sufficiently low impedance to permit buoyant circulation of a large volume of fluid may be difficult, and the possibility exists of short-circuiting of cool water from the injection hole directly to the recovery well. If the formation containing the fractures has an appreciable permeability, the rate of fluid loss from the system may be too high to permit operation of the pressurized-water loop described above. Presumably this could be avoided by permitting the water to flash to steam at any desired level in the system. This, however, introduces the danger of plugging the crack system with minerals dissolved at some lower level, and would also greatly reduce the rate at which heat was carried upward through the recovery well. Alternatively, a down-hole pump might be used in the recovery well, to maintain pressure in the upper part of the hole sufficient to prevent boiling while the rest of the system was kept at a reduced pressure. Unfortunately, the high-temperature down-hole pumps required by such a system have not yet been developed.

Other circulation systems and operating modes are evidently possible to inject cool fluid into dry geothermal reservoirs and recover it after it has been sufficiently heated by the rock. In general such systems will be completely contained, and therefore

essentially nonpolluting. To some degree, however, they will all be faced with the same chemical and corrosion problems as will the natural hot-water and steam systems discussed above.

Perhaps the greatest problems facing the large-scale development of geothermal energy in the United States are not the scientific and engineering ones so far considered, which are straightforward, but rather are traditional, organizational, financial, and legal problems, which are very complex. For example, where surface, mineral, and water rights exist separately, it is not clear who owns the geothermal energy or how this ownership can be established or transferred. A large fraction of the known geothermal resource of the United States is on public land, where prospecting in private is virtually impossible and for which a geothermal leasing system is still being developed. Local, state, and federal laws, tax structures, and licensing and regulatory systems are incomplete, overlapping, occasionally contradictory, and generally uncorrelated and incompletely interpreted. Legal requirements on public utilities require that a reliable, long-term fuel supply be certified before a new power plant is built. In the case of geothermal energy, this now requires that enough production wells to support the plant be drilled and demonstrated by venting to the atmosphere -- for months or years -- before construction of the power plant can begin. This long delay in securing a financial return makes the financing of a geothermal development very difficult. There are other "institutional" problems facing the geothermal industry of the United States, and in sum they are formidable.

5.0 COSTS

The major cost of exploring for, developing, and producing a geothermal energy supply is that of drilling and casing large, deep holes in hot formations, which is very expensive. However, to compensate for this, the surface plant required to use the thermal energy taken from the earth is in general relatively simple and inexpensive. An electrical generating plant powered by geothermal heat does not require fuel-handling space or equipment, boilers, smokestacks, or a smoke-abatement system, so that the plant cost per kilowatt of installed generating capacity is low. If the system

is to be used simply as a heat-source, for example for desalination, the surface plant is principally plumbing and heat-exchangers and the plant cost per thermal kilowatt again is low. In either case the subsequent "fuel" cost is the capital charge against the wells and collection system, which is generally low relative to the costs of fossil fuels or of producing and reprocessing fuel elements. Operating and maintenance costs again are typically low because of plant simplicity and relatively low operating temperatures and pressures. In general, then, for "conventional" geothermal energy systems, both plant and generating or heat costs are low.

In the United States, the only firm cost experience with geothermal power systems is at The Geysers, in California. Based principally on that experience, Bowen and Groh⁶ have produced the cost estimates listed in Table I for developing, building, and operating a 110 MWe natural-steam power plant. In Table II these costs are compared with those similarly estimated for other power systems. Both this comparison and the commercial success of The Geysers operation indicate that a geothermal power plant using natural steam is at least competitive with plants of other types. This is confirmed by the long and successful history of the natural-steam system at Larderello, Italy.

No comparable cost information is available for wet-steam systems. Undoubtedly both plant and generating costs are higher than for dry-steam systems because more production wells are required per unit of generating capacity, plant equipment is larger, chemical problems are more serious, and a very large volume of hot water -- produced with the steam -- must be separated, handled, and disposed of by reinjection or some other means. However the cost increment is generally estimated to be small, and wet-steam power plants in New Zealand and elsewhere have been very successful. American industry will be watching with particular interest the operating experience of a wet-steam plant just being completed at Cerro Prieto in northwestern Mexico, where the superheated geothermal water is a relatively concentrated brine very similar to that in some parts of the Imperial Valley of California.

Very little information is available concerning the U.S.S.R. plant on Kamchatka, and there is no U.S. operating or cost experience with contained hot-water geothermal

Steam winning:

Wells necessary to produce steam for	
110,000-kw. plant (16 wells at \$150,000)	\$2,400,000
Steam transmission lines at \$10/kw.	1,100,000
Total	3,500,000

Overhead charges:

Annual fixed charges at 14 %	\$490,000
Royalty payment to landowners	175,600
Total annual	665,600

Heat cost:

Steam winning cost in mills/kwh.	0.80
Exploration, mills/kwh.	0.33
Disposal charge, mills/kwh.	0.02
Total energy cost, mills/kwh.	1.15

Conversion cost :

Fixed charges, mills/kwh.	1.95
Operating cost, mills/kwh.	0.25
Total power cost, mills/kwh.	3.35

Table I. Costs associated with a 110 MWe natural-steam power plant.

An exploration cost of \$2 million is assumed to find the natural-steam field. (From Bowen and Groh, Ref. 6.)

	Electric Power Costs			
	<u>Geothermal</u>	<u>Nuclear</u>	<u>Hydropower</u>	<u>Coal</u>
Plant investment, \$/kw.	\$ 110.00	\$ 225.00	\$ 250.00	\$ 150.00
Fixed charges, 14%/year/kw.	15.40	31.50	35.00	21.00
Fixed charges, mills/kwh.	1.95	4.00	6.10	4.36
Operating costs, mills/kwh.	0.25	0.50	0.10	0.25
Energy costs, mills/kwh.	2.66	2.00	---	3.00
Total costs:				
Variable load factor, mills/kwh.	4.86	6.50	6.20	7.61
90% load factor, mills/kwh.	4.86	6.50	4.55	5.92

Table II. Plant and generating costs for several types of power plants in the United States in 1970. (From Bowen and Groh, Ref. 6.)

systems, use of relatively low-temperature geothermal water for generating electricity, or two-fluid power plants in this type of service. However a 19 MWe isobutane-turbine demonstration generating plant is now being built in the Imperial Valley. If it is successful, it will undoubtedly lead to a rapid development of low-temperature geothermal power systems and of contained two-fluid systems in general.

Cost projections for dry-rock systems are of course still more uncertain than those for natural hot-water systems, since none has ever been built or operated. However, reliable estimates are available for the costs of drilling, fracturing, and constructing the surface plant. Mineral and gas contents of the circulating fluid and the accompanying scaling, plugging, corrosion, and pollution problems should be less than with most superheated natural brines. Accordingly, if such a system can be made to operate at all, its plant and operating costs should be no greater than those of natural wet-steam and hot-water geothermal systems, which are expected to be at least competitive with fuel-fired and nuclear power plants.

6.0 STATE OF THE ART

Natural dry-steam and wet-steam geothermal power systems are demonstrated commercial successes, as are space-heating and chemical-processing applications of lower-temperature geothermal waters. Industrial-scale investigations of a relatively low-temperature, two-fluid power plant and of the use of geothermal heat for desalination of water are in progress in California and, if successful, should lead to a rapid expansion of geothermal-energy utilization in the United States. Experiments leading to the first demonstration of a large-scale, dry-rock, energy extraction system are also in progress, and may lead to a very large increase in the nation's geothermal resource.

7.0 REQUIRED DEVELOPMENTS

The problems facing geothermal-energy systems of various types have been outlined above. The most formidable and baffling of these are the ones related to financing, leasing, marketing, licensing, regulation, and legal requirements, which are not peculiar to the geothermal industry but are now particularly acute for it. These of

course have no scientific or engineering solutions, and perhaps no immediate solutions of any kind. However, concerted efforts to enact new, rational, coordinated legislation to control and encourage development of geothermal energy are obviously required.

Otherwise, the extension and expansion of geothermal-energy extraction and utilization require principally education, intelligent application of existing equipment and techniques, and incremental improvements in and extrapolations of present technology. A long list of problems facing the industry can be developed, but it is evident that in general these have straightforward engineering solutions and that they are almost trivial compared with the problems faced by power systems based on the use of fossil fuels, fissionable materials, and controlled thermonuclear reactions.

8.0 ENVIRONMENTAL IMPACT

No power system will have zero impact on its environment. However, of those so far in existence or proposed, geothermal systems appear to be the least objectionable in this respect.

With regard to land usage and effect on the landscape, a geothermal power plant will have the disadvantages of any power plant, mitigated by a typically small plant size and the absence of fuel-storage and handling yards, combustion equipment, and smokestacks. A steam- or water-collection system will be required and, like that for a municipal water system or an oil or gas field, it can be either unobtrusive or very unsightly according to local environmental regulations and the conscience of the operator.

Noise and odors from geothermal systems can be dealt with, although some technological development will be required before this can be done effectively in natural steam fields at a cost that the industry can afford. Here completely contained hot-water and dry-rock systems will have an advantage.

Concentrations of undesirable minerals in steam condensates and in unflashed water from wet-steam fields have traditionally been disposed of by draining the mineralized water into the nearest body of surface water. This has usually resulted in a high degree of both chemical and thermal pollution, and in most developed

countries it is no longer acceptable. The emerging solution is to reinject this water into the producing formation through unproductive wells or injection wells drilled especially for that purpose. By replacing part of the fluid removed from the reservoir, this should also reduce the danger of significant surface subsidence.

Subsidence is a common problem wherever a large amount of any material, including water or steam, is removed from beneath the earth's surface. Dry-rock systems, unless developed by water-flooding of a large area, are expected to affect only a deeply buried region of limited lateral extent, and are unlikely to produce a detectable subsidence of the ground surface above them. Wet systems, however, in general involve larger areas, shallower formations, porous rock, and withdrawal of large volumes of fluid, so that for them the probability of subsidence is high. Fortunately, oil-field experience indicates that reinjection of a volume of fluid sufficient to maintain the reservoir pressure can prevent significant subsidence. This may not always be possible in geothermal fields, but it will certainly be attempted.

Microearthquake activity seems commonly to be concentrated in potentially productive geothermal regions and may, in fact, be a useful guide to their locations. Earthquakes intense enough to cause even local damage at the surface seem if anything to be less common in geothermal reservoirs than in geologically similar regions elsewhere, perhaps because the small energy releases associated with microearthquakes prevent accumulation of the large amount of stored energy required to produce a major shock. The only real danger of triggering earthquakes appears to be that associated with reinjection of fluids into natural geothermal reservoirs and of fluid pressurization in the creation and operation of man-made systems. Studies by the U.S. Geological Survey and others of the Denver earthquake experience and of controlled earthquake experiments at Rangely, Colorado, suggest that significant earthquake activity can be induced only if very large volumes of fluid are injected under relatively high pressures into active fault systems. In general this combination of conditions can be avoided, and the possibility of initiating a damaging earthquake by developing or operating a geothermal-energy system appears to be very remote.

9.0 BENEFITS -- ADVANTAGES AND DISADVANTAGES

Geothermal energy, the natural heat of the earth's interior, is the largest energy reservoir that is directly accessible to man. Where nature delivers energy from this reservoir to the earth's surface in the form of steam or superheated water capable of producing steam, its direct conversion to electricity has proven to be economical and to produce minimal environmental damage. Active prospecting for new geothermal reservoirs of this type is in progress in many places, and new ones will undoubtedly be found -- although probably never in large numbers. Where they are found, industry will be anxious to develop and produce them, and the technology for doing so exists -- although incremental improvements in it are still badly needed.

Natural hot-water reservoirs at lower temperatures are both larger and more common than dry- or wet-steam systems, and the attention of the geothermal community is now being refocussed on them. Wherever a hot spring exists or hot water flows into a drilled hole, the possibility of extracting useful geothermal energy is demonstrated to exist. To this point, such low-temperature geothermal energy is being used almost exclusively for space-heating, and in the United States even this usage is small. Nevertheless this type of use is important and should be encouraged, particularly because it saves higher-grade heat sources for higher-temperature uses, and can significantly reduce the balance-of-payments and national-security problems associated with importation of fossil fuels from abroad.

Typically, hot-water systems are both lower in temperature and higher in dissolved mineral content than are natural steam systems, which presents problems with regard to their use for generating electricity. However, the engineering and geochemical developments required to solve these problems are easily defined and straightforward, and are now being pursued vigorously. Growth of this type of system into a major producer of electrical energy can be predicted with confidence, and the time scale for it can be short.

The individual units of wet geothermal energy systems are naturally small, which has both advantages and disadvantages. Because steam cannot economically be transported over long distances, a geothermal steam plant is necessarily located at

the steam field -- which is likely to be remote from major markets for heat and electricity. Hot water at moderate pressure can be piped efficiently over much longer distances, up to at least tens of miles, but to a lesser degree this same limitation on plant location also applies to hot-water systems.

The possibility of extracting energy from dry geothermal reservoirs is therefore attractive for more than one reason. Dry hot rock represents not only our largest but also our most broadly distributed energy supply. If economical methods can be developed to extract energy from it, it may become possible to create a geothermal-energy system almost anywhere that heat or electricity is needed -- which would have the incidental advantage of greatly reducing the need for new transmission lines, pipelines, and other transportation systems. Investigations of the possibilities, problems, and economics of such systems are just beginning, but the results of initial studies make it appear probable that dry-rock geothermal systems will eventually contribute significantly to the long-term solution of the world's energy and pollution problems.

10.0 REFERENCES

1. D. L. Peck, Coordinator, "Assessment of Geothermal Energy Resources," a report prepared by the Panel on Geothermal Energy Resources for the Committee on Energy Research and Development Goals, Federal Council of Science and Technology, June 26, 1972.
2. J. Banwell and T. Meidav, "Geothermal Energy for the Future," presented at the 138th Annual Meeting of the American Association for the Advancement of Science, Philadelphia, December, 1971.
3. L. J. Muffler and D. E. White, "Geothermal Energy," *The Science Teacher*, 39, 3, March 1972.
4. W. J. Hickel, "Geothermal Energy," Final Report of the Geothermal Resources Research Conference, Battelle Seattle Research Center, Seattle, Washington, September 18-20, 1972.
5. American Oil Shale Corporation, Battelle-Northwest, Westinghouse Electric Corporation and Lawrence Livermore Laboratory, "Feasibility Study of Plowshare Geothermal Power Plant," 1971.
6. R. G. Bowen and E. A. Groh, "Geothermal -- Earth's Primordial Energy," Technology Review, Oct./Nov. 1971, pp 42-48.