NUMEC-2389-4

Progress Report
DEVELOPMENT
OF
PLUTONIUM-BEARING FUEL MATERIALS
January 1 through March 31, 1964
AEC R&D Contract AT(30-1)-2389

NUMEC-2389-4

Nuclear Materials and Equipment Corporation
Apollo, Pennsylvania

~~For Official Use Only, Pending Patent Release~~

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

External Distribution

- U. S. Atomic Energy Commission, New York Operations Office
 - J. Hart
 - H. S. Potter, Patent Group
- U. S. Atomic Energy Commission, Washington
 - R. Grube
 - W. L. R. Rice
 - J. M. Simmons (2)
 - G. W. Wensch
- U. S. Atomic Energy Commission, National Laboratories
 - F. Foote, Argonne National Laboratory
 - Library Services Department, Argonne National Laboratory (4)
 - E. Childs, Dow Chemical
 - E. A. Eschbach, Hanford Atomic Products Operation
 - E. A. Evans, Hanford Atomic Products Operation
 - O. J. Wick, Hanford Atomic Products Operation
 - M. Musser, Hanford Atomic Products Operation
 - W. E. Roake, Hanford Atomic Products Operation
 - W. Cashin, Knolls Atomic Power Laboratory
 - H. Rizzo, Lawrence Radiation Laboratory
 - R. D. Baker, Los Alamos Scientific Laboratory
 - L. B. Jones, Mound Laboratory
 - E. S. Bomar, Oak Ridge National Laboratory
 - D. F. Cope, Oak Ridge National Laboratory
 - R. L. Shannon, Oak Ridge National Laboratory
 - E. J. Kreh, Westinghouse-Bettis Atomic Power Laboratory
- U. S. Atomic Energy Commission, Contractors
 - R. W. Dayton, Battelle Memorial Institute
 - R. F. Dickerson, Battelle Memorial Institute
 - H. D. Batha, Carborundum Company
 - K. Taylor, Carborundum Company
 - A. D. Schwope, Clevite Research Center
 - W. Alter, General Electric-Vallecitos
 - K. Cohen, General Electric-San Jose
 - L. D. Harris, National Carbon Company
 - A. Strasser, United Nuclear Corporation
 - R. W. Hartwell, Power Reactor Development Company
 - D. E. Hamby, Union Carbide Metals Company

Previous Quarterly Progress Reports issued in this series are:

<u>NUMBER</u>	<u>FOR THE PERIOD ENDING:</u>
NUMEC P-10	December 31, 1959
NUMEC P-20	March 31, 1960
NUMEC P-30	June 30, 1960
NUMEC P-40	September 30, 1960
NUMEC P-50	December 31, 1960
NUMEC P-60	March 31, 1961
NUMEC P-70	June 30, 1961
NUMEC P-80	September 30, 1961
NUMEC P-90	December 31, 1961
NUMEC P-100	March 31, 1962
NUMEC P-101	June 30, 1962
NUMEC P-102	September 30, 1962
NUMEC P-103	December 31, 1962
NUMEC P-104	March 31, 1963
NUMEC P-105	June 30, 1963
NUMEC P-106	September 30, 1963
NUMEC-2389-1	December 31, 1963

TABLE OF CONTENTS

PROJECT AND FACILITY ADMINISTRATION - TASK 1.00	1
PREPARATION AND CHARACTERIZATION OF FUEL MATERIALS - TASK 2.00	3
Preparation and Characterization of Mixed Plutonium-Uranium Oxides	3
Preparation and Characterization of Plutonium Oxide	3
Filtrate Waste Treatment	8
Dry Preblending of UO_2 -20 w/o PuO_2 Mixed Powders	8
Analytical Chemistry	14
FABRICATION AND EVALUATION OF FUEL SHAPES - TASK 3.00	25
Mixed Oxide Sintering Studies	25
Oxidation Kinetics of $(U,Pu)O_2$	31
The Electron Microscopy of Plutonium Bearing Materials	31
X-Ray Diffraction	35
Coefficient of Thermal Expansion	35
FUEL ELEMENT FABRICATION AND EVALUATION - TASK 4.00	51
Fabrication of High Burnup Test Specimens	51
RADIATION TESTING AND EVALUATION - TASK 5.00	53
Short-Term Irradiation Test	53
High Burnup Tests	57
PLUTONIUM SINGLE CRYSTAL GROWTH - TASK 20.00	59

PROJECT AND FACILITY ADMINISTRATION

Task 1.00

K. H. Puechl

I. D. Thomas

Major efforts during the past quarter were concentrated on mixed oxide sintering studies, preparation of high burnup test specimens, and physical property measurements.

A variety of plutonium dioxide and $\text{UO}_2\text{-PuO}_2$ feed materials were prepared for sintering studies, physical property measurements, and fabrication of irradiation test specimens. Additional processing details have been evaluated, and improved control of impurity pickup during hammermilling has been attained. Also, reslurry washing for removal of ionic residuals from freshly prepared plutonium oxalate was studied. While this technique is a process convenience, powder of inferior sinterability results. Additional powder blending studies have been performed for the preparation of homogeneous feed material as an alternate to coprecipitated feed. Homogeneity is then determined by means of autoradiography of pressed and sintered pellets. The results indicate that the fine-scale homogeneity obtained by hammer-milling of twin-shell blended powders is not improved by repeated cycles of blending and hammermilling.

Additional work has been performed on techniques for the determination of oxygen-to-metal ratio in $\text{UO}_2\text{-PuO}_2$ mixed oxides. Two independent techniques are being developed. The first of these is based on the change in weight when the sample is hydrogen reduced to definite stoichiometric composition. The effect of reduction temperature, time, and atmosphere on reference stoichiometry has been evaluated. The second method utilizes controlled potential coulometry for determination of the Pu-III/Pu-IV ratio. Thus, this method provides a direct measurement of the reduced phase Pu_2O_3 . The combined data from both these techniques will provide detailed information on sintering behavior.

Metallography on pressed and sintered pellets formed from high-fired PuO_2 spheres in a UO_2 matrix revealed an extensive void had formed around each PuO_2 particle which effectively blocks inter-diffusion. This had been previously observed around segregated PuO_2 powder clumps in pellets made from $\text{UO}_2\text{-PuO}_2$ mixed powder and has been explained on the basis of differential shrinkage on sintering. However, in this case, the PuO_2 particles were of high density prior to sintering; therefore, this explanation is not valid. A possible explanation is that UO_3 forms by reduction of the PuO_2 and vaporizes away from the $\text{PuO}_2\text{-UO}_2$ interface, thus forming the void.

Oxygen diffusion constants and oxidation rate parameters have been determined for $\text{UO}_2\text{-PuO}_2$ ceramic grade powders in sintered pellets ranging in composition from 5² to 35 w/o PuO_2 . In addition, the effect of oxidation parameters on subsequent oxygen pickup were evaluated as a function of plutonia content.

Thermal expansion data to 1250°C was determined for $\text{UO}_2\text{-5 w/o PuO}_2$, $\text{UO}_2\text{-12.5 w/o PuO}_2$, $\text{UO}_2\text{-20 w/o PuO}_2$, and $\text{UO}_2\text{-35 w/o PuO}_2$ by means of high temperature x-ray diffraction. A nonreactive internal thoria standard was used for calibration. The coefficient of thermal expansion first increases and then decreases with increasing PuO_2 content.

All pelletized fuel material for the high exposure radiation tests has been fabricated. Loading and assembly of the capsules is in progress. For the short-term irradiation testing program, the remaining three capsules of fourteen total have been irradiated to complete this program. One capsule was inadvertently lost at the reactor. All thirteen capsules have been visually examined with no noticeable effects caused by the irradiation. Three of the capsules have been cut open and the contained fuel elements show no increase in physical dimensions or change in appearance. Radiometallurgical examination is continuing.

PREPARATION AND CHARACTERIZATION OF FUEL MATERIALS

Task 2.00

C. S. Caldwell

O. Menis

Preparation and Characterization of Mixed Plutonium-Uranium Dioxide
(J. Goodman)

Preparation data for ammonia-precipitated UO_2 -50 w/o PuO_2 , UO_2 -80 w/o PuO_2 , and PuO_2 are given in Table 2.1. These materials are being utilized for x-ray diffraction, oxygen diffusion, sinterability, and thermal expansion studies in the plutonium-rich region.

Previous impurity contamination difficulties which occurred during hammer-milling of the plutonium-rich mixed oxides after reduction have been largely eliminated by pre-reduction milling under conditions which involve maximum attrition and minimum wear rate. Whereas previous contamination levels of 10,000-15,000 ppm were observed, the improved milling method yielded negligible impurity pickup.

Preparation data for two UO_2 preparations are given in Table 2.2. These constitute reference samples for physico-chemical evaluation studies in the UO_2 -rich region of the UO_2 - PuO_2 system.

Preparation and Characterization of Plutonium Oxide
(J. Goodman)

Four small-scale continuous plutonium (IV) oxalate precipitation runs were carried out to ascertain reproducibility of product material using more accurate control of feed flow rate. The preparation conditions for these runs are presented in Table 2.3. For the first run, a reslurry washing technique for removal of ionic residuals from the freshly precipitated plutonium (IV) oxalate was used as is done in the preparation of coprecipitated UO_2 - PuO_2 via plutonium hydroxide ADU precipitation. The resultant PuO_2 from this run did not have the usual characteristics; the reslurry washing appears to be responsible for increased particle size, bulk density, and tap density and thereby results in a product having inferior sinterability. For the three runs carried out under normal washing conditions, the reproducibility of powder characteristics was excellent. These data are presented in Table 2.4.

Table 2.1

Process Conditions
for Coprecipitated $\text{UO}_2\text{-PuO}_2$ Materials

Run Identification	297Pu53	297Pu55	297Pu57
Composition	$\text{UO}_2\text{-50 w/o PuO}_2$	$\text{UO}_2\text{-80 w/o PuO}_2$	PuO_2
Precipitation Conditions			
Method	Continuous	Continuous	Continuous
Temperature, °C	55	55	55
Feed Composition			
gm Pu/liter	50.0	80.0	100.0
gm U/liter	50.0	20.0	
H ⁺ molarity	1.0	1.0	1.0
Feed Flow Rate, liters/hour	1.2	1.2	1.2
Precipitation Composition, NH_3	Gas	Gas	Gas
Precipitant Flow Rate, cc/minute	380-24.7 psia	325-24.7 psia	700-24.7 psia
Precipitant Average Holdups, minutes	30	30	30
Total Number Throughputs	4.6	2.4	1.3
Drying Temperature, °C	100	100	100
Drying Time, minutes	Overnight	Overnight	40 hours
Gas Atmosphere	$\text{N}_2\text{-8% H}_2$	$\text{N}_2\text{-6% H}_2$	$\text{N}_2\text{-6% H}_2$
Gas Flow, SCFH	6	6	6
Conversion Temperature, °C	840	840	840
Time at Temperature, minutes	160	160	160
Furnace Charge, grams	74.2	49.8	118.0

Table 2.2
Process Conditions for UO₂ Preparation

Run Identification	297Pu54	297Pu56
Composition	Natural UO ₂	Natural UO ₂
Precipitation Conditions Method Temperature, °C	Continuous	Continuous
Feed Composition gm U/liter H ⁺ , molarity	100.0 1.0	100.0 0.3
Feed Flow Rate, liters/hour	1.2	1.2
Precipitation Composition, NH ₃	Gas	Gas
Precipitant Flow Rate, cc/minute	475 - 24.7 psia	140 24.7 psia
Precipitation Average Holdup, minutes	30	30
Total Number Throughputs	5.8	5.3
Drying Temperature, °C	180	180
Drying Time, minutes	Overnight	Overnight
Gas Atmosphere	N ₂ -6% H ₂	N ₂ -6% H ₂
Gas Flow, SCFH	8	6
Conversion Temperature, °C	840	840
Time at Temperature, minutes	160	80
Furnace Charge, grams	278	100

Table 2.3

Conditions for PuO₂ Preparation
by Continuous Oxalate Process

Run Identification	297Pu52-Lot I	297Pu52-Lot II	297Pu52-Lot III	297Pu52-LotIV
Composition	PuO ₂	PuO ₂	PuO ₂	PuO ₂
Precipitation Conditions				
Method	Continuous	Continuous	Continuous	Continuous
Temperature, °C	35	35	35	35
Feed Composition				
gm Pu/liter	69.6	55.4	55.4	26.4
Ht, molarity	3	3	3	3
Feed Flow Rate, ml/minute	8.2	9.0	9.0	9.0
Precipitant Composition				
Oxalic Acid, molarity	1.0	1.0	1.0	1.0
H ₂ O ₂ , molarity	0.8	0.8	0.8	0.8
Precipitant Flow Rate, ml/minute	6.8	5.8	5.8	5.8
Precipitant Average Holdup, minutes	30	30	30	30
Number of Throughputs	12	12	6	12
Drying Temperature, °C	100	180	180	180
Drying Time, hours	16	16	16	8
Calcination Temperature, °C	760	760	760	760
Calcination Time, minutes	30	17	17	17
Charge Weight, grams	329.8	159.5	89.3	188.3

Table 2.4

PuO₂ Powder Characterization Data

Identification	Surface Area M ² /gm	Bulk Density gm/cc	Tap Density gm/cc	Subsieve Size microns	Total Metallic Impurity ppm
297Pu52-Lot I*	6.6	2.36	2.80	3.62	420
297Pu52-Lot II**	9.1	1.75	2.46	2.05	500
297Pu52-Lot III**	9.9	1.85	2.42	2.98	490
297Pu52-Lot IV**	9.6	1.83	2.50	2.88	-

* 1000 milliliter reslurry wash - 3 cycles

** 1000 milliliter fixed bed wash - one cycle

Filtrate Waste Treatment
(F. Markosek - T. Potter)

A process for the removal of microgram quantities of plutonium from basic filtrate waste generated in the mixed oxide coprecipitation process was operated successfully on a two-gallon batch basis. The waste was composed of combined ammonical filtrate and precipitate water washes having a pH of 7.5 to 8.5. The alpha activity varied with the mixed oxide plutonium percentage in accordance with Figure 2.1. The waste solution was drawn into a cone-bottom plastic vessel equipped with a stirrer. Various flocculating agents were drawn into the solution with stirring. After the floccules settled, the entire slurry was batch-filtered through a double-layer filter paper. In most cases, Schleicher and Schuell #576 OR-602 was used with a paper pulp edge seal.

After decontamination to residual levels of 11 dpm/ml, the treated solution was directly discharged to the low level drain system. During preliminary development work, reflocculation was occasionally required; however, allowing for a dilution factor of 5-10 as would normally be available in practice, one flocculation stage was found to be sufficient.

With the common flocculating agents tested, such as lime, iron salts, and calcium phosphate, it was possible to lower the alpha activity of the waste filtrate to levels satisfactory for disposal to the environment within settling times consistent with normal sludge-blanket water treatment practice as shown in Table 2.5 and Figure 2.1. Typical flocculation conditions are summarized in Table 2.6.

Dry Preblending of UO₂-20 w/o PuO₂ Mixed Powders
(C. W. Beck)

Autoradiographs of UO₂-PuO₂ sintered pellets made from two component powders mixed by the twin-shell method normally show gross micro-inhomogeneity since "snowball" agglomerates form readily as a result of the blending action. To test the effectiveness of twin-shell blending combined with mechanical attrition, a series of tests were made using a UO₂-20 w/o PuO₂ powder mixture.

Figure 2.2 is an autoradiograph of a cross-sectioned pellet made from mixed powder blended for ten minutes. The starting ingredients contained a normal percentage of "snowball" agglomerates resulting from standard handling practice. This powder was then given three successive passes through a Bantam micropulverizer hammermill. Figure 2.3 is an autoradiograph of a sintered pellet of the final materials illustrating agglomerate breakdown. Following this milling, the powder was blended five minutes and again hammermilled. Figure 2.4 shows the results of this five minute blend prior to hammermilling. The material was then blended 10 minutes

Table 2.5

Waste Treatment Decontamination Data*

Process Identification Basic Waste	α -Activity dpm/ml Untreated	α -Activity dpm/ml Treated	Decontamination Factor
0.45% PuO ₂ -UO ₂	40,000	20	2,000
5.0% PuO ₂ -UO ₂	18,000	14	1,290
12.5% PuO ₂ -UO ₂	2,800	8	350
20% PuO ₂ -UO ₂	3,120	10	312
35% PuO ₂ -UO ₂	3,810	20	190
50% PuO ₂ -UO ₂	30,700	32	960
80% PuO ₂ -UO ₂ **	169,100	60	2,820
100% PuO ₂ **	166,100	75	2,210

* Activities listed represent average activity of solution treated by calcium phosphate and iron hydroxide flocculating agents.

** The 80% PuO₂-UO₂ and 100% PuO₂ data represent 50 ml laboratory trials.

Table 2.6

Typical Flocculation Conditions
for Basic Waste Decontamination

	<u>Run 14</u>	<u>Run 16</u>
<u>Volume Waste:</u>	7.5 l	7.5 l
<u>Flocculation Reagents:</u>	a) 100 ml conc. NH_4OH b) 150 ml 4% $\text{Ca}(\text{OH})_2$ c) 50 ml (250 g/l) $\text{NaPO}_4 \cdot 12 \text{H}_2\text{O}$	a) 16 ml 4% $\text{Ca}(\text{OH})_2$ b) 60 ml 4% FeCl_3
<u>Flocculated Solids:</u>	2.5 g $\text{Ca}_3(\text{PO}_4)_2$ /gal waste	2.5 $\text{Fe}(\text{OH})_3$ /gal waste
<u>Stirring Time:</u>	20 minutes	20 minutes
<u>Settling Time:</u>	60 minutes	60 minutes
<u>Filtration Media:</u>	2 sheets S&S #602	2 sheets S&S #602
<u>Initial Activity:</u>	40,000 dpm/ml	40,000 dpm/ml
<u>Final Activity:</u>	26 dpm/ml	72 dpm/ml

Figure 2.1
DECONTAMINATION OF BASIC WASTE FILTRATE FROM
MIXED U/Pu OXIDE COPRECIPITATION PROCESS

Figure 2.2
THERMOGRAVIMETRIC REDUCTION OF CRUSHED
UO₂-PuO₂ PELLETS FOR O/m REDUCTION

Figure 2.2
 $\frac{\text{UO}_2-20 \text{ w/o PuO}_2}{\text{Original 10 minute twin-shell blend}}$

Figure 2.3
 $\frac{\text{UO}_2-20 \text{ w/o PuO}_2}{\text{10 minute blend - hammermilled}}$

Figure 2.4
 $\frac{\text{UO}_2-20 \text{ w/o PuO}_2}{\text{5 minute blend}}$

Figure 2.5
 $\frac{\text{UO}_2-20 \text{ w/o PuO}_2}{\text{10 minute blend}}$

Figure 2.6
 $\frac{\text{UO}_2-20 \text{ w/o PuO}_2}{\text{10 minute blend - hammermilled}}$

Figure 2.7
 $\frac{\text{UO}_2-20 \text{ w/o PuO}_2}{\text{15 minute twin-shell blend}}$

followed by further hammermilling (Figures 2.5 and 2.6, respectively). Figure 2.7 shows the results of a subsequent 15 minute twin-shell blend.

It is apparent that agglomeration in UO_2 and PuO_2 powder pre-blending can be offset by combining attrition with the twin-shell approach; however, the resultant homogeneity is not improved significantly by multiple-pass treatment.

Analytical Chemistry

(O. Menis, B. Conroy, S. Eleftheriou, W. Judd, J. Limpert)

During this reporting period, controlled potential coulometric procedures for the determination of fuel material in irradiated mixed oxides were evaluated. Oxygen-to-metal ratio studies were continued both by the hydrogen reduction process and by a coulometric technique, and further modifications were made on the hollow cathode optical spectroscopy systems for the determination of isotopic composition of plutonium.

As reported in the last quarterly report⁽ⁱ⁾, the determination of oxygen-to-metal ratio based on a technique in which the mixed oxides are reduced with hydrogen to a definite stoichiometric composition was further evaluated. In this technique, two procedures have been reported: One in Great Britain in which the mixed oxides are reduced at 1100°C under 100% hydrogen and the other used at General Electric, San Jose in which the oxides are reduced at 750°C in a hydrogen-helium gas mixture. As previously indicated, test results with powder preparations showed no significant difference whether the reduction was carried out at 750°C or 1100°C with 6% hydrogen-nitrogen gas. Also, data were presented for reduction at 750°C for a series of specimens of high-fired (1600°C) pellets either in broken or crushed form. Current tests extend this work to a reduction temperature of 1100°C with more stringent control of impurities in the gas system. Both the argon gas and $\text{H}_2\text{-N}_2$ mixture were passed through magnesium perchlorate and zirconium sponge to remove traces of water and oxygen. Figure 2.2 presents a representative thermogravimetric curve of the reduction at 1100°C of ceramic pellets. Under our experimental conditions using a manual thermogravimetric technique, it is possible to follow the change in weight as a function of both time and temperature. The results indicate again that at either temperature a constant weight can be obtained. These data differ significantly from those obtained in Great Britain where with the use of 100% hydrogen reduction, a weight change was noted with time. This was attributed to the reduction of PuO_2 to Pu_2O_3 .

(i) NUMEC-2389-1, Progress Report, "Development of Plutonium-Bearing Fuel Materials", page 4.

Another procedure is presently under study to determine the validity of the estimation of oxygen-to-metal ratio by the hydrogen reduction method. The basic procedure used in this method includes a step in which the material is preoxidized before a final reduction is carried out. Since it is known that Pu_2O_3 can be oxidized to PuO_2 at 1100°C , this procedure would introduce an error in the method based on weight change in the reduction process so that a direct method of determining the presence of Pu-III would be desirable. Contrary to indications in the literature, Pu-III can be quantitatively oxidized by controlled potential coulometry to Pu-IV. Since the mixed oxides can be dissolved in phosphoric acid under nonoxidizing conditions, some preliminary data on the Pu-III content of mixed oxides have been determined. A typical coulogram of the oxidation of Pu-III to Pu-IV in phosphoric acid is shown in Figure 2.8. As soon as sufficient data are collected to evaluate the quantitative aspect of this determination, the results will be reported.

The controlled potential coulometric method was evaluated for the determination of plutonium concentration and its oxidation state in situ. Scott and Peekema⁽¹⁾ have shown that in HCl and HNO_3 media, in which iron behaves reversibly, a correction could be applied in the determination of plutonium. This study was extended to the phosphate media to determine the degree of interference and whether appropriate corrections could be made for iron, chromium, manganese, and vanadium. The other aspect of this study was to investigate the oxidation state of the stainless steel components in the dissolver solution. This is of interest in the application of an alternate method for the estimation of oxide-to-metal ratio in the fuel material. The presence of impurities in various oxidation states could, through interaction in the dissolver solution with uranium or plutonium, alter their oxidation state.

The experimental variables which were studied involved the selection of the proper media for the dissolver solution necessary to determine oxidation reduction ratios of these several elements. Data are presented in the form of plots of percent reduced or oxidized versus potential values. These plots or coulograms are shown in Figures 2.9 to 2.12. The data presenting the formal potentials are also summarized in Table 2.7.

As can be noted from Figure 2.8, the Pu-III-IV couple is affected by the complexing tendency of the given medium. In both sulphate and phosphate media, the formal potential is shifted to more negative values. The tendency

(i) F. A. Scott and R. M. Peekema, "The Determination of Plutonium in Irradiated Uranium Solutions by Controlled Potential Coulometry", HW-58491 (December 1958).

Table 2.7

Formal Potentials

<u>System</u>	<u>Media</u>	$\frac{[OX]}{[RED]} = 1$	
Pu IV $\rightleftharpoons$ Pu III	1M H_2SO_4	+0.50	Reversible
Pu IV $\rightleftharpoons$ Pu III	1M $HClO_4$	+0.77	Reversible
Pu III $\longrightarrow$ Pu IV	5M H_3PO_4 , 0.1M $HClO_4$	+0.34	Irreversible
Fe III $\rightleftharpoons$ Fe II	1M H_2SO_4	+0.50	Reversible
Fe III $\rightleftharpoons$ Fe II	1M $HClO_4$	+0.52	Reversible
Fe III $\rightleftharpoons$ Fe II	1M NaAc (pH 2.0)	+0.42	Reversible
Fe III $\longrightarrow$ Fe II	1M PO_4 (pH 2.0)	-0.6	Irreversible
Fe II $\longrightarrow$ Fe III	1M PO_4 (pH 2.0)	+0.27	Irreversible
$MnO_4^- \longrightarrow Mn^{++}$	1M H_2SO_4	+1.09	Irreversible
$MnO_4^- \longrightarrow Mn^{++}$	1M PO_4 (pH 2.0)	+0.91	Irreversible
$VO_3^- \longrightarrow VO^{++}$	1M H_2SO_4	+0.55	Irreversible
$VO_3^- \longrightarrow VO^{++}$	1M PO_4 (pH 2.0)	+0.52	Irreversible
$VO^{++} \longrightarrow VO_3^-$	1M PO_4 (pH 2.0)	+0.83	Irreversible
$VO_3^- \longrightarrow VO^{++}$	2M NaAc (pH 2.0)	+0.36	Irreversible

Figure 2.8

OXIDATION OF Au₃ IN PHOSPHATE MEDIA

COULOGRAMS OF IRON AND PLUTONIUM IN
VARIOUS MEDIA

Figure 2.9

COULOGRAMS OF IRON IN VARIOUS MEDIA

Figure 2.10

COULOGRAMS OF VANADIUM IN VARIOUS MEDIA

Figure 2.11

REDUCTION OF MnO_4^- IN VARIOUS MEDIA

Figure 2.12

is due to the greater complexing ability of the sulfate and phosphate ion versus the perchlorate ion. In the current study it was shown that Pu-III can be readily oxidized to Pu-IV in the phosphate media. It was previously (i) indicated in the literature that phosphate is not suitable for this titration. As is mentioned in the section on oxygen-to-metal ratio determination, the phosphate media can also be used to dissolve the refractory material; the quantitative aspects of this determination were evaluated. It was found that the oxidation of Pu-III-Pu-IV was quantitative. On the reduction cycle, however, the results were generally high. This was in part due to the high background of the phosphoric acid medium. The experimental conditions for this test were to dilute the concentrated phosphoric acid solution of Pu-III to 5 M with 0.1 M perchloric acid. The oxidation then was carried out at a potential of +0.45 v versus SCE. The reduction cycle was carried out at a potential of +0.1 v versus SCE. For duplicate determinations, the concentration of plutonium using the oxidation cycle was 7.03 mg Pu/ml while on the reduction cycle it was 7.10 mg Pu/ml. This method therefore would be suitable for determination of Pu-III in ceramic fuel materials.

The second phase of this work was to evaluate the degree of interference from other elements in the system. As shown in Figure 2.10 the coulograms of iron in several media is presented. It can be noted that in a phosphate media both iron and plutonium will be oxidized at +0.45 v versus SCE. A correction, however, can be made for the amount of iron present by carrying out a reduction at +0.1 v versus SCE. At that potential, plutonium will be reduced, but not iron. Iron can then be reduced at -0.2 v versus SCE and the iron content determined, and from this value a correction can be applied in the plutonium determination. The data with vanadium are presented in Figure 2.11. Again in a phosphate media, vanadium will not interfere with the Pu-III-Pu-IV determination at +0.45 v. V-IV does not start to oxidize until +0.6 v. The reduction of permanganate ion in two media is presented in Figure 2.12. Permanganate would be a serious interference, as it would chemically oxidize Pu-III to Pu-IV; however, when present as the Mn-II, it would not interfere. Dichromate reduction is shown in Figure 2.13. In general, it is expected that in a dissolution of a refractory mixed oxide from an irradiated fuel element the contaminants such as iron, manganese, chromium, and vanadium would be present in their lower oxidation state and would not interfere in the determination of Pu-III in a phosphate media.

It is planned next to determine Pu-III in various mixed oxide ceramic preparations and to verify whether there are any serious interferences from interaction of ceramic oxides with stainless steel cladding material.

(1) W. D. Shults, Talanta, 10, 833-849 (1963).

REDUCTION OF Cr₂O₇ ON PLATINUM ELECTRODE

Figure 2.13

The hollow cathode discharge tube for the determination of isotopic ratio of plutonium, which was described in the last quarterly, has been tested and modified.

In the initial tests, problems due to the construction material and vacuum integrity were encountered. Considerable deterioration was noted in the back of the tube which holds the cathode power rod. The back was constructed from teflon to provide insulation of the hot cathode. Since the temperature of the cathode reaches several hundred degrees, it caused, under vacuum conditions, a partial melting of the teflon. The molten teflon migrated and momentarily deposited on the cathode and was subsequently decomposed. Deposits on these cathodes on microscopic examination were identified as teflon. Also, carbon was found on the cathode and its insulator sleeve. For this reason the teflon was replaced by natural lava as the backing construction.

During the initial tests, excessive arcing was also encountered. This situation was remedied by carefully rounding off all sharp edges in the tube and gradually adjusting the current and voltage to the operating levels of 200 ma and 60 v. By avoiding sudden application of high current, the tube was operated for several hours without voltage breakdown.

In the initial blank trials, the spectra obtained exhibited intense band systems. These were identified as N_2 and weak N_2^+ bands⁽ⁱ⁾. This could be attributed to either impurities in the argon excitation gas or to leakage in the vacuum system. To assure higher purity of the gas system, the argon gas was further purified. This was accomplished by passing the gas through a purifying train of ascarite to remove CO_2 , anhydrone, and P_2O_5 to remove moisture, and uranium metal at 900 C to remove O_2 and N_2 .

(i) R. W. B. Pearson and A. G. Gaydon, "Identification of Molecular Spectra", John Wiley and Sons, Inc. (1963).

FABRICATION AND EVALUATION OF FUEL SHAPES

Task 3.00

E. K. Halteman

I. D. Thomas

Mixed Oxide Sintering Studies

(M. D. Houston)

The mixed oxide sintering studies for this quarter have been directed toward two areas: (1) The evaluation of various coprecipitated and mechanical blended compositions to correlate sintering behavior with the chemical processing technique and (2) The assessment of solid solution formation between UO_2 and PuO_2 with starting materials as the oxides or some unconverted compound such as ammonium diuranate, plutonium hydroxide, plutonium peroxide, or plutonium oxalate.

The sintering results for various UO_2 - PuO_2 preparations are shown in Tables 3.1 and 3.2. The series of prepared powders from Pu48 through Pu55 were converted at a fairly high temperature for a longer time period to give a much lower oxygen-to-metal ratio, approximately 2.05. As can be seen in the data, this low oxygen-to-metal ratio did not deter the sinterability of this material. In the range 5 to 35 percent PuO_2 , high final densities were observed in agreement with other coprecipitated material of similar plutonium concentration. The lower electrical resistivities for these pellets could result from the initial lower oxygen-to-metal ratio figure, but further investigation is necessary to verify this.

As observed, the coprecipitated materials of UO_2 -50 w/o PuO_2 and UO_2 -80 w/o PuO_2 did not sinter to a high density. This has been previously reported for similar compositions, Pu43 and Pu47 (50%) and Pu28 (80%). Various powder conversion parameters as shown in Table 3.2 were utilized in an attempt to produce a sinterable product. Although these methods differed greatly in atmosphere and temperature, the final properties varied only slightly and did not indicate optimum process conditions.

A complete study of the UO_2 - PuO_2 system at 10 percent increments was reported previously⁽¹⁾. The compositions were prepared from paste blending

(i) NUMEC-2389-1 - Progress Report, "Development of Plutonium-Bearing Fuel Materials", pages 13-17.

Table 3.1

Sintering Characteristics
of Coprecipitated UO_2 - PuO_2 Preparations
 Sintered at 1600°C for 1 Hour in N_2 -6% H_2
 Compaction Pressure - 10 tsi

Preparation	Composition PuO_2 Content %	Green Density gm/cc	Weight Loss on Firing %	Linear Shrinkage %	Fired Density gm/cc	% Theoretical Density	Electrical Resistivity ohm-cm
Pu48SS80+80-840	5	5.47	0.6	20.2	10.59	96.4	7.5×10^4
Pu48SS160-840	5	5.44	1.0	20.2	10.69	97.4	7.6×10^4
Pu49SS160-840	12.5	5.38	1.1	20.8	10.74	97.0	7.1×10^3
Pu50SS160-840	20	5.54	1.1	19.8	10.72	96.9	3.9×10^3
Pu51SS160-840	35	5.85	0.8	18.4	10.34	92.9	2.0×10^3
Pu52 - Lot II	100	7.01	1.8	13.4	10.68	93.2	1.0×10^7
Pu53SS160-840	50	7.00	1.3	8.6	9.30	83.0	2.0×10^4
Pu55SS160-840	80	6.00	2.3	9.0	8.09	71.2	3.2×10^4

Table 3.2

Sintering Characteristics of Coprecipitated UO_2 -50% PuO_2
 (Sintered at 1600°C for 1 Hour in N_2 -6% H_2)

Conversion Parameters			Compaction Pressure psi	Green Density gm/cc	Weight Loss on Firing %	Fired Density gm/cc	% Theoretical Density	Electrical Resistivity ohm-cm
Atmosphere	Time min	Temp $^\circ\text{C}$						
N_2 -6% H_2	80	400	10	4.72	4.1	8.89	79.3	3.8×10^4
N_2 -6% H_2	17	760	10	6.92	1.1	9.78	87.2	-
N_2 -6% H_2	160	840	10	7.00	1.3	9.30	83.0	2.0×10^4
N_2 -6% H_2	160	840	20	7.55	1.3	9.58	85.5	2.0×10^4
Air	180	400	10	5.00	4.5	8.94	79.7	-
Air	30	600	10	5.37	3.4	9.18	81.9	2.0×10^4
Air	17	760	10	6.08	2.7	8.83	78.8	-
Argon	30	600	10	5.92	2.4	9.31	83.0	1.3×10^4

of $\text{UO}_{2.2}$ and PuO_2 with the pellets sintered from 1 to 64 hours. A lack of complete solid solution formation in this system in the range UO_2 -10 w/o PuO_2 to UO_2 -90 w/o PuO_2 was shown both by x-ray diffraction and the instability of pellets in oxygen at 800°C . This latter characteristic can be utilized as a simple evaluation for compositions from UO_2 -30 w/o PuO_2 to UO_2 -90 w/o PuO_2 . Upon oxidation, if extensive solid solution is formed, the material proceeds from $(\text{U,Pu})\text{O}_2$ to $(\text{U,Pu})\text{O}_{2+x}$ without any crystallographic transformation. If solid solution does not exist, oxidation proceeds as usual to give an end product of U_3O_8 and PuO_2 . An investigation was undertaken to evaluate the solid solution possibilities between various uranium and plutonium compounds with a composition of UO_2 -40 w/o PuO_2 . The compound combinations and heat treatments are shown in Table 3.3. Final sintered densities were fairly low, but high density was not a specific goal at this time. All of the listed pellets when oxidized at 800°C completely disintegrated into powder, indicating that little solid solution had occurred. The electrical resistivities ranged from 10^2 to 10^6 ohm-cm, and little correlation can be made at this time between this property and solid solution.

The apparent reason for the absence of solid solution can be seen in Figure 3.1. In this photomicrograph, an extensive void can be observed around previously air sintered PuO_2 spheres (90-93% theoretical density) when compacted in a UO_2 matrix and reduction sintered. A similar phenomena observed in pellets made from mixed powders has been previously explained as differential shrinkage on sintering, but this seems unlikely in this instance. Instead, if one examines the high temperature behavior of the two oxides, a very logical phenomena can be deduced. At the sintering temperature, two concurrent reactions are proceeding:

With the UO_3 vaporizing away from the PuO_2 - UO_2 interface, the void which is formed becomes an insurmountable barrier to the diffusion process. One mixture, ADU and $\text{Pu}(\text{C}_2\text{O}_4)_2$, was also sintered at 1200°C and 1400°C in N_2 -6 w/o H_2 for times of 1 to 88 hours and 1200°C in 10^{-4} mm Hg vacuum. In all cases the pellets continued to disintegrate upon oxidation, indicating limited solid solution formation.

Table 3.3

Solid Solution Studies with UO_2 -40% PuO_2
 Sintered at 1600°C for 1 Hour in N_2 -6% H_2
 Converted at 750°C for 1 Hour in N_2 -6% H_2

Uranium Compound	Plutonium Compound	Compaction Pressure tsi	Green Density gm/cc	Sintering Time hours	Weight Loss on Firing %	Fired Density gm/cc	% Theoretical Density	Electrical Resistivity ohm/cm
$\text{UO}_{2.2}$	PuO_2	10	5.28	4	1.7	10.39	93.1	3.9×10^5
$\text{UO}_{2.2}$	PuO_2	10	5.28	16	1.7	10.28	92.1	6.5×10^5
ADU	Oxalate	10	4.72	4	2.1	8.60	77.1	2.0×10^3
ADU	Oxalate	10	4.83	16	2.1	9.39	84.1	7.5×10^2
ADU	Peroxide	35	6.85	4	1.2	9.80	87.8	4.8×10^3
ADU	Peroxide	35	6.86	16	0.9	10.11	90.6	1.2×10^6
ADU	Hydroxide	35	6.45	4	1.3	9.82	88.0	1.1×10^4
ADU	Hydroxide	35	6.45	16	1.5	9.92	88.9	3.9×10^5
$\text{UO}_{2.2}$	Peroxide	35	6.80	4	1.1	9.02	80.8	1.1×10^6
$\text{UO}_{2.2}$	Peroxide	35	6.77	16	1.4	8.74	78.3	5.7×10^4
$\text{UO}_{2.2}$	Hydroxide	35	6.95	4	1.5	10.06	90.1	4.0×10^5
$\text{UO}_{2.2}$	Hydroxide	35	6.95	16	1.4	9.95	89.2	8.5×10^4

NUMEC-2389-4

Figure 3.1

Fired PuO₂ Spheres in UO₂
(Sintered at 1600°C in N₂-6% H₂)

Neg. 944

50X

Oxidation Kinetics of (U,Pu)O₂
(R. W. Gerrish)

Studies of the oxidation kinetics of coprecipitated (U,Pu)O₂ powder are continuing using isothermal thermogravimetric methods. This quarter the emphasis has been on ceramic grade powders in the 5 to 35 w/o PuO₂ range with some additional work on the oxidation of sintered pellets. The results of the oxidation of the lower composition (<20 w/o) plutonium materials tend to go to a (U,Pu)₃O₇ and then a secondary product of (U,Pu)₃O₈ - x at higher temperatures.

The surface area for the resultant powders of the oxidized sintered pellets with a composition <20 w/o PuO₂, all of which completely fragmented on oxidation, was determined by krypton absorption using the B.E.T. analysis. This resultant surface area was used in the diffusion calculations and the rate equations. The resultant diffusion equations computed using this actual surface area to give an absolute value for the rate of diffusion, are shown in Table 3.4. The oxidation rate of the growth of the second phase is shown in Table 3.5.

Additional studies of the effect of the oxidation parameters as to the subsequent oxygen pickup were performed using UO₂ powder and low percentage plutonium coprecipitated powder; the results are shown in Table 3.6. Excessive oxygen pickup independent of the oxidation process was not observed with the UO₂ powder in the 500°C range. With the 5 w/o PuO₂ coprecipitated powder, a consistently higher oxygen pickup was noted where the samples were placed in the furnace, brought to temperature, and then removed from the furnace, effectively being quenched in air and allowed to reach ambient temperature before weighing. The dependence of the oxygen pickup on the oxidation process was not as prominent for the low plutonium concentration coprecipitated powder as for the oxidation of 20 w/o PuO₂ pellets⁽ⁱ⁾. However, the general influence of the oxidation process on oxygen pickup is similar and would greatly influence the results of the oxygen-to-metal data depending on an oxidation technique.

The Electron Microscopy of Plutonium Bearing Materials
(J. Roth)

A comparison of double replication versus single replication techniques is shown in Figure 3.2 as a flow sheet diagram. As can be seen, the single replication technique is less involved and takes much less time. The

(i) NUMEC P-106, Progress Report, "Development of Plutonium-Bearing Fuel Materials", page 27.

Table 3.4

Diffusion Equation

Composition	Form	Oxygen Diffusion
5	Sintered Pellet	$D = 7.42 \times 10^{-8} \exp(-9,300/RT)$
12.5 NM	Sintered Pellet	$D = 1.92 \times 10^{-6} \exp(-29,200/RT)$
12.5 HM	Sintered Pellet	$D = 2.25 \times 10^{-4} \exp(-32,900/RT)$
20	Sintered Pellet	$D = 7.62 \times 10^{-8} \exp(-28,500/RT)$
35	Sintered Pellet	$D = 2.46 \times 10^{-5} \exp(-9,500/RT)$
0.5	Powder	$D = 3.56 \times 10^{-6} \exp(20,561/RT)$
5	Powder	$D = 2.42 \times 10^{-5} \exp(23,200/RT)$

Table 3.5

Rate Equation

Composition w/o PuO ₂	Form	Rate Equation
5	Sintered Pellet	$R_2 = 4.25 \times 10^{-1} \exp(-30,100/RT)$
12.5 HM	Sintered Pellet	$R_2 = 1.09 \times 10^{-2} \exp(-28,000/RT)$
20		
35	Sintered Pellet	$R_2 = 7.50 \times 10^{-4} \exp(-9,300/RT)$
0.5	Powder	$R_2 = 1.16 \times 10^{-9} \exp(-39,200/RT)$
5	Powder	$R_2 = 2.01 \times 10^{-6} \exp(-11,100/RT)$
12.5	Powder	$R_2 = 7.60 \times 10^{-3} \exp(-19,100/RT)$
5	Powder	$R_2 = 7.70 \times 10^{-7} \exp(-9,500/RT)$

 $R_2 = \text{moles O}_2/\text{cm}^2\text{-min}$

Table 3.6

Effect of Oxidation Parameters
on Measured Weight Changes for Powders
(Oxidized in Air One Hour)

Material	Oxidation Procedure	Oxidation Temperature °C	Weight Gain on Oxidation %
UO ₂	In cool - Out hot	525	3.73
	In hot - Out hot		3.83
	In cool - Out cool		3.82
U _{.95} Pu _{.05} O ₂ + X	In cool - Out hot	550	1.47
	In hot - Out hot		
	In cool - Out cool		
	In hot - Out cool		
(U _{.95} Pu _{.05})O ₂ + X	In cool - Out hot	750	1.38
	In hot - Out hot		0.91
	In hot - Out cold		0.98

Figure 3.2
COMPARISON OF MULTIPLE-STEP vs
SINGLE-STEP REPLICATION TECHNIQUES

final photographs (Figures 3.3 and 3.4) show much greater structural detail for the single replication technique than for the double replication technique. Figure 3.3 shows the structure of ADU as replicated by the single replication technique using platinum as a shadowing material and carbon as the backing. Figure 3.4 shows the same, but subdued, structure as replicated by the double replication technique using a polystyrene disc as the first replica which is then platinum shadowed and backed with carbon. The step involving the acid dissolution of the replicated materials, in this case ADU, causes artifacts in the surface of the plastic. In addition, the step involving the dissolution of the plastics normally breaks up the shadowed replica to the extent that very little, if any, useable replica is remaining. This single replication technique has been used to prepare replicas thus far of materials ranging from 0 to 100 w/o PuO_2 . An example of these samples can be seen in Figure 3.5 which is a photograph of a 5 w/o powder sample at 10,600 magnification. The single replication technique has also been used successfully for the replication of ceramic compacts. Figure 3.6 shows a 5% PuO_2 -95 w/o UO_2 compact at 2400 magnification.

X-ray Diffraction (J. Roth)

Installation of the capillary loading box for x-ray diffraction work was completed during this quarter, and the box was committed to plutonium. The box (Figure 3.7) is constructed in such a way that the radioactive material contaminates only the top half. The capillaries which are made of quartz are inserted from the clean bottom chamber into a sphincter between the two chambers and then filled from the top. It is then flame-sealed with an oxyacetylene torch from the bottom. Techniques have been devised which allow the sealed capillary to drop into water which will contain the radioactive material if breakage occurs. An x-ray powder camera is taken into the bottom of the box through the air locks provided. The capillary is placed in the camera, the entire assembly is removed from the box, taken into the dark room, loaded with film, and then exposed to x-radiation. This procedure is followed in reverse to remove the capillary from the camera. The capillary is then placed in a vial and stored for future reference if necessary. The atmosphere of the box can be changed from air to pure nitrogen to allow examination of samples which are chemically attacked in an oxidizing atmosphere.

Coefficient of Thermal Expansion (J. Roth)

Techniques were devised for the measurement of the coefficient of thermal expansion of PuO_2 - UO_2 solid solutions using an M.R.C. high temperature diffractometer. A tungsten stage was fabricated and installed when it was found that the solid solutions being analyzed reacted with the available

Figure 3.3

ADU Direct Replica

Neg. 25-35

15,000X

Figure 3.4

ADU Double Replica

Neg. 73-11

15,000X

Figure 3.5

Direct Replica
5 w/o Pu-UO₂ Powder

Neg. 53-2

10,600X

Figure 3.6

Direct Replica
5 w/o Pu-UO₂ Compact

Neg. 52-1

2400X

Figure 3.7

Capillary Loading Box

platinum or tantalum stages. Because of the lack of a thermocouple on the fabricated tungsten stage, several materials were checked for use as an internal standard. Thoria was selected as the most suitable internal standard, since it was inert with respect to the materials being analyzed over the required temperature range. A standard curve for the lattice parameter of thoria as a function of temperature was calculated on the basis of results obtained by various investigators.⁽ⁱ⁾ The coefficient of thermal expansion for this material was calculated to be $9.73 \times 10^{-6}/^{\circ}\text{C}$ between 0 and 1250°C . The experimental points for the coefficient of thermal expansion of thoria⁽ⁱ⁾ were redetermined on the M.R.C. high temperature-high vacuum diffractometer (Table 3.7 and Figure 3.8).

The polynomial expansion for the lattice parameter of ThO_2 as a function of the temperature in $^{\circ}\text{C}$ was determined to be:

$$a_0 = 4.595 \times 10^{-9}t^2 + 5.0134 \times 10^{-5}t + 5.5958$$

The coefficient of thermal expansion for ThO_2 as computed from the experimental points between 23 and 1000°C is $9.99 \times 10^{-6}/^{\circ}\text{C}$ between 0 and 1250°C .

The diffractometer traces obtained from the pure urania and plutonia samples were remeasured and the values for the lattice parameters recomputed. The new results agreed to within .0001A of the previously reported results⁽ⁱ⁾. The coefficients of thermal expansion were recalculated based on a 1250°C span instead of the 1500°C span reported in NUMEC P-107:

$$\text{For urania} = 11.16 \times 10^{-6}/^{\circ}\text{C} \text{ between } 0 \text{ and } 1250^{\circ}\text{C}$$

$$\text{For plutonia} = 8.13 \times 10^{-6}/^{\circ}\text{C} \text{ between } 0 \text{ and } 1250^{\circ}\text{C}$$

In addition to the above work, several new compositions of urania-plutonia solid solutions were analyzed. The equation for the 5% PuO_2 -95% UO_2 solid solution (Table 3.8, Figure 3.9) took the form of:

$$a_0 = 10.7464 \times 10^{-9}t^2 + 5.2001 \times 10^{-5}t + 5.4637$$

The coefficient of thermal expansion for this mixture as calculated from the above equation for experimental points between 26 and 1258°C is $11.98 \times 10^{-6}/^{\circ}\text{C}$ between 0 and 1250°C . The 12.5% PuO_2 -87.5% UO_2 solid solution (Table 3.9, Figure 3.10) gave the equation:

$$a_0 = 7.3535 \times 10^{-9}t^2 + 4.9199 \times 10^{-5}t + 5.4559$$

(i) NUMEC-2389-1, Progress Report, "Development of Plutonium-Bearing Fuel Materials", page 18.

Table 3.7

Variation of Lattice Parameter a_0 of Thoria with Temperature
Experimental

<u>a_0 for Thoria</u> <u>A($\pm$ 0.001)</u>	<u>Temperature</u> <u>$^{\circ}\text{C}$</u>
5.5965	23
5.5965	25.2
5.5989	50
5.6001	100
5.6022	150
5.6065	197
5.6112	256
5.6095	259
5.6124	298
5.6131	343
5.6171	404
5.6193	450
5.6209	493
5.6213	493
5.6209	497
5.6213	498
5.6362	757
5.6494	986
5.6512	1000

Table 3.8

Variation of Lattice Parameter a_0
of 5 w/o Plutonia-95 w/o Urania with Temperature
ThO₂ - Internal Standard

a_0 for 5w/o PuO ₂ -95 w/o UO ₂ A($\pm$ 0.0011)	a_0 for Thoria A($\pm$ 0.0011)	Temperature °C
5.4665	5.5971	26
5.4667	5.5983	52
5.4677	5.5998	83
5.4683	5.6008	104
5.4688	5.6020	127
5.4807	5.6103	293
5.4861	5.6173	427
5.5010	5.6241	555
5.5168	5.6435	902
5.5283	5.6514	1045
5.5427	5.6621	1234
5.5314	5.6527	1067
5.5493	5.6634	1258

Table 3.9

Variation of Lattice Parameter a_0
of 12.5 w/o Plutonia-87.5 w/o Urania with Temperature
ThO₂ - Internal Standard

a_0 for 12.5 w/o PuO ₂ -87.5 w/o UO ₂	a_0 for Thoria	Temperature °C
5.4589	5.5969	24
5.4600	5.5988	63
5.4623	5.6027	143
5.4654	5.6051	191
5.4731	5.6173	426
5.4842	5.6227	530
5.5007	5.6378	804
5.5064	5.6446	923
5.5147	5.6466	957
5.5183	5.6527	1067
5.5308	5.6668	1318

Figure 3.8
THERMAL EXPANSION ThO₂ (STANDARD)

Figure 3.9
THERMAL EXPANSION ThO₂ (EXPERIMENTAL)

Figure 3.10
THERMAL EXPANSION PuO_2 (Pu9 LOT 2)

The experimental limits for which the equation was calculated are 24 to 1318°C, and the calculated coefficient of thermal expansion is $10.7 \times 10^{-6}/^{\circ}\text{C}$ between 0 and 1250°C. The polynomial expansion for the 20% PuO₂-80% UO₂ solid solution (Table 3.10, Figure 3.11) was:

$$a_0 = 2.5426 \times 10^{-8}t^2 + 3.2822 \times 10^{-5}t + 5.4497$$

The coefficient of thermal expansion for this material as calculated from the above equation for experimental points between 25 and 1364°C is $11.85 \times 10^{-6}/^{\circ}\text{C}$ between 0 and 1250°C. The 35% PuO₂-65% UO₂ solid solution was measured under the same conditions as the other materials using ThO₂ as an internal standard, and the equation for the lattice expansion is (Table 3.11, Figure 3.12):

$$a_0 = 1.3299 \times 10^{-8}t^2 + 4.2010 \times 10^{-5}t + 5.4431$$

The coefficient of thermal expansion for this material computed from experimental points between 24 and 1304°C is $10.77 \times 10^{-6}/^{\circ}\text{C}$ between 0 and 1250°C. The coefficient of thermal expansion is obtained from the polynomial expansion of the lattice parameter as a function of temperature by differentiating the polynomial and calculating $(da/dT)a_0$ at the midpoint of the temperature interval, 625°C.

Table 3.10

Variation of Lattice Parameter a_0 of 20% Plutonia-80% Urania
with Temperature ThO₂
Internal Standard

a_0 for 20% PuO ₂ -80% UO ₂ A(± 0.0011)	a_0 for Thoria A(± 0.0011)	Temperature °C
5.4531	5.5969	25
5.4536	5.6020	127
5.4551	5.6044	176
5.4697	5.6204	487
5.4827	5.6306	674
5.4804	5.6292	649
5.4920	5.6371	790
5.5051	5.6455	939
5.5134	5.6512	1040
5.5317	5.6625	1240
5.5384	5.6694	1364

Table 3.11

Variation of Lattice Parameter a_0 of 35% Plutonia-65% Urania
Urania with Temperature ThO₂
Internal Standard

a_0 for 35% PuO ₂ -65% UO ₂ A (± 0.0011)	a_{00} for Thoria A (± 0.0011)	Temperature °C
5.4439	5.5969	24
5.4444	5.5972	30
5.4450	5.5988	63
5.4465	5.5994	74
5.4490	5.6004	95
5.4532	5.6069	227
5.4581	5.6133	348
5.5008	5.6492	1002
5.5055	5.6556	1121
5.5139	5.6617	1226
5.5210	5.6661	1304

Figure 3.11
THERMAL EXPANSION UO_2

Figure 3.12

THERMAL EXPANSION 5 w/o PuO₂ - 95 w/o UO₂

FUEL ELEMENT FABRICATION AND EVALUATION

Task 4.00
I. D. Thomas

Fabrication of High Burnup Test Specimens
(R. M. Horgos, M. D. Houston)

The fabrication of all pelletized high burnup test specimens of the general compositions UO_2 -5% PuO_2 (7.5% U^{235}) and UO_2 -20% PuO_2 was completed during this period. The sintering characteristics for the various compositions and preparations are shown in Table 4.1. All pellets were sintered to slightly oversize and centerless ground to 0.199 ± 0.0005 inch to facilitate a close fit with the fuel element tube, 0.200 inch I.D. These pellets were ultrasonically cleaned in alcohol and dried in a vacuum oven at 60°C until a constant final weight was observed. Electrical resistivity determinations on these finished pellets indicated that the initial oxidation or reduction status had not been significantly altered. Subsequent oxygen-to-metal ratios determined by the gravimetric oxidation-reduction process also indicated a stability of the material throughout the grinding, cleaning, and drying process.

Table 4.1

Sintering Characteristics of UO₂-PuO₂ Compositions
for High Burnup Irradiation Specimens
 (Sintered at 1600°C in N₂-6% H₂)
 (Compaction Pressure - 10 tsi)

Preparation	Composition	Green Density gm/cc	Sintering		Fired Density % Theoretical	Electrical Resistivity ohm-cm	Oxygen-Metal Ratio
			Time hours	Atmosphere			
Pu45SS80-840	5.0% PuO ₂ 7.5% U ₂ 35	5.75	1	Dry	96.8	8.0 x 10 ⁴	1.985
MBRL-5	5.0% PuO ₂ 7.5% U ₂ 35	5.24	16	Dry	95.6	3.3 x 10 ⁴	1.980
MBRL-5	5.0% PuO ₂ 7.5% U ₂ 35	5.24	16	Wet	92.5	4.1 x 10 ²	1.982
UO ₂ - Unfired PuO ₂ Spheres	5.0% PuO ₂ 7.5% U ₂ 35	5.21	1	Dry	94.1	2.2 x 10 ⁵	-
UO ₂ - Fired PuO ₂ Spheres	5.0% PuO ₂ 7.5% U ₂ 35	5.30	1	Dry	93.5	1.1 x 10 ⁵	-
UO ₂ - Fired UO ₂ - 35% PuO ₂ Spheres	5.0% PuO ₂ 6.4% U ₂ 35	5.56	1	Dry	92.4	4.5 x 10 ⁵	-
Pu44SS80-840	20% PuO ₂	5.80	1	Dry	97.5	1.9 x 10 ⁶	1.986
MBRL-20	20% PuO ₂	5.26	16	Dry	93.8	1.7 x 10 ⁷	1.979
MBRL-20	20% PuO ₂	5.26	16	Wet	89.5	8.9 x 10 ²	2.001

RADIATION TESTING AND EVALUATION

Task 5.00

O. Menis

I. D. Thomas

Short-Term Irradiation Test

(R. M. Horgos, W. Judd)

The remaining three capsules, of the fourteen total, have been irradiated to complete this phase of the program. One of the capsules, containing 0.5 w/o PuO_2 had been inadvertently mixed with some material consigned for disposal and has been lost. The remaining thirteen capsules have been returned to NUMEC for subsequent post-irradiation evaluation.

All thirteen capsules were examined, usually with no noticeable or apparent deleterious effects caused the the irradiation. Three of the capsules were cut open to release the specimens. All specimens were examined and showed no increase in physical dimensions or change in appearance. Element Number 1-46 has been cut open to expose the fuel for examination. One pellet from this element was mounted, polished, and cathodically vacuum etched. Figure 5.1 depicts the typical structure of the fuel. Figure 5.2 is a macrophotograph of the pellet.

Complete examination of additional elements is planned with emphasis being placed on those elements which have been exposed to the maximum neutron flux and thus have reached centerline temperatures in excess of the melting temperature of the fuel material.

Data has been obtained on the fission rate experienced by the fuel capsules using a gamma scan. Figure 5.3 shows the spectrum of gamma emission obtained on some of the fuel removed from one of the elements (1-56, Capsule 1-7). The gamma energies which predominate are 0.75, 0.50, 0.13, and 0.05 Mev corresponding to $\text{Zr}^{95}\text{-Nb}^{95}$, Ru^{103} , and Ce^{141} , respectively.

It was felt that measurement of the $\text{Zr}^{95}\text{-Nb}^{95}$ gamma would give a good indication of the fission density of the fuel material during the one hour irradiation tests, and consequently the measurements were made on a weighed portion of the fuel, appropriate corrections for decay applied, and the fission density calculated for the sample. A value of 5.8×10^{13} fissions/second/cc was obtained by this method. This corresponds to a calculated value of 6.2×10^{13} fissions/second/cc.⁽¹⁾

(i) NUMEC P-90, Progress Report, "Development of Plutonium-Bearing Fuel Elements"

Figure 5.1

Typical Fuel Structure

Element 1-46

(UO_2 -0.5 w/o PuO_2)

400X

NUMEC-2389-4

Figure 5.2

Macrograph of Pellet
Element 1-46
(UO_2 -0.5 w/o PuO_2)

3X

Figure 5.3
POST-IRRADIATION EXAMINATION OF ONE HOUR
IRRADIATED FUEL SPECIMEN

Subsequently in a non-destructive test, most of the irradiated elements have been "gamma-scanned" to obtain a radiation profile as a function of position along the major axis of the element, and representative scans are presented in Figure 5.4.

The "gamma scanning" was performed by passage of the element in front of a 1/16 inch slit in a four inch thick lead shield. The radiation from a 1/16 section of fuel was thus allowed to impinge upon a standard gamma detector, and the resultant output was fed to a 256 Channel Analyzer. The sample elements were counted every 1/4 inch along their length, and the photopeak count due to the decay of Zr^{95} - Nb^{95} was calculated.

An inspection of these figures reveals that, for the most part, the flux was fairly flat along the longitudinal axis of the element. In a few cases there seems to be evidence of change in flux along the longitudinal axis of the element.

The relative count rate of a section of an element can be used as a correlation of the fission rate of that particular section to other sections, and relative count rates of different elements can be used to estimate the relative fission rates of the different elements. The parameters which affect the fission rate are fuel content and flux; the final count rate is, of course, affected by these parameters and also by the decay time.

These data will be normalized by radiochemically separating and calculating the absolute disintegration rate of a single element. It will then be possible to make a final estimation of the absolute flux experienced by each fuel increment.

High Burnup Irradiation Tests (R. M. Horgos)

Fabrication of the test components has been initiated after obtaining a general approval of the test design and operational parameters of the program. Purchase orders have been placed for the Zircaloy capsules and the thermocouple assemblies. Cladding components for the fuel elements have been received.

Detailed discussions of the program have been held with the reactor operators, and a critical evaluation of the test parameters was made. No major changes were necessary to the capsule or element design; however, the inherent hazards associated with the irradiation testing of plutonium-bearing fuels dictated additional testing of the components to verify the safe operation of the program.

Figure 5.4

GAMMA SCAN OF CAPSULE 1-34

4-27-64

PLUTONIUM SINGLE CRYSTAL GROWTH

Task 20.00

I. D. Thomas

G. M. Miller

This program is directed towards the growth of plutonium and plutonium alloy single crystals having the room temperature stabilized morphology of the various plutonium allotropes. Initial work is being directed towards pure alpha phase crystals and aluminum stabilized delta phase crystals.

The growth of alpha plutonium single crystals is complicated by a number of factors. The most important of these are the complex monoclinic structure and the low solid state diffusion rates associated with the upper temperature limit for phase stability (120°C). However, there are a number of other unique properties that can be exploited to at least partially offset these detrimental factors. The large volume change associated with the phase transformation suggests that phase stability temperature ranges should be greatly affected by pressure. The magnitude of this effect has recently been experimentally determined by Stephens⁽ⁱ⁾. At very high pressures (500,000 psi) the alpha range is stable to 400°C so that with the application of increased temperature, the associated increased solid state diffusion rate can be utilized for the growth of alpha single crystals. Nachtrich^(ii,iii) has shown that D , the self-diffusion coefficient as a function of temperature and pressure, is proportional to $T/T_m(P)$, where $T_m(P)$ is the melting temperature at pressure P . Since dT_m/dP for plutonium is negative⁽¹⁾, the self-diffusion rate can be expected to increase with pressure as well as with temperature. Right circular cylinders of pure plutonium will be given a variety of heat treatments under moderately high ($< 100,000$ psi) pressures. Samples will

-
- (i) D. R. Stephens, "The Phase Diagram of Plutonium", Phys. Chem. Solids, Pergamon Press, 24, pp 1197-1202 (1963).
 - (ii) N. H. Nachtrich and J. Petit, J. Chem. Phys., 24, Number 5, p. 1027 (1955)
 - (iii) W. Paul, D. M. Warschauer, Solids Under Pressure, McGraw Hill, p. 88 (1963).

be examined metallographically and by means of x-ray diffraction to determine the heat treatment parameters which most markedly affect grain growth. An attempt is being made to utilize the 10 percent volume expansion associated with the alpha to beta transformation to achieve high pressures. Precision machined plutonium cylinders are close fit into massive dies and totally enclosed. At the transformation temperature, the plutonium expands to fill the die and is pressurized by the driving force of the alpha to beta transformation. In this way, the alpha phase should be retained at elevated temperatures with the magnitude of the internal pressure buildup shown experimentally by Stephens⁽ⁱ⁾ pressure-temperature phase diagram for unalloyed plutonium. Concurrent with these high pressure experiments, an ultra high pressure apparatus (two million psi) is being fabricated which will allow additional definitive experiments to be performed.

Techniques for growing single crystals of metals which possess similar properties to plutonium are being investigated. A modified Andrade apparatus has been fabricated after a method which has proved successful in obtaining single crystals of uranium⁽ⁱⁱ⁾ (complex crystal structure) and thallium⁽ⁱⁱⁱ⁾ (low beta to alpha transformation temperature) (Figure 20.1) The technique is to progressively pass a wire or rod through the beta to alpha transformation temperature. A steep temperature gradient is used to reduce the probability that a new alpha grain will be nucleated in the beta phase ahead of the advancing alpha grain. The sample is heated electrically into the beta phase region and cooled through the beta to alpha transformation by slowly lowering it into an oil bath in the alpha temperature range. A high resistance (relative to the plutonium wire resistance) is placed in the wire heating circuit to insure constant current flow regardless of any resistance change in the plutonium wire as it decreases its temperature and transforms to alpha. The apparatus has been designed to tensile load a sample during transformation. The decision to include stress as a growth parameter is based on a preliminary study by Bronisz^(iv) which revealed that the alpha plutonium grain size is increased by creep loading in tension during the beta to alpha transformation.

-
- (i) D. R. Stephens, "The Phase Diagram of Plutonium", Phys. Chem. Solids, Pergamon Press, 24, pp. 1197-1202 (1963).
 - (ii) A. N. Holden, "Growth and Crystallography of Deformation of B-Phase Uranium Single Crystals", Acta Cryst., 5, p. 182 (1952).
 - (iii) O. D. Sherby, Trans. AIME, 212, p. 798 (1958).
 - (iv) S. Bronisz, LASL, private communication, April 1963.

Unalloyed plutonium wire (0.187 inch diameter and 0.040 inch diameter) has been extruded for the preparation of samples. See Table 20.1 for the extrusion data. Moly disulphite dispersed in alcohol was applied to the die as lubricant. The plutonium was arc melted just prior to extruding, heated in place, and extruded with a 10,000 psi hand press. The extrusion constant, K , was obtained from the relation $P = 2 K \ln A_1/A_2$ where P is the maximum extrusion pressure and A_1 and A_2 are the container area and die area, respectively.

Three tests have been performed, two with the wire tensile loaded to 1000 psi at 150°C and one with the wire tensile loaded to 475 psi at 205°C. In all three tests, the oil temperature was 76°C, and the feed rate was 0.185 cm/hr. Two specimens loaded to 1900 psi and 100 psi, respectively, at 205°C crept very rapidly, causing the tests to be discontinued. This is contradictory to Gardener's data⁽¹⁾ which gives the yield stress of unalloyed plutonium at 200°C as greater than 1950 psi.

The two samples heated to 150°C showed room temperature ductility as evidenced by an ~15° permanent set in the wire after fracture by bending. As extruded samples and the sample heated to 205°C showed no signs of ductility. Metallography is being performed and back-reflection Lave x-ray photographs are being made to determine grain size and the possible existence of a single crystal.

The strain anneal technique will be investigated for aluminum stabilized delta plutonium. Many materials show grain growth at a specific critical strain which often covers only a narrow range. By straining a taper bar in tension to produce varying degrees of strain along the bar, it should be possible to determine the critical strain region if it exists.

(i) H. R. Gradener, I. B. Mann, "Mechanical Property and Formability Studies on Unalloyed Plutonium", HW-65019 (1959).

MODIFIED ANDRADE APPARATUS