440 OMS
4-14-65

~~CONFIDENTIAL~~

MASTER

NAA-SR-9704

COPY

26 PAGES

33304

UNCLASSIFIED

MASTER

C-RO Classification
Completed 11-2-71
J. H. [illegible]

MICROSTRUCTURE STUDIES
OF
SNAP FUELS
(Title Unclassified)

AEC Research and Development Report

~~RESTRICTED DATA~~

This document contains restricted data as defined in the Atomic Energy Act of 1954. Its transmittal or the disclosure of its contents in any manner to an unauthorized person is prohibited.

This document contains Confidential-Restricted Data relating to civilian applications of atomic energy.

~~CONFIDENTIAL~~
Excluded from automatic downgrading and declassification

ATOMICS INTERNATIONAL

A DIVISION OF NORTH AMERICAN AVIATION, INC.

UNCLASSIFIED

0 665 000

0 665 000

~~CONFIDENTIAL~~

1 1166

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

CLASSIFIED

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

Printed in USA

Price: \$0.50

Available from the

U. S. Atomic Energy Commission
Technical Information Extension,
P. O. Box 1001
Oak Ridge, Tennessee.

Please direct to the same address inquiries covering the procurement of other classified AEC reports.

CLASSIFIED

UNCLASSIFIED

CONFIDENTIAL

NAA-SR-9704
SNAP REACTOR-
SNAP PROGRAM
M-3679 (38th Ed.)

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

MICROSTRUCTURE STUDIES

OF

SNAP FUELS

(Title Unclassified)

By

H. TAKETANI

Classification cancelled (or changed to)

UNCLASSIFIED

by authority of

Letter 4/17/73

Bram Feldman, Div of Class.

by GG

DTIE, date

6/18/73

Wash DC

Exempt from CCRP Re-review Requirement

(per 7/22/82 Duff/Caudle memorandum)

HA 7/04

RESTRICTED DATA

This document contains restricted data as defined in the Atomic Energy Act of 1954. Its transmittal or the disclosure of its contents in any manner to an unauthorized person is prohibited.

This document contains Confidential-Restricted Data relating to civilian applications of atomic energy.

ATOMICS INTERNATIONAL

A DIVISION OF NORTH AMERICAN AVIATION, INC.
P.O. BOX 309 CANOGA PARK, CALIFORNIA

UNCLASSIFIED

CONFIDENTIAL

CONTRACT: AT(11-1)-GEN-8
ISSUED: MARCH 30, 1965

UNCLASSIFIED

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

~~CONFIDENTIAL~~

DISTRIBUTION

SYSTEMS FOR NUCLEAR AUXILIARY POWER (SNAP)-REACTOR SNAP PROGRAM M-3679 (38th Ed.)

	No. of Copies		No. of Copies
Aerojet-General Corporation (NASA)	6	Minnesota Mining and Manufacturing Co.	1
Aerojet-General Corporation, Sacramento	1	Monsanto Dayton Laboratory	1
Aerojet-General Nucleonics	1	Mound Laboratory	1
Aerojet-General Nucleonics (NASA)	1	NASA Ames Research Center	1
Aeronautical Systems Division	2	NASA Goddard Space Flight Center	2
Aerospace Corporation	1	NASA Langley Research Center	1
Aerospace Test Wing (AFSC)	1	NASA Lewis Research Center	7
Air Force Surgeon General	1	NASA Manned Spacecraft Center	1
Air Force Weapons Laboratory	2	NASA Marshall Space Flight Center	1
Air University Library	1	NASA Scientific and Technical Information	
AIResearch Manufacturing Company, Phoenix	1	Facility	3
Allison Division - GMC	1	National Aeronautics and Space Administration,	
Argonne National Laboratory	1	Washington	2
Army Ballistic Research Laboratories	1	NASA Western Operations Office	1
Army Missile Command	1	Naval Air Development Center	1
Army Weapons Command	1	Naval Ordnance Laboratory	2
ARO, Inc.	1	Naval Postgraduate School	1
Avco Corporation	1	Naval Radiological Defense Laboratory	1
Battelle Memorial Institute	1	Naval Research Laboratory	2
Bendix Corporation (AF)	1	Naval Underwater Ordnance Station	1
Brookhaven National Laboratory	1	Navy Marine Engineering Laboratory	1
Bureau of Naval Weapons	2	New York Operations Office	1
Bureau of Ships	2	New York Operations Office, Canel Project	
Bureau of Yards and Docks	1	Office	1
California Patent Group	1	Nuclear Metals, Inc.	1
Central Intelligence Agency	1	Office of Naval Research	2
Chicago Patent Group	1	Office of the Assistant General Counsel for	
Defense Atomic Support Agency, Sandia	1	Patents (AEC)	1
Department of the Army	1	Office of the Chief of Engineers	1
Director of Defense Research and		Office of the Chief of Naval Operations	3
Engineering (OAP)	1	Office of the Chief of Naval Operations (OP-03EG)	2
Douglas Aircraft Company, Inc., Newport Beach	1	Office of the Chief of Transportation	1
Edgerton, Germeshausen and Grier, Inc.,		Phillips Petroleum Company (NRTS)	4
Goleta	1	Pratt and Whitney Aircraft Division	1
Electro-Optical Systems, Inc.	1	Pratt and Whitney Aircraft Division (NASA)	1
Foreign Technology Division (AFSC)	1	Radio Corporation of America	1
General Atomic Division	1	Rand Corporation	1
General Dynamics/Astronautics (AF)	1	Sandia Corporation	1
General Dynamics/Fort Worth	1	School of Aerospace Medicine	1
General Electric Company, Cincinnati	1	Union Carbide Corporation (ORNL)	8
General Electric Company (FPD)	2	United Nuclear Corporation (NDA)	1
General Electric Company (MSVD)	1	USAF Headquarters	1
General Electric Company, Richland	2	University of California, Livermore	1
General Electric Company, San Jose	1	Westinghouse Electric Corporation, Lima	1
Institute for Defense Analyses	1	Westinghouse Electric Corporation, Lima (AF)	1
Jet Propulsion Laboratory	2	Westinghouse Electric Corporation (NASA)	1
Johns Hopkins University (APL)	1	White Sands Missile Range	2
Lockheed-Georgia Company	1	Division of Technical Information Extension	40
Lockheed Missiles and Space Company	1	AI Library (Includes 2 copies to CPAO,	
Los Alamos Scientific Laboratory	1	2 copies to AEC, Washington,	
Martin-Marietta Corporation, Denver	1	2 copies to COO)	104

NAA-SR-9704

2

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

CONTENTS

	Page
Abstract	6
I. Introduction	7
II. Materials	8
III. Procedure	9
A. Metallography	9
B. Electron Microscopy	9
C. X-ray Diffraction	10
D. Electron Microprobe	10
IV. Results	11
A. Uranium Precipitate	11
B. Zirconium Carbide Compounds	11
C. Submicron Artifacts	13
D. Quantitative Metallographic Analysis	13
E. ϵ Hydride Matrix Phase	19
V. Conclusions	25
References	26

TABLES

1. Fuel Material Analysis	8
2. Precipitate Phases	25

FIGURES

1. Uranium Precipitate in ϵ Phase	12
2. Incomplete Hydriding of $ZrC_{0.54}$ Precipitate	12
3. Fracture Surface of Fuel Without ZrC Addition	14
4. Fracture Surface of Fuel With ZrC Addition	14
5. δ Phase Forming Around ZrC Compounds	15
6. ZrC Compounds in ϵ Phase	15
7. Effects of ZrC on Structure — 0.02 wt % C Fuel	16
8. Effects of ZrC on Structure — 0.21 wt % C Fuel	16

FIGURES

	Page
9. Effects of ZrC on Structure — 0.50 wt % C Fuel	17
10. Submicron Artifacts with a Spherical Uranium Precipitate	17
11. Submicron Artifacts on Top of Ternary Precipitate	18
12. Submicron Artifacts in Recessed Region of ϵ Banding	18
13. Zr-U-H Phase Diagram	20
14. Cross Twinning in ϵ Phase	21
15. Sub-Banding in ϵ Phase (Note submicron artifacts)	21
16. Microhardness Indentions to Mark Probe Traces	22
17. As-Polished Surface, Ready for Probe Examination	22
18. Back Scattered Electron Scan	24
19. Specimen Current Scan	24

~~CONFIDENTIAL~~

ACKNOWLEDGMENT

Appreciation is expressed to D. T. Shoop and J. T. Wade for the metallographic preparation of the samples. Chemical preparation of the fuel for x-ray studies was performed by L. Silverman, and x-ray studies were conducted by D. J. Klein and W. L. Korst.

Special thanks are extended to W. G. Brammer and E. G. Szmborski, for their assistance in the electron microscopy studies, and to C. Nealy, for the electron microprobe examination.

NAA-SR-9704

5

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

ABSTRACT

The microstructure of SNAP 8 and 2/10A fuels consists of two precipitate phases within a matrix of ϵ zirconium hydride.

The precipitate phases are: α uranium, and reacted zirconium carbide ($\text{ZrC} \cdot \text{ZrH}_x$). The banded ϵ matrix was found to consist of alternating layers of elements with different atomic numbers, as indicated by back scattered electrons and specimen current detection methods. However, dispersive x-ray intensities did not confirm this.

NAA-SR-9704

6

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

I. INTRODUCTION

The microstructure of SNAP fuels was examined in detail, in order to supply supporting material property information for the fuels irradiation program. The techniques used were:

- 1) Quantitative metallography,
- 2) Electron microscopy,
- 3) X-ray diffraction, and
- 4) Electron microprobe analysis.

The SNAP fuel consists of a zirconium - 10 wt % uranium alloy hydrided to a minimum hydrogen content of 1.7 wt %. In addition, small amounts of ZrC are added to promote grain refinement during the hydriding process in order to prevent cracking.

NAA-SR-9704

7

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

II. MATERIALS

Fuel materials having three levels of ZrC additions were studied, since they represented the range of composition used for the core loadings. Detailed chemical analyses are presented in Table 1. For historical reasons, carbon levels

TABLE 1
FUEL MATERIAL ANALYSIS

Rod No.	C (wt %)	H (wt %)	U (wt %)	Total Impurity (wt %)
110-9	0.02 (0.17 wt % ZrC)*	1.82	10.3	~0.2 [†]
241-6	0.21 (1.73 wt % ZrC)	1.68	10.1	~0.2
205-2	0.50 (4.30 wt % ZrC)	1.76	9.85	~0.2

*Exists as impurity in zirconium sponge starting material.

[†]Impurity is primarily oxygen.

were referred to instead of ZrC additions. Thus, the fuel materials were referenced as; 0.02, 0.20, and 0.51 wt % C.

These fuel materials were prepared by melting, extruding, and hydriding. Alloys were melted using triple consumable arc melting techniques in a vacuum of approximately 1 μ . The melt stock consisted of reactor grade carborundum zirconium sponge, reactor grade National Lead uranium feedstock, and high-purity Wah Chang zirconium carbide powder (-325 mesh). Extrusion was carried out at 540°C, using a reduction in area of approximately 10 to 1. The extruded billets were then machined into 1-1/2-in.-diameter by 13-in.-long fuel rods. The fuel rods were hydrided at 900°C using the process employed for the S2DR-1 core.⁽¹⁾ High-purity hydrogen gas, with a certified total impurity content of less than 10 ppm, was used.

~~CONFIDENTIAL~~

III. PROCEDURE

The procedures used for studying the microstructures of the fuel materials consisted primarily of preparing the samples for:

- 1) Quantitative metallographic studies
- 2) Electron microscopy examination
- 3) X-ray diffraction analysis
- 4) Electron microprobe scans.

A. METALLOGRAPHY

For the metallographic studies, the fuel was carefully mounted in Bakelite, since excessive mounting pressure causes cracking. The samples were rough ground through 180, 320, 400, and 600 grit SiC paper, using the polishing wheel at low speeds. To remove the 600 grit scratches, the samples were polished with 30 μ diamond paste on a damp Metcloth. Disturbed metal was removed from the sample surface by a final polish with "Linde B" powder and a 10% oxalic acid solution. This was followed by an attack polish, consisting of 200 cc H_2O , 5 cc HNO_3 , and 3 drops of HF on a high-speed polishing wheel.

Two etching techniques were used: electrolytic and chemical. The former was used for phase-contrast studies, and the latter for electron microscopy and electron microprobe examination. For electrolytic etching, the fuel was used as the anode and a stainless steel ring as the cathode, in a solution of 10% oxalic acid. A potential of 16 volts was applied, for a fraction of a second, to the face of the specimen with a copper probe. Chemical etching was accomplished by varying the final stage of the attack polish by reducing the wheel speed and polishing pressure.

B. ELECTRON MICROSCOPY

Germanium-shadowed carbon replicas were used for the microscopy studies. Germanium was shadowed on the sample's surface at a 45° angle; and carbon was evaporated over the germanium, normal to the surface. The sample was "scored" with a fine point and was slowly inserted in water. When the replicas floated free, they were picked up on copper grids and dried on filter paper. Due to artifacts being introduced by the etching process, modification of the standard metallographic preparation was made. This consisted of using a different attack

~~CONFIDENTIAL~~

polish, followed by a flush. The attack polish consisted of two-step procedure:

- 1) A slight under-etch with a solution of 600 cc H_2O , 1 drop HF, 10 to 16 cc HCl, and 10 to 16 cc lactic acid
- 2) A final etch, using a solution of 300 cc H_2O , 5 cc HCl, and 10 to 15 cc lactic acid.

This was followed by a flushing operation, which consisted of applying high-flow distilled water to the sample while it was still on the polishing wheel.

C. X-RAY DIFFRACTION

X-ray diffraction techniques were used to determine the chemical form of the precipitates found in the fuel. The precipitates were coalesced by dissolving the fuel with bromine in ethyl acetate, and successively filtering through 1.5, 0.25, and 0.05 μ filters. The selection of bromine was the result of a study⁽²⁾ made to develop a solvent that would dissolve zirconium hydride, but would not react with ZrC. The residue on the filters was then examined by conventional x-ray diffraction technique, using Norelco equipment with a diffractometer, and with a G-M counter filtered on copper $K\alpha$ radiation, using normal settings.

D. ELECTRON MICROPROBE

Samples were prepared for electron microprobe examinations by using standard metallographic procedures. Microhardness indentations were used to mark the probe traces. An ARL Electron Microprobe X-Ray Analyzer was used. Quantitative microprobe data were obtained primarily by comparisons with known standards, and corrections were made where they failed to give precise comparisons. These consisted of deadtime, background, absorption, fluorescence, and wave length shift. The detection methods used were specimen current, back scattered electrons, and dispersive and nondispersive x-rays.

NAA-SR-9704

10

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

IV. RESULTS

These studies revealed that the SNAP fuel microstructure consisted of two precipitate phases within a matrix of ϵ hydride. The precipitates are α uranium and $\text{ZrC} \cdot \text{ZrH}_x$. A third "precipitate" was found, but later studies revealed that they were artifacts.

A. URANIUM PRECIPITATE

Optical metallographic techniques revealed uranium precipitate at the hydride grain boundaries and within the hydride grains. The precipitates at the grain boundaries are large and elongated, whereas those within the grains are small and symmetrical (i.e., spheres approximately 0.5μ in diameter.) This can be seen in Figure 1. X-ray diffraction studies by Biganey *et al.*⁽³⁾ revealed the crystalline structure of the uranium precipitate in the uranium-zirconium-hydrogen to be α uranium.

B. ZIRCONIUM CARBIDE COMPOUNDS

The zirconium carbide compounds occur as platelets, usually within the grains. The ZrC was added to the fuel during the melting operation as a powder in the primary electrode. In the presence of excess zirconium, sub-stoichiometric zirconium carbide forms. Novotny *et al.*⁽⁴⁾ have reported a value of $\text{ZrC}_{0.54}$ for this compound. When the fuel material is hydrided, this compound also hydrides to form $\text{ZrC} \cdot \text{ZrH}_x$. Rexer and Peterson⁽⁵⁾ had previously discovered this compound and had indexed the metal atoms on a hexagonal close-packed lattice. However, not all the sub-stoichiometric $\text{ZrC}_{0.54}$ hydrides under our conditions. Chemical separation and x-ray diffraction studies indicate that 10 to 20% of the $\text{ZrC}_{0.54}$ is unreacted. A possible explanation is that the core or center of each large $\text{ZrC}_{0.54}$ particle is unreacted since hydriding is a diffusion process and, under our hydriding conditions, sufficient time is not allowed for complete hydriding to take place. Careful examination of Figure 2 reveals a cored structure for the hydrided particles which indicates a possibility of the hydriding reaction moving inwards from the periphery of each particle.

It is interesting to note that stoichiometric ZrC does not hydride. ZrC powders have been exposed to hydrogen gas at 1000°C for times up to three weeks and weight gain measurements and x-ray diffraction patterns revealed no hydriding taking place.

3794-3-3

Figure 1. Uranium Precipitate
in ϵ Phase

3794-12-3

Figure 2. Incomplete Hydriding of
 $ZrC_{0.54}$ Precipitate

NAA-SR-9704

12

CONFIDENTIAL

The addition of ZrC increases the hydriding yield of acting as grain refiners and their effects can be seen in Figures 3 and 4. There is a strong indication that the grain refinement is one of nucleation, since:

- 1) These dispersions are usually within the new hydride grains at the onset of hydriding (Figure 5).
- 2) They are predominantly absent from the grain boundaries in a completely hydrided structure (Figure 6).

Increasing the ZrC additions results in:

- 1) Increased compound precipitate size
- 2) Finer hydride grains and thinner ϵ banding, reaching an optimum value at a composition corresponding to 0.15 wt % C. This can be seen in Figures 7, 8, and 9.

C. SUBMICRON ARTIFACTS

Electron microscopy studies revealed what at first were thought to be sub-micron precipitates (Figure 10). However, by varying the etching and replicating techniques, these particles could be made to vary in number. In addition, they were found on top of the ternary compound (Figure 11) and concentrated in the recessed regions of the ϵ banding (Figure 12), indicating that they were etching artifacts that had been washed onto the surfaces of the specimens.

D. QUANTITATIVE METALLOGRAPHIC ANALYSIS

Quantitative metallographic analyses were made of the various precipitate sizes and distributions, using the same technique that was employed by Kramer.⁽⁶⁾ The properties measured were the average particle diameter (D), and the average number of particles per cc (N). For the uranium precipitate, electron photomicrographs at 6,000X were used. However, for the zirconium carbide compounds, optical photomicrographs at 600X were used, due to the larger size of these particles. Two assumptions were made in the calculation of N:

- 1) The particles are spheres of equal diameter, and
- 2) The area fraction seen on a plane is equal to the volume fraction.

CONFIDENTIAL

Figure 3. Fracture Surface of Fuel Without ZrC Addition

7568-47180

Figure 4. Fracture Surface of Fuel With ZrC Addition

7568-47179

NAA-SR-9704

14

CONFIDENTIAL

CONFIDENTIAL

Figure 5. δ Phase Forming Around ZrC Compounds

4513-7-3

Figure 6. ZrC Compounds in ϵ Phase

3794-11-1

Figure 7. Effects of ZrC on Structure —
0.02 wt % C Fuel

4397-7

Figure 8. Effects of ZrC on Structure—
0.21 wt % C Fuel

4397-4

Figure 9. Effects of ZrC on Structure —
0.50 wt % C Fuel

3794-10-1

Figure 10. Submicron Artifacts with a
Spherical Uranium Precipitate

EMBB 131

Figure 11. Submicron Artifacts on Top of Ternary Precipitate

EMBB 1937

Figure 12. Submicron Artifacts in Recessed Region of ϵ Banding

EMBB 1957

Thus,

$$N = \frac{\pi n}{4d}$$

and,

$$d^2 = \frac{2D^2}{3}$$

where

n = number of particles seen in a random plane

d = average diameter of particles seen in a random plane

As a result of the irregular shape and segregation of the zirconium carbide compounds, calculations were made from both a transverse and longitudinal section to determine D and N. Thus, the real values of D and N lie somewhere between the two values reported in Section V.

E. ϵ HYDRIDE MATRIX PHASE

Epsilon hydride has an fct structure with a c/a ratio <1 , but varying with hydrogen content. The formation of ϵ hydride from δ hydride (a fcc phase existing over a range of hydrogen content near an H/Zr atomic ratio of 1.5), is considered to be a martensitic reaction. If this is true, then PCT measurements should not be affected. However, Atkins⁽⁷⁾ and Libowitz⁽⁸⁾ have noticed an effect of ϵ hydride on isotherms. Consequently, it must not be a true equilibrium phase in the classic thermodynamic sense.⁽⁹⁾

A phase diagram of the Zr-U-H system is shown in Figure 13. This was taken from x-ray diffraction and isotherm studies by Bigony et al.⁽³⁾

Metallographically, the ϵ phase appears to be a result of twinning, with alternate layers of light and dark bands traversing the grains (Figure 14). In addition, sub-banding occurs within the bands (Figure 15). Microprobe traces were made within these bands to look for zirconium content differences, in order to resolve the question of δ -to- ϵ transformation being first or second order. The material was etched and hardness indentions were made within the bands to mark the probe traces (Figure 16). The etched surface was repolished to remove the etchant to prevent contamination and probe traces were made on an as-polished surface from one hardness indentation to another (Figure 17).

7568-1531@

Figure 13. Zr-U-H Phase Diagram

Figure 14. Cross Twinning in ϵ Phase

4397-6

Figure 15. Sub-Banding in ϵ Phase
(Note submicron artifacts)

EMBB 132

NAA-SR-9704

21

CONFIDENTIAL

Figure 16. Microhardness Indentations to Mark Probe Traces

5212-4-3

Figure 17. As-Polished Surface, Ready for Probe Examination

5212-4-5

~~CONFIDENTIAL~~

Dispersive x-ray intensities indicated that no variation in zirconium content existed. However, back scattered electron (Figure 18) and specimen current photos (Figure 19) did reveal the banding. This is normally indicative of atomic number differences. However, in this case, crystal orientation may be responsible. Continued microprobe studies are required before this question can be resolved.

NAA-SR-9704

23

~~CONFIDENTIAL~~

Figure 18. Back Scattered Electron Scan

5212-10

Figure 19. Specimen Current Scan

5212-11

V. CONCLUSIONS

Results of these examinations revealed the microstructure of SNAP 8 and 2/10A fuel to consist of two precipitate phases within a matrix of ϵ zirconium hydride. The precipitate phases are α uranium and the ternary compound $\text{ZrC} \cdot \text{ZrH}_x$ with $x < 2$. However, due to kinetic considerations, the ternary precipitate in our fuel does not completely hydride. Consequently, it is a cored structure with an unreacted center of sub-stoichiometric $\text{ZrC}_{0.54}$. The amount of the unreacted compound corresponds to 10 to 20 wt % of the original stoichiometric ZrC addition.

Quantitative metallographic measurements of the size and distribution of these precipitates were made. The results are shown in Table 2.

TABLE 2
PRECIPITATE PHASES

C Level of Fuel (wt %)	Uranium Precipitates		$\text{ZrC} \cdot \text{ZrH}_x$ Precipitates			
	Size μ	Distribution (No. of ppts/cc)	Size μ		Distribution (No. of ppts/cc)	
	Trans	Trans	Long.	Trans	Long	Trans
0.02	0.9	3×10^{10}	Traces	Traces	Traces	Traces
0.21	0.5	6×10^{10}	4	6	4×10^8	3×10^8
0.50	0.5	5×10^{10}	18	10	5×10^7	1×10^8

The matrix material, ϵ hydride, is a fct phase with a c/a ratio < 1 , which varies with hydrogen content. At our composition, a c/a ratio of 0.927^{10} would be expected. Microprobe analyses were made within the ϵ banding to determine whether zirconium content variations existed. Back scattered electron and specimen current scans indicated that a variation did exist. However, correlation was not obtained with dispersive x-ray intensities. Consequently, continued probe studies will be required before the question of ϵ transformation being first or second order can be resolved.

~~CONFIDENTIAL~~

REFERENCES

1. H. Taketani, "Hydriding of SNAP 2 Fuel Rods," NAA-SR-5037 (June 1, 1963)
2. H. Taketani, L. Silverman, and W. L. Korst, "Identification of the Modifier in SNAP Fuel," NAA-SR-10174 (February 1, 1965)
3. H. E. Bigony et al., "Fueled Moderator Studies: Phase Relations and Radiation Damage in Hydrided Zirconium-Uranium Alloys, Second Metal Hydride Conference, October 14, 15, 16, 1959," LAR 6 (February 1960)
4. R. Kieffer and F. Benesovsky, Hartstoffe (1st ed., Vienna, Springer-Verlag, 1963) p 109
5. J. Rexer and D. T. Peterson, "Ternary Metal-Carbon-Hydrogen Compounds of Some Transition Metals," Nuc. Met. 10, 327 (1964)
6. D. Kramer, "Finely Dispersed Phases in Uranium-Molybdenum Ternary Alloys," J. Nuc. Mat. 4, 11 281-286 (1961)
7. D. F. Atkins, "Dissociation Pressures of Hydrided Zirconium-Uranium Alloys," NAA-SR-4245 (February 15, 1960)
8. G. G. Libowitz, "A Pressure-Composition-Temperature Study of the Zirconium-Hydrogen System at High Hydrogen Contents," J. Nuc. Mat. 5, pp 228-233 (1962)
9. G. M. Wolten, "Martensite Transformations and the Phase Rule," J. Chem. Educ. 37, pp 237-239 (1960)
10. W. L. Korst, "X-Ray Studies of δ and ϵ Zirconium Hydrides," NAA-SR-6880 (March 30, 1962)

~~CONFIDENTIAL~~