216
12-16-69

1132

AI-AEC-12864
COPY

MASTER

SNAP 8 DEVELOPMENT REACTOR
NUCLEAR ANALYSIS

AEC Research and Development Report

Atomics International
North American Rockwell

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report; or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

Printed in the United States of America
Available from
Clearinghouse for Federal Scientific and Technical Information
National Bureau of Standards, U.S. Department of Commerce
Springfield, Virginia 22151
Price: Printed Copy \$3.00; Microfiche \$0.65

SNAP 8 DEVELOPMENT REACTOR
NUCLEAR ANALYSIS

By
L. D. SWENSON

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States nor the Commission nor any person acting on behalf of the Commission

A. Makes any warranty or representation expressed or implied with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights, or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, person acting on behalf of the Commission includes any employee or contractor of the Commission or employee of such contractor to the extent that such employee or contractor of the Commission or employee of such contractor prepares, disseminates, or provides access to any information pursuant to his employment or contract with the Commission or his employment with such contractor.

Atomics International
North American Rockwell

CONTRACT: AT(04-3)701
ISSUED: OCTOBER 31, 1969

100-100000-100000
100-100000-100000

DISTRIBUTION

This report has been distributed according to the category "Reactor Technology" as given in the Standard Distribution for Unclassified Scientific and Technical Reports, TID-4500.

CONTENTS

	Page
Abstract	7
I. Introduction	9
II. Description of S8DR	11
A. System Description	11
B. Reactor Description	13
III. Calculational Techniques	21
A. Computer Codes	21
B. Nuclear Cross-Sections	22
C. Normalization of Calculations	22
D. Nuclear Model of the Core	25
IV. Results of Calculations	29
A. Reactivity Requirements	29
1. Fission-Product Buildup and Uranium Burnout	29
2. Hydrogen Redistribution	33
3. Hydrogen Loss	35
4. Temperature Coefficients of Reactivity	39
5. Power Coefficient of Reactivity	47
B. Control Requirements	48
1. Diffusion-Theory Calculations	49
2. Transport-Theory Calculations	50
3. Scaled Drum Worth From S8ER	50
4. Control Worth Scaled From SCA-4A Critical Experiments	52
5. Reflector-Shim Worth	55
6. Desirability of a Nuclear Prepoison	58
C. Excess Reactivity Calculations	59
1. Two-Dimensional Transport-Theory Calculations	59
2. Differencing from S8ER	60
3. Final Prediction of S8DR Excess Reactivity	60
D. Neutron Fluxes and Power Distributions	60
1. Core-Averaged Neutron Fluxes	60
2. Thermal-Flux Spectra	62

CONTENTS

	Page
3. Delayed-Neutron Fraction	62
4. Prompt-Neutron Lifetime	65
5. Median Fission Energy	65
E. Material Coefficients of Reactivity	66
1. Hydrogen Worth	67
2. Uranium Worth	68
3. Fuel-Rod Diameter	68
4. Cladding Material	68
5. Core Vessel	68
6. Beryllium Oxide in Internal Reflectors	69
7. Samarium	69
8. Fuel-Rod Length	69
9. Gap Between the Core Vessel and Reflector	69
10. Additional Cladding-Worth Coefficients	69
V. Performance Summary	73
A. Initial and Short-Term Operating Losses	73
B. Long-Term Operating Losses	76
VI. Conclusions	79
References	81

TABLES

	Page
1. S8DR Parameters	18
2. Energy Breakpoints for 16-Group Library and 26-Group Library	23
3. S8DR Radial Model	26
4. S8DR Axial Model	27
5. Typical 28-Group Geometric Buckling Factors for S8DR	28
6. Linear Fuel-Expansion Coefficient	42
7. S8DR Spectral-Temperature Coefficient	43
8. S8DR Temperature and Power Coefficients	48
9. Predicted S8DR Reactivity Control for 4.50-in. -Radius Drums	53
10. Excess Reactivity of S8DR from One-Dimensional Differencing Calculations	61
11. Final Prediction of S8DR Excess Reactivity	61
12. Comparison of Core-Averaged Fluxes	62
13. Delayed Fraction of the Total Fission Spectrum by Neutron-Energy Group	64
14. β_{eff} as a Function of Drum Position	65
15. S8DR Median Fission Energy	66
16. Predicted and Measured H ₂ Worth for the Center Fuel Element in S8ER	67
17. Material Coefficients of Reactivity for S8DS (S8DR)	70
18. Cladding-Material Worth Coefficients	71
19. Predicted Short-Term Operating Losses for S8DR	74

FIGURES

	Page
1. SNAP 8 Developmental Reactor in Test Vault	12
2. SNAP 8 Developmental Reactor Fuel Element	14
3. Reflector and Control Drums for SNAP 8 Developmental Reactor	16
4. SNAP 8 Developmental Reactor Design	19
5. Xenon Equilibrium Worth vs Power	32
6. Xenon Decay After Operation at 600 kwt for Various Times	32
7. Calculated Hydrogen-Redistribution Worth for S8DR	36
8. Hydrogen-Redistribution Time Constant	36
9. S8DR Fuel-Element Hydrogen-Barrier Performance	38
10. SNAP 8 Experimental Reactor Hydrogen-Worth Profile	40
11. Predicted Reactivity Loss for S8DR at 600 kwt 1300°F Outlet	40
12. Schematic of S8DR External Reflector and Control Drums	54
13. Integral Drum Worth for S8DR	56
14. Differential Drum Worth for S8DR (5.125-in. thick)	56
15. Calculated S8DR Reflector-Shim Worth	57
16. Temperature Variation of SNAP Thermal Spectra	63
17. Predicted Reactivity Losses for the First 60 hr of S8DR Operation	75
18. Predicted Long-Term Reactivity Loss for S8DR at 600 kwt	77
19. Predicted Long-Term Reactivity Loss for S8DR at 1000 kwt	77
20. Predicted Reactivity Losses for Projected S8DR Operation	78

ABSTRACT

SNAP (Systems for Nuclear Auxiliary Power) reactors are intended primarily for use as lightweight reliable heat sources for production of electrical power in outer space. The S8DR (SNAP 8 Developmental Reactor), the second SNAP 8 type to be constructed and tested, has a design goal of 12,000 hr of operation at 600 kwt, with NaK coolant temperatures of 1100°F inlet, 1300°F outlet. The reactor nuclear analyses are described including the determination of reactivity requirements, nuclear control requirements, material nuclear worths, and system excess reactivity. Comparison and normalization of analytical calculations with experimental results are discussed. Based on nuclear considerations, the calculations indicate that the reactor is capable of achieving its design goal with a considerable margin of operational capability.

BLANK

I. INTRODUCTION

The SNAP (Systems for Nuclear Auxiliary Power) reactor program is directed toward the development of lightweight highly reliable nuclear reactors which will serve as heat sources for the production of electrical energy in the environment of outer space. Other potential uses include remote terrestrial and undersea bases, and other applications where it is desirable and/or necessary to provide a highly reliable system which has the capability of operating for long lifetimes ($> 10,000$ hr) without refueling.

The SNAP 8 Developmental Reactor (S8DR) is the second SNAP 8 design to be constructed and tested. The SNAP 8 Experimental Reactor (S8ER) operated for over 10,000 hr at high temperature in an inert atmosphere. Several other SNAP reactor designs also were tested. The SNAP 10A reactors were tested in a vacuum environment; S10FS-3 operated for 10,000 hr in a ground test and S10FS-4 operated in space for 43 days. In addition, the SNAP Experimental Reactor (SER) and the SNAP 2 Developmental Reactor (S2DR) were extensively tested under high temperature in an inert atmosphere, but at lower powers than in S8ER. This broad experience served as the technological base for the development of the S8DR reactor design.

These reactors were fueled with a hydrided-zirconium enriched-uranium alloy and cooled with eutectic sodium-potassium alloy (NaK-78). The reactors were controlled by movable beryllium neutron reflectors which regulate the neutron leakage from the core. The trend of the development work has been toward the production of higher power reactors which will operate at higher coolant-outlet temperatures to provide better power-conversion efficiency. The SNAP 8 family of reactors is designed to operate at powers in excess of 300 kw with average coolant temperatures of 1200°F . By contrast the SNAP 10A family of reactors operated at power levels of less than 50 kw and average coolant temperatures of about 1000°F .

This report describes in detail the methods and results of the nuclear analysis of the S8DR reactor. It is primarily concerned with the reactivity and control requirements, and excess reactivity of the final reactor design. The material worth studies required to perform material selection trade studies are also

included. The calculational techniques employed are discussed, as are comparison of analytical calculations with experimental results from prior reactor testing, and subsequent normalization of the calculational results for the S8DR reactor design.

A significant portion of the nuclear analyses for S8DR was performed based on the reference design for the S8DS (SNAP 8 Development System) reactor. The changes to the S8DS reactor design which culminated in the current reference S8DR reactor design have a negligible effect on the majority of the nuclear calculations. The majority of the design changes were of a "systems" nature, rather than changes in reactor materials or configuration which would affect the nuclear parameters of the system. The differences and their effects on the calculations are described in Section IV-C.

It should be noted that this report does not treat such items as core temperatures, stress analysis, and the prediction of reactor operating lifetime. These and other items relating to the predicted reactor system performance for the long-term endurance testing, have been discussed in other reports.^{(1,2,3)*}

*Superscript numbers in parentheses are for References at back of this report.

II. DESCRIPTION OF S8DR

A. SYSTEM DESCRIPTION

The S8DR reactor design is an extension of the basic SNAP 8 technology developed during the production and testing of the SNAP 8 Experimental Reactor. S8DR represents an improvement of the S8ER design which was evolved to provide the capability for higher power and longer lifetime operation with improved reliability.

The S8ER reactor was designed to operate for ~ 3000 hr at a power level of 300 kwt with coolant-outlet temperature of 1300°F .⁽⁴⁾ It was believed that deterioration of the hydrogen-barrier coating applied to the inside of the fuel-element cladding tubes and growth of the fuel rods due to fuel burnup would limit the endurance lifetime to about 3000 hr. However, S8ER was operated more than 12,000 hr and released a total of 5.1×10^6 kwhr of energy. The reactor operated at or above 400 kwt, 1300°F outlet for 365 days, including operation at a power of 600 kwt with 1300°F coolant-outlet temperature for 100 days. Before final shutdown the reactor operated continuously for 5000 hr at greater than 400 kwt and outlet temperatures above 1200°F .⁽⁵⁾ S8ER compiled this impressive record in spite of the failure (cracking) of fuel-element cladding after approximately 3000-hr operation.⁽⁶⁾

The S8DR reactor is designed for 12,000-hr operation at 600 kwt and 1300°F coolant-outlet temperature. The reactor and associated control components (control-drum actuators, stepper motors, etc.) will be tested in a vacuum test chamber to simulate the vacuum conditions of outer space. The majority of the operation is planned to be in the "hands-off" mode, to simulate the unattended operation which the reactor would experience in an unmanned application in outer space. Reactor control during that period will be provided by the automatic controller which will provide the necessary inputs to the control-drum stepper motors to keep the reactor operating at stable power and temperature. The system will be tested in a typical flight configuration and will include a radiation shield such as might be used in an instrument-rated flight system. Figure 1 shows the S8DR reactor installed in its test vault. The original design operating goal for S8DR was 10,000-hr operation at 600 kwt and 1300°F coolant-outlet temperature.⁽⁸⁾

Figure 1. SNAP 8 Developmental Reactor
in Test Vault

Reactor operation during the entire test will be closely monitored. Reactor power, temperatures, coolant flow, control-drum positions, etc. will be monitored as well as various component temperatures. Provision has been made to monitor the outlet temperature of selected coolant channels within the core. The local flow information thus provided should be particularly useful in determining the effectiveness of the flow shaping and the variation of the radial power profile with operating lifetime. This will allow the hydrogen leakage from the fuel elements to be inferred as a function of core position. The temperature measurements will also be used to assess the adequacy of the thermal models used in the performance predictions. Control-drum positions will be used to determine the reactivity losses as a function of time.

B. REACTOR DESCRIPTION

The S8DR reactor is very similar to the S8ER reactor which was tested for 12,000 hr in an inert atmosphere. However, since the S8ER test was a proof-of-concept test it did not have the flight-type control-drum actuators, radiation shield, and other associated components which will be used on the S8DR. The use of movable beryllium reflector "drums" to achieve reactor control, fuel composition, fuel-element OD, coolant, and other features of the core design were essentially the same for both reactors.

The major differences between the core designs of S8ER and S8DR are that the latter uses longer fuel rods, an improved hydrogen-retention barrier, larger radial and axial gas gaps within the fuel elements, and an improved coolant flow profile within the core. Other minor changes include a slight change in fuel hydrogen concentration, fuel additive content, uranium weight fraction in the fuel, internal reflector design, and details of the fuel-element closure. These changes have been shown to produce a small effect on the nuclear parameters of interest. Thus, much of the experimental data obtained from S8ER operation is directly applicable to S8DR when small scaling changes are applied. The primary purpose for testing S8DR is to provide long-term operating experience at rated conditions, and to verify the design of "flight-rateable" hardware.

The fuel for both reactors is a vacuum-melted extruded uranium-zirconium alloy. The alloy for S8DR is 10.5 wt % U (unhydrided alloy), with the U being 93% enriched in U^{235} . The fuel was hydrided after extrusion and machined to

the final dimensional specifications. The H_2 content of the fuel after hydriding is $1.74 (H/Zr)_{eff}$ which corresponds to a fuel H_2 concentration of 6.07×10^{22} atoms H/cc fuel.

The S8DR fuel-element design, which is very similar to that of the S8ER, is shown in Figure 2. The element has an active fuel length (U-ZrH fuel rod) of 16.825 in., with a fuel-rod OD of 0.529 in. This is compared to an active length of 14.00 in. and OD of 0.532 in. for S8ER. There are several other subtle differences in the design which give better long-term reliability than the S8ER elements.

Figure 2. SNAP 8 Developmental Reactor Fuel Element

S8DR fuel elements have an improved hydrogen-retention barrier over the S8ER's. The SCB-1 hydrogen-retention barrier in the S8DR fuel elements has greater resistance to thermal shock than the AI-8763D barrier in S8ER. Further, the SCB-1 material has better adherence to the cladding material than AI-8763D.

The diametral and axial hydrogen gas gaps within the S8DR fuel element have been increased to allow sufficient room for fuel growth. The data indicate that a significant number of the S8ER fuel rods had grown sufficiently to close the axial hydrogen gas gap after approximately 3000-hr operation. Subsequent fuel-element cladding failure caused substantial increase in the reactivity loss due to hydrogen leakage. To accommodate fuel growth, the axial gas gap was increased to 240 mils in the S8DR fuel elements. This gap provides zero probability of full axial fuel-cladding contact. It also allows space for dilution of the fission-product gases which are released to the gas gap. The diametral gas gap was increased from 3.2 mils (cold) in the S8ER to 7.0 mils (cold) in the S8DR. This increase provides a decreased probability of fuel-element failure caused by diametral fuel growth. Finally, the end caps of the S8DR fuel elements have been changed to decrease the susceptibility of the element to thermal shocks.

The control of S8DR is achieved by regulating the neutron leakage from the core. The leakage is varied by rotation of six control drums. The control drums, shown schematically in Figure 3, are rotatable segments of the external^{*} beryllium reflector. The neutron leakage is at minimum when the control drums are in the full-in position; rotating the control drums to the full-out position causes sufficient additional neutron leakage to make the reactor subcritical.

The excess reactivity of the reactor may be adjusted within the limits specified in Section IV of this report by changing the effective thickness of the reflector. The change in reflector thickness is achieved by "shimming" the basic 2.125-in.-thick control drum. The shims are solid blocks of beryllium 12.17 in. long and 7.5 in. wide, bolted onto the back of the 15.3-in. long control drum. Shim thicknesses of 1.0, 2.0, and 3.0 in. are available, with the current reference design calling for the use of the 3.0-in. shims on all six control drums.

^{*}Outside the core vessel

7568-02178

7 29 69 UNCL

7759 4608

7-19 65

SIDE VIEW

TOP VIEW

Figure 3. Reflector and Control Drums for SNAP 8 Developmental Reactor

The shims are not as long as the base control drum, which is not as long as the 16.825-in. active fuel length. The reflector is centered axially to the active fuel in the core.

Additional neutron reflection is obtained from the stationary beryllium cusps which are placed next to the core vessel between the movable control drums, and to a lesser extent from the remainder of the fixed Be reflector above and below the movable control drums. The fixed reflector reduces the neutron streaming from the core, thereby increasing the nuclear worth of the control drums and the excess reactivity of the core.

Finally, internal reflectors have been placed in the space between the outermost fuel elements and the core vessel wall. The internal reflectors are made of BeO clad in 316 stainless steel. A total of 30 BeO internal reflectors are used, plus 12 smaller filler rods fabricated of 316 stainless steel. The internal reflectors and filler rods increase the excess reactivity of the reactor by decreasing the neutron streaming from the core and increasing the neutron reflection.

The S8DR core utilizes an inlet orifice plate below the lower gridplate to obtain the desired coolant flow profile within the reactor core.⁽⁹⁾ The S8ER core employed a baffle plate to gain the desired flow shaping. Although the plates are different in design and result in different flow profiles, the effect of the difference on the nuclear parameters of the cores is insignificant.

The pertinent parameters of S8DR are shown in Table 1. Figure 4 shows the S8DR core with fuel elements and internal reflectors, the core with the external reflector, and the complete S8DR reactor-shield subsystem.

TABLE 1

SNAP 8 DEVELOPMENTAL REACTOR PARAMETERS

General		Control Drums	
Design Power Level	600 kw	Number of Drums	6
Reactor-outlet temperature	1300°F	Material	Beryllium
Reactor-inlet temperature	1100°F	Length	15.375 in. (total reflector length = 18.5 in.)
Average power density	37 kw/liter of core	Drum Radius of Curvature	4.5 in.
Maximum Power Level	1Mwt	Nominal Thickness	5.125 in.
Reactor-outlet temperature	1100°F	Drive Means	Electromagnetic stepping motor
Reactor-inlet temperature	830°F	Rotation Range	0 to 109°
Design Life	12,000 hr	Full-In Stop	1.0 ± 1.0°
Primary Coolant	NaK	Full-Out Stop	135 ± 2.0°
Secondary Coolant	NaK	Drive-System Backlash	±0.05°
Number of Fuel Elements	211	Scram Power	Torsional spring
Fuel Loading	8.2-kg U enriched to 93.15% U ²³⁵		
Reflector	5.125-in., nominal thickness		
Control	6 rotating Be reflector drums		
Reactor Core		Nuclear Characteristics	
Core Vessel Size*	9 214-in ID by 32.2-in. height to outlet line	Mean Prompt Neutron Lifetime	8.4 μsec
Material	316 stainless steel	Effective Delayed Neutron Fraction	0.0080
Wall thickness	0.091 in.	Median Fission Energy (at room temperature)	0.20 ev
Gridplates		Thermal Flux at 600 kw (<1 ev)	3 × 10 ¹² n/cm ² sec
Coolant passages	420 (0.156-in. diam)	Radial Peak to Average Power	1.29
Spacing of fuel-element positioning holes	0.573 in. (triangular lattice)	Axial Peak to Average Power	1.36
Spacing of coolant holes	0.331 in. (hexagonal lattice)	Clean Wet Excess Reactivity	\$14.40
Upper gridplate		NaK Reactivity Worth	\$0.25
Material	316 stainless steel	Total Isothermal Temperature Coefficient of Reactivity	{ -0.21¢/°F at 70°F -0.23¢/°F at 1200°F
Diameter	9.217 in.	Power Coefficient of Reactivity	-0.03¢/kw
Thickness	0.850 in.	Rise to 600-kw Power and 1200°F Core Average Temperature	-\$3.00
Lower gridplate		Reactivity Inventory (12,000 hr)	
Material	Hastelloy-C	Hot end-of-life excess (600 kw)	\$7.75
Diameter	9.217 in.	Samarium burnout	\$2.50
Thickness	0.65 in.	Fission-product poisoning	
Internal Reflectors		Xe	-\$1.05
Material	30 stainless-steel-clad BeO and 12 solid stainless-steel pieces	Sm	-\$1.09
Cladding thickness	0.030 in.	Other	-\$1.10
Cladding material	316 stainless steel	Axial hydrogen redistribution	-\$0.29
		Hydrogen loss	-\$2.00
		U ²³⁵ burnup	-\$0.62
Fuel Elements		Control-Drum Worth	
Fuel Rods		Total, 6 drums	\$21.06
Composition	Hydrided ZrU alloy	Single drum	\$3.90
Fuel	10.5 wt % U	Maximum differential worth	5.75¢/degree
Enrichment	93.15 wt % U ²³⁵		
Hydrogen concentration	6.07 × 10 ²² atoms/cc		
Diameter	0.529 in.		
Length	16.825 in.		
Axial hydrogen gap	0.240 in.		
Radial hydrogen gap	3.5 mils		
H ₂ diffusion barrier	2-mil ceramic coating on inside of cladding surface		
Burnable Poison	58-mg Sm ₂ O ₃ /element (in ceramic)		
Cladding (Hastelloy-N)	0.540-in. ID, 11.3 mils thick		
Fuel Elements			
Diameter	0.563 in.		
Length	17.325 in. (excluding positioning pins)		
Peak fuel temperature at design power level	1485°F		
Peak cladding temperature at design power level	1367°F		
Average fuel burnup (12,000 hr at 600 kw)	0.22 met. at. %		

*All dimensions are at room temperature conditions unless otherwise specified.

CORE

S8DR REFLECTOR

**S8DR FUEL ELEMENT
ASSEMBLY**

COMPLETE REACTOR

7-7695-023-107

Figure 4. SNAP 8 Development Reactor Design

BLANK

III. CALCULATIONAL TECHNIQUES

A. COMPUTER CODES

The method of calculation is in general broken down into two parts. The first part uses the appropriate computer code to examine the parameter of interest, the second step normalizes the calculation to the available experimental data.

In this study the calculations generally agreed relatively well with the experimental data. The nuclear calculations were made with a variety of multi-group computer codes, because of the relatively long time period (about 6 yr) between the start of serious effort on the S8DS reactor design and its completion under the new designation, S8DR. The nuclear codes used were based on either diffusion theory or transport theory, and included both one-dimensional and two-dimensional geometry approximations.

Although it is generally conceded that diffusion theory is not entirely accurate for calculations performed on small cores such as the SNAP family of reactors, properly normalized diffusion-theory calculations have been quite successful in predicting measured nuclear worths. The one-dimensional diffusion-theory codes used included AIM-FAIM, ULCER, and SIZZLE. The two-dimensional diffusion-theory code CURE was also employed.

The transport-theory codes used for calculations in one space dimension were DTK, DTF, and ANISN. Two-dimensional transport-theory codes which were used were 2DXY, DDK, and DOT.⁽¹⁰⁾ In addition the one-dimensional transport-theory depletion code, PABUC, was used to calculate fuel burnup and fission-product buildup.

Several other special codes were used which did not perform nuclear calculations per se. These codes were used to calculate the magnitude and worth of hydrogen redistribution and hydrogen loss. These codes included HYREP, HYTRAN, and FUSAK⁽¹¹⁾ to calculate the hydrogen redistribution, and LOAFER,⁽¹²⁾ to calculate the hydrogen loss. Small special-purpose codes were used from time to time to calculate such items as xenon-135 and samarium-149 buildup and burnout.

B. NUCLEAR CROSS-SECTIONS

The majority of the multigroup nuclear calculations utilized a 16-energy-group cross-section library based on the group structure and the cross-sections (for energies above 0.4 ev) of Hansen and Roach of Los Alamos.⁽¹³⁾ The energy breakpoints for the 16-group library are shown in Table 2.

In addition to the basic 16-group cross-section library, cross-section libraries were developed, first with 23 groups and later with 26 energy groups. In both of these libraries the top 13 energy groups were the same as in the 16-group library. However, a finer group structure and neutron upscatter were used in the thermal-energy range, and the cross-sections were weighted over a zirconium-hydride spectrum. The zirconium-hydride spectrum used for the cross-section weighting was based on the model in the SUMMIT computer code.⁽¹⁴⁾ A comparison of the 16- and 26-group energy breakpoints is shown in Table 2.

The cross-section library used in any given calculation was determined by the type of calculation to be performed. The majority of the nuclear-worth calculations and excess-reactivity calculations were done with the 16-group library. Calculations of samarium-149 poison worth, xenon-135 worth, determination of median fission energy, and effective one-group cross-sections were made using the 23- and 26-group libraries. Finally, calculations of drum worth in 4 and 6 energy groups were performed for two-dimensional geometry using group reductions of the 16-group library. While the finer energy structure of the 26-group library would in theory provide the best results for all these calculations, considerations of computer size, computer running time, and calculational uncertainty required for a given type of computation indicated that such an approach was not practical. Therefore, the library chosen for a given calculation was the one which would "best do the job", rather than the one that would "do the job best."

C. NORMALIZATION OF CALCULATIONS

Comparison of calculated results with experimental results for the previous SNAP reactor experiments has demonstrated the need for applying a normalization factor to certain types of nuclear calculations. Past experience has shown that material-worth calculations, and other calculations of changes in core

TABLE 2
ENERGY BREAKPOINTS FOR 16-GROUP
LIBRARY AND 26-GROUP LIBRARY

Group Number	Lower Energy Limit (ev)	
	16-Group	26-Group
0	10 $\times 10^6$	10 $\times 10^6$
1	3	3
2	1.4	1.4
3	0.9	0.9
4	0.4	0.4
5	0.1	0.1
6	17.0 $\times 10^3$	17.0 $\times 10^3$
7	3.0	3.0
8	0.55	0.55
9	100 $\times 10^0$	100 $\times 10^0$
10	30	30
11	10	10
12	3	3
13	1	1
14	0.4	0.675
15	0.1	0.55
16	0.025	0.405
17		0.27
18		0.2075
19		0.135
20		0.1055
21		0.0775
22		0.0475
23		0.0240
24		0.0120
25		0.0040
26		0.0000

reactivity, agree well with experimental results. Calculations of the total system excess reactivity, and calculations of the control worth of the void-backed control drums do not agree as well with the experimental values. It has been found, however, that use of the proper normalization factor allows the satisfactory prediction of new reactor designs.

The normalization factors for the S8DR reactor design were derived from comparison of S8ER experimental and calculated results. The majority of the S8ER experimental results are directly applicable to S8DR since the two reactors are very similar. Calculations were made of the difference between the S8ER and S8DR cladding worth, hydrogen worth, xenon buildup, excess reactivity, etc. and these differences were added to the experimentally determined S8ER values. Comparison of these results to the calculated absolute value of the effects allowed determination of the normalization factor.

In addition to the results from S8ER which were used for normalization, results from experiments on the SNAP Critical Assemblies (SCA-4A, SCA-4C, SCA-5) and from S10FS-3 have been used where applicable. In particular, the results of the SCA-4A control-drum experiments were extensively used in preparing the final prediction of S8DR drum worth.

The three primary causes for the difference between the calculated and experimental results are as follows:

- 1) The small core size and consequent large neutron leakage;
- 2) Differences arising from using a one- or two-dimensional model to describe a real three-dimensional reactor; and
- 3) Uncertainties in the multigroup nuclear cross-sections.

The small core size presents a particularly difficult problem for one-dimensional nuclear calculations. In this type calculation it is necessary to calculate the transverse neutron leakage by adding an artificial neutron-absorption term. The magnitude of this term is calculated from a series of radial and axial one-dimensional core calculations (APC code) or from the results of two-dimensional $r - z$ calculations (e.g. DOT). Relatively small errors in the group-dependent absorption terms which are used to approximate the transverse leakage can lead to large errors in the calculated absolute magnitude of the

particular effect being investigated. Even two-dimensional calculations, while providing much better treatment of the leakage problem, do not adequately treat such effects as neutron streaming through void regions and coolant channels. Since two-dimensional calculations are very complex to set up and quite expensive to perform, the majority of calculations are performed in one dimension using the artificial absorption to account for neutron leakage.

Two difficulties arise in constructing a calculational model for a reactor. The first is the problem of ascertaining that the correct physical dimensions of the reactor and the actual materials compositions are used in developing the model. The second is to properly homogenize the materials and obtain correct equivalent dimensions for the calculational model. These problems have been somewhat simplified for SNAP reactors since extensive calculations and measurements have shown that the core may be treated as a homogeneous region to a good approximation. While great care was taken in preparation of the model, there is no standard way to do the job. The professional judgment of the individual who prepared the model will thus influence the final model; more importantly, the cross-comparison of calculations of different cores will be more difficult if the respective models are prepared by different people.

A third problem lies in the uncertainty of the nuclear cross-sections used. While the SNAP reactors have a median fission energy not too far removed from the thermal region (0.2 ev vs 0.025) and are generally considered thermal reactors, the behavior of the fast neutrons in the core and their slowing down is very important because of their effect on neutron leakage from the core. It is thus important to have accurate nuclear cross-sections for the entire energy range from fission to thermal energy. Further, the various cross-section libraries have used somewhat different treatments in the weighting of the cross-sections over the ZrH core spectrum, different energy breakpoints, and, in some cases, different cross-section data. As a result it is necessary to use a base calculation to determine the normalization factor for each cross-section library used.

D. NUCLEAR MODEL OF THE CORE

The radial and axial nuclear models of the S8DR reactor are given in Tables 3 and 4, respectively. It was necessary to use an equivalent core radius

TABLE 3
S8DR RADIAL MODEL

Region Number	Region Description	Region Dimensions, cm (in.)		Region Composition	
		Outer Radius	Thickness	Component Material	Volume Fraction
1	Core/S8DR fuel elements	Variable (11.09 for 211 elements)	(Center of core at 0.0)	Fuel (hydrided U/Zr) Hastelloy-N cladding* Void (fuel-element radial gap) NaK (void in dry core)	0.77404 0.06893 0.03253 0.1245
2	Core/stainless steel dummy rods (Dry critical loading only)	11.0922 (4.367)	Variable	316 stainless steel Void	0.8893 0.1107
3	Internal reflector	11.7348 (4.620)	0.6426 (0.253)	BeO inserts 316 stainless steel cladding and filler rods Void (radial gap) NaK (void in dry core)	0.4992 0.3218 0.0578 0.1212
4	Core vessel and gap	12.1666 (4.790)	0.4318 (0.170)	316 stainless steel vessel Void	0.5351 0.4649
5	Stationary reflector and unshimmed drums	18.27 (7.191)	6.10 (2.401)	Beryllium metal Void	1.0000 0.0000
6	1-in. Shim	20.98 (8.258)	2.71 (1.067)	Beryllium metal Void	0.8977 0.1023
7	1-in. Shim	23.67 (9.317)	2.69 (1.059)	Beryllium metal Void	0.7960 0.2040
8	1-in. Shim	26.35 (10.373)	2.68 (1.056)	Beryllium metal Void	0.7113 0.2887

*Sm₂O₃ loading of 12.06 gm for 211 elements, based on as-fabricated average for 221 S8DR fuel elements; this loading corresponds to 2.52×10^{18} Sm atoms/cc (S8DR core).

TABLE 4
S8DR AXIAL MODEL

Region Number	Region Description	Region Dimensions, cm (in.)		Region Compositions	
		Region Height	Lower Boundary	Component Material	Volume Fraction
1	Upper plenum (including thermocouple bridge and 26 TC's)	7.823 (3.080)	7.823 (3.080)	Stainless steel 316 NaK	0.02 0.98
2	Upper gridplate	2.146 (0.845)	9.969 (3.925)	Stainless steel 316 Hastelloy-N NaK	0.57 0.11 0.32
3	End cap (including axial gap)	1.011 (0.398)	10.980 (4.323)	Hastelloy-N Void (fuel-element axial gap) NaK	0.18 0.40 0.42
4	Core	42.736 (16.825)	53.716 (21.148)	Fuel (hydrided U/Zr) Hastelloy-N cladding* Void (fuel-element radial gap) NaK	0.77404 0.06893 0.03253 0.1245
5	Lower gridplate (plus end cap and baffle plate)	3.012 (1.186)	56.728 (22.334)	316 stainless steel Hastelloy-N Hastelloy-C gridplate NaK	0.25 0.14 0.39 0.22
6	Lower plenum (including flow distributor)	5.740 (2.260)	62.469 (24.594)	316 stainless steel NaK	0.08 0.92
7	Lower vessel head	1.905 (0.750)	64.374 (25.344)	316 stainless steel NaK	0.66 0.34

*Sm₂O₃ loading of 12.06 gm for 211 elements, based on as-fabricated average for 221 S8DR fuel elements; this loading corresponds to 2.52×10^{18} Sm atoms/cc (S8DR core).

rather than the physical reactor vessel ID in order to properly homogenize the hexagonal fuel array of the core for the radial calculational model. As noted in the previous section it was also necessary to correct the radial and axial calculations for the transverse neutron leakage. The data shown in Table 5 give the values of the geometric bucklings used to simulate the transverse leakage in the one-dimensional calculations. The bucklings, B^2 , provide the neutron leakage on a group-dependent basis when multiplied by the diffusion coefficient, D , and the neutron flux, ϕ , for that group. Bucklings for the noncore regions were found to be essentially group-independent, and are also shown in Table 5. The values of B^2 shown in Table 5 were determined from APC buckling iteration calculations of the S8DR reactor.

TABLE 5
TYPICAL 28-GROUP GEOMETRIC BUCKLING FACTORS FOR S8DR

Energy Group	Lower Energy Limit (ev)	Geometric Buckling Factors, B^2			
		Axial		Radial	
		Core	Noncore	Core	Noncore
0	10 $\times 10^6$	—	—	—	—
1	6.5	1.692×10^{-2}	1.403×10^{-2}	2.246×10^{-3}	3.189×10^{-3}
2	4.0	1.871		2.504	
3	2.5	1.961		2.682	
4	1.4	1.919		2.771	
5	0.9	1.954		2.919	
6	0.4	1.342		3.321	
7	0.1	0.952		3.715	
8	17.0 $\times 10^3$	0.463		4.012	
9	3.0	0.664		2.876	
10	0.55	0.662		2.456	
11	100.0 $\times 10^0$	1.128		3.877	
12	30.0	1.031		5.042	
13	10.0	0.264		4.066	
14	3.0	-0.180		4.058	
15	1.0	1.323		4.467	
16	0.675	1.274		5.026	
17	0.55	3.040		6.312	
18	0.405	0.986		6.010	
19	0.270	0.981		7.425	
20	0.207	1.388		8.267	
21	0.135	-1.595		8.713	
22	0.105	0.682		9.243	
23	0.0775	-6.088		10.09	
24	0.0475	-22.40		12.50	
25	0.0240	-55.68		17.22	
26	0.0120	-97.25		23.75	
27	0.0040	-128.5		32.30	
28	0.0010	-102.4		48.74	

IV. RESULTS OF CALCULATIONS

A. REACTIVITY REQUIREMENTS

1. Fission-Product Buildup and Uranium Burnout

The reactivity depletion from these effects is divided into two categories, short-term saturating and long-term nonsaturating effects. The short-term effects are due to Xe^{135} and Sm^{149} . The Sm^{149} effect is complicated by the natural samarium prepoison in the fuel elements. The other samarium isotope, which appears primarily as a fission product, Sm^{151} , is included in the calculation of the buildup of long-term fission products. The natural samarium prepoison material is included in the core to decrease the initial reactivity swing caused by the buildup of the Sm^{149} fission product and the reactivity losses resulting from hydrogen leakage.

The equilibrium fission-product concentration of the Sm^{149} is a constant value for a given reactor, independent of the operating power level. This may be seen by considering the following one-group derivation. The poisoning effect of the material in a reactor may be defined as the ratio of the macroscopic absorption cross-section of the poison material to that of the fuel material as shown in Equation 1.

$$P = \frac{\Sigma_p}{\Sigma_u} \quad \dots(1)$$

The rate of buildup of the samarium may be given by

$$\frac{ds}{dt} = \gamma\phi\Sigma_f - \phi\Sigma_p \quad \dots(2)$$

since the Sm^{149} , with a half life of $\sim 4 \times 10^{14}$ years, is essentially a stable material. Thus the macroscopic absorption cross-section of the Sm^{149} at equilibrium is given by

$$\Sigma_p = \frac{\gamma\phi\Sigma_f}{\phi} = \gamma\Sigma_f \quad \dots(3)$$

and the resulting equilibrium poison worth is

$$P = \gamma \left(\frac{\Sigma_f}{\Sigma_a} \right)_u \quad \dots (4)$$

where Σ_f is the macroscopic fission cross-section of the fuel material and Σ_a is the macroscopic absorption (fission + capture) cross-section of the fuel.

The equilibrium value of the samarium poisoning may be determined by using the appropriate weighted one-group neutron cross-section. The equilibrium Sm^{149} buildup value for S8DR is \$1.09 (where $\beta_{\text{eff}} = 0.008$). However, the rate of Sm^{149} buildup is a function of the neutron flux (power level).

Similarly it may be shown that the equilibrium xenon-135 concentration and the buildup rate are functions of the operating power level. The rate of Xe^{135} buildup is given by

$$\frac{dx}{dt} = \gamma_x \phi \Sigma_f + \lambda_I I - \lambda_x X - \phi X \sigma_x \quad \dots (5)$$

where

γ_x = fission product yield of Xe^{135} ,

ϕ = neutron flux,

λ_I = I^{135} radioactive decay constant,

I = concentration of I^{135} ,

λ_x = radioactive decay constant for Xe^{135} ,

X = concentration of Xe^{135} , and

σ_x = microscopic absorption cross-section of Xe^{135} .

The buildup of iodine-135, the precursor of the Xe^{135} , is

$$\frac{dI}{dt} = \gamma_I \phi \Sigma_f - \lambda_I I \quad ,$$

$$\gamma_I = \text{fission-product yield of } \text{I}^{135} \quad \dots (6)$$

The equilibrium concentration of the xenon and iodine are

$$X = \frac{(\gamma_x + \gamma_I) \phi \Sigma_f}{\lambda + \phi \sigma_x} \quad \dots(7)$$

and

$$I = \frac{\gamma_I \phi \Sigma_f}{\lambda_I} \quad \dots(8)$$

Since the I^{135} has an absorption cross-section of zero it does not act as a poison material. The poison worth of the xenon is thus given by

$$P = \frac{X \sigma_x}{\Sigma_u} \quad , \quad \dots(9)$$

which becomes

$$P = \frac{(\gamma_x + \gamma_I) \phi \sigma_x}{\gamma + \phi \sigma_x} \left(\frac{\Sigma_f}{\Sigma_a} \right)_u \quad \dots(10)$$

In actual practice both the Sm^{149} and Xe^{135} equilibrium poison concentrations were calculated using multigroup computer codes. The change of concentration as a function of time may be predicted quite well by using the one-group models. The equilibrium Xe^{135} concentration for S8DR operating at 600 kw is \$1.05.

The equilibrium concentration of Xe^{135} in S8DR is shown in Figure 5 as a function of operating power level. The decay of the Xe^{135} is shown in Figure 6 as a function of time for various lengths of operation at the reference power of 600 kw.

The rate of reactivity losses in S8DR as a result of the long-term fission-product buildup and fuel burnout has been calculated as a function of reactor operating lifetime. The calculations were performed with the PABUC computer code.

PABUC is a versatile one-dimensional burnup code which allows the calculation of changing neutron flux and effective nuclear cross-sections as a function of operating time. PABUC provides a two-part calculation, composed of a

7-16-69 UNCL

7759-4601

Figure 5. Xenon Equilibrium Worth vs Power

7-17-69 UNCL

7759-4602

Figure 6. Xenon Decay After Operation at 600 kw for Various Times

multigroup diffusion or transport-theory nuclear calculation followed by a one-group calculation of fuel burnout and fission-product buildup. The results of the nuclear calculation based on the ANISN computer code, are used to weight the cross-sections according to the calculated neutron fluxes. These one-group cross-sections are then used to determine the burnout of the U for a series of discrete time steps. Following this burnout calculation a new ANISN calculation is made to determine the flux levels which have resulted from new material concentrations caused by the burnout of the U and the buildup of the fission products. These steps are then repeated until the desired operating time has been calculated. The calculations for S8DR used the 16-energy-group cross-section library for the ANISN calculations, with the S_4 transport-theory approximation.

The analysis indicated that the rotation of the control drums inward during the operating lifetime of S8DR had the effect of decreasing the nuclear worth of the fission products and the fuel burnup. The decrease resulted from the flattening of the radial power profile. It was also found that the worth of the fission products and the fuel burnout increased with time for constant drum position. The fuel was depleted and the fission products accumulated preferentially in the high-flux high-worth region of the core under these conditions.

The two effects are calculated to offset each other in S8DR. Consequently a single value is applicable for the reactivity-loss coefficient. For core operation from startup through 20 months (at 600 kw) the reactivity-loss coefficient for fission-product buildup and fuel burnout is $-0.0175 \pm 0.0002\text{¢/kw-mo.}$ The total reactivity loss due to fission-product buildup and fuel burnout at a power level of 600 kw for 12,000 hr is thus calculated to be \$1.72.

2. Hydrogen Redistribution

The hydrogen moderator in the ZrH fuel material redistributes itself under the operating temperature gradient so that a uniform pressure exists in the fuel-element gas gap. This redistribution of the hydrogen causes a reactivity loss as the hydrogen migrates axially, moving from the high-temperature high-flux region of the core to the lower temperature ends of the fuel rods. The effect of the hydrogen redistribution is almost entirely an axial geometry effect. The radial hydrogen redistribution within each fuel rod has an insignificant effect on the reactivity.

The worth of the hydrogen redistribution was initially calculated using the HYREP-GASLIK and DTF computer programs. The HYREP-GASLIK program was used to determine the axial hydrogen concentration gradients for the calculated 600 kwt temperature distribution in the fuel rod. It was assumed that the final hydrogen redistribution must be such that an equilibrium hydrogen pressure existed in the fuel-element gas gap. Using the results of the HYREP-GASLIK program, the hydrogen concentration values were used as input in an axial DTF calculation of the reactivity worth of the redistribution effect. The worth was determined by comparing the calculated eigenvalue for the case with the redistributed hydrogen to the case with axially uniform hydrogen in the core.

The technique had been used to calculate the hydrogen redistribution for the S8ER reactor. The results obtained agreed quite well with the experimental results, to an accuracy with which the hydrogen redistribution effect could be determined. For example, the experimentally determined value of hydrogen redistribution in S8ER at operating conditions of 700°F inlet, 200°F ΔT , and 450 kwt was -35 to -40¢. This compared to a calculated value using the previously described techniques of -36.5¢. It must be noted, however, that the method of measuring the hydrogen redistribution effect included some uncertainties which were introduced because of changes in operating reactor conditions which were required in order to isolate the redistribution effect.

One of the significant changes which was made in the design of the S8DS reactor when it was redesignated the S8DR reactor was the change in the coolant profile in the core. This change was necessitated by re-evaluation of the reactivity lifetime data which indicated that a changed coolant profile in the core could result in increased reactor lifetime.⁽¹⁵⁾ The coolant profile was flattened considerably from that which had been used in the S8ER reactor and from that which had been proposed for the S8DS reactor design.

The resulting coolant profile for S8DR is relatively flat in the radial direction and has a much smaller variation in the axial direction along the fuel elements than the previously specified profile.⁽¹⁶⁾ This change in the coolant profile has had a marked effect on the calculated hydrogen redistribution worth for the S8DR core. The worth value which had been calculated for the S8DS reactor was -55¢ at 600 kwt, 1100°F inlet, and 200°F ΔT . As a consequence of using the new coolant profile, the hydrogen redistribution worth decreased significantly.

APC-II calculations were made to provide consistent bucklings for the radial and axial one-dimensional transport-theory calculations used to calculate the redistribution worth. The temperature profiles along the fuel rods obtained from the UA computer code calculations were used as input to the FUSAK code, which in turn was used to calculate the hydrogen distribution within the S8DR fuel elements. This distribution was used as input to the ten-axial-node core model used in the APC-II calculations. The resulting calculations of the hydrogen redistribution worth yield a value of -29¢ for the S8DR reactor operating at 600 kwt, 1100°F inlet, and 200°F ΔT . When the reactor is operated at 1000 kwt, 830°F inlet, and 270°F ΔT it is -52¢.

Since several previous studies had shown that the effect of ΔT on hydrogen redistribution worth is a minor effect, the results of previous S8DS worth calculations have been rescaled to the current results and are shown in Figure 7 to give an indication of the reactivity effect as a function of power level and inlet temperature.

It is important to note that the rate at which the hydrogen redistribution occurs is a function of the fuel temperature. The experimentally inferred hydrogen redistribution time constant is shown in Figure 8 as a function of fuel temperature. It has a value of approximately 10 hr for S8DR operating conditions.

3. Hydrogen Loss

The loss of the hydrogen moderator from the fuel-moderator elements represents one of the major reactivity-loss mechanisms during long-term operation at rated conditions. While extensive out-of-pile tests have been made to characterize the hydrogen-retention properties of the SCB hydrogen-barrier material used in S8DR, its exact performance under the long-term irradiation environment of the operating reactor is not precisely known. The predictions of hydrogen loss were made on the basis of available out-of-pile test data plus some very limited data on the in-pile degradation of a similar barrier material.⁽¹⁷⁾ (Details of the hydrogen-loss calculation are discussed in Reference 1.)

The hydrogen-loss calculation is complicated by the necessity of using two hydrogen-loss models. The first predicts the gross reactivity loss associated with hydrogen leakage from the core. The second predicts fuel-element phase change (formation of β -phase fuel) in a small fraction of the core. This second

Figure 7. Calculated Hydrogen — Redistribution Worth for S8DR

Figure 8. Hydrogen-Redistribution Time Constant

model is based on the projected hydrogen-loss characteristics of a very few elements in the core whereas the first is based on the performance of the average element in the core.

The hydrogen-loss models have been based on the isothermal out-of-core testing of S8DR fuel elements. Since the reactivity losses associated with the hydrogen loss are of major consequence the gross-reactivity loss model is continually updated. Initial tests of seven developmental S8DR fuel elements indicated that the hydrogen leakage increased as a function of operating time and thermal inputs. Subsequent development work has resulted in the production of greatly improved fuel elements. The improved fuel elements, similar to those produced for use in the S8DR reactor, have undergone long endurance testing which indicates much better hydrogen-retention properties than the previous developmental elements.⁽¹⁸⁾ These tests also indicate that the current S8DR production fuel elements are much less susceptible to thermal shock than earlier elements.

Elements which are characteristic of the S8DR production fuel elements have currently undergone more than 10,000 hr of long-term endurance testing. These test results indicate that the degradation of the hydrogen barrier as a function of operating time is very small. These data were also used to analyze the possibility of fuel phase change. An analysis of the data was used to determine the uncertainty of the mean barrier performance as a function of time. It was thus possible to predict the probability of fuel phase change based on extrapolation of the mean data and its associated uncertainty.

Additional fuel elements have been put into the long-term endurance testing during the regular production process of the S8DR fuel elements. While the accumulated endurance data for these elements are currently of the order of 8000 hr and less, the data are not inconsistent with those previously obtained. Figure 9 shows the accumulated data and projection of the mean hydrogen loss as well as the phase-change hydrogen-loss model. The data in Figure 9 do not show the actual hydrogen loss, but rather a normalized hydrogen-barrier parameter which indicates the quality of the barrier. An increase in the barrier parameter, K_D , indicates an increase in hydrogen loss rate at conditions of constant temperature and internal hydrogen pressure. This parameter is then used to calculate

8-19-69 UNCL

7759-40200A

Figure 9. S8DR Fuel-Element Hydrogen-Barrier Performance

the hydrogen leakage as a function of time, taking into account the variation in the internal hydrogen pressure and the change in fuel temperature.

It is then necessary to convert the absolute magnitude of the hydrogen loss into a reactivity-loss effect, since this is the change in reactivity due to hydrogen loss inferred from experimental operation of the S8DR. The reactivity worth as a function of core radial positions of the hydrogen in the core was measured experimentally on the S8ER. Using this worth profile, shown in Figure 10, and an average hydrogen worth for the core which was calculated using the DTF transport-theory code, the integrated hydrogen loss from the core was calculated as a function of operating time.

The details of these hydrogen-loss calculations have been discussed in a previous report.⁽¹⁾ The total calculated reactivity loss as a function of time and the magnitude of the hydrogen-loss component of the reactivity loss are shown in Figure 11. These calculations used the latest hydrogen-loss model as shown in Figure 9.

4. Temperature Coefficients of Reactivity

The temperature coefficients of reactivity are required, to predict the kinetic behavior of the reactor and the reactivity loss in going to rated operating conditions. While a discussion of the kinetic response is beyond the scope of this report, a discussion of the individual components of the temperature coefficients will provide the information required for such a study. The overall isothermal temperature coefficient is the quantity which will be determined experimentally and is of prime interest in determining the reactivity defect. The sum of the individual temperature coefficients is used to predict the total isothermal coefficient. The use of the individual coefficients for prediction of the reactor kinetic response is discussed in Reference 19.

The total isothermal temperature coefficient may be divided into two parts, prompt and delayed. The prompt coefficient includes the fuel and effective plenum coefficients. The delayed coefficient is due to the relatively slower heating of the beryllium reflector. Whereas the effect of the prompt is essentially instantaneous, the delayed has a time constant of approximately 1 hr and is a function of the absolute temperature of the reflector. The individual parts of the total isothermal temperature coefficient are discussed below.

8 19 69 UNCL

7759 4606

Figure 10. SNAP 8 Experimental Reactor Hydrogen-Worth Profile

8 22 69 UNCL

7759 4607

Figure 11. Predicted Reactivity Loss for S8DR at 600 kw 1300°F Outlet

The ZrH-fuel-temperature coefficient is composed of components caused by (a) fuel expansion, (b) neutron spectrum changes, and (c) Doppler broadening of the zirconium and uranium-238 resonance absorption cross-sections. The sum of these effects gives the total coefficient. The fuel-temperature coefficient provides the most rapid negative reactivity feedback of all the coefficient parts. The time constant for the fuel coefficient is 8 sec at operating temperature.⁽¹⁹⁾

The expansion component of the fuel-temperature coefficient is a result of the expansion of the heated fuel which effectively decreases the fuel density in the core. The decrease in fuel density causes a decrease in the neutron multiplication of the core. A partially compensating effect arises because the increase in core size (decrease in core density) causes a decrease in the neutron leakage. The magnitude of these two effects was determined from the results of two series of radial FAIM one-dimensional diffusion-theory calculations for the S8DS reactor. A series of calculations was performed to determine the change in the neutron multiplication with changes in the effective core fuel density, while maintaining the original radial dimensions of the core. This corresponds to the axial expansion of the fuel material. A second series of calculations was then made in which the change in neutron multiplications was evaluated as a function of decreasing transverse neutron leakage, i. e. decreasing DB^2 with increased core size, again maintaining constant radial dimensions.

Since both of these effects were due to the axial expansion of the fuel, it was possible to express each effect as a change in neutron multiplication per unit change in the axial core dimensions. The change in the axial dimension could, in turn, be equated to the temperature change times the linear-expansion coefficient for the fuel. Assuming separability of the expansion and leakage effect, the two were combined algebraically to give the change in multiplication per unit change in fuel temperature as a function of the linear-expansion coefficient of the fuel material. The magnitude of the fuel-expansion effect was about a factor of three larger than the transverse-leakage effect, and of opposite sign for a given change in temperature.

The combined fuel-expansion coefficient, expressed in units of cents reactivity per °F* is given in Equation 11. The linear fuel-expansion coefficient,⁽²⁰⁾ α_E , converted to units/°F, is given in Equation 12.

$$\frac{\Delta \rho}{\Delta T} = -4.9 \times 10^3 \alpha_E, \text{ ¢/°F} \quad \dots(11)$$

where

$$\alpha_E = 1.99 \times 10^{-6} + 1.09 \times 10^{-8} T - 0.60 \times 10^{-11} T^2, \text{ with} \quad \dots(12)$$

T = fuel temperature, °F.

The fuel-expansion coefficient was evaluated at room temperature, at an average core temperature of 1200°F, and averaged over the temperature range from room temperature to 1200°F. Table 6 shows the fuel-expansion coefficient for these three conditions.

TABLE 6
LINEAR FUEL-EXPANSION
TEMPERATURE COEFFICIENT

Temperature (°F)	α_F (¢/°F)
78	-0.014
1200	-0.031
78 to 1200	-0.027

The effect of radial expansion of the fuel within the fuel elements was found to be insignificant if the gridplates maintain the fuel elements at their initial locations. Although each element would expand around its axis, the net effect on the effective core radius would be negligible; so the calculated reactivity effect for the homogenized core would be nil. Similarly, the effect of the axial expansion of the cladding was examined and found to be negligible.

$$*\Delta \rho(\text{¢}) = \Delta K / K_1 K_2 \beta .$$

K is the effective neutron multiplication, and β is the effective delayed neutron fraction.

The fuel spectral temperature coefficient⁽²¹⁾ arises because increasing the core temperature increases the energy of the neutrons in thermal equilibrium with the system, making the fission process less probable. This is a result of the decrease in the fission-to-absorption cross-section ratio with increasing neutron energy, i.e. as the neutron spectrum is hardened.

The fuel spectral-temperature coefficient of reactivity has been theoretically determined for S8DR as a function of samarium concentration. The calculations were made using the ANISN transport-theory computer code with a 26-energy-group cross-section library. The values of k_{eff} were calculated at temperatures of 73° and 1293°F, and these were used to calculate the average spectral-temperature coefficient for that temperature range. These values are shown in Table 7 as a function of Sm^{149} loading. They indicate that the spectral-temperature coefficient is a linear function of the Sm loading over the range of Sm concentrations investigated.

The spectral-coefficient values shown in Table 7 are averaged over the temperature range from 73° to 1293°F. Previous calculations of the spectral component of the fuel coefficient for SNAPTRAN fuel⁽²²⁾ have shown that it decreases from about -0.04 $\text{¢}/^\circ\text{F}$ at ambient temperature to about -0.08 $\text{¢}/^\circ\text{F}$ at 1200°F for a cold Sm^{149} loading of approximately \$1.50.

TABLE 7
S8DR SPECTRAL-TEMPERATURE COEFFICIENT
73° to 1293°F

<u>Sm^{149} Loading (cold, \$)</u>	<u>Spectral-Temperature Coefficient ($\text{¢}/^\circ\text{F}$)</u>
0.00	-0.078
1.09	-0.063
2.60	-0.043
3.00 (S8DR design point)	-0.037

The third component of the fuel-temperature coefficient is caused by Doppler broadening of the resonance absorption cross-sections of zirconium and uranium-238. Analysis of the SNAPTRAN experiments showed this effect to be an important component of the fuel-temperature coefficient.⁽²²⁾ The effect, which is a characteristic of a particular fuel composition, is essentially the same for all the U-ZrH-fueled SNAP cores, and thus was not recalculated for S8DR. The average magnitude of the Doppler coefficient over the temperature range from 78° to 1300°F is $-0.03\text{¢}/^{\circ}\text{F}$ with the value varying from $-0.04\text{¢}/^{\circ}\text{F}$ at 78° to $-0.02\text{¢}/^{\circ}\text{F}$ at 1300°F.

The effective plenum coefficients, sometimes called effective gridplate coefficients, are also large contributors to the prompt isothermal temperature coefficient. These coefficients arise because of the radial expansion of the gridplates and reflector as the core is heated. The expansion of the gridplates effectively causes the fuel to become less dense, while the vessel expansion simultaneously is pushing the reflector farther from the core center. Both effects will cause a decrease in reactivity. The prompt reflector effect caused by the vessel expansion has been included with the gridplate coefficient because its effect is closely tied to the coolant temperature, rather than to the relatively slow heating of the beryllium reflector.

The reactivity effect of the gridplate expansion was calculated by assuming that both gridplates would expand at the same rate and for the same distance so that the geometry would remain simple. The reactivity effect was calculated using FAIM, assuming the only effect was a decrease in fuel density caused by the radial expansion of the core. As in the case of axial fuel expansion, the reactivity change is proportional to the fractional change in the fuel density.

The original reflector location was used in the calculation of the gridplate expansion effect. Consequently, a partially compensating reactivity effect occurs because the radial expansion of the core moves it closer to the reflector, thereby increasing the reflector worth.

Assuming these reactivity effects could be attributed equally to the upper and lower gridplates, the effect at each gridplate due to the fuel-density decrease expressed in terms of the linear-expansion coefficient of the gridplate is

$$\left(\frac{\Delta\rho}{\Delta T}\right)_{\text{gp}} = -77.5\alpha_{\text{E}_g}, \quad \dots(13)$$

and due to the movement of the fuel closer to the reflector is

$$\left(\frac{\Delta\rho}{\Delta T}\right)_{\text{refl}} = +52.5\alpha_{E_g} \quad \dots(14)$$

Thus, the combined effect results in the gridplate expansion coefficient,

$$\frac{\Delta\rho}{\Delta T} = -25\alpha_{E_g} \quad \dots(15)$$

The gridplate expansion coefficient is different for the upper and lower gridplates, however, because of the different materials used. The upper is made of 316 stainless steel, the lower of Hastelloy-C. The coefficient of linear expansion for the upper is almost constant and equal to $1.05 \times 10^{-5}/^{\circ}\text{F}$. The lower has a variable coefficient of linear expansion. It varies from a value of $6.0 \times 10^{-6}/^{\circ}\text{F}$ at approximately 100°F to a value of $7.5 \times 10^{-6}/^{\circ}\text{F}$ at temperatures of approximately 1000°F . Thus the lower gridplate coefficient is a variable depending on the operating temperature. The temperature coefficients thus become

$$\alpha_{\text{ugp}} = -0.026\epsilon/^{\circ}\text{F} \quad \dots(16)$$

for the upper gridplate, and

$$\alpha_{\text{lgp}} = -0.015\epsilon/^{\circ}\text{F} \text{ at } 100^{\circ}\text{F} \quad , \quad \dots(17)$$

$$\alpha_{\text{lgp}} = -0.019\epsilon/^{\circ}\text{F} \text{ at } 1000^{\circ}\text{F} \quad \dots(18)$$

for the lower.

Since the reflector is in intimate contact with the reactor vessel, the expansion of the core vessel causes the reflector to move farther away from the active fuel. This prompt reflector movement, which is not related to the heating of the reflector itself, is directly related to the core-vessel temperature. The prompt reflector effect is difficult to treat analytically because of the importance of neutron streaming effects. Neutron streaming is increased as the gap between the core vessel and the reflector increases. Consequently, both analytical techniques and a prediction based on experimental results from the SCA-4A critical experiments were used.

The SCA-4A provided a direct measurement of the nuclear worth of opening the radial gap between the core and reflector.⁽²³⁾ The SCA-4A reflector assembly had nearly the same nuclear worth as an S8DR reflector of the same thickness. In addition, the core vessel size was essentially the same for the two cores. Consequently, the experimental value of -1.5 ¢/mil from the SCA-4A experiments should be directly applicable to S8DR. Using the experimental gap worth value and the expansion coefficient of the vessel, the calculated effect of the prompt reflector displacement is -0.08 ¢/°F for the entire reflector. Since the reflector is mounted in such a fashion as to result in nearly equal effects at both the upper and lower ends of the reflector, the value of -0.08 ¢/°F can be equally divided between the upper and lower reactor plenums.

The effective plenum coefficient is thus obtained when the prompt reflector effect is added to the previously quoted gridplate expansion effect. The plenum coefficient for the upper end of the core is

$$\alpha_{\text{up}} = -0.066 \text{ ¢/°F} \quad \dots(19)$$

and for the lower plenum the coefficient is

$$\alpha_{\text{lp}} = -0.055 \text{ ¢/°F at } 100^\circ\text{F, and} \quad \dots(20)$$

$$\alpha_{\text{lp}} = -0.059 \text{ ¢/°F at } 1000^\circ\text{F} \quad \dots(21)$$

In addition to the prompt reflector displacement effect due to core vessel heating, a delayed reflector heating effect must also be included in the prediction of the total isothermal temperature defect. The delayed effect results from the time lag in the heating of the reflector as the coolant temperature is increased. Due to the poor thermal coupling between the core and reflector, and the large mass of the reflector, the time constant for heating of the reflector as the core is heated is significant. Initial evaluation of the reflector heating-time constant from the non-nuclear testing of the S8DR core indicates a time constant of approximately 1 hr. The magnitude of the reactivity effect is difficult to calculate because of competing effects. As the reflector is heated, the Be expands moving

the outer radius of the reflector farther from the fuel. Consequently, the Be density is decreased. The decrease in density is partially offset by the decrease in neutron leakage caused by the larger radius. These effects have been calculated to produce a combined reactivity defect of

$$\alpha_{dr} = -0.03\text{¢}/^{\circ}\text{F} \quad \dots(22)$$

However, the uncertainty associated with this calculation is estimated to be $\pm 0.02\text{¢}/^{\circ}\text{F}$.

The potential reactivity effect of fuel-rod bowing for S8DR was investigated and found to be negligible.⁽²⁴⁾ It was estimated that the maximum reactivity insertion which could occur due to fuel-rod bowing was $+6\text{¢}$ for a rapid transient, and that the maximum magnitude effect under steady-state operating conditions would be -4¢ . Since these small values represent the calculated extremes of the reactivity effect of fuel bowing, it was not considered further.

5. Power Coefficient of Reactivity

The discussion thus far has centered on the isothermal coefficients. After isothermal conditions have been established and it is desired to bring the reactor to its operating power level, an additional reactivity defect occurs. This is caused by the change in the temperature conditions as the reactor is brought to its operating power. An expression for the power coefficient is given in Equation 23.

$$\alpha_p = \left[\frac{1}{2} \frac{(\Delta T_i + \Delta T_o)}{p} + \frac{1}{UA} \right] \alpha_f + \frac{\Delta T_i}{p} \alpha_{lp} + \frac{\Delta T_o}{p} \alpha_{up} + \frac{\Delta T_{refl}}{p} \alpha_{dr} \quad \dots(23)$$

If it is assumed that the reactor core average temperature is established and then the reactor is brought to its operating power level by allowing the inlet temperature to decrease and the outlet temperature to increase while maintaining the core average temperature, the power coefficient for the S8DR reactor is

$$\alpha_p = -0.03 \text{ ¢/kwt} \quad \dots(24)$$

If, however, it is assumed that the core inlet-temperature is the temperature which is maintained constant in bringing the reactor to full-power operating conditions, the power coefficient becomes

$$\alpha_p = -0.065 \text{ } \$/\text{kwt} \quad \dots(25)$$

It should be noted, however, that the total reactivity defect will be the same for both of these cases.

The temperature and power coefficients along with their estimated tolerance limits (3σ) are shown in Table 8.

TABLE 8
S8DR TEMPERATURE AND POWER COEFFICIENTS

Fuel Temperature Coefficient, $\$/^\circ\text{F}$	$-0.094 \pm 0.03\$/^\circ\text{F}$
Fuel-expansion component	-0.027
Spectral component	-0.037
Doppler broadening component	-0.030
Upper Plenum Temperature Coefficient, $\$/^\circ\text{F}$	-0.066 ± 0.02
Lower Plenum Temperature Coefficient, $\$/^\circ\text{F}$	-0.057 ± 0.02
Total Isothermal Temperature Coefficient, $\$/^\circ\text{F}$	$-0.217 \pm 0.04\$/^\circ\text{F}$
Power Coefficient*, $\$/\text{kwt}$	-0.03 ± 0.01

*Assuming mean coolant temperature remains unchanged

B. CONTROL REQUIREMENTS

The initial design requirements used in the specification of the S8DS control drums called for a nominal value of 2.4% $\Delta k/k$ (\$3.00) per drum (neighboring drums full-in) in order to maintain adequate shutdown margin. Control worth of that magnitude allowed reactor shutdown even in the event that one of the control drums stuck in its most reactive position, i. e. full-in.

Calculation of the control-drum worth is one of the more difficult calculations which must be performed in the prediction of the operating characteristics of the SNAP reactors. The difficulty is primarily a result of the large neutron

leakage from the core and is complicated by the neutron streaming effects which occur when the control drums are rotated to the drums-out position. A number of techniques have been used in an attempt to accurately calculate the worth of control drums. The following discussion describes four techniques which were used in the analysis of the S8DR control-drum worth. The first three methods were used in the early analysis of the S8DS control-drum worth and resulted in the requirement of a 4.50-in.-radius control drum for use on the S8DS reactor design. The final method of analysis was performed at a later time and made use of extensive parametric control-drum measurements which had been made on the SCA-4A critical assembly.⁽²³⁾ The SCA-4A critical experiment data were used to prepare the final prediction of the S8DR control-drum worth.

The tentative S8DS control drums had a 4.00-in. radius and were of the S8DRM-1 design. Three different methods were used to calculate their worth: (1) the CURE two-dimensional diffusion-theory program; (2) the 2DXY two-dimensional transport-theory program; and (3) a scaling technique involving the use of experimental S8ER data on reflector worth.

1. Diffusion-Theory Calculations

The CURE diffusion-theory studies of S8DS control-drum worth utilized the R- θ geometry option of the code and three neutron-energy groups. Identical techniques were used to calculate the control worths of the S8DS and S8ER control drums. This allowed a direct comparison to be made between the calculated worths of the two types of drums, and a comparison with the experimentally measured S8ER control-drum worth. The CURE calculations were made using the 4.00-in.-radius drums for S8DS which had been chosen as the reference design at that time.

The calculated result for the S8ER control drum was 2.45% $\Delta k/k$ (\$3.06), and the experimentally measured value was 2.6 % $\Delta k/k$ (\$3.25).^{*} The difference was used as the correction factor in determining the worth of the S8DS control drums from the CURE calculations. The worth of the S8DS 4.00-in. control drum was calculated using the same cross-sections and similar mesh spacing

^{*}Drum worth with the neighboring drums full-in.

as in the CURE calculation of the S8ER drum worth. The S8DS drum worth, after adjusting for the difference between the measured and calculated S8ER drum worths, was 2.87% $\Delta k/k$ (\$3.60) for the 4.00-in.-radius control drum.

The control worth of six control drums is less than six times the worth of a single control drum with neighbors full-in due to the neutron scattering between drums in the full-out position. This interaction effect was estimated by calculations of the simultaneous rotation of all six drums from full-in to full-out. The difference between the six times the control worth of a single drum with neighbors in and the control worth for the simultaneous rotation of all six drums gives the calculated drum interaction effect. The calculated total interaction effect for the six drums was 1.3% $\Delta k/k$ (\$1.63). This was in fair agreement with later experiments on the interaction effect performed on the SCA-4A assembly.

2. Transport-Theory Calculations

The 2DXY program was used with Cartesian geometry for the transport-theory studies of control-drum worth. The QUICKIE program was used to reduce the 23-group set of neutron cross-sections to four neutron-energy groups. Due to symmetry requirements of the program, the actual calculations involved the rotation of two control drums. The calculated S8ER drum worth was 2.7% $\Delta k/k$ (\$3.38) compared to a measured worth of 2.6% $\Delta k/k$ (\$3.25). A similar calculation for the 4.00-in.-radius S8DS control drum, when corrected for the difference between the measured and calculated values for the S8ER drum worth, gave 2.95% $\Delta k/k$ (\$3.80).

3. Scaled Drum Worth from S8ER

The third method utilized a scaling technique which made use of the measured S8ER reflector worth as a function of reflector thickness. This curve was extrapolated to cover the entire range occupied by portions of the drum from the full-in to the full-out positions. It was then redrawn to show the rate of change of reactivity as a function of drum radius. The curve of $\Delta k/k$ (reactivity) was then translated to a Be worth per square centimeter as a function of drum radius. Full-scale drawings of the control drums were made and grids laid out on the drawings to determine the area of the control drum at each radius. The removal of the control drum resulted in less reflector material being located near the

core, which decreased the system reactivity. However, it also resulted in the addition of a smaller amount of reactivity as the reflector material was rotated into a position of lower worth. The summation of effects was used to determine the net change in the reactivity as the control drum was rotated from the full-in to the full-out position.

Similar grids were laid out for both the S8ER and the S8DS drum configurations. Calculations were made for the S8ER configuration and the unnormalized results were then compared to the measured S8ER drum worth. This provided a normalization factor, which, when applied to the results obtained for the S8DS control drum worth, resulted in a worth for the 4.00-in.-radius S8DS control drum of 2.06% $\Delta k/k$ (\$2.58).

The resulting calculated worth was much less than the 2.4% $\Delta k/k$ per drum, which was the design requirement to insure an adequate shutdown margin. Scaling studies were then made of 4.25-, 4.40-, and 4.50-in.-radius control drums to determine a control-drum size which would assure the required drum worth.

While it was recognized some potential sources of error were included in the calculation, the values which were scaled from the S8ER reflector-worth measurements were believed to be the most valid of the three techniques used. Calculations of the S8ER drum worth with three shim configurations indicated that the scaled drum worths for all three configurations were within about 5% of the measured worth. This tended to give additional credence to the scaled S8DS drum worth.

The two possible sources of error in the scaling of the S8ER drum worth were the extrapolation of the S8ER reflector worth to a radius which corresponded to the full-out position of the S8DS control drums, and the manner in which the grid was drawn on the diagrams of the control-drum positions. A second calculation of the S8DS control-drum worth was made in which both the extrapolation and the method of drawing the grid were done in such a fashion as to provide the maximum increase in the calculated drum worth. The resulting recalculation gave rise to an increase of about 7% in drum worth, thus indicating what was believed to be an upper limit due to such errors.

In spite of the agreement between the CURE and the 2DXY two-dimensional calculations of the drum worth, the lower value of 2.06 % $\Delta k/k$ for the S8DS drum

worth from the scaled results was believed to be the more accurate calculation. Based on the additional scaled-worth studies for other control-drum radii for S8DS, a 4.50-in.-radius drum was chosen as the reference design for the S8DS reactor.

This choice was also influenced by the possible consequences of calculational errors. If the larger drum were chosen, some decrease in the structural strength of the stationary reflector would result. However, if the smaller drum were chosen, the reflector might have insufficient control capability. The calculations indicated that the stationary reflectors would be sufficiently strong even with the 4.50-in.-radius control drums. The decision was made, therefore, to proceed with the larger-radius drums to assure sufficient control worth. These calculations were performed for a 3.25-in.-thick control drum for each of the S8DS control-drum radii.

4. Control Worth Scaled From SCA-4A Critical Experiments

Following the analysis of the control-drum worth discussed above, a series of critical experiments was performed using the SCA-4A critical assembly to parametrically determine control-drum worth as a function of drum thickness and drum radius. Care was taken in these experiments to insure that the reflectors being measured would be a reasonable approximation of practical designs for SNAP reactor systems. As a result the parameter study appears to be universal for SNAP void-backed control drums. It was necessary to make small scaling changes to account for the difference in control-drum length between S8DR and the drums calibrated on SCA-4A, and to account for the difference in core sizes and compositions. The scaling factors were derived from both experimental data and analytical calculations.

It was assumed that for control drums of the same thickness and radius a full-length control drum on the SCA-4A would provide control equal to the same fraction of the total reflector worth as similar drums on the S8ER and S8DR. A scaling factor equal to the ratio of the reflector worths was then used to account for the differences in the core sizes and compositions. Control-drum calibrations which were performed on the S8ER reactor were used to account for the differences between the S8ER and the SCA-4A cores. Finally, calculations of S8ER and S8DR reflector worths using DTF-II were used to account for the differences between the S8ER and S8DR cores.

While this normalization procedure may appear somewhat circuitous, it was believed to be the method which would minimize the error in the final result. The material compositions and the core dimensions of the S8ER more closely approximate those of the S8DR than do the material composition and core dimensions of the SCA-4A. It had been observed that the calculated ratio of the reflector worths for the S8ER and S8DR were independent of the reflector thickness. It was assumed that the experimental ratio of the reflector worths would also be independent of thickness, and that this independence from thickness was true for any two of the three reactors considered. The ratio of the experimental control worth of the full-length drums with equal thickness and radius on the S8ER and the SCA-4A was expected to be equal to the actual ratio of reflector worths regardless of the reflector thickness. Thus the calculated portion of the scaling factor was minimized.

The calculated control-drum worth for the S8DR reactor is shown in Table 9 as a function of drum thickness for 4.50-in.-radius drums. Figure 12 shows a schematic diagram of the control drums in which the differentiation between drum thickness and radius is shown. Table 9 also shows the total system control in dollars.

TABLE 9
PREDICTED S8DR REACTIVITY CONTROL FOR
4.50-in.-RADIUS DRUMS

Drum Thickness (in.)	Drum Control (\$)	System Control (\$)
3-1/8	3.90	20.40
4-1/8	4.31	22.50
5-1/8	4.20	21.90

The prediction of total control was based on the interaction effect observed between two adjacent control drums in the S8ER experiments. During these a control drum was calibrated both with an adjacent control drum full-open (105° from full-shut) and with the adjacent drums full-shut. The ratio of these results was taken to be the interaction ratio. From the results of this experiment, the interaction effect between drums was calculated to be 0.74, i.e. the ratio of the

7-29-69 UNCL

7759-4608

Figure 12. Schematic of S8DR External Reflector and Control Drums

drum worth with interaction to that with no interaction. The average ratio between the two was calculated to be 0.87. Thus the total system control quoted in Table 9 is the product of six times the control for a single drum and the average control-worth interaction effect.

Analysis of the S8ER reactivity losses during the full-power operation pointed toward the desirability of increasing the system excess reactivity in the S8DR to assure the attainment of the design lifetime goal. The reference reflector thickness for S8DR was thus increased to 5.125 in. The predicted control-drum worth curve for a 4.50-in.-radius 5.125-in.-thick control drum is shown in Figure 13. Figure 14 shows the predicted differential control-drum worth for this control drum. The shape of these curves was obtained from the SCA-4A experiments and scaled to the total drum-worth values.

The total reflector worth of the S8DR reflector with 5.125-in.-thick control drums has been calculated to be \$40. Thus the control worth of the drums is equal to 55% of the total reflector worth for the reference S8DR reflector-drum configuration.

Total worth available in the control drum, however, is not actually available for control of the reactor core. The maximum control-worth swing occurs as the drum goes from a position of 0° (full-in) to 135° . On the S8DR, however, the control-drum full-out stop is set at 109° ; consequently only the portion of the control drum from 0° to 109° is available for the actual control of the reactor. This does not significantly affect the total control worth, however, since the last 26° of control-drum movement toward the full-out position is calculated to be worth only 30¢ per drum (see Figure 13).

5. Reflector-Shim Worth

The control-drum thickness was set at 2.125-in. base plus a 3-in. shim. Since it was necessary to know the worths of reflector shims on the control drum, a series of one-dimensional transport-theory calculations was made to determine the nuclear worth of the shims. Using the nuclear model described in Table 3, the calculations were made for: the base 2.125-in.-thickness; base plus a 1.0-in. shim; base plus a 2.0-in. shim; and base thickness plus a 3.0-in. shim. The results are shown in Figure 15. The worth increase for each inch increase in shim thickness decreases rapidly as the shim thickness approaches 3.0 in.

Figure 13. Integral Drum Worth for S8DR
(4.50-in. radius, 5.125 in. thick)

Figure 14. Differential Drum Worth for S8DR
(5.125 in. thick)

7-29-69 UNCL

7759-4611

Figure 15. Calculated S8DR Reflector-Shim Worth

6. Desirability of a Nuclear Prepoison

The use of a nuclear prepoison in SNAP reactor cores is desirable to reduce the reactivity control requirements. If the prepoison is properly chosen, it is theoretically possible to operate the reactor in a static control mode,⁽²⁵⁾ i.e. no control-drum movement. The SNAP 10A reactor used this technique to operate in a static control mode for nearly 10,000 hr. Unfortunately this is not a readily useable technique for the SNAP-8-type reactors because of the much larger magnitude of reactivity loss. In addition, in order to operate in the static control mode it is necessary to match the prepoison burnout rate to the total reactivity lossrate.

Even in situations where it is not possible to obtain a precise match between the reactivity losses and the prepoison burnout rate, use of a prepoison can still be attractive. In the case of the SNAP 8 reactor cores the buildup of the Sm¹⁴⁹ fission product represents a fairly large reactivity-loss component (\$1.09) which is a saturating effect. The reactivity loss due to the Sm¹⁴⁹ buildup is most pronounced in the early operating lifetime, with its rate of buildup decreasing as operating time is accumulated. Use of a Sm prepoison to match the fission-product buildup would result in a reduced control requirement. This technique was also used in the S8ER reactor.

The selection of natural samarium as the prepoison material in S8DR was made at a very early point in the design of the S8DS reactor. While a prepoison such as gadolinium-155 would provide a better match of prepoison burnout to the reactivity lossrate, natural Sm was selected based on the previous experience with its application in the ceramic barrier of the fuel elements and on the basis of availability. It represented state-of-the-art technology and provided a reduced reactivity control requirement even though it was not an ideal prepoison for this application.

Samarium has a rather large cross-section, and it burns out of the reactor at a rate greater than the reactivity losses under S8DR operating conditions. Consequently an increase in the total system reactivity can occur if a sufficient quantity of Sm prepoison is loaded into the reactor. Studies to determine the Sm prepoison loading for the S8DR reactor core indicated that the positive

reactivity swing associated with a \$3.00 Sm prepoison loading would be acceptable. Greater amounts would result in control swings larger than desirable. Thus a \$3.00 Sm prepoison loading was specified for the S8DR core.

It is of significance to note that the calculated worth of Sm loaded into the core is a function of operating fuel temperature. A given concentration of Sm loaded into the core was calculated to be worth 16% less at 1293° than at 73°F. This effect is caused by the shift in the neutron spectrum as indicated by the shift in the median fission energy with increased temperature. The Sm resonance at 0.098 ev is relatively close to the median fission energy of 0.19 ev at 73°F. However, the subsequent shift of the median fission energy to 0.26 ev at 1293°F reduces the effectiveness of the Sm absorption, thereby reducing its worth. The Sm prepoison loading specified in Table 3 was calculated to provide \$3.00 poisoning for the reactor at room temperature. The corresponding hot (1293°F) prepoison worth is calculated to be \$2.52.

C. EXCESS REACTIVITY CALCULATIONS

1. Two-Dimensional Transport-Theory Calculations

One of the most difficult nuclear calculations to make is an accurate un-normalized calculation of the excess reactivity for a given reactor core. The difficulty is due to the limitations of the theoretical models, the calculational model used to mock up the actual physical configuration of the reactor, and the nuclear cross-sections which are used. The calculation of the excess reactivity of a small reactor core is complicated even further by the problems associated with large neutron leakages. Being very highly enriched in uranium-235, these systems require the use of multigroup calculations. Since experiments have been carried out in which the excess reactivity was determined for similar reactor cores, normalization of the calculations to a previously measured core was available, thus providing the best method of predicting the excess reactivity for a new core.

Since the neutron leakage is a large factor for SNAP reactor cores, two-dimensional calculations were made in an attempt to treat neutron leakage from the reactor more accurately. Identical techniques were used to set up the nuclear models for the S8ER and S8DS reactor cores. Calculations were then made

for both reactors using a 16-energy-group neutron cross-section library. The S8ER reflector shim configuration used for the calculation was that which provided a total reflector thickness most like the S8DS reference design. The calculated reactivity difference between the two cores was assumed to be correct even though the magnitude of the calculated excess reactivity for the S8ER core was too low. This difference was then added to the experimentally inferred excess reactivity for the S8ER reactor core.

2. Differencing From S8ER

A second technique of estimating the total system excess reactivity for the S8DS reactor core was used as a check on the two-dimensional calculations. This technique involved the assessing of all the changes made between the S8ER and the S8DS reactor cores and calculating each of these effects individually from one-dimensional calculations. Assuming these effects were all separable, they were then added together to determine the total effect on the excess reactivity for S8DS. Results of a similar calculation, made for S8DR, are shown in Table 10.

3. Final Prediction of S8DR Excess Reactivity

The two studies noted above gave good agreement for the S8DS reactor. Thus, a two-dimensional calculation (DDK) was not performed for S8DR. Rather, the differencing technique and a normalization factor were used, with the normalization factor equal to the difference between the DDK and the differencing calculation for the S8DS core. The magnitude of the changes between S8DR and S8DS was calculated with one-dimensional transport-theory calculations. Table 11 shows the reactivity effect of the final change between S8DS and S8DR cores and also the predicted total excess reactivity of the S8DR reactor.

D. NEUTRON FLUXES AND POWER DISTRIBUTIONS

1. Core-Averaged Neutron Fluxes

Neutron fluxes for the reactor core are calculated every time one of the neutron physics codes is used in a calculation. Consequently, many sets of neutron fluxes exist ranging from three to 26 neutron-energy groups in both one and two dimensions for radial, axial, and angular directions. Various energy-

TABLE 10
EXCESS REACTIVITY OF S8DR FROM ONE-
DIMENSIONAL DIFFERENCING CALCULATIONS
(Cold poisoned 5-1/8-in.-thick reflector)

Wet Excess of S8ER	\$10.68 ± 0.50
Shave fuel to 0.529-in. OD	-1.05 ± 0.30
Add length, 14.00 to 16.825 in.	+4.85 ± 0.75
Add hydrogen, 5.95 to 6.05 N _H	+1.00 ± 0.10
Add prepoison, \$2.72 to \$3.00	-0.28 ± 0.30
Add uranium, 10 to 10.5 wt %	+0.20 ± 0.05
Change internal reflectors	-0.50 ± 0.10
Change cladding thickness	-0.50 ± 0.10
Change vessel-reflector gap	-0.50 ± 0.10
Wet Excess of S8DR (\$3.00 prepoison)	\$13.90 ± 1.00

TABLE 11
FINAL PREDICTION OF S8DR EXCESS REACTIVITY

Calculation of S8DS by DDK [*] Normalized to S8ER	\$14.75
Difference Calculation Based on S8ER Hot Excess Reactivity	\$13.90 ± 1.00
Best Estimate for S8DS	\$14.75 ± 1.50
Calculated difference between S8DR and S8DS	-0.35 ± 0.15
Best Estimate, S8DR Cold Poisoned Excess Reactivity	\$14.40 ± 1.50

*Two-dimension transport-theory code

group structures have been used depending on the type of solution sought. A collapsed set of fluxes from a DTK one-dimensional transport-theory calculation is shown in Table 12 in comparison to results from the same case calculated in two dimensions with the DDK two-dimensional transport-theory program. These fluxes were averaged over the core for an operating power level of 600 kw. It is noted that the agreement between the two calculations is very close for each of the neutron-energy groups considered.

TABLE 12
COMPARISON OF CORE-AVERAGED FLUXES
(From One- and Two-Dimension Transport-Theory Calculations)

Neutron Group	Energy Range	DTK Flux*	DDK Flux**
Fast	0.1 Mev to 10 Mev	2.99×10^{13} nv	3.10×10^{13} nv
Intermediate	1 kev to 0.1 Mev	1.02×10^{13} nv	2.01×10^{13} nv
Epithermal	1 ev to 1 kev	1.08×10^{13} nv	
Thermal	Below 1 ev	0.39×10^{13} nv	0.32×10^{13} nv

*One-dimensional calculation

**Two-dimensional calculation

2. Thermal-Flux Spectra

While the flux spectrum in the SNAP reactors is essentially thermal, it cannot be accurately characterized by a typical Maxwellian thermal-neutron energy spectrum. This is a consequence of the zirconium-bound hydrogen in the uranium zirconium-hydride fuel matrix. Using the neutron-scattering kernel based on the SUMMIT II code, a 26-group set of cross-sections was prepared for use in calculations of the SNAP reactor cores. A calculated neutron spectrum for the S8DR reactor core operating at 73 °F is shown in Figure 16. Superimposed on the same curve is the neutron spectrum for the reactor operating at 1293 °F. The effect of hardening the spectrum is clearly noted in this comparison.

3. Delayed-Neutron Fraction

A fraction, β , of the neutrons produced in the fission process are born at a later time than the prompt fraction, $1 - \beta$. These β neutrons effectively increase

7-29-69 UNCL

7759-4612

Figure 16. Temperature Variation of SNAP Thermal Spectra

the neutron lifetime in the reactor core. A value of β_{eff} , i.e. the effective delayed-neutron fraction, is used to convert neutron multiplications to reactivities and vice versa. The effective delayed-neutron fraction is slightly different than the actual delayed fraction of neutrons because of differences in the spectra of the prompt and delayed neutrons.

The calculation of the effective delayed-neutron fraction may be performed in a straightforward fashion. First a multigroup core calculation with a fission spectrum using χ_1 values (fraction of the fission neutrons born in each energy group) for prompt plus delayed neutrons is performed. The neutron multiplication is then recalculated based on χ_1 values for the prompt neutrons only. The difference in neutron multiplication between the two cases is the effect due to the delayed neutrons, β . The delayed-neutron energy spectrum which was used in these calculations⁽²⁶⁾ is shown in Table 13. The calculational results show that β_{eff} is a function of the reflector configuration. The data shown in Table 14 indicate that the value of β_{eff} varies from 0.00782 to 0.00824 with a value of 0.00805 for an effective multiplication factor of 1.0. A value of 0.0080 is therefore satisfactory for converting Δk to reactivity in dollars.

TABLE 13
DELAYED FRACTION OF THE TOTAL FISSION SPECTRUM
BY NEUTRON-ENERGY GROUP

Energy Group	Energy Limits	Delayed Fraction
2	1.4 Mev to 3.0 Mev	0.0003094
3	0.9 Mev to 1.4 Mev	0.0006747
4	0.4 Mev to 0.9 Mev	0.0024635
5	0.1 Mev to 0.4 Mev	0.002637
6	17.0 kev to 0.1 Mev	0.000415
Total		0.0065

TABLE 14
 β_{eff} AS A FUNCTION OF DRUM
 POSITION

Reflector Configuration	β_{eff}
Drums full-in	0.00782
$k_{\text{eff}} = 1.0$	0.00805
Drums full-out	0.00824

4. Prompt-Neutron Lifetime

The prompt-neutron lifetimes for the S8DR reactor were calculated using the multigroup diffusion-theory programs with standard techniques of modifying the steady-state diffusion-theory equations to simulate the kinetics equations. The results of these calculations, however, were not entirely satisfactory, and the final results were adjusted by comparison to S8ER experimental data. A number of calculations were performed using the FAIM, ULCER, and QUICKIE diffusion-theory programs to calculate the prompt-neutron lifetime for neutrons only in the core and for neutrons in all regions of the reactor. The results yielded a calculated prompt-neutron lifetime ranging from about 4.7 μsec for neutrons in the core only to a value of 6.9 μsec for neutrons in all regions with the control drums in the full-in configuration.

Experiments on the S8ER core yielded a value of 8.4 $\mu\text{sec} \pm 10\%$ based on a β_{eff} of 0.0080. Calculations of the S8DR prompt-neutron lifetime by the identical method used to calculate that for the S8ER showed no difference in the results for the two cores. For this reason and because of the large difference between the calculated prompt-neutron lifetime on the S8ER and that experimentally observed on it, the experimentally based value of 8.4 $\mu\text{sec} \pm 10\%$ has been accepted as the best value for the S8DR prompt-neutron lifetime.

5. Median Fission Energy

Results from 26-group ANISN calculations were used to determine the median fission energy of the S8DR core. The median fission energy of the core was found to be a rather strong function of the operating fuel temperature, and was also influenced by the Sm loading. The calculated median fission energy as a function of fuel temperature and initial cold Sm loading is shown in Table 15.

TABLE 15
S8DR MEDIAN FISSION ENERGY

Fuel Temperature (°F)	Samarium-149 Loading (cold, \$)	Median Fission Energy (ev)
73	0.00	0.19
73	3.00	0.20
1293	0.00	0.26
1293	3.00	0.27

E. MATERIAL COEFFICIENTS OF REACTIVITY

Numerous calculations were performed in the course of the S8DS-S8DR reactor design to evaluate the effects of various material changes in the core. These calculations were performed over a period of approximately six years, and used both the S8DS and the S8DR reference designs as bases for the calculations. As a consequence of this long time lag, the standard calculational codes have changed. The majority of the material-coefficient studies which were made using the S8DS reference design as a base used the FAIM and ULCER diffusion-theory calculations. The more recent calculations have used the ANISN family of transport-theory codes almost exclusively. Nevertheless, the majority of the results calculated some time ago for the S8DS core are still valid for the S8DR reactor because of the small nuclear changes between the two cores.

Most of the material coefficients listed herein were of primary consideration during the initial phases of the reactor core design. At that time it was desirable to know the effects of small changes in the various material coefficients to account for design changes and for slight differences between as-built components and the nominal design specifications. Recomputation of previously calculated coefficients using the current analytical techniques would be of academic interest, but are of little practical value since the change in results would be slight.

1. Hydrogen Worth

The loss of the hydrogen moderator from the core represents one of the major reactivity-loss components during the S8DR reactor operating lifetime. Consequently the calculation of the hydrogen-reactivity coefficient is very important. The overall core-averaged hydrogen worth was initially calculated using the FAIM one-dimensional diffusion-theory computer code. A value of $0.44(\Delta k/k)/(\Delta H/H)$ was obtained, i.e. a 1% change in the hydrogen concentration would change the system k_{eff} by 0.44%. Later calculations were made with one-dimensional transport-theory code DTF, which gave rise to a somewhat larger value of $0.50(\Delta k/k)/(\Delta H/H)$. This value corresponds to a change of \$10.30 per 1.0 N_H or 62.5¢ per % H, using a β_{eff} of 0.008.

Verification of the analytical technique was provided by the extremely close agreement between the predicted and experimentally measured hydrogen worth for a fuel rod at the center of the S8ER core. Fuel rods of various hydrogen concentration were substituted for a normal fuel rod in the center of the S8ER core. The predicted and experimentally measured hydrogen worths relative to a fueled rod with no hydrogen are shown in Table 16.

TABLE 16
PREDICTED AND MEASURED HYDROGEN
WORTH FOR THE CENTER FUEL
ELEMENT IN S8ER

Hydrogen Concentration (atoms x 10^{22} /cc fuel)	Worth (¢)	
	Experimental	Predicted
0.0	0	-
3.0	23 ± 2	20
5.0	34 ± 2	34
6.0	40 ± 2	40

An analysis of the core-averaged hydrogen worth in the S8ER reactor indicated that it was a function both of the hydrogen concentration in the core and of the control-drum position. Fortunately, the effects are nearly compensating, and the hydrogen worth for the S8ER core was shown to be a nearly constant value of \$1.00 per 0.1 N_H.⁽²⁷⁾ Thus, an averaged value of \$1.03 per 0.1 N_H for S8DR appears quite reasonable.

2. Uranium Worth

Diffusion-theory calculations of the uranium worth in the S8DS core yielded a value of 0.67 ($\Delta k/k$)/($\Delta M/M$), or 84¢ per wt % change in the U. (The uranium is 93.15% enriched in U²³⁵.) A 1 wt % change in U in the fuel corresponds to a 10% change in the total number of U atoms since the fuel is only 10.5 % U by weight. The U worth is a function of its concentration, so the value quoted should be used only for relatively small changes in U concentration.

3. Fuel-Rod Diameter

The effect of small changes in the fuel-rod diameter was calculated using the FAIM program. A value of 1.068 ($\Delta k/k$)/($\Delta D/D$) was obtained, meaning a change of 1 mil in fuel diameter (about 0.2%) would cause a change of 0.2% in reactivity. Converting to cents-reactivity yields 25¢/mil diameter change.

4. Cladding Material

FAIM was also used to find the effect of small changes in the Hastelloy-N cladding. The reactivity coefficient was found to be -0.03 ($\Delta k/k$)/($\Delta M/M$), or -38¢/mil increase in cladding thickness.

5. Core Vessel

The reactivity coefficient for the core vessel was calculated using both the FAIM and ULCER diffusion-theory programs and the SNG transport-theory program. The results from all three programs were in agreement. The reactivity coefficient was calculated to be -0.00485 ($\Delta k/k$)/($\Delta M/M$) with drums in, or -0.64¢/mil of core vessel thickness for changes from 60 to 105 mils.

All three calculations showed the core vessel to have a positive worth with the drums out due to reflection of neutrons by the iron and nickel in the vessel. Consequently, the control-drum worth was reduced by a larger amount than the

reduction in the base drums-in reactivity which results from the thicker vessel. Only the drums-in values of the coefficient are given.

6. Beryllium Oxide in Internal Reflectors

An estimate was made of the effect of removing BeO from the internal reflectors using DTF one-dimensional transport-theory calculations of total internal reflector worth. The reactivity coefficient was found to be about $-0.0175 (\Delta K/K)/(\Delta M/M)$ or -2.2% per percent removed.

7. Samarium

Based on changes of the order of 20% of the Sm, the DTF program gave a value of $+0.021 (\Delta K/K)/(\Delta M/M)$ or $+2.6\%$ Sm decrease.

8. Fuel-Rod Length

The effect of changing the fuel-rod length was calculated using the DTF program. The value obtained was $1.5\% (\Delta k/k)/(\Delta L)$, or $\$1.88/\text{in.}$ of added core length for a change from 14.0 to 16.5 in. The value is a rather strong function of the length, decreasing as the length increases.

9. Gap Between the Core Vessel and Reflector

While the reflector-vessel gap coefficient was not calculated analytically, it is included here because of the interest in perturbations of this type on the core design. The value was obtained from experiments on the SCA-4A critical assembly. A value of 1.5% /mil of gap was determined for small gap thicknesses for the 3.25-in.-thick reflector. The gap worth is a function of the reflector thickness and is approximately proportional to the total reflector worth.

A summary of the material-worth calculations is given in Table 17. The nominal S8DS value used in the base calculation is also given for each of the materials. The coefficients lose validity for changes greater than 10% of the base-case value.

10. Additional Cladding-Worth Coefficients

An additional study was performed to determine the reactivity effect of each of the components in the cladding material. The results were normalized so that rapid comparisons could be made between various cladding-material nuclear worths, eliminating the necessity of a separate computer case for each new

TABLE 17
MATERIAL COEFFICIENTS OF REACTIVITY FOR S8DS (S8DR)

Material Parameter	Nominal S8DS Value	Reactivity Coefficient	Calculation Technique	Comments
Hydrogen Concentration	$N_H = 6.05^*$	$\$10.30/N_H$ or $62.5¢/\% \frac{\Delta H}{H}$	FAIM and DTF	Function of N_H and reflector thickness. Effects compensate in S8DS to provide constant value throughout life.
Uranium Concentration	10.5 wt %	84¢/wt %	ULCER	Strong decreasing function of amount added.
Fuel-Rod Diameter	0.530 in.	25¢/mil	FAIM and DTF	
Cladding Thickness	10 mils	-38¢/mil	DTF	Good only for small changes.
Core-Vessel Thickness	105 mils	-0.64¢/mil	FAIM	Average for change from 60 to 105 mils. Strong function of reflector thickness
Samarium Concentration	$3.2 \times 10^{16} \frac{\text{atoms}}{\text{cc fuel}}$	$-2.6¢/\% \frac{\Delta m}{m}$	DTF	
Fuel-Rod Length	16.825 in.	\$1.88/in.	DTF	Average for change from 14.00 to 16.825 in.
Vessel-Reflector Gap	80 mils	-1.50¢/mil	SCA-4A Experiment	Strong function of reflector thickness. Good only for small changes.

*Actual hydrogen concentration is 6.05×10^{22} atoms H/cc fuel, abbreviated to $N_H = 6.05$

cladding material considered. Only the density of the cladding, the weight fraction of each component, and the cladding thickness are required for a cladding comparison.

The normalized worths listed in Table 18 were calculated by a one-group method. The one-group cross-sections necessary for the calculation were obtained by averaging the absorption cross-section of each element over S8DS core average fluxes, obtained from the DDK two-dimension multigroup transport-theory calculation. The one-group $\nu\Sigma_f$, $\Sigma_{a(\text{total})}$, and total neutron leakage were also obtained from DDK. Low cross-section elements such as carbon, silicon, and aluminum were not included in the calculation because of their small effect on reactivity. Use of the normalized worths shown in Table 18 yields cladding worths within about 10% of the values computed by the DTF transport-theory calculations.

TABLE 18
CLADDING-MATERIAL WORTH COEFFICIENTS

Element	Normalized Material Worth (ϕ)*
Nickel	3.16
Molybdenum	7.42
Iron	1.42
Chromium	2.08
Manganese	12.92
Boron	20250.00
Cobalt	47.34
Tungsten	47.46
Titanium	3.59

*Multiply the normalized element worth by the cladding density (gm/cc), the cladding thickness (mils), and the weight fraction of the element in the cladding to obtain the element's contribution to the cladding worth.

BLANK

V. PERFORMANCE SUMMARY

A. INITIAL AND SHORT-TERM OPERATING LOSSES

The predicted reactivity losses for the initial operating phases of S8DR operation are shown in Table 19 and Figure 17. The results shown in the table include the individual reactivity coefficients, the initial temperature and power defect incurred in going from ambient shutdown to operating conditions, and the predicted reactivity lossrate after one week of operation. The data shown in the figure indicate the short-term reactivity losses for the first 60 hr after arriving at the rated operating conditions of 600 kw_t, 1100°F NaK inlet, and 1300°F NaK outlet. The loss shown in Figure 17 is due almost entirely to the xenon-135 buildup and to the hydrogen redistribution. The results also show the associated tolerance limits (3 σ deviations) for each of the individual components as well as for the totals.

The predicted vault-effect worth shown in Table 19 results from the expected difference in the initial cold excess reactivity of the core as measured in the vacuum chamber relative to the measured excess in the equipment vault. The values for the vault and NaK worths have not been rigorously calculated but rather were scaled from experimental measurements on previous SNAP reactor cores.

The isothermal temperature coefficient which will be calculated based on the reactivity defects measured during the low-temperature phases (through $\sim 500^\circ\text{F}$) of the vacuum vessel critical tests will most likely fall between the prompt isothermal coefficient and the total of it and the delayed reflector coefficient. It is anticipated that the measurements during the low-temperature phases of the testing will be made too rapidly for the reflector temperature to reach equilibrium. It appears that the higher temperature measurements will be performed in such a fashion as to allow the reflector to reach its equilibrium temperature, so that the measured coefficient should be the sum of the prompt coefficient and the delayed reflector coefficient. The time constant for reflector heating is approximately 1 hr.

The results shown in Figure 17 give the calculated reactivity losses following the initial \$3.00 reactivity loss associated with initially bringing the system

TABLE 19
PREDICTED SHORT-TERM OPERATING LOSSES FOR S8DR

<u>Reactivity Coefficients</u>	
Vault Effect, ¢	+20 ± 20
NaK Worth, ¢	+30 ± 20
Prompt Isothermal Temperature Coefficient, ¢/°F	-0.22 ± 0.04
Fuel	- 0.09 ± 0.03
Upper plenum	- 0.07 ± 0.02
Lower plenum	- 0.06 ± 0.02
Delayed Reflector Coefficient, ¢/°F	-0.03 ± 0.02
Reflector time constant, hr	~ 1.0
Power Coefficient, ¢/kwt	-0.03 ± 0.01
<u>Defects for 600 kwt, 1100°F T_i, 200°F ΔT</u>	
Prompt Isothermal Temperature Defect, \$	-2.48 ± 0.45
Delayed Reflector Defect, \$	-0.34 ± 0.22
Reflector time constant, hr	~ 1.0
Power Defect, \$	-0.18 ± 0.06
Total Initial Loss, \$	-3.00 ± 0.50
Xenon Defect, \$	-1.05 ± 0.10
Effective xenon time constant, hr	16 ± 2
Hydrogen Redistribution, \$	-0.29 ^{+ 11} / _{- 9}
Effective redistribution time constant, hr	10 ^{+ 6.0} / _{- 3.5}
<u>Reactivity Change Rate After One Week of Operation</u>	
Hydrogen Loss, ¢/day	-0.50 ± 0.10
Fission-Product Buildup and Fuel Burnout, ¢/day	-0.34 ± 0.03
Samarium-149 Prepoison Burnout, ¢/day	+1.14 ± 0.30
Total	+0.30 ± 0.31

Figure 17. Predicted Reactivity Losses for the First 60 hr of S8DR Operation

to temperature and power. The distribution of \$3.00 initial defects quoted in Table 19 assumes that the average coolant temperature was established and remained unchanged in going to full power. If the inlet temperature rather than the average temperature were held constant in going to full power, the effective power coefficient would be $\alpha_p = 0.065¢/\text{kw}$, but the total defect would remain unchanged.

The reactivity losses shown in Figure 17 are essentially a linear function of time after the initial losses due to xenon buildup and hydrogen redistribution have taken place. After 60 hr operation both of these effects have essentially reached their equilibrium value.

As seen in Table 19 the largest factor in the reactivity lossrate after 1-wk operation at 600 kw is the positive effect of burning-out the samarium prepoison. The prepoison-loading nuclear worth was not determined experimentally. It was therefore taken at its calculated value of \$3.00 cold (\$2.52 at operating conditions), and used with the calculated equilibrium Sm^{149} worth of \$1.09 to calculate its burnout rate. Thus the quoted lossrate after 1-wk operation has a large uncertainty because of the uncertainty in the Sm^{149} burnout.

B. LONG-TERM OPERATING LOSSES

Long-term operating losses were calculated for S8DR for operating conditions of 600 kwt, 1100°F inlet, and 1300°F outlet, and for conditions of 1000 kwt, 830°F inlet, and 1100°F outlet. The actual operating sequence is expected to include both modes of operation. The current operating plans call for operating S8DR at 600 kwt for 1 month, then 1 month of operation at 1000 kwt, followed by the remainder of the long-term endurance testing at 600 kwt until the design operating goal has been attained.

Figure 18 shows the predicted reactivity losses for S8DR for long-term operation at 600 kwt. This curve does not include the initial short-term reactivity losses such as hydrogen redistribution, Xe buildup, and the temperature and power defects; but it does include the effect of the Sm prepoison burnout. Figure 19 is a similar curve for 1000-kwt operation. The expected reactivity losses for S8DR with the currently anticipated sequence of powers are shown in Figure 20.

The predicted reactivity losses at 600 kwt are a strong function of the assumed hydrogen-loss model. The model for these calculations was based on the long-term isothermal hydrogen leakage data from the S8DR preproduction fuel elements, and from the Phase I, II, and III S8DR production fuel elements. The mean of the data was plotted as a function of operating time and extrapolated to operating times of 10,000 to 25,000 hr. This mean as a function of time was then used to predict the reactivity loss due to hydrogen leakage. The current estimates of hydrogen loss during the S8DR testing are considerably less than earlier estimates (see Section IV-A-3).

Figure 18. Predicted Long-Term Reactivity Loss for S8DR at 600 kw

Figure 19. Predicted Long-Term Reactivity Loss for S8DR at 1000 kw

8-28-69 UNCL

7759-4616

Figure 20. Predicted Reactivity Losses for Projected S8DR Operation

VI. CONCLUSIONS

The calculations and analyses given herein represent the current state-of-the-art of nuclear calculations for compact U-ZrH-fueled SNAP reactors. The calculational techniques used have been discussed along with limitations of the calculations and their normalization to appropriate experimental results. Specifically, the results from S8ER testing have been extensively used for normalizing calculated results, and give a high degree of confidence that the calculations are within a very small error band.

The analyses indicate that the S8DR reactor is capable of achieving its design goal of 12,000 hr of operation at 600 kwt, 1100°F inlet, and 1300°F outlet NaK with a considerable margin of operational capability. The calculated excess reactivity of \$14.40 far exceeds the predicted reactivity losses of \$6.70 for the design lifetime. The predicted control worth of \$21.90 will provide adequate shutdown margin even at the beginning-of-life with one control drum stuck in its most reactive (full-in) position.

The long-term endurance testing of S8DR will provide (1) the operational data required to check the calculations of reactor performance and (2) vital long-term data which will be used for performance predictions of future SNAP reactors.

BLANK

REFERENCES

1. L. D. Swenson, "S8DR Core Performance Evaluation," NAA-SR-12482 (CRD), August 9, 1967
2. P. M. Magee, "SNAP 8 Development Reactor (S8DR) Core Thermal and Hydraulic Performance," NAA-SR-12564 (CRD), March 10, 1968
3. A. W. Dalcher, "Structural Analysis of the SNAP 8 Developmental Reactor Fuel Element Cladding," AI-AEC-TDR-12824, April 15, 1969
4. C. E. Johnson, ed., "SNAP 8 Quarterly Progress Report July - September 1962 Vol.I. Reactor Engineering and System Tests," NAA-SR-7792, Vol I, (CRD) April 22, 1963, p 171
5. R. E. Dyer, "Disassembly and Postoperation Examination of the SNAP 8 Experimental Reactor," NAA-SR-11520, p 9
6. P. S. Olson, K. J. Miller, E. J. Donovan, "Postoperation Evaluation of Fuel Elements From the SNAP 8 Experimental Reactor," NAA-SR-12029 (CRD), September 15, 1967, pp 125-127
7. W. C. Miller, ed., "SNAP 8 Developmental Reactor Safety Analysis Report," NAA-SR-MEMO-11373 (CRD), September 6, 1967, p 31
8. C. E. Johnson, "SNAP 8 Quarterly Progress Report, July - September 1963" NAA-SR-8992 (SRD), November 15, 1963, p 15
9. Magee, *ibid.* pp 21-28
10. The following are included in this reference:
 - a. J. Bengston, et al, "2DXY - Two Dimensional, Cartesian Coordinate SN Transport Calculation," AGN TM-392, June 1961
 - b. D. C. Baller, "The FAIM Code - A Multigroup, One-Dimensional Diffusion Equation Code," AMTD-118 (NAA-SR-7137), January 1961
 - c. D. S. Vargofcak, W. T. Hayes and D. W. Roeder, "ULCER - A One-Dimensional Multigroup Diffusion Equation Code with Upscatter," NAA-SR-MEMO-9891, May 1964
 - d. E. L. Wachspress, "CURE, A Generalized Two-Spaced-Dimension Multigroup Coding for the IBM 704," KAPL-1724, 1957
 - e. D. P. Stakus, and H. P. Flatt, "SIZZLE, A Fast or Immediate Reactor Burnup Code," AI-64-MEMO-183, August 1964

- f. M. A. Boling, W. A. Rhoades, "NAA Program Description ANISN/DTF II Conversion to IBM System/360, " AI-66-MEMO-171 Vol. I, 1966
- g. F. R. Mynatt, "A Users Manual for DOT, a Two-Dimensional Discrete Ordinates Transport Code with Anisotropic Scattering, " K-1694, unpublished
11. M. E. Nathan, "FUSAK, A Computing Code for Theoretical Evaluation of SNAP 8 and SNAP 10A Fuel Element Performance During Reactor Operation, " NAA-SR-11400, November 1, 1965
12. K. R. Birney, D. J. McGoff, "LOAFER, A Code for Determining Performance Characteristics of SNAP Reactors, " NAA-SR-12237 (CRD), February 1, 1967
13. E. H. Ottewitte, "An Updated Sixteen-Group Hansen-Roach Structure Library, " NAA-SR-TDR-11907, May 12, 1966
14. J. Bell, "SUMMIT, An IBM-7090 Program for the Computations of Crystalline Scattering Kernels, " GA-2492, February 1, 1962
15. L. D. Swenson, *ibid*, pp 36-39
16. D. G. Mason, "SNAP 8 Progress Report, November 1966 - January 1967, " NAA-SR-12293 (CRD), April 7, 1967, pp 94-95
17. C. J. Engberg, et al., "Irradiation Stability of SCB-1 Coated Hastelloy-N SNAP 8 Fuel Cladding Experiment NAA 77-1, " NAA-SR-11457, October 15, 1965
18. R. L. Detterman, "SNAP Reactor Programs Progress Report, November 1968 - January 1969, " AI-AEC-12773 (CRD), pp 123-128
19. R. F. Audette, "SNAP 8 Automatic Startup and Power Conversion System Mercury Injection Simulation Tests, " AI-AEC-12850, to be published
20. W. A. Young, et al., "Thermophysical Properties of Unirradiated SNAP Fuels, " NAA-SR-12607, February 23, 1968
21. D. G. Mason, "SNAP Reactor Programs Progress Report August - October 1967, " NAA-SR-12583 (CRD), December 15, 1967, p 107
22. J. F. Jackson, W. F. Rhoades, L. I. Moss, "Analysis of SNAPTRAN-1 and -2 Reactor Kinetics Experiments, " NAA-SR-11850, June 26, 1967
23. D. W. Clifford, "Interim Report on the SNAP Critical Assembly 4A (SCA-4A) Experimental Results, " NAA-SR-10245 (CRD), March 20, 1965 p 26

24. D. G. Mason, "SNAP 8 Progress Report, February - April 1966," NAA-SR-11898 (CRD), July 15, 1966, p 169-171
25. K. R. Birney, D. J. McGoff, "Static Control of SNAP Reactors," NAA-SR-11911 (CRD), May 30, 1966
26. Nucleonics 20, No. 8, 152, August 1962
27. D. G. Mason, "SNAP 8 Progress Report, October 1965 - January 1966," NAA-SR-11758 (CRD), April 8, 1966, p 121