2cp

MASTER
THE
UNIVERSITY
OF
WISCONSIN

DEPARTMENT OF
ELECTRICAL ENGINEERING

RECEIVED BY DTIE NOV 8 1971

QUARTERLY PROGRESS REPORT NO 18

"Plasma Instabilities and Waves Excited
by an Anisotropic Energy Distribution
Produced by Electron Cyclotron Resonance"

U.S. Atomic Energy Commission
Contract No. AT(11-1) 1695

REPORT NO. COO-1695-39

September 15, 1971

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Madison, Wisconsin 53706

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

QUARTERLY PROGRESS REPORT NO. 18

Plasma Instabilities and waves Excited by an Anisotropic Energy
Distribution Produced by Electron Cyclotron Resonance

Contract No. AT(11-1) 1695

U.S. Atomic Energy Commission

J. L. Shohet
D. G. S. Greene
P. A. Raimbault
S. N. Golovato
R. T. Pedley
J. C. Martyn

Principal Investigator
Graduate Research Assistant
Graduate Research Assistant
Graduate Research Assistant
Student Technician
Student Technician

September 15, 1971

Department of Electrical Engineering
The University of Wisconsin
Madison, Wisconsin 53706

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

INTRODUCTION

J. L. Shohet

This report covers the period between June 15, 1971 and September 14, 1971.

Basically the work performed covered three areas. They are

1. Polarization measurements of the free-free bremsstrahlung x-rays.
2. Optical diagnostics
3. Microwave calculations.

The bremsstrahlung measurements have been made to determine the polarization distribution of the free-free bremsstrahlung exiting radially along the mid-plane as a function of various plasma parameters.

Specifically they are: pressure, magnet current, mirror ratio and off-resonance power, as well as axial displacement of both the heating and observing location.

Optical measurements of intensity ratios have been made to determine the effects of plasma parameters on neutral and ion temperatures.

Finally, further progress on microwave cavity calculations for a warm plasma have been made.

FREE-FREE BREMSSTRAHLUNG POLARIZATION MEASUREMENTS

P. A. Raimbault

The polarization of the free-free bremsstrahlung x-rays coming from the plasma was measured as a function of various parameters. The same experimental setup was used as the one described in the previous progress reports.

1) The Mylar windows as well as the microwave inputs were displaced 15 cm along the axis of the machine to measure the polarization of the x-rays emitted closer to the throats of the magnetic mirror. Moving the horns was necessary to provide a greater intensity of x-rays at the detector. By comparing Figures 1(a,b) and 2(a,b) we can notice an increase in the polarization at the location closest to the mirror throats which can be explained because the anisotropy of the plasma is greater at this location than in the mid-plane.

2) The influence of the mirror ratio upon the polarization was studied. The mirror ratio was 1.19 for the data shown in Figure 2. When the mirror ratio was changed to 1.435, the result was a decrease in the polarization, i.e., a decrease in the anisotropy of the plasma as shown in Figure 3(a,b). This can be explained because the confinement characteristics are improved with a higher mirror ratio. This results in a more collisional plasma and therefore a greater relaxation of the anisotropy.

3) The intensity and polarization of the x-rays coming out in the radial direction were measured as a function of lower off

Polarization Measurements

3.

Phototube Horizontal

Figure 1(a)

Phototube Vertical

Figure 1(b)

Mid plane Measurement

Figure 2(a)

New location

Figure 2(b)

Measurement $R = 1.19$

Figure 3(a)

New location

Figure 3(b)

Measurement $R = 1.435$

resonance heating, (LORH) produced by a 50 watt, CW microwave source using a QK61 magnetron, tunable from 2975 to 3170 MHz.

a) Intensity

Figure 4 shows the intensity of x-rays without LORH. Figure 5 shows the intensity with LORH at a power level just below the point where the plasma extinguishes. A flattening of the x-ray spectrum can be noticed. This corresponds to a higher temperature of the plasma if we assume

$$\ln(\text{Intensity}) = - \frac{w}{kT_e}$$

where $-\frac{1}{kT_e}$ is then the slope of the curve and w is the energy.

This can be explained because there is an enhanced loss of cold plasma through the mirror throats so the confined plasma particles make fewer collisions and can thus become hotter.

b) Polarization

The polarization was measured with LORH just below the point where the plasma extinguishes as shown in Figure 6(a,b). A decrease of the polarization with respect to Figure 2 again shows that there is a flux of electrons towards the throats of the machine that results in a decrease of the anisotropy.

Bremsstrahlung Measurements and LORH

5.

Figure 4

Figure 5

Phototube Horizontal

Figure 6(a)

Phototube Vertical

Figure 6(b)

THEORY OF FREE-FREE BREMSSTRAHLUNG

P. A. Raimbault

We shall define the process of bremsstrahlung as follows: A photon of radiation is emitted whenever an electron which passes a positive ion is decelerated.

The problem we consider is to find the polarization of the emitted radiation. A quantum mechanical non-relativistic model was described in the previous reports which developed a cross section for free-free bremsstrahlung. These results are now to be integrated over the velocity distribution of electrons. The integration is done for several cases.

I. Integration of the scattering cross section over a beam of monoenergetic electrons.

Let us first define some quantities for the problem as shown in Figure 7. They are:

- $\vec{p}_0, E_0$: the momentum and energy of the incident electron
- $\vec{p}, E$: the momentum and energy of the scattered electron
- $\vec{k}$: the momentum of the emitted photon; $\vec{k}$ is always assumed to lie in the y direction
- $\vec{j}$: the unit vector in the direction of the polarization of the photon. It is always perpendicular to $\vec{k}$
- ξ_0 & ξ : the angles between $\vec{p}_0$ and $\vec{j}$ and $\vec{p}$ and $\vec{j}$, respectively
- θ_0 & θ : the angles between $\vec{p}_0$ and $\vec{k}$ and $\vec{p}$ and $\vec{k}$
- ϕ : the angle between the planes $(\vec{p}_0, \vec{k})$ and $(\vec{p}, \vec{k})$.

The scattering cross section was previously found to be

Figure 7

$$\sigma(\vec{p}, \vec{p}_0, E, E_0) = A \frac{p}{p_0} \frac{1}{E_0 - E} \frac{(p_0 \cos \xi_0 - p \cos \xi)^2}{|\vec{p}_0 - \vec{p}|^4} \quad (1)$$

A is a scale factor.

We have to compute the degree of polarization P of the photons emitted in the y direction. It is given by the expression

$$P = \frac{J_{\parallel} - J_{\perp}}{J_{\parallel} + J_{\perp}}$$

where $J_{\parallel}$ and $J_{\perp}$ are the relative probabilities for the polarization of the photon in the x-direction and z-direction respectively.

We wish to find the degree of polarization as a function of photon energy $|\vec{k}|c = E_p$

$$E_p = \frac{1}{2m} (p_0^2 - p^2)$$

To do this we first integrate the cross section over all directions of the scattered electrons. The magnitudes of the polarization in the two directions are given by

$$J_{\parallel} \sim p_0 \int \sigma_{\parallel} \sin \theta \, d\theta \, d\phi \quad (2)$$

$$J_{\perp} \sim p_0 \int \sigma_{\perp} \sin \theta \, d\theta \, d\phi \quad (3)$$

If we suppose the beam of particles to be incident in the x direction, then

$$\sigma_{\parallel} = A \frac{p}{p_0} \frac{1}{E_0 - E} \frac{(p_0 - p \sin \theta \cos \phi)^2}{|\vec{p}_0 - \vec{p}|^4} \quad (4)$$

$$\sigma_{\perp} = A \frac{p}{p_0} \frac{1}{E_0 - E} \frac{p^2 \sin^2 \theta \sin^2 \phi}{|\vec{p}_0 - \vec{p}|^4} \quad (5)$$

where $|\vec{p}_0 - \vec{p}|^4 = (p^2 + p_0^2 - 2pp_0 \sin\theta \cos\phi)^2$

We may combine the cross sections (4) and (5) as:

$$\sigma_{\parallel} + \sigma_{\perp} = k \frac{p}{p_0} \frac{1}{(E_0 - E)} \frac{p_0^2 + p^2 \sin^2\theta - 2p_0 p \sin\theta \cos\phi}{(p_0^2 + p^2 - 2p_0 p \sin\theta \cos\phi)^2} \quad (6)$$

and

$$\sigma_{\parallel} - \sigma_{\perp} = k \frac{p}{p_0} \frac{1}{(E_0 - E)} \frac{p_0^2 + p^2 \sin^2\theta \cos^2\phi - 2p_0 p \sin\theta \cos\phi}{(p_0^2 + p^2 - 2p_0 p \sin\theta \cos\phi)^2} \quad (7)$$

We wish to find

$$P = \frac{\int (\sigma_{\parallel} - \sigma_{\perp}) \sin\theta \, d\theta \, d\phi}{\int (\sigma_{\parallel} + \sigma_{\perp}) \sin\theta \, d\theta \, d\phi} \quad (8)$$

After integration over the azimuthal angle ϕ , eqs. (6) and (7) become

$$\int (\sigma_{\parallel} + \sigma_{\perp}) d\phi = 2\pi \frac{p_0^2(p_0^2 + p^2) + \sin^2\theta[p^2(p^2 - 3p_0^2)]}{[(p_0^2 + p^2)^2 - 4p_0^2 p^2 \sin^2\theta]^{3/2}} \quad (9)$$

$$\begin{aligned} \int (\sigma_{\parallel} - \sigma_{\perp}) d\phi &= 2\pi \frac{(p_0^2 + p^2)[2p_0^4 - (p_0^2 + p^2)]^2 / 2p_0^2 + \sin^2\theta[p^2(3p^2 - p_0^2)]}{[(p_0^2 + p^2)^2 - 4p_0^2 p^2 \sin^2\theta]^{3/2}} \\ &\quad + \frac{\pi}{p_0^2} \end{aligned} \quad (10)$$

After integration over the polar angle θ we obtain

$$P = \frac{(p_0^2 - 3p^2) \operatorname{Log} \frac{p_0 + p}{p_0 - p} + 6p_0 p}{(3p_0^2 - p^2) \operatorname{Log} \frac{p_0 + p}{p_0 - p} + 2p_0 p} \quad (11)$$

for the degree of polarization.

This value of the polarization has been compared with previous experiments and appears to agree with them.

II. Integration of the scattering cross section over a velocity distribution function of particles.

We define the following geometry for this problem (Figure 8).

In this figure

α : is the angle between $\vec{p}$ and the z axis (axis of the machine as well as the direction of the magnetic field)

ρ : is the angle between the $(z, \vec{p})$ plane and the (x, z) plane

ψ : is the angle between the $(\vec{p}, \vec{k})$ plane and the (x, y) plane

In the parallel direction (x-direction)

$$\begin{aligned}\cos \xi &= \cos(\phi+\psi) \sin \theta \\ \cos \xi_0 &= \sin \alpha \cos \beta\end{aligned}\tag{12}$$

In the perpendicular direction (z-direction)

$$\begin{aligned}\cos \xi &= \sin(\phi+\psi) \sin \theta \\ \cos \xi_0 &= \cos \alpha\end{aligned}\tag{13}$$

where

$$\cos \theta = \frac{\sin \alpha}{\sqrt{1 - \cos^2 \alpha \sin \beta}}\tag{14}$$

and

Figure 8

$$\sin \psi = \frac{\cos \alpha}{\sqrt{1 - \sin^2 \alpha \sin^2 \beta}} \quad (15)$$

This means that in the parallel direction $\cos \xi$ becomes

$$\cos \xi = \frac{(\cos \phi \sin \alpha - \cos \beta \cos \alpha \sin \phi) \sin \theta}{\sqrt{1 - \cos^2 \alpha \sin^2 \beta}} \quad (16)$$

while in the perpendicular it is

$$\cos \xi = \frac{(\cos \phi \cos \alpha \cos \beta + \sin \alpha \sin \phi) \sin \theta}{\sqrt{1 - \cos^2 \alpha \sin^2 \beta}} \quad (17)$$

The result is that $\sigma_{\parallel}$ and $\sigma_{\perp}$ become

$$\sigma_{\parallel} = k \frac{p}{p_0} \frac{1}{(E_0 - E)} \frac{(p_0 \sin \alpha \cos \beta - p(\cos \phi \sin \alpha - \cos \beta \cos \alpha \sin \phi) \sin \theta / D)^2}{|\vec{p} - \vec{p}_0|^4} \quad (18)$$

$$\sigma_{\perp} = k \frac{p}{p_0} \frac{1}{(E_0 - E)} \frac{(p_0 \cos \alpha - p(\cos \phi \cos \alpha \cos \beta + \sin \alpha \sin \phi) \sin \theta / D)^2}{|\vec{p} - \vec{p}_0|^4} \quad (19)$$

$$\text{with } D = \sqrt{1 - \cos^2 \alpha \sin^2 \beta}$$

$$\text{Now } |\vec{p} - \vec{p}_0|^4 = [p_0^2 + p^2 - 2p_0 p (\cos \theta_0 \cos \theta + \sin \theta_0 \sin \theta) \cos \phi]^2$$

$$\text{where } \cos \theta_0 = \sin \alpha \sin \beta$$

$$\text{and } \sin \theta_0 = \sqrt{1 - \sin^2 \alpha \sin^2 \beta}$$

$J_{\parallel}$ and $J_{\perp}$ can be found by integrating the cross sections (18) and (19) over the momentum p_0 after they have been weighted by a

velocity distribution function $f(p_o, \alpha)$. This is:

$$J_{11} \sim \int \sigma_{11T} p_o^3 f(p_o, \alpha) \sin \alpha \, d\alpha \, d\beta \quad (20)$$

$$J \sim \int \sigma_{1T} p_o^3 f(p_o, \alpha) \sin \alpha \, d\alpha \, d\beta \quad (21)$$

where

$$\begin{aligned} \sigma_{11T} &= \int T_{11} \sin \theta \, d\theta \, d\phi \\ \sigma_{1T} &= \int \sigma_1 \sin \theta \, d\theta \, d\phi \end{aligned}$$

An anisotropic velocity distribution of the form

$$f(p_o, \alpha) = c \exp\left(-\frac{1}{2} \frac{p_o^2}{m} (\cos^2 \alpha / kT_{11} + \sin^2 \alpha / kT_1)\right) \quad (22)$$

will be used with c as a normalization constant.

The integration will be done numerically.

ESTIMATES OF THE PLASMA TEMPERATURE BY INTENSITY RATIO

S. N. Golovato

There exist several methods for estimating the plasma temperature by observing the relative intensities of certain wavelengths of light emitted by the plasma. The applicability of these methods to the helium plasma in the magnetic mirror was investigated and estimates of the plasma temperature were made using one of the methods. The confining magnetic field, the microwave heating power and the pressure were varied independently and the effects on the temperature were observed. The effect on temperature when off-resonance heating was applied to the plasma was also recorded.

The Measuring Apparatus (Fig. 9)

The measurements were made using a monochromator and photomultiplier tube. The output of the photomultiplier was recorded on a chart recorder. By this method, the average intensity of the spectral lines was measured. The range of the photomultiplier response was 3000-6000 Å°. This was of sufficient range to find the particular lines of helium that were being sought. The sensitivity of the photomultiplier could be varied by altering the voltage to the tube or the slit width of the monochromator. The monochromator was capable of increments as small as 0.1 Å°. Either one wavelength could be viewed or any portion of the optical spectrum could be scanned. Since the photomultiplier response was a negative going signal, a biasing battery was used to obtain a net positive voltage to which the chart recorder could respond. It

Fig. 9 Measuring Apparatus

was found that the fluorescent lighting in the lab had a significant effect on intensities so all measurements were done with the lights out.

Determination of the Plasma Temperature

An estimate of the plasma temperature can be made using the fact that the relative intensities of spectral lines from two different ionic states of a given atom will generally be a function of temperature.¹ In this particular case, lines of neutral helium (HeI) and singly ionized helium (HeII) could be easily treated theoretically to yield a temperature estimate.

Another method involves the relative intensities of a helium singlet and triplet.^{2,3} This method makes use of experimental data on cross sections for the excitation of certain singlet and triplet lines. Particular information is available in the form of a curve of the intensity ratio of a helium triplet at $4713 \text{ \AA}$ to helium singlet at $4921 \text{ \AA}$ versus temperature. (Fig. 10)¹

By scanning the entire range of the monochromator it was found that only HeI lines were present, including those at $4713 \text{ \AA}$ and $4920 \text{ \AA}$ (Fig. 11). It was therefore necessary to adopt the second method to determine the temperature.

There are three important limitations to this method. First, the cross section data used to produce the intensity ratio-temperature curve neglected the consideration of metastable states of helium. Their effect, if large, could cause the curve to be invalid.² In the derivation of this method, it was assumed that the plasma has a Maxwellian velocity distribution, and that it is in local thermal equilibrium. Neither of these conditions are met

Fig 10

Fig 11

by the plasma being observed. Thus any temperature derived by this method can only be taken as an estimate. But even as an estimate, it can still yield information as to how the temperature changes when other plasma parameters are varied.

It is important to understand exactly what temperature is being estimated. The plasma is formed by microwave pulses which ionize helium atoms. Thus there are populations of neutral helium, helium ions, cold electrons still tied to these atoms and ions, and extremely hot free electrons. These hot electrons collide with the atoms and ions exciting electrons and sometimes freeing them. Since no HeII lines were observed, the electron in singly ionized Helium is not being appreciably excited. Apparently, hot electrons collide mostly with neutrals, indicating that the neutral population is much greater than the ion population. Also, during the inter-pulse period, the hot electrons cool and when they collide with an ion, they will recombine. Thus, the sources of the light emitted by the plasma are the recombining electrons emitting radiation as they fall to lower energy states in the atom, and the excited, though never free, electrons in the atom doing the same thing. The intensity of a line was compared with the time of occurrence of the microwave pulses. It was observed that the light intensity was maximum slightly after the pulse occurred. This is when recombination will occur, indicating that recombining electrons are the major source of the light.

Since the light is emitted basically by excited neutrals in a plasma of neutrals, ions, and cold, recombining electrons, we will

assume that the temperature estimate can be applied to all of these populations except the hot electrons. An approximate thermal equilibrium may exist and the temperature estimate may not be too unreliable under these conditions.

Results of Measurements

The temperature was found to vary between 35-43 eV ($4-5 \times 10^5$ K). A parametric study was made with the magnetic field, pressure and microwave power as the parameters. Each parameter was varied while the other two were held constant. For both pressure and power variations, the measured temperature remained approximately constant, except when they were lowered to the point where the plasma was extinguished (Figs. 12, 13). At these lower ranges, the temperature dropped sharply as would be expected. The variation of the magnetic field produced a temperature maximum at 54-54.5 mV. (Fig. 14).

The effect of off-resonance heating on the temperature was also investigated. Microwave radiation below cyclotron resonance was applied to the plasma with pressure, resonance power and magnetic field held constant. The power of the off-resonance heating was then varied. It was found that the temperature increased as the power was increased, until the plasma was extinguished. This occurred at three different values of magnetic field (Fig. 15). The temperature was found to increase to over 50 eV for magnetic field equal to 54.5 mV. This result is interesting because it indicates that, rather than extinguishing the plasma, the off-resonance heating is somehow dispersing it which is in agreement with previous models for lower off resonance heating. It may be

Fig. 12

Fig 13

Resonance Power = .15 mW

Pressure = 6×10^{-4} Torr

Magnetic Field = ○ 54.5 mV

□ 55.62 mV

x 52.08 mV

Fig 15

that the hot electrons are thrown out of the chamber, and therefore no plasma can be formed. The following observation backs up this supposition. The plasma can be viewed through two ports, one in the central chamber and one to the side, past a perforated copper plug. In normal operation, plasma can be seen through the central port only. But as the off-resonance power was increased, the plasma disappeared from the center of the chamber, but could now be seen to appear through the side port, which was beyond the mirror throats. X-ray flux also was produced in this region. Apparently, the hot electrons were thrown out of the center of the chamber and ionized the helium in the side chamber. Further increase in power put out the plasma completely, both inside and outside the mirror region.

MEASURE OF PLASMA ION TEMPERATURE BY LINE BROADENING

P. A. Raimbault

Ion temperature can also be measured by line broadening with the use of a monochromator. In order to understand this process we must examine the different causes of line broadening. Some of these are:

1. Broadening due to the monochromator itself.

This can be eliminated by closing the entrance slit until the width of the line remains constant.

2. Natural broadening.

This is a characteristic of the line itself and is usually negligible with respect to the other broadenings. ($\Delta\lambda \sim 10^{-4} \text{ \AA}$)

3. Stark broadening.

This process is due to collisions in the plasma and is related to the density. Stark broadening gives a Lorentzian shape to the line. The broadening is insignificant for densities less than 10^{14} particles/cm³.

4. Doppler broadening.

This is due to the shift in line frequency produced by the Doppler effect on moving radiating particles; hence this broadening must be temperature dependent.

In this case the line will have a gaussian shape, viz.,

$$I(\Delta\lambda) = \frac{I_t}{\pi^{1/2} \Delta\lambda_D} \exp\left(-\left(\frac{\Delta\lambda}{\Delta\lambda_D}\right)^2\right]$$

where I_t is the total line intensity.

The expression for the line half width is given by

$$\Delta\lambda_{1/2} = 7.16 \times 10^{-7} \lambda (T/\mu)^{1/2}$$

T is the temperature in $^{\circ}\text{K}$ of the particles in the plasma (ions or neutral atoms can be considered if we make the assumption that these two species thermalize rapidly).

μ is the atomic mass and $\mu = 4$ for helium.

An experimental observation of the helium line $\lambda = 5015 \text{ \AA}$ in helium when ECRH was used, $\Delta\lambda_{1/2}$ was found to be equal to $0.4 \text{ \AA}$. This implies $T_1 = 5 \text{ eV}$. which gives a reasonable result.

CALCULATION OF EIGENVALUES OF A PLASMA IN A MICROWAVE
CAVITY CONSIDERING THE BOLTZMANN EQUATION

R. T. Pedley and J. L. Shohet

Upon attempting to solve for k from the dispersion relation (Eq. 84) derived in Quarterly Progress Report No. 17 it was found that the equation was dimensionally incorrect. It was found that equation 84 should read

$$k^2 = \mu_0 \epsilon_0 \omega^2 + \omega \omega_p^2 \mu_0 \epsilon_0 \int_{-\infty}^{\infty} \frac{f_0(\vec{v})}{\vec{k} \cdot \vec{v} - \omega} d\vec{v} \quad (23)$$

continuing then, assuming $\vec{k}$ is parallel to $\vec{v}$, then

$$k^2 = \mu_0 \epsilon_0 \omega^2 + \mu_0 \epsilon_0 \omega \omega_p^2 \frac{1}{k} \int_{-\infty}^{\infty} \frac{f_0(\vec{v})}{v - \frac{\omega}{k}} dv \quad (24)$$

Assume now that the distribution $f_0(\vec{v})$ is Maxwellian, that is

$$f_0(\vec{v}) = \left(\frac{m}{2\pi kT}\right)^{3/2} \exp\left(\frac{-mv^2}{2kT}\right) 4\pi v^2$$

Also, assume that f_0 is a function of the complex variable v

$$F(v) = \int_{-\infty}^{\infty} \frac{f_0(v)}{v - \frac{\omega}{k}} dv \quad (25)$$

which has a singularity at $v = \frac{\omega}{k}$. With the restriction that $k > 0$ and $I_m \omega > 0$, then by use of the Cauchy Residue Theorem, Equation (3) becomes

$$F\left(\frac{\omega}{k}\right)_{\text{contour 1}} = F\left(\frac{\omega}{k}\right)_{\text{contour 2}} + 2\pi i f\left(\frac{\omega}{k}\right)$$

Assuming F has no other singularities, contour 2 may be pushed to infinity. Thus equation (24) becomes

$$k^2 = \mu_0 \epsilon_0 \omega^2 + \omega \omega_p^2 \omega_0 \epsilon_0 \frac{1}{k} 2\pi i \left[\left(\frac{m}{2\pi T} \right)^{3/2} \exp\left(\frac{-m}{2\pi T} \frac{\omega^2}{k^2} \right) 4\pi \frac{\omega^2}{k^2} \right] \quad (26)$$

which is a transcendental equation that can be solved for k for various values of ω by iterative techniques on the computer. It was found that some of the parameters required scaling to obtain meaningful results. The following values were used

$$\omega_p = \frac{q^2 n}{m \epsilon_0} = 5.06 \times 10^5$$

which corresponds to $n \sim 10^9$ particles per meter³.

$$\alpha = \frac{m}{2\pi T} = 1.0 \times 10^{-16}$$

which corresponds to $T = 27.6$ kev.

The program basically takes equation (26) which says that k is equal to some function of k . It then iterates through values

of ω and k until it finds a combination where the solved value of k equals the assumed value of k and prints these values out.

From the previous report, considering Maxwell's equations and the boundary conditions of the plasma in the cavity, a set of linear homogeneous equations in 6 unknowns can be obtained. The resulting system of equations has a non-trivial solution only when the system 6×6 determinant is set equal to zero. The program for this is also being developed at this time. This should eventually be extended to anisotropic energy distributions.

References

- 1) S. Huddleston and S. L. Leonard, Plasma Diagnostic Techniques
- 2) Glasstone and Lorberg, Controlled Thermonuclear Reactions
- 3) G. Herzberg, Atomic Spectra and Atomic Structure
- 4) Striganov and Sventitskii, Tables of Spectral Lines of Neutral and Ionized Atoms