TITLE OF PAPER RESIN FUEL PARTICLES FOR HIGH-TEMPERATURE GAS-COOLED REACTORS*

AUTHORS	Complete Business Mail Address	ACS Member?	Division Member?	App. Chem. Eng. or Phys.?
<u>M. D. Silverman</u>	Oak Ridge National Laboratory Union Carbide Nuclear Division P. O. Box X Oak Ridge, Tennessee 37830	Yes	No	Yes
C. B. Pollock		No	No	Materials

*Research sponsored by the U.S. Atomic Energy Commission under contract with Union Carbide Corporation.

Work done at

Plan ACS _____ nonACS _____ publication. Where? _____ No _____ Uncertain ☒

Presentation requires projector: 2x2" (35 mm) ☒ 3 1/2x4" (standard) _____ Overhead _____ Vu-Graph _____ Film: 8 mm _____ 16 mm _____ Sound _____ Other equipment (specify) _____

ABSTRACT: 200 words or equivalent. TITLE OF PAPER, Authors' Names, Addresses with Zip Code. One-Line Space. Abstract. Single-space typing. Use full width of ruled area below.

DO NOT
USE

DO NOT
USE

RESIN FUEL PARTICLES FOR HIGH-TEMPERATURE GAS-COOLED REACTORS. M. D. Silverman and
C. B. Pollock, Metals and Ceramics Division, Oak Ridge National Laboratory,
Oak Ridge, Tennessee 37830

Fuel particles for high-temperature gas-cooled nuclear reactors have been prepared from weak-acid exchange resins. Loading with uranium is accomplished by using UO_3 in slurry form and heavy metal loading ensures stability of the microspheres during subsequent carbonization and heat treatment, which is performed under an inert gas in a fluidized bed. Water is largely removed endothermally between 100 and 200°C, and breakup of the polymer occurs in the 300 to 350°C range. Carbonization along with decarboxylation takes place exothermally from 350 to 450°C, with appreciable formation of carbon monoxide and carbon dioxide. Carbonization is largely completed by 600°C, with minor loss of hydrogen and CO on additional heating to 1000°C, yielding spheres of approximate overall composition $UO_{2+x} + 5C$. Heat treatment above 1200°C is used to remove oxygen and gradually convert the fuel phase from UO_2 to UC_2 . The ratio of oxide to carbide and the amount of excess carbon in the kernels can be adjusted by varying the time and temperature of the heat treatment. The major advantages of the resin-prepared kernels over those prepared by conventional methods such as the sol-gel process and high-temperature fusion techniques are (1) inexpensive raw materials available from several sources, (2) excellent control of sphere size, shape, and quality established before fuel loading, (3) good reproducibility of heavy metal loading, (4) relatively easy remote loading ^{233}U , (5) reduced importance of variations in buffer coating thickness, and (6) potential improved resistance to thermal gradient-induced kernel migration.

DO NOT
USE

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT TO PERSON NAMED IN ACS DIVISIONAL DEADLINES PUBLISHED (JUNE & DEC.) IN OPEN

PAPER RESIN FUEL PARTICLES FOR HIGH-TEMPERATURE GAS-COOLED REACTORS*

Complete Business Mail Address

ACS
Member?Division
Member?Author or Contributor
Chemical Engineer?

Oak Ridge National Laboratory
Union Carbide Nuclear Division
P. O. Box X
Oak Ridge, Tennessee 37830

Yes

No

Yes

No

No

Materials

Research sponsored by the U.S. Atomic Energy Commission under contract with Union Carbide Corporation.

For ACS publication? Where?

No

Uncertain ☒ X

Requires projector: 2x2" (35 mm) ☒ 4x4" (graph) ☐ Overhead ☐ Graph ☐ Film 8 mm
and _____ Other equipment (specify) _____
10 words or equivalent. TITLE OF PAPER, Author Name, Address, and Zip Code. Outline, Synopsis,
and space typing. Use full width of ruled area.

FUEL PARTICLES FOR HIGH-TEMPERATURE GAS-COOLED REACTORS. M. D. Silverman and
Pollock, Metals and Ceramics Division, Oak Ridge National Laboratory,
Tennessee 37830

Articles for high-temperature gas-cooled nuclear reactors have been prepared using acid exchange resins. Loading with uranium is accomplished by using UO_2 in the resin and heavy metal loading ensures stability of the microspheres during sublimation and heat treatment, which is performed under an inert gas in a fluidized bed. Water is largely removed endothermally between 100 and 200°C, and breakup of the resin occurs in the 300 to 350°C range. Carbonization along with decarboxylation occurs exothermally from 350 to 450°C, with appreciable formation of carbon monoxide and carbon dioxide. Carbonization is largely completed by 600°C, with minor loss of CO on additional heating to 1000°C, yielding spheres of approximate overall composition $UO_{2-x} + 5C$. Heat treatment above 1200°C is used to remove oxygen and gradually convert the fuel phase from UO_2 to UC_2 . The ratio of oxide to carbide and the amount of carbon in the kernels can be adjusted by varying the time and temperature of the heat treatment. The major advantages of the resin-prepared kernels over those prepared by conventional methods such as the sol-gel process and high-temperature fusion techniques are (1) expensive raw materials available from several sources, (2) excellent control of size, shape, and quality established before fuel loading, (3) good reproducibility of heavy metal loading, (4) relatively easy remote loading ^{235}U , (5) reduced impurities in buffer coating thickness, and (6) potential improved resistance to thermal gradient-induced kernel migration.

RESIN FUEL PARTICLES FOR HIGH-TEMPERATURE GAS-COOLED REACTORS*

by

M. D. Silverman and C. B. Pollock

Metals and Ceramics Division, Oak Ridge National Laboratory
Oak Ridge, Tennessee 37830

High-temperature gas-cooled nuclear reactors¹ contain a graphite core cooled by high pressure helium. The fuel elements, located within holes drilled into hexagonal graphite blocks, contain the fissile material in the form of coated microspheres, which are bonded with various materials and heated to form the solid fuel rods. Heretofore, the kernels of these coated particles have been made by conventional methods such as the sol-gel process (where sol drops are gelled in an organic solvent) or by high temperature fusion techniques. The uranium oxide or carbide kernels produced in these processes usually have a high density (approx 10 g/cm³) and a low surface area (approx 0.5 m²/g), and thick carbon buffer coatings are required to accommodate fuel swelling and fission-gas release. By contrast, resin derived particles have been prepared at ORNL in which the kernels are much more porous ($\rho \approx 3.5$), and have a much higher surface area (approx 100 m²/g), thereby lessening the restrictions on coatings. In this paper the preparation of these porous kernels from polymeric organic cation exchangers and the advantages of this type of microsphere over that produced by conventional methods for use in nuclear reactors are discussed.

The major requirements for a satisfactory fuel microsphere are proper size range, size uniformity, good sphericity, and internal integrity. Moreover, control of impurities and availability from numerous vendors at reasonable cost are also important considerations. For resin derived kernels most of these requirements can be met at the manufacturer's level, thereby reducing costs and chemical problems during the later processing stages.

The resins used in this work are addition copolymers prepared from vinyl-type monomers. These polymers have a much higher chemical and thermal stability than the older condensation polymers such as the phenol-formaldehyde types. Moreover, addition polymerization has the advantage that the degree of cross-linking and particle size of the resins can be adjusted more easily.

Strong-acid cation exchangers such as Dowex 50 and Amberlite IR-120 have been loaded with uranium, carbonized, and heat treated to form fissile microspheres. The strong-acid cation exchangers that have been used are polystyrenes cross-linked with divinyl benzene. Sulfonic acid groups are introduced after polymerization by treatment with concentrated sulfuric acid or chlorosulfonic acid. Carbonization and subsequent heat treatment can produce uranium carbosulfide or uranium carbide spheres. The resins are thermosetting since they are formed from aromatic compounds and they yield fine-grained spherical microspheres on heating, whether in the acid or uranium-loaded form.

In contrast to the strong-acid type, the weak-acid resins are thermoplastic and the acid form fuses on heating. However, after loading with uranium the resin becomes thermosetting on heating, yielding porous, coarse-grained microspheres with high surface area. Uranium has been loaded on weak-acid cation exchangers such as Amberlite IRC-72 and Relite CC (Ionac). These type exchangers, also addition copolymers, are prepared from acrylic or methylacrylic acid with divinyl benzene as the cross-linking agent. Carbonization and heat treatment of these uranium-loaded resins can be

*Research sponsored by the U.S. Atomic Energy Commission under contract with the Union Carbide Corporation.

adjusted to yield kernels which are uranium oxide, carbide, or a mixture of the two phases, each in a matrix of carbon. Because the presence of sulfur is undesirable in process systems and is not easily eliminated from the uranium-loaded strong-acid resins during fuel preparation, recent work has concentrated on the weak-acid ion exchangers.

The process for loading uranium on a weak-acid ion exchanger is summarized by the following equations:

Since nitric acid is liberated by the reaction between the resin and the uranyl nitrate, UO_3 (acting as a base) in slurry form is added to the system to neutralize the acid formed and thus to obtain maximum loading of uranium. A detailed study of this system² indicated that Amberlite IRC-72 gave the best results of all the commercial weak-acid resins tested. The carbonization of the loaded uranium microspheres was investigated, using three different types of instruments: the differential thermal analyzer (DTA), the thermal gravimetric analyzer (TGA), and the gas chromatograph. The data obtained were interpreted as follows:

1. Most of the water present is removed endothermically between 100 and 200°C; small amounts entrapped within the particles and any water formed by decomposition are not removed completely until temperatures of about 400°C are attained.

2. A minor endothermic reaction in the 300 to 350°C range is probably due to breakup of the polymer (carbon-to-carbon bonds), yielding allyl radicals which subsequently form light unsaturated hydrocarbons, such as ethylene, acetylene, and propylene.

3. Broad exotherms in the 350 to 450°C range indicate carbonization takes place along with some decarboxylation and carbon monoxide and carbon dioxide are both formed in appreciable amounts.

4. A small endotherm in the 475 to 525°C range may be due to depolymerization of heavy organic fractions.

5. Carbonization is largely completed by 600°C, since there is only a minor loss in weight upon additional heating to 1000°C, the loss probably resulting from the elimination of residual hydrogen and carbon monoxide. The overall composition of the carbonized microspheres, after heating to 1000°C, is approximately $\text{UO}_{2+x} + 5\text{C}$.

Carbonization and subsequent heat treatment at 1000 to 2000°C of the uranium-loaded resin are both performed under an inert atmosphere in fluidized-bed equipment. Conversion of uranium dioxide to uranium carbide occurs readily above 1300°C. The reaction which takes place³ is:

The extent of the reaction is time and temperature dependent. Since CO is removed by the fluidizing inert gas stream, the reaction will proceed to the right unless the CO pressure is fixed in the fluidizing gas.

Kernel migration into the coating, the "amoeba effect," a result of a temperature gradient imposed across the particle, is occasionally observed during irradiation. This type of attack has been observed with either UO_2 or UC_2 prepared as the dense fuel phase, but the rate of migration appears

lower for the carbide at temperatures expected in a large reactor. A model for the "amoeba effect" involving UO_2 kernels, discussed by T. B. Lindemer,⁴ is based on the $2\text{CO} \rightleftharpoons \text{CO}_2 + \text{C}$ equilibrium, which provides a mechanism for carbon transport from the hot to the cold side of the fuel kernel. It is believed that the addition of some carbide to an oxide kernel will lower the rate of carbon transport as a result of fixing the CO pressure in equilibrium over the carbide phase. Approximately 1% carbide is produced per 10% burnup of the fissile atom under irradiation, and since the desired burnup is $\geq 90\%$, it is believed that particle attack by the above mechanism can be alleviated by preparing resin-derived oxide kernels in which the initial uranium carbide content is controlled at $\geq 10\%$, by adjustment of the appropriate variables during the heat treatment. This transformation of uranium oxide to carbide has been studied by following the changes in composition analytically and by x-ray diffraction powder pattern analysis.

The advantages of the resin-prepared kernels over those produced by conventional techniques are the following:

1. The raw materials are inexpensive and available from several sources.
2. Control of particle size and shape, as well as sphere quality, is established before adding the fuel.
3. Good reproducibility of heavy metal loading.
4. Remote loading of ^{233}U is simplified for recycled fuel.⁵
5. Thick buffer coatings are not needed, thus eliminating a major source of undesirable variations in coating thickness.
6. Kernels up to 300 μm are easily prepared, making fuel rod fabrication easier.
7. This fuel form promises to be more resistant to the "amoeba" effect.

Thus, it is clearly evident that microspheres prepared from uranium-loaded weak-acid cation exchange resins show considerable promise for use as fissile fuel particles in high-temperature gas-cooled nuclear reactors.

REFERENCES

1. T. D. Gulden et al., *Nucl. Technol.* 16: 100 (1972).
2. P. A. Haas, *HTGR Fuel Development: Use of UO_3 to Load Cation Exchange Resin for Microsphere Preparation*, ORNL-TM-3817 (September 1972).
3. J. M. Leitnaker and T. G. Godfrey, *J. Chem. Eng. Data* 11(2): 392 (1966).
4. T. B. Lindemer, *Metals and Ceramics Div. Annu. Prog. Rep. June 30, 1972*, ORNL-4820, pp. 107-108.
5. K. J. Notz, *Chemical Technology Div. Annu. Prog. Rep. Mar. 31, 1972*, ORNL-4794, pp. 47-50.

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.