Copy No 1

MASTER

AP Note-426

PATENT CLEARANCE OBTAINED. RELEASE TO
THE PUBLIC IS APPROVED. PROCEDURES
ARE ON FILE IN THE RECEIVING SECTION.

ALCO PRODUCTS, INC.
NUCLEAR POWER ENGINEERING DEPARTMENT

MAY 19 1965

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

NOTES ON PLACZEK'S THEOREM

$$P_0 = \rho_{av} / \rho_{\infty}$$

by

Dr. R. L. Murray
North Carolina State College

Approved by:

E. W. Schrader, Acting Project Engineer

Issued: June 20, 1962

Contract No. AT(30-1)-2639
with U.S. Atomic Energy Commission
New York Operations Office

ALCO PRODUCTS, INCORPORATED
Nuclear Power Engineering Department
Post Office Box 414
Schenectady, New York

AEC LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights:

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to this employment or contract with the Commission, or his employment with such contractor.

ALCO LEGAL NOTICE

This report was prepared by Alco Products, Incorporated in the course of work under, or in connection with, Contract No. AT(30-1)-2639, issued by U. S. Atomic Energy Commission, NYOO; and subject only to the rights of the United States, under the provisions of this contract, Alco Products, Incorporated makes no warranty or representation, express or implied, and shall have no liability with respect to this report or any of its contents or with respect to the use thereof or with respect to whether any such use will infringe the rights of others.

DISTRIBUTION

External
Copies

- 1-3 New York Operations Office
U. S. Atomic Energy Commission
376 Hudson Street
New York 14, New York

Attention: I. M. Adler (2)

Attention: Library (1)
- 4-6 U. S. Atomic Energy Commission
Washington 25, D. C.

Attention: Chief, Water Systems Project Branch,
(Army Reactors)
Division of Reactor Development
Mail Station F-311
- 7 Idaho Nuclear Power Field Office
P. O. Box 2106
Idaho Falls, Idaho
- 8-9 Office of the Chief of Engineers
Department of the Army
Building T-7
Washington 25, D. C.

Attention: Chief, Projects Branch
Nuclear Power Division
- 10-12 Nuclear Power Field Office
U. S. Army Engineer Reactors Group
Fort Belvoir, Virginia

Attention: Chief, Nuclear Power Field Office
- 13 Nuclear Power Field Office
U. S. Army Engineer Reactors Group
Fort Belvoir, Virginia

Attention: O.I.C. SM-1
- 14 Chief, U. S. Army Reactors Group
Fort Greely, Alaska
APO 733
Seattle, Washington

Attention: O.I.C. SM-1A
- 15 Commanding Officer
U. S. Army Polar Research & Development Center
Fort Belvoir, Virginia

Attention: Nuclear Power Officer

External
Copies

- 16 Union Carbide Nuclear Corporation
Oak Ridge National Laboratory
Y-12 Building 9704-1
P. O. Box 777
Oak Ridge, Tennessee

Attention: L. D. Schaffer
- 17 Alco Products, Inc.
Post Office Box 145
Fort Belvoir, Va.

Attention: W. C. Best
- 18-19 R. L. Murray
North Carolina State College
Raleigh, N. C.

Internal
Copies

- 20 K. Kasschau
21 J. G. Gallagher
22 J. F. Haines
23 E. W. Schrader
24-25 B. E. Bohe
26 W. T. Williams
27 E. F. Clancy
28 B. E. Fried
29 F. G. Moote
30-33 NPED File

TABLE OF CONTENTS

	<u>Page</u>
Introduction	1
Numerical Data	9
Comments	10
Appendix	i

LIST OF FIGURES

<u>Figure</u>	<u>Title</u>	<u>Page</u>
1	Comparison of Placzek's P_0 and Diffusion Theory for Spheres in H_2O .	12
2	Comparison of Placzek's P_0 and Amoyal-Benoist Theory for Spheres in H_2O .	13

NOTES ON PLACZEK'S THEOREM, $P_0 = \frac{\rho_{AV}}{\rho_{\infty}}$

The problem of determination of neutron flux distribution in a strongly absorbing object surrounded by a moderator has challenged reactor theorists for many years. The general neutron transport theory is applicable but unwieldy.

Widespread use is made of the simple theorem* displayed, but there is not a general understanding of its implications. In this note, a careful description of its form and ingredients is given, along with discussion of its application and limitations.

First, the escape probability P_0 is defined. Visualize a uniform purely absorbing body without concavities that emits monoenergetic neutrons isotropically and uniformly. The substance has a macroscopic cross section Σ_a . On first flight from their point of origin, a fraction P_0 of the neutrons escapes from the body, a fraction $1 - P_0 = P_c$ collides. The definition of P_0 does not consider the fate of the particles either upon collision inside or after flow

*

See K. M. Case, F. de Hoffmann, and G. Placzek, Introduction to the Theory of Neutron Diffusion, Vol. I, Los Alamos, June 1953 (Superintendent of Documents, Washington 25, D.C.)

through the boundary. Thus P_0 for first flight neutrons is the same whether the cross section were Σ_a , Σ_s or Σ .

Second, we visualize the same body located within an infinite medium in which there is an "isotropic bath" of neutrons.

The flux and density everywhere are uniform (see sketch) and the angular distribution is isotropic. This situation would of course obtain in a medium with uniform isotropic source and uniform absorption cross section everywhere (including the body). Let us relax this ideal to the extent of allowing the flux in the body to be depressed (see sketch) because of an excess absorption, such that its average is $\bar{\phi}$, while at great distances from the object the flux is ϕ_{∞} .

Placzek's theorem states that the ratio of flux in the body to the distance flux is numerically equal to the escape probability of the body, i.e.

$$\frac{\bar{\phi}}{\phi_{\infty}} = P_0$$

An obvious problem is that any flux depression tends to render the flux anisotropic. However, if the bulk of the entering neutrons come from great distances, or if the body is very small, this anisotropy will not cause a serious error. The general derivation is based on a chord method, as described by Case, et al. A simple diffusion theory approach is presented here instead. Suppose that the flux outside is constant right up to the surface, but dips within, as sketched below.

The inward-directed surface current density is

$$j = -\frac{\phi_{\infty}}{4}$$

Inside, with an average flux $\bar{\phi}$, the rate of absorption per unit volume is $\bar{\phi}\Sigma_a$. Now if no neutrons traverse the body,

those that enter the surface S are absorbed in the volume V , i.e.

$$j_e S = \bar{\phi} \Sigma_a V$$

or

$$\frac{\bar{\phi}}{\phi_\infty} = \frac{S}{4\Sigma_a V}$$

The right side is the escape probability for a large purely absorbing body, as is proved below. Let the uniform source strength in a large body (of many mean free paths in dimension) be Q . The escaping surface current is

$$j_e = \int_V \frac{Q e^{-\Sigma_a r}}{4\pi r^2} \cos\theta dV$$

by analogy with the usual derivation of Fick's law, where θ is the angle between a ray and the normal to the surface. Letting $dV = 2\pi r^2 dr \sin\theta d\theta$ and integrating on θ from 0 to $\pi/2$, r from 0 to a large value ($\approx \infty$) we obtain

$$j_e \approx \frac{Q}{4\Sigma_a}$$

Now the total number of neutrons produced is QV , the total escaping is $j_e S$, hence the escape probability is

$$P_e = \frac{\frac{QS}{4\Sigma_a}}{QV} = \frac{S}{4\Sigma_a V} \quad \text{Q.E.D.}$$

It will be noted that we have required two incompatible conditions in the derivation, namely that the object is

optically large, but that it does not render the flux anisotropic. The derivation thus cannot be considered as more than indicative.

In order to obtain some appreciation of the comparison of the theorem's predictions with those of transport theory, we consider the conventional P_1 approximation solution of a two region sphere-moderator problem. The flux distribution for medium 0 (absorber) and medium 1 (moderator) are

$$\phi_0 = A \frac{\sinh \kappa_0 r}{\kappa_0 r} + \frac{S_0}{\Sigma_{a0}}$$

$$\phi_1 = \frac{C e^{-\kappa_1 r}}{\kappa_1 r} + \frac{S_1}{\Sigma_{a1}} \quad \phi_1(\infty) = \frac{S_1}{\Sigma_{a1}}$$

where sources are allowed in each medium. The application of continuity condition in the form

$$\phi_0(a) = \phi_1(a)$$

$$-D\phi_0'(a) = -D_1\phi_1'(a)$$

leads to the expressions for A and C, and the flux ratio

$$\frac{\bar{\phi}_0}{\phi_1(\infty)} = \frac{\Sigma_{a1}}{\Sigma_{a0}} \frac{S_0}{S_1} + \frac{3}{(\kappa_0 a)^2} \left(1 - \frac{\Sigma_{a1}}{\Sigma_{a0}} \frac{S_0}{S_1} \right) \left[\frac{1}{\kappa_0 a \coth \kappa_0 a - 1} + \frac{D_0}{D_1(1 + \kappa_1 a)} \right]^{-1}$$

The derivation appears in the Appendix. In the P_1 approximation with isotropic scattering $D = 1/3(\Sigma_a + \Sigma_s)$ and $\kappa^2 = \Sigma_a/D = 3\Sigma_a/(\Sigma_a + \Sigma_s)$.

The diffusion theory result would be expected to be accurate only for the region $\Sigma_{a0}a \simeq 0$. For more strongly absorbing spheres, higher order transport methods are required, in general. An indication of trends can be obtained however by application of the Amouyal-Benoist method* which is a simple extension of diffusion theory that gives results comparable to transport theory in heterogeneous cell problems. The approach assumes, for strongly-absorbing objects embedded in a moderator, that the surface current is equal to the volume absorption rate,

$$4\pi a^2 |j_1| = \bar{\Sigma}_{a0} \frac{4\pi a^3}{3} \quad \text{or} \quad |j_1| = \frac{\bar{\Sigma}_{a0} a}{3}$$

with the diffusion theory flux $\phi_1(r)$ and current $j_1 = -D_1 \phi_1'$ being applicable in the moderator. Also the extrapolation distance from the moderator into the body is borrowed from transport theory,

$$\frac{\phi_1(a)}{\phi_1'(a)} = d$$

The moderator flux solution is recast in these terms. Let

$$\phi_1 = \frac{C e^{-\kappa_1 r}}{\kappa_1 r} + \frac{S_1}{\Sigma_{a1}}$$

*

A. Amouyal and P. Benoist, Journ. Nuc. Energy, 6, 79 (1957)

and use the extrapolation distance boundary condition, along with the definition $\phi_{1\infty} = S_1/\Sigma_{a1}$. Straightforward operations (see Appendix) yield the arbitrary constant C and we find

$$\phi_1(a) = \frac{\phi_1(\infty)}{1 + \frac{a}{d(1 + \kappa_1 a)}}$$

The conservation relation is, by Fick's law

$$|j_1| = \frac{\bar{\phi}_0 \Sigma_{a0} a}{3} = \frac{1}{3\Sigma_1} \phi_1'(a) = \frac{1}{3\Sigma_1} \frac{\phi_1(a)}{d}$$

or $\phi_1(a) = \bar{\phi}_0 \Sigma_{a0} \Sigma_1 a d$

Then

$$\frac{\bar{\phi}_0}{\phi_1} = \frac{1}{\Sigma_{a0} a \Sigma_1 d \left[1 + \frac{a}{d(1 + \kappa_1 a)} \right]}$$

Consider the special case of a small black sphere $\Sigma_{a0} a \gg 1$, $a \ll \lambda_1 = 1/\Sigma_1$, for which transport theory* gives an extrapolation distance

$$d \approx \frac{4}{3} \lambda_1$$

Then

$$\frac{\bar{\phi}_0}{\phi_1} \approx \frac{\frac{3}{4\Sigma_{a0}a}}{1 + \frac{3\Sigma_1 a}{4(1 + \kappa_1 a)}}$$

*

B. Davison, Neutron Transport Theory, Oxford Press (1957) page 101.

If also the moderator absorption is weak, $\Sigma_{a1} \ll \Sigma_{s1}$,

then $\kappa_1 \approx \sqrt{3\Sigma_{a1}(\Sigma_{a1} + \Sigma_{s1})} \approx \sqrt{3\Sigma_{a1}\Sigma_{s1}} \approx 0$ and

$$\frac{\bar{\rho}_0}{\rho_1} \approx \frac{\frac{3}{4\Sigma_{a0}a}}{1 + \frac{3\Sigma_{1a}}{4}}$$

However $\Sigma_{1a} = a/\lambda_1 \approx 0$, and

$$\frac{\bar{\rho}_0}{\rho_1} = \frac{3}{4\Sigma_{a0}a}$$

This is the same formula as the limiting approximation for the escape probability of a sphere with $\Sigma_{a0}a \gg 1$.

Numerical Data

Consider water as typical moderator, with $\Sigma_s \approx 3.12$, $\Sigma_a \approx 0.02$, $\kappa_1 \approx \sqrt{3\Sigma_a(\Sigma_a + \Sigma_s)} = 0.4341$. Assume that the sphere has no source, $S_0 = 0$, and has no scattering cross section, but contains a strong absorber with variable Σ_{a0} , and with variable a . Values of $\bar{\rho}_0/\rho_\infty$ as a function of $x = \Sigma_{a0}a$, were computed from the P_1 approximation and from the Amouyal-Benoist method. For limiting diffusion theory cases, the following approximations were used:

$$\begin{array}{lll} y \coth y = 1 + \frac{y^2}{3} & y \ll 1 & y = \kappa_0 a \\ y \coth y = y & y \gg 1 & \end{array}$$

For comparison, the values of P_0 obtained from graphs of the relation* were found:

$$P_0 = \frac{3}{8x^3} \left[2x^2 - 1 + (1 + 2x)e^{-2x} \right]$$

The approximate expression for escape probability at limits are

$$P_0 \simeq 1 - 0.75x \quad x \ll 1$$

$$P_0 \simeq \frac{0.75}{x} \left(1 - \frac{1}{2x^2} \right) \quad x \gg 1$$

The ranges for x and a were taken as 0.01 to 10; Figures 1 and 2 show the results.

Comments

Inspection of the curves shows that the general trend of diffusion theory flux ratio is in accord with the escape probability prediction. Good agreement between simple diffusion theory with Placzek's formula is seen in the region $\Sigma_{a0}a$ small, as would be expected, but large differences occur at $\Sigma_{a0}a$ large. The Amouyal-Benoist method, which provides a distinct improvement on diffusion theory, is seen to match the escape probability theorem extremely well for small black spheres. For $\Sigma_{a0}a > 2$ and $a = 0.01$ cm,

*

Case, et al, pp. 28, 29.

Figure 1 Comparison of Placzek's P_0 and Diffusion Theory $\bar{\phi}_0/\phi_{(0)}$ for Spheres in H_2O

2
2
6

Figure 2

Comparison of Placzek's P_0
and Amouyal-Benoist $\bar{\phi}_0 / \phi_{i(\infty)}$
for Spheres in H_2O

the results are indistinguishable. Higher order transport calculations would be expected to give even better agreement, and such would be recommended to fully settle the matter. It is notable that the flux ratio depends on both sphere radius a and $\Sigma_{a0}a$, while the Placzek expression has a unique dependence on $\Sigma_{a0}a$. The former is the case in any transport theory approximation.

We may view Placzek's theorem as a simple and useful method for computing the flux ratio under conditions of strong absorption where diffusion theory is inadequate and the calculation of exact values would require high order transport theory.

For the estimation of self-shielding in small boron-carbide particles used as burnable poison in fuel plates, the Placzek formula is recommended as a good substitute for transport machine methods.

APPENDIX

P₁ solution for sphere surrounded by infinite moderator.

$$\text{Let } X = \frac{\sinh \kappa_0 r}{\kappa_0 r}, \quad Y = \frac{e^{-\kappa_1 r}}{\kappa_1 r}, \quad \text{and } [X], [Y] \text{ denote}$$

their values at $r = a$. The fluxes are

$$\phi_0 = AX + \frac{S_0}{\Sigma_{a0}}$$

$$\phi_1 = CY + \frac{S_1}{\Sigma_{a1}}$$

Equating fluxes and currents

$$A[X] + \frac{S_0}{\Sigma_{a0}} = C[Y] + \frac{S_1}{\Sigma_{a1}}$$

$$AD_0[X'] = CD_1[Y']$$

Solving simultaneously,

$$\frac{A}{S} = \frac{\frac{1}{[X']} \left(\frac{1}{\Sigma_{a1}} - \frac{S_0/S_1}{\Sigma_{a0}} \right)}{\frac{[X]}{[X']} - \frac{[Y]}{[Y']} \frac{D_0}{D_1}}$$

$$\text{Now } \bar{\phi}_0 = A\bar{X} + \frac{S}{\Sigma_{a0}}$$

$$\text{where } \bar{X} = \frac{1}{V} \int_0^a \frac{\sinh \kappa_0 r}{\kappa_0 r} 4\pi r^2 dr = \frac{3}{\kappa_0^3 a^3} [\kappa_0 a \cosh \kappa_0 a - \sinh \kappa_0 a]$$

Compare with

$$[X] = \frac{1}{\kappa_0 a^2} [\kappa_0 a \cosh \kappa_0 a - \sinh \kappa_0 a]$$

$$\text{to note that } \bar{X} = \frac{3[X']}{\kappa_0^2 a}$$

Also
$$\frac{[X']}{[X]} = \frac{\kappa_0 a \coth \kappa_1 a - 1}{a}$$

$$\frac{[Y']}{[Y]} = -\frac{(1 + \kappa_1 a)}{a}, \quad \phi_{1(\infty)} = \frac{S_1}{\Sigma_{a1}}$$

Then

$$\frac{\bar{\phi}_0}{\phi_\infty} = \frac{\Sigma_{a1}}{\Sigma_{a0}} + \frac{S_0}{S_1} + \frac{3}{\kappa_0^2 a^2} \left[1 - \frac{\Sigma_{a1}}{\Sigma_{a0}} \frac{S_0}{S_1} \right] \left(\frac{1}{\kappa_0 a \coth \kappa_0 a - 1} + \frac{D_0/D_1}{1 + \kappa_1 a} \right)^{-1}$$

Amouyal-Benoist flux distribution

Let the moderator flux be

$$\phi_1(r) = \frac{C e^{-\kappa_1 r}}{\kappa_1 r} + \frac{S_1}{\Sigma_{a1}}$$

and apply the boundary condition at a in the form

$$\phi_1(a) - d\phi_1'(a) = 0$$

Then

$$\frac{C e^{-\kappa_1 a}}{\kappa_1 a} + \frac{S_1}{\Sigma_{a1}} + d \frac{C e^{-\kappa_1 a}}{\kappa_1 a} (1 + \kappa_1 a) = 0$$

Letting $S_1/\Sigma_{a1} = \phi_{1\infty}$ and solving for C ,

$$C = \frac{-\phi_{1\infty} \kappa_1 a e^{-\kappa_1 a}}{1 + \frac{d}{a}(1 + \kappa_1 a)}$$

Then

$$\phi_1(r) = \phi_{1\infty} \left[1 - \frac{\frac{a}{r} e^{-\kappa_1(r-a)}}{1 + \frac{d}{a}(1 + \kappa_1 a)} \right]$$

and

$$\vartheta_1(a) = \frac{\vartheta_1(\infty)}{1 + \frac{a}{d(1 + \kappa_1 a)}}$$