DOE/SF/18862--T1

DE92 017030

FINAL REPORT

NATIONAL LASER USER'S FACILITY GRANT DE-FG03-91SF18862

UNIVERSITY OF ROCHESTER

LABORATORY FOR LASER ENERGETICS

TITLE: Fusion with Highly Spin Polarized HD and D₂

Principal Investigator: Arnold Honig, Physics Dept, Syracuse Univ.

Co-Investigators at LLE: Sam Letzring and Stanley Skupsky

Period: December 14, 1990 - December 13, 1991.

June 29, 1992.

ABSTRACT

During the period of this grant, we carried out a full implementation of transporting a cold (4K) sample to Rochester and inserting it cold into OMEGA. This included filling to 45 atmospheres a parylene-polystyrene target shell with unpolarized deuterium, cryocondensing it at Syracuse, transporting it in our liquid helium transport cryostat by truck to Rochester, retrieving it at Rochester from the cryostat with our cold-transfer apparatus, and finally inserting it cold into OMEGA. Target positioning within OMEGA prior to simultaneous withdrawal of our shroud and insertion of OMEGA's cold shroud was cut short by a helium leak into OMEGA from the OMEGA shroud, which thermally shorted our cold-retrieval system, and threatened warmup and explosion of our shell. A hasty attempt to manipulate the shrouds before accurate sample positioning could be effected resulted in aborting the shot. Otherwise, all phases of the low temperature operations behaved correctly. (Target centering with the shrouds present had previously been carried out at room temperature, and that aspect does not have any significant dependence on temperature). In addition to achieving this first demonstration of the cryogenic procedures for manipulation of frozen targets, we completed construction of the 3.5 m long, 15 mm diameter dilution refrigerator cold-retrieval system. This apparatus strains the technology to its dimensional limits, but nevertheless operates very well. Brushes were designed and tested for reducing the temperature of the outer jacket of the cold retrieval system to near 4K, very necessary in the dilution

refrigerator and desirable even for unpolarized high density targets. Both target-shell-loading permeators (high pressure, 4K; and low pressure, 77K) were utilized for shell-loading, cryocondensation, and non-destructive shell leak-out for reversible target shell loadings. The low pressure, 77K permeator apparatus was modified to measure the tensile strength of the shells through quantitative observation of the explosive or slow-leak-out release of gas from a single shell, using a small volume system and a sensitive Barotron pressure detector. This modification was also applied to the high pressure, cryogenic permeator, for determining the temperature dependence of the tensile strength of the shells. Work was continued on fast temperature excursions through the triple point to liquid D_2 with polarization preservation. A detailed mapping of T_1^H and T_1^D for an HD sample revealed clustering of $J = 1$ impurities at temperature below 200 mK, which causes anomalous increase in the T_1 values. A similar effect has been seen in H_2 , but in this case (HD), since quantum diffusion (ortho-para switching between neighbors) cannot occur, all ambiguity regarding the existence of a new molecular motion quantum transport mode is removed. Because of the more rapid increase of T_1 with time, proton-deuteron dynamic polarization at low fields can be achieved earlier in the polarization process, thus decreasing the time to prepare a polarized target under most conditions.

I. INTRODUCTION

We have been engaged over the past 3 years in an effort to carry out ICF experiments on polarized D in deuterium or HD. This represents a first step towards the goal of imploding polarized $\uparrow\text{D}\uparrow\text{T}$. There is reason to believe this would result in increased reaction yield¹, necessitating only about half the laser driver energy to achieve the same gain² as with unpolarized fuel. Other benefits of polarized D_2 fusion fuel, such as favorable reaction product anisotropies and possible $\uparrow\text{D} - \uparrow\text{D}$ reaction suppression for a neutronless $\uparrow\text{D} - {}^3\text{He}$ reactor are also of interest. In order to carry out this experiment, means of polarizing the deuteron and maintaining the polarization after removal from the 10 mK dilution refrigerator and 13 Tesla magnetic field had to be developed³⁻⁵, and cryogenic procedures never before undertaken had to be invented and implemented. These included cold-entry and retrieval⁶ of samples at temperatures near 4K, above which depolarization would rapidly take place, permeation of polymer targets with the correct isotopic composition for the polarization method to operate efficiently⁷, and permeation of plastic targets to high pressures after which they could be cryocondensed, transported and utilized as a solid, or as a high density, low temperature gas ICF target. These aspects were accomplished and described in detail in our previous final report of last year⁸. This year, we put the entire system together and mated an unpolarized frozen sample with the LLE OMEGA fusion chamber, constructed and tested the cold-retrieval system for the dilution refrigerator which is necessary for employment of

polarized targets, designed and tested a variety of "cold-brushes" for cooling the outer tube of the dilution refrigerator to temperatures near 4K and improving the performance of the cold-retrieval for high density unpolarized targets as well, experimented with a novel technique for determining low temperature tensile strengths of shells, important to our program when we want to gasify the target just prior to laser implosion, and made a broad study of spin-lattice relaxation in HD samples in the concentration range useful for polarization. This led to discovery of a low temperature (millikelvin) molecular transport mechanism in HD which can shorten the time required for producing highly polarized D targets. These phases of our activities are described in the following sections of this report.

II. LOW TEMPERATURE IMPLEMENTATION OF MATING A TARGET TO OMEGA

This experiment puts to test all of the elements of our program except for the high spin polarization. It consists of mounting a polymer shell on a target holder, inserting this into our cryogenic permeator, filling the target shell in incremental stages with deuterium gas to a desired pressure at room temperature (we used 45 atmospheres in this initial experiment), reducing the temperature until the deuterium cryocondenses, evacuating the reservoir gas since the shell will not explode as long as it is in a condensed phase, and storing the frozen sample, kept cold by conduction, in the storage-transport cryostat. For ready reference, we show in Figs. 1 and 2 the cryo-permeation set-up. The gas-fill tube attached to valve V_7 is removed, using the vacuum lock between gate valves, after the gas

Fig. 1. Polymer shell permeation system operating between 300K and 4K. Shells containing condensed high density hydrogens can be removed while remaining at 4K, using cold transfer operations.

Fig. 2. Detail drawing of permeator cryostat showing removable gas fill tube connected to permeation chamber by compression seal, breakable at low temperature. Also shown at the left is the mechanical assembly which drives the variable-diameter diaphragm in order to close bottom shutter of shroud of cold-transfer apparatus.

is loaded in the shells and condensed, as described above. The target shell is next transported in the cryostat to Rochester, a trip of about 2 hours (this time is of no importance for unpolarized targets but is very relevant to polarized target experiments), after which it is removed (at a temperature of 4K) with our cold-transfer system, and inserted into the OMEGA chamber. The cold-transfer operation in the hall which houses OMEGA is depicted in the photograph, Fig. 3, and Fig. 4 is a photograph showing the cold-target inserted in the OMEGA fusion chamber. In Fig. 4, our cold-transfer system is labeled c-t. A magnetic field is applied in a direction in the equatorial plane of the OMEGA chamber roughly left to right in the photo. The polar and azimuthal proton detectors are labeled respectively p and a. The latter is a true 90° from the magnetic field direction, whereas the polar detector is necessarily off by about 10° from true axial, necessitated by the geometrical constraints. The polar and azimuthal large area neutron detectors do not show in the photo. They are external to the chamber, and their centers occupy true polar and azimuthal positions with respect to the nuclear-spin-orienting magnetic field.

The LLE target fabrication group⁹ prepared the target shell, a parylene-coated polystyrene shell of 372 μm outer diameter, and 12.7 μm total wall thickness, the outer 8 μm of which are parylene-C. It was suspended between the prongs of a standard copper fork by a single spider silk and two 5 μm diameter gold wires, which were themselves finally overlaid with 0.2 μm parylene. From the liquid helium temperature cold-finger, the

Fig. 3. Cold-transfer operation at LLE.

Fig. 4. Cold (4K) target (c-t) inserted in OMEGA. See text.

gold wires provide the thermal conduction to the target shell, which was calculated with the aid of the experimental results in Ref. 6 to be adequate under the shroud-controlled background infrared radiation load to which the target shell is subjected. The target stalk is mounted in our sample holder, which has provision for attachment or detachment from the cold finger of our cold-retrieval system via a left-right thread system⁶.

While discussing the mating system of our targets to OMEGA, we include in this section the design and fabrication of a holding-magnet to be inserted in OMEGA for the upcoming polarized D targets. Because of geometrical constraints and limits on proximity to the target, a pair of tapered cylindrical Nd-B-Fe magnets was designed, fabricated and tested. Allowing 2.5 cm between the pole faces and tapering so as to be clear of all laser beams, this magnet provides approximately 900 Gauss magnetic field, adequate for our experiments. The nuclear spins adiabatically orient from the field direction produced by the small magnets in our cold-retrieval (insertion) system to the field in OMEGA, without polarization loss.

We conclude this section noting that our development has been successfully tested, except for the laser shot itself, and that this will take place on our next scheduled shot, which unfortunately has been delayed due to laser problems at LLE.

III. Dilution-Refrigerator Cold-Entry and Retrieval System.

This system is substantially the same as the OMEGA one, except that due to the limited axial access to and through the mixing chamber and cold-finger in the mK cryostat, the outer

diameter had to be kept to 15 mm. Because of this, the thermally isolating teflon star spacers are only a few mils thick, and there must be more of these fragile isolators because of the 3.5 m length of system. Nevertheless, this system works well, and holds liquid helium for several hours, more than enough for its limited use in cold transferring only between the storage-transport cryostat and the dilution refrigerator. Its shroud is simpler than that of the OMEGA cold-transfer system, in that no optical transmission section is necessary, and thus it is all metal. However, a brush system anchored at the 1.4K cold pot is necessary to cool the outer jacket of this tube to near 1.4K before it enters the region of the mixing chamber. If this precaution is not taken, the entire ^3He - ^4He mixture in the mixing chamber can flash out from contact with a "hot tube". Because of the large vertical lengths required for these operations, we cut a hole of about 2 square feet area in the ceiling above the dilution refrigerator, allowing full vertical access up to the ceiling of the room above. For transferring to the storage-transport cryostat from the dilution refrigerator retrieval tube, special internal spacers in the lower sections of that cryostat allow tilting it up to 45° without excessive liquid helium loss. The target is inserted into that cryostat after removal from the dilution refrigerator at an angle which allows clearance of the dilution refrigerator itself.

IV. TARGET SHELL TENSILE STRENGTH CHARACTERIZATION AT LOW TEMPERATURES.

We have developed a new technique for determining the

explosion pressure of target shells. Normally, this is done visually at room temperature. However, there is a need to know the tensile strengths at low temperatures as well, especially if one intends to gasify solid targets prior to implosion. In that case, the gas law permits reasonably high density targets since at about 30K, the pressure is only about 1/10 that at room temperature. We have modified the permeation set-up seen in Fig. 1 by simply adding a high sensitivity Barotron pressure detector, whose sensitivity is sufficient to detect the bursting of a single target shell, provided the background desorption is kept low enough. In preliminary experiments, conducted mostly in the low pressure permeation apparatus (see Ref. 7), similarly modified to include the Barotron detector, we have begun investigation of the competitive gas-release from desorption, and have shown that it is essential to use gas considerably purer than the 99.99% typical of deuterium, or the 99.995% high purity tank helium gas. From these preliminary experiments, we have proven the feasibility of the method, and our proposal to NLUF for next year is based on this new technique.

V. PROTON AND DEUTERON SPIN-LATTICE RELAXATION MEASUREMENTS IN HD IN THE MILLIKELVIN TEMPERATURE RANGE.

The method for spin-polarization of D in HD which we employ is controlled more by the spin-lattice relaxation of H and D than by any other parameters. Similarly, use of NMR for analysis of isotopic constitution of the hydrogens molecules in target shells also requires thorough understanding of the relaxation times. We thus undertook a program of measurement which spans the important

$J=1$ concentration range for polarized samples, the relevant temperature range of 9 mK to 1K, and the magnetic field range from 0.1T to 13T. These measurements add significantly to the theoretical understanding of the relaxation processes¹⁰. For example, we have shown that the assumption of exponential growth of T_1^H with decreasing temperature, based on measurements by others down only to 40 mK, was not correct, and that a linear dependence better represents the behavior down to 15 mK. This is of importance to the polarization program, since with refrigerators operating near 5 mK, much higher polarizations would be available without the obstacle of prohibitively long relaxation times. Another discovery was the thermal history dependence of the relaxation time in the mK region. An effect which was noted in solid H_2 , clustering of $J = 1$ molecules¹¹ below 200 mK, was deduced from the thermal history of T_1^H values to be operative in HD also. Whereas the clustering in solid H_2 could be due to quantum diffusion, i.e. energy conserving para-ortho switching in a neighboring pair, or to a molecular quantum tunneling process, in HD the former mechanism is ruled out since a para- H_2 neighbor is a rarity. Thus, the new quantum transport process is unambiguously identified. This latter allows T_1^H to increase more rapidly than would be expected just from ortho-para conversion of the H_2 impurities, and thus can shorten the time for producing polarized D samples.

Some of the work on highly polarized liquid D_2 was reported this year at the American Physical Society spring meeting¹¹. A paper is in preparation.

VI. CONCLUSIONS

We have carried out all the elements of the ambitious original proposal to test ICF with spin-polarized fuels. The completion of the experimental program awaits scheduling of shots at LLE before OMEGA is shut down. In addition, we have expanded greatly the information base on high-density fueled ICF targets, cold transfer of cryo-targets, properties of polymer shells, and relaxation processes in solid hydrogens.

REFERENCES:

1. R. M. Kulsrud, H. P. Furth, E. J. Valeo and M. Goldhaber, Phys. Rev. Lett. 49, 1148 (1982).
2. Y. -L. Pan and S. P. Hatchett, Nucl. Fusion 27, 815 (1987).
3. A. Honig, Phys. Rev. Lett. 19, 1009 (1967).
4. A. Honig, N. Alexander and S. Yucel, Workshop on Muon-Catalyzed Fusion, Sanibel Is., Fl. May 2-6, 1988. AIP Conf. Proc. No. 181, p. 199.
5. N. Alexander, Y. Y. Yu, Q. Fan, X. Wei and A. Honig, Bull. Am. Phys. Soc. 35, 925 (1990).
6. N. Alexander, J. Barden, Q. Fan and A. Honig, Rev. Sci. Instrum. 62, 2729 (1991).
7. A. Honig, N. Alexander, Q. Fan, R. Q. Gram, and H. Kim, J. Vac. Sci. Technol. A9, 3149 (1991).
8. Final Report for NLUF Grant DE-FG03-90SF18432; May 5, 1991.
9. Thanks are due to Roger Gram and Hyogun Kim for providing us with these specially mounted target shells.
10. N. Alexander, Q. Fan, X. Wei and A. Honig, Bull. Am. Phys. Soc. 37, 610 (1992).

11. R. Schweizer, S. Washburn and H. Meyer, J. Low Temp. Phys.
37, 289 (1979).

12. Y. Y. Yu, X. Wei and A. Honig, Bull. Am. Phys. Soc. 36, 1354
(1991).

Personel on this project during the grant year:

Neil Alexander, Research Assistant. (He completes his PhD in July
1992, and has accepted a staff position at General Atomics in
San Diego, where he will work on ICF-related projects).

Q. Fan, Graduate Research Assistant, PhD candidate.

X. Wei, Graduate Research Assistant, PhD candidate.

**DATE
FILMED**

8 / 14 / 92