DOE/ER/12821--2

DE92 015969

Technical Progress Report

Phase II (1989-1990)

for

Research on

EXPERIMENTAL DEVELOPMENT OF NUCLEAR PUMPED LASER CANDIDATE
FOR INERTIAL CONFINEMENT FUSION DRIVER

Supported by

U. S. Department of Energy

Under Contract #DOE DEFG07-88ER12821

George H. Miley
Principal Investigator
Fusion Studies Laboratory
University of Illinois
Urbana, Illinois 61801

6 June 1990

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Abstract

A report is given on progress made during the second year of a three year contract studying the feasibility of nuclear pumping the atomic iodine laser. Experimental results are presented showing efficiencies of 25-38% at converting neutron-induced nuclear reaction energy in the excimer XeBr into UV photons which can be used to pump the laser. Parametric studies were done utilizing the $^{10}\text{B}(n,\alpha)^7\text{Li}$ reaction, with three bromine donor chemicals, over a range of pressures and mix ratios, to optimize the fluorescence efficiency.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Table of Contents

Introduction	1
Project Overview	1
Experimental Set-up	5
Gas Handling/Vacuum System	6
Test Cell	7
Optical Collection System	9
Bromine Donor and Gas Selection	10
³ He Test Cell	11
Photon Coupling Calculations	13
Experimental Results to Date.....	14
Pressure Transducer	14
Fluorescence Measurements	16
Technical Conference Presentations	27
Summary and Conclusions	27
References	29

Introduction

This technical progress report is submitted near the end of the second year of a three year project studying the viability of pumping the atomic iodine laser using nuclear-induced fluorescence. The first section of the report gives an overview of the plans for the entire project, as well as some background on the laser system being studied. The second section details the experimental set-up used for this year's work, followed by a section on results and a listing of past and pending technical conference presentations of the work. A summary and conclusions are given in the final section. Plans for next year's work are given in the accompanying proposal, "Project Plans for 1990-1991".

Project Overview

This project was originally conceived as a three year effort to study the possibility of driving the atomic iodine laser ($1.31 \mu\text{m}$) using nuclear energy. This gas laser is a photolytically driven laser, in that it uses UV light to photodissociate an iodine-containing molecule into an iodine atom and the remaining portion of the molecule. A sufficient number of the iodine atoms formed from the photodissociation are in an excited state to allow lasing on the $5^2P_{1/2}(I^*) - 5^2P_{3/2}(I)$ transition. Successful study of such a laser system, showing its scalability to high powers, could have important applications in Inertial Confinement Fusion, where high power laser drivers are needed. Nuclear

pumped lasers may also have important applications in space power transmission or communications, where the nuclear fuel represents a compact energy source.

Typically the UV light for the laser is supplied by an electrical flashlamp (e.g. Xe). Past work¹, however, has been done to suggest using energetic nuclear reaction products to generate UV fluorescence in an excimer gas mixture. Theoretical work by Wilson and Shappiro^{2,3} was done especially for this laser system. Extrapolation of their predictions indicated the TRIGA reactor at the Univ. of Illinois to be an excellent facility to study the viability of such a pumping scheme.

Lasers which use nuclear reaction energy as a power source are generically termed Nuclear Pumped Lasers (NPL's). If the energy goes to directly drive the lasant, it is termed direct nuclear pumping. A system which simply uses nuclear reactions to generate fluorescence, rather than directly stimulating a lasing medium, is termed a Nuclear Driven Flashlamp (NDF). This present study, then, is primarily concerned with the development of an NDF-pumped iodine laser. This work over the past year was mainly concerned with developing and optimizing the NDF. Discussion of plans for using this NDF to pump the laser, as well as plans for direct nuclear pumping of the laser are given in the proposal for next year's work.

Nuclear reactions typically considered and used for nuclear pumping are

The first and last reactions are typically used by placing thin coatings of enriched boron or uranium on the inside of a test cell. The second reaction has the advantage of using a gaseous reactant, making pumping of large volumes feasible, but has the disadvantage of high cost for the ${}^3\text{He}$, and a relatively low energy release per event.

A sizeable flux of neutrons is needed to achieve the power densities required for laser applications, so reasonably high powered nuclear reactors, such as a fast burst reactor or the TRIGA, are needed for such research. The TRIGA has a pulsing capability as outlined in Table 1. Our calculations predicted that sufficient fluorescence should be generated in the TRIGA, with optimum gas mixtures, to exceed threshold requirements for the atomic iodine system, producing a peak power of approximately 100 W at the 1.31 μm line. This would represent a substantial power output for such a small scale experiment. A schematic of the planned laser is shown in Figure 1.

Table 1. TRIGA Pulsing Characteristics

- 12 msec fwhm
- $3 \times 10^{15} \text{ n/cm}^2\text{-sec}$ peak thermal flux
- 4 pulses/hour

Plans for this work were originally broken into three phases:

Figure 1. Schematic of planned laser cell.

Phase 1: Nuclear-pumped fluorescence studies and optimization.

Phase 2: coupling of fluorescence to a laser cell, and testing of the laser.

Phase 3: Direct nuclear pumping of the laser.

Progress during the first year allowed construction of a vacuum and gas handling system, as well as a boron-coated test cell. Preliminary measurements were also begun on the fluorescence of the excimer XeBr. Work accomplished to date in the present budget period will be discussed in the following sections.

Experimental Set-up

Efforts during this second year of testing have largely centered on continued fluorescence measurements with the boron-coated cell. Original plans had been to test different excimer gas systems, e.g. XeBr, KrF, Ar₂F, to seek an optimum fluorescing gas. Results to date, however, with XeBr have proved sufficiently promising that the effort has been restricted to that system.

During early testing it was found that low concentrations of impurities apparently strongly inhibit fluorescence. Thus considerable effort was needed to build a system which restricted impurities to a level consistent with good fluorescence. As will be discussed below, however, this effort allowed us to achieve fluorescence results that approach the theoretical limit in efficiency.

Experiments were also done with three different bromine donor gases in an attempt to help optimize output for the XeBr system.

A second test cell has recently been constructed, and experiments begun on fluorescence generation with ^3He in XeBr. This work will extend into the summer. This phase of the investigation will allow us to accurately predict the intensity of UV light which can be generated in a laser cell configuration.

A computer code is concurrently being prepared which will predict the fraction of the light generated in a laser cell geometry which can be coupled from the outer fluorescence portion of the cell to the inner lasant portion. Variables will include the laser cell geometry, lasant pressure, and cell surface reflectivity.

The laser cell itself is also being designed. We had originally hoped to begin laser testing during this second year of the project, but it is presently anticipated that, due to the impurity difficulties encountered in fluorescence testing, this work will be delayed to the start of next year's work.

A discussion of the work in each of these efforts follows.

Gas Handling/Vacuum System

As indicated above, a significant challenge encountered as this research progressed has been the need to reduce

impurities in the test cell to a low enough concentration to allow good fluorescence. The major stumbling block has been the distance between the test cell installed in the reactor and the vacuum station, approximately 20 feet. It was found through several testing attempts that special care had to be taken to use as large a diameter vacuum line as possible up to the test cell, as well as using quality vacuum valves and connections in the system. One inch diameter vacuum line was found to be suitable, with pneumatic vacuum valves and KF fittings. This allowed a pressure of approximately 1 mtorr to be obtained in the cell, using a large diffusion pump outside of the beam port.

Materials compatibility with the bromine donor compounds (Br_2 , CHBr_3 , and BBr_3) required the use of stainless steel and glass components in the system. A special halogen-based manometer fluid was also required to measure the bromine donor pressures.

Test Cell

The boron coated test cell used for experiments to date is shown in Figure 2. The cell windows are made of fused silica to minimize radiation darkening during pulsing.

The fast-response (μsec) pressure transducer attached to the cell serves to measure the energy deposition in the cell gas. It was found the transducer used was sufficiently resistant to radiation to be used up through 7.5 MRad (75

Figure 2. Test cell used for $n\text{-}^{10}\text{B}$ reaction-induced fluorescence.

pulses) of exposure before its performance started to degrade.

Optical Collection System

Two diagnostics systems were used to collect and analyze the fluorescence from the testing. The first was a monochromator (CGA-McPherson model EU-700), which gave time-resolved information for the 282 nm line. This helped assess the potential of any dose or dose rate effects on the output. In all cases of interest the fluorescence was found to be fully synchronous with the temporal shape of the reactor pulse.

The second light collection system used was an Optical Multichannel Analyzer (OMA) which collected a time-integrated spectrum of the fluorescence. Two OMA's were used, a Princeton Applied Research model 1450/1452 and model 1460/1456. The latter is a better model, but only became available on loan from another laboratory toward the end of experiment. Both systems were attached to a spectrograph to take a spectrum from approximately 250 to 600 nm.

The opportunity to use two OMA's was fortuitous in that it provided two independent spectral intensity measurements, which were found to agree fairly well (see the section on Fluorescence Results). The sensitivities of the OMA's and the throughput of the spectrographs, as stated in the product literatures, were used to determine the absolute light output from the cell shown in the attached data. An

intensity-calibrated light source was recently borrowed which will allow a check on these calibrations.

Bromine Donor and Gas Selection

Three bromine donors were evaluated, Br_2 , CHBr_3 , and BBr_3 . All three are liquids at room temperature, with sufficiently high vapor pressures to be used for this application. All materials were A/R grade with purities of 99.6%, 99+%, and 99.99%, respectively. All were treated with several freeze/vacuum evacuate/thaw cycles using dry ice/acetone to remove entrapped volatile gases.

Selection of which bromine-containing materials to test was aided by a reported study⁴ of the trimer of this system, Xe_2Br . In that work four compounds were tested, the best being carbon tetrabromide (CBr_4), with bromoform (CHBr_3) performing about as well. Carbon tetrabromide, however, requires heating to achieve a sufficiently high vapor pressure for testing, so was not used in this investigation. Of the three studied for this work, bromoform was found easiest to handle from a chemical point of view, as it was less reactive than Br_2 and BBr_3 . All the bromine donors used, however, have low exposure limits, requiring extreme care in handling. The other gases involved, research grade Xe and Ar, were used as received.

^3He Test Cell

A schematic of the cell recently constructed to be used for fluorescence testing of XeBr in ^3He is shown in Figure 3. It is very similar in design to the boron coated cell, except an additional fill line has been added directly to the cell to minimize the amount of ^3He used in each test. The inside bore of the cell is also tapered to allow the entire inside of the cell to be viewable from a wider angle, making optical alignment easier. This tapered bore has a disadvantage of increasing the solid angle view of the cell wall, as seen by the optical detector, increasing the fraction of fluorescence light reflected into the detector. Bench top measurements have allowed this effect to be factored out, however.

This cell was also designed to allow fill pressures up to 3-4 atmospheres since the fluorescence efficiency in the laser configuration is expected to maximize in this range. A \$3.00 pulse on a fill of three atmospheres was expected to yield a transient temperature rise of 600°C . and a corresponding pressure rise to 9-10 atmospheres. This necessitated building a more durable cell than was used with ^{10}B testing, with thicker windows (6 mm). A special ball valve attached to the test cell was acquired to meet both the pressure requirements as well as the high conductance, low leakage requirements for vacuum work. A worm gear fixture was built for the valve to allow remote actuation.

Figure 3. Test cell for $n\text{-}^3\text{He}$ reaction-induced fluorescence measurements.

Photon Coupling Calculations

A critical parameter in the efficiency of this laser system will be the coupling of the fluorescence light from the outer portion of the laser cell into the smaller inner tube containing the lasant. The efficiency with which this can be done is termed the "coupling efficiency". Literature estimates for the coupling efficiency for concentric cylindrical or parabolic geometries range from 18% to 80%^{3,5,6}. This wide range of predictions is clearly unacceptable so we have begun an independent study of the coupling. To aid in our design work, a Fortran code to predict the coupling efficiency has been obtained from Dr. Mark Prelas (Univ. of Missouri). This code is being modified for this our application to test various geometries and sizes, as well as different lasant pressures.

The reflectivity of the inner surface of the cell is a parameter of much interest since it limits the number of bounces a photon can make within the cavity. The reflectance of bare aluminum mirror at 282 nm is about 85%. If calculations with this code indicate that improving this reflectivity would significantly enhance the coupling efficiency, consideration will be given to depositing a high-reflectance coating on the mirror surface. Previous work by our group has shown that the environment of high-energy charged particles and UV light in a nuclear pumped excimer laser can be damaging to dielectric coatings. Hence, care will be required in selection of such a coating.

Experimental Results to Date

A significant amount of data has been taken to date on the fluorescence of XeBr under ^{10}B excitation. A discussion of results from pressure transducer measurements (used to determine energy deposition in the cell) is given, followed by fluorescence measurement results.

Pressure Transducer

Typical pressure transducer results are shown in Figure 4. It is seen that the pressure rises up through about the end of the pulse, but quickly decreases thereafter as the heated gas cools against the test cell wall. This cooling rate is significant compared to the pulse duration, so some correction is needed to extract information on the total energy deposited in the gas. This was done by assuming the gas cools exponentially in time with a time constant of 0.009 sec^{-1} , as determined from the data shown in Figure 4. Approximating the reactor pulse by a gaussian in time, the energy actually deposited can be back calculated to be equivalent to a 12.6 psi pressure rise, as opposed to the 11.6 shown in the figure. If the radiation effect on the detector, as measured on an empty cell, is subtracted from the signal, the increase in pressure corresponds to an energy deposition of 0.1 J/cm^3 . Added to this, however, must be the fluorescence energy release. Based on results discussed below, this was a maximum of $0.10 - 0.17 \text{ J/cm}^3$, indicating a total energy deposition in the gas of $0.20 -$

Figure 4. Typical pressure transducer results, used to determine energy deposition in the cell.

0.27 J/cm³. This correlates fairly well with other experimental and theoretical determinations of dose for this cell geometry and neutron flux^{7,8}.

Fluorescence Measurements

A schematic of the test set-up with the boron coated test cell is shown in Figure 5.

A typical fluorescence spectrum, as recorded by the less sensitive OMA, is shown in Figure 6. The strong XeBr peak of interest at 282 nm is apparent. Also indicated are the two other major peaks. A similar emission spectrum has been measured in e-beam pumping⁹.

A portion of a typical fluorescence spectrum from the more sensitive OMA is shown in Figure 7, overlaid on the photodissociation cross-sections of the two commonly used atomic iodine lasants. This figure shows the suitability of XeBr for this laser system.

By using the pressure transducer results, coupled with a determination of the sensitivity of the detector over the wavelength range, a determination of the efficiency of the fluorescence, as defined as the percent of the energy deposited in the cell which is emitted at 282 nm, can be made. The results for a number of tests with Br₂ as the bromine donor are shown in Figure 8, plotted as fluorescence efficiency vs Xe pressure. The letters A, B, and C represent sequential pulses on the same fill of gas. The optimum Xe pressure appears to be near 75 torr with 1 torr

Figure 5. Test set-up in the TRIGA reactor.

Figure 6. Typical fluorescence spectrum, as recorded by the less sensitive OMA.

Figure 7. Excimer emission recorded by the more sensitive OMA, overlaid on the photodissociation cross-sections for two common atomic iodine lasants.

Figure 8. Fluorescence efficiency (light out at 282 nm/energy deposited in the excimer) for 1 torr Br₂ in varying Xe/Ar ratios.

Br₂. The decrease in intensity with repeated pulses on a fill is ascribed to one of two mechanisms: either depletion of the bromine donor as bromine radicals react to form stable BBr₃ with the boron coated wall; or release of impurities from the cell wall during pulsing. Testing with ³He this summer should help determine which mechanism is responsible for this observation.

Some pulses to investigate the dependance on Br₂ pressure were done with results shown in Figure 9. It is difficult to make a conclusive inference from the limited data, but it appears that 1 torr is a good bromine pressure.

The dependance on argon pressure is shown in Figure 10 for 1 torr Br₂ with 75 torr Xe. The absolute fluorescence intensity is about the same at all pressures.

Figure 11 summarizes some test results for varying pressures of bromoform in 250 torr Xe, 550 torr Ar. Some fluorescer intensity dependance is seen in the range tested of 0-1.0 torr. There is some concern about the accuracy of the data, however, in that XeBr fluorescence at 0 torr bromoform was registered. Since the low pressure shots were done last in the experiments, this anomaly is attributed to adsorption of bromine-containing species on the cell wall from previous pulses. The adsorbed species may not have been completely swept out during evacuation between pulses. Still, it appears that good fluorescence is obtained with CHBr₃ pressures in the range of 0.1-0.5 torr.

Figure 9. Fluorescence intensities for varied Br₂ pressures at constant Xe, Ar pressures.

Figure 10. Fluorescence intensities for varied Ar pressures at constant Xe, Br₂ pressures.

Figure 11. Fluorescence intensities for varied CHBr₃ pressures at constant Xe, Ar pressures.

The effect of varying Xe pressure with 0.5 torr bromoform is shown in Figure 12, along with data BBr_3 . Data for bromoform from both OMA's are shown in the figure, the OMA 1460/1456 system indicating somewhat higher efficiencies than the other system. It is felt that the true fluorescence efficiencies probably lie between the two data sets. Further measurements with a calibrated light source will help determine the correct efficiencies. It is seen that the fluorescence peaks near a Xe to bromine donor ratio of 200/0.5 for CHBr_3 as compared to 75/1 for Br_2 , as shown in Figure 8. Also, the bromoform is the better fluorescer of the two. This result agrees quite well with an e-beam investigation of the trimer Xe_2Br from ref. 4, shown in Figure 13.

Figure 12 also shows one data point for boron tribromide, showing good fluorescence. Several shots were taken, but only one gave fluorescence. The failure of others is attributed to impurities.

It is seen that the optimum fluorescence efficiency is 25-38% when using CHBr_3 . This compares well with the maximum theoretical efficiency for the XeBr system of 53%¹⁰. The 22% measured for Br_2 is somewhat higher than the 11+-5% measured in e-beam excitation by Swingle, et al.⁹, and with the predicted efficiency of 13-15% from kinetic modeling by Wilson². No firm explanation has been found for this discrepancy at present. It may be due to processes in a nuclear-pumped plasma which do not occur in an electron beam

Figure 12. Fluorescence efficiencies for 0.5 torr CHBr_3 in varying Xe, Ar pressures. Also shown is one data point for 1 torr BBr_3 .

excitation, and which have not been theoretically accounted for.

As discussed in the accompanying report, "Project Plans for 1990-1991", these results bode very well for building a laser system in the TRIGA. Extrapolation of these efficiencies to the expected power densities in a ^3He system predict, given concentric laser cell and fluorescing cell of diameters 1.5 cm and 5 cm, respectively, a UV fluorescence intensity of up to 50 W/cm^2 on the laser tube wall. This compares with reported threshold intensities for the iodine laser of 0.07 to 0.5 W/cm^2 , for somewhat different sources and geometries^{11,12}. These results then suggest that lasing should be achievable in the TRIGA. If this turns out to be true, this would be a most significant achievement.

Technical Conference Presentations

Parts of this work have been presented to date at three technical conferences, the 16th Intl. IEEE Conf. on Plasma Science (May 1989, Buffalo), the 9th Intl. Workshop on Laser Interaction and Related Plasma Phenomena (Nov. 1989, Monterey), and the Intl. Conf. on Lasers '89 (Dec. 1989, New Orleans). An abstract has also been submitted to be considered for inclusion at the APS 6th Interdisciplinary Laser Science Conf. (Sep. 1990, Minneapolis).

Summary and Conclusions

Research has continued during this year on measuring fluorescence efficiencies of the XeBr excimer under ^{10}B

excitation. Results have proven encouraging that good efficiencies (near theoretical limits) can be achieved through nuclear pumping, and indicate it should be possible to attain lasing at $1.31 \mu\text{m}$ in iodine using this fluorescence. Experiments will be done this summer to determine the fluorescence efficiencies under ^3He excitation.

References

1. Miley, G. H., et al., Bult. APS, 24, 117 (1978).
2. Wilson, J. W., Appl. Phys. Lett., 37(8), 695 (1980).
3. Wilson, J. W., Shapiro, A. J., Appl. Phys., 51(5), 2387 (1980).
4. Wilson, W. L., Jr., et al., J. Chem. Phys., 77(4), 1830 (1982).
5. Prelas, M. A., Jones, G. L., J. Appl. Phys., 53(1), 165 (1982).
6. Prelas, M. A., et al., Lasers and Part. Beams, 6(1), 25 (1988).
7. Elsayed Ali, H. E., Miley, G. H., Rev. Sci. Ins., 55(8), 1353 (1984)
8. Chung, A., Prelas, M., presented at the 1983 Int. Conf. on Plasma Sci., San Diego, paper 6A5 (1983).
9. Swingle, J. C., et al., Appl. Phys. Lett., 28(7), 387 (1976).
10. Verdeyan, J. T., Laser Electronics, (New Jersey; Prentice Hall, 1989).
11. Witte, K. J., et al., Optics Comm., 28(2), 202 (1979).
12. DeYoung, R. J., Conway, E. J., Proc. Intl. Conf. on Lasers '85, 467.

**DATE
FILMED**
8/11/92