**Brown University
Division of Engineering**

**TWO STUDIES OF NONLINEAR PROCESSES
IN IRREVERSIBLE THERMODYNAMICS**

Grant DE-FG02-87ER13687

FINAL REPORT

for period 05/01/89 - 04/30/92

Prepared by
Joseph Kestin
Research Professor
(Member, National Academy of Engineering)

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed or represents that its use would not infringe privately-owned rights.

Endorsement:

_____
Joseph Kestin
Research Professor
Division of Engineering
(401) 863-2685

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TWO STUDIES OF NONLINEAR PROCESSES IN IRREVERSIBLE THERMODYNAMICS

Abstract

The investigation dealt with two lines of research into two well-defined problems of engineering science: a study of two-phase flow and of nonelastic deformations in structural solids. Both topics fall into the broad field of nonlinear irreversible processes.

The study of two-phase flow resulted in a complete topological analysis of the canonical mathematical model of one-dimensional flow of a mixture of two phases, now predominantly used in industry, especially the nuclear industry. The topological analysis is confronted with the practice of discretizing the analytic model for the purpose of formulating a numerical computer code. It is shown that in the presence of singular points in the phase space of the differential equations of the model there occur **spurious numerical solutions**. Such solutions may contain segments which are correct approximations to the exact trajectory, but always include branches which are totally false and misleading. The topological method allows the operator to formulate a subroutine which eliminates spurious solutions.

The study of inelastic deformations, i.e., of irreversible processes in structural solids provided a consistent presentation of the **local-state approximation** erroneously called the method of local equilibrium in the literature. The key concept which impedes the correct use of thermodynamics in this field is the definition of a **measurable entropy of a nonequilibrium state**. The local state approximation solves this problem by assigning to a nonequilibrium state n the entropy of the **accompanying equilibrium state** e . The two states, n and e , are linked by having the same values of a specified set of extensive properties. The same principle settles the comparison between the intensive properties of n and e , which are different.

Scope and purpose

The investigation dealt with two productive lines of research into two well-defined fundamental problems of engineering science. The research topics are relevant to the development of advanced energy technologies and to the improvement of currently used technologies. They fall into the broad field of nonlinear irreversible processes: One deals with flow of two-phase systems and the other with inelastic deformations in structural solids. The link between the two is provided by the use of nonlinear mathematical analysis and the common background in irreversible thermodynamics. Both aim at creating a scientific basis for the search for constitutive laws and for formulations which are predictive.

Two-phase flow

The Principal Investigator was materially assisted by his collaboration with Professor Z. Bilicki, of the Institute for Fluid-Flow Machinery of the Polish Academy of Sciences in Gdansk, Poland, who spent several periods of time in Providence at Brown University. The principal achievement was the adaptation of topological methods of mathematical analysis to the study of the properties of the canonical mathematical model of one-dimensional, adiabatic flows of compressible fluids consisting of two phases. These could either be a liquid and its vapor or a liquid with dispersed gas bubbles through its bulk.

The topological method of analysis applies to essentially all one-dimensional mathematical models of flows through channels of varying cross-sectional areas now in use, regardless of the number of coupled nonlinear ordinary differential equations of which the model is composed, i.e., to homogeneous as well as to two-fluid models. Being topological, the analysis produces a clear "portrait" of all possible solutions, represented as a set of curves in the phase space of the system. The latter consists of

$n+1$ dimensions, where n is the number of components of the state-velocity vector (equal to the number of differential equations). Such a "portrait" provides complete qualitative information on which to base an understanding of the physical characteristics of the ensemble of solutions.

The key concept is the determination of the singular points of the system at which the uniqueness theorem of Cauchy-Kowalewska breaks down.

The most remarkable achievement was to show that regardless of the number n of coupled equations (but disregarding degenerate cases) the system admits only three types of singular points: saddle points, nodal points, and spirals, each case being clearly defined by the roots of the characteristic equation of the system. Again, regardless of the number n , the characteristic equation is always quadratic.

The most important topological pattern is that involving a saddle point, especially because it is the one most likely to occur in practical applications. The physical conclusions which follow correct several misconceptions which workers in the field of two-phase flow retained on the basis of their earlier studies of ideal-gas flows through de Laval nozzles. The correct conclusions are especially important when the conditions surrounding choking (critical flows) are required. In particular, it is found that the critical cross-section does not coincide with the narrowest cross-section (throat) and that the pressure in it does not bear a constant ratio to the upstream stagnation pressure. In adiabatic flows the critical conditions place themselves in the divergent portion of the channel and in some cases move to the exit (or even beyond) as they always do in convergent nozzles or pipes of constant cross-section.

The investigation was able to include the effects of dispersion due to relaxation processes in the fluid, as described by one or more relaxation times τ . In such cases, it is necessary to distinguish between two speeds of sound: One corresponding to frozen

conditions ($\tau \rightarrow \infty$), the other to unconstrained equilibrium ($\tau \rightarrow 0$). It is the former that prevails at the critical cross-section.

The preceding ideas enabled the investigators to re-examine the results of the classical experiments known by the code-name "Moby Dick" and to remove some erroneous conclusions that were based upon them. This was a case when, unrecognized by the original authors, the saddle point moved outside the experimental channel, even though the latter incorporated a clear throat.

A second, and no less important, development concerns the discretized codes used in industry to generate individual numerical solutions which form the basis of design analyses and of the monitoring of the safety condition of operation of nuclear reactors. The development starts with the question whether the totality of solutions inherent in a numerical code based on a discretized form of the canonical set of equations of the physically correct mathematical model is identical with its topologically revealed "portrait." The answer here depends on the region of phase space involved. It is proved that solutions which are not represented by curves which pass through a saddle point are correctly approximated by a competent numerical scheme (solutions passing through regular points). However, no numerical scheme is capable of crossing a singular point including the important saddle points. In such cases a code used without regard to the topological structure of the phase space will produce so-called **spurious or phantom solutions**. Spurious solutions may contain segments which are a correct approximation to the exact curve, but always include branches which are totally false and misleading. When examined by themselves, it is impossible rationally to make the proper distinction. This must be done in conjunction with the topological analysis developed earlier which, moreover, provides the analyst with a method to design an auxiliary code and so to resolve the issue.

The formalisms developed under this grant are slowly gaining acceptance as evidenced by the fact that the Principal Investigator was co-opted to the juries of two doctoral examinations (Universities of Louvain in Belgium and Grenoble in France) and invited to deliver a keynote lecture at the International Conference on Multiphase Flow '91-Tsukuba, held in Japan.

Last, but not least, the Principal Investigator has been made a member of the Organizing Committee of the Third International Workshop on Two-Phase Flow Fundamentals, to be held at Imperial College in London in June 1992. The workshop is co-sponsored by DOE and EPRI.

Inelastic deformations

It is a fact that thermodynamics, as a discipline, and in spite of its long history of development, has not reached the stage of a generally acceptable formalism. The dichotomy is particularly acute when a comparison is made between research workers in the field of fluid mechanics and those who attempt to use its teachings in application to solid mechanics. It is quite legitimate to speak about different "schools," especially between classical thermodynamics and "rational" thermodynamics, which appear to be fundamentally different. The differences are partly semantic in nature, which impedes communication and has led to vituperative confrontations, but also turn on quite basic concepts. For this reason a good deal of time was spent on re-examining the concepts and equations which are used in fluid mechanics and which are referred to as the method of local equilibrium.

It is well known that all formalisms are in agreement in the handling of equilibrium states ("thermostatistics") and reversible processes. Problems arise in the treatment of irreversible processes, i.e., of nonequilibrium states and here the key

difference between "schools" is the way they assign a measure to, and the very concept of, **entropy of a nonequilibrium state**.

First, it must be recognized that a rational study of irreversible processes requires a continuum description. Clarity in the description of the **state** of an element ("point") of a continuum is achieved by concentrating on extensive properties and observing that the variables needed to define a nonequilibrium state are more numerous than those which define an equilibrium state of the same system. The equilibrium state of a system studied in fluid or solid mechanics is uniquely defined by indicating its internal energy, u , a set of external deformation parameters, a , and a set of internal deformation parameters, α , all extensive in nature. It is convenient to regard these variables as the coordinates of a multidimensional (Gibbsian) **phase space** $\mathcal{h}$ whose points all represent equilibrium states. Classical methods prove that in such a space it is possible to define a **measurable*** entropy s , which is a convex function of the above set of extensive variables,

$$s = s(u, a, \alpha). \quad (1)$$

The intensive properties of the equilibrium state are obtained in the form of partial derivatives of the function (1)--the fundamental equation of the system.

A nonequilibrium state of an element requires for its description more variables than those in Eqn. (1) because it interacts with its neighbors. Therefore, such states cannot be represented as points in $\mathcal{h}$. We refer to the continuum as the **physical space** and note that in it the extensive variables u, a, α can be measured (in the sense of Sommerfeld), but the intensive variables (referred to as **contact quantities** by

---

* To this term we attach the meaning given to it by Arnold Sommerfeld: "Word definitions have very little meaning; physically significant definitions are obtained as soon as we prescribe a way of measuring the quantity in question. Such a prescription need not contain the details of practical procedure, but merely state a way to measure the quantity in principle."

(*Mechanics*, Academic Press, 1952, p. 6)

W. Muschik) are no longer the partial derivatives of the function in Eqn. (1) and have different numerical values. Moreover, the classical prescription (Carathéodory's theorem) which defines an entropy measure of an equilibrium state is not available in the physical space. Declaring entropy "a primitive quantity" does not lead to a clear measure for it. This must be achieved by a suitable physical hypothesis. The merciless "war of schools" is precisely about this point.

In fluid mechanics the operative hypothesis is known as the method of local equilibrium, which is a misnomer. We prefer the term **principle of local state** instead because an element in a continuum is emphatically not in, even local, equilibrium.

The principle of local state compares a nonequilibrium state n with measurable values u , a , α with its **accompanying equilibrium state** e of **equal** measures of its **extensive properties**,

$$u(n) = u(e), \quad a(n) = a(e), \quad \alpha(n) = \alpha(e). \quad (2)$$

Based on a long history of successful application in fluid mechanics, the principle of local state assigns to n the values of entropy s and temperature T , but not of the remaining intensive properties, measured in e . This is clearly, not in any sense exact, and for this reason we prefer to speak about the **local-equilibrium approximation**. This heuristic principle is hotly disputed in the literature of solid mechanics, but we are convinced first, that it is also applicable there, and secondly, that it is the only principle proposed so far for the definition of the entropy of a nonequilibrium state which satisfies Sommerfeld's criterion of being measurable.

The nature of the approximation has been explored and it has been shown (if it is not obvious) that for $n \rightarrow e$ the two measures coincide.

The dominant ambition was to extend the application of the local-state approximation to problems of inelastic deformation and to persuade solid

mechanicians to use it. The advantages to be gained, apart from the elimination of many misstatements encountered in the literature, is to open the way to calculating the temperature fields which arise in the continuum during an irreversible process and so to generalize beyond the standard assumption of a spatially constant temperature. The theory would, further, make it possible to calculate the heat exchanged during an irreversible process. Moreover, such a development would also contribute to a rational search for constitutive laws, which in the local-state formalism consist of a fundamental equation of the type of Eqn. (1) and of a set of rate equations $\dot{\alpha}$.

A promising beginning in this direction has been made in the study of the mechanical behavior of materials with internal damage zones through cooperation with Professor George Herrmann of Stanford University.

END

**DATE
FILMED**

8 / 12 / 92