120
8-5-92 JS(2)

DOE/BC/14600-29
(DE92001057)

IN SITU COMBUSTION WITH METALLIC ADDITIVES

SUPRI TR 87

**By
Richard Joseph Holt**

July 1992

Performed Under Contract No. FG22-90BC14600

**Stanford University
Petroleum Research Institute
Stanford, California**

**Bartlesville Project Office
U. S. DEPARTMENT OF ENERGY
Bartlesville, Oklahoma**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

DOE/BC/14600--29

DE92 001057

Distribution

IN SITU COMBUSTION WITH METALLIC ADDITIVES

SUPRI TR 87

By
Richard Joseph Holt

July 1992

Work Performed Under Contract No. FG22-90BC14600

Prepared for
U. S. Department of Energy
Assistant Secretary for Fossil Energy

Thomas B. Reid, Project Manager
Bartlesville Project Office
P. O. Box 1398
Bartlesville, OK 74005

Prepared by
Stanford University
Petroleum Research Institute
Stanford, CA 94305-4042

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

1. Acknowledgements

Daulat Mamora and Paul Pettit of SUPRI are gratefully acknowledged for their advice and assistance during many hours of experimentation. Daulat Mamora is further credited for designing and building, as part of his own research, the efficient and reliable experimental system which drastically reduced the time and effort required to complete this project.

David Meinert of Chevron is acknowledged for generously providing the crude oil samples used in this study.

2. Abstract

In-situ combustion is the most energy efficient of the thermal oil recovery methods. In this process, a portion of a reservoir's oil is burned in-situ as fuel to drive the recovery process. In light oil reservoirs, too little fuel may be deposited, making sustained combustion difficult. In heavy oil reservoirs, too much fuel may be deposited leading to high air injection requirements and unfavorable economics. This study has been designed to attack these problems. Water soluble metallic additives are investigated as agents to modify fuel deposition and combustion performance.

In previous papers (Shallcross 1989, De los Rios et al, 1988), results were reported from kinetics experiments run on Huntington Beach (California) and Hamaca (Venezuela) crude oils. In these experiments, mixtures of sand, crude oil, and aqueous metallic salts were oxidized. While the presence of copper, nickel and cadmium had little or no effect; iron and tin increased oxidation rates and oxygen consumption.

This report describes seven combustion tube runs using two crude oils and two metallic additives. The oils are 12° and 34° API, both from Cymric (California). The metallic additives tested are iron nitrate ($Fe(NO_3)_3 \cdot 9H_2O$) and zinc nitrate ($Zn(NO_3)_2 \cdot 6H_2O$). In previous studies, Baena et al (1990) and Castanier et al (1992), have presented a total of eight combustion tube runs with the metallic additives iron chloride ($FeCl_2 \cdot 4H_2O$), zinc chloride ($ZnCl_2$), and tin chloride ($SnCl_4 \cdot 5H_2O$) using Huntington Beach (California) and Hamaca (Venezuela) oils.

Iron and tin additives improved the combustion efficiency in all cases. Fluctuations in the produced gas compositions were observed in all control runs, but nearly disappeared with the iron and tin additives. The combustion front velocities were also increased by iron and tin. Changes were also observed in the apparent hydrogen to carbon (H/C) ratio of the fuel, heat of combustion, air requirements, and amount of fuel deposited. Iron and tin caused increases in fuel concentration while causing a decrease in air requirement. The increase in fuel concentration varied between the oils, however, tin and iron were consistently more effective than zinc.

A particularly interesting result occurred with the Cymric light oil. In the control runs, a sustained combustion front was not achieved, while in the iron additive runs, stable, sustained combustion was achieved.

Iron and tin salts are suitable additives to increase fuel deposition when that is needed. Additives suitable for use as a fuel reducing agent have not yet been found.

Contents

1 Acknowledgements	iii
2 Abstract	iv
List of Tables	vii
List of Figures	viii
3 Introduction	1
4 Literature Survey	3
4.1 Field Studies with Metals and Metallic Additives	3
4.2 Kinetic Studies with Metallic Additives	3
4.3 Tube Studies with Metallic Additives	4
5 Statement of Purpose	5
6 Experimental Equipment and Procedure	6
6.1 Experimental Equipment	6
6.1.1 Combustion Tube	6
6.1.2 Experimental System	8
6.2 Experimental Procedure	8
7 Experimental Program	12
8 Results and Discussion	14
8.1 Qualitative Observations - Sustained Combustion	14
8.2 Produced Gas Compositions	14
8.2.1 Cymric Heavy Oil	14
8.2.2 Cymric Light Oil	15
8.3 Temperature Profiles	15
8.3.1 Cymric Heavy Oil	23
8.3.2 Cymric Light Oil	23
8.4 Liquid Production	23
8.4.1 Cymric Heavy Oil	31
8.4.2 Cymric Light Oil	31
8.5 Effect of Metallic Additives	39
8.5.1 Cymric Heavy Oil	39

8.5.2 Cymric Light Oil	39
9 Conclusions	42
References	43
A Data Analysis	46
B FORTRAN Computer Program TUBE	49

List of Tables

6.1	Sieve analysis of 20-30 mesh Ottawa sand, Unisil Corporation	11
7.1	Experimental conditions for three runs performed with the 12° API Cymric heavy oil.	12
7.2	Experimental conditions for two runs performed with the 34° API Cymric light oil.	13
7.3	Experimental conditions for two runs performed with the 34° API Cymric light oil.	13
8.1	Results for three runs performed with the 12° API Cymric heavy oil.	40
8.2	Results for four runs performed with the 34° API Cymric light oil.	41

List of Figures

6.1	Schematic of the combustion tube and combustion tube holder	7
6.2	The overall combustion system	9
8.1	Produced gas composition, Cymric heavy oil, control run.	16
8.2	Produced gas composition, Cymric heavy oil, iron nitrate run.	17
8.3	Produced gas composition, Cymric heavy oil, zinc nitrate run.	18
8.4	Produced gas composition, Cymric light oil, control run number 1.	19
8.5	Produced gas composition, Cymric light oil, iron nitrate run number 1.	20
8.6	Produced gas composition, Cymric light oil, control run number 2.	21
8.7	Produced gas composition, Cymric light oil, iron nitrate run number 2.	22
8.8	Axial temperature profiles, Cymric heavy oil, control run.	24
8.9	Axial temperature profiles, Cymric heavy oil, iron nitrate run.	25
8.10	Axial temperature profiles, Cymric heavy oil, zinc nitrate run.	26
8.11	Axial temperature profiles, Cymric light oil, control run number 1.	27
8.12	Axial temperature profiles, Cymric light oil, iron nitrate run number 1.	28
8.13	Axial temperature profiles, Cymric light oil, control run number 2.	29
8.14	Axial temperature profiles, Cymric light oil, iron nitrate run number 2.	30
8.15	Liquid production, Cymric heavy oil, control run.	32
8.16	Liquid production, Cymric heavy oil, iron nitrate run.	33
8.17	Liquid production, Cymric heavy oil, zinc nitrate run.	34
8.18	Liquid production, Cymric light oil, control run number 1.	35
8.19	Liquid production, Cymric light oil, iron nitrate control run number 1.	36
8.20	Liquid production, Cymric light oil, control run number 2.	37
8.21	Liquid production, Cymric light oil, iron nitrate run number 2.	38

3. Introduction

In-situ combustion is a thermal oil recovery technique. In this process, air or oxygen is injected through a well to a burning front which propagates through the reservoir burning a portion of the oil in place. Ahead of the burning front is steam, hot water, and combustion gasses. Oil production is improved by a host of mechanisms including frontal displacement, gravity drainage, steam flood, miscible flood, and hot water flood. Although the main application of thermal recovery is to recover viscous, heavy oils, a broad range of oils and reservoirs are potential targets for thermal recovery methods. For in-situ combustion, a major factor limiting its applicability is the amount of fuel deposited on the reservoir matrix ahead of the combustion front. If insufficient fuel is deposited, as can be the case for light oils, the combustion front may not be sustained and subsequently fail. Conversely, if excessive fuel is deposited, as can be the case for many heavy oils, the frontal advance will be slow and the air requirement per unit of production may be too high for economical operation (Alexander et al, 1962, Dew et al, 1964, Chu, 1982, Nelson and McNeil, 1961, Showalter, 1963).

Fuel deposition includes steam distillation of the oil ahead of the combustion front. The residue from steam distillation is available to the combustion process. Previous studies (Baena et al, 1990, Castanier et al, 1992) report on combustion tube studies with metallic additives. They report increased fuel deposition in runs which had either an iron or tin metallic additive. The mechanism by which metallic additives cause an increase in fuel deposition is not fully understood, however. It is possible, but not proven, that the metallic additives affect the steam distillation behavior of the crude oil. At each temperature in the distillation process, if a larger mass fraction remained in the liquid phase, then a greater amount of residue would form on the reservoir matrix. This increase in residue formation would lead to increased fuel concentration.

Two studies report on kinetic experiments with metallic additives (Shallcross, 1991 and De los Rios et al, 1988). They report that metallic additives affected the kinetics of combustion reactions in all three temperature ranges: low, medium, and high temperature oxidation. The kinetics of combustion affects the manner in which the deposited fuel is burned. Therefore, catalytic compounds which affect kinetics could affect the overall performance of a combustion process. It is also possible, but again not proven, that catalytic compounds increase fuel concentration by affecting the kinetics of lower temperature reactions occurring ahead of the combustion front. These lower temperature oxidation reactions would be acting as fuel formation reactions. Therefore, as a result of increased reaction rates for lower temperature oxidation, larger amounts of residue could be formed, leading to increased fuel concentration.

Interest in the effects of metallic additives on the combustion process was largely influenced by the success of a metallic additive field pilot reported by Racz (1985). Racz reports that in the Demjen field in Hungary, sustained combustion could not be obtained due to low fuel concentration. The later addition of an aqueous metallic compound allowed sustained combustion to be achieved. By employing the catalyzed combustion technique, the field pilot was successful and a recovery factor of 60% was eventually reached. The ability to sustain combustion in the reservoir was attributed to the catalytic properties of the metallic

additive which increased fuel concentration.

It is the goal of this study to investigate the effects of metallic additives both quantitatively and qualitatively. Combustion tube studies are conducted and analyzed with the goal of furthering the understanding of the effects of metallic additives. The oils used are Cymric heavy (12° API) and Cymric light (34° API), both from California. The additives are zinc nitrate ($Zn(NO_3)_2 \cdot 6H_2O$) and iron nitrate ($Fe(NO_3)_3 \cdot 9H_2O$).

4. Literature Survey

Published work on the effects of metals on the in-situ combustion process first appeared in the 1970's. These papers report observations of increased air requirements and increased fuel deposited in reservoirs which had a high content of metals-rich minerals (Earlougher et al, 1970, Hardy et al, 1972, Burger and Sahuquet, 1974). Laboratory research on combustion with metals includes kinetic studies (Burger and Sahuquet, 1974, Fassihi et al, 1981, Racz, 1985, De los Rios et al, 1988, Shallcross, 1989), and combustion tube studies (Baena et al, 1990, Castanier et al, 1992, Vossoughi et al, 1982). One paper, (Racz, 1985) reports a successful field application of aqueous metallic additives. The following is a summary of the results of the above papers.

4.1 Field Studies with Metals and Metallic Additives

The effects of metals on in-situ combustion were first noticed in reservoirs containing high concentrations of metals rich minerals. An in-situ combustion field test was conducted on the 40° API May Libby reservoir in the Delhi field (Hardy et al, 1972). Before the actual May Libby field experiment was conducted, laboratory combustion tube tests were performed on native core material and also on a man made mixture of 95% sand and 5% clay. They reported that combustion could not be sustained in the man made core, but stable, sustained combustion was achieved in the native core material. Larger amounts of fuel were deposited in the native core material. In the field, combustion was successful, and was attributed to the metal content of natural minerals which acted as catalysts to the combustion process.

The only published report of a metallic additive solution being injected into a reservoir to enhance combustion is by Racz (1985). Racz reports a 50x50 meter field test on the 39° API Demjen field in Hungary. Early attempts at combustion in the Demjen reservoir were unsuccessful because a sustained combustion front could not be achieved. The chemical tertiary butylhydroperoxide (TBH) was injected along with air until combustion was initiated. After combustion was initiated, a 1% solution of iron pentacarbonyl was injected. The results were quite favorable. A sustained combustion front was achieved and an overall recovery factor of 60% was reached. The iron solution proved to be an effective catalyzing agent.

4.2 Kinetic Studies with Metallic Additives

Several studies on the effects of metallic additives on the kinetics of crude oil combustion have been performed. Of particular importance to the present study are the kinetics studies performed by De los Rios et al (1988), and Shallcross (1989) at Stanford University. De los Rios performed kinetic experiments on Huntington Beach oil and various metallic additives. Shallcross performed kinetic experiments on Huntington Beach and Venezuelan oils with various metallic additives. Both studies analyzed oxygen consumption data by decoupling the total oxygen consumption data into three parts. This was done to represent the oxygen consumed by three competing groups of reactions. They found that the metallic additives iron and tin increased oxygen consumption. They also reported that iron and tin

increased the reaction rates for the oxidation reactions. They found that zinc did not produce the effects reported for iron and tin. From the results of these studies it is expected that iron and tin may be useful agents in catalyzing combustion reactions.

Burger and Sahuquet (1974) report on two kinetic experiments on crude oil with 2000 ppm copper metal. The experiments were performed on a 27° API oil. They found that the activation energy for the low temperature oxidation reactions were lowered by the presence of copper metal.

Fassihi et al (1981) report on kinetic experiments with 2000 ppm copper. They found that the activation energy of the low temperature reaction was unaffected, but its reaction rate was increased. Fassihi also reported that the activation energy for the high temperature portion of the reaction was reduced.

To summarize, it has been found by previous researchers that the presence of certain metals can affect the kinetic parameters used to model combustion reactions. These kinetic experiments can give estimates of activation energies and rates of reaction for combustion reactions. Tube studies and field experiments are required to estimate fuel concentration, air requirements, and front velocity.

4.3 Tube Studies with Metallic Additives

Observations that the physical and chemical nature of core material can affect the combustion performance in tube runs was made by several researchers (Vossoughi et al, 1982, Hardy et al, 1972, Alexander et al, 1962). Their observations show that, for a particular oil, more fuel can be expected from a native core than from a clean sand pack. This is believed to result from both physical and chemical processes. Fine grained material in native cores provides more surface area for combustion reactions while metals in natural minerals act as catalysts.

Two recent studies have investigated the effects of metallic additives on combustion tube experiments (Baena et al, 1996, Castanier et al, 1992). Baena reports on experiments with 22° API Huntington Beach Oil. Baena reports that tin and iron additives increased oxygen utilization efficiency, burning front velocity, and fuel concentration. The zinc additive showed a lesser effect. Castanier et al (1992), report on thirteen metallic additive combustion tube runs. Of the 13 runs, four are Baena's runs described above, five runs are from the present study, and the remaining four runs are previously unpublished runs made with 10° API Hamaca oil. The runs show that tin and iron increased fuel deposition, oxygen utilization efficiency, and front velocity while zinc was less effective.

5. Statement of Purpose

The applicability of in-situ combustion is largely influenced by the physical and chemical processes involved in fuel deposition and oxidation. In light oil reservoirs, a lack of fuel deposition may prevent the formation of a sustained, stable combustion front. In heavy oil reservoirs, a large amount of fuel may be deposited resulting in uneconomically high oxidizing gas requirements. Observations by previous researchers show that certain metals promote the combustion process. In this study, the effects of metallic additives will be studied both quantitatively and qualitatively by performing combustion tube experiments.

Based on field observations, several researchers have reported increased fuel deposited in reservoirs which had a high concentration of metals present in natural minerals (Hardy et al, 1972, Earlougher et al, 1970). Racz (1985) reports on a metallic additive catalyzed combustion field pilot in Hungary. In this field project, a reservoir which had previously failed to sustain combustion was successfully burned by catalyzing with 1% iron pentacarbonyl solution.

In the laboratory, both kinetic and tube studies have been performed to study the effects of metallic additives. Kinetic studies were performed by De los Rios et al (1987) and Shallcross (1989). The results of kinetic studies show that the metals iron and tin caused a marked increase in both oxygen consumption and oxidation rate in crude oil combustion. Other metals, zinc, magnesium, chromium, and manganese produced less pronounced effects. Combustion tube studies were performed by Baena et al (1990) and Castanier et al (1992). The results of these combustion tube experiments showed increased fuel deposition and efficiency for iron and tin additives. Zinc showed little or no effect. The above kinetic and tube studies were performed on both Huntington Beach (California) and Hamaca (Venezuela) oils.

The present study consists of a series of seven combustion tube experiments performed with two different oils and two aqueous metallic additives. The oils are Cymric light, 34° API, and Cymric heavy, 12° API, both from California. The additive used are 1% mole iron nitrate and 1% mole zinc nitrate. Three runs were performed with the Cymric heavy oil: control run, iron nitrate run, and zinc nitrate. Four runs were performed with the Cymric light oil: two control runs and two iron nitrate runs.

6. Experimental Equipment and Procedure

The experimental system and procedure are similar to that used by several previous researchers at Stanford University (Satman et al, 1979, Fassihi et al, 1982, Andrade, 1984, Sidqi et al, 1985, Baena et al, 1990). The design and operating conditions of the experiments are described below.

6.1 Experimental Equipment

The equipment consists of three units: the combustion tube, the combustion tube holder, and the overall system.

6.1.1 Combustion Tube

The combustion tube is made of stainless steel alloy (SS 321). Its dimensions are 1.0 meter in length, 7.5 cm. I.D., with a 0.041 wall thickness. Flanges are attached to each end of the tube with silver solder. Flange covers are attached using 0.64 cm. diameter bolts and matching nuts. A brass o-ring gasket is used between the flange and flange cover. Figure 6.1 shows the combustion tube, which has been loaded into the tube holder.

Two 240 V, 1000 W *Watlow*[™] heater coils, which serve as ignition heaters, are wrapped around the combustion tube at distances of 5 and 10 cm. from the top flange. The heater at 5 cm is the primary ignition heater while the heater at 10 cm serves as a backup in the case that the first heater should fail to ignite the sand pack. Power is supplied to the heaters with a 240 V *Powerstat*[™] variable autotransformer.

A small diameter tube, which is referred to as the thermowell, is placed along the axis of the combustion tube. The thermowell is 120 cm in length, 1/16 inch O.D., with a wall thickness of 0.006 inch., and is made of stainless steel alloy (SS 321). The bottom end of the thermowell is sealed with a stainless steel ferrule. A 7.4 cm circle of 200 Tyler mesh screen is attached to the bottom end of the thermowell. Before packing the tube, the screened end of the thermowell is placed inside of the combustion tube, with the screened end on the bottom. The top end of the thermowell extends out of the tube through the inlet T connector. The thermowell is sealed with a teflon ferrule at the top. The top end of the thermowell remains open to allow a thermocouple to be moved into the thermowell. This thermocouple can be moved to record vertical temperature profiles along the axis of the tube.

The combustion tube is placed in a thermally insulated unpressurized tube holder. The tube holder is 15.0 cm. I.D. and 25.0 cm O.D. and is insulated with a permanent pack of *Dacotherm*[™] insulation. The annular space between the combustion tube and the inner wall of the tube holder is insulated with a removable pack of vermiculite. The vermiculite is removed after each run and replaced before the next run.

Three *Brisket*[™] electrical heating tapes are wound inside the tube holder. These heaters are controlled by three *Love*[™] proportional temperature controllers. These heaters and controllers are used together to attain a preheat of the sandpack to 90 °F. This is done to approximate a reservoir temperature and does not drive the combustion process.

Combustion Tube

Figure 6.1: Schematic of the combustion tube and combustion tube holder

6.1.2 Experimental System

The experimental system consists of the supply equipment, flow lines, separators, condenser, dessicator, acid scrubber and analyzing devices. Figure 6.2 is a schematic of the experimental system.

Air supply to the combustion tube is controlled by a *Matheson*[™] mass flow controller. Between the supply tanks and the mass flow controller is a pressure regulator. A liquid-gas separator is connected to the outlet end of the combustion tube. This separator is wrapped with heating tape to prevent plugging due to heavy, viscous oils. Liquid production samples are taken from this separator which is equipped with a two valve sampling chamber. The first valve opens the bottom of the separator into the sampling chamber. With the first valve closed, the second valve opens the sampling chamber to atmosphere allowing a 50 ml sample bottle to be filled for later analysis.

The gas stream coming away from the separator flows through a shell and tube cold water condenser. A pump circulates water at approximately 0 °C through the condenser shell. This process removes condensible gasses such as steam from the gas stream.

The gas stream then flows through a packed bed of Drierite dessicating material. This process removes a further amount of moisture. The gas stream then passes through a packed bed of permanganate acid removal material. This process removes potentially damaging acid gasses from the gas stream protecting the analyzing equipment. Acid gasses were particularly prevalent in metallic additive runs.

The gas stream, now dry, then flows through a bank of gas analyzers and meters. The gas is first metered by a *Matheson*[™] electronic mass flow indicator. It is then split into three streams. Stream 1 flows into a *Beckman*[™] carbon dioxide analyzer and then into a *Beckman*[™] carbon monoxide analyzer. Stream 2 flows into a *Teledyne*[™] oxygen analyzer. Stream 3 flows into the gas chromatograph. The three streams are then combined and vented.

A Hewlett-Packard 3497A data logger communicates data to a 386SX *IBMPC*[™] clone computer. Data are logged every 30 seconds and include voltages from the gas analyzers, nitrogen composition from the G.C., and flow rate from the tube inlet and outlet.

Temperature profile data is recorded manually. A vertical meter stick is attached above the tube holder. A marker is placed on the thermocouple and moved in front of the meter stick to determine thermocouple position. One worker moves the thermocouple to a position and reads distance in centimeters on the meter stick. An assistant then records distance and the temperature reading from the digital voltmeter. This temperature versus distance data provides temperature profiles and front position information.

A *Damon*[™] IEC PR-6000 centrifuge is used to facilitate the separation of oil and water in the liquid samples. Into each liquid sample bottle, a 0.2 ml dose of *Tetrolite*[™] RN 3003 is added before placing in the centrifuge to aid in breaking down oil-water emulsions.

6.2 Experimental Procedure

This section describes the procedure employed during all seven. This procedure is very similar to the procedure used by previous researchers at Stanford University. The following steps were used in the combustion tube experiments:

Combustion Tube System

Figure 6.2: The overall combustion system

1. The combustion tube is first assembled with the thermowell in place and leak checked with nitrogen to 150 psi. The top flange is then removed to allow the sand mixture to be packed into the tube.

2. The sand pack mixture is prepared. Known masses of 20-30 mesh Ottawa sand, clay, oil, and aqueous solution are mixed in a 2 gallon bucket. For a control run, the aqueous solution is distilled water. For a metallic additive run, the aqueous solution is a 1% mole aqueous metallic solution. Table 6.1 shows a sieve analysis of the Ottawa sand as reported by Baena et al (1990). Mixing is continued until the mixture is uniform. Material balance calculations are performed to estimate porosity and saturations.

3. The combustion tube is packed as follows. A 200-300cc scoop of the sand mixture is dropped into the tube from the top. Each scoop fills about 3 to 4 cm of the tube. The sand pack is then tamped from the top. Before the next scoop is dropped in, the top of sand pack is scratched to a depth of about 0.5 cm. This scratching process allows the next scoop to join the sand pack more readily. The tube is packed to within 5 cm. of the top flange, giving a 95 cm. pack.

4. Five milliliters of raw linseed oil are poured on top of the sand pack to facilitate ignition. The remaining 5 cm at the top of the tube is packed with clean, dry sand. The dry sand serves as a flow diffuser for the air, and prevents high combustion temperatures from damaging the top flange.

5. The top flange is replaced and the tube is again pressure tested to 150 psi. The combustion tube is then placed into the tube holder. To provide thermal insulation, the annular space between the combustion tube and tube holder is packed with vermiculite.

6. The combustion tube inlet and outlet connections are made. The entire system is then tested for leaks, to 150 psi. The electrical connections for the igniter are made.

7. The ambient heaters are turned on and set to 90 °F, to preheat the core. The system is then allowed 10 to 14 hours to achieve thermal equilibrium.

8. The experiment begins by taking an initial temperature profile with the axial thermocouple.

9. The gas analyzers are calibrated using four different calibration gasses of known composition.

10. The ignition heater and data logging system are turned on. The data logging system logs CO_2 , CO , O_2 , N_2 , inlet flow rate, outlet flow rate, and pressure drop every thirty seconds for the entire length of the experiment. The thermocouple is moved within the thermowell to the position 5 cm from the top of the tube, adjacent to the top ignition heater.

11. When the top of the pack reaches about 250 °C, a 3.0 slpm continuous flow of air is started. The thermocouple is moved to 7 cm. When the combustion front reaches 7 cm. the ignition heater is turned off, and a temperature profile is taken by traversing the length of the tube with the thermocouple.

12. The thermocouple is then moved to 10 cm. and the increasing temperature is monitored as the front approaches. When the front arrives at 10 cm., the time and peak temperature are recorded. A temperature profile is immediately taken. The thermocouple is moved to 15 cm., and the procedure is repeated when the front arrives there. This procedure is continued on 5 cm. intervals until the front reaches 90 cm.

13. During the experiment, liquid samples are collected in 50 ml sample bottles. A typical run will produce enough liquid to at least partially fill 15 to 20 of these liquid

Sieve Size (Tyler mesh)	Percent Retained (by mass)
20	4.70
24	82.1
28	11.9
32	0.55
35	0.36
60	0.24
>60	0.18

Table 6.1: Sieve analysis of 20-30 mesh Ottawa sand, Unisil Corporation

sample bottles.

14. When the combustion front reaches about 90 cm., the feed gas is switched from air to nitrogen which quenches the combustion. The gas analyzers are calibrated again. The tube is left to cool 12 to 24 hours.

15. The cooled tube is removed from the tube holder and unpacked. Sand samples are taken from the combustion tube for later study. These samples include regions behind and ahead of the combustion front.

16. The fluid samples are centrifuged for about 15 min. at 3500 rpm to aid in separating oil and water.

17. The combustion data is processed with the computer program TUBE. (see Appendix B)

7. Experimental Program

A total of seven combustion tube runs were performed in this study. A series of three runs was first made with Cymric heavy oil (12° API). A second series of two runs was performed with Cymric light oil (34° API). Additionally, a third series of two runs was performed with Cymric light oil. The objective of each series of runs was to compare the behavior of a control run to runs made with an aqueous metallic additive. Each series was designed such that control runs and additive runs had the same porosity, oil saturation, water saturation, operating pressure, air flow rate, clay/sand ratio, and initial temperature.

Table 7.1 lists the conditions for the first series of runs with the Cymric heavy oil. The first run was a control run which contained no metallic additive. The second and third runs contained 1% mole aqueous solutions of iron nitrate and zinc nitrate, respectively.

Table 7.2 lists the operating conditions for the first series of two runs made with the Cymric light oil. The first run was a control run. The second run had 1% mole iron nitrate in its water saturation.

Table 7.3 lists the operating conditions for the second set of two runs performed with the Cymric light oil. This series of two runs had lower porosity, higher oil saturation, higher water saturation, and higher sand/clay ratio than the first set of two runs made with the Cymric light oil.

Type of Run	Control Run	Iron Nitrate	Zinc Nitrate
Length of Pack,cm	95.0	95.0	95.0
Porosity, %	38.4	38.9	38.0
Oil Saturation,%	20.8	20.3	21.4
Water Saturation,%	18.7	18.5	19.2
Clay/Sand Mass Ratio,%	5.3	5.3	5.3
Air Flow Rate, slpm	3.0	3.0	3.0
Concentration of Metal,%mole	0.0	1.0	1.0

Table 7.1: Experimental conditions for three runs performed with the 12° API Cymric heavy oil.

Type of Run	Control	Iron Nitrate
Length of Pack,cm	95.0	95.0
Porosity, %	37.3	37.6
Oil Saturation,%	19.5	25.3
Water Saturation,%	9.8	9.7
Clay/Sand Mass Ratio,%	7.0	7.0
Air Flow Rate,slpm	2.0	2.0
Concentration of Metal,%mole	0.0	1.0

Table 7.2: Experimental conditions for two runs performed with the 34° API Cymric light oil.

Type of Run	Control	Iron Nitrate
Length of Pack,cm	95.0	95.0
Porosity, %	35.1	34.7
Oil Saturation,%	36.0	39.4
Water Saturation,%	11.1	11.3
Clay/Sand Mass Ratio,%	11.3	11.3
Air Flow Rate,slpm	3.0	3.0
Concentration of Metal,%mole	0.0	1.0

Table 7.3: Experimental conditions for two runs performed with the 34° API Cymric light oil.

8. Results and Discussion

In this section the results of seven combustion tube runs are presented. First, some qualitative observations are made. Following the qualitative observations, data are presented and discussed.

8.1 Qualitative Observations - Sustained Combustion

Sustained combustion was achieved in all Cymric heavy oil runs. The control run as well as the iron and zinc additive runs ignited readily and burned in a sustained manner.

In the Cymric light oil runs, however, sustained combustion was not achieved in all experiments. In the two control runs, sustained combustion was not achieved. In these runs, ignition was achieved, but the combustion front extinguished after moving only 1-2 centimeters into the sand pack. When these runs were repeated with the iron nitrate additive, sustained combustion did occur. This result is important because, without the need for calculations, information is given about the effects of metallic additives. The iron additive allowed combustion in a situation where sustained combustion was otherwise impossible or difficult to achieve.

8.2 Produced Gas Compositions

In this section produced gas compositions are presented for all seven runs. The data presented are percent volume for carbon dioxide, carbon monoxide, and oxygen versus time. The data logging system was programmed to digitally record voltages from the gas analyzers at 30 second intervals. Calibration data was then used to convert the voltages into composition percentages.

8.2.1 Cymric Heavy Oil

Figure 8.1 shows produced gas composition for the control run with Cymric heavy oil. The pack ignited after about 20 minutes as is evidenced by the rise in carbon dioxide composition from 0 to about 15%. The sand pack burned for 450 minutes and was then quenched. The gas composition showed fluctuations on the order of 3 to 4 percent. The instruments are accurate to less than 1 mole percent, therefore the fluctuations are significant. Notice that the carbon monoxide composition showed less fluctuation than the carbon dioxide and oxygen. These fluctuations are likely caused by surging and waning instabilities in the combustion reactions. Average values were used for the purpose of calculating combustion parameters. For this run, average CO_2 was 9.24%, and average O_2 was 2.14%.

Figure 8.2 shows the produced gas composition for Cymric heavy oil with 1% iron nitrate solution. Ignition was achieved at 20 minutes. Combustion proceeded in a stable manner for 415 minutes and was then quenched. Carbon dioxide composition was increased and oxygen was decreased as compared to the control run. In this run, average CO_2 was

15.5%, and average O_2 was 0.69%. Fluctuations in gas compositions were greatly reduced in this run.

Figure 8.3 shows produced gas composition for Cymric heavy oil with 1% zinc nitrate solution. Ignition was achieved at 15 minutes. Combustion proceeded for 440 minutes and was then quenched. In this run strong fluctuations were again prevalent in gas compositions. The fluctuations in this run were greater than those in the control run. Carbon dioxide composition and oxygen composition were both slightly higher than the control run. Composition averages were, 11.9% for CO_2 , and 2.37% for O_2 .

8.2.2 Cymric Light Oil

Figure 8.4 shows the produced gas composition for the first control run with Cymric light oil. Ignition was achieved at about 40 minutes as evidenced by the increase in carbon dioxide composition from 0 to 16%. The combustion front did not propagate, however. At 45 minutes carbon dioxide composition began to decrease as the combustion front began to fail. At 150 minutes, carbon dioxide composition had decreased to less than 1% while oxygen composition reached 20%. Sustained combustion was not achieved.

Figure 8.5 shows the gas composition for the first run with Cymric light oil with 1% iron nitrate solution in its water saturation. Ignition was achieved at 15 minutes, as shown by an increase in carbon dioxide to 16%. A combustion front propagated in the tube for 425 minutes, and was then quenched. Sustained combustion was achieved. This run was similar to the light oil control run described above with the exception of the addition of 1% iron nitrate solution.

Figure 8.6 shows produced gas composition for the second control run with Cymric light oil. Ignition was achieved at about 5 minutes as evidenced by the increase in carbon dioxide composition from 0 to 13%. The combustion front did not propagate, however. At 10 minutes carbon dioxide composition began to decrease as the combustion front began to extinguish. The backup ignition heater was turned on at 40 minutes to attempt re-ignition. Carbon dioxide increased to 8% but then decreased rapidly. At 100 minutes, carbon dioxide had decreased to less than 1% while oxygen production reached 18%. Sustained combustion was not achieved.

Figure 8.7 shows the gas composition for the second run with Cymric light oil with 1% iron nitrate solution. Ignition was achieved at 25 minutes, as shown by an increase in carbon dioxide to 17%. A combustion front propagated in the tube for 325 minutes, and was then quenched. Sustained combustion was achieved. This run was similar to the run described above, with the exception of the addition of 1% iron nitrate solution.

8.3 Temperature Profiles

This section presents temperature profile data. Temperature profile data were taken approximately every 20 minutes. Temperature profile data for the second Cymric light oil run were lost due to mechanical failure of the thermowell well during the beginning of the experiment.

12 API Cymric Heavy Oil -- Control Run

Figure 8.1: Produced gas composition, Cymric heavy oil, control run.

12 API Cymric Heavy Oil -- Iron Nitrate Run

Figure 8.2: Produced gas composition, Cymric heavy oil, iron nitrate run.

12 API Cymric Heavy Oil -- Zinc Nitrate Run

Figure 8.3: Produced gas composition, Cymric heavy oil, zinc nitrate run.

34 API Cymric Light Oil -- Control Run #1

Figure 8.4: Produced gas composition, Cymric light oil, control run number 1.

34 API Cymric Light Oil -- Iron Nitrate Run #1

Figure 8.5: Produced gas composition, Cymric light oil, iron nitrate run number 1.

34 API Cymric Light Oil -- Control Run #2

Figure 8.6: Produced gas composition, Cymric light oil, control run number 2.

34 API Cymric Light Oil -- Iron Nitrate Run #2

Figure 8.7: Produced gas composition, Cymric light oil, iron nitrate run number 2.

8.3.1 Cymric Heavy Oil

Figure 8.8 shows the vertical temperature profiles for the Cymric heavy oil control run. The combustion front propagated through the sand pack with fairly uniform velocity and peak temperature. Average velocity was 12.3 centimeters per hour, and average peak temperature was 501.7 °C.

Figure 8.9 shows the axial temperature profiles for the Cymric heavy oil iron nitrate run. The combustion front propagated through the sand pack with fairly uniform velocity and peak temperature. The front velocity and peak temperature averages were both higher than in the control run. Average front velocity was 13.9 centimeters per hour, and average peak temperature was 539.3 °C.

Figure 8.10 shows the axial temperature profiles for the Cymric heavy oil zinc nitrate run. The combustion front propagated through the sand pack with fairly uniform velocity and peak temperature. The front velocity was 12.1 centimeters per hour which was slightly lower than the control run. Front temperature was 517.8 °C, which was slightly higher than the control run.

8.3.2 Cymric Light Oil

Figure 8.11 shows the axial temperature profiles for the first control run with Cymric light oil. Ignition was achieved but not sustained in this experiment. At 30 minutes, a temperature of 475 °C was recorded near the heater located at 5 centimeters. The combustion front then began to rapidly lose temperature as the experiment progressed. After 121.0 minutes, the front had moved 5 centimeters, but its temperature had fallen to 200 °C. The combustion front had spontaneously extinguished.

Figure 8.12 shows the axial temperature profiles for the first iron nitrate run with Cymric light oil. Ignition was achieved and sustained in this experiment. Mechanical failure of the thermowell early in the experiment prevented the collection of most of the temperature profile data. Two profiles were successfully recorded and are shown. Front temperature was 505.0 °C.

Figure 8.13 shows the axial temperature profiles for the second control run with Cymric light oil. Ignition was achieved but not sustained in this experiment. At 6.0 minutes, a temperature of 495 °C was recorded near the heater located at 5 centimeters. The combustion front then began to rapidly lose temperature as the experiment progressed. After 77.0 minutes, the front had moved 7 centimeters, but its temperature had fallen to 325.0 °C. The combustion front had spontaneously extinguished.

Figure 8.14 shows the axial temperature profiles for the second iron nitrate run with Cymric light oil. Sustained combustion was achieved in this experiment. The front propagated through the sand pack with fairly uniform velocity and peak temperature. Average velocity was 12.7 centimeters per hour, and average peak temperature was 537.9 °C.

8.4 Liquid Production

This section presents the liquid production. Liquid samples were taken from the separator at approximately 20 minute intervals. Emulsions of oil and water were processed by adding a drop of demulsifying agent and placing in a 3500 rpm centrifuge for 30 minutes.

Figure 8.8: Axial temperature profiles, Cymric heavy oil, control run.

Figure 8.9: Axial temperature profiles, Cymric heavy oil, iron nitrate run.

Figure 8.10: Axial temperature profiles, Cymric heavy oil, zinc nitrate run.

Figure 8.11: Axial temperature profiles, Cymric light oil, control run number 1.

Figure 8.12: Axial temperature profiles, Cymric light oil, iron nitrate run number 1.

Figure 8.13: Axial temperature profiles, Cymric light oil, control run number 2.

Figure 8.14: Axial temperature profiles, Cymric light oil, iron nitrate run number 2.

The packed tubes were placed into the assembly and remained for about 10 hours during the equilibration period (overnight). During this time oil drained from the pack into the separator. For the purpose of calculating oil saturations, the volume of oil drained from the pack was accounted for. Gravity drainage did not occur in any of the heavy oil runs, but did occur in the light oil runs.

8.4.1 Cymric Heavy Oil

Figure 8.15 shows the liquid production for the control run with Cymric heavy oil. There was no gravity drainage prior to start of experiment. First water production occurred at 170 minutes. Oil production began at 230 minutes. Oil production versus time formed a fairly straight line, inferring piston-like displacement. Total water production was 282 grams, total oil production was 276 grams.

Figure 8.16 shows the liquid production for the iron nitrate run with Cymric heavy oil. There was no gravity drainage prior to start of experiment. Total water production and total oil production were similar to the control run, 261 grams, and 286 grams, respectively. Water production began at 120 minutes, and oil production began at 180 minutes. Both water and oil began production at earlier times than control run. This was expected, because the front velocity was increased in this run.

Figure 8.17 shows the liquid production for the zinc nitrate run with Cymric heavy oil. There was no gravity drainage prior to start of experiment. Total water production and total oil production were 344 grams, and 223 grams, respectively. Total water production was higher than the control run, while total oil production was less than the control run. Water production began at 180 minutes, and oil production began at 260 minutes. Both water and oil began production at later times than control run. This is expected because the front velocity decreased in the zinc nitrate run.

8.4.2 Cymric Light Oil

Figure 8.18 shows the liquid production for the first control run with Cymric light oil. The gravity drainage prior to the experiment was 213 grams of oil. In this experiment, combustion was achieved but not sustained. No fluid production samples were collected before the combustion front extinguished.

Figure 8.19 shows the liquid production for the first iron nitrate run with Cymric light oil. Gravity drainage prior to start of experiment was 106 grams of oil. First water production occurred at 300 minutes. Oil production began at 20 minutes. Oil production versus time formed a fairly straight line, inferring piston-like displacement. Total water production was 25 grams, total oil production was 265 grams.

Figure 8.20 shows the liquid production for the second control run with Cymric light oil. The gravity drainage prior to the experiment was 299 grams of oil. In this experiment, combustion was achieved but not sustained. No fluid production were collected before the combustion front extinguished.

Figure 8.21 shows the liquid production for the first iron nitrate run with Cymric light oil. Gravity drainage prior to start of experiment was 256 grams of oil. First water production occurred at 200 minutes. Oil production began at 20 minutes. Total water production was 110 grams, total oil production was 492 grams.

Figure 8.15: Liquid production, Cymric heavy oil, control run.

Figure 8.16: Liquid production, Cymric heavy oil, iron nitrate run.

Figure 8.17: Liquid production, Cymric heavy oil, zinc nitrate run.

Figure 8.18: Liquid production, Cymric light oil, control run number 1.

Figure 8.19: Liquid production, Cymric light oil, iron nitrate control run number 1.

Figure 8.20: Liquid production, Cymric light oil, control run number 2.

Figure 8.21: Liquid production, Cymric light oil, iron nitrate run number 2.

8.5 Effect of Metallic Additives

In this section the effects of metallic additives on combustion parameters as determined by the method of Dew and Martin (1964,1965) are presented. The FORTRAN computer program TUBE was used to process combustion data. The program TUBE is shown in Appendix B.

8.5.1 Cymric Heavy Oil

Table 8.1 lists the calculated combustion parameters for the Cymric heavy oil tube runs. Both the iron and the zinc additives increased the concentration of carbon dioxide and carbon monoxide in the produced gas. Oxygen concentration in the produced gas was decreased by the iron additive. The zinc additive caused a slight increase in the oxygen concentration in the produced gas. Combustion front velocity was increased by the iron additive, but was decreased slightly by the zinc additive. The inlet flow rate of air was identical for these three runs. The outlet air flow rate was increased somewhat by both the iron and zinc additives.

Oxygen utilization efficiency provides a measure of the fraction of injected oxygen which is used by oxidation reactions. Oxygen utilization efficiency for the control run was 90.5%. The iron additive increased the oxygen utilization efficiency to 96.7%, while the zinc additive caused a decrease to 89.1%. The iron additive proved to be a good agent for increasing efficiency.

The nature and amount of fuel formed was affected by the presence of metallic additives. The apparent hydrogen to carbon ratio of the deposited fuel was compared. For the control run, an H/C ratio of 2.64 was calculated. The iron additive run showed an H/C ratio of 0.57, the zinc additive run, 1.40. By lowering the H/C ratio of the fuel, the additives made the fuel more carbonaceous. This was especially true for the iron additive.

The iron nitrate additive was effective in increasing fuel concentration. The control run showed a fuel concentration of 2.74 lbs./cu.ft., while the iron nitrate run showed a fuel concentration of 3.29 lbs./cu.ft. Zinc was not as effective as iron, the zinc additive run has a fuel concentration of 2.90 lbs./cu.ft., only slightly higher than the control run.

Another combustion parameter of interest is the air requirement, expressed in (scf. air/ cu. ft. reservoir). For the control run, an air requirement of 343.9 scf/cu.ft. was calculated. For the iron nitrate run, air requirement was 310.2 scf/cu.ft. For the zinc nitrate run, 335.3 scf/cu.ft. It is interesting to note that while the iron additive increased fuel concentration, it also reduced air requirement. This apparent discrepancy is explained by the observation that the chemical nature of the fuel may have been affected by the presence of the iron additive. An equal amount of fuel may be burned by different amounts of air, if those fuels are chemically different. Furthermore, combustion front velocity was also increased by the iron additive. These two effects act together to explain how more fuel can be burned with less air in the iron additive run.

8.5.2 Cymric Light Oil

Table 8.2 shows the results for four runs made with the Cymric light oil. In both iron nitrate runs, sustained combustion was achieved. In both control runs, however, sustained

Run Type	Control	Iron Nitrate	Zinc Nitrate
Sustained Combustion	YES	YES	YES
Average CO ₂ ,%	9.24	15.5	11.9
Average CO,%	4.40	4.30	3.92
Average O ₂ ,%	2.14	0.69	2.37
H/C Ratio	2.64	0.57	1.40
Oxygen Utilization Efficiency, %	90.5	96.7	89.1
Air-Fuel Ratio,(scf/lbfuel)	184.3	148.4	165.1
Heat of Combustion,(btu/lbfuel)	20220	14525	17150
Fuel Concentration,(lbs/cu.ft.)	2.74	3.29	2.90
Air Requirement,(scf/cu.ft.)	343.9	310.2	335.3
Front Velocity,(cm./hr.)	12.3	13.9	12.1
Front Temperature,(C)	501.7	529.3	517.8
Inlet Air Flow,(liter/min.)	2.99	2.99	2.99
Outlet Air Flow,(liter/min.)	2.80	2.97	2.89
Concentration of Metal,%mole	0.0	1.0	1.0

Table 8.1: Results for three runs performed with the 12° API Cymric heavy oil.

combustion was not achieved.

The combustion performance parameters calculated for the two iron nitrate runs are fairly consistent. The two runs were fairly similar with respect to combustion performance. The two control runs were also consistent, both did not produce sustained combustion.

The qualitative observation that the control runs did not burn, while the iron additive runs did burn provides much evidence to the effect of metallic additives. As described above, the iron additive increased fuel concentration and oxygen utilization efficiency for the Cymric heavy oil. In the Cymric light oil, the control runs lacked sufficient fuel to allow sustained combustion. The addition of 1% mole iron nitrate solution to the sand pack increased fuel concentration and efficiency enough to allow sustained combustion.

Run Type	Control	Iron Nitrate	Control	Iron Nitrate
Sustained Combustion	NO	YES	NO	YES
Average CO ₂ ,%	n/a	15.40	n/a	14.65
Average CO,%	n/a	3.35	n/a	3.65
Average O ₂ ,%	n/a	0.19	n/a	0.28
H/C Ratio	n/a	0.92	n/a	1.07
Oxygen Utilization Efficiency, %	n/a	99.1	n/a	98.7
Air-Fuel Ratio,(scf/lbfuel)	n/a	159.2	n/a	161.3
Heat of Combustion,(btu/lbfuel)	n/a	16150	n/a	16500
Fuel Concentration,(lbs/cu.ft.)	n/a	3.08	n/a	3.08
Air Requirement,(scf/cu.ft.)	n/a	302.6	n/a	322.4
Front Velocity,(cm./hr.)	n/a	8.9	n/a	12.68
Front Temperature,(C)	n/a	505.0	n/a	537.9
Inlet Air Flow,(liter/min.)	n/a	2.00	n/a	3.01
Outlet Air Flow,(liter/min.)	n/a	1.95	n/a	2.92
Concentration of Metal,%mole	0.0	1.00	0.0	1.00

Table 8.2: Results for four runs performed with the 34° API Cymric light oil.

9. Conclusions

The effects of aqueous solutions of iron nitrate and zinc nitrate on combustion tube performance have been studied for two different crude oils, Cymric heavy (12° API), and Cymric light (34° API).

The results for the Cymric heavy oil show that iron nitrate is an effective agent for increasing fuel deposition. Addition of a 1% mole iron nitrate solution increased fuel concentration by 20% as compared to the control run. Zinc nitrate increased fuel concentration by only 5%. The iron nitrate additive reduced the air fuel ratio by 19.5% as compared to the control run. This result is notable. An increase in fuel concentration would normally be expected to increase air requirements. In the case of the iron nitrate run, however, 20% more fuel was burned with 19.5% less air. This was possible because for the iron nitrate run, the fuel deposited was chemically different than that deposited in the control run. Evidence for this explanation is provided by considering the changes that occurred in the apparent H/C ratio of the deposited fuel. For the control run, an H/C ratio of 2.64 was calculated. For the iron nitrate run, an H/C ratio of 0.57 was calculated. These fuels require different amounts of air to burn unit masses.

For the case of the runs with Cymric light oil, a particularly interesting result occurred. In all, two control runs and two iron nitrate runs were conducted with the Cymric light oil. In both control runs, despite earnest attempts, sustained combustion could not be achieved. The combustion fronts were started, but rapidly died while only moving a few centimeters. Lack of sufficient fuel prevented sustained combustion. These failed runs were repeated under identical conditions with the exception of the addition of 1% mole iron nitrate solution. The iron nitrate runs did produce sustained combustion. The addition of iron nitrate increased fuel concentration and efficiency in a sufficient amount to allow sustained combustion. This qualitative observation provides much evidence to the efficacy of metallic additives.

These results are consistent with results of previous studies of the effects of metallic additives on combustion tube experiments, specifically those performed by Baena et al, (1990) and Castanier et al, (1992). They report increased fuel concentration and combustion efficiency for iron and tin additives, but marginal effects for the zinc additive.

Aqueous solutions of iron salts are effective agents for increasing fuel deposition. In a reservoir application, a field may be treated with iron additive by injecting the aqueous solution into the reservoir prior to ignition. This technique may be particularly useful in situations where low fuel concentration makes sustained combustion difficult.

References

- [1] Alexander, J. D., Martin, W. L., and Dew, J. N.: "Factors Affecting Fuel Availability and Composition During In Situ Combustion," *J. Pet. Tech.* (October 1962) 1154-1162.
- [2] Andrade, G. M.: "An Investigation of Pressure Effects on Combustion Tube Runs," Master's thesis, Stanford University, Stanford, California (1984).
- [3] Baena, C. J., Brigham, W. E., and Castanier, L. M.: "Effect of Metallic Additives on In-Situ Combustion of Huntington Beach Crude Experiments," Stanford University Petroleum Research Institute, SUPRI-TR-78, report submitted to the U.S. Dept. of Energy under contract no. DE-FG19-87BC14126, Stanford University, Stanford, California (August 1990).
- [4] Benham, A. L. and Poettmann, F. H.: "The Thermal Recovery Process-An Analysis of Laboratory Combustion Data," *Petroleum Transactions, AIME* (September 1958) **213**, 406-408.
- [5] Burger, J. G. and Sahuquet, B. C.: "Chemical Aspects of In-Situ Combustion - Heat of Combustion Kinetics," *Soc. Pet. Eng. J.* (October 1972) 410-420.
- [6] Castanier, L. M., Baena, C. J., Tavares, C., Holt, R. J., and Brigham, W. E.: "In Situ Combustion with Metallic Additives," No. SPE 23708, paper presented at the SPE-AIME Latin American Petroleum Engineering Conference, Caracas (March 1992).
- [7] Chu, C.: "State-of-the-Art Review of Fireflood Field Projects," *J. Pet. Tech.* (January 1982) 19-36.
- [8] De los Rios, C. F., Brigham, W. E., and Castanier, L. M.: "The Effect of Metallic Additives on the Kinetics of Oil Oxidation Reactions in In-Situ Combustion," Stanford University Petroleum Research Institute, SUPRI-TR-63, report submitted to the U.S. Dept. of Energy under contract no. DE-FG19-87BC14126, Stanford University, Stanford, California (November 1988).
- [9] Dew, J. N. and Martin, W. L.: "Air Requirements for Forward Combustion-Part I," *Petroleum Engineer* (December 1964) 82-86.
- [10] Dew, J. N. and Martin, W. L.: "Air Requirements for Forward Combustion-Part II," *Petroleum Engineer* (January 1965) 82-85.
- [11] Dyck, V. A., Lawson, J. D., and Smith, J. A.: *FORTRAN 77 - An Introduction to Structured Problem Solving*, Reston Publishing Company, Inc, a Prentice Hall Company, Reston, Virginia (1984) Appendix D.

- [12] Earlougher, R. C., Galloway, J. R., and Parsons, R. W.: "Performance of the Fry In-Situ Combustion Project," *J. Pet. Tech.* (May 1970) 551-557.
- [13] Fassihi, M. R., Brigham, W. E., and Ramey, Jr., H. J.: "The Reaction Kinetics of In Situ Combustion," No. SPE 9454, paper presented at the 55th Annual SPE-AIME Technical Conference and Exhibition, Dallas (September 1980).
- [14] Fassihi, M. R., Ramey, Jr., H. J., and Brigham, W. E.: "Laboratory Combustion Tube Studies - Final Report," Stanford University Petroleum Research Institute, SUPRI-TR-22, report submitted to the U.S. Dept. of Energy under contract no. DE-AC03-76ET12056, Stanford University, Stanford, California (September 1980).
- [15] Fassihi, M. R., Satman, A., Williams, R. L., Pettit, P., Grim, J., and Ramey, Jr., H. J.: "Laboratory Combustion Tube Studies - Part II," Stanford University Petroleum Research Institute, SUPRI-TR-10, report submitted to the U.S. Dept. of Energy under contract no. DE-AC03-76ET12056, Stanford University, Stanford, California (September 1978).
- [16] Gates, C. F. and Sklar, I.: "Combustion as a Primary Recovery Process- Midway Sunset Field," *J. Pet. Tech.* (August 1971) 981-986.
- [17] Hardy, W. C., Fletcher, P. B., Shepard, J. C., Dittman, E. W., and Zadow, D. W.: "In-Situ Combustion Performance in a Thin Reservoir Containing High-Gravity Oil," *J. Pet. Tech.* (February 1972) 199-208.
- [18] Martin, W. L., Alexander, J. D., and Dew, J. N.: "Process Variables of In Situ Combustion," *Petroleum Transactions AIME* (1958) **213**, 28-35.
- [19] Mickley, H. S., Sherwood, T. K., and Reed, C. E.: *Applied Mathematics in Chemical Engineering*, McGraw-Hill, New York, New York (1957) 95-100.
- [20] Nelson, T. W. and McNeil, J. S.: "How to Engineer an In Situ Combustion Project," *Oil and Gas Journal* (1961) **23**, 72-79.
- [21] Penberthy, W. L. and Ramey, Jr., H. J.: "Design and Operation of Laboratory Combustion Tubes," *Soc. Pet. Eng. J.* (June 1966) 183-198.
- [22] Racz, D.: "Development and Application of a Thermocatalytic In Situ Combustion Process in Hungary," paper presented at the 1985 European Meeting on Improved Oil Recovery, Rome, Italy (April 1985).
- [23] Satman, A., Fassihi, M. R., Williams, R. L., Pettit, P., Grim, J., and Ramey, Jr., H. J.: "Laboratory Combustion Tube Studies - Part I," Stanford University Petroleum Research Institute, SUPRI-TR-7, report submitted to the U.S. Dept. of Energy under contract no. DE-O4-3-1265, Stanford University, Stanford, California (June 1978).
- [24] Shallcross, D. C.: "Modifying In Situ Combustion Performance by the use of Water-Soluble Metallic Additives," No. SPE 19485, paper presented at the SPE-AIME Asia-Pacific Conference, Sydney, Australia (September 1989).

- [25] Showalter, W. E.: "Combustion-Drive Tests," *Soc. Pet. Eng. J.* (March 1963) 53-58.
- [26] Vossoughi, S., Willhite, G. P., Kritikos, W. P., Guvenir, I. M., and Shoubary, Y. E.: "Automation of an In-Situ Combustion Tube and Study of the Effect of Clay on the In-Situ Combustion Process," *Soc. Pet. Eng. J.* (August 1982) 493-502.

Appendix A. Data Analysis

To quantitatively analyze data obtained in the combustion tube runs, the model of Alexander, Martin and Dew (1964,1965) is used. This model assumes that the fuel deposited and thus available to high temperature oxidation is of the chemical form CH_n . The variable n is the ratio of hydrogen atoms to carbon atoms in the deposited fuel. It is called the hydrogen to carbon ratio, or H/C ratio, and is defined in equation A.1.

$$n = \frac{H}{C} \quad (A.1)$$

Stoichiometric analysis on the oxidation of this type of hydrocarbon molecule produces equation A.2.

In equation A.2, n is the H/C ratio and m is the ratio of CO_2 to CO in the produced gas. The value of m is defined by equation A.3.

$$m = \frac{\%CO_2}{\%CO} \quad (A.3)$$

The H/C ratio in equation A.2 can be calculated by using the stoichiometric equation, produced gas compositions, and an overall material balance on oxygen and nitrogen. From the stoichiometric equation (A.2), the H/C ratio can be related to the moles of oxygen converted to water and the moles of carbon oxide gasses formed. The relationship is shown in equation A.4.

$$n = 4 \frac{(\text{moles of oxygen converted to water})}{(\text{moles of carbon oxides produced})} \quad (A.4)$$

The moles of oxygen converted to water is determined by performing a material balance on oxygen and nitrogen. Assuming that the injected air consists of 79% nitrogen and 21% oxygen, equation A.5 holds. This equation is used to relate moles of oxygen in the injected air to moles of nitrogen.

$$n_{O_2} = \frac{0.21}{0.79} n_{N_2} \quad (A.5)$$

Assuming that all of the nitrogen which enters the tube also exits the tube, nitrogen composition can be used as a tracer. Exit composition of nitrogen can be put into equation A.5, to determine the moles of oxygen which were available to the combustion reactions. Composition of nitrogen in the produced gas was directly measured using a gas chromatograph (G.C.). Equipment and software complications, however, deemed the G.C. derived nitrogen measurements to be unreliable. An approximate method for nitrogen composition was used instead.

Assuming that the produced gas consists only of CO_2 , CO , O_2 and N_2 , equation A.6 can be used to estimate the amount of nitrogen in the produced gas.

$$N_2 = 100 - (CO_2 + CO + O_2) \quad (A.6)$$

The moles of oxygen injected into the combustion reaction is therefore obtained by combining equations A.5 and A.6. The result is equation A.7.

$$n_{O_2}^{inject} = \frac{0.21}{0.79} (100 - (CO_2 + CO + O_2)) \quad (A.7)$$

Moles of O_2 in the produced gas stream is given by equation A.8.

$$n_{O_2}^{produce} = (CO_2 + 0.5CO + O_2) \quad (A.8)$$

Moles of carbon oxide gasses in the produced gas stream is given by equation A.9.

$$CO_x^{produce} = (CO_2 + CO) \quad (A.9)$$

An expression for n in terms of the measured produced gas compositions is obtained by combining equations A.9, A.8, A.7, and A.4. This is shown in equations A.10 and A.11.

$$n = \frac{4 (n_{O_2}^{inject} - n_{O_2}^{produce})}{n_{CO_x}^{produce}} \quad (A.10)$$

$$n = \frac{106.3 - 2CO - 5.06 (CO_2 + CO + O_2)}{(CO_2 + CO)} \quad (A.11)$$

Equation A.11 is the apparent H/C ratio of the fuel oxidized in the combustion tube. It cannot be exactly true, however, because in its derivation it was assumed that all oxygen consumed has gone into the reaction shown in equation A.2, which is the high temperature combustion reaction. It is possible that some of the oxygen consumed has gone into low temperature reactions resulting in products such as oxygenated liquids or phenols. The apparent H/C ratio does, however, give an approximate measure of the chemical nature of the deposited fuel.

A measure of the efficiency of the combustion processes is given by calculating the ratio of injected oxygen which is consumed to the total oxygen which was injected. In equation A.12, Y is the oxygen utilization efficiency.

$$Y = 100 - 100 \left(\frac{0.79}{0.21} \right) \left(\frac{O_2}{N_2} \right) \quad (A.12)$$

Air required to burn one pound of fuel at 100% combustion efficiency is the air-fuel ratio, F_{aF} , and is given in the units of standard cubic feet of air per pound of fuel (scf./lb.fuel). The expression for F_{aF} can be derived by using the stoichiometric equation (A.2), and converting the moles of oxygen to the volume of air at standard conditions. The air-fuel ratio at 100% combustion efficiency is given by equation A.13.

$$F_{aF} = 902.38 \frac{\left(\frac{2m+1}{m+1} + \frac{n}{2} \right)}{(12 + n)} \quad (A.13)$$

The heat liberated by the combustion of one pound of fuel is calculated by adding the contributions of the heats of formation of CO_2 , CO , and H_2O . The heat of combustion, H_c , in units of Btu per pound of fuel (Btu./lb.fuel) is given by equation A.14.

$$H_c = \frac{174000m}{(m+1)(12+n)} + \frac{52500}{(m+1)(12+n)} + \frac{123000n}{2(12+n)} \quad (\text{A.14})$$

In equation A.14, the quantities 174,000, 52,500, and 123,000 are the heats of formation of CO_2 , CO , and H_2O in units (Btu/lb.mole).

To determine the amount of fuel deposited, a material balance on N_2 , and carbon oxides, CO_x , is performed for an incremental advancement of the combustion front. The combustion front moves from a position x_1 to x_2 during a time interval of t_1 to t_2 . During this interval, the cumulative carbon oxide production is calculated in units of (scf.). The cumulative CO_x production during an interval is simply the average CO_x composition for the interval multiplied by the average exit flow rate. Recognizing that the molecular weight of the fuel is $12+n$, the cumulative carbon oxide production can be related to pounds of fuel burned during the interval.

Assuming complete conservation of nitrogen, equation A.15 must hold.

$$q_{in} (N_2)_{in} = q_{out} (N_2)_{out} \quad (\text{A.15})$$

In equation A.15 q_{out} is the flow rate leaving the combustion tube, and q_{in} is the flow rate entering the tube, in units of standard liters per minute (slpm). Equation A.16 is the cumulative carbon oxide production during the time interval in units of (scf.).

$$(Q_{out})_{\text{CO}_x} = \frac{60}{(28.32)(100)} q_{out} (t_2 - t_1) (\text{CO}_2 + \text{CO}) \quad (\text{A.16})$$

In equation A.16 t_2 and t_1 are measured in hours, and the factor of 60 converts to minutes. The factor of 100 converts from percentages, and the factor of 28.32 converts liters to cubic feet.

One pound mole of gas occupies 379 cubic feet at standard conditions. Therefore, the standard cubic feet in equation A.16 can be converted to pound moles. Using the molecular weight of the fuel, pound moles can be converted to pounds of fuel. Equation A.17 expressed pounds of fuel burned, W , during the interval of x_1 to x_2 . W has units of pounds of fuel (lb.fuel).

$$W = \frac{(Q_{out})_{\text{CO}_x} (12+n)}{379} \quad (\text{A.17})$$

Fuel deposition, M_R , is measured in units of pounds of fuel per cubic foot of reservoir (lb.fuel/cu.ft.). It is obtained by considering an incremental volume of reservoir. Within the tube, the combustion front moved from x_1 to x_2 , while burning W pounds of fuel. Equation A.18 expresses M_R .

$$M_R = \frac{(28317) W}{A (x_2 - x_1) (1.0 - \phi)} \quad (\text{A.18})$$

In equation A.18 A is the cross sectional area of the combustion tube, in square centimeters. The factor 28,317 converts cubic centimeters to cubic feet. Front positions, x_1 and x_2 , are measured in centimeters.

The calculations described in this section are carried out in the FORTRAN computer program TUBE.F, see Appendix B.

Appendix B. FORTRAN Computer Program TUBE

This section contains the FORTRAN computer program TUBE which was used to process combustion tube data. The program reads in gas analyzer voltages, front position data, calibration data, fluid production data, and temperature profile data. The model of Dew and Martin (1964,1965) is then applied to calibrated data. The outputs are combustion parameters and plot files for the graphical presentation of data.

```

*****
*                               PROGRAM TUBE                               *
*****
*      Program by Richard J. Holt                                         *
*      This program analyzes combustion tube data                         *
*      Stanford University, Petroleum Engineering                         *
*      APRIL 1991                                                         *
*****
*
*****
*                               MAIN PROGRAM                               *
*****
*
*****
*                               DECLARATIONS                               *
*****
      PARAMETER (N1=1000)
      PARAMETER (N3=50)
      IMPLICIT REAL*8 (A-H,K-M,O-Z)
      IMPLICIT INTEGER (I,J,N)
C**
      REAL*8 O2(N1),CO2(N1),CO(N1),N2(N1),RN2(N1),RN2ave(N1)
      REAL*8 O2ave(N3),CO2ave(N3),COave(N3),N2ave(N3),FLOWoave(N3)
      REAL*8 TIME(N1),FLOWi(N1),TEMP1(N1),FLOWiave(N3)
      REAL*8 TIMEar(N3),Xar(N3),Tpeak(N3),VEL(N3)
      REAL*8 RM(N3),RN(N3),Yd(N3),FaF(N3)
      REAL*8 qout(N3),Qinc(N3),W(N3),Hc(N3)
      REAL*8 AR(N3),WR(N3),MR(N3),FLOWo(N1)
      REAL*8 a(6),b(6),c(6),N2aved
      REAL*8 XTMP(N3),TMP(N3),CUMWATER(N3),CUMOIL(N3),TIMEPRO(N3)
      CHARACTER*10 nameMIS,namePOS,nameGAS,nameTMP,namePRO
      CHARACTER*15 pro_in(10),tmp_in(10),mis_in(10),pos_in(10)
      CHARACTER*15 gas_in(10),pos_out(10),gas_out(10),tmp_out(10)
      CHARACTER*15 pro_out(10),vel_out(10),pek_out(10)
C**
*****
*                               DEFINE FILES TO BE USED                     *
*****
C**
      pro_in(1)='tub1_pro.dat'
      pro_in(2)='tub2_pro.dat'
      pro_in(3)='tub3_pro.dat'
      pro_in(4)='tub4_pro.dat'
      pro_in(5)='tub5_pro.dat'
      pro_in(6)='tub6_pro.dat'
      pro_in(7)='tub7_pro.dat'
C**
      tmp_in(1)='tub1_tmp.dat'
      tmp_in(2)='tub2_tmp.dat'
      tmp_in(3)='tub3_tmp.dat'
      tmp_in(4)='tub4_tmp.dat'
      tmp_in(5)='tub5_tmp.dat'
      tmp_in(6)='tub6_tmp.dat'
      tmp_in(7)='tub7_tmp.dat'
C**
      mis_in(1)='tub1_mis.dat'
      mis_in(2)='tub2_mis.dat'
      mis_in(3)='tub3_mis.dat'
      mis_in(4)='tub4_mis.dat'
      mis_in(5)='tub5_mis.dat'
      mis_in(6)='tub6_mis.dat'
      mis_in(7)='tub7_mis.dat'
C**
      pos_in(1)='tub1_pos.dat'
      pos_in(2)='tub2_pos.dat'
      pos_in(3)='tub3_pos.dat'

```

```

pos_in(4)='tub4_pos.dat'
pos_in(5)='tub5_pos.dat'
pos_in(6)='tub6_pos.dat'
pos_in(7)='tub7_pos.dat'

C**
gas_in(1)='tub1_gas.dat'
gas_in(2)='tub2_gas.dat'
gas_in(3)='tub3_gas.dat'
gas_in(4)='tub4_gas.dat'
gas_in(5)='tub5_gas.dat'
gas_in(6)='tub6_gas.dat'
gas_in(7)='tub7_gas.dat'

C**
pos_out(1)='tub1_pos.out'
pos_out(2)='tub2_pos.out'
pos_out(3)='tub3_pos.out'
pos_out(4)='tub4_pos.out'
pos_out(5)='tub5_pos.out'
pos_out(6)='tub6_pos.out'
pos_out(7)='tub7_pos.out'

C**
gas_out(1)='tub1_gas.out'
gas_out(2)='tub2_gas.out'
gas_out(3)='tub3_gas.out'
gas_out(4)='tub4_gas.out'
gas_out(5)='tub5_gas.out'
gas_out(6)='tub6_gas.out'
gas_out(7)='tub7_gas.out'

C**
tmp_out(1)='tub1_tmp.out'
tmp_out(2)='tub2_tmp.out'
tmp_out(3)='tub3_tmp.out'
tmp_out(4)='tub4_tmp.out'
tmp_out(5)='tub5_tmp.out'
tmp_out(6)='tub6_tmp.out'
tmp_out(7)='tub7_tmp.out'

C**
pro_out(1)='tub1_pro.out'
pro_out(2)='tub2_pro.out'
pro_out(3)='tub3_pro.out'
pro_out(4)='tub4_pro.out'
pro_out(5)='tub5_pro.out'
pro_out(6)='tub6_pro.out'
pro_out(7)='tub7_pro.out'

C**
vel_out(1)='tub1_vel.out'
vel_out(2)='tub2_vel.out'
vel_out(3)='tub3_vel.out'
vel_out(4)='tub4_vel.out'
vel_out(5)='tub5_vel.out'
vel_out(6)='tub6_vel.out'
vel_out(7)='tub7_vel.out'

C**
pek_out(1)='tub1_pek.out'
pek_out(2)='tub2_pek.out'
pek_out(3)='tub3_pek.out'
pek_out(4)='tub4_pek.out'
pek_out(5)='tub5_pek.out'
pek_out(6)='tub6_pek.out'
pek_out(7)='tub7_pek.out'

*****
*
*      OUTER LOOP CONTROL
*
*****
C      WRITE(*,3101)
C      READ(*,*) NFILE
C      WRITE(*,3102) NFILE

```

```

      DO 400 NFILE=1,7
*****
*           INPUT AND OUTPUT FILES           *
*****
C**
      OPEN (UNIT=2,file=pro_in(NFILE))
      OPEN (UNIT=3,file=tmp_in(NFILE))
      OPEN (UNIT=4,file=mis_in(NFILE))
      OPEN (UNIT=5,file=pos_in(NFILE))
      OPEN (UNIT=6,file=gas_in(NFILE))

C**
      OPEN (UNIT=7,file=pos_out(NFILE))
      OPEN (UNIT=8,file=gas_out(NFILE))
      OPEN (UNIT=9,file=tmp_out(NFILE))
      OPEN (UNIT=10,file=pro_out(NFILE))
      OPEN (UNIT=11,file=vel_out(NFILE))
      OPEN (UNIT=12,file=pek_out(NFILE))
      OPEN (UNIT=13,file='tub_mis.out')

C**
*****
*           PROCESS THE TEMPERATURE PROFILE DATA           *
*****
      READ(3,*) nameTMP
      ITMP=1
100    READ(3,*) XTMP(ITMP),TMP(ITMP)
      IF(XTMP(ITMP) .LT. 0) GOTO 102
      IF(XTMP(ITMP) .EQ. 0) THEN
C!! GPS
      WRITE(9,*) ITMP-1
C!! GPS
      DO 101 I=1,ITMP-1
      WRITE(9,9200) XTMP(I),TMP(I)
101    CONTINUE
C!! PC
C!!      WRITE(9,*)
C!! PC
      ITMP=1
      GOTO 100
      ELSE
      ITMP=ITMP+1
      GOTO 100
      ENDIF
*****
*           PROCESS THE PRODUCTION DATA           *
*****
102    READ(2,*) namePRO
      READ(2,*) SGoil,SGwater
      READ(2,*) NPRO
      DO 200 I=1,NPRO
      READ(2,*) TIMEPRO(I),TOTMASS,VOLOIL,VOLWATER
      IF (I .EQ. 1) GOTO 200
      CUMOIL(I)=CUMOIL(I-1)+VOLOIL*SGOIL
      CUMWATER(I)=CUMWATER(I-1)+VOLWATER*SGWATER
200    CONTINUE
C!! GPS
      WRITE(10,*) NPRO
C!! GPS
      DO 201 I=1,NPRO
      WRITE(10,9200) TIMEPRO(I),CUMOIL(I)/CUMOIL(NPRO)*100
201    CONTINUE
C!! PC
      WRITE(10,*)
C!! PC
C!! GPS
      WRITE(10,*) NPRO
C!! GPS

```

```

DO 202 I=1,NPRO
WRITE(10,9200) TIMEPRO(I),CUMWATER(I)/CUMWATER(NPRO)*100
202 CONTINUE
write(13,*) cumoil(npro),cumwater(npro),nfile
*****
* READ TUBE DATA and CALIBRATION DATA *
* This calibration allows for calibration drift *
* Allows for pre and post calibrations, and assumes linear drift*
* Uses Least Squares Method to fit both calibrations to a *
* third order polynomial *
*****
READ(4,*) nameMIS
READ(5,*) namePOS
READ(6,*) nameGAS
IF (nameMIS .EQ. namePOS .AND. nameMIS .EQ. nameGAS) THEN
ELSE
WRITE(7,999)
WRITE(8,999)
WRITE(9,999)
GOTO 666
ENDIF
READ(4,*) AREA,RCKDENS,phi
READ(4,*) TIMEi,TIMEf
DO 5 ii=1,6
READ(4,*) V1,V2,V3,V4,COMP1,COMP2,COMP3,COMP4
CALL CALIB(V1,V2,V3,V4,COMP1,COMP2,COMP3,COMP4,a1,b1,c1)
a(ii)=a1
b(ii)=b1
c(ii)=c1
5 CONTINUE
*****
* READ IN ARRIVAL DATA TO BE USED *
*****
READ(5,*) Nar
DO 15 i=1,Nar
15 READ(5,*) TIMEar(i),Xar(i),Tpeak(i)
DO 11 i=1,Nar-1
VEL(i)=(Xar(i+1)-Xar(i))/(TIMEar(i+1)-TIMEar(i))*60
11 CONTINUE
*****
* PROCESS POSITION DATA AND PEAK TEMPERATURE DATA *
*****
C!! GPS
WRITE(11,*) Nar
WRITE(12,*) Nar
C!! GPS
DO 300 I=1,Nar
WRITE(11,9200) TIMEar(i),Xar(i)
WRITE(12,9200) Xar(i),Tpeak(i)
300 CONTINUE
*****
* READ EFFLUENT DATA (voltage) AND APPLY CALIBRATION EQUATIONS*
* Compositon %, Time min., Flow SLPM, P psig, T Cels *
*****
DTif=(TIMEf-TIMEi)
READ(6,*) Ncomp
DO 20 i=1,Ncomp
C**
IF (NFILE .LE. 3) THEN
READ(6,*) TIME(i),CO2V,COV,O2V,FLOWo(i),FLOWi(i)
c ,PP,TEMP1(i),RN2(i)
ENDIF
C**
IF (NFILE .GE. 4) THEN
READ(6,*) TIME(i),CO2V,COV,O2V,FLOWi(i),FLOWo(i)
c ,PP,TEMP1(i),RN2(i)

```

```

ENDIF
C**
CO2V=CO2V/20
COV=COV/10
O2V=O2V/25
C
CO2i= a(1) + b(1)*CO2V + c(1)*CO2V**2
COi= a(3) + b(3)*COV + c(3)*COV**2
O2i= a(5) + b(5)*O2V + c(5)*O2V**2
C
CO2f= a(2) + b(2)*CO2V + c(2)*CO2V**2
COf= a(4) + b(4)*COV + c(4)*COV**2
O2f= a(6) + b(6)*O2V + c(6)*O2V**2
C
CO2(i)=(CO2f-CO2i)*(TIME(i)-TIMEi)/DTif+CO2i
CO(i)=(COf-COi)*(TIME(i)-TIMEi)/DTif+COi
O2(i)=(O2f-O2i)*(TIME(i)-TIMEi)/DTif+O2i
IF (CO2(i) .LT. 0.0) CO2(i)=0.0
IF (CO(i) .LT. 0.0) CO(i)=0.0
IF ( O2(i) .LT. 0.0) O2(i)=0.0
C
N2(i)=100-O2(i)-CO2(i)-CO(i)
20
CONTINUE
C!! GPS
WRITE(8,*) Ncomp/1
C!! GPS
DO 21 i=1,Ncomp,1
WRITE(8,9200) TIME(i),CO2(i)
21
CONTINUE
C!! GPS
WRITE(8,*) Ncomp/1
C!! GPS
C!! PC
C!!
WRITE(8,*)
C!! PC
DO 22 i=1,Ncomp,1
WRITE(8,9200) TIME(i),CO(i)
22
CONTINUE
C!! GPS
WRITE(8,*) Ncomp/1
C!! GPS
C!! PC
C!!
WRITE(8,*)
C!! PC
DO 23 i=1,Ncomp,1
WRITE(8,9200) TIME(i),O2(i)
23
CONTINUE
*****
*          CALCULATE GAS AVERAGES FOR EACH ARRIVAL INTERVAL          *
*****
sumCO=0
sumCO2=0
sumO2=0
sumN2=0
sumFLOWo=0
sumFLOWi=0
sumRN2=0
j=1
k=0.000
DO 30 i=1,Ncomp
IF (TIME(i) .GE. TIMEar(j+1)) THEN
COave(j)=sumCO/k
CO2ave(j)=sumCO2/k
O2ave(j)=sumO2/k
N2ave(j)=sumN2/k
RN2ave(j)=sumRN2/k

```

```

        FLOWoave(j)=sumFLOWo/k
        FLOWiave(j)=sumFLOWi/k
        j=j+1
        k=0.000
        sumCO=0
        sumCO2=0
        sumO2=0
        sumN2=0
        sumFLOWo=0
        sumFLOWi=0
        sumRN2=0
    ENDIF
    IF (TIME(i) .GT. TIMEar(Nar)) GOTO 31
    IF (TIME(i) .GE. TIMEar(j)) THEN
        sumCO=sumCO+CO(i)
        sumCO2=sumCO2+CO2(i)
        sumO2=sumO2+O2(i)
        sumN2=sumN2+N2(i)
        sumFLOWo=sumFLOWo+FLOWo(i)
        sumFLOWi=sumFLOWi+FLOWi(i)
        sumRN2=sumRN2+RN2(i)
        k=k+1.0
    ENDIF
30    CONTINUE
*****
*    CALCULATE M,N,Yd,FaF,and Hc FOR EACH INTERVAL          *
*    ALSO FIND AVERAGES FOR ENTIRE RUN                      *
*****
31    DO 40 i=1,Nar-1
C**
        CO(i)=COave(i)
        CO2(i)=CO2ave(i)
        O2(i)=O2ave(i)
        N2(i)=N2ave(i)
        RN2(i)=RN2ave(i)
C**
        RM(i)=CO2(i)/CO(i)
        Mt=106.33+2*CO(i)-5.063*(CO2(i)+CO(i)+O2(i))
        Mb=CO2(i)+CO(i)
        RN(i)=Mt/Mb
        Yd(i)=1-3.76*(O2(i)/N2(i))
        F1=902.38/(12+RN(i))
        F2=(2*RM(i)+1)/(RM(i)+1) + RN(i)/2
        FaF(i)=F1*F2
        H1=174000*RM(i)/(RM(i)+1)
        H2=52500/(RM(i)+1)
        H3=123000*RN(i)/2
        Hc(i)=(H1+H2+H3)/(12+RN(i))
40    CONTINUE
C**
        sumRM=0
        sumRN=0
        sumYd=0
        sumFaF=0
        sumHc=0
        sumCO=0
        sumCO2=0
        sumO2=0
        sumN2=0
        sumRN2=0
        sumVEL=0
        sumPeak=0
        sumFLOWi=0
        sumFLOWo=0
C**
        DO 50 i=1,Nar-1

```


[illegible]

```

      WRITE(7,*) NAMEPOS  

      WRITE(7,1000)  

      DO 80 i=1,Nar  

        WRITE(7,1002) TIMEAr(i),Xar(i),Tpeak(i)  

60     CONTINUE  

        WRITE(7,4001)  

        WRITE(7,1001)  

C**  

        DO 90 i=1,Nar-1  

          WRITE(7,4001)  

          WRITE(7,2015) TIMEAr(i),Xar(i)  

          WRITE(7,4001)  

          WRITE(7,4000)  

          WRITE(7,2001) CO2ave(i),COave(i),O2ave(i)  

          WRITE(7,2014) RN2ave(i),N2ave(i)  

          WRITE(7,2002) RN(i),RM(i)  

          WRITE(7,2003) Yd(i)  

          WRITE(7,2004) FaF(i)  

          WRITE(7,2005) Hc(i)  

          WRITE(7,2006) W(i)  

          WRITE(7,2007) MR(i)  

          WRITE(7,2008) AR(i)  

          WRITE(7,2009) WR(i)  

          WRITE(7,2010) VEL(i)  

          WRITE(7,2011) Tpeak(i)  

          WRITE(7,2012) FLOWiave(i),FLOWoave(i)  

          WRITE(7,2013) qout(i)  

          WRITE(7,4000)  

90    CONTINUE  

C**  

        WRITE(7,4001)  

        WRITE(7,3000)  

        WRITE(7,2001) CO2aved,COaved,O2aved  

        WRITE(7,2014) RN2aved,N2aved  

        WRITE(7,2002) RNaVe,RMaVe  

        WRITE(7,2003) Ydave  

        WRITE(7,2004) FaFaVe  

        WRITE(7,2005) Hcave  

        WRITE(7,2006) Wave  

        WRITE(7,2007) MRave  

        WRITE(7,2008) ARave  

        WRITE(7,2009) WRave  

        WRITE(7,2010) VELave  

        WRITE(7,2011) Tpeakave  

        WRITE(7,2012) FLOWiaved,FLOWoaved  

        WRITE(7,2013) qoutaved  

*****  

*                END OF OUTER LOOP                *  

*****  

400   CONTINUE  

C*****  

C>>>>>>>>>>>>>>>>>>>>>>>>> FORMATS <<<<<<<<<<<<<<<<<<<<<<<<  

C*****  

999   FORMAT ('***** ERROR *****')  

1000  FORMAT ('THE FRONT ARRIVAL DATA SET.....')  

1001  FORMAT ('***** COMBUSTION PARAMETERS FOR EACH INTERVAL *****')  

1002  FORMAT ('TIME(min.)=',F7.2,3X,'X(cm)=',F7.2,3X,'Tpeak(C)=',F7.2)  

2001  FORMAT ('CO2%=',F5.2,1x,'CO%=',F5.2,1x,'O2%=',F5.2)  

2002  FORMAT ('N=',F7.2,3X,'M=',F7.2)  

2003  FORMAT ('Yd=',F7.3)  

2004  FORMAT ('FaF(scflbfuel)=',F7.2)  

2005  FORMAT ('Hc(btu/lbfuel)=',F9.2)  

2006  FORMAT ('W=',F9.4)  

2007  FORMAT ('MR(lbs/ft^3)=',F7.2)  

2008  FORMAT ('AR(scflft^3)=',F7.2)  

2009  FORMAT ('WR(lbfue/100lbrock)=',F7.2)

```


**DATE
FILMED**
9/01/92