325
8-14-61

UCRL 6467

MASTER

UNIVERSITY OF
CALIFORNIA

Ernest O. Lawrence

*Radiation
Laboratory*

OSCILLATING VERTICAL MAGNETIC DIPOLE
ABOVE A CONDUCTING HALF-SPACE

LIVERMORE SITE

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

UCRL-6467
Physics, UC-34,
TID-4500 (16th Ed.)

UNIVERSITY OF CALIFORNIA
Lawrence Radiation Laboratory
Livermore, California

Contract No. W-7405-eng-48

OSCILLATING VERTICAL MAGNETIC DIPOLE ABOVE A
CONDUCTING HALF-SPACE

James Paul Wesley

April 2, 1961

Printed in USA. Price 50 cents. Available from the
Office of Technical Services
U. S. Department of Commerce
Washington 25, D.C.

OSCILLATING VERTICAL MAGNETIC DIPOLE ABOVE A
CONDUCTING HALF-SPACE*

James Paul Wesley

Lawrence Radiation Laboratory, University of California
Livermore, California

April 2, 1961

ABSTRACT

The electromagnetic field produced by a vertical oscillating magnetic dipole above a plane conducting earth is obtained in integral form. An exact solution in closed form is obtained for the dipole and the point of observation located on the surface of the earth.

* Work performed under the auspices of the U. S. Atomic Energy Commission.

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

OSCILLATING VERTICAL MAGNETIC DIPOLE ABOVE A CONDUCTING HALF-SPACE

James Paul Wesley

Lawrence Radiation Laboratory, University of California
Livermore, California

INTRODUCTION

The present work investigates the electromagnetic field produced by a vertical magnetic dipole above a plane conducting earth. For the case of especial interest, the dipole and the point of observation located on the interface between air and earth, the field components may be obtained in exact closed form for all ranges of the parameters.

The magnitudes of the parameters of interest here are specified as follows:

Frequency: $\approx 10^4$ cycles/second.
Distance from dipole: < 4775 meters (wavelength in air).
Conductivity of earth: 10^{-2} mho/meter for damp earth to
 10^{-5} mho/meter for dry earth.

CHOICE OF COORDINATES

An oscillating vertical magnetic dipole of time variation $\exp(-i\omega t)$ is located, at a distance h , above a half-infinite conducting earth as shown in Fig. 1. Cylindrical coordinates are chosen with z directed upwards through the dipole, and the radius ρ taken horizontally and in the plane of the surface of the earth. The air is characterized by the parameters ϵ_0, μ_0 , and $\sigma_1 = 0$, while the earth is characterized by ϵ_0, μ_0 , and $\sigma_2 = \sigma \neq 0$, where rationalized mks units are assumed.

DERIVATION OF THE DIFFERENTIAL EQUATION

Introducing the wave number, k ,

$$k^2 = \omega^2 \mu \epsilon + i \omega \mu \sigma, \quad (1)$$

and the intrinsic admittance, η ,

$$k \eta = \omega \epsilon + i \sigma, \quad (2)$$

Fig. 1. Choice of coordinates for the magnetic dipole placed a distance h above a plane conducting earth.

one may write Maxwell's equations in rationalized mks units as follows:

$$\begin{aligned} \nabla \times \underline{\underline{E}} &= ik \underline{\underline{H}}, & \nabla \cdot \underline{\underline{H}} &= 0, \\ \nabla \times \underline{\underline{H}} &= -ik\eta \underline{\underline{E}} + \underline{\underline{J}}^0, & \nabla \cdot \underline{\underline{E}} &= \nabla \cdot \underline{\underline{J}}^0 / ik\eta. \end{aligned} \quad (3)$$

When combined with the Hertzian vector potential

$$\underline{\underline{E}} = \nabla \nabla \cdot \underline{\underline{\pi}} + k^2 \underline{\underline{\pi}}, \quad \underline{\underline{H}} = -ik\eta \nabla \times \underline{\underline{\pi}}, \quad (4)$$

Maxwell's equations (3) yield the differential equation

$$\nabla \times \nabla \times \underline{\underline{\pi}} - \nabla \nabla \cdot \underline{\underline{\pi}} - k^2 \underline{\underline{\pi}} = -\underline{\underline{J}}^0 / ik\eta. \quad (5)$$

The source current for a magnetic dipole may be specified as the current in a circular loop where the radius goes to zero as the current goes to infinity in such a way that the current times the area of the loop remains finite and nonzero. Thus,

$$\underline{\underline{J}}^0 = \lim_{\pi a^2 I \rightarrow m} \underline{\underline{e}}_\phi I \delta(\rho - a) \delta(z - h), \quad (6)$$

where $\delta(\rho - a)$ and $\delta(z - h)$ are the Dirac delta functions, I is the current, m is the magnetic dipole moment, and $\underline{e}_\phi$ is a unit vector in the ϕ direction.

Since there is symmetry about the z axis, we may attempt a solution using only the ϕ component of the Hertz vector. Noting that nothing will be a function of the azimuthal angle ϕ , we have Eq. (5) yielding

$$\left[\frac{1}{\rho} \frac{\partial}{\partial \rho} \left(\rho \frac{\partial}{\partial \rho} \right) - \frac{1}{\rho^2} + \frac{\partial^2}{\partial z^2} + k^2 \right] \pi_\phi = J^0 / ik \eta. \quad (7)$$

This differential Eq. (7) may be simplified by letting

$$\pi_\phi = \partial \Psi / \partial \rho. \quad (8)$$

Substituting Eqs. (8) and (6) into Eq. (7) then yields the desired differential equation

$$(\nabla^2 + k^2) \Psi = - \lim_{\pi a^2 I \rightarrow m} \frac{I}{ik \eta} \mathcal{A}(a - \rho) \delta(z - h), \quad (9)$$

where $\mathcal{A}(z - \rho)$ is the unit step function, zero for $\rho \geq a$.

SOLUTION TO THE INHOMOGENEOUS EQUATION

To solve Eq. (9) for the inhomogeneous part we may apply Green's theorem to Ψ and Φ in an infinite space where Φ is defined by

$$(\nabla^2 + k^2) \Phi = - \delta(\underline{r} - \underline{r}'), \quad (10)$$

where

$$\Phi = e^{ik|\underline{r} - \underline{r}'|} / 4\pi |\underline{r} - \underline{r}'|. \quad (11)$$

We thus obtain

$$\int_V \left[\Phi(\nabla^2 + k^2) \Psi - \Psi(\nabla^2 + k^2) \Phi \right] dV = \int_S \left(\Phi \frac{\partial \Psi}{\partial n} - \Psi \frac{\partial \Phi}{\partial n} \right) dS = 0, \quad (12)$$

where Φ and $\partial \Phi / \partial n$ vanish on the sphere at infinity.

Substituting Eqs. (9), (10), and (11) into Eq. (12) then yields

$$\Psi(\underline{r}') = \lim_{\pi a^2 I \rightarrow m} \frac{I}{4\pi ik \eta} \int_V \mathcal{A}(a - \rho) \delta(z - h) \frac{e^{ik|\underline{r} - \underline{r}'|}}{|\underline{r} - \underline{r}'|} dV. \quad (13)$$

Performing the z integration, we have

$$\Psi(\underline{r}') = \lim_{\pi a^2 I \rightarrow m} \frac{I}{4\pi i k \eta} \int_0^{2\pi} \int_0^a \rho \frac{e^{ikR'}}{R'} d\rho d\phi, \quad (14)$$

where

$$R'^2 = \rho'^2 + \rho^2 - 2\rho\rho' \cos(\phi' - \phi) + (z' - h)^2. \quad (15)$$

In the limit as $a \rightarrow 0$ (such that as $I \rightarrow \infty$, $\pi a^2 I \rightarrow m$) we have by the mean value theorem for integrals

$$\Psi(\underline{r}') = \lim_{\pi a^2 I \rightarrow m} \frac{I}{4\pi i k \eta} (a - 0) \frac{a}{2} \int_0^{2\pi} d\phi \frac{e^{ikR''}}{R''}, \quad (16)$$

where

$$R''^2 = \rho'^2 + (a/2)^2 - a\rho' \cos(\phi' - \phi) + (z' - h)^2. \quad (17)$$

In the limit as $a \rightarrow 0$ we can perform the ϕ integration to obtain

$$\Psi(\underline{r}) = \frac{m}{4\pi i k \eta} \frac{e^{ikR_1}}{R_1}, \quad (18)$$

where

$$R_1^2 = \rho^2 + (z - h)^2. \quad (19)$$

From Eqs. (18) and (8) the Hertz vector then becomes

$$\pi_\phi^0 = \frac{m}{4\pi i k \eta} \frac{\partial}{\partial \rho} \frac{e^{ikR_1}}{R_1}, \quad (20)$$

where the superscript zero indicates that this is the solution to the inhomogeneous part of Eq. (7).

SOLUTION OF THE HOMOGENEOUS EQUATION

Using the Sommerfeld¹ representation we get the solution to the homogeneous part of Eq. (7), Eq. (8), by differentiating Eq. (9):

¹ A. Sommerfeld, Ann. Physik 28, 665-737 (1909).

$$\pi_{\phi}^1 = -\frac{m}{4\pi i k_1 \eta_1} \int_0^{\infty} f(\lambda) e^{-\gamma_1 z} J_1(\lambda \rho) \lambda^2 d\lambda, \quad (21)$$

where

$$\gamma = (\lambda^2 - k^2), \quad (22)$$

such that

$$\lim_{\lambda \rightarrow 0} \gamma \rightarrow -ik. \quad (23)$$

INTEGRAL FORM OF THE SOLUTION

Using Sommerfeld's¹ integral representation

$$\frac{e^{ik_1 R_1}}{R_1} = \int_0^{\infty} \frac{1}{\gamma_1} e^{-\gamma_1 |z-h|} J_0(\lambda \rho) \lambda d\lambda, \quad (24)$$

where

$$\gamma_1 = (\lambda^2 - k_1^2)^{1/2}, \quad (25)$$

and introducing an image function which is a solution to the homogeneous Eq. (9), we have

$$-\frac{e^{ik_1 R_2}}{R_2} = -\int_0^{\infty} \frac{1}{\gamma_1} e^{-\gamma_1 (z+h)} J_0(\lambda \rho) \lambda d\lambda, \quad \text{for } z \geq 0, \quad (26)$$

where

$$R_2^2 = \rho^2 + (z+h)^2; \quad (27)$$

the Hertz vector in air, according to Eqs. (20) and (21), may be written in the form

$$\pi_{\phi 1} = -\frac{m}{4\pi i k_1 \eta_1} \int_0^{\infty} \left\{ \frac{1}{\gamma_1} e^{-\gamma_1 |z-h|} - \frac{1}{\gamma_1} e^{-\gamma_1 (z+h)} + f_1(\lambda) e^{-\gamma_1 (z+h)} \right\} J_1(\lambda \rho) \lambda^2 d\lambda, \quad (28)$$

for $z \geq 0$. In the conducting earth Eq. (21) yields

$$\pi_{\phi 2} = -\frac{m}{4\pi i k_2 \eta_2} \int_0^{\infty} f_2(\lambda) e^{-\gamma_1 h + \gamma_2 z} J_1(\lambda \rho) \lambda^2 d\lambda, \quad (29)$$

for $z \leq 0$ and where

$$\gamma_2 = (\lambda^2 - k_2^2)^{1/2}. \quad (30)$$

APPLICATION OF THE BOUNDARY CONDITIONS

From Eq. (4) and the assumption that only a ϕ component of the Hertz vector is needed, the field components are given by

$$\begin{aligned} H_z &= -ik\eta \frac{1}{\rho} \frac{\partial}{\partial \rho} (\rho \pi_\phi), \\ H_\rho &= -ik\eta \frac{\partial}{\partial z} \pi_\phi, \\ E_\phi &= k^2 \pi_\phi. \end{aligned} \quad (31)$$

For the continuity of the magnetic field across the boundary between earth and air and the continuity of the horizontal component of the electric field across the boundary, Eq. (30) yields the boundary conditions

$$\begin{aligned} k_1^2 \pi_{\phi 1} &= k_2^2 \pi_{\phi 2}, \\ k_1^2 \frac{\partial \pi_{\phi 1}}{\partial z} &= k_2^2 \frac{\partial \pi_{\phi 2}}{\partial z}. \end{aligned} \quad (32)$$

Substituting Eqs. (28) and (29) into Eqs. (32) then yields the requirements on $f_1(\lambda)$ and $f_2(\lambda)$,

$$\begin{aligned} f_1(\lambda) &= f_2(\lambda), \\ -2 + \gamma_1 f_1(\lambda) &= -\gamma_2 f_2(\lambda). \end{aligned} \quad (33)$$

Solving Eqs. (33) yields

$$f_1(\lambda) = f_2(\lambda) = \frac{2}{\gamma_1 + \gamma_2}. \quad (34)$$

Substituting Eqs. (34) into Eqs. (28) and (29) then yields the result

$$\begin{aligned} \pi_{\phi 1} &= \frac{m}{4\pi ik_1 \eta_1} \frac{\partial}{\partial \rho} \left(\frac{e^{ik_1 R_1}}{R_1} - \frac{e^{ik_1 R_2}}{R_2} + \mathcal{U}_1 \right), \\ \pi_{\phi 2} &= \frac{m}{4\pi ik_2 \eta_2} \frac{\partial}{\partial \rho} \mathcal{U}_2, \end{aligned} \quad (35)$$

where

$$\begin{aligned} \mathcal{U}_1 &= \int_0^\infty \frac{2}{\gamma_1 + \gamma_2} e^{-\gamma_1(z+h)} J_0(\lambda\rho) \lambda \, d\lambda, \quad z \geq 0, \\ \mathcal{U}_2 &= \int_0^\infty \frac{2}{\gamma_1 + \gamma_2} e^{-\gamma_1 h + \gamma_2 z} J_0(\lambda\rho) \lambda \, d\lambda, \quad z \leq 0. \end{aligned} \quad (36)$$

EVALUATION OF THE INTEGRALS

The problem has now been reduced to evaluating the integrals $\mathcal{U}_1$ and $\mathcal{U}_2$ in Eqs. (36), the Hertz vector and the field components being given by differentiation according to Eqs. (35) and (31). Both of the integrals $\mathcal{U}_1$ and $\mathcal{U}_2$ may be obtained from a single more general integral. First, we note that

$$\frac{2}{\gamma_1 + \gamma_2} \equiv - \frac{2}{k_1^2 - k_2^2} (\gamma_1 - \gamma_2), \quad (37)$$

using Eqs. (25) and (30). We thus define the general integral, J ,

$$J \equiv 2 \int_0^\infty e^{-\gamma_1 a - \gamma_2 b} J_0(\lambda\rho) \lambda \, d\lambda, \quad (38)$$

and obtain

$$\begin{aligned} \mathcal{U}_1 &= \frac{1}{k_1^2 - k_2^2} \left[J_a - J_b \right]_{a=z+h}^{b=0}, \\ \mathcal{U}_2 &= \frac{1}{k_1^2 - k_2^2} \left[J_a - J_b \right]_{a=h}^{b=-z}, \end{aligned} \quad (39)$$

where the subscripts on the J 's denote differentiation. The problem has now been reduced to evaluating the general integral J , Eq. (38).

The evaluation of the integral J , Eq. (38), for various ranges of the pertinent parameters has been treated at some length in a previous work by Baños and Wesley.² Here we will limit our consideration to the case of

² A. Baños and J. P. Wesley, "The Horizontal Electric Dipole in a Conducting Half-Space, Part II," Scripps Institute of Oceanography, La Jolla, California, Monograph SIO 54-31, 62 (1954).

both the source and the observer on the surface of the earth, $h = 0$, $z = 0$.

SPECIAL CASE $z = 0$, $h = 0$

The integrals may be evaluated in closed form for this special case where h and z are both zero, no approximations being necessary. The derivative of J , Eq. (38), with respect to a may be evaluated by first letting $b \rightarrow 0$; thus,

$$\lim_{a \rightarrow 0} J_a = \lim_{a \rightarrow 0} 2 \frac{\partial}{\partial a} \int_0^{\infty} e^{-\gamma_1 a} J_0(\lambda \rho) \lambda d\lambda. \quad (40)$$

Using the integral representation, Eq. (24), we then obtain for the right-hand side of Eq. (40),

$$-\lim_{a \rightarrow 0} 2 \frac{\partial^2}{\partial a^2} \frac{e^{ik_1 R}}{R}, \quad (41)$$

where

$$R^2 = \rho^2 + a^2. \quad (42)$$

Performing the indicated differentiations in (41) and going to the limit as $a \rightarrow 0$ then yields the result

$$\lim_{\substack{a \rightarrow 0 \\ b \rightarrow 0}} J_a = -\frac{2}{\rho} \frac{\partial}{\partial \rho} \frac{e^{ik_1 \rho}}{\rho}. \quad (43)$$

Using the same analysis for the derivative of J with respect to b , we get from Eqs. (39) the exact result for $h = 0$, $z = 0$,

$$\mathcal{U} = -\frac{2}{k_1^2 - k_2^2} \frac{1}{\rho} \frac{\partial}{\partial \rho} \left(\frac{e^{ik_1 \rho}}{\rho} - \frac{e^{ik_2 \rho}}{\rho} \right), \quad (44)$$

a result first obtained by van der Pol.³ The subscript 1 or 2 on $\mathcal{U}$ has been

³ B. van der Pol, Z. Hochfrequenz-Technologie 37, 152-157 (1931).

dropped in Eq. (44), since on the surface there is no need to differentiate between medium 1 and medium 2, the value $\mathcal{U}$ being the same for both media.

FIELD COMPONENTS FOR $h = 0, z = 0$

To obtain the ρ component of the magnetic field, as given by the second of Eqs. (31), it is necessary to differentiate Eqs. (39) again with respect to a or b before letting a or $b \rightarrow 0$. Since even derivatives of J will vanish as a or $b \rightarrow 0$, the ρ component of the magnetic field is identically zero, a result which could have been anticipated from the symmetry.

From Eqs. (35) and (44) the Hertz vector becomes

$$\begin{aligned}\pi_{\phi 1} &= -\frac{m}{4\pi i k_1 \eta_1} \frac{2}{k_1^2 - k_2^2} \frac{\partial}{\partial \rho} \left[\frac{1}{\rho} \frac{\partial}{\partial \rho} \left(\frac{e^{i k_1 \rho}}{\rho} - \frac{e^{i k_2 \rho}}{\rho} \right) \right], \\ \pi_{\phi 2} &= -\frac{m}{4\pi i k_2 \eta_2} \frac{2}{k_1^2 - k_2^2} \frac{\partial}{\partial \rho} \left[\frac{1}{\rho} \frac{\partial}{\partial \rho} \left(\frac{e^{i k_1 \rho}}{\rho} - \frac{e^{i k_2 \rho}}{\rho} \right) \right].\end{aligned}\quad (45)$$

Performing the differentiations indicated in the first of Eqs. (45) yields

$$\begin{aligned}\pi_{\phi 1} &= -\frac{m}{4\pi i k_1 \eta_1} \frac{2}{k_1^2 - k_2^2} \left\{ \left(-\frac{k_1^2}{\rho^2} - \frac{3i k_1}{\rho^3} + \frac{3}{\rho^4} \right) e^{i k_1 \rho} \right. \\ &\quad \left. - \left(-\frac{k_2^2}{\rho^2} - \frac{3i k_1}{\rho^3} + \frac{3}{\rho^4} \right) e^{i k_2 \rho} \right\},\end{aligned}\quad (46)$$

where a similar expression holds for $\pi_{\phi 2}$. It may be noted that as $k_1 \rightarrow k_2$, Eq. (46) reduces to the free-space expression, Eq. (20),

$$\pi_{\phi 1} = \frac{m}{4\pi i k \eta} \left(\frac{i k}{\rho} - \frac{1}{\rho^2} \right) e^{i k \rho}, \quad (47)$$

as it should.

Substituting Eq. (46) into the first and third of Eqs. (31) (the second being identically zero for $h = 0, z = 0$), and performing the indicated differentiations, we obtain the exact expressions for the field components for $h = 0, z = 0$,

$$\begin{aligned}
H_z = \frac{m}{4\pi} \frac{2}{k_1^2 - k_2^2} & \left\{ \left(-\frac{ik_1^3}{\rho^2} + \frac{4k_1^2}{\rho^3} + \frac{9ik_1}{\rho^4} - \frac{9}{\rho^5} \right) e^{ik_1\rho} \right. \\
& \left. - \left(-\frac{ik_2^3}{\rho^2} + \frac{4k_2^2}{\rho^3} + \frac{9ik_2}{\rho^4} - \frac{9}{\rho^5} \right) e^{ik_2\rho} \right\}; \\
E_\phi = \frac{m}{4\pi} \frac{2i\omega\mu}{k_1^2 - k_2^2} & \left\{ \left(-\frac{k_1^2}{\rho^2} - \frac{3ik_1}{\rho^3} + \frac{3}{\rho^4} \right) e^{ik_1\rho} - \left(-\frac{k_2^2}{\rho^2} - \frac{3ik_2}{\rho^3} + \frac{3}{\rho^4} \right) e^{ik_2\rho} \right\}
\end{aligned} \tag{48}$$

where it isn't necessary to distinguish between mediums 1 and 2 on the interface because of the continuity of H_z and E_ϕ .

FIELD COMPONENTS FOR $k_1\rho \ll 1$

For points of observation much less than a wavelength in air, the field components for the source and the point of observation on the surface of the earth, as given by Eqs. (48), become

$$\begin{aligned}
H_z & \approx \frac{m}{4\pi} \frac{2}{k_2^2} \left\{ \frac{9}{\rho^5} + \left(-\frac{ik_2^3}{\rho^2} + \frac{4k_2^2}{\rho^3} + \frac{9ik_2}{\rho^4} - \frac{9}{\rho^5} \right) e^{ik_2\rho} \right\}, \\
E_\phi & \approx \frac{m}{4\pi} \frac{2i\omega\mu}{k_2^2} \left\{ -\frac{3}{\rho^4} + \left(\frac{k_2^2}{\rho^2} - \frac{3ik_2}{\rho^3} + \frac{3}{\rho^4} \right) e^{ik_2\rho} \right\}.
\end{aligned} \tag{49}$$

FIELD COMPONENTS FOR $k_1\rho < |k_2\rho| \ll 1$

For points of observation less than a wavelength in air and also less than a wavelength in the conducting medium, we obtain the quasi-static limit,

$$\begin{aligned}
H_z & \approx -\frac{m}{4\pi} \frac{1}{\rho^3}, \\
E_\phi & \approx \frac{m}{4\pi} \frac{i\omega\mu}{\rho^2},
\end{aligned} \tag{50}$$

for source and point of observation on the surface of the earth.

NUMERICAL WORK

For numerical work it is of interest to investigate the ranges of the parameters in some detail. From Eq. (1) the wave number, k , may be written as

$$k = \frac{1}{\delta} \left\{ \left(\sqrt{1 + \beta^2} + \beta \right)^{1/2} + i \left(\sqrt{1 + \beta^2} - \beta \right)^{1/2} \right\}, \quad (51)$$

where δ is the skin depth,

$$\delta = (2/\omega \mu_0 \sigma)^{1/2}, \quad (52)$$

and

$$\beta = \omega \epsilon_0 / \sigma. \quad (53)$$

For the conducting earth we are interested in the case where $\sigma > 10^{-5}$ mho/meter and $\omega = 2\pi \times 10^4$ cycles per second. Since $\epsilon_0 = 8.854 \times 10^{-12}$ farad/meter, we may neglect $\beta^2 < 0.003$ as compared with unity. Thus, for the present case of interest, Eqs. (1) and (51) yield

$$\begin{aligned} k_1 &= \omega \sqrt{\mu_0 \epsilon_0} = \omega/c = 1/\lambda_1, \\ k_2 &= (1 + i)/\delta = (1 + i)/\sqrt{2} \lambda_2. \end{aligned} \quad (54)$$

It is convenient to introduce the numerical distance x ,

$$x \equiv \rho/\delta, \quad (55)$$

and the ratio

$$n \equiv \delta \omega/c = \sqrt{2} \lambda_2/\lambda_1, \quad (56)$$

where

$$0.01 < n < 0.3, \quad (57)$$

for $\omega = 2\pi \times 10^4$ cycles per second and $10^{-5} < \sigma < 10^{-2}$ mho/meter.

It is now possible to separate the exact result, Eqs. (48), into real and imaginary parts using Eqs. (54), (55), and (56). Thus we obtain

$$\begin{aligned}
h_{zr} &\equiv \operatorname{Re} \left\{ \frac{2\pi}{m} \delta^3 (n^4 + 4) H_z \right\} \\
&= x^{-5} \left[A_1 F(nx) + B_1 G(nx) + e^{-x} C_1 F(x) + e^{-x} D_1 G(x) \right], \\
h_{zi} &\equiv \operatorname{Im} \left\{ \frac{2\pi}{m} \delta^3 (n^4 + 4) H_z \right\} \\
&= x^{-5} \left[A_1 G(nx) - B_1 F(nx) + e^{-x} C_1 G(x) - e^{-x} D_1 F(x) \right], \\
e_{\phi r} &\equiv \operatorname{Re} \left\{ \frac{2\pi}{m} \frac{\delta^2}{\omega \mu} (n^4 + 4) E_\phi \right\} \\
&= x^{-4} \left[-A_2 G(nx) + B_2 F(nx) + e^{-x} C_2 G(x) - e^{-x} D_2 F(x) \right], \\
e_{\phi i} &\equiv \operatorname{Im} \left\{ \frac{2\pi}{m} \frac{\delta^2}{\omega \mu} (n^4 + 4) E_\phi \right\} \\
&= x^{-4} \left[A_2 F(nx) + B_2 G(nx) - e^{-x} C_2 F(x) - e^{-x} D_2 G(x) \right],
\end{aligned} \tag{58}$$

where

$$\begin{aligned}
F(x) &= n^2 \cos x - 2 \sin x, & G(x) &= n^2 \sin x + 2 \cos x, \\
A_1 &= 4n^2 x^2 - 9, & B_1 &= n^3 x^3 - 9nx, \\
C_1 &= -2x^3 + 9x + 9, & D_1 &= 2x^3 + 8x^2 + 9x, \\
A_2 &= -n^2 x^2 + 3, & B_2 &= 3nx, \\
C_2 &= 3x + 3, & D_2 &= 2x^2 + 3x.
\end{aligned} \tag{59}$$

For the case of points of observation much less than a wavelength in air, $k_1 \rho \ll 1$, Eqs. (49) yield the simpler expressions:

$$\begin{aligned}
 h_{zr} &\equiv \operatorname{Re} \left\{ \frac{4\pi}{m} \delta^3 H_z \right\} \approx x^{-5} e^{-x} (A \cos x + B \sin x), \\
 h_{zi} &\equiv \operatorname{Im} \left\{ \frac{4\pi}{m} \delta^3 H_z \right\} \approx -x^{-5} \left[9 + e^{-x} (B \cos x - A \sin x) \right], \\
 e_{\phi r} &\equiv \operatorname{Re} \left\{ \frac{4\pi}{m} \frac{\delta^2}{\omega \mu} E \right\} \approx 3x^{-4} \left[-1 + e^{-x} (C \cos x + D \sin x) \right], \\
 e_{\phi i} &\equiv \operatorname{Im} \left\{ \frac{4\pi}{m} \frac{\delta^2}{\omega \mu} E \right\} \approx 3x^{-4} e^{-x} (-D \cos x + C \sin x),
 \end{aligned} \tag{60}$$

where

$$\begin{aligned}
 A &= 2x^3 + 8x^2 + 9x, & B &= 2x^3 - 9x - 9, \\
 C &= x + 1, & D &= \frac{2}{3}x^2 + x.
 \end{aligned} \tag{61}$$

CONCLUSIONS

A vertical oscillating magnetic dipole on the surface of an infinite plane conducting earth yields an electromagnetic field at the surface of the earth given exactly by Eqs. (48) for all ranges of the parameters. For points of observation less than a wavelength in the conducting earth away from the source, $k_1 \rho < |k_2 \rho| \ll 1$, Eqs. (50) show that the magnetic field varies as ρ^{-3} and the electric field varies as ρ^{-2} . For distances from the source greater than a wavelength in the conducting earth but less than a wavelength in air, $k_1 \rho \ll 1 < |k_2 \rho|$, Eqs. (49) show that the magnetic field varies as ρ^{-m} where $2 < m < 3$, and the electric field also varies as ρ^{-n} where $2 < n < 3$. For distances greater than a wavelength in air, both the electric and magnetic field components, Eqs. (48), vary as ρ^{-2} .

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

- A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or
- B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.