Pacific Northwest Laboratory Annual Report for 1983 to the DOE Office of Energy Research

Part 4 Physical Sciences February 1984

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PACIFIC NORTHWEST LABORATORY
operated by
BATTELLE
for the
UNITED STATES DEPARTMENT OF ENERGY
under Contract DE-AC06-76RLO 1830

Printed in the United States of America
Available from
National Technical Information Service
United States Department of Commerce
5285 Port Royal Road
Springfield, Virginia 22161

NTIS Price Codes
Microfiche A01

Printed Copy

Pages	Price Codes
001-025	A02
026-050	A03
051-075	A04
076-100	A05
101-125	A06
126-150	A07
151-175	A08
176-200	A09
201-225	A010
226-250	A011
251-275	A012
276-300	A013

**Pacific Northwest Laboratory
Annual Report for 1983 to the
DOE Office of Energy Research**

Part 4 Physical Sciences

J. M. Nielson and Staff Members
of Pacific Northwest Laboratory

February 1984

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Richland, Washington 99352

PREFACE

This 1983 annual report from Pacific Northwest Laboratory (PNL) to the Department of Energy (DOE) describes research in environment, health, and safety conducted during fiscal year 1983. The report again consists of five parts, each in a separate volume.

The five parts of the report are oriented to particular segments of our program. Parts 1 to 4 report on research performed for the DOE Office of Health and Environmental Research in the Office of Energy Research. Part 5 reports progress on all research performed for the Assistant Secretary for Environmental Protection, Safety and Emergency Preparedness. In some instances, the volumes report on research funded by other DOE components or by other governmental entities under interagency agreements. Each part consists of project reports authored by scientists from several PNL research departments, reflecting the multidisciplinary nature of the research effort.

The parts of the 1983 Annual Report are:

Part 1: Biomedical Sciences

Program Manager - J. F. Park

D. L. Felton, Report Coordinator and Editor

Part 2: Ecological Sciences

Program Manager - B. E. Vaughan

B. E. Vaughan, Report Coordinator
C. M. Novich, Editor

Part 3: Atmospheric Sciences

Program Manager - C. E. Elderkin

N. S. Laulainen, Report Coordinator
J. L. Downs-Berg, Editor

Part 4: Physical Sciences

Program Manager - J. M. Nielsen

R. M. Garcia, Report Coordinator
J. E. Danko, Editor

Part 5: Overview and Assessment

Program Managers - S. Marks
W. A. Glass

R. W. Baalman, Report Coordinator
and Editor

Activities of the scientists whose work is described in this annual report are broader in scope than the articles indicate. PNL staff have responded to numerous requests from DOE during the year for planning, for service on various task groups, and for special assistance.

Credit for this annual report goes to many scientists who performed the research and wrote the individual project reports, to the program managers who directed the

research and coordinated the technical progress reports, to the editors who edited the individual project reports and assembled the five parts, and to Ray Baalman editor in chief, who directed the total effort.

W. J. Bair, Manager
S. Marks, Associate Manager
Environment, Health and Safety Research
Program

Previous reports in this series:

Annual Report for

1951	W-25021, HW-25709
1952	HW-27814, HW-28636
1953	HW-30437, HW-30464
1954	HW-30306, HW-33128, HW-35905, HW-35917
1955	HW-39558, HW-41315, HW-41500
1956	HW-47500
1957	HW-53500
1958	HW-59500
1959	HW-63824, HW-65500
1960	HW-69500, HW-70050
1961	HW-72500, HW-73337
1962	HW-76000, HW-77609
1963	HW-80500, HW-81746
1964	BNWL-122
1965	BNWL-280; BNWL-235, Vol. 1-4; BNWL-361
1966	BNWL-480, Vol. 1; BNWL-481, Vol. 2, Pt. 1-4
1967	BNWL-714, Vol. 1; BNWL-715, Vol. 2, Pt. 1-4
1968	BNWL-1050, Vol. 1, Pt. 1-2; BNWL-1051, Vol. 2, Pt. 1-3
1969	BNWL-1306, Vol. 1, Pt. 1-2; BNWL-1307, Vol. 2, Pt. 1-3
1970	BNWL-1550, Vol. 1, Pt. 1-2; BNWL-1551, Vol. 2, Pt. 1-2
1971	BNWL-1650, Vol. 1, Pt. 1-2; BNWL-1651, Vol. 2, Pt. 1-2
1972	BNWL-1750, Vol. 1, Pt. 1-2; BNWL-1751, Vol. 2, Pt. 1-2
1973	BNWL-1850, Pt. 1-4
1974	BNWL-1950, Pt. 1-4
1975	BNWL-2000, Pt. 1-4
1976	BNWL-2100, Pt. 1-5
1977	PNL-2500, Pt. 1-5
1978	PNL-2850, Pt. 1-5
1979	PNL-3300, Pt. 1-5
1980	PNL-3700, Pt. 1-5
1981	PNL-4100, Pt. 1-5
1982	PNL-4600, Pt. 1-5

FOREWORD

Part 4 of the Pacific Northwest Laboratory Annual Report for 1983 to the Office of Energy Research, includes those programs funded under the title "Physical and Technological Research." The Field Task Program Studies reports in this document are grouped under the subheadings and each section is introduced by a divider page that indicates the Field Task Agreement reported in that section. These reports only briefly indicate progress made during 1983. The reader should contact the principal investigators named or examine the publications cited for more details.

CONTENTS

PREFACE	iii
FOREWORD	v
ANALYTICAL STUDIES	
Chemical Basis for the Biological Response to Conversion Materials	1
Chemical Characterization of Coal Conversion Materials, <i>B. W. Wilson and W. C. Weimer</i>	1
Oil Shale and Tar Sands Research	5
Development of a Microwave-Induced Helium Plasma Detector for Gas Chromatography and Supercritical Fluid Chromatography, <i>K. B. Olsen, D. S. Sklarew, J. C. Evans, H. R. Udseth and R. D. Smith</i>	5
Use of a Gas Chromatograph-Microwave Induced Plasma Detector for Speciation of Organometallics in Fossil Fuel Process Streams, <i>D. S. Sklarew, K. B. Olsen and S. P. Downey</i>	7
Effect(s) of Water Treatment on the Organic Content of Oil Shale Retort Waters, <i>A. P. Toste, C. J. English, B. W. Mercer and R. B. Myers</i> ,	9
Inorganic and Organic Anions in Retort Waters, <i>D. S. Sklarew and M. McCulloch</i>	10
MEASUREMENT AND DOSIMETRY	
Characterization of Synfuels and Combustion Products	15
Supercritical Fluid Chromatography/Mass Spectrometry, <i>R. D. Smith,</i> <i>B. W. Wright and H. R. Udseth</i>	15
Lasers in Analytical Chemistry	17
Kinetic Phosphorimetry: Development of New Instrumentation for Low-Level Uranium Analyses, <i>B. A. Bushaw</i>	17
Continuous Wave Double-Resonance Ionization, <i>B. A. Bushaw and T. J. Whitaker</i>	17
PHYSICAL PROCESSES	
PHYSICAL PROCESSES IN RADIATION BIOLOGY	21
Radiation Physics	23
Initial Interaction Processes	23
Doubly Differential Ionization Cross Sections, <i>L. H. Toburen, R. D. DuBois,</i> <i>W. E. Wilson, and F. M. Cummings</i>	23
Total Ion and Electron Yields, <i>R. D. DuBois and M. E. Rudd</i>	24
Partial Ionization Cross Sections for H^+ and He^+ Impact, <i>R. D. DuBois</i>	24
Interpretation of Multiple Ionization Processes for Proton Impact, <i>R. D. DuBois,</i> <i>L. H. Toburen and S. T. Manson</i>	25
Construction of a New Doubly Differential Cross Section Apparatus, <i>R. D. DuBois</i>	27
Electron Capture Leading to L-Shell Vacancy Production in H^+ -Mg Collisions, <i>R. D. DuBois, C. L. Cocke and J. Giese</i>	27
Theoretical Single Differential Cross Sections for Helium, Neon and Argon, <i>J. H. Miller, L. H. Toburen, W. E. Wilson and S. T. Manson</i>	27

Track Structure	29
Measurement of Energy Deposition Near Heavy Ion Tracks, <i>N. F. Metting, L. A. Braby, H. H. Rossi, P. J. Kliauga, J. Howard and M. Rapkin</i>	29
Analytical Model for Primary Ionization by Positive Ions, <i>W. E. Wilson and J. H. Miller</i>	31
Mean Delta-Ray Energies in Ion Molecule Collisions, <i>W. E. Wilson</i>	34
Energy Imparted to DNA-Like Structures by High Linear Energy Transfer Radiations, <i>W. E. Wilson</i>	36
Calculating Transient Yields of Water Radicals Produced in Pulse Radiolysis with Ion Beams, <i>J. H. Miller, W. E. Wilson, D. J. Brenner and M. Zaider</i>	36
Radiation Dosimetry	39
Dosimetry	39
Moments and Their Use in Microdosimetry and Dosimetry, <i>W. C. Roesch</i>	39
Re-Evaluation of the Hiroshima-Nagasaki Radiation Doses, <i>W. C. Roesch</i>	40
Beta-Particle Dosimetry, <i>W. C. Roesch</i>	40
Conceptual Basis of Calculating of Dose Distributions, <i>W. C. Roesch</i>	41
Modeling and Cellular Studies	43
The Linear Energy Transfer Dependence of One-Event and Two-Event Damage in <i>Chlamydomonas reinhardtii</i> , <i>L. A. Braby and B. S. Jacobson</i>	43
Effects of Linear Energy Transfer on Cellular Repair Rates, <i>L. A. Braby and B. S. Jacobson</i>	45
Radiation Biophysics	49
Characterization of Chinese Hamster Ovary (CHO) Cells in Plateau-Phase Cultures, <i>J. M. Nelson and N. F. Metting</i>	49
Kinetics of Sublethal and Potentially Lethal Damage Removal by Simultaneous Repair Processes in Plateau-Phase Mammalian Cells, <i>J. M. Nelson, N. F. Metting, W. C. Roesch and L. A. Braby</i>	50
Dose Rate Evidence of Damage Accumulation in Stationary-Phase Mammalian Cells, <i>N. F. Metting, W. C. Roesch, L. A. Braby and J. M. Nelson</i>	52
Modeling Cellular Response to Genetic Damage	57
Control of DNA Synthesis by Deoxynucleoside Triphosphates (dNTPs) in Permeable Chinese Hamster Ovary Cells, <i>C. N. Newman and J. H. Miller</i>	57
Carcinogen-Induced Deoxynucleoside Triphosphate Pool Imbalances: Effect on DNA Synthesis in Growing Chinese Hamster Ovary Cells, <i>C. N. Newman and J. H. Miller</i>	58
Mechanisms of UV-Induced dNTP Pool Imbalance and Its Relationship to Inhibition of DNA Synthesis, <i>J. H. Miller and C. N. Newman</i>	61
The Effect of Biphasic Repair Kinetics on the Survival of Human Cells Exposed to Radiation and Chemical Carcinogens, <i>J. H. Miller and R. H. Heflich</i>	62

Internal Microdosimetry	65
Lung Microdosimetry Calculations, <i>W. C. Roesch</i>	65
Dose Distribution Effects at the Cellular Level, <i>D. R. Fisher and M. E. Frazier</i>	65
Lung Dose Calculations for Beagle Dogs Exposed to $^{239}\text{PuO}_2$, <i>D. R. Fisher,</i> <i>W. C. Cannon, R. T. Hadley and J. F. Park</i>	67
PUBLICATIONS	71
PRESENTATIONS	75
AUTHOR INDEX	81
ORGANIZATION CHARTS	85
DISTRIBUTION	87

Analytical Studies

• Chemical Basis for the Biological Response to Coal Conversion Materials

The major focus of analytical chemistry components in the coal program has been to identify biologically active constituents in materials related to coal conversion. Such studies at Pacific Northwest Laboratory have resulted in the evaluation of process modifications aimed at reducing the biological activity of certain process materials. The more basic aspects of this research are funded by the Office of Health and Environmental Research; aspects relating to specific processes (e.g., integrated two-stage liquefaction) or modifications of these processes (e.g., heavy distillate recycle of SRC-II materials) are funded by the Office of Fossil Energy.

CHEMICAL CHARACTERIZATION OF COAL CONVERSION MATERIALS

B. W. Wilson and W. C. Weimer

Supporting Staff: R. B. Lucke, C. W. Wright, D. W. Later, E. K. Chess, and D. R. Kalkwarf

• Chemical Stability of Coal Liquefaction Materials

Both long-term and short-term stability studies of the chemical composition and biological activity of Solvent Refined Coal (SRC) I and II liquids have been performed. Major sample constituency was monitored as a function of storage time, temperature, dilution, cover atmosphere, and ambient lighting conditions. Biological activity was measured with the Ames assay *Salmonella typhimurium* TA98 with S-9 metabolic activation. Chemical composition was monitored using high resolution gas chromatography (GC) and gas chromatography/mass spectrometry (GC/MS). The data were analyzed by computer-based analysis of variance techniques (ANOVA). The parameters of the experiments performed at 4°C, 20°C, 60°C, and 100°C, along with the results obtained, follow.

Seventeen total samples of SRC-I light oils, wash solvents, and process solvents, and SRC-II naphthas, middle distillates, heavy distillates, and fuel oil blends (FOB) were monitored during storage in the repository. Conditions of repository storage were 4°C, in the dark, under a nitrogen atmosphere, in inert (glass) containers. After storage for four years under these conditions, it was found there was no significant change in the chemical composition or biological activity of the SRC materials.

The SRC-II FOB were chosen as a sample to undergo storage at harsher conditions than those of the repository, since many of the components found in this sample are representative of the components found in the other SRC materials. Any changes that occurred in the FOB under harsher conditions

will serve as benchmarks for changes that may occur over longer periods of time in the repository. Samples of FOB were stored in duplicate under storage parameters of cover atmosphere (air versus nitrogen), ambient lighting (light versus darkness), and dilution (undiluted versus methylene chloride) at -20°C and at room temperature (20°C) for one year. No significant change in the major chemical constituency was found for any of the samples stored under these conditions, except the ones stored diluted in methylene chloride, under an atmosphere, in the light. For this sample, the creosols and more highly alkylated phenols, indan and alkylated indans, indanol, and tetralin peaks showed a significant decrease in concentration. The only significant changes in biological activity, as measured by the Ames test, occurred in the samples stored either diluted or undiluted at room temperature, in the light, under an air atmosphere. When diluted, the activity was completely eliminated; while undiluted, it decreased by about a factor of 2 after storage for one year.

Eighteen FOB samples were stored at 60°C and three at 100°C, in the dark, under an air atmosphere. The samples were monitored seven times over a 32-week period under these severe conditions. Monitoring of the major chemical constituency showed that the creosols, alkylated indans, and indanol decreased in concentrations most significantly. In addition, when the nitrogen-containing polycyclic aromatic fraction was studied more closely after storage at 100°C for 16 weeks, the indole and primary aromatic amines were found to have degraded. Biological activity was completely eliminated after storage at these increased temperatures.

Overall, when degradation occurred, biological activity decreased and concentrations of hydroxylated polynuclear aromatic hydrocarbon (PAH), partially hydrogenated PAH, indoles, and amino PAH decreased. Thus far, degradation of materials stored in the repository has not been noted.

- Physical/Chemical Degradation of Coal Liquids

Studies were continued to evaluate the effects of environmental factors on the chemical stability and mutagenicity of coal liquids. In one of these studies, environmental conditions were arranged to simulate the exposure of coal liquids to air and sunlight during an outdoor spill. Thin layers of an SRC-II fuel oil blend and an SRC-I process solvent were exposed to air in darkness or in light simulating the emission spectrum and maximum intensity of bright sunshine. During exposure, each sample was held at 23°C in a closed container to inhibit volatilization. After exposure, the samples were separated into fractions according to chemical class and these fractions were tested for mutagenicity by the histidine reversion mutagenicity assay using *S. typhimurium* TA98. In all samples, the amino polycyclic aromatic hydrocarbon (APAH) fraction was the most mutagenic, and its mutagenicity decreased with exposure of the total sample to air, either in darkness or simulated sunlight. A 36-h exposure of the fuel oil blend to air in the dark reduced the mutagenicity of its APAH-rich fraction by 65%, whereas an equally long exposure in the light reduced the mutagenicity by 92%. Similar rates of reduction in mutagenicity were achieved in exposures of the process solvent. Analysis of the APAH-rich fractions by gas chromatography and gas chromatography/mass spectrometry showed that most of the amine constituents contained less than 4 rings, and their concentrations decreased with exposure to air and sunlight. The mutagenicities of other sample fractions remained low and generally decreased during exposure. The results of this study suggest that the mutagenic activity of coal liquids spilled outdoors will be reduced gradually by exposure to air and sunlight. The speed of this process will depend on the ability of air and light to reach all of the spilled material.

In another investigation of environmental degradation of coal liquids, a series of 92 individual samples (70 samples from external surfaces, 22 samples from internal surfaces) was collected from the former SRC-I and SRC-II pilot plant at Ft. Lewis, Washington, which has now been dismantled. The samples were selected to represent materials to which workers in a coal liquefaction facility would be exposed, both during normal operating conditions and during welding or other repair operations on process-line pipes. Thus, the materials include coatings from equipment, railings, stairways, walls, floors, support structures, concrete pads beneath the process equipment, and scrapings from within valves

and pipes. These samples were very diverse in physical appearance, heterogeneous in composition (many contained varying quantities of insoluble mineral matter), and were soluble (in three solvent systems) to different degrees. The polynuclear aromatic hydrocarbon (PAH) concentration in the soluble portions of the samples composed a significant fraction of the total soluble constituents. The mean concentrations and the concentration range for PAH compounds having two to six aromatic rings are as follows: two-ring PAHs, 630 ppm (0-8,700 ppm); three-ring PAHs, 74,400 ppm (1,300-434,000); four-ring PAHs, 100,000 ppm (820-217,000 ppm); five- and six-ring PAHs, 19,500 ppm (740-232,000 ppm). Preliminary data from initiation/promotion skin tumorigenicity studies show biological activity that approaches that of certain heavy-end coal liquids. These data suggest that extensive environmental weathering and exposure to sunlight and moisture have little effect on the potential carcinogenic agents in these coal liquids.

- Integrated Two-Stage Liquefaction

Separation of the initial solvation or liquefaction from the hydrogenation or upgrading steps in direct coal liquefaction affords the opportunity to better optimize each as a unit operation. The Integrated Two-Stage Liquefaction (ITSL) process currently being developed by C. E. Lummus, with support from the U.S. Department of Energy, integrates these separate functions to allow more efficient use of available hydrogen and thermal energy. ITSL relies on a low-severity short contact time (SCT) initial liquefaction step, followed by antisolvent deashing and catalytic hydrogenation by a proprietary process called LC fining. Resids and underflow from the hydrogenation and deashing operations, respectively, make up the recycle solvent used to slurry fresh coal in the process.

Results from Process Development Unit (PDU) operations to date indicate that the SCT product can be effectively deashed by an antisolvent system; the SCT product can be upgraded by LC fining under fairly mild conditions without undue deactivation of the catalyst. The SCT approach results in minimal gas with most of the product oil produced in the 650° to 850°F boiling range.

Sets of samples were collected under normal operating conditions from runs 3LCF7 and 3LF9 during processing of Indiana No. 5 and Illinois No. 6 coal, respectively. Set 2 was taken during alternate operation wherein feed was recycled back to the short contact time reactor, for an average of one cycle, prior to entering the LC finer for hydrotreatment

to produce LC finer total liquid product. This mode of operation effectively increased the liquefaction reactor residence time for the process stream eventually entering the LC finer. This configuration does not constitute a regular operational mode for the ITSL process and was set up as a one-time study only. Sample set 3 was collected subsequent to a significant exothermic excursion in the first two of three series-coupled LC fining reactors, during which their catalyst beds were exposed to temperatures as high as 900°F and 1000°F, respectively. It should be noted, however, that similar conditions may arise from catalyst deactivation resulting from extended run periods, etc.

Chemical analysis of these materials showed that SCT products were composed of fewer compounds than analogous materials from Solvent Refined Coal (SRC) processes. Major components in the SCT materials were three-, four-, five- and six-ring neutral polycyclic aromatic hydrocarbons (PAH). Methyl(C₁) and C₂ homologs of these compounds were present in relatively low concentrations, compared to their nonalkylated homologs. Organic nitrogen was primarily in the form of tertiary polycyclic aromatic nitrogen heterocycles (which will be designated here as 3°-PANH), and carbazoles (2°-PANH). Little or no amino PAH (APAH) was detected in samples taken during normal PDU operations; however, mutagenic APAHs were produced during off-normal operation as described below.

Compared to SRC materials, the ITSL process streams contained fewer different organic compounds that could be detected by gas chromatography, a fact which is due in part to the higher initial boiling point of the ITSL liquids tested (650°F which is nominally 100°F higher than that of SRC-II). Comparison of LC finer product to SCT product material showed that substantial partial hydrogenation had occurred in the fining operation, with concurrent reduction in the heteroatom content and aromaticity of the LC finer product.

Catalyst condition in the LC finer reactors appeared to have substantial effect on chemical functional groups in the process streams as well as on their mutagenic activity: catalyst in good condition appeared to produce materials that were more highly hydrogenated and had substantially less mutagenicity than materials produced after the LC fining catalyst had undergone a slightly damaging exothermic temperature excursion. Total liquid product (TLP) from the LC finer produced during single recycle of the LC finer feed through the SCT reactor also showed increased mutagenic activity compared

to products resulting from normal-mode operation. Mutagenic activity of both SCT and LC fining product materials, produced under normal operating conditions with good catalyst, was substantially lower than for SRC-II heavy distillate, for example.

The ITSL process can generate a TLP that is low in mutagenic activity compared to the total liquids produced in the reactor of SRC-I and SRC-II processes. However, boiling ranges and composition of these materials are not directly comparable and none are analogous to products that would be produced by a commercial facility. Thus, caution should be exercised when comparing mutagenicity of products produced by different processes.

Organic nitrogen was found in the ITSL process in higher boiling distillate cuts than in SRC processes. The difference is probably due to reduced C-N bond (thermolytic) scission in the ITSL SCT reactor. Microbial mutagenicity was attributed mainly to the presence of APAH. Formation of APAH was evident after an accidental exothermic temperature excursion of the catalyst bed, with much lower concentrations found in samples from normal LC finer operations. The slightly deactivated catalyst apparently fails to promote deamination of nitrogen-containing hydroaromatics. APAHs were the most important microbial mutagens in these coal liquids, as shown by reduction of mutagenicity after nitrosation. However, measurements of APAH concentrations in the mutagenically active fractions of the total liquid product (TLP) from the LC finer showed that the gas chromatographable APAH content alone was insufficient to account for all activity, suggesting possible synergism among TLP components.

Carcinogenic activity of ITSL materials, as assessed by tumors per animal in the initiation/promotion mouse skin painting assay, was slightly reduced for materials produced with good catalyst under normal operation compared to those collected during recycle of the LC finer feed. Initiation activity of the latter samples, however, was not significantly different from that of SRC-II coal-derived heavy distillate that has a lower initial boiling point. The observed initiation activity was not unexpected, considering analytical data that showed the presence of four-, five- and six-ring PAH in ITSL materials. However, if compared to materials derived from SRC-II on an equivalent boiling range basis, the ITSL 650° to 850°F materials would probably be lower in initiating activity, since about 40 wt% of the SRC-II heavy distillate boils between 550° and 650°F. For comparison, this would

be equivalent to diluting the ITSL materials with 40 wt% 650°F SRC-II distillate, which has very low initiating activity.

- Heavy Distillate Recycle of SRC-II Materials

Recent work from the Merriam Laboratory continuous coal liquefaction unit shows that heavy distillate from the SRC-II process can be recycled to extinction; hence, a distillate product boiling entirely below 310°C (590°F) (or other selected boiling point) is feasible. In these runs, distillate yield was not reduced, gas make was unaffected, and hydrogen consumption increased only slightly, in keeping with the generally higher hydrogen content of lighter end products. Total distillate yield (C₅-590°F) was 56 wt%, MAF coal in runs with subbituminous coal from the Amax Belle Ayr mine. Product endpoint is well below 371°C (700°F), the temperature above

which coal distillates appear to become genotoxic. The product was shown to be free of mutagenic activity in the Ames test.

Chemical analyses showed both the <270°C (<518°F) and the <310°C (<590°C) distillates to be essentially devoid of several reference polycyclic compounds known to be carcinogenically active in laboratory animals. Tests for tumorigenic or carcinogenic activity were not carried out on these materials. However, comparing chemical data from the Merriam heavy distillate samples with data from the other SRC-II distillates (where carcinogenesis or tumorigenesis data are available) leads to the expectation that <371°C (<700°C) materials from the Merriam Laboratory will have greatly reduced tumorigenic and carcinogenic activity in skin painting tests. Other studies suggest the product should be more readily upgraded than full-range (C₅-900°F) distillate.

• Oil Shale and Tar Sands Research

Oil shale and tar sand in the United States represent a potential supply of at least 600 billion barrels of crude oil. Past and potential future commercial interest in developing these reserves has resulted in studies that should help provide assurance to developers that conversion processes are environmentally feasible. A vital part of these environmental studies is the physical and chemical characterization of the effluents that may be generated from the various proposed conversion schemes. Due to the complex nature of the effluents, their characterization has required the development of new procedures for sampling and analysis and for chemical separation. Characterization studies are important and should begin early in the development of a given technology, preferably at the pilot-plant or semiworks stage. This section presents results of the application of these techniques to the characterization of oil shale effluents.

DEVELOPMENT OF A MICROWAVE-INDUCED HELIUM PLASMA DETECTOR FOR GAS CHROMATOGRAPHY AND SUPERCRITICAL FLUID CHROMATOGRAPHY

K. B. Olsen, D. S. Sklarew, J. C. Evans, H. R. Udseth, and R. O. Smith

The microwave-induced helium plasma has excellent potential as a detector for gas chromatography (GC) and supercritical fluid chromatography (SFC). Its major strength lies in its ability to simultaneously monitor a wide range of elements in the components of a mixture separated by GC or SFC. Two chromatographic-microwave induced plasma detector (MIP) systems have been assembled, namely a low-pressure (Figure 1) and an atmospheric-pressure (Figure 2) microwave-induced helium plasma detector system. The main components are the separation system, the interface, the microwave cavity and generator, the spectrometer, and the data acquisition system. The low-pressure system consists of a Hewlett Packard Model 5880 gas chromatograph interfaced to an Applied Chromatography Systems MPD 850; the microwave cavity is a 1/4-wave Enenson type. The atmospheric-pressure system consists of a Hewlett Packard 5840 GC interfaced to a Spectrospan III B Echelle spectrometer; the microwave cavity is a Beenakker type.

Several considerations are important in the interface between the GC and the plasma detector: 1) to prevent degradation of the separation achieved by capillary column chromatography, the dead volume must be minimized; 2) to prevent condensation of the sample, cold spots must be eliminated and the interface must be able to be heated to the same temperature as the GC oven; 3) to prevent quenching of the plasma, the solvent peak must be vented; 4) to maintain the plasma, a helium flow of ~50-100 ml/min must be introduced; and 5) to prevent deposition

of the sample on the walls of the plasma tube, a scavenge flow of 1-2 ml/min must be maintained.

In both the low-pressure and the atmospheric-pressure MIP, the fused silica column is threaded through 1/16-in. capillary nickel or stainless steel tubing and introduced directly to a low dead volume switching valve for venting the solvent. In the low-pressure MIP, one port of the switching valve is connected directly to the quartz plasma tube. In the atmospheric-pressure MIP, a second piece of fused silica is threaded through nickel tubing to connect the valve to the plasma tube. The tube was modified so that the nickel tubing could be sealed inside with Sauereisen cement and the fused silica column delivers samples directly into the plasma. In both the low-pressure and the atmospheric-pressure MIP systems, the nickel tubing is insulated, wrapped with nichrome wire, and heated to 200-300°C, depending on the application. Both additional helium flow and a scavenge gas (O₂, H₂, or N₂) are introduced by means of a tee.

Results obtained with the GC-MIP instruments are described in the next section and indicate that the method is indeed useful for separating and detecting organometallics.

Gas chromatography has been utilized very heavily in this research program. However, GC requires that the analyte compounds be volatile. Thus, many compounds of environmental interest are not amenable to GC analysis. To examine high molecular weight or thermally unstable compounds, a supercritical fluid chromatograph/supercritical fluid extraction (SFC/SFE) microwave-induced helium plasma instrument has also been developed. The initial test of the supercritical fluid extraction microwave-induced plasma (SFE/MIP) instrument involved the extraction of a high

FIGURE 1. Schematic Diagram of the GC Low-Pressure Microwave-Induced Plasma Detector System.

FIGURE 2. Schematic Diagram of the GC Atmospheric-Pressure Microwave-Induced Plasma Detector System.

sulfur coal using supercritical fluid CO₂. The extraction cell was coupled to the MIP using microbore 80/20 Pt/Ir tubing placed within a 1/16-in. heated stainless steel line. The initial flow rate at 70 atm was ~5 µl/min. The temperature was held isothermal at 35°C. The pressure was increased at a rate of 10 atm/min to a maximum pressure of 400 atm. Elution of hydrogen-containing compounds first starts at 100 atm, is maximized at about 260 atm, and returns to the base line at 370 atm. This experiment demonstrates the feasibility of interfacing the SFE system to the MIP spectrometer system.

A moderate power microwave-induced helium plasma detector for monitoring the SFC/SFE effluents is being developed. Supercritical solvents such as CO₂, N₂O, and H₂O require system modification to handle the additional solvent loading. The typical system consists of a modified Beenakker cavity, a moderate power (50-500 watt) 2450-MHz microwave generator, a GC oven, and a spectrometer. Preliminary data indicate that this technique is very promising for the specific element monitoring of nonvolatile and thermally labile compounds.

USE OF A GAS CHROMATOGRAPH-MICROWAVE INDUCED PLASMA DETECTOR FOR SPECIATION OF ORGANO-METALLICS IN FOSSIL FUEL PROCESS STREAMS

D. S. Sklarew, K. B. Olsen, and S. P. Downey

While a great deal of work has been done on analysis of major and trace elements in fossil fuel process streams and hazardous wastes, very little speciation information is available. As is well known, the form of the element will drastically affect its properties. For example, organomercury compounds are more toxic than inorganic mercury; dimethyl mercury is more volatile than diphenyl mercury, etc. In contrast, organic arsenic is less toxic than inorganic arsenic. Knowledge of the particular species present will thus help determine the type and degree of control procedures needed in fossil fuel industries. Organometallics that are particularly amenable to gas chromatography (GC) analysis because of their volatility include mercury, arsenic, and selenium compounds. The GC-MIP (microwave-induced helium plasma) described in the previous section is ideally suited for speciation of these volatile organometallics because of its unique capability as a sensitive detector of metallic species.

Ten mercury standards have been analyzed by GC-MIP using a 30-m fused silica capillary column coated with Durabond-5 (DB-5, a phenyl

methyl siloxane). The standards include dialkyl mercury compounds from dimethyl through di-n-hexyl (Figure 1); monoalkyl mercury chloride compounds (C₁ and C₂), and diaryl mercury compounds (diphenyl and dibenzyl). Since these three compound classes can be separated by normal phase high performance liquid chromatography (HPLC) or

FIGURE 1. Detection of Dialkyl Mercury Standards—Comparison of Channels on GC-Low-Pressure MIP.

silica gel column chromatography, they were chromatographed separately; however, separation of all ten compounds is feasible by capillary GC. Separating dimethyl mercury from the solvent peak is a more difficult problem. This can be accomplished either by using cryogenic cooling or by increasing the thickness of the liquid film on the capillary column from the 0.25 μm shown here to 1 μm .

The peak shapes of the mercury standards are as symmetrical and sharp on the two GC-MIP systems as they are on the conventional GC-FID (flame ionization detector). This indicates that the interface designs are satisfactory with no dead volume and no cold spots. Detection limits on the carbon channel for the low-pressure MIP are comparable to those obtainable with a conventional FID. These results are similar to those of Wasik and Schwarz (1980) who reported that the MIP carbon channel had the same sensitivity as the FID for diethyl mercury. The mercury channel is about an order of magnitude more sensitive than the FID (100 pg for the MIP versus 5 ng for the FID absolute amount injected). For the atmospheric-pressure detector, the mercury channel is about two orders of magnitude more sensitive than the FID for the same compounds. It should be noted that in this work parameters have not yet been fully optimized for maximum sensitivity.

Selectivity of the atmospheric-pressure MIP is significantly better than for the low-pressure system (Figure 2). Selectivity of mercury over carbon is about 200:1 for the low-pressure system, while it was found to be greater than 10000:1 for the atmospheric-pressure system. This difference may be due to the much better resolution of the Echelle spectrometer combined with a better choice of analytical line for the atmospheric system, which is not limited by geometrical considerations as is the Rowland circle instrument.

Selection of the scavenge gas for the low-pressure system has a pronounced effect on peak shapes for the mercury channel and peak heights for the carbon channel. When an oxygen scavenge is used for mercury compounds, peak symmetry on the mercury channel is destroyed. This is presumably due to oxidation of mercury onto the plasma tube, with resulting wall losses of the less volatile mercury oxides. Use of hydrogen as a scavenge gas serves to keep the mercury in a reduced oxidation state. It thus eliminates the tailing problem and does not result in a significant change in sensitivity. Use of oxygen versus hydrogen scavenge gases for

FIGURE 2. Comparison of the Selectivity of the Atmospheric-Pressure and Low-Pressure MIP Systems

mercury compounds results in no effect on peak symmetry for the carbon channel. Oxygen was, however, found to provide considerably more sensitivity for the carbon response, presumably due to oxidation of the carbon and atomization of the resulting CO (McLean, Stanton and Penketh 1973).

Several arsenic standards have also been examined on the arsenic and carbon channels of the low-pressure MIP. Results for triphenylarsine are shown in Figure 3. The peak signal on the carbon channel is significantly greater than on the arsenic channel. This is mainly a consequence of the high ratio of carbon-to-arsenic atoms in the standard (18:1) and the relative oscillator strengths of the arsenic and carbon lines.

Figure 3. Detection of an Arsenic Compound by GC-Low-Pressure MIP.

REFERENCES

- McLean, W. R., D. L. Stanton and G. E. Penketh. 1973. *Analyst* 98:432-442.
- Wasik, S. P., and F. P. Schwarz. 1980. *J. Chromatog. Sci.* 18:660-663.

EFFECT(S) OF WATER TREATMENT ON THE ORGANIC CONTENT OF OIL SHALE RETORT WATERS

A. P. Toste, C. J. English, B. W. Mercer, and R. B. Myers

In addition to the synfuels themselves, numerous potentially hazardous by-products may be generated during synfuel production. A by-product of special concern is the retort water co-produced during the retorting of oil shale. The quantity and chemical properties of the retort water vary, depending upon the retorting technology used; aboveground retorting processes generate much less retort water than shale oil, whereas in situ processes generate approximately equal amounts of retort water and shale oil. All of the retorting processes designed to date provide for complete recycling of all process waters, with no discharge into the environment. Nevertheless, considering the enormous amounts of retort waters that may be produced in a large-scale shale oil industry, there is considerable concern about the health and environmental impacts associated with the recycling of these waters and any accidental release into the environment. Past research has demonstrated that the organic content of retort waters can be toxic and/or mutagenic. Perhaps as a result of such research, several treatment procedures typically used to clean up waste waters, e.g., wet air oxidation, are currently being applied to retort waters. In this study, we have begun examining the effect(s) of treatment on the organic content of retort waters. Two retort waters, one from an aboveground retort (Retort 1) and one from a modified in situ retort (vertical) (Retort 2), underwent wet air oxidation for time periods ranging from 20 min to 2 h. A third water, obtained from Retort 2, was treated by Retort 2 personnel using a proprietary method.

To date, several bulk properties of the treated waters have been analyzed: total dissolved solids (TDS), total carbon (TC), and nonvolatile organic carbon, typically referred to as total organic carbon (TOC). The results are summarized in Figure 1. Wet air oxidation does not appear to affect the concentration of TDS in the retort waters. The TDS concentration in the Retort 1 water did not decrease with time, whereas the TDS concentration of the Retort 2 water decreased by only 13% after 2 h of treatment. In contrast, wet air oxidation reduced the TC and TOC concentrations of the waters markedly.

FIGURE 1. Wet Air Oxidation of Retort Waters: a) retort water from Retort 1 (above ground) underwent wet air oxidation treatment for 20-120 min; b) retort water from Retort 2 (modified in situ) underwent treatment for 30-120 min. The concentration of total dissolved solids (TDS), total carbon (TC), and nonvolatile organic carbon, or total organic carbon (TOC), was measured.

Both the TC and the TOC followed the same trends. The greatest reduction in the carbon content occurred in the first 20-30 min of treatment. Very little decrease occurred after 20-30 min, suggesting that treatment times greater than ~30 min are not effective, at least relative to decreasing the carbon content of the retort waters.

The treatment procedure used at Retort 2 was quite effective in decreasing the TOC content of the Retort 2 water. Compared to two untreated retort waters collected at the retort

(3972 ppm and 2001 ppm), the content of the Retort 2 treated water (238 ppm) represents a 16.7-fold to 8.4-fold decrease in TOC. Nevertheless, the treated retort water still remains fairly high in TOC, suggesting that further treatment is necessary.

Detailed organic analyses using gas chromatography (GC) and GC/mass spectrometry (GC/MS) are currently underway and will provide information about the effect(s) of treatment on specific organic species present in the retort waters. Based on such analyses, it will be possible to determine, for example, whether certain classes of organic compounds are preferentially eliminated from solution upon treatment of the retort water.

INORGANIC AND ORGANIC ANIONS IN RETORT WATERS

D. S. Sklarew and M. McCulloch

Ion chromatography (IC) and ion chromatography exclusion (ICE) were used to qualitatively determine both inorganic and organic anions in retort waters from four different retorts. Knowledge of the presence of some of these constituents is important for both environmental and processing considerations.

For IC, both "slow-run" and "fast-run" anion columns were used with the "standard" eluent (0.003 M NaHCO_3 /0.0024 M Na_2CO_3) on a Dionex Model 16 IC. For ICE, two columns were used in sequence to improve the separation of a wide range of organic carboxylic acids. The eluent was 0.001 M HCl. Standard solutions containing inorganic and organic anions were run on both IC and ICE columns so that unknowns could be identified by retention time values on two different columns. For example, glutaric and acetic acids were not separated by ICE but were readily separated by IC. Relative retention characteristics were established for the following anions: F^- , Cl^- , NO_2^- , PO_4^{3-} , Br^- , NO_3^- , SO_4^{2-} , C_1 - C_6 -monocarboxylic acids, C_2 - C_6 -dicarboxylic acids, C_4 -unsaturated dicarboxylic acids, glycolic acid, and lactic acid. Of these anions, F^- , Cl^- , NO_2^- , SO_4^{2-} , and the C_1 - C_5 -monocarboxylic acids were observed in some or all of the four retort waters examined (see Table 1). The remaining anions were below detection limits.

TABLE 1. Inorganic and Organic Ions Found in Sample Retort Water from Four Retorts

	Retort 1	Retort 2	Retort 3	Retort 4
F ⁻	?	X	X	X
Cl ⁻	X	X	X	X
NO ₂ ⁻	?	?	n.d.	n.d.
SO ₄ ⁼	X	X	X	X
Formic Acid	X	n.d.	n.d.	n.d.
Acetic Acid	X	X	X	X
Propionic Acid	X	X	?	?
Butyric Acid	X	X	X	?
Valeric Acid	X	X	n.d.	?

? = not positively identified

X = present

n.d. = not detected

Measurement
and
Dosimetry

• Characterization of Synfuels and Combustion Products

Characterization of process and effluent streams for synfuel plants requires instruments capable of detecting and measuring high molecular weight compounds, polar compounds, or other generally intractable materials. The purpose of this study has been to investigate the application of supercritical fluid chromatographic techniques to this important problem. In this report, the successful interfacing of a supercritical fluid chromatograph to a mass spectrometer is described. Applications include the analysis of polynuclear aromatic hydrocarbons and model high molecular weight polymers.

SUPERCritical FLUID CHROMATOGRAPHY/ MASS SPECTROMETRY

R. D. Smith, B. W. Wright, and H. R. Udseth

The combination of capillary column supercritical fluid chromatography (SFC) with mass spectrometry (MS) offers unique advantages. The range of compounds that may be separated with SFC is quite similar to high performance liquid chromatography (HPLC). Both techniques allow the separation of materials that are thermally labile and of much higher molecular weight than is possible using gas chromatography (GC). Supercritical fluid chromatography has the added capabilities of much greater chromatographic efficiencies and of pressure programming, providing precise control of the solvating power of the mobile phase. The much higher volatility of most SFC mobile phases provides an additional significant advantage in the design of the SFC/MS interface. The use of wall-coated open tubular capillary columns also provides mobile phase flow rates ideally compatible with mass spectrometry.

The goal of this program is to develop improved chromatographic and mass spectrometric techniques using supercritical fluids. The method of direct fluid injection-mass spectrometry (DFI/MS) is being explored in our laboratory for the purpose of interfacing capillary column supercritical fluid chromatography with mass spectrometry. While SFC technology continues to progress rapidly, the columns available to date are best suited for relatively nonpolar compounds. The DFI/MS (and DFI/MS/MS) methods, however, are readily applicable to a wide range of compounds using a variety of fluids. The DFI method allows mass spectra to be obtained for essentially

any compound soluble in a supercritical fluid and, hence, allows a rapid qualitative evaluation for fluid phase solubility. Our experience indicates that the DFI methods have considerable potential for the rapid characterization of a wide range of compounds and complex mixtures.

The DFI/MS method has the limitation of requiring solute solubility in a supercritical fluid. This does not seem to be a severe limitation. For example, many highly polar components of coal liquids are surprisingly soluble in supercritical carbon dioxide at pressures of 250 atm. For more polar compounds, a more polar supercritical fluid is often required. Ammonia, with a critical temperature of 132°C, provides a reasonable choice for chemically compatible compounds. Figure 1 gives typical mass spectra for 4-amino biphenyl, 4,4-diamino biphenyl, and 3,3-dichloro-4,4-diamino biphenyl obtained using ammonia at 150°C and 400 atm.

The separations that can be obtained using capillary column SFC have improved considerably in the last year due to smaller bore columns and improved stationary phase preparation procedures. Figure 2 gives an example of an SFC/MS separation obtained for a coal tar fraction using a column 100 μ m wide, 10 m long. Improved results are anticipated as column preparation procedures are improved and as we progress to smaller diameter columns (25-60 μ m). Other improvements being investigated involve preparing columns more suited to polar materials and more polar fluid systems. The development of less expensive alternative detectors to mass spectrometry (which maintain the necessary sensitivity) is also being investigated.

FIGURE 1. Examples of Direct Fluid Injection Mass Spectra Obtained Using Supercritical Ammonia

FIGURE 2. An Example of an SFC/MS Separation of a Coal Tar Using Supercritical Carbon Dioxide at 60°C and Supercritical Fluid Pressure Programming.

• Lasers in Analytical Chemistry*

Lasers have several unique properties that allow them to be applied to analytical chemistry in a variety of ways. Pacific Northwest Laboratory is actively involved in developing laser-based methods for measuring low levels of materials related to health and/or the environment. A major advance in the past year has been the development of a routine technique for rapid, accurate measurements of low concentrations of uranium in biological and environmental samples. A prototype instrument has been constructed and a plan for the transfer of this technology to the private sector has been formulated.

*This program was formerly titled "Trace Analysis by Laser Excitation."

KINETIC PHOSPHORIMETRY: DEVELOPMENT OF NEW INSTRUMENTATION FOR LOW-LEVEL URANIUM ANALYSES

B. A. Bushaw

Kinetic phosphorimetry, described in the 1982 annual report, has been developed into a routine measurement procedure. Sample pre-treatment methods have been optimized for simplicity and accuracy of the measurements. Several "real world" samples have been analyzed by the technique, including ground and surface waters, brines, biological tissue digestions, simulated lung fluids, ore dissolutions, and both real and simulated urine samples. The results from five repetitive analyses of a simulated-urine blind standard were averaged to give a measured uranium concentration that was within 2% of the actual value consistent with the 1.8% relative standard deviation (RSD) precision of the measurements. The concentration of this sample (7 µg/l) was near the detection limit of currently accepted fused-salt methods. Several brine water samples with uranium concentrations of less than 1 µg/l were obtained from salt dome structures and analyzed. These results were verified by ²³³U tracer filament source mass spectrometry. In each case, the results from the two different techniques agreed to within the error limits.

Major improvements in the design of the original kinetic phosphorimeter have been incorporated into a new prototype system. Light-gathering efficiency has been improved by approximately a factor of 18 over the original apparatus. The rather large laser system (including nitrogen laser, dye laser, vacuum pump, cooling water, and gas bottle) has been replaced with a very compact, self-contained nitrogen laser-dye laser combination without significantly reducing the photon count rate. Thus, the overall size of the apparatus is reduced and the entire prototype system is transportable.

Improvements have also been made in the counting electronics. Two detectors now feed into a dual-input multichannel scaler (MCS) so that measurements can be simultaneously made on the sample and a reference standard. A microcomputer has been interfaced to inter-actively control the MCS, gather data, perform data reduction, and display prompts to the user. This has greatly simplified operation of the instrument so that only minimal user training is necessary.

The resulting instrument is relatively compact and requires only normal house current for operation. It is capable of making rapid, accurate uranium measurements at concentrations of less than one µg/l. Operation is highly automated and thus requires minimal operator training. We expect that general availability of such an instrument will have a major impact on the field of low-level uranium analysis. We have therefore developed a plan of action to transfer this technology to the private sector, beginning in FY84.

CONTINUOUS WAVE DOUBLE-RESONANCE IONIZATION

B. A. Bushaw and T. J. Whitaker

Resonance ionization is recognized as a sensitive analytical technique, but practically all experiments to date have been performed with pulsed lasers. We have developed a simple, theoretical model which shows that cw (continuous-wave) lasers can efficiently produce ionization in atomic systems. The technique involves population of two resonant intermediates followed by photoionization by a powerful infrared laser. This double-resonance technique should have several advantages over pulsed laser methods. Among these are increased ion yield and the ability to selectively ionize specific isotopes. We have ordered equipment that will allow experiments to be performed in FY84 to verify these predictions.

Physical
Processes

PHYSICAL PROCESSES IN RADIATION BIOLOGY

The Radiological Physics programs address the physical processes of radiation action on biological systems. Through integrated, multidisciplinary studies, the interaction of radiation with matter of biological significance is examined. The resulting information is integrated into predictive models of biological response.

Increased understanding of the physical, chemical, and biological mechanisms of radiation action results in a better understanding of dose-response relationships in terms of quantifiable characteristics of the radiation and the absorbing media. Experimental studies into the fundamental physical properties of energy deposition, energy transport, and cellular response are conducted to provide a data base for developing and testing chemical and biophysical models. Emphasis is on correlating radiation quality and energy transport with the formation of active chemical species, on understanding the mechanisms by which chemical agents interact at the cell level, and on developing models that correlate physical parameters of the radiation, chemical/biochemical interactions, and cellular repair phenomena with observed dose-response relationships.

• Radiation Physics

Initial Interaction Processes

A fundamental knowledge of the mechanisms by which radiation interacts with matter is essential to understanding dose-response relationships in terms of quantifiable chemical and physical processes. Our study of the initial interaction processes in the absorption of energy from a radiation field has concentrated on measuring and interpreting absolute cross sections for the interaction of fast charged particles with atomic and molecular targets. Since ionization is the primary means of energy deposition by fast charged particles, we have emphasized measurements of total, differential, and partial ionization cross sections. Cross sections for the production of electrons, differential in ejected electron energy and emission angle, are required for detailed track structure information, whereas partial ionization cross sections provide information on the final states of the target atom molecule. Of particular interest is the determination of cross section systematics and interaction mechanisms that enable extrapolation of experimental results into regions where experiments are either impractical or unfeasible. During the past year, a major study of total ionization cross sections was completed and accepted for publication (this work done in collaboration with Prof. M. E. Rudd, University of Nebraska); and studies of multiple ionization of atomic targets by proton impact were completed. Evaluation of the Bethe-Born theory for extrapolation of single differential electron emission cross sections was published for atomic targets, and the extension to molecular targets was completed. Additional data were compiled for doubly differential cross sections for ionization of H_2O and CH_4 by protons. Data analysis was extended for ionization of several target systems by C^+ ions.

DOUBLY DIFFERENTIAL IONIZATION CROSS SECTIONS

L. H. Toburen, R. D. DuBois, W. E. Wilson,
and F. M. Cummings*

The spatial distribution of primary events along a charged particle track has important consequences in the subsequent chemical and biological processes. Accurate representation of these distributions are obtained using Monte Carlo techniques that require as input detailed information on the energy and angular distributions of secondary electrons generated in the slowing down process. In the past we have made detailed studies of doubly differential cross sections for electron emission in collisions of protons with atomic and molecular targets for proton energies about 0.25 to 2 MeV. For the past few years we have undertaken to extend these results to 4 MeV and to include the study of more complex ions representative of heavy

recoil ions generated by the absorption of neutrons in tissue. For this we have concentrated on the study of ionization produced by carbon ions.

The study of doubly differential cross sections results in the accumulation, analysis, presentation, and storage of large quantities of data. A major part of our effort in this area in the past year has been to develop computer software that would enable us to efficiently analyze, plot, and store these data. The ability to provide analysis on-line is a major step in performing efficient and accurate measurements.

Analysis of data for 0.8 to 4.2 MeV C^+ ionization of helium, neon, argon, and CH_4 in terms of absolute cross sections has now been completed. Evaluation of cross section systematics can now proceed using these data. Analysis of data for proton ionization of xenon (1.5-4.2 MeV), H_2O (1.0-4.2 MeV) and CH_4 (1.0-4.2 MeV) has also been completed; the use of H_2O and CH_4 results to evaluate the Bethe-Born theory will be discussed in a later element of this report. Analysis of the CH_4 and H_2O data still indicates considerable uncertainty in the evaluation of background counts due to slit edge scattering of the primary beam. This is a particularly troublesome problem for the study of small

* Mr. Cummings is a staff member of the Dosimetry Technology Section, Radiological Sciences Department, at Pacific Northwest Laboratory and is participating in a masters degree program through the University of Washington, Joint Center for Graduate Study. The study of differential cross sections will provide the basis for his thesis.

molecules, such as CH_4 , by high energy protons because the interaction cross sections are relatively small. New data acquired during the past year have reduced many of these uncertainties, but further data will be required before results can be published.

TOTAL ION AND ELECTRON YIELDS

R. D. DuBois and M. E. Rudd*

Total ion and electron production cross sections for proton-gas collisions were initiated in 1981 in collaboration with Prof. M. E. Rudd (University of Nebraska). The emphasis of these studies was 1) to provide accurate absolute cross sections over a broad energy range suitable for assessing the accuracy of our existing data on doubly differential ionization cross sections, and 2) to provide more accurate normalization for track structure calculations.

During the past year, a major portion of this work has been concluded and a paper entitled "Cross Sections for Ionization of Gases by 5-4000 keV Protons and for Electron Capture by 5-150 keV Protons" has been accepted for publication by Physical Review A. This paper (coauthored by M. E. Rudd and T. V. Goffe of the University of Nebraska, and R. D. DuBois, L. H. Toburen, and C. A. Ratcliffe of Pacific Northwest Laboratory) represents a comprehensive study of proton ionization of atomic and molecular gas targets.

Using the parallel-plate capacitor method and a capacitance manometer to determine pressures, total cross sections for the production of positive and negative charges were measured for 5-4000 keV proton impact on He, Ne, Ar, Kr, H_2 , N_2 , CO, O_2 , CH_4 , and CO_2 . From these, ionization and electron capture cross sections were obtained and fitted to semi-empirical equations, describing the energy dependence in terms of a few parameters. At high energies, very good agreement is obtained in comparing the ionization cross

sections with earlier proton and electron impact measurements and with theoretical treatments where they are available, but discrepancies exist for some targets at low energy. Above 10 keV the electron capture cross sections are in agreement with earlier work for all the targets except CO and CH_4 , where they are 20-40% higher.

Our future plans are to continue the collaboration for measurements involving He^+ and He^{2+} impact ionization.

PARTIAL IONIZATION CROSS SECTIONS FOR H^+ AND He^+ IMPACT

R. D. DuBois

No information on the final target charge state is obtained from our measurements of total and doubly differential ionization cross sections. For theoretical interpretation, it is generally assumed that single ionization dominantly occurs and multiple ionization occurs only through the Auger channel following inner-shell ionization, a relatively rare event.

To determine the degree of multiple ionization, we have measured multiple/single ionization ratios of H^+ , He^+ -rare gas collisions. This was done by a time-of-flight target ion charge state analyzer. Absolute cross sections (σ_q) for 10-4000 keV proton impact were obtained from these ratios by normalizing to our total ion production cross sections (σ_i), i.e., $\sigma_i = \sum_q q \sigma_q$. In some cases (see Figure 1), multiple ionization cannot be ignored in interpreting ionization cross section data, e.g., multiple ionization for 1-4 MeV H^+ -Kr collisions account for ~60% of the total ionization cross sections.

A paper entitled "Multiple Ionization of Rare Gases by H^+ and He^+ " describes this work and has been accepted for publication in Physical Review A.

* Consultant, Department of Physics, University of Nebraska, Lincoln, Nebraska.

FIGURE 1. Partial Ionization Cross Sections for H⁺-Kr Impact.

INTERPRETATION OF MULTIPLE IONIZATION PROCESSES FOR PROTON IMPACT

R. D. DuBois, L. H. Toburen and S. T. Manson*

A detailed understanding of the processes leading to multiple ionization is essential for making reliable comparisons between theoretical and experimental data. In general, many processes, e.g., direct multiple ionization or inner-shell ionization followed by Auger decay, can contribute to multiple ionization. These processes can occur either by direct Coulomb ionization or by electron transfer processes.

A year ago at the International Conference on X-Ray and Atomic Inner-Shell Physics (Eugene, Oregon) we presented a preliminary analysis of the multiple ionization that occurs in

* Consultant, Department of Physics, Georgia State University, Atlanta, Georgia.

fast H⁺-Kr collisions (Toburen, DuBois and Manson 1982). Unfortunately, the complicated Auger structure of krypton made a comprehensive evaluation of the ionization pathways difficult. During the past year, we analyzed a simpler system: H⁺-Ne. By combining various experimental and theoretical data (Rødbro et al. 1979; Stolterfoht, Gabler and Leithauser 1973; Beyer, Hippler and Scharfner 1979), we were able to derive cross sections for all relevant channels leading to single and double ionization as shown in Figure 1. This work has been accepted for publication in *Physical Review Letters*. We plan to continue this type of analysis for other targets and over a broader ion energy range during the next year.

The analysis of interaction processes leading to multiply charged targets discussed above was restricted to fast proton collisions where any contributions due to electron capture could be ignored. For proton energies less than 100 keV, electron capture plays an important, if not dominant, role in target ionization. To more fully understand interaction processes near the end of charged particle tracks, a greater knowledge of electron capture will be required. Previous studies of doubly differential ionization cross sections have not provided information on the electron capture processes, since single electron capture produces no free electrons.

To learn more of the final target charge states and the influence of electron capture, we have performed coincidence measurements for multiple target ionization resulting from direct Coulomb ionization and from single electron capture by the projectile. Collisions for 15-100 keV H⁺, and He⁺ ions with rare gases were studied. An example of the results is shown in Figure 2, which illustrates that in some cases a large percentage of the total electron production (Rudd et al. 1984) originates from the second order process σ_{102} (single electron transfer plus ionization), as compared to the first order process σ_{111} (direct single ionization). Here the notation σ_{ifq} represents the cross section in which i is the incident ion charge state, f is the outgoing charge state, and q is the target charge state following the collision.

These data were described in a paper, "Multiple Ionization of Argon by Charge Transfer and Direct Ionization," presented at the XIII International Conference on the Physics of Electronic and Atomic Collisions (DuBois and Toburen 1983) held in Berlin in August 1983.

FIGURE 1. Cross Sections for Various Channels Leading to Single and Double Ionization of Neon by Proton Impact. Calculated $2s^{-1}$, $2p^{-1}$, $2s^{-2}$, and $2s^{-1} 2p^{-1}$ cross sections from Beyer, Hippler and Schartner (1979); Auger channels from Rødbro et al. (1979) and Stolterfoht et al. (1973); $2p^{-2}$ channel by deduction.

REFERENCES

Beyer, H. F., R. Hippler and K-H Schartner. 1979. "Single and Double Ionization of Neon $2s$ - and $2p$ Subshells by Proton and Electron Impact." *Z. Phys.* 292:353.

FIGURE 2. Multiple Ionization Cross Sections for Direct Coulomb Ionization and Single Electron Transfer in H^+ -Ar Collisions. Dashed curve is total electron production cross section from Rudd et al. (1984).

DuBois, R. D. and L. H. Toburen. 1983. "Multiple Ionization of Argon by Charge Transfer and Direct Ionization." Abstracts of papers for XIII International Conference on the Physics of Electronic and Atomic Collisions (ICPEAC) 498, eds. J. Eichler, W. Fritsch, I. V. Hertel, N. Stolterfoht and U. Wille.

Rødbro, M., E. Horsdal-Pederson, C. L. Cocke and J. R. Macdonald. 1979. "Inner-Shell-Electron Capture by H^+ , He^{+2} and Li^{+3} Projectiles from CH_4 , Ne and Ar." *Phys. Rev. A* 19:1936.

Rudd, M. E., R. D. DuBois, L. H. Toburen, C. A. Ratcliffe and T. V. Goffe. 1984. "Cross Sections for Ionization of Gases by 5-4000 keV Protons and for Electron Capture by 5-150 keV Protons." *Phys. Rev. A*.

Stolterfoht, N., H. Gabler and U. Leithauser. 1973. "High Resolution Ne-Auger Spectrum Produced in 4.2 MeV H^+ -Ne Collisions." *Phys. Lett.* 45A:351.

CONSTRUCTION OF A NEW DOUBLY DIFFERENTIAL CROSS SECTION APPARATUS

R. D. DuBois

A year ago we began constructing a new apparatus for the measurement of doubly differential ionization cross sections. This apparatus is designed to be fully computer controlled, to incorporate the capability of coincidence measurements between the various collision partners, and to allow electron emission measurements to be performed for gaseous and solid targets over a broader angular range than is currently accessible. During the past year, magnetic shielding was installed and initial testing of a new parallel plate electrostatic spectrometer was initiated. Development of the angular drive mechanism is continuing.

To use the new spectrometer in a way that takes advantage of its larger, solid angle capability, we require an electron detector with a larger area than that available with our standard electron multiplier. A multi-channel plate electron detector has been installed and is being tested to determine its electron detection efficiency. This detector has both larger collection area and faster timing characteristics that will enable us to more readily perform coincidence measurements, e.g., separate electron emission from target and projectile ion collisions involving structured projectiles such as He^+ , C^+ .

Initial measurements with the apparatus will commence within the next year. Initially gaseous atomic targets will be studied to determine the capabilities and limitations of the apparatus.

ELECTRON CAPTURE LEADING TO L-SHELL VACANCY PRODUCTION IN H^+ -Mg COLLISIONS

R. D. DuBois, C. L. Cocke* and J. Giese*

In collaboration with Kansas State University, we have performed measurements of 2p electron capture and direct ionization cross sections for H^+ -Mg collisions. These cross sections are important in the theoretical analysis (Berezhko, Kabachnik and Sisov 1980) of the angular distribution of Auger electron emission, which, in turn, is a sensitive measurement of the collision process.

* Kansas State University.

The experimental portion of this work is completed and a draft of the paper to be submitted to Physical Review A has been written.

REFERENCE

Berezhko, E. G., N. M. Kabachnik and V. V. Sisov. 1980. "On the Role of Electron Capture in the Inner-Shell Alignment of Atoms in Ion-Atom Collisions." Phys. Lett. A. 77A:231.

THEORETICAL SINGLE DIFFERENTIAL CROSS SECTIONS FOR HELIUM, NEON AND ARGON

J. H. Miller, L. H. Toburen, W. E. Wilson and S. T. Manson*

A model based on Bethe's theory for inelastic scattering of fast charged particles was developed to extend single differential cross sections (SDCS) for ionization of helium, neon and argon by protons with energy between 0.25 and 1.0 MeV to higher proton energies (Miller, Toburen and Manson 1983). Results predicted by this model show good agreement with measured total and SDCS and with quantum mechanical calculations using the first Born approximation.

Our approach focuses on determining coefficients in the Bethe theory that depend upon the electronic structure of the target but are independent of the projectile. Hence, the coefficients used to predict SDCS for ionization by protons should also give good results for ionization of helium, neon and argon by electron impact. Figure 1 compares our calculations for electron impact ionization of helium with data obtained with 0.5 and 2 keV electrons (Peterson, Opal and Beaty 1971). Kim (1983) has analyzed these data and deduced cross sections that he feels are accurate enough to serve as normalization standards for experimental secondary-electron distributions. The good agreement between our calculations, which are based on photo-absorption data and SDCS with protons, and the cross sections recommended by Kim give strong support to the method we have developed to predict SDCS in regions of primary and secondary energy where data are limited due to experimental difficulties. These results are being prepared for publication in Physical Review A.

* Consultant, Department of Physics, Georgia State University, Atlanta, Georgia.

FIGURE 1. Comparison of Theoretical and Experimental SDCS for Ionization of Helium by 0.5 and 2.0 keV Electrons.

REFERENCES

- Kim, Yong-Ki. 1983. "Angular and Energy Distributions of Secondary Electrons from Helium. Slow Electrons Ejected by Electron Impact." *Phys. Rev. A* 28:656-666.
- Miller, J. H., L. H. Toburen and S. T. Manson. 1983. "Differential Cross Sections for Ionization of Helium, Neon, and Argon by High-Velocity Ions." *Phys. Rev. A* 27:1337-1344.
- Peterson, W. K., C. B. Opal and E. C. Beaty. 1971. "Energy Distributions of Electrons Ejected in Ionizing Collisions of Electrons with Helium." *J. Phys. B* 4:1020-1025.

Track Structure

The initial spatial pattern of energy deposition by ionizing radiation plays a significant role in the subsequent evolution of biologically active chemical species. Radiochemical and radiobiological models of radiation action initiated by high linear energy transfer (LET) particles rely heavily on an accurate description of charged particle tracks. Our study of track structure includes both theoretical and experimental investigation of the spatial pattern of energy deposition. Incorporation of these data into models of energy transport in condensed phase clarifies the effects of the initial spatial patterns on evolving chemical yields. During the past year, a measurement of the radial distribution of ionization around high energy heavy ions was initiated at the Bevalac at Lawrence Berkeley Laboratory in collaboration with Columbia University (H. Rossi) and Lawrence Berkeley Laboratory (J. Howard). Because of experimental limitations on determination of energy deposition in nanometer-sized target sites, we continue to develop Monte Carlo codes to calculate ionization and energy imparted in small sites. During the past year, we have concentrated on analyzing molecular cross sections to determine a sounder theoretical basis for extrapolating data to higher ion energies. We have also investigated the systematics of energy loss derived from the track structure codes. The detailed description of energy deposition provided by track structure codes has been used to derive the initial spatial pattern of chemical species along a charged particle track. This information, coupled with the reaction kinetics of liquid water, provides a direct means of calculating the yield of transient species in liquid water, beginning with interaction cross sections and following through to final yields. These data are compared with time-dependent yields measured for proton, deuteron, and alpha particle impact; reasonable agreement has been obtained.

MEASUREMENT OF ENERGY DEPOSITION NEAR HEAVY ION TRACKS

N. F. Metting, L. A. Braby, H. H. Rossi,*
P. J. Kliauga,* J. Howard** and M. Rapkin**

Preliminary experiments have been completed (in collaboration with Columbia University and Lawrence Berkeley Laboratory) that use microdosimetric methods to measure energy deposition as a function of the distance from the center of heavy ion tracks.

It is generally agreed that most biological effects of exposure to ionizing radiation are a function of the spatial deposition of, as well as the rate at which, energy is deposited in tissue. High energy heavy ion beams are used for radiobiology and radiotherapy because of their large LET and favorable ratio of dose at peak to dose at entrance plateau. The associated delta-ray spectrum produces a significant low LET contribution to the lineal energy distribution. The range of these delta rays is such that, in a uniformly irradiated medium, many events are produced by delta rays of primary particles passing outside the site. The number of such events depends on the charge of the primary

ion, while the range of delta rays depends on the primary particle's velocity.

The cross section data needed to calculate these lineal energy distributions are not yet available, so experimental measurements are required. To make this measurement, it is necessary to have conditions of charged particle equilibrium. Early experiments using proportional counters mounted in 8-in. diameter tissue equivalent shells were hampered by wall effects. It was also realized that although it was possible to build a larger shell or tank to house and pressurize the detectors, it was not possible to expand the diameter of the Bevalac beam so that it completely filled the tank. Therefore, the most practical method of obtaining accurate microdosimetric spectra of these beams is by taking differential spectra; i.e., to record energy events in the proportional counter that are coincided with primary ions at known simulated distances (impact parameters). The data will then be properly integrated to construct a complete spectrum.

The experimental apparatus (see Figure 1) consists of a large aluminum tank, 8 ft long by 2 ft in diameter, with a forward window of mylar and sail cloth. Two detectors are mounted inside: a solid-state, position-sensitive detector to determine the position

* Columbia University.

** Lawrence Berkeley Laboratory.

FIGURE 1. Experimental Apparatus. The interior of the vacuum tank shows the proportional counter, the position-sensitive solid-state detector, and the tissue equivalent plastic plate.

of each primary ion; and a wall-less proportional counter, 0.64 cm in diameter, capable of detecting low or high energy events. The tank was pressurized with propane gas to 82 torr, so that the proportional counter simulated a 1 μm diameter volume of tissue.

Measurements were made of ^{20}Ne (670 MeV/amu), ^{40}Ar (570 MeV/amu) and ^{56}Fe (600 MeV/amu) beams. To determine the existence of charged particle equilibrium, a 1/4-in. thick tissue equivalent (TE) plastic plate was placed between the proportional counter and the beam source at simulated distances ranging from 52 to 140 μm from the proportional counter. Figure 2 summarizes the data for argon for three different impact parameter ranges. As illustrated, both the probability of energy deposition events per primary ion (R), and the average lineal energies ($\bar{y}$) of these events are essentially independent of the distance to the TE plate. Similar results were measured for neon. Both of these quantities are expected to decrease as distance to the wall increases, if secondary particle equilibrium has not been established. Therefore, it appears that equilibrium occurs within 52 μm of the wall for these ions. The present experimental design prevented closer positioning of the TE plate, which would be necessary to determine when secondary charged particle equilibrium is established.

Figure 3 shows the probability of energy deposition per primary ion (R), this time as a function of impact parameter for neon, argon, and iron. The unexpected shape of the neon curve may be the result of poor spatial resolution in the solid-state, position-sensitive detector. Figure 4 shows the energy distribution in the solid-state detector for neon and iron beams. The full-width half-maximum (FWHM) of the peaks is

FIGURE 2. Test for Secondary Particle Equilibrium. The probability of energy depositions per primary ion (R) and relative values of the average lineal energy ($\bar{y}$) are plotted versus the simulated distance to the TE plate for three impact parameter ranges, b,c,d. The data approximate the plateau area of the theoretical shape of such curves.

FIGURE 3. The Probability of Energy Deposition Per Primary Ion (R) Versus Impact Parameter.

FIGURE 4. The Energy Distribution in Relative Units for Neon and Iron.

much greater than the expected energy loss straggling. Also, the FWHM decreases as stopping power increases; this is consistent with the width being caused by electronic noise. If this is the case, this noise translates to a position noise of 3 mm FWHM for neon, or about one-half the proportional counter diameter.

These experiments have delineated the ranges of impact parameter and wall distance over which measurements of this kind should be made. They have also provided information necessary to improve the design of the detector-positioning apparatus. Improvements in the signal-to-noise ratio of the position-determining detector electronics should also be considered.

ANALYTICAL MODEL FOR PRIMARY IONIZATION BY POSITIVE IONS

W. E. Wilson and J. H. Miller

Development of reliable Monte Carlo track structure codes capable of providing accurate information over a wide range of experimental parameters requires cross section data that, in many cases, must be extrapolated beyond the range of available experimental data.

Such an extrapolation can be reliable only if it has a firm basis in theory that has been extensively tested by experiment. Our effort to obtain a theoretically sound analytic model for delta-ray emission probabilities has been continued. We have taken a careful look at Bethe-Born theory and the optical approximation. Bethe derived for the differential cross section for energy-loss E by a structureless ion of charge z and velocity v ,

$$d\sigma/dE = 4\pi a_0^2 z^2/T [A(E) \ln(4T/R) + B(E) + O(E/T)] \quad (1)$$

where a_0 is the Bohr radius (0.529×10^{-8} cm), R is the Rydberg energy (13.606 eV) and $T = m_0 v^2/2$, where m_0 is the electron mass.

The $\ln(4T/R)$ term in Equation (1) accounts for the contribution to the cross sections from glancing collisions and the coefficient of this term is related to the optical oscillator strength, df/dE , of the target by

$$A(E) = R^2/E df(E)/dE \quad (2)$$

The $B(E)$ term in Equation (1) accounts for the contribution to the cross section from hard collisions. This coefficient can be derived from the generalized oscillator strength of the target if accurate wave functions for the ejected electron are known. However, for molecular targets, this quantum mechanical approach is not practical and empirical methods must be used.

The basic purpose of the present work is to evaluate $B(E)$ for a group of molecules using Bethe-Born theory and experimental single differential cross sections for electron emission (SDCS). Miller, Toburen and Manson (1983) have laid the groundwork by showing how to combine experiment with theory to obtain $B(E)$ for atoms. That general procedure has been followed in applying it to molecules, with careful attention to molecular orbital effects.

Inasmuch as the available cross sections do not distinguish the contribution from individual shells of the target and are measured in terms of secondary electron energy, w , rather than energy loss, E , Equation (2) should be written as a sum over shells and viewed as a function of w ,

$$A(w) = \sum_i R^2/(w+I_i) df_i/dw \quad (3)$$

where df_i/dw is the partial oscillator strength for ionization with energy loss $E_i = w + I_i$ and obtained from df/dE by applying appropriate branching ratios. It is the

shape of $A(w)$ that influences most importantly the SDCS at small energy losses.

For energy losses $E \ll T$, measured SDCS and optical oscillator strengths have been used to obtain the hard collisions component from the relationship,

$$B(w) = T/(4\pi a_0^2 z^2) \frac{d\sigma(w)}{dw} - A(w) \ln[4T/R]$$

In this equation $d\sigma(w)/dw$ is the differential cross section for ejection of electrons with energy between w and $w+dw$ by fast ions, and $A(w)$ is given by Equation (3).

We have evaluated $B(w)$ for the iso-electronic target molecules CH_4 , NH_3 and H_2O for proton energies 0.3 to 2 MeV. The results have been used to predict SDCS at 3.0 MeV (CH_4 and H_2O) and at 4.2 MeV (H_2O) for comparison with SDCS data measured at these energies.

The photoabsorption data required for the evaluation of Equation (4) for the three subject molecules were, for the most part, obtained from Berkowitz's compilation (1979). The optical oscillator strengths were adapted from the photoabsorption cross sections using the relation $Rdf/dE = \sigma(E)/8.07 \text{ Mb}$. Efficiency for photoionization and branching

ratios was applied to produce the appropriate partial oscillator strength for ionization, df_i/dw , needed to evaluate Equation (3).

For methane and ammonia, $B(w)$ was evaluated using SDCS data at three ion energies 0.25, 1.0 and 2.0 MeV (Lynch, Toburen, and Wilson 1976); for H_2O , data at four energies, 0.3, 0.5, 1.0 and 1.5 MeV, were available for evaluation (Toburen and Wilson 1977); we show here the results for only H_2O (Figure 1). According to Bethe-Born theory, $B(w)$ should be independent of ion energy; the results in Figure 1 support this very well. The solid line (empirical) in the left panel of the figure is a simple average of the data points. The dashed line is calculated in the binary-encounter approximation (Rudd and Macek 1972) and is essentially given by Rutherford scattering, i.e., $B(w) \approx 1/w^2$. The right panel in Figure 1 presents $B(w)$ plotted on a log-log scale in order to better show the small values of B . The hard collisions component approaches the classical limit for very large energy losses.

With $B(w)$ evaluated from experimental data and recognizing that it is independent of ion energy, we can now predict the SDCS at other ion energies. We have done this for methane and water for which we have additional but

FIGURE 1. Hard-Collisions Component for Proton Ionization of Water. Solid line (left panel) is a simple average of the points, the dashed line is the result of a binary-encounter-approximation calculation. The spikes on the experimental data curves in the right panel arise from Auger emission following inner-shell ionization of oxygen and are ignored in the present work.

previously unpublished ionization data. Results for our model are shown for water at 0.5-4.2 MeV (Figure 2).

Since the data for ion energies 2.0 MeV and less were used to obtain $B(w)$, comparison with that data is no real test of our model; we must have good agreement for them. Nevertheless, the $B(w)$ used in the model is an average obtained from these several energies and the recalculation of this low energy SDCS data shows to what accuracy it is possible to fit the original data. The results shown in Figure 2 indicate that the model reflects the source data very well, easily within their

experimental error. Owing to experimental difficulties, the SDCS data at 3.0 and 4.2 MeV in Figure 2 do not enjoy the same precision as the lower energy data. They are sufficiently accurate, however, to provide a useful comparison with model predictions at higher energies and with data not used in the model definition. With no additional assumptions or modifications the model is able to predict very well the experimental results above 30 eV electron energy; and below that energy, the difficulties are clearly experimental ones. This good agreement gives us considerable confidence in the reliability of model-SDCS results for higher ion energies.

FIGURE 2. Cross Section Differential in Electron Energy for Electron Ejection from Water by Protons; Comparison of Model Predictions with Data. Upper three curves are each displaced by a decade from the curve below.

REFERENCES

- Berkowitz, J. 1979. "Photoabsorption, Photoionization, and Photoelectron Spectroscopy." Academic Press, New York, ISBN 0-12-091650-9.
- Lynch, D. J., L. H. Toburen and W. E. Wilson. 1976. "Electron Emission from Methane, Ammonia, Monomethylamine, and Dimethylamine by 0.25 to 2.0 MeV Protons." J. Chem. Phys. 64:2616-2622.
- Miller, J. M., L. H. Toburen and S. T. Manson. 1983. "Differential Cross Sections for Ionization of Helium, Neon, and Argon by High-Velocity Ions." Phys. Rev. A. 27:1337-1344.
- Toburen, L. H., and W. E. Wilson. 1977. "Energy and Angular Distributions of Electrons Ejected from Water Vapor by 0.3-1.5 MeV Protons." J. Chem. Phys. 66:5202-5213.
- Rudd, M. E., and J. H. Macek. 1972. "Mechanisms of Electron Production in Ion-Atom Collisions." Case Studies in Atomic Physics 3:47-136.

MEAN DELTA-RAY ENERGIES IN ION MOLECULE COLLISIONS

W. E. Wilson

In Monte Carlo track structure simulations, we often need reliable ways of testing or checking to see that results are realistic. To this end, a simple analytic expression was derived for obtaining the mean energy of energetic delta-rays arising when positive ions pass through tissue-like matter; calculated values were compared with experimental measurements and the regions of applicability were estimated.

The energy spectra of secondary electrons ejected when energetic ions undergo ionizing collisions with the atoms and molecules of an absorber are of fundamental importance in high LET radiation dosimetry. A sizeable literature has been published on the ionization of atomic and molecular targets by protons of up to a few MeV. This literature is sufficiently developed that some rather general observations and conclusions can be obtained about the secondary electron distributions that are important for developing concepts of ion-track structure.

One of these general features is that the functional dependence of the delta-ray spectrum on secondary electron energy is rather faithfully $1/w^2$ for energetic delta rays.

This feature allows a very simple relationship to be derived for the mean delta-ray energy.

We begin by generalizing the usual definition of the mean delta-ray energy, $\langle w \rangle$, in the following way:

$$\langle w(\Delta) \rangle = \frac{\int_{\Delta}^{\infty} w \sigma(w) dw}{\int_{\Delta}^{\infty} \sigma(w) dw} \quad (1)$$

In this equation, $\langle w(\Delta) \rangle$ is the expected delta-ray energy obtained from averaging over that portion of the spectrum for which w is greater than Δ . Here Δ has the practical significance of a cut-off energy exactly in the sense of energy restricted LET. $\langle w(\Delta) \rangle$ is the mean energy of the delta rays that are not localized when considering L_{Δ} .

Values for $\langle w(\Delta) \rangle$ for H₂O and neon, numerically evaluated according to Equation (1), from experimental data (Lynch, Toburen, and Wilson 1976; Toburen and Wilson 1977) are indicated in Figure 1 by the broken lines. For clarity, each of the upper three curves is successively displaced upward by one decade from the curve below it. The inflection in the 1 and 1.5 MeV data curves is caused by the respective Auger peak in the cross section data.

The classical (Rutherford) cross section for elastic collisions is given by

$$\sigma(w) = \frac{2}{m_0} \frac{Z^2 e^4}{V^2} \frac{1}{w^2} \quad (2)$$

where m_0 is the mass of the struck particle (electron in this case), and V is the velocity of the striking particle (ion of charge Ze) [see, for example, Evans (1955, p. 571)]. If this expression is substituted into Equation (1), the terms that do not depend on w can be factored out and cancelled because they appear in both numerator and denominator. The resulting integral equation can be easily solved analytically to give

$$\langle w(\Delta) \rangle = [\Delta * w_m / w_m - \Delta] \ln(w_m / \Delta) \quad (3)$$

$$w_m \text{ is given by } w_m = 2m_0 V^2 / (1 - \beta^2) \quad (4a)$$

$$\text{which simplifies to } w_m = 4m_0 E_i / m_i \quad (4b)$$

for non-relativistic ion energies E_i and mass m_i (Evans 1955, p. 575).

$\langle w(\Delta) \rangle$ calculated from Equation (3) is indicated in Figure 1 by the solid lines for the four ion energies. The excellent agreement for Δ greater than about 50 eV reflects the

FIGURE 1. Mean Secondary Electron Energies as a Function of Low-Energy Integration Limit, Δ (see Equation 1). The broken curves are from numerical integration of cross section data. The solid line is calculated assuming the cross sections are given by classical theory, i.e., are proportional to $1/w^2$. For clarity, each of the upper three examples is successively offset by one decade from the one below it.

extent to which the collisions may be regarded as classical and the binding of the electrons ignored for calculation of mean energies. The agreement is poorest for the 0.3 MeV/amu data because at this low ion energy the experimental spectrum does not exhibit a w^{-2} dependence over a significant range of w (see Toburen and Wilson 1977). Nevertheless, the magnitude and major functional dependence on Δ is adequate for many

computational purposes. The divergence of experiment from Equation 2 for large Δ arises because the experimental data in this energy region indicate a dependence of w^{-x} , where $x < 2$. At present, this is considered to be an anomaly, perhaps arising from insufficient doubly differential cross section data that are integrated to give the single differentials.

These results indicate that Equations (1-4) can be used to predict mean delta-ray energies for ion energies, E_i , greater than about 0.3 MeV/amu and for $w \gtrsim 50$ eV where the SDCS spectra are reasonably well approximated by a $1/w^2$ dependence.

REFERENCES

Evans, R. D. 1955. The Atomic Nucleus. McGraw-Hill Book Co., New York.

Lynch, D. J., L. H. Toburen and W. E. Wilson. 1976. "Electron Emission from Methane, Ammonia, Monomethylamine and Dimethylamine by 0.25 to 2.0 MeV Protons." J. Chem. Phys. 64:2616-2622.

Toburen, L. H., and W. E. Wilson. 1977. "Energy and Angular Distributions of Electrons Ejected from Water Vapor by 0.3-1.5 MeV Protons." J. Chem. Phys. 66:5202-5213.

ENERGY IMPARTED TO DNA-LIKE STRUCTURES BY HIGH LINEAR ENERGY TRANSFER RADIATIONS

W. E. Wilson

A collaborative effort was initiated with Drs. D. T. Goodhead and D. E. Charlton of the Medical Research Council-Radiobiology Unit at Harwell (UK). The purpose of the effort was to investigate patterns of energy deposition by protons, deuterons and helium ions in various geometrics (including spherical and cylindrical) with dimensions comparable to those of likely genetic targets. These targets include the DNA molecule of diameter ≈ 2 nm and the higher order structures of DNA associated with nucleosomes and elementary chromatin fibers. The Monte Carlo code MOCA13 is used to generate full histories of segments of tracks of positive ions, including the histories of all secondary electrons down to low energies (~ 10 eV). The output data of energy deposition and spatial coordinates of inelastic interactions are sampled with a scoring routine for each of the various geometries of interest. Initial work has focused on spheres and cylinders of varying diameter and length covering dimensions of special interest from ~ 1 nm to 100 nm. These data will be compared with existing and future experimental results on the biological effectiveness of heavy ion irradiations of mammalian cells. These comparisons will seek to identify properties that may be responsible for the biological action of the ions and to constrain possible mechanisms of radiation action.

CALCULATING TRANSIENT YIELDS OF WATER RADICALS PRODUCED IN PULSE RADIOLYSIS WITH ION BEAMS

J. H. Miller, W. E. Wilson, D. J. Brenner* and M. Zaider*

A collaboration with Drs. Brenner and Zaider at the Radiological Physics Laboratory of Columbia University has led to the development of a more mechanistic approach to the calculation of transient yields in water irradiated by high energy ion beams. Previous calculations of transient yields (Miller and Wilson 1982) were based on the spatial distribution of absorbed energy with the assumption that the initial concentration of radicals is proportional to the local energy density. The mechanistic approach attempts to identify the reactive species that evolve from each inelastic collision of the primary ion and all generations of secondary electrons.

Little is known about the final state of inelastic collisions in liquid water. Our model assumes two types of energy loss events: neutral excitations that produce H and OH, and ionizations with final states that contain e_{aq}^- , H_3O^+ and OH. In water vapor the G values (yield per 100 eV of energy absorbed) of neutral final states and ionizations are both about 3.8 (Miller and Green 1973). Based on this result and our assumption about final states in the liquid, we would predict initial yields of e_{aq}^- and OH equal to 3.8 and 7.6, respectively. Using picosecond pulse radiolysis with high energy electrons, Jonah and Miller (1977) observed $G_{e_{aq}^-} = 4.5$ and $G_{OH} = 5.9$. This difference between the yield of radicals in vapor and liquid phase can be explained by autoionization and geminate recombination that result from intermolecular energy transfer in a condensed medium. Although these processes are not understood in detail, simple models with physically reasonable parameters can be developed that will account for the yield of e_{aq}^- and OH observed in liquid water at early times with radiation of low linear energy transfer.

Given the initial yield and spatial distribution of water radicals, the kinetics of their

* Radiological Research Laboratory, Columbia University, New York, New York.

decay through diffusion and chemical reactions can be calculated by several numerical techniques. We developed a semi-analytic method by assuming that the concentration of radicals is a linear superposition of Gaussian distribution functions (prescribed diffusion approximation). Figure 1 compares our calculated results with measurements of the yield of hydrated electrons produced in a water jet by a pulsed 3 MeV proton beam (Rice et al. 1982). Although the shape of the calculated decay is similar to the data, the magnitude is too small by 25% to 50%.

Possible sources of this discrepancy are currently being investigated. These results do not include the recent improvements in source terms for production of secondary electrons discussed above. A part of this discrepancy between theory and experiment may result from our use of the prescribed diffusion approximation. This possibility will be tested by comparing our present results with a stochastic diffusion model (Clifford et al. 1982). It is also possible that the difference between theory and experiment results from the fundamental assumption in our model that the initial G value for hydrated electrons produced by proton irradiations is the same as that observed with high energy electrons (Jonah and Miller 1977). We will test this possibility by varying the parameters of our model that influence the initial radical yields.

FIGURE 1. Comparison of Calculated and Experimental Yields of the Hydrated Electron Produced by a 3 MeV, Pulsed Proton Beam Stopped in a Water Jet.

REFERENCES

- Clifford, P., N. J. B. Green and M. J. Pilling. 1982. "Monte Carlo Simulation of Diffusion and Reaction in Radiation-Induced Spurs. Comparisons with Analytic Models." *J. Phys. Chem.* 86:1322-1327.
- Jonah, D. C., and J. R. Miller. 1977. "Yield and Decay of the OH Radical from 200 ps to 3 ns." *J. Phys. Chem.* 81:1974-1976.
- Miller, J. H., and A. E. S. Green. 1973. "Proton Energy Deposition in Water Vapor." *Radiat. Res.* 54:343-363.
- Miller, J. H., and W. E. Wilson. 1982. "Modeling Early Events in the Radiation Chemistry of Dilute Aqueous Solutions." In: *Proceedings of the Workshop on the Interface Between Radiation Chemistry and Radiation Physics*, pp. 73-81. ANL-82-88, Argonne National Laboratory, Argonne, Illinois.
- Rice, S. A., V. J. Playford, W. G. Burns and G. V. Buxton. 1982. "Nanosecond Proton Pulse Radiolysis." *J. Phys. E* 15:1240-1243.

• Radiation Dosimetry

Dosimetry

The basic goal of the Radiation Dosimetry task is to explore the connections between the primary physical events produced by the interaction of radiation with matter and their subsequent biological consequences. Dosimetry concentrates on the physical aspects of the problem, emphasizing the use of fundamental physical data in deriving detailed dosimetric information. Special mathematical and experimental techniques are developed to investigate specialized dosimetry problems arising in radiobiological research and encountered in the environment. During the past year, the experience gained from these studies has been applied through national and international committees studying special dosimetry problems.

MOMENTS AND THEIR USE IN MICRODOSIMETRY AND DOSIMETRY

W. C. Roesch

Kellerer and Rossi (1970) showed that the mean square of the specific energy, z , a microdosimetric quantity, was linear-quadratic in the absorbed dose, D : $\langle z^2 \rangle = hD + D^2$, where h is independent of the dose. I extended the theory of such moments by showing how some of them could be calculated for internally deposited sources (Roesch 1977). Kellerer and Rossi (1972) used their relation in developing what they called the dual-action theory of radiobiological damage. Regardless of the status of their theory, they opened a useful route for linking microdosimetry with radiobiological theory. To further open up this route, I completed the derivations for the moments for all the cases of internally deposited radioactive particulates (and some external radiations) known to me.

Most of these moments can be put in the form

$$\langle z^2 \rangle = (h + ah')D + D^2 \quad (1)$$

where h is the same quantity found by Kellerer and Rossi and h' is another quantity independent of the dose. The quantity a is the mean number of charged particles emitted by each particulate, and the product ah' represents the effect of more than one particle emerging from the same particulate. Such a term does not enter into the Kellerer-Rossi expression because they considered only external radiations that produce charged particles at random in a medium, with negligible probability of more than one particle being produced at the same point. While h' does not depend on the dose, the quantity a may. For example, if a (the number of particles per particulate) is changed, the dose will change. But, if a is kept constant, the dose

can still be changed by changing the number of particulates. Equation (1) correctly reflects the dependence on dose for this latter case. But, when the number of particles emitted changes, $a = kD$, where k is independent of dose; and

$$\langle z^2 \rangle = hD + (1 + kh')D^2 \quad (2)$$

for a different dependence on dose.

Much experimental data, at low doses, can be represented by $E = AD + BD^2$, where E is the yield of the effect and A and B are constants. The above considerations about moments suggest how such a linear-quadratic relation might arise. For example, the Kellerer-Rossi hypothesis is that the effects are proportional to the mean square of z ; this leads to both linear and quadratic dependence on dose. The results reported here show that for internally deposited particulates the situation is more complicated: the coefficients A and B can depend on how the experiment is carried out, i.e., on whether the dose is changed by changing the number of particles per particulate or by changing the number of particulates (or by some other method).

The linear-quadratic dependence of $\langle z^2 \rangle$ on dose comes about because the z values have a stochastic distribution. I have also been studying the effect on the $E = AD + BD^2$ relation of a much different form of dose variation. Ideally, the relation can be thought of as that established under conditions where every cell is exposed to the same dose. But in many situations, particularly in radiation protection and in epidemiological studies, we assign a person a single dose--neglecting the actual variation of the dose in his body. In these circumstances then, there is a distribution of doses for different cells apart from the stochastic differences studied

above; and the dose effect relation that should be used is

$$E = AD + B\overline{D}^2 \quad (3)$$

where the bars indicate that the mean and mean-square over the distribution of doses should be used. This relation can also be written in terms of just the mean dose and the variance, s^2 , of the dose:

$$E = A\overline{D} + B(\overline{D}^2 + s^2) \quad (4)$$

This form suggests, as one might expect, that the simpler form is applicable only when the variance of the dose distribution is small.

Calculations for typical dose distributions (exponential absorption, surface transition dose, variation in dose across a beam) all show a result similar to that for the mean-square specific energy: the mean-square dose is a linear-quadratic function of the mean dose. The implication is that a dose-effect relation determined from the type of incomplete dosimetry being discussed will give linear and quadratic components, but the division between these components will depend on the particular dose distribution that exists. And that division will not be the same as in the "good-dosimetry" situation described by Equation (3).

REFERENCES

Kellerer, A. M. and H. H. Rossi. 1970. "Summary of the Quantities and Functions Employed in Microdosimetry." In: Proc. of the Second Symposium on Microdosimetry, ed. H. G. Ebert, pp. 843-853, Euratom, Brussels.

Kellerer, A. M. and H. H. Rossi. 1972. "The Theory of Dual Radiation Action." Curr. Topics Radiat. Res. Quarterly 8:85-158.

Roesch, W. C. 1977. "Microdosimetry of Internal Sources." Radiat. Res. 70:494-510.

RE-EVALUATION OF THE HIROSHIMA-NAGASAKI RADIATION DOSES

W. C. Roesch

The re-evaluation of the doses of the atom-bomb survivors is proceeding vigorously. The National Academy of Sciences Panel on Re-assessment of A-Bomb Dosimetry met in October and May. The Panel and their Japanese counterparts co-sponsored the U.S.-Japan Joint Workshop for Reassessment of A-Bomb Dosimetry in Hiroshima and Nagasaki, which was held at

Nagasaki in February. A second joint workshop is scheduled to be held at Hiroshima in November. In September a seminar was held at Los Alamos National Laboratory to present the results of criticality measurements and measurements of the radiation external to a duplicate of Little Boy, the Hiroshima weapon.

The aim of these cooperative efforts is to develop a computer program that can be used to calculate doses from the data base concerning the bomb survivors. This data base is held at the Radiation Effects Research Foundation, a joint U.S.-Japanese effort located at Hiroshima. The program is not yet at the stage of designing the computer code. The bits and pieces of information that will go into the computer code and the data base are still being assembled and reconciled. There are so many such pieces that an extensive effort is under way to determine the validity of each piece, and therefore, ultimately, the confidence we have in the final dosimetry.

BETA-PARTICLE DOSIMETRY

W. C. Roesch

About 25 years ago, Radiological Physics had an extensive program of research and development in the measurement of beta-particle dose (Roesch and Donaldson 1956). Interest in this old work was revived two years ago when the Nuclear Regulatory Commission began reviewing how beta-particle dosimetry was being performed by its licensees. In December 1981, I attended the Beta Dosimetry Workshop, held at the DOE Environmental Measurements Laboratory in New York, to consult about our old results. During the past year I was invited to present a paper (Roesch 1983a) and chair a workshop (Roesch 1983b) at the International Beta Dosimetry Symposium held in Washington, D.C.

One of the recommendations of the 1981 workshop was that the National Council on Radiation Protection and Measurements (NCRP) be asked to review the conditions under which beta-particle doses in the skin should be measured for radiation-protection purposes. I was assigned to refer the question to them. The NCRP responded by having a representative at the 1982 symposium. After the symposium, the NCRP agreed that skin dosimetry should be re-examined and set up the NCRP Scientific Committee No. 80, Radiobiology of the Skin (and Beta-Particle Dosimetry) to do it. I was appointed chairman of the committee. The other members of the committee are being selected now.

REFERENCES

Roesch, W. C. and E. E. Donaldson. 1956. "Portable Instruments for Beta-Ray Dosimetry." In: Proc. Int. Conf. on the Peaceful Uses of Atomic Energy 14:172-175.

Roesch, W. C. 1983a. "Field Practices and Techniques: Introduction," presented at the International Beta Dosimetry Symposium, Washington, D.C.

Roesch, W. C. 1983b. "Dose Assessment," a workshop at the International Beta Dosimetry Symposium, Washington, D.C.

CONCEPTUAL BASIS OF CALCULATIONS OF DOSE DISTRIBUTIONS

W. C. Roesch

In 1980, the National Council on Radiation Protection activated a scientific committee (SC 52) to prepare a broad analysis of the principles of dose calculations. Under the chairmanship of Dr. H. H. Rossi of Columbia University, the committee completed a first

draft of its report and met in March to review it. The committee is still working on the extensive revisions resulting from that review.

Last year a study growing out of the committee work was reported. Its aim was to estimate the effect of the nonuniformity of source distribution in conventional dosimetry. That study was extended and incorporated into computer programs for calculating microdosimetric distributions for internally deposited radionuclides. In essence, the incorporation represents merely a "turning off" of the microdosimetry part of the computer program. The program had been developed for use with alpha-particle emitters; suitable approximations to the microdosimetry data for beta-particle and gamma-ray sources were added so their dosimetry could be studied also. This work was reported at the Radiation Research Society meeting (Roesch 1983).

REFERENCE

Roesch, W. C. 1983. "Inhomogeneous Distributions of Sources." Radiat. Res. 94:577-578.

Modeling and Cellular Studies

The effects of ionizing radiation on living systems begin with the basic physical processes of energy deposition and develop through many stages of chemical reactions and biological responses. The modeling effort attempts to develop mathematical descriptions of the response of cells to radiation and to provide a systematic means of interpreting the biological response in terms of quantifiable physical parameters of the radiation field. Studying the kinetics of cell response as a function of dose, dose rate, and radiation quality provides a means of testing fundamental assumptions regarding the mechanisms of damage and repair.

Mathematical modeling and cellular studies complement each other. Modeling provides guidance in designing experiments capable of disproving the model, while the experiments themselves provide new input to the model. Based on previous experimental results, the model for the accumulation of damage in *Chlamydomonas reinhardtii* has been extended to include various multiple two-event combinations. Since conventional split-dose experiments at low linear energy transfer (LET) cannot discriminate between these models, they have been extended to include ion irradiations at LET up to 100 keV/ μ m.

THE LINEAR ENERGY TRANSFER DEPENDENCE OF ONE-EVENT AND TWO-EVENT DAMAGE IN *Chlamydomonas reinhardtii*

L. A. Braby and B. S. Jacobson

In previous studies using electron irradiation, it was shown that at least two different types of damage, repaired by separate processes, are involved in the response of *C. reinhardtii* to ionizing radiation (Nelson, Braby and Roesch 1980). In addition, these cells show a remarkably large increase in relative biological effect (RBE) with decrease in electron energy (Braby, Nelson and Roesch 1980). Since this increase in RBE occurs without measurable single-event damage, we have concluded that there must be two steps in the production of potentially lethal damage in these cells. First, the damage is produced by single charged-particle tracks in some way that depends on radiation quality. In addition, the products of separate tracks interact in some way.

We refer to this general scheme as a multiple two-event model, on the assumption that the damage that is dependent on radiation quality involves the interaction of two or more initial products of the radiation. There are a great many possible forms of multiple two-event models with two or more repair processes. As a result, it is difficult to devise experiments that are capable of disproving all but the kinetic system used by the cells. Data on the dose dependence of survival in split-dose irradiations have provided guidance regarding the characteristics a model must possess (Nelson, Roesch and Braby 1982). Further guidance in formulating

multiple two-event models can probably be found in the response of *C. reinhardtii* to radiations of different linear energy transfer (LET), and to its response to split-dose irradiations using different LETs. However, the response of cells to radiations of different qualities depends not only on the rates of damage interaction and repair, but also on the distance between initial products. Thus, these experiments also provide information needed to determine which track structure characteristics control the production of damage.

In an effort to provide the information needed to further develop models, experiments have been undertaken using hydrogen, deuterium, ^3He and ^4He ion irradiation. Preliminary results were reported at the Radiation Research Society meeting (Braby and Jacobson 1983). These ions have stopping powers ranging from 10 to 100 keV/ μ m in water. Typical survival data for a range of ion energies are shown in Figure 1. When plotted as $\ln S/D$ (Figure 2) these data show an essentially zero intercept for all of the hydrogen ions. Thus, we must conclude that the probability of producing lethal damage in *C. reinhardtii* in a single proton or deuteron event is extremely small. On the other hand, the probability of producing damage that can interact with additional damage, proportional to the slope of these lines, more than doubles between 13 and 26 keV/ μ m. This increase in the probability of two-event damage without apparent single-event damage is consistent with multiple two-event models in general. However, the helium ions show a very different situation. At 81 keV/ μ m the intercept is 0.17 Gray^{-1} and increases threefold at

FIGURE 1. Survival of *C. reinhardtii* Cells Exposed to the Specified Mono-Energetic Ions.

99 keV/μm. This indicates that if initial products along tracks are of high enough densities, there is a relatively high probability of a single track producing all of the damage needed to kill a cell. Interestingly, the slope of $\ln S/D$ increases even more rapidly, by almost a factor of 5, between 81 and 99 keV/μm. As expected, there is no simple relationship between stopping power and slope or intercept. Rather, we expect the relationship to involve some characteristic of the track structure that includes the distance between ionizations or groups of ionizations. These measurements are now being refined and suitable track structure calculations are being made.

REFERENCES

- Braby, L. A. and B. S. Jacobson. 1983. "L.E.T. Dependence of Two Event Damage in *Chlamydomonas reinhardtii*." *Rad. Res.* 94:556.
- Braby, L. A., J. M. Nelson and W. C. Roesch. 1980. "Studies of *Chlamydomonas reinhardtii*: Experimental." In *Physical Sciences. Part 4 of Pacific Northwest Laboratory Annual Report for 1979 to the DOE Assistant Secretary for Environment*, p. 40-44. PNL-3300 PT4, Pacific Northwest Laboratory, Richland, Washington.
- Nelson, J. M., L. A. Braby and W. C. Roesch. 1980. "Rapid Repair of Ionizing Radiation Injury in *Chlamydomonas reinhardtii*." *Radiat. Res.* 83:279-289.
- Nelson, J. M., W. C. Roesch and L. A. Braby. 1982. "Experimental Evidence and Support of Multiple Two-Event Models." In *Physical Sciences. Part 4 of Pacific Northwest Laboratory Annual Report for 1981 to the DOE Office of Energy Research*, pp. 42-44. PNL-4100 PT4, Pacific Northwest Laboratory, Richland, Washington.

FIGURE 2. The Data of Figure 1 Plotted as $-\ln S/D$ So That the Intercept and Slope of Each Line Give the Parameters α and β in the Expression $S=e^{-(\alpha D + \beta D^2)}$.

EFFECTS OF LINEAR ENERGY TRANSFER ON CELLULAR REPAIR RATES

L. A. Braby and B. S. Jacobson

A wide variety of different models of the effects of ionizing radiation on cells has been proposed by various researchers. These models differ widely in assumptions made about the fundamental mechanisms of damage and repair. However, because of the complexity of biological processes, many of these models have not been formulated in mathematical detail. As a result, these models cannot be evaluated with respect to the kinetics of cellular response. In fact, several different kinds of kinetics may be compatible with each type of model, depending on how the fundamental mechanisms are assumed to interact. If some of these proposed mechanisms can be eliminated, it will greatly simplify the problem of developing alternative models that can be tested in detail, and that can then be used as a basis of extrapolation to low doses.

One assumption, which appears to be testable and which is common to many models of potentially lethal damage, is that only one type of damage is produced but that it is less repairable when produced by high linear energy transfer (LET) radiation. A variation of this assumption is that two different types of damage are produced by high- and low-LET radiations, but both are repaired by the same process. A result of this assumption is that the repair rate observed in split-dose experiments is expected to increase for damage produced by higher LET radiation. Other models, including those that assume a single type of sublethal damage with the probability of interaction increasing as LET increases, lead to the conclusion that the repair rate should be unchanged, but the maximum amount of damage repaired should decrease with increasing LET.

We are testing these alternative hypotheses with *C. reinhardtii* as a test system. Similar experiments using mammalian cells, which require additional modifications to our cell

irradiation beam line, are planned for the future. Split-dose irradiations using proton, deuteron, ^3He , and ^4He ions giving a stopping power range from 10 to 100 keV/ μm are being used to measure repair rates. The results for protons and ^3He ions with stopping powers of 13 and 81 keV/ μm are shown in Figure 1. These results will be reported at the 1984 Radiation Research Society Meeting. The mean repair time with both ions is about 33 min, only slightly longer than the 29 min measured with electron irradiation. Results for ^4He ions show a marked increase in single-event damage and the corresponding decrease in the amount of repairable damage.

Because the irradiated field in these experiments is small, statistics are still limited, and the uncertainty in the repair rates could conceal differences as large as about 50%. However, it is unlikely that even a 50% change in the rate at which potentially lethal damage is repaired could be responsible for the observed increase in RBE, a factor of 3. Thus, we tentatively conclude that the increased effectiveness of high LET radiations is not due to the production of repair resistant damage, but rather to the difference in the spatial distribution of damage.

FIGURE 1. Split-Dose Survival Data for *C. reinhardtii* Exposed to Proton and ^3He Tracks Plotted as $\ln S_m/S$, So That the Mean Repair Time for Sublethal Damage Can Be Easily Determined. These two radiations, with widely different stopping power and RBE, result in the same mean repair time, 50 min.

These experiments tested the rate of the repair process that is dominant near the optimum culture temperature (25°C) for these cells. There is a faster repair process (Nelson, Braby and Roesch 1980) observed only at temperatures above 25°C, which remains to be tested for change in rate with radiations of different LET.

REFERENCE

Nelson, J. M., L. A. Braby and W. C. Roesch. 1980. "Rapid Repair of Ionizing Radiation Injury in Chlamydomonas reinhardi." Radiat. Res. 83:279-289.

 

• Radiation Biophysics

Experimental studies in cellular radiobiology are undertaken to provide comprehensive tests of theoretical models that relate biological phenomena with their initiating physical events. These studies are closely coordinated with the models being developed in the Radiation Dosimetry task, giving laboratory support and guidance to development of the theory. Studies involving synchronized mammalian cell cultures [Chinese hamster ovary (CHO) cells] and various irradiation parameters such as dose rate, dose fractionation, and radiation quality are designed and selected to provide optimum tests of the theory. To perform dose and dose-rate measurements at low doses, cells with constant radiosensitivity are required. To provide this consistency with mammalian cells, stationary-phase cultures must be used. Methods of arresting growth of Chinese hamster ovary cultures have been developed, and the kinetics of stationary cell systems produced by such methods have been thoroughly evaluated. Repair of cumulative damage resulting from exposure of these and other cell systems to ionizing radiation is being investigated.

CHARACTERIZATION OF CHINESE HAMSTER OVARY (CHO) CELLS IN PLATEAU-PHASE CULTURES

J. M. Nelson and N. F. Metting

Accurate measurements of characteristic repair times are required as input into the modeling effort of the Radiation Dosimetry program. These repair constants may be determined by either split-dose or dose-rate methods, provided that cellular radiation sensitivity remains relatively constant throughout the experiment. However, radiation sensitivity of mammalian cells changes rapidly as the cells progress through the intermitotic cycle and irradiation itself affects the rate of cell-cycle traverse. This makes it difficult, if not impossible, to gain useful information from exponentially growing cell cultures by either method when the experiments last more than just a few minutes. Consequently, stationary-phase cells, whose radiation sensitivity is not expected to change with time, should be suitable for such quantitative determinations.

Long-term culture with either periodic medium refreshment or continuous nutritional deprivation produce plateau-phase cultures in which no net increase in cell number occurs. These cultures often include a proportion of stationary-phase cells that do not progress through the intermitotic cycle. Historically, most investigators have assumed plateau-phase mammalian cells to be static, noncycling populations. These cells were believed to have exited the proliferative cycle as G₁-phase cells, and little difference was expected between the starved and fed cultures. However, cells brought into plateau phase by these different methods have

been found to respond differently to ionizing radiation and data now available suggest a less simplistic characterization of nonprogressing cells.

Our Chinese hamster (CHO-K1) cells are grown in monolayer cultures and have been evaluated long after they reach confluence. They are found to have ceased proliferative activity and entered stationary (nonprogressing) phase at different positions within the intermitotic cycle. Aged cells in starved and fed, late plateau-phase cultures were analyzed by four methods. Reproductive integrity and cell viability were determined daily by clonogenic-cell assay and ethyrosine-b dye-exclusion techniques. Time lapse video microscopic observations of dividing cells were used to measure mitotic frequencies of cells harvested from 18-day-old cultures. Tritiated-thymidine (³H-TdR) autoradiography was used to determine the fractions of DNA-synthesizing cells in cultures entering plateau phase and during regrowth after harvest. The rate of labeled precursor uptake and incorporation into DNA was measured by liquid-scintillation or gamma counting after labeling with ³H-TdR or ¹²⁵I-UdR. In addition to being different from exponentially growing cells, the cycle phase distributions in the two types of plateau-phase cultures were found to differ substantially from one another (Figure 1).

Noncycling cells in starved cultures are found to have accumulated primarily in G₁ phase, with the balance in G₂ phase. Very few cells (<2%) are found in S phase. In contrast, however, nearly half of the cells in fed cultures are found in S phase. This fraction was found to vary considerably in

	G ₁	S	G ₂	M
EXPONENTIALLY GROWING CELLS	4 ½ h 30%	7 h 55%	1 ½ h 10%	1 h 5%
STARVED PLATEAU-PHASE CELLS	> 500 h 70%	— < 1%	> 500 h 30%	— 0%
FED PLATEAU-PHASE CELLS	60 h 40%	70 h 40%	10 h 20%	1 h < 1%

DURATION OF CYCLE PHASE
PERCENTAGE OF CELLS IN EACH PHASE

FIGURE 1. Estimates of the Duration of Cell Cycle Phases and Approximate Distributions of Cells Throughout the Cell Cycle for Exponentially Growing, Starved and Fed Plateau-Phase Populations of CHO Cells.

response to the frequency and pattern of medium replacement. Upon harvest and reculturing, populations of both types of plateau-phase cultures demonstrate extremely coherent cyclic patterns of DNA synthesis. They retain this high degree of synchrony for more than three generations after the resumption of growth. We conclude that nutritionally deprived (starved) late plateau-phase cells can become stationary in both G₁ and G₂ phases, while density-inhibited cells that are fed periodically never actually stop proliferating. Rather, these fed cultures contain a very large and variable fraction of active, but slowly cycling cells. Regardless of their origins, starved cultures and fed ones are very different from one another in terms of composition, cell age distributions, and most other characteristics. Only in superficial appearance and various qualitative growth criteria are they similar.

A manuscript describing this work, entitled "Kinetic Differences Between Fed and Starved Chinese Hamster Ovary Cells," by J. M. Nelson, P. W. Todd, and N. F. Metting, has been prepared and submitted for publication. The paper also discusses the implications of our experimental observations relative to conclusions drawn from plateau-phase cell experiments by other investigators. Publication of this paper will represent a significant milestone in the investigation of plateau-phase kinetics. However, a number of other questions relative to interpreting and understanding the influence of cell kinetics on radiation repair phenomena remain unanswered. Consequently, further refinements in the understanding of the behavior of plateau-phase cell populations may be necessary.

KINETICS OF SUBLETHAL AND POTENTIALLY LETHAL DAMAGE REMOVAL BY SIMULTANEOUS REPAIR PROCESSES IN PLATEAU-PHASE MAMMALIAN CELLS

J. M. Nelson, N. F. Metting, W. C. Roesch and L. A. Braby

Interaction of radiation-induced damage resulting from both high- and low-LET irradiations, has been observed by several investigators (Ngo, Blakely and Tobias 1981; R. P. Bird et al. 1983). This interaction has been interpreted in terms of biophysical models that assume either 1) the accumulation and interaction of biochemical sublesions, or 2) the saturation of some damage-removal system. The increased survival with time between doses, observed in split-dose experiments, as well as the shape (shoulder region) of the survival curve in dose rate experiments, may be explained by either of these assumptions. Several of these models differ only at the molecular or biochemical level, e.g., the assumption about the nature of the interaction and the fate of the damage if it does not interact. Consequently, models assuming sublethal and potentially lethal lesions could not be distinguished from one another on the basis of the cell survival alone. However, many other aspects of these models can still be tested by comparing observed with predicted cellular response patterns. We have studied the kinetics of repair processes which remove both sublethal and potentially lethal damage following photon and electron irradiations in starved plateau-phase cultures of CHO cells. These split-dose, delayed-plating, and dose-rate experiments were done in an effort to clarify the relative roles in cell survival of damage

repair processes for both sublethal and potentially lethal damage.

Several split-dose experiments using two equal doses of either 1.5 MeV electrons or 250 kV X-rays, separated by intervals ranging from 1/2 min to 24 h, have now been analyzed. As seen in Figure 1, the electron data clearly demonstrate two distinct repair processes. One of these has a characteristic time (τ) of about 60 min, the other about 16 to 20 h. Sufficient data from split-dose photon experiments are not yet available to accurately determine the repair constants. However, values for τ have been determined from photon dose-rate survival data. These appear consistent with the electron split-dose data. This implies the existence of two distinct types of damage since two repair processes operating on one type of damage would show only a single, average repair rate.

Delayed-plating experiments using plateau-phase CHO cells irradiated with photons have

FIGURE 1. Split-Dose Survival Data from Starved Plateau-Phase CHO Cells Irradiated With Two Equal Doses of 1.5 MeV Electrons. Data are plotted such that data from cells having only a single exponential repair process would fall on a straight line. The maximum survival, S_m , is estimated by the product of the survivals for each individual dose fraction.

demonstrated a small, but significant amount of repair of potentially lethal damage, as may be seen in the lower curve in Figure 2. We have completed only a limited number of experiments with electrons, but the data available are consistent with that of the photon experiments. In both cases the repair rate observed for removal of potentially lethal damage is also on the order of 16 to 20 h, and appears to correspond to the longer process observed in split-dose experiments. As seen in the same figure, the amount of damage removed during the interval between irradiation and subculturing in delayed-plating experiments was found to be considerably less than that removed during protracted irradiations in dose-rate experiments. Simple repair depletion models predict a greater increase in survival (less residual damage) after a given amount of time for repair in delayed-plating experiments than during protracted exposures of the same length. In order for protracted exposures to yield greater survivals, some damage fixation process that is dependent on damage concentration must exist. Such concentration dependence can only result from the interaction between damage produced by different energy deposition events; we refer to this sort of damage as sublethal damage. From these experiments we have concluded that the starved plateau-phase CHO cells repair both sublethal damage, with a characteristic time of about 1 h, and potentially lethal damage, with a time on the order of 16 to 20 h.

FIGURE 2. Increase in Relative Survival with Time After Irradiation (Lower) and Immediately after Protracted Exposures (Upper), for the Same Cells Irradiated with 250 kV X-rays. Delayed-plating data are plotted as survival of cells subcultured at various times after irradiation relative to the survival of cells subcultured immediately following exposure. Survival after protracted exposure is plotted relative to that after the same dose given at a high dose rate and subcultured immediately.

REFERENCES

Bird, R. P., M. Zaider, H. H. Rossi, E. J. Hall, S. A. Marino and N. Rohrig. 1983. "The Sequential Irradiation of Mammalian Cells with X-rays and Charged Particles of High LET." *Radiat. Res.* 93:444-452.

Ngo, F. Q., E. A. Blakely and C. A. Tobias. 1981. "Sequential Exposures of Mammalian Cells to Low- and High-LET Radiations." *Radiat. Res.* 87:59-78.

DOSE RATE EVIDENCE OF DAMAGE ACCUMULATION IN STATIONARY-PHASE MAMMALIAN CELLS

N. F. Metting, W. C. Roesch, L. A. Braby, and J. M. Nelson

The Accumulation Model of radiation damage (Braby and Roesch 1978) allows for the

existence of both single-event and multiple-event killing. Dose-rate studies using plateau-phase CHO cells were reported last year (Metting et al. 1983). These results, analyzed according to the Accumulation Model, indicated that both types of damage were occurring in the cells in response to X-ray insult.

Additional dose-rate survival experiments were performed this year to reduce uncertainties in the determination of τ , the repair time for two-event damage. Figure 1 shows the survival data plotted in the traditional way, i.e., as survival versus dose. Much repair is evident.

Some authors say that this repair is the same as that observed in delayed-plating experiments. To determine the extent of delayed-plating repair in these cells, an additional series of delayed-plating experiments was performed. Plateau cell

FIGURE 1. Survival Versus Dose for Stationary-Phase CHO Cells Exposed to 250 kV X-rays at Five Dose Rates.

populations were treated with various doses at a high dose rate, and then incubated in spent medium for varied lengths of time before exponential growth was initiated. Figure 2 shows the amount of repair that occurred within 4 to 48 h of delay; clearly, it is not enough to account for all of the dose-rate effect.

Another possible mechanism that has been proposed to account for the higher survival at lower dose rates is that the initial radiation damage triggers an increase in repair capacity that enables the cell to more successfully repair subsequent damage. Another interpretation of the experimental evidence for this process might be that the initial dose eliminates the most sensitive cells in a heterogeneous population, leaving the more resistant cells to be damaged by the remainder of the dose. In such experiments, cell populations are subjected to a moderate dose of radiation, held for varying periods of time, and then irradiated again. Some researchers have seen an enhancement of survival to predosed populations of some cell lines, as manifested by a shallower slope on the subsequent survival curve. The largely

parallel curves of Figure 3 indicate the lack of a significant repair potentiation in the plateau-phase CHO cells.

Figure 4 shows the dose-rate data plotted as $(-\ln S/D^2)$ versus t . The heavy line indicates where these points would fall if only two-event damage were present, according to the Accumulation Model. It is possible to subtract the effect of single-event killing (C/D) from the experimentally obtained values of $-\ln S/D^2$, thereby generating the two-event damage curve seen in Figure 5. Analysis of this curve yields a probable value for τ of 59 min.

Braby and Roesch (1978) have previously shown that this type of response is not compatible with the many models which assume that damage progresses through successive steps until the cell sustains potentially lethal damage. Instead, these results demonstrate that damage accumulates, and that there is a corresponding increase in the probability of this damage becoming lethal. Several models developed recently (Curtis 1982) incorporate some form of interaction that is proportional to the dose squared. Our results indicate that

FIGURE 2. Survival of CHO Cells Exposed to 250 kV X-rays at 100 rad/min, and Then Assayed After Incubation of 4 to 48 h.

FIGURE 3. Survival of CHO Cells Given a First Dose of 400 rads at Various Periods Before a Second Dose of X-rays Was Administered.

FIGURE 4. The Survival Data from Figure 1 Replotted as $-\ln S/D^2$ Versus t , the Irradiation Period.

FIGURE 5. The Data of Figure 1 Plotted as $-\ln S/D^2 - C/D$ where C , a Parameter Related to the Probability of Producing Lethal Damage in a Single Event, Was Determined by Iterative Fitting. The resulting curve is consistent with the curve predicted by the Accumulation Model.

such an interaction must be of the accumulation type, at least in plateau-phase CHO cells.

REFERENCES

Braby, L. A. and W. C. Roesch. 1978. "Testing of Dose-Rate Models with Chlamydomonas reinhardi." Radiat. Res. 76:259-270.

Curtis, S. B. 1982. "Ideas on the Unification of Radiobiological Theories." In: Proceedings of the Eighth Symposium on Microdosimetry, ed. J. Booz and H. G. Ebert, pp. 527-536.

Metting, N. F., W. C. Roesch, J. M. Nelson, and L. A. Braby. 1983. "Dose-Rate Effects in Stationary-Phase Mammalian Cells: Testing the Accumulation Model." In Physical Sciences. Part 4 of PNL Annual Report for 1982 to the DOE Office of Energy Research, pp. 54-55. PNL-4100 PT4, Pacific Northwest Laboratory, Richland, Washington.

• Modeling Cellular Response to Genetic Damage

The role of cellular biochemical processes initiated by radiation or by chemical carcinogens on the production and repair of genetic damage is a key element in developing predictive models of cellular effects at low doses and dose rates. This program focuses on understanding the mechanisms by which chemical alterations in mammalian cell chromosomes produce toxic and mutagenic effects. Our experimental studies have concentrated on the rodent cell line CHO-K1 where replica plating techniques have proved useful in isolating mutants with altered repair capability. Characterization of these mutants has lead to investigations of the role of DNA precursor pools in the ability of cells to repair chromosome damage. Theoretical studies have focused on biochemical mechanisms for pool imbalance induced by radiation or chemical exposure and on the effect of this pool imbalance on other cellular processes. Our theoretical modeling effort is also extended to human cell lines through an active collaboration with Dr. R. H. Heflich at the National Center for Toxicology Research in Jefferson, Arkansas.

CONTROL OF DNA SYNTHESIS BY DEOXYNUCLEOSIDE TRIPHOSPHATES (dNTPs) IN PERMEABLE CHINESE HAMSTER OVARY CELLS

C. N. Newman and J. H. Miller

A previous report (Newman 1983) suggested an important role for deoxynucleoside triphosphate (dNTP) pools in effecting repair of DNA in Chinese hamster ovary cells (CHO-K1) that have been damaged by dimethylsulfate or UV radiation. This idea was surmised from studies of Mut 8-16, a carcinogen-resistant mutant of CHO-K1 whose only demonstrable biochemical defect is a dNTP imbalance. The mechanism by which altered dNTP concentrations affect biological responses to carcinogens is not clear; however, the work of Nicander and Reichard (1981) suggests that one such dNTP, deoxycytidine triphosphate (dCTP), may act at an allosteric site on the DNA-replicase complex to increase the affinity of the DNA synthesis system for all dNTP substrates. Thus, regulation of DNA synthesis by dNTP pools may be one mechanism that mediates the biological response of cells to carcinogens.

We have examined DNA synthesis in permeable CHO cells to ascertain the significance of an altered dNTP pool balance on replication, both in CHO-K1 and in Mut 8-16 cells (Newman and Miller 1983). In Figure 1 rates of replication in a standard reaction mixture containing all four dNTP substrates and permeable cells (here assigned a value of unity) are compared to rates obtained by singularly increasing the concentrations of each of the four dNTP substrates. No effect on the rate of synthesis was observed with up to a 22-fold increase in the concentration of deoxyadenosine triphosphate (dATP). Only a small (and equivalent) stimulation of synthesis was obtained in both cell lines when

deoxyguanosine triphosphate (dGTP) was increased by the same magnitude. In contrast, a dramatic effect on the replication rate resulted when excess deoxythymidine triphosphate (dTTP) or excess dCTP was added to the standard mixture. A 20-fold excess in dTTP inhibited synthesis to ~5% of normal in both cell lines, while a 23-fold excess in dCTP enhanced synthesis up to twofold. The effect of dCTP was most dramatic in CHO-K1 cells; little stimulation of replicative activity in Mut 8-16 was observed at or below dCTP concentrations of 1 mM (10-fold excess) compared to a 1.4-fold increase in parent cells. Judging from the absence of response or small response of both cell lines to excess dATP and dGTP, respectively, substrate concentrations were not otherwise rate-limiting.

Replication in Chinese hamster ovary cells thus appears to be stimulated by excess dCTP. This finding agrees with the hypothesis of Nicander and Reichard (1981). A new finding is that replication is inhibited by excess dTTP. Thus, a mechanism depicting the regulation of DNA synthesis (and possibly the biological response of cells) via allosteric control of DNA synthesis by dCTP and/or dTTP is now clearer. The reason for the greater resistance of the replicase complex in Mut 8-16 to regulation by dCTP is not yet apparent but is probably related to its increased resistance to chemical carcinogens and to ultraviolet radiation (Newman 1982).

REFERENCES

- Newman, C. N. 1982. "Characterization of a UV-Resistant Mutant of CHO-K1 Cells with Normal Repair Activity." *Mut. Res.* 96:99-108.

FIGURE 1. Effects of dNTP Substrate Concentrations on Rate of DNA Synthesis in Permeable Cells. Rates of DNA synthesis were determined in the standard reaction mixture (relative rate = 1.0) or in the standard mixture containing excess dCTP (●,○), dGTP (▼,▽), dATP (■,□) or dTTP (▲,△) at the indicated concentrations. [^3H]dTTP was maintained at a constant specific activity (3.4×10^6 dpm/nmol). Open symbols are permeable CHO-K1 cells; closed symbols are permeable Mut 8-16 cells.

Newman, C. N. 1983. "Pool Sizes in an Ultraviolet (UV)-Radiation-Resistant Mutant of Chinese Hamster Ovary Cells." In Physical Sciences, Part 4 of Pacific Northwest Laboratory Annual Report for 1982 to the DOE Office of Energy Research. PNL-4600 PT4, Pacific Northwest Laboratory, Richland, Washington.

Newman, C. N. and J. H. Miller. 1983. "Mutagen-Induced Changes in Cellular Deoxycytidine Triphosphate and Thymidine Triphosphate in Chinese Hamster Ovary Cells." Biochem. Biophys. Res. Commun. 114:34-40.

Nicander, B. and P. Reichard. 1981. "Aphidicolin Sensitivity of Variation 3T6 Cells Selected for Changes in Ribonucleotide Reductase." Biochem. Biophys. Res. Commun. 103:148-155.

CARCINOGEN-INDUCED DEOXYNUCLEOSIDE TRIPHOSPHATE POOL IMBALANCES: EFFECT ON DNA SYNTHESIS IN GROWING CHINESE HAMSTER OVARY CELLS

C. N. Newman and J. H. Miller

In a presentation at the Symposium on Genetic Consequences of Nucleotide Pool Imbalance (May 9-11, 1983), we proposed that radiation or chemical insult, by inducing transient inhibition of DNA synthesis (Edenberg 1983), predisposes cells to secondary DNA lesions, possibly via a type II topoisomerase acting on partially replicated DNA (in accordance with the model of Painter [1980]). We suggested that the initial inhibition leading to secondary damage may occur in response to a carcinogen-induced deoxynucleoside triphosphate (dNTP) pool imbalance (Figure 1). This possibility is further explored by examining at various times after exposure both the concentrations of dNTP pools and the rates of DNA synthesis in UV-treated cells.

There is, indeed, a marked dNTP pool imbalance beginning 10 min after irradiation of CHO-K1 cells (see Figures 2 and 3). The most dramatic effects are in cellular dCTP, which decreases (Figure 2), and in cellular dTTP, which increases (Figure 3). These effects are observed even at a UV-fluence (3Jm^{-2}) that kills less than 5% of the cells (Newman 1982). These changes in dCTP and dTTP are initially quite large, on the order of three- to tenfold; recovery to normal levels takes over 5 h for dTTP and 12 h for dCTP. For comparison, levels of dATP are also illustrated (Figure 2). No change in the concentration of this DNA precursor is observed for 1-2 h; thereafter, only a gradual decrease to 30% to 50% of normal occurs. The level of dATP recovers to nearly normal 8 h after irradiation. No significant variation in cellular dGTP is observed during the same period (not shown).

The rapid increase in dTTP and/or decrease in dCTP would be expected to favor inhibition of DNA synthesis, as discussed in the previous section and earlier (Newman and Miller 1983). To further examine this possibility, the rate of DNA synthesis in untreated (control) cells and in cells 8 min or 8 h following exposure to 3Jm^{-2} of UV radiation was measured.

FIGURE 1. Two Hours After UV- or Dimethylsulfate-Induced Changes in Relative Concentrations of dTTP and dCTP. Cell monolayers were exposed to UV, then incubated in fresh growth medium for 2 h, or cells were grown in the presence of dimethylsulfate for 2 h. The concentrations of dNTP pools in extracts from treated cells were compared to that from untreated control cultures. Survival values after UV or dimethylsulfate exposure were obtained earlier (Newman 1982). Relative dTTP: after UV ($\square$, $\square$) or after dimethylsulfate (∇ , ∇); relative dCTP: after UV ($\bullet$, $\bullet$), or after dimethylsulfate ($\blacktriangle$, $\blacktriangle$). Closed symbols are CHO-K1; open symbols are Mut 8-16.

Figure 4 illustrates that pulse-incorporation of ^3H -thymidine into DNA at 8 min after exposure, when dCTP and dTTP levels are lowest and highest, respectively, (Figures 2 and 3) is reduced to ~25% of that observed in the control. At 8 h after exposure, when the dTTP level is normal and the dCTP level is partially recovered, the rate of replication is greater, ~75% of normal. The rate of DNA synthesis at 8 min is lower than would be expected if only UV-induced lesions in DNA were blocking ongoing replication forks (Edenberg 1983). This is illustrated by comparison with Chinese hamster V-79 cells.

FIGURE 2. Relative Levels of dCTP and dATP Following Exposure to 3 J/m^2 (dashed lines) or 10 J/m^2 (solid lines) of UV. There were 18.77 pmol dCTP/ μg DNA and 11.1 pmol dATP/ μg DNA in unirradiated control cells.

These cells have genomes, biochemical repair pathways and rates of replicon fork movement comparable to those of CHO-K1 cells (Kapp and Painter 1983). However, carcinogen-induced dNTP imbalances in V-79 cells, unlike results with CHO cells, do not occur for at least 2 h following exposure (Das, Benditt and Loeb 1983). It is, therefore, significant that in a similar measurement the DNA replication rate of V-79 cells at 10 min after irradiation (even after exposure to 5 J/m^2 of UV), was only slightly reduced (80% to 90%) in comparison to untreated cells (Doniger 1978; Dahle, Griffiths and Carpenter 1980).

We believe these findings represent a convincing argument to support a direct role for dNTP pools in regulating DNA synthesis in response to damaging agents. Coupled with our analysis of a pool-altered, carcinogen-resistant mutant of CHO-K1, Mut 8-16, which we also presented at the Symposium on Genetic Consequences of Nucleotide Pool Imbalance, a relationship between the extent of carcinogen-induced inhibition of DNA replication (mediated by dCTP and/or dTTP) and the biological consequence of this inhibition must be strongly considered. Finally, while the series of events resulting in a dNTP pool imbalance following an insult is not yet clear, the possibility of a non-DNA target intermediate is being investigated (see next section).

FIGURE 3. Relative Levels of dTTP Following Exposure to 3 J/m^2 , 10 J/m^2 or 20 J/m^2 of UV. Unirradiated control cultures had $2.12 \text{ pmol dTTP}/\mu\text{g DNA}$.

REFERENCES

- Dahle, D., T. Griffiths and J. Carpenter. 1980. "Inhibition and Recovery of DNA Synthesis in UV-Irradiated Chinese Hamster V-79 Cells." *Photochem. Photobiol.* 32:157-165.
- Das, S., E. Benditt and L. Loeb. 1983. "Rapid Changes in Deoxynucleoside Triphosphate Pools in Mammalian Cells Treated with Mutagens." *Biochem. Biophys. Res. Commun.* 114:458-464.
- Doniger, J. 1978. "DNA Replication in Ultra-violet Light Irradiated Chinese Hamster Cells: The Nature of Replication Inhibition and Post-Replication Repair." *J. Mol. Biol.* 120:433-446.
- Edenberg, H. 1983. "Do Pyrimidine Dimers Block Replication Forks in Mammalian Cell DNA? Analytical Look at Evidence from DNA Fiber Autoradiography." *Comments Mol. Cell Biophys.* 1:383-397.
- Kapp, L. and R. Painter. 1983. "DNA Replication Fork Movement Rates in Mammalian Cells." *Int'l. Rev. Cytol.* 80:1-25.

FIGURE 4. Pulse-incorporation of $[^3\text{H}]$ Thymidine into DNA Following Exposure to 3 J/m^2 of UV: a) (●, dashed line) unirradiated control; (○, solid line) 8 h post-exposure; b) (●, dashed line) unirradiated control, same as "a"; (□, solid line) 8 min post-exposure; (○, solid line) 8 min post-exposure, "corrected" for transient variation in dTTP (Figure 3) which ranged from 3.07-fold (1", 2", 5" pulse-length) to 2.3-fold (15" pulse-length).

which, as noted earlier, is converted to dTTP. We also observe that deaminase activity in CHO cells is not blocked by low doses of UV. Hence, a possible mechanism for the rapid increase of dTTP and simultaneous decrease in dCTP in CHO cells (see previous section, Figures 2 and 3) induced by low doses of UV is the loss of dCDP produced from the CDP substrate. The presence of deaminase activity would then favor an equilibrium shift converting the residual dCTP to dTTP. This would also explain why the rapid increase in dTTP and the decrease in dCTP are not observed in V-79 (Das, Benditt and Loeb 1983) since the deaminase pathway is not active in these cells (results not shown). To ascertain why dCDP is reduced we have investigated whether UV inhibits CDP reductase. However, preliminary results show no diminution in this activity resulting from radiation. Hence, our tentative conclusion is that the rapid UV-induced dCTP/dTTP pool imbalance in CHO must result from limitation on the substrate for reductase, CDP.

Experiments with drugs that block DNA replication (Nicander and Reichard 1981, McMillan and Fox 1981) suggest that dCTP is a constitutive component of a multi-enzyme-DNA complex required for chain elongation. If binding of dCTP to the DNA polymerase regulates its affinity for all dNTP substrates, then a decrease of dCTP would reduce the number of replicons that function at a given time rather than slow down the rate of synthesis at operational forks by random competition for substrates. This is consistent with the results of DNA fiber autoradiography following low doses of UV (Doniger 1978).

We are currently investigating this mechanism to explain the correlation between pool imbalance and inhibition of DNA synthesis that we observe in UV-irradiated CHO cells. We speculate that regulation of DNA synthesis by dCTP might be a mechanism to protect cells from mutation due to miscoding that is more probable when DNA synthesis continues during a dNTP pool imbalance.

REFERENCES

- Ashman, C. R. and R. L. Davidson. 1981. "Bromodeoxyuridine Mutagenesis in Mammalian Cells Is Related to Deoxyribonucleotide Pool Imbalance." Molec. Cell. Biol. 1:254-260.
- Das, S. K., E. P. Benditt and L. A. Loeb. 1983. "Rapid Changes in Deoxynucleoside Triphosphate Pools in Mammalian Cells Treated with Mutagens." Biochem. Biophys. Res. Commun. 114:458-464.
- Doniger, J. 1978. "DNA Replication in Ultraviolet Light Irradiated Chinese Hamster Cells: The Nature of Replicon Inhibition and Post-Replication Repair." J. Mol. Biol. 120:433-446.
- McMillan, S. and M. Fox. 1981. "Effects of Metabolic Inhibitors on Cell Lethality and Mutation Induction in Chinese Hamster Cells. 1. Inhibition of de Novo Purine Synthesis and a Comparison with the Effects of Caffeine." Chem.-Biol. Interactions 36:71-88.
- Meuth, M. 1981. "Role of Deoxynucleoside Triphosphate Pools in the Cytotoxic and Mutagenic Effects of DNA Alkylating Agents." Somat. Cell. Genet. 7:89-102.
- Nicander, B. and P. Reichard. 1981. "Aphidicolin Sensitivity of Variant 3T6 Cells Selected for Changes in Ribonucleotide Reductase." Biochem. Biophys. Res. Commun. 103:148-155.
- Robert de Saint Vincent, B., M. Dechamps and G. Buttin. 1980. "The Modulation of the Thymidine Triphosphate Pool of Chinese Hamster Cells by dCMP Deaminase and UDP Reductase." J. Biol. Chem. 255:162-167.
- THE EFFECT OF BIPHASIC REPAIR KINETICS ON THE SURVIVAL OF HUMAN CELLS EXPOSED TO RADIATION AND CHEMICAL CARCINOGENS
- J. H. Miller and R. H. Heflich*
- Biphasic kinetics are frequently observed when repair in human cells is measured by adduct removal (Kaneko and Cerutti 1980), by removal of sites that are susceptible to UV endonuclease (Zelle and Lohman 1979) and by unscheduled DNA synthesis (Zelle, Berends and Lohman 1980). Our previous model for the influence of excision repair on survival (Miller and Heflich 1982) assumed a single, first-order repair process. Although this model was successful in accounting for the slope of the exponential part of the survival dose-response, it could not explain shouldered survival curves. We are currently investigating the hypothesis that these shoulders result from biphasic repair kinetics.
- Kaneko and Cerutti (1980) attribute the repair kinetics that they observe to a single repair process operating in different chemical environments due to chromosome structure. This can be treated as a special case of a two component, first-order model in

* National Center for Toxicological Research, Jefferson, Arkansas.

which the fraction of damage remaining at time t after a dose D is

$$f(t,D) = f_1(D)e^{-k_1 t} + [1 - f_1(D)]e^{-k_2 t} \quad (1)$$

where f_1 is the fraction of type 1 damage that results from the treatment. The survival, S^+ , of a repair proficient cell is then related to the survival, S^- , of a repair deficient cell by the equation

$$\log[S^+(\tau,D)] = \log[S^-(D)]f(\tau,D) \quad (2)$$

where τ is the average time available to repair a lesion before it is fixed by other biochemical processes in the cell, such as DNA replication.

To apply this type of model requires accurate, dose-dependent, kinetic repair data to determine the rate constants k_1 and k_2 and the function $f_1(D)$. Data meeting all these requirements are not currently available. Hence, in this report we can only speculate on possible implications of the model that can be tested as more data become available. The most promising test of the model appears to be the difference in survival of normal human fibroblasts and fibroblasts from xeroderma pigmentosum XP patients in complementation group F (Arase et al. 1979). Normal human fibroblasts (NF) have a rapid component in their repair of damage induced by UV light (Zelle, Berends and Lohman 1980). The fraction of damage repaired by this component varies from about 40% at a dose of 2.9J/m² to an undetectable level at 23.2J/m². This approximately corresponds to the shoulder region of the UV dose-response for NF. XP

cells from complementation group F do not exhibit the rapid repair component and do not have a shoulder on their UV dose-response. The initial test of the model will be to predict the shoulder on the UV dose-response of NF from measured characteristics of the fast repair component.

REFERENCES

- Arase, S., T. Kozuka, K. Tanaka, M. Ikenaga and H. Takebe. 1979. "A Sixth Complementation Group in Xeroderma Pigmentosum." Mut. Res. 59:143-146.
- Kaneko, A. and P. A. Cerutti. 1980. "Excision of N-Acetoxy-2-acetylaminofluorene-induced DNA Adducts from Chromatin Fractions of Human Fibroblasts." Cancer Res. 40:4313-4319.
- Miller, J. H. and R. H. Heflich. 1982. "A Model for the Effect of Excision Repair on the Survival of Human Cells Exposed to Chemical Carcinogens." Chem.-Biol. Interactions 39:45-55.
- Zelle, B. and P. H. M. Lohman. 1979. "Repair of UV-endonuclease-susceptible Sites in the 7 Complementation Groups of Xeroderma Pigmentosum A through G." Mut. Res. 62:363-368.
- Zelle, B., F. Berends and P. H. M. Lohman. 1980. "Repair of Damage by Ultraviolet Radiation in Xeroderma Pigmentosum Cell Strains of Complementation Groups E and F." Mut. Res. 73:157-169.

• Internal Microdosimetry

The purpose of this study is to develop practical methods for calculating microdosimetric distributions for plutonium or other alpha-emitting elements that are deposited internally, especially as particulates, in soft tissue and lung tissue. This study will aid the correlation and extrapolation of radiation effects measured at different levels of exposure, different distributions in dose and in different species. Computational methods are developed and tested in the Radiological Physics Section. Concurrently, the Dosimetry Technology Section develops cell and tissue models in which those methods are applied.

LUNG MICRODOSIMETRY CALCULATIONS

W. C. Roesch

Last year work was started on calculating the probability of finding an alpha-particle-emitting particulate as a function of distance from a sensitive site by means of a formal relation between certain Fourier transforms,

$$\frac{H(1+G)}{1-GF}$$

where H is the transform of the probability density for the distance between the site and the next alveolar wall; G that for the distance across an alveolus; and F that for the thickness of an alveolar wall. The difficulty in handling this expression was a singularity at the value zero for the transform variable. The difficulty was circumvented by using a modified version of the expression,

$$\frac{H(1+G)(1-[GF]^n)}{1-GF}$$

where n is a number of alveolar walls plus alveoli traversed. This expression gives the density only out to this number n of alveoli. But beyond that, the density is a constant that can be derived from the original expression, and the constant can be smoothly attached to the result of the calculation from the last expression to give the required probability.

DOSE DISTRIBUTION EFFECTS AT THE CELLULAR LEVEL

D. R. Fisher and M. E. Frazier

Experiments are in progress to demonstrate the biological effects on cells from varying alpha particle dose distributions. The purpose of this work is to demonstrate the applicability of computer codes for internal microdosimetry.

Microdosimetric theory suggests that the biological effects of irradiation by alpha

particles will vary with changing dose distribution patterns, even though the absorbed dose is held constant. We wished to test this prediction of the theory using 1) a uniformly distributed alpha particle emitter, and 2) "hot particles"--alpha particle emitters in particulate form.

Cultured Chinese hamster ovary (CHO-K1 BH₄) cells were exposed in vitro to inert, insoluble ceramic microspheres of zirconium dioxide labeled with ²³⁹Pu.* The average exit energy of the 5.15 MeV alpha particle was calculated to be 4.3 MeV. Exposure times varied from four to seven hours to achieve the desired dose level.

The CHO cells and ²³⁹PuZrO₂ microspheres were mixed forming a planar geometry on the bottom surface of a plastic culture dish measuring 25 cm². The cells and microspheres were separated by centrifugation at the end of the exposure period.

Cells were exposed to hot particles, uniformly distributed alpha particle radiation, and ⁶⁰Co gamma radiation (Tables 1 and 2). A uniform distribution of alpha-emitting ²³⁹Pu was achieved by gently rocking one group of culture dishes during the exposure period; the rocking motion caused the microspheres to roll about on the bottom of the dishes while the CHO cells remained attached. Approximately 10⁶ cells per dish were exposed.

Biological effects monitored in this study include cell survival, mutation rates and primary DNA damage. Preliminary results for cell survival and mutation frequencies in two experiments are reported here. Initial survival was determined by a clonal growth assay. The mutation assay involved scoring for specific mutations at the HGPRT locus.

Absorbed doses were calculated by determining the mean specific energy imparted to CHO cell

* Generously provided for this work by Dr. L. M. Holland of Los Alamos National Laboratory, Los Alamos, New Mexico.

TABLE 1. Cell Survival and Mutation Frequencies (a) (per 10⁶ surviving cells) for CHO Cells Exposed to 0.07 pCi Plutonium Microspheres or Gamma Radiation

Group	Condition	Dose (rad)	S _r (%)	S _a (%)	Mutation Frequency/10 ⁶
A	0.07 pCi ²³⁹ Pu	70	67	41 ± 0.9	6.4 ± 1.6
B	Uniform ²³⁹ Pu	70	74	45 ± 2.2	23.8 ± 8.0
E	⁶⁰ Co Gamma	69.5	95	58 ± 2.0	12.3 ± 2.2
F	Sham Exposed	0	100	61 ± 3.8	4.5 ± 1.2

(a) Mean ± Standard Error.

S_r = Relative Survival

S_a = Absolute Survival

TABLE 2. Cell Survival and Mutation Frequencies (a) (per 10⁶ surviving cells) for CHO Cells Exposed to 1.87 pCi Plutonium Microspheres

Group	Condition	Dose (rad)	S _r (%)	S _a (%)	Mutation Frequency/10 ⁶
C	1.87 pCi ²³⁹ Pu	70	94	57 ± 2.6	7.3 ± 0.9
D	Uniform ²³⁹ Pu	70	103	63 ± 5.0	18.4 ± 3.2
G	Controls	0	100	—	1.2 ± 0.3

(a) Mean ± Standard Error.

S_r = Relative Survival

S_a = Absolute Survival

nuclei for each exposure condition. The mathematical methods of Roesch (1977) for internal microdosimetry were employed. Cell nuclei were assumed to be spherical (diam. = 9.0 micrometers).

The numbers and distributions of microspheres per dish were counted by photomicrographs. The emitted radiation was also measured by a 3-in. NaI(Tl) crystal detector and a multi-channel analyzer.

The survival and mutation frequencies for CHO cells that were given one of seven different exposure regimens are shown in Table 1 (for

the 0.7 pCi microspheres) and Table 2 (for the 1.87 pCi microspheres).

Our results confirm the importance of dose distribution in the analysis of biological effects from internal emitters. Different levels of cytotoxicity were observed for alpha radiation from particulate sources compared to the more uniformly distributed activity, even though the absorbed (mean) doses were the same.

The order of increasing mutation frequency for equivalent total absorbed dose (70 rad) was found to be:

Stationary microspheres (alpha radiation) < ⁶⁰Co (gamma radiation) < Uniformly distributed microspheres (alpha radiation)

This was true regardless of the microspheres' specific activity. With mutation frequency as an endpoint, we found that the biological effectiveness of "equivalent doses" of alpha radiation can vary from <1 to ~10 (relative to gamma radiation) with the only variable factor being the physical distribution of the dose.

When cell survival was the endpoint, cell killing was slightly greater in the presence of stationary microspheres than in cultures exposed to the same numbers of mixed (uniformly distributed) microspheres. In addition, cell death was greater in cultures exposed to microspheres with the lowest specific activity (but the highest number of microspheres) regardless of particle distribution. Again, with cell survival as the biological endpoint, the relative biological effectiveness of alpha radiation varied from >1 to ~7, depending on dose distribution.

These dose levels were sufficient to assure that a large portion of the surviving cells received one or more alpha particle interactions. These data support the concept that multiple hits are required to kill a cell.

Assuming that mutation frequency is an indicator of the potential for radiation-induced carcinogenesis, these results agree with animal studies that suggest the carcinogenic effect of hot particles is considerably less than the effect of uniformly distributed alpha activity. Finally, the data clearly show that cellular response to radiation is not simply a function of "average" dose. Indeed, dose distribution at the cellular level is of utmost importance. Further experiments are necessary to quantify the relative biological effectiveness of alpha particles and to more fully define the significance of various dose distribution geometries.

REFERENCE

Roesch, W. C. 1977. "Microdosimetry of Internal Sources." *Radiat. Res.* 70:494-510.

LUNG DOSE CALCULATIONS FOR BEAGLE DOGS EXPOSED TO $^{239}\text{PuO}_2$

D. R. Fisher, W. C. Cannon, R. T. Hadley, and J. F. Park

The objectives (Fisher, Cannon and Blanton 1983) of this work are: 1) development of capabilities for calculating the microdosimetry of alpha-particle emitters in the

lung, and 2) correlation of the microdosimetry with long-term biological effects.

During the past year, calculations were begun on the microdosimetry for each of about 120 beagle dogs exposed at this laboratory to plutonium dioxide. The surviving dogs are being followed for life-span radiation effects (Park et al. 1983).

A computer method for internal microdosimetry (Roesch 1977) was revised and combined with a statistical model of the microanatomical structure of the dog lung (Fisher, Hadley and Roesch 1982) to form a computer code for lung microdosimetry. The complexity of the calculations performed by this code is not fully appreciated by most observers. It requires detailed information concerning the distribution, concentration, specific activity, and number of radioactive particulates deposited in the lung. It takes into account the residence time for particulates in the lung over the life-span of the dog, and with considerable computing, calculates a probability distribution of "doses" received by cells in the lung. The mean specific energy of the probability distribution is equivalent to the cumulative absorbed dose. The code also provides the probability that cells or other biological targets in the lung are irradiated or not during a specified exposure period.

The end-product of a microdosimetry calculation is a probability density in specific energy (a distribution of doses to individual cells or cell nuclei). Microdosimetry calculations show that the actual doses to individual cell nuclei of the lung are highly variable, and range from 0-20,000 rad, depending upon the proximity of the cell to nearby plutonium particulates.

We are in the process of calculating probability densities for each dog lung in the current $^{239}\text{PuO}_2$ inhalation study at this laboratory, taking into account the characteristics of the inhaled aerosol and individual plutonium retention parameters. The results for each dog will then be compared. An example comparison for seven dogs is shown in Figure 1. It illustrates the specific energy distributions for seven different cases where the average doses were 25, 80, 150, 500, 1200, 2500, and 6000 rad, respectively.

It is of interest to relate the microdosimetry of plutonium in the beagle dog lung to long-term radiobiological effects. Lung tumors predominate in dogs receiving 500-2500 rad to the lung from inhaled $^{239}\text{PuO}_2$.

FIGURE 1. A Comparison of Specific Energy Distributions for Seven Sample Exposures. Cumulative absorbed doses range from 25 to 6000 rad.

Early death due to radiation pneumonitis predominates at doses above 4000 rad. The effects of inhaled plutonium appear to be non-specific at doses of less than about 300 rad (refer to Figure 1). Further work will be required to understand how the information provided by microdosimetry can be used to interpret the dose-response relationships and predict biological effects in the lung.

REFERENCES

- Fisher, D. R., W. C. Cannon and E. F. Blanton. 1983. "Lung Dose Calculations for Beagle Dogs Exposed to $^{239}\text{PuO}_2$ --A Progress Report." In Physical Sciences. Part 4 of Pacific Northwest Laboratory Annual Report for 1982 to the DOE Office of Energy Research, pp. 67-69. PNL-4600 PT4, Pacific Northwest Laboratory, Richland, Washington.
- Fisher, D. R., R. T. Hadley and W. C. Roesch. 1982. "Statistical Modeling of Beagle Dog Lung for Microdosimetry." In Physical Sciences. Part 4 of Pacific Northwest Laboratory Annual Report for 1981 to the DOE Office of Energy Research, pp. 57-59. PNL-4100 PT4, Pacific Northwest Laboratory, Richland, Washington.
- Park, J. F., et al. 1983. "Inhaled Plutonium Oxide in Dogs." In Pacific Northwest Laboratory Annual Report for 1982 to the DOE Office of Energy Research. PNL-4600 PT1, Pacific Northwest Laboratory, Richland, Washington.
- Roesch, W. C. 1977. "Microdosimetry of Internal Sources." Radiat. Res. 70:494-510.

Publications
and
Presentations

PUBLICATIONS

- DuBois, R. D., L. H. Toburen and M. E. Rudd. 1983. "Multiple Ionization of Rare Gases by H^+ and He^+ Impact." Accepted for publication in Physical Review. (PNL-SA-111439)
- Bushaw, B. A. 1983. "Kinetic Analysis of Laser Induced Phosphorescence in Uranyl Phosphate for Improved Analytical Measurements." In: Proc. of the 26th ORNL-DOE Conference on Analytical Chemistry in Energy Technology (in press). Elsevier, Amsterdam, The Netherlands.
- Chess, E. K., D. D. Mahlum, R. B. Lucke, W. C. Weimer, B. W. Wilson and C. W. Wright. 1983. "Initiation-Promotion Studies with Fractionated Coal Liquids." In: Abstracts, Third International Congress on Toxicology (in press).
- Chess, E. K., D. W. Later, B. W. Wilson and W. R. Harris. 1983. "MS Detection and Characterization of Novel Nitro-PAH in Mutagenic Fly Ash Extract." In: Proceedings, 31st Annual Conference on Mass Spectrometry and Allied Topics, American Society for Mass Spectrometry (in press).
- Fisher, D. R. 1983. Concepts of Dose to Soft Tissue at the Cellular Level. PNL-SA-11419, Pacific Northwest Laboratory, Richland, Washington.
- Fisher, D. R., ed. 1983. Current Concepts in Lung Dosimetry. CONF-820492--Pt. 1. Technical Information Center, U.S. Department of Energy, Oak Ridge, Tennessee.
- Fisher, D. R., ed. 1983. "In Search of the Relevant Lung Dose." In: Current Concepts in Lung Dosimetry, pp. 29-36. CONF-820492--Pt. 1. Technical Information Center, U.S. Department of Energy, Oak Ridge, Tennessee.
- Fruchter, J. S., C. W. Wilkerson, D. S. Sklarew, K. B. Olsen and J. M. Ondov. 1983. "Potential Air Emissions from Oil Shale Retorting." In: Oil Shale: The Environmental Challenges III, ed. K. K. Peterson.
- Gray, R. H., D. D. Mahlum, J. A. Strand and W. C. Weimer. 1982. "Summary of Health and Environmental Research Relative to Direct Coal Liquefaction." In: Proceedings, Fifth ORNL Life Sciences Symposium, Synthetic Fossil Fuel Technologies: Results of Health and Environmental Studies. Ann Arbor Science Publishers, Woburn, Massachusetts (in press).
- Harris, W. R., E. K. Chess, D. Okamoto, J. F. Remsen and D. W. Later. 1983. "Contribution of Mitropyrene to the Mutagenic Activity of Coal Fly Ash." Environ. Mutagen. (in press).
- Jacobson, B. S. and L. A. Braby. 1983. "Effects of Varying LET on Sublethal Damage Repair in *Chlamydomonas*." Rad. Res. 94:556.
- Later, D. W. and M. L. Lee. 1983. "Analytical Methods for the Chemical Characterization of Polycyclic Aromatic Compounds in Coal-Derived Synfuels." In: Advanced Techniques in Synthetic Fuels Analysis, eds. C. W. Wright, W. C. Weimer and W. D. Felix, pp. 44-73.
- Later, D. W., M. L. Lee, R. A. Pelroy and B. W. Wilson. 1983. "Mutagenicity of Polycyclic Aromatic Compound Chemical Class Fractions from a Coal Liquid." Mutat. Res. (in press).
- Later, D. W., R. A. Pelroy, D. L. Stewart, T. McFall, G. M. Booth, M. L. Lee, M. Tedjamulia and R. N. Castle. 1983. "Microbial Mutagenicity of Isomeric Two-, Three-, and Four-Ring Amino Polycyclic Aromatic Hydrocarbons." Environ. Mutat. (in press).
- Later, D. W. and B. W. Wright. 1983. "Capillary Column Gas Chromatographic Separation of Amino Polycyclic Aromatic Hydrocarbon Isomers." J. Chromatogr. (in press).
- Later, D. W., R. A. Pelroy, D. D. Mahlum, C. W. Wright, M. L. Lee, W. C. Weimer and B. W. Wilson. 1983. "Identification and Comparative Genotoxicity of Polycyclic Aromatic Hydrocarbons and Related Nitrogen-Containing Heteroatomic Species in Products from Coal Liquefaction Processes." In: Polynuclear Aromatic Hydrocarbons: Formation, Metabolism and Measurement, eds. M. Cooke and A. J. Dennis, pp. 771-783. Battelle Press, Columbus, Ohio.
- Later, D. W., C. W. Wright, B. W. Wright, R. B. Lucke and W. C. Weimer. 1983. "Applied Capillary Column Gas Chromatography for the Analysis of Biologically Active Polycyclic Aromatic Compounds in Coal Liquefaction Process Materials." In: Proceedings, 2nd International Symposium on Capillary Chromatography (in press).
- Later, D. W. 1983. "Analytical and Chromatographic Methods for the Determination of Cyano Polycyclic Aromatic Hydrocarbons in Coal-Derived Materials." In: Proceedings, Eighth Int. Symp. on Polynuclear Aromatic Hydrocarbons (in press). Battelle Press, Columbus, Ohio.

Later, D. W. and B. W. Wilson. 1983. "Process Related Aspects of the Toxicology of Coal-Derived Materials." In: Abstracts, Third Congress on Toxicology (in press), Int. Union of Toxicology.

Later, D. W., C. W. Wright and B. W. Wilson. 1983. "The Analytical Chemistry of Products from Process Strategies Designed to Reduce the Biological Activity of Direct Coal Liquefaction Materials." In: Proceedings, Division of Fuel Chemistry, American Chemical Society Meeting (in press).

Later, D. W. and B. W. Wright. 1983. "Capillary Gas Chromatographic Methods for the Selective Separation of Biologically Active Amino Polycyclic Aromatic Hydrocarbon Isomers in Coal-Derived Material." In: Abstracts, International Symposium on Advances in Chromatography (in press).

Mahlum, D. D. and B. W. Wilson. 1983. "Components Responsible for Skin Tumor Initiating Activity in Coal Liquids." The Toxicologist 3:49.

Manson, S. T., R. D. DuBois and L. H. Toburen. 1983. "Multiple Ionization Mechanisms in Fast Proton Impact on Neon." Accepted for publication in Physical Review Letters.

Metting, N. F., J. M. Nelson, W. C. Roesch and L. A. Braby. 1983. "Low Dose-Rate Effects in Stationary Phase Mammalian Cells." Rad. Res. 94:628-629.

Miller, J. H. and L. H. Toburen. 1983. "Differential Cross Sections for Ionization of Helium, Neon, and Argon by High-Velocity Ions." Phys. Rev. A27:1337-1344.

Miller, J. H. and W. E. Wilson. 1983. "Modeling Early Events in the Radiation Chemistry on Dilute Aqueous Solutions." In: Proceedings of the Workshop on the Interface Between Radiation Chemistry and Radiation Physics, ANL-82-88, pp. 73-81.

Miller, J. H. and W. E. Wilson. 1983. "Monte Carlo Approach to Track Structure in Diffusion Kinetics: Pulse Radiolysis of Water with 3 MeV Protons." Rad. Res. 94:555.

Nelson, J. M. and N. F. Metting. 1983. "Plateau Phase Growth Kinetics: Effects on Radiation Damage Repair." Rad. Res. 94:623-624.

Newman, C. N. 1983. "The Effects of Cell Culture Density on Cell Inactivation by Benzo(a)pyrene-4,5-oxide." Mutation Research 120:61-67.

Newman, C. N. and J. H. Miller. 1983. "Mutagen Induced Changes in Cellular Deoxycytidine Triphosphate and Thymidine Triphosphate in Chinese Hamster Ovary Cells." Biochemical and Biophysical Research Communications 114:34-40.

Newman, C. N. and J. H. Miller. 1983. "Response to CHO Cell DNA Polymerase Alpha to dCTP and dTTP Pool Imbalance: Relation to DNA Synthesis Inhibition, Survival and Mutation." In: Proceedings of the Symposium on Genetic Consequences of Nucleotide Pool Imbalance.

Newman, C. N. 1983. "Repair of Ultraviolet Light or Chemical Alkylation-Induced Damage May Be Affected by Deoxynucleoside Triphosphate Pool Imbalance." Rad. Res. 94:662.

Olsen, K. B., D. R. Kalkwarf and C. Veverka, Jr. 1983. "Analysis and Collection of PAHs in the Flue Gas of Energy Conversion Facilities." In: Proceedings of the 8th International PAH Conference (in press).

Pelroy, R. A., D. D. Mahlum, M. E. Frazier, R. A. Renne, D. L. Stewart and E. K. Chess. 1982. "Comparison of in vivo Carcinogenesis and in vitro Genotoxicity of Complex Hydrocarbon Mixtures." In: Proceedings, Fifth ORNL Life Sciences Symposium, Synthetic Fossil Fuel Technologies: Results of Health and Environmental Studies (in press).

Renne, R. A., R. A. Pelroy, M. E. Frazier, B. W. Wilson and D. D. Mahlum. 1983. "Epidermal Carcinogenesis Studies of Synthetic Fuel Materials in Mice: Comparison and Correlation with in vitro Genotoxicity Assays and Chemical Analysis." In: Proceedings, Skin Carcinogenicity: Experimental and Occupational Aspects (in press).

Roesch, W. C. 1983. "Field Practices and Techniques: Introduction." In: Proceedings, International Beta Dosimetry Symposium (in press).

Roesch, W. C. 1983. "Inhomogeneous Distributions of Sources." Rad. Res. 94:577-578.

Sanders, R. W., K. B. Olsen, W. C. Weimer and K. K. Nielson. 1983. "Multielement Analysis of Unweighed Oil Samples Using Dual X-Ray Fluorescence Spectra." Anal. Chem. 55:1911-1914.

Schneider, D., M. Prost, N. Stolterfoht, G. Nolte and R. DuBois. 1983. "Projectile Ionization by Fast Heavy Ion-Atom Collisions." Phys. Rev. A28:649.

- Smith, R. D. and H. R. Udseth. 1983. "Applications of Direct Fluid Injection Mass Spectrometry: Instrumentation and Methods." Anal. Chem. (in press).
- Smith, R. D. and H. R. Udseth. 1983. "Direct Fluid Injection of Mass Spectrometry and MS/MS: Fundamental Aspects and Applications." Anal. Chem. (in press).
- Smith, R. D., B. W. Wright and H. R. Udseth. 1983. "Supercritical Fluid Methods in Analytical Chemistry." Analytical Spectroscopy, Vol. 26, Elsevier; Science (accepted for publication).
- Smith, R. D., B. W. Wright and H. R. Udseth. 1983. "Supercritical Fluid Methods for Coal Extraction, Separation and Analysis." American Chemical Society, Division of Fuel Chemistry, Preprints, 28:235-240.
- Smith, R. D., J. Fjeldsted and M. L. Lee. 1983. "Supercritical Fluid Chromatography-Mass Spectrometry." Int. J. Mass Spectrom. Ion Phys. 46:217.
- Smith, R. D. and H. R. Udseth. 1983. "Direct Analysis of Supercritical Fluid Extraction Products." Sep. Sci. Tech. 18:245-252.
- Smith, R. D. and H. R. Udseth. 1983. "A Method for the Direct Analysis of Supercritical Fluid Coal Extraction and Liquefaction." Fuel 62:466-469.
- Toburen, L. H., R. D. DuBois and S. T. Manson. 1983. "Multiple Ionization of Atomic Targets by Proton Impact." Science 30:923-927.
- Toburen, L. H., W. E. Wilson, R. D. DuBois and J. H. Miller. 1983. "Fundamental Interactions for Energy Transfer by High LET Radiation." Rad. Res. 94:620.
- Toste, A. P., D. S. Sklarew and R. A. Pelroy. 1983. "The Role of Partition Chromatography/HPLC in the Organic and Mutagenic Characterization of Synfuels." In: Advanced Techniques in Synthetic Fuels Analysis, eds. C. W. Wright, W. C. Weimer, W. D. Felix, Technical Information Center, Oak Ridge, Tennessee.
- Toste, A. P., D. S. Sklarew and R. A. Pelroy. 1982. "Partition Chromatography-High Performance Liquid Chromatography Facilitates the Organic Analysis and Biotesting of Synfuels." J. Chromatogr. 249:267-282.
- Weimer, W. C. and B. W. Wilson. 1983. "Integration of Chemical Analysis and Biological Testing in the Study of Coal Liquid Toxicology." In: Abstracts, Third International Congress on Toxicology (in press), International Union of Toxicology.
- Wilson, B. W., R. A. Pelroy, D. D. Mahlum, M. E. Frazier and C. W. Wright. 1983. "Heteroatomic Polycyclic Aromatic Hydrocarbons in Coal Liquids." In: Advanced Techniques in Synthetic Fuels Analysis, eds. C. W. Wright, W. C. Weimer, W. D. Felix, Technical Information Center, Oak Ridge, Tennessee.
- Wilson, B. W., R. A. Pelroy, D. D. Mahlum, M. E. Frazier, R. A. Renne and P. J. Mellinger. 1981. "Heteroatomic PAH: Analysis, Bioassay and Implications for Air Quality." In: Proceedings of OECD Workshop on PAH, October 1981 (in press).
- Wilson, B. W., E. K. Chess, D. W. Later, W. R. Harris and D. Okamoto. 1983. "Identification of Mutagenic Constituents in Coal Combustion Fly Ash." In: Proceedings, First International Fluidized Bed Combustion and Applied Technology Symposium (in press), Beijing, People's Republic of China. McGraw-Hill, Inc., New York.
- Wilson, W. E. 1983. "Track Modeling by Monte Carlo Techniques." In: Proceedings of the Workshop on the Interface Between Radiation Chemistry and Radiation Physics, ANL-82-88, pp. 101-105.
- Wilson, W. E., J. H. Miller and L. H. Toburen. 1983. "Secondary Electrons from Ionization of Atoms and Molecules by High Velocity Ions." Rad. Res. 94:577.
- Wright, C. W., W. C. Weimer and W. D. Felix, eds. 1983. Advanced Techniques in Synthetic Fuels Analysis, p. 416. Technical Information Center, Oak Ridge, Tennessee.
- Wright, C. W., W. C. Weimer and D. S. Daly. 1983. "Stability Studies on the Chemical Composition and Biological Activity of Coal-Derived Liquids." In: Proceedings, Eighth International Symposium on Polynuclear Aromatic Hydrocarbons (in press). Battelle Press, Columbus, Ohio.
- Wright, C. W. 1983. "Simultaneous Quantitative Analysis Using Dual Capillary Columns of Different Polarities." In: Abstracts, 25th Rocky Mountain Conference, Society of Applied Spectroscopy (in press).

Wright, C. W., W. C. Weimer, D. W. Later and R. B. Lucke. 1983. "Preparation of Coal Liquids for Chemical Analysis and Biological Assay." In: Abstracts, Third International Congress on Toxicology (in press).

Zaider, M., D. J. Brenner and W. E. Wilson. 1983. "The Applications of Track Calculations to Radiobiology I. Monte Carlo Simulation of Proton Tracks." Radiation Research 95:231-247.

PRESENTATIONS

Braby, L. A., W. C. Roesch and B. S. Jacobson. 1983. "L.E.T. Dependence of Two-Event Damage in *Chlamydomonas reinhardtii*." Presented at the Annual Meeting of the Radiation Research Society in San Antonio, Texas, February 27-March 3, 1983.

Braby, L. A. 1983. "Modeling Multiple Damage and Repair Process in *Chlamydomonas reinhardtii*." Presented at the DOE Contractors Meeting, Gettysburg, Pennsylvania, May 17-19, 1983.

Bushaw, B. A. 1983. "Kinetic Analysis of Laser Induced Phosphorescence in Uranyl Phosphate for Improved Analytical Measurements." Presented at the Oak Ridge Analytical Chemistry Conference, Knoxville, Tennessee, October 11, 1983.

Chess, E. K., D. W. Later, B. W. Wilson and W. R. Harris. "MS Detection and Characterization of Novel Nitro-PAH in Mutagenic Fly Ash Extract." Presented at the 31st Annual Conference on Mass Spectrometry and Allied Topics, American Society for Mass Spectrometry, Boston, Massachusetts, May 8-13, 1983.

Chess, E. K., D. D. Mahlum, R. B. Lucke, W. C. Weimer, B. W. Wilson and C. W. Wright. 1983. "Initiation-Promotion Studies with Fractionated Coal Liquids." Presented at the Third International Congress on Toxicology, International Union of Toxicology, San Diego, California, August 28-September 2, 1983.

DuBois, R. D., L. H. Toburen and S. T. Manson. 1983. "Mechanisms for Production of Multi-Charged Ions by Proton Impact Ionization of Neon." Presented at the DEAP Meeting of the American Physical Society, Boulder, Colorado, May 23-25, 1983.

DuBois, R. D. and L. H. Toburen. 1983. "Multiple Ionization of Argon by Charge Transfer and Direct Ionization." Presented at the XIII ICPEAC Meeting, Berlin, West Germany, July 27-August 2, 1983.

DuBois, R. D., L. H. Toburen and S. T. Manson. 1983. "Double Ionization Mechanisms in H^+-Ne Collisions." Presented at the XIII ICPEAC Meeting, Berlin, West Germany, July 27-August 2, 1983.

Fisher, D. R. 1983. "Concepts of Dose to Soft Tissue at the Cellular Level." Health Physics Society Summer School on Internal Dosimetry, June 13-17, 1983, Baltimore, Maryland.

Fisher, D. R., W. C. Cannon, R. T. Hadley and J. F. Park. 1983. "Preliminary Evaluation of Lung Doses of Dogs Exposed to $^{239}PuO_2$." Twenty-Second Hanford Life Sciences Symposium, September 27-29, 1983, Richland, Washington.

Fisher, D. R. and M. E. Frazier. 1983. "The 'Hot Particle' Controversy: New Answers to Old Questions." Health Physics Society Annual Meeting, June 20-23, 1983, Baltimore, Maryland.

Jacobson, B. S. and L. A. Braby. 1983. "Effects of Varying LET on Sublethal Damage Repair in *Chlamydomonas*." Presented at the Annual Meeting of the Radiation Research Society, San Antonio, Texas, February 27-March 3, 1983.

Later, D. W. and B. W. Wilson. 1983. "Process Related Aspects of the Toxicology of Coal-Derived Materials." Presented at the Third International Congress on Toxicology, San Diego, California, August 28-September 2, 1983.

Later, D. W. and B. W. Wright. 1983. "Capillary Gas Chromatographic Methods for the Selective Separation of Biologically Active Amino Polycyclic Aromatic Hydrocarbon Isomers in Coal-Derived Materials." Presented at the International Symposium on Advances in Chromatography, Amsterdam, The Netherlands, October 3-6, 1983.

Later, D. W., B. W. Wright and C. W. Wright. 1983. "Applied Capillary Column Gas Chromatography for the Analyses of Biologically Active Polycyclic Aromatic Compounds in Coal Liquefaction Process Materials." Presented at the Capillary Chromatography 1983: Second International Symposium, Tarrytown, New York, October 10-12, 1983.

Later, D. W. 1983. "Analytical and Chromatographic Methods for the Determination of Cyano Polycyclic Aromatic Hydrocarbons in Coal-Derived Materials." Presented at the Eighth International Symposium on Polynuclear Aromatic Hydrocarbons, Columbus, Ohio, October 26-28, 1983.

Metting, N. F., J. M. Nelson, W. C. Roesch and L. A. Braby. "Low Dose-Rate Effects in Stationary Phase Mammalian Cells." Presented at the Annual Meeting of the Radiation Research Society, San Antonio, Texas, February 27-March 3, 1983.

- Miller, J. H. and W. E. Wilson. 1983. "Monte Carlo Approach to Track Structure in Diffusion Kinetics: Pulse Radiolysis of Water with 3 MeV Protons." Presented at the Annual Meeting of the Radiation Research Society, San Antonio, Texas, February 27-March 3, 1983.
- Miller, J. H. 1983. "Correlation Between Survival and the Rate of Excision of DNA-Carcinogen Residues." Presented at the 1983 UCLA Symposia, Keystone, Colorado, April 10-15, 1983.
- Miller, J. H. 1983. "Monte Carlo Approach to Track Structure in Diffusion Kinetics: Pulse Radiolysis of Water with 3 MeV." Presented at the DOE Contractors Meeting, Gettysburg, Pennsylvania, May 17-19, 1983.
- Nelson, J. M. and N. F. Metting. 1983. "Plateau Phase Growth Kinetics: Effects on Radiation Damage Repair." Presented at the Annual Meeting of the Radiation Research Society, San Antonio, Texas, February 27-March 3, 1983.
- Nelson, J. M. 1983. "Characterization of Plateau-Phase Growth Kinetics." Presented at the 7th Annual Meeting of Cell Kinetics Society, Baltimore, Maryland, March 15-19, 1983.
- Nelson, J. M., L. A. Braby, W. C. Roesch and N. F. Metting. 1983. "Correlation Between Cell Survival, Sublethal Damage Repair, and Age Distributions in Plateau Phase Mammalian Cells." Presented at the 7th International Congress of Radiation Research, Amsterdam, The Netherlands, July 3-8, 1983.
- Nelson, J. M., L. A. Braby, N. F. Metting and W. C. Roesch. 1983. "Influence of Kinetic Status on the Removal of Cumulative Damage in Irradiated Plateau-Phase Mammalian Cells." Presented at the Eleventh L. H. Gray Conference, Bearsden (Glasgow), Scotland, July 18-22, 1983.
- Nelson, J. M. 1983. "Introduction and Rapporteur of Posters." Presented at the Eleventh L. H. Gray Conference, Bearsden (Glasgow), Scotland, July 18-22, 1983.
- Nelson, J. M., N. F. Metting, W. C. Roesch and L. A. Braby. 1983. "Kinetics of Simultaneous Sublethal and Potentially Lethal Damage Repair in Plateau Phase CHO Cells." Presented at Workshop on Heavy Particles in Biology and Medicine, Darmstadt, West Germany, June 27-29, 1983.
- Newman, C. N. 1983. "Repair of Ultraviolet Light or Chemical Alkylation-Induced Damage May be Affected by Deoxynucleoside Triphosphate Pool Imbalance." Presented at the Annual Meeting of the Radiation Research Society, San Antonio, Texas, February 27-March 3, 1983.
- Newman, C. N. and J. H. Miller. 1983. "Response of CHO Cell DNA Polymerase Alpha to dCTP and dTTP Pool Imbalance: Relation to DNA Synthesis Inhibition, Survival and Mutation." Presented at the Conference on Genetic Consequences of Nucleotide Pool Imbalance, Research Triangle Park, North Carolina, May 9-11, 1983.
- Olsen, K. B., D. R. Kalkwarf and C. Veverka, Jr. 1983. "Analysis and Collection of PAHs in the Flue Gas of Energy Conversion Facilities." Presented at the Eighth International PAH Conference, Columbus, Ohio, October 1983.
- Roesch, W. C. 1983. "Field Practices and Techniques: Introduction." Presented at the International Beta Dosimetry Symposium, Washington, D.C., February 15-17, 1983.
- Roesch, W. C. 1983. "Inhomogeneous Distributions of Sources." Presented at the Annual Meeting of the Radiation Research Society, San Antonio, Texas, February 27-March 3, 1983.
- Rudd, M. E., T. V. Goffe, R. D. DuBois, L. H. Toburen and C. A. Ratcliffe. 1983. "Ionization Cross Sections for 5-4000 keV Protons in Gases." Presented at the XIII ICPEAC Meeting, Berlin, West Germany, July 27-August 2, 1983.
- Sklarew, D. S., D. J. Hayes, M. R. Petersen, K. B. Olsen and C. D. Pearson. 1983. "Gas Chromatographic Analysis of Trace Sulfur and Nitrogen Species in an Oil Shale Retort Off-gas." Presented at the Analytical Instrumentation Division of the Instrument Society of America Symposium, Houston, Texas.
- Sklarew, D. S., D. J. Hayes, M. R. Petersen, K. B. Olsen and C. D. Pearson. 1983. "Analysis of Nonhydrocarbon Trace Species from Two Oil Shale Retorts." Presented at the National Meeting of the American Chemical Society, Division of Analytical Chemistry, Washington, D.C., August 28-September 2, 1983.

Sklarew, D. S., K. B. Olsen and J. C. Evans. 1983. "Speciation of Organo-Mercury Compounds by a Capillary Column GC-Microwave Plasma Detector System." Presented at the Eighth National Conference on Spectrochemical Excitation and Analysis, Edgartown, Massachusetts, September 6-9, 1983.

Smith, R. D., H. R. Udseth and E. K. Chess. 1983. "Rapid Analysis Using Direct Supercritical Fluid Injection-Mass Spectrometry." Presented at the 31st Annual Conference on Mass Spectrometry and Allied Topics, American Society for Mass Spectrometry, Boston, Massachusetts, May 8-13, 1983.

Smith, R. D. and H. R. Udseth. 1983. "Applications of Direct Fluid Injection Mass Spectrometry: Instrumentation and Methods." Presented at the FACCS Meeting, Philadelphia, Pennsylvania, September 25-30, 1983.

Smith, R. D., H. R. Udseth and B. W. Wright. 1983. "Supercritical Fluid Methods in Analytical Chemistry." Presented at the 26th Conference on Analytical Chemistry in Energy Technology, Knoxville, Tennessee, October 11-13, 1983.

Smith, R. D., E. K. Chess and H. R. Udseth. 1983. "Rapid Analysis Using Direct Supercritical Fluid Injection-Mass Spectrometry." Presented at the 31st Annual American Society for Mass Spectrometry Meeting, Boston, Massachusetts, May 5-12, 1983.

Smith, R. D., B. W. Wright and H. R. Udseth. 1983. "Supercritical Fluids and Mass Spectrometry: New Analytical Methods." Presented at the 1983 Pacific Conference on Spectrometry, Los Angeles, California, October 25-30, 1983.

Smith, R. D., H. R. Udseth and B. W. Wright. 1983. "Applications of Capillary Supercritical Fluid Chromatography-Mass Spectrometry." Presented at the 31st Annual American Society for Mass Spectrometry, Boston, Massachusetts, May 5-12, 1983.

Smith, R. D., H. R. Udseth and B. W. Wright. 1983. "Supercritical Fluid Methods for Coal Extraction, Separation, and Analysis." Presented at the National ACS Meeting, Washington, D.C., August 28, 1983.

Smith, R. D., E. K. Chess and H. R. Udseth. 1983. "Applications of Supercritical Fluids for the Mass Spectrometry of Large Molecules." Presented at the National ACS Meeting, Seattle, Washington, March 20-25, 1983.

Smith, R. D., H. R. Udseth and E. K. Chess. 1983. "Applications for Direct Supercritical Fluid Injection-Mass Spectrometry." Presented at the 31st Pittsburgh Conference on Analytical Chemistry and Applied Spectroscopy, Atlantic City, New Jersey, March 7-12, 1983.

Toburen, L. H., W. E. Wilson, R. D. DuBois and J. H. Miller. 1983. "Fundamental Interactions for Energy Transfer by High LET Radiation." Presented at the Annual Meeting of the Radiation Research Society, San Antonio, Texas, February 27-March 3, 1983.

Toburen, L. H., R. D. DuBois, J. H. Miller and W. E. Wilson. 1983. "Secondary Electron Emission and Effects of Screening on Energy Deposition by Fast Heavy Ions." Presented at the Seventh International Congress of Radiation Research, Amsterdam, The Netherlands, July 3-8, 1983.

Toburen, L. H. 1983. "Fundamental Interactions for Energy Transfer by High LET Radiation." Presented at the DOE Contractors Meeting, Gettysburg, Pennsylvania, May 17-19, 1983.

Toste, A. P. and T. R. Pahl. "Development of Chromatographic Techniques for the Analysis of Synfuel Samples." Presented at the 25th Rocky Mountain Conference, Denver, Colorado, August 15, 1983.

Weimer, W. C. and B. W. Wilson. 1983. "Integration of Chemical Analysis and Biological Testing in a Study of Coal Liquid Toxicology." Presented at the Third International Congress on Toxicology, San Diego, California, August 28-September 2, 1983.

Wilson, B. W., E. K. Chess, D. W. Later, W. R. Harris and D. Okamoto. 1983. "Identification of Mutagenic Constituents in Coal Combustion Fly Ash." Presented at the First International Fluidized Bed Combustion Symposium, Peking, China, August 22-26, 1983.

Wilson, W. E., J. H. Miller and L. H. Toburen. 1983. "Secondary Electrons from Ionization of Atoms and Molecules by High Velocity Ions." Presented at the Annual Meeting of the Radiation Research Society, San Antonio, Texas, February 27-March 3, 1983.

Wilson, W. E. 1983. "Radiation Transport for Dosimetry." Presented at the University of Washington-Seattle and at the Joint Center for Graduate Study, Richland, Washington, January 1983.

Wilson, W. E. 1983. "Fundamental Interactions for Energy Transfer by High LET Radiation." Presented at Informal Workshop on Penetration Phenomena: Properties of Ion-Induced Tracks in Matter, Oak Ridge National Laboratory, Oak Ridge, Tennessee, January 12, 1983.

Wright, C. W., W. C. Weimer and D. S. Daly. 1983. "Stability Studies on the Chemical Composition and Biological Activity of Coal-Derived Liquids." Presented at the Eighth International Symposium on Polynuclear Aromatic Hydrocarbons, Columbus, Ohio, October 26-28, 1983.

Wright, C. W. 1983. "Simultaneous Quantitative Analysis Using Dual Capillary Columns of Different Polarities." Presented at the 25th Rocky Mountain Conference, Society of Applied Spectroscopy, Denver, Colorado, August 14-19, 1983.

Wright, C. W., W. C. Weimer, D. W. Later and R. B. Lucke. 1983. "Preparation of Coal Liquids for Chemical Analysis and Biological Assay." Presented at the Third International Congress on Toxicology, International Union of Toxicology, San Diego, California, August 28-September 2, 1983.

Wright, B. W., R. D. Smith and H. R. Udseth. 1983. "Application of Supercritical Fluid Chromatography and Supercritical Fluid Chromatography Mass Spectrometry to the Analysis of Thermally Labile Compounds." Presented at the Labcon West 83 Conference, San Jose, California, May 10-21, 1983.

Wright, B. W., H. R. Udseth and R. D. Smith. 1983. "Capillary Column Supercritical Fluid Chromatography: Approaches and Applications." Presented at the National ACS Meeting, Washington, D.C., August 28-September 2, 1983.

Wright, B. W., R. D. Smith and H. R. Udseth. 1983. "Supercritical Fluid Mass Spectrometry Techniques." Presented at the DOE Analytical Characterization Group Meeting, Ames, Iowa, November 2, 1983.

Author Index

AUTHOR INDEX

Braby, L. A.; 29, 43, 45, 50, 52	Jacobson, B.S.; 43, 45	Rapkin, M.; 29
Brenner, D. J.; 36	Kalkwarf, D. R.; 1	Roesch, W. C.; 39, 40, 41, 50, 52, 65
Bushaw, B. A.; 17	Kliauga, P. J.; 29	Rossi, H. H.; 29
Cannon, W. C.; 67	Later, D. W.; 1	Rudd, M. E.; 24
Chess, E. K.; 1	Lucke, R. B.; 1	Sklarew, D. S.; 5, 7, 10
Cocke, C. L.; 27	Manson, S. T.; 25, 27	Smith, R. D.; 5, 15
Cummings, F. M.; 23	McCulloch, M.; 10	Toburen, L. H.; 23, 25, 27
Downey, S. P.; 7	Mercer, B. W.; 9	Toste, A. P.; 9
DuBois, R. D.; 23, 24, 25, 27	Metting, N. F.; 29, 49, 50, 52	Udseth, H. R.; 5, 15
English, C. J.; 9	Miller, J. H.; 27, 31, 36, 57, 58, 61, 62	Weimer, W. C.; 1
Evans, J. C.; 5	Myers, R. B.; 9	Whitaker, T. J.; 17
Fisher, D. R.; 65, 67	Nelson, J. M.; 49, 50, 52	Wilson, B. W.; 1
Frazier, M. E.; 65	Newman, C. N.; 57, 58, 61	Wilson, W. E.; 23, 27, 31, 34, 36
Giese, J.; 27	Olsen, K. B.; 5, 7	Wright, B. W.; 15
Hadley, R. T.; 67	Park, J. F.; 67	Wright, C. W.; 1
Heflich, R. H.; 62		Zaider, M.; 36
Howard, J.; 29		

Organization Charts Distribution

ENVIRONMENT, HEALTH AND SAFETY RESEARCH

NOTE

— SOLID LINES DENOTE ORGANIZATIONAL COMPONENTS IN WHICH HEALTH AND ENVIRONMENTAL RESEARCH IS BEING CONDUCTED AS OF DECEMBER 1, 1982

— FUNCTIONAL MANAGEMENT RELATIONSHIP

--- EH&SR PROGRAM MANAGEMENT RELATIONSHIP

DISTRIBUTION

PNL-5000 PT4
UC-48

<u>No. of Copies</u>	<u>No. of Copies</u>	<u>No. of Copies</u>
27 DOE Technical Information Center	A. P. Duhamel Office of Health & Environmental Research Office of Energy Research Department of Energy ER-74, GTN Germantown, MD 20545	J. Kane Deputy Director Office of Energy Research ER-2, FORR Department of Energy Washington, DC 20585
W. R. Albers Environmental Protection, Safety and Emergency Preparedness Department of Energy Washington, DC 20545	C. W. Edington Associate Director Office of Health & Environmental Research Office of Energy Research Department of Energy ER-70, GTN Germantown, MD 20545	W. J. Little, Jr. Environmental Protection, Safety and Emergency Preparedness Department of Energy Washington, DC 20545
R. Barber Environmental Protection, Safety and Emergency Preparedness Department of Energy Washington, DC 20545	G. Goldstein Office of Energy Research Department of Energy Washington, DC 20545	J. N. Maddox Office of Energy Research Department of Energy Washington, DC 20545
D. Ballantine Office of Health and Environmental Research Office of Energy Research Department of Energy ER-74, GTN Germantown, MD 20545	S. H. Greenleigh Environmental Protection, Safety and Emergency Preparedness Department of Energy Washington, DC 20545	J. R. Maher Acting Director Office of Nuclear Safety Office for Environmental Protection, Safety & Emergency Preparedness Department of Energy EP-34, GTN Germantown, MD 20545
N. F. Barr Office of Health and Environmental Research Office of Energy Research Department of Energy ER-73, GTN Germantown, MD 20545	E. Harvey Office of Energy Research Department of Energy Washington, DC 20545	C. R. Mandelbaum Office for Program Analysis Office of Energy Research Department of Energy ER-32, GTN Germantown, MD 20545
L. C. Brazely, Jr. Office of Operational Safety Office for Environmental Protection, Safety & Emergency Preparedness Department of Energy EP-32, GTN Germantown, MD 20545	H. L. Hollister Office of Deputy Assistant Secretary Office of Environmental Protection, Safety & Emergency Preparedness Department of Energy ER-30, FORR Washington, DC 20585	D. D. Mayhew Office of Energy Research Department of Energy Washington, DC 20545
J. Coleman Office of Energy Research Department of Energy Washington, DC 20545	F. Hudson Office of Energy Research Department of Energy Washington, DC 20545	H. McCammon, Office of Health & Environmental Research Office of Energy Research Department of Energy ER-75, GTN Germantown, MD 20545
R. W. Davies Deputy Assistant Secretary Office for Environmental Protection, Safety & Emergency Preparedness Department of Energy EP-30, FORR Washington, DC 20585	G. Y. Jordy, Director Office of Program Analysis Office of Energy Research Department of Energy ER-30, GTN Germantown, MD 20545	T. F. McCraw Environmental Protection, Safety and Emergency Preparedness Department of Energy Washington, DC 20545

No. of
Copies

M. L. Minthorn, Jr.
Office of Health &
Environmental Research
Office of Energy Research
Department of Energy
ER-72, GTN
Germantown, MD 20545

W. E. Mott
Office of Operational
Safety
Office for Environmental
Protection, Safety &
Emergency Preparedness
Department of Energy
EP-32, GTN
Germantown, MD 20545

D. E. Patterson
Acting Director
Office of Operational
Safety
Office for Environmental
Protection, Safety &
Emergency Preparedness
Department of Energy
EP-32, GTN
Germantown, MD 20545

R. G. Rader
Office of Program Analysis
Office of Energy Research
Department of Energy
ER-32, GTN
Germantown, MD 20545

M. Schulman
Office of Health &
Environmental Research
Office of Energy Research
Department of Energy
ER-70, GTN
Germantown, MD 20545

D. H. Slade
Office of Health &
Environmental Research
Office of Energy Research
Department of Energy
ER-74, GTN
Germantown, MD 20545

J. Snow
Office of Energy Research
Department of Energy
ER-6, FORR
Washington, DC 20585

No. of
Copies

J. Swinebroad
Environmental Protection,
Safety and Emergency
Preparedness
Department of Energy
Washington, DC 20545

J. W. Thiessen
Acting Deputy
Associate Director
Office of Health &
Environmental Research
Office of Energy Research
Department of Energy
ER-71, GTN
Germantown, MD 20545

A. Triveliece, Director
Office of Energy Research
Department of Energy
ER-1, FORR
Washington, DC 20585

W. A. Vaughan
Assistant Secretary for
Environmental Protection
Safety & Emergency
Preparedness
Department of Energy
EP-1, FORR
Washington, DC 20585

B. W. Wachholz
Low-Level Radiation
Effects Branch
National Institutes
of Health
Landau Bldg.
Room 8C-09
9000 Rockville Pike
Bethesda, MD 20205

6 R. W. Wood
Office of Health &
Environmental Research
Office of Energy Research
Department of Energy
ER-74, GTN
Germantown, MD 20545

H. L. Volchok
Department of Energy
Environmental Measurements
Laboratory
376 Hudson St.
New York, NY 10014

No. of
Copies

J. R. Roeder
DOE - Albuquerque
Operations Office
P.O. Box 5400
Albuquerque, NM 87115

D. S. Ingle
Dayton Area Office
DOE - Albuquerque
Operations Office
P.O. Box 66
Miamisburg, OH 45342

E. W. Bean
Rocky Flats Area Office
DOE - Albuquerque
Operations Office
P.O. Box 928
Golden, CO 80401

D. M. Gardiner
DOE - Chicago
Operations Office
9800 South Cass Avenue
Argonne, IL 60439

J. H. Spickard
DOE - Idaho Operations
Commission
550 Second Street
Idaho Falls, ID 83401

M. M. Williamson
DOE - Idaho Operations
Commission
550 Second Street
Idaho Falls, ID 83401

P. B. Dunnaway
DOE - Oak Ridge Operations
Office
P.O. Box E
Oak Ridge, TN 32830

W. Bibb
DOE - Oak Ridge
Operations Office
P.O. Box 14100
Las Vegas, NV 89114

C. Jackson
DOE - San Francisco
Operations Office
133 Broadway
Wells Fargo Building
Oakland, CA 94616

No. of
Copies

B. Morgan
DOE - Savannah River
Operations Office
P.O. Box A
Aiken, SC 29801

W. Reese
DOE - Savannah River
Operations Office
P.O. Box A
Aiken, SC 29801

Library
Bartlesville Energy
Research Center
Department of Energy
P.O. Box 1398
Bartlesville, OK 74005

G. H. Gronhoyd
Grand Forks Energy
Research Center
Department of Energy
Box 8213
University Station
Grand Forks, ND 58202

A. W. Decora
Laramie Energy
Research Center
Department of Energy
P.O. Box 3395
University Station
Laramie, WY 83071

A. A. Pitrolo
Morgantown Energy
Research Center
Department of Energy
P.O. Box 880
Morgantown, WV 26505

B. M. Erickson
DOE - Schenectady Naval
Reactors Office
P.O. Box 1069
Schenectady, NY 12301

M. Inokuti
Argonne National
Laboratory
9800 S. Cass Avenue
Argonne, IL 60439

H. Drucker
Argonne National
Laboratory
9800 S. Cass Avenue
Argonne, IL 60439

No. of
Copies

V. P. Bond
Brookhaven National
Laboratory
Upton, Long Island,
NY 11973

Librarian
Research Library,
Reference
Brookhaven National
Laboratory
Upton, Long Island,
NY 11973

C. B. Meinhold
Brookhaven National
Laboratory
Upton, Long Island,
NY 11973

D. Beirman
Chief, Document Service
Branch
Central Intelligence
Agency
Attn: CRS/DPSD/DSB/IAS/
409779/DB
Washington, DC 20505

H. Rossi
Radiological Research
Laboratory
Columbia University
630 West 168th Street
New York, NY 10032

Council of Environmental
Quality
72 Jackson Place, N.W.
Washington, DC 20006

Technical Information
Service
Room 773A
Savannah River Laboratory
E. I. du Pont de Nemours
and Company
Aiken, SC 29801

W. Weyzen
Electric Power Research
Institute
3412 Hillview Avenue
Palo Alto, CA 94304

H. Ellett
Environmental Protection
Agency
Washington, DC 20460

No. of
Copies

J. W. McCaslin
INEL, Aerojet Nuclear
550 Second Street
Idaho Falls, ID 83401

Librarian
Joint Center for
Graduate Study
100 Sprout Road
Richland, WA 99352

J. F. Johnson
Kenworth Trucking
30 Vreeland Rd.
Florham Park, NJ 07932

E. L. Alpen
Lawrence Berkeley
Laboratory
University of California
Building 90, Room 2056
No. 1 Cyclotron Road
Berkeley, CA 94720

Librarian
Lawrence Radiation
Laboratory
University of California
Technical Information
Department, L-3
P.O. Box 808
Livermore, CA 94500

J. L. Magee
Lawrence Berkeley
Laboratory
Bldg. 29, Rm 206
Berkeley, CA 94720

M. L. Mendelsohn
University of California
Lawrence Livermore
Laboratory
P.O. Box 808
Livermore, CA 94550

Y. E. Ricker,
Lawrence Livermore
National Laboratory
P.O. Box 5507,
Livermore, CA 94550

J. Birely
Los Alamos Scientific
Laboratory
University of California
P.O. Box 1663
Los Alamos, NM 87545

No. of
Copies

D. J. Brenner
Los Alamos National
Laboratory
M.S. H809
Los Alamos, NM 87545

J. W. Healy
Los Alamos Scientific
Laboratory
University of California
P.O. Box 1663
Los Alamos, NM 87545

Librarian
Los Alamos Scientific
Laboratory
P.O. Box 1663
Los Alamos, NM 87545

D. F. Petersen
Los Alamos Scientific
Laboratory
University of California
P.O. Box 1663
Los Alamos, NM 87545

G. L. Voelz
Los Alamos Scientific
Laboratory
University of California
P.O. Box 1663
Los Alamos, NM 87545

R. O. McClellan
Inhalation Toxicology
Research Institute
Lovelace Foundation for
Medical Education and
Research
P.O. Box 5890
Albuquerque, NM 87115

W. R. Ney
Executive Director
National Council on
Radiation Protection
and Measurement
7910 Woodmont Avenue
Suite 1061
Washington, DC 20014

R. Alexander
Nuclear Regulatory
Commission
Washington, DC 20545

No. of
Copies

P. A. Comella
Division of Health, Siting
and Waste Management
Office of Nuclear
Regulatory Research
Nuclear Regulatory
Commission
Washington, DC 20545

E. Conti
Nuclear Regulatory
Commission
Washington, DC 20545

J. J. Davis
Nuclear Regulatory
Commission
Washington, DC 20545

NRC Advisory Committee
on Reactor Safeguards
Washington, DC 20555

R. A. Scarano
Nuclear Regulatory
Commission
Mill Licensing Section
Washington, DC 20545

F. Swanberg
Nuclear Regulatory
Commission
Washington, DC 20545

S. I. Auerbach
Oak Ridge National
Laboratory
P.O. Box X
Oak Ridge, TN 37830

J. A. Auxier
Oak Ridge National
Laboratory
P.O. Box X
Oak Ridge, TN 37830

W. R. Garrett
Oak Ridge National
Laboratory
P.O. Box X
Oak Ridge, TN 37830

C. R. Richmond
Oak Ridge National
Laboratory
P.O. Box X
Oak Ridge, TN 37830

No. of
Copies

D. Rall, Director
NIEHS
P.O. Box 12233
Research Triangle Park,
NC 27709

K. A. Smith
Sandia Laboratories
P.O. Box 5800
Albuquerque, NM 87187

P. W. Todd
793 Westerly Parkway
State College, PA 16801

R. Lunt
University of California
Center of Life Sciences
900 Veteran Avenue
West Los Angeles,
CA 90024

Leo Bustad, Dean
College of Veterinary
Medicine
Washington State
University
Pullman, WA 99163

FOREIGN

Librarian
Australian AEC
Riverina Laboratory
P.O. Box 226
Deniliquin
New South Wales
AUSTRALIA 2710

Librarian
Commonwealth Scientific
and Industrial Research
Organization
314 Albert Street
P.O. Box 89
East Melbourne, Victoria
AUSTRALIA

H. Daw
Director, Division of
Health, Safety and
Waste Management
International Atomic
Energy Agency
Vienna 1, Kaerentnerring
11,
AUSTRIA

<u>No. of Copies</u>	<u>No. of Copies</u>	<u>No. of Copies</u>
A. M. Marko Director Atomic Energy of Canada Ltd. Biology and Health Physics Division Chalk River Nuclear Laboratories Chalk River Ontario K0J 1J0 CANADA	Wang Hengde North China Institute of Radiation Protection P.O. Box 120 Tai-yuan City, Shan-xi Province CHINA	Sun Shi-quan Head of Radiation-Medicine Department North China Institute of Radiation Protection Tai-yuan Shan-xi CHINA
M. Anderson Library Department of National Health and Welfare Ottawa, Ontario CANADA	Deng Zhicheng North China Institute of Radiation Protection P.O. Box 120 Tai-yuan City, Shan-xi Province CHINA	Jiang Shengjie, Professor Standing Vice-President Chinese Nuclear Society P.O. Box 2125 Beijing CHINA
Chen Xing-an, M.D. Assoc. Prof. of Lab of Industrial Hygiene Ministry of Public Health P.O. Box No. 753 Beijing CHINA	Zhu Zhixian North China Institute of Radiation Protection P.O. Box 120 Tai-yuan City, Shan-xi Province CHINA	J. Dunster National Radiological Protection Board Harwell, Didcot Oxfordshire OX11 0RQ ENGLAND
Wang Ruifa Ministry of Public Health P.O. Box No. 753 Beijing CHINA	Professor Yibing Wang North China Institute of Radiation Protection P.O. Box 120 Tai-yuan City, Shan-xi Province CHINA	Librarian, Building 465 Atomic Energy Research Establishment Harwell, Didcot OXON OX11 0RD ENGLAND
Ma Fubang, Director Chief Engineer Institute of Atomic Energy P.O. Box 275 Beijing CHINA	Shu-Zheng Liu, M.D. Professor and Chief, Department of Radiation Biology Bethune Medical University 7 Xinmin Street Changchun, Jilin CHINA	D. H. Perison Atomic Energy Research Establishment Health Physics and Medical Division B. 364 Harwell, Didcot, Berkshire ENGLAND
Pan Zi-qiang Head of Health Physics Lab Atomic Energy Institute Beijing CHINA	Wu De-Chang Institute of Radiation Medicine 11# Tai Ping Rd. Beijing CHINA	Mrs. Yvonne Cocking, Librarian Medical Research Council MRC Radiobiology Unit Harwell, Didcot Oxon OX11 0RD ENGLAND
Li De-ping Professor & Director of North China Institute of Radiation Protection, MNI Tai-yuan, Shan-xi CHINA	Cao Shu-yuan Associate Professor & Deputy Head of Laboratory of Radiation Medicine North China Institute of Radiation Protection, MNI Tai-yuan Shan-xi CHINA	Dr. H. Smith Head of Biology Department National Radiological Protection Board Chilton, Didcot Oxfordshire, OX11 0RQ ENGLAND
Xie Zi, Senior Engineer Scientific Secretary of Radiation Protection Laboratory Institute of Atomic Energy P.O. Box 275 Beijing CHINA		

No. of
Copies

F. D. Sowby
International Commission
on Radiological
Protection
Clifton Avenue
Sutton, Surrey
ENGLAND

Mrs. A. M. Beau, Librarian
Commissariat à l'Energie
Atomique
Département de Protection
Sanitaire
BP 6, F-92260
Fontenay Aux Roses
FRANCE

Librarian
Centre d'Etudes
Nucleaires de Saclay
P.O. Box 2, Saclay
Fig-sur-Yvette (S&O)
FRANCE

J. C. Nenot
Comite de Radioprotection
69, Rue de Micromesnil
75008 Paris,
FRANCE

M. Rzekiecki
Commissariat à l'Energie
Atomique
Centre d'Etudes
Nucleaires de Cadarache
BP n 13-St. Paul
Lès Durance
FRANCE

T. Jaakkola
University of Helsinki
Department of
Radiochemistry
Unioninkatu 35, 00170
Helsinki 17
FINLAND

A. R. Gopal-Ayengar
c/o P.K. Dayanidhi
15-D Gulmarg
Anushaktinagar
Bombay-400 094
INDIA

No. of
Copies

W. Jacobi
Institut für
Strahlenschutz
D-8042 Neuherberg
Ingolstadter
Landstrasse 1
FEDERAL REPUBLIC OF
GERMANY

L. Feinendegen
Director of Institute of
Medicine
Institut für Medizin
Kernforschungsanlage
Jülich
Postfach 1913
517, Jülich
FEDERAL REPUBLIC OF
GERMANY

Dr. rer. nat. Hans-Joachim
Klimisch
BASF Aktiengesellschaft
Abteilung Toxikologie
6700 Ludwigshafen
FEDERAL REPUBLIC OF
GERMANY

Dr. Vittorio Prodi
Department of Physics
University of Bologna
Via Irmerio 46
30126 Bologna
ITALY

T. Kumatori
Director
National Institute of
Radiological Sciences
4-9-1, Anagawa
Chiba-shi, Chiba 260
JAPAN

Kenjiro Yokoro, M.D.
Professor, Department
of Pathology
Director, Research
Institute for Nuclear
Medicine and Biology
Hiroshima University
1-2-3 Kasumi Minami-ku
Hiroshima
JAPAN

Z. M. Beekman
President of IRPA
Roosevelttlaan 197
1079 AP Amsterdam
THE NETHERLANDS

No. of
Copies

J. K. Basson
Vice-President
Raad Op Atomic
Atoomkrag Energy Board
Privaatsk X 256
Pretoria 0001
REPUBLIC OF SOUTH AFRICA

A Brink
Sasol-One Limited
P.O. Box 1
Sasolburg 9570
REPUBLIC OF SOUTH AFRICA

B. C. Winkler
Director, Licensing
(Standards)
Raad Op Atoomkrag/Atomic
Energy Board
Privaatsak X 256/
Private Bag X 256
Pretoria 001
REPUBLIC OF SOUTH AFRICA

E. Komarov
Environmental Health
Division
World Health Organization
Avenue Appia 1211
Geneva 27, SWITZERLAND

K. E. Lennart Johansson
National Defense Research
Institute
FOA 45 1
S-901-82
Umea, SWEDEN

M. J. Suess
Regional Officer for
Environmental Hazards
World Health Organization
8, Scherfigsvej
DK-2100
Copenhagen, DENMARK

D. Djuric
Institute of Occupational
& Radiological Health
11000 Beograd
Belgradska 29,
YUGOSLAVIA

<u>No. of Copies</u>	<u>No. of Copies</u>	<u>No. of Copies</u>
<u>ONSITE</u>	11 <u>Battelle Memorial Institute</u>	C. R. Hann R. Harty R. C. Liikala S. Marks R. P. Marshall J. E. Mendel N. F. Metting J. H. Miller J. E. Minor D. W. Murphy J. M. Nelson C. N. Newman L. L. Nichols J. M. Nielsen (5) R. E. Nightingale D. E. Olesen J. F. Park R. W. Perkins (10) A. M. Platt C. A. Ratcliffe W. D. Richmond W. C. Roesch G. F. Schiefelbein R. E. Schirmer (10) L. C. Schmid J. B. Schuette C. L. Simpson M. E. Stifter A. M. Sutey L. H. Toburen R. J. Traub B. E. Vaughan M. L. West W. R. Wiley L. D. Williams W. E. Wilson N. A. Wogman (10) Technical Information (5) Publishing Coordination (2)
4 <u>DOE Richland Operations Office</u>	A. H. Adelman A. D. Barker N. E. Carter L. L. German Librarian F. J. Milford R. S. Paul R. H. Poirier L. A. Rancitelli D. B. Shipler C. R. Vest	
P. F. Dunigan D. R. Elle H. E. Ransom/P. K. Clark F. R. Standerfer		
<u>Rockwell Hanford Operations</u>		
P. G. Lorenzini		
<u>UNC Nuclear Industries</u>	2 <u>Battelle-Washington DC Office</u>	
T. E. Dabrowski	G. Johnson S. Stryker	
2 <u>Westinghouse Hanford Company</u>	132 <u>Pacific Northwest Laboratory</u>	
R. O. Budd D. E. Simpson	R. W. Baalman (5) W. J. Bair (15) N. E. Ballou (5) L. A. Braby T. P. Chikalla J. E. Danko J. M. Davidson R. D. DuBois C. E. Elderkin S. J. Farmer W. D. Felix D. R. Fisher J. S. Fruchter (10) J. J. Fuquay W. A. Glass (10) R. H. Gray R. T. Hadley	
2 <u>Hanford Environmental Health Foundation</u>		
D. B. Breitenstein R. D. Gilmore		
8 <u>Battelle-Seattle</u>		
S. M. Nealey E. B. Perrin J. E. Rasmussen A. H. Schilling C. R. Schuller R. Skiklar M. E. Walsh M. T. Wood		