DIRECT CONVERSION OF LIGHT HYDROCARBON
GASES TO LIQUID FUEL

Report No. 27

Quarterly Technical Status Report
for
Third Quarter F.Y. 1991

Project Manager: R. D. Kaplan

Principal Investigator: M. J. Foral

Work performed under Contract No. DE-AC22-89PC89866

For

U. S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania

By

Amoco Oil Company
Research & Development Department
Post Office Box 3011
Naperville, IL 60566

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

JUN 17 1992

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

js

MAY 07 1992
2

FINAL QUARTERLY PROGRESS REPORT SUBMITTED TO:

1. George Cinquegrane (2 copies)
Contracting Officer's Representative
U.S. DOE/PETC
P.O. Box 10940
Pittsburgh, PA 15236
2. Dona G. Sheehan
Contract Specialist
U.S. DOE/PETC
P.O. Box 10940
Pittsburgh, PA 15236
3. Robert M. Hamilton
FE-231, E-155/GTN
U.S. Department of Energy
Washington, DC 20545
4. Gilbert V. McGurl
Program Manager
U.S. DOE/PETC, MS 922-H
P.O. Box 10940
Pittsburgh, PA 15236

ADDITIONAL CIRCULATION FOR DRAFT REPORTS TO:

Amoco Corporation
Suite 600
305 East Shuman Boulevard
Naperville, IL 60563-8408
T. H. Fleisch

Amoco Oil Company
P.O. Box 3011
Naperville, IL 50566
R. D. Kaplan, H-4
M. J. Foral, H-4
A. R. LaPuma, H-4
D. W. Washecheck, H-2
D. B. Lerman, H-1
E. G. Wollaston, H-3
A. S. Couper, H-1
J. A. Mahoney, F-7

TABLE OF CONTENTS

	<u>Page</u>
EXECUTIVE SUMMARY	7
BACKGROUND	8
PROGRAM OBJECTIVES	9
PROJECT DESCRIPTION	9
RESULTS AND DISCUSSION	10
Task 3.4: Effect of Product Quench.....	11
Task 3.5: Effect of Reactor Geometry.....	11
Task 3.6: Effect of Reactor Recycle.....	16
Effect of Carbon Dioxide Addition.....	16
Effect of Hydrogen Addition.....	20
CONCLUSIONS	26
ACKNOWLEDGEMENT	28

LIST OF FIGURES

- FIGURE 1 Effect of Oxygen Concentration on Hydrocarbon Conversion
- FIGURE 2 Effect of Oxygen Concentration on Methanol Yield
- FIGURE 3 Effect of Oxygen Concentration on Methane Conversion
- FIGURE 4 Effect of Product Quench on Hydrocarbon Conversion
- FIGURE 5 Effect of Product Quench on Methane Conversion
- FIGURE 6 Effect of Product Quench on Methanol Selectivity
- FIGURE 7 Effect of Product Quench on Methanol Yield
- FIGURE 8 Effect of Reactor Packing on Methanol Selectivity
- FIGURE 9 Effect of Reactor Packing on Methanol Yield
- FIGURE 10 Effect of Added CO_2 on Methanol Selectivity
- FIGURE 11 Effect of Added CO_2 on CO Selectivity
- FIGURE 12 Effect of Added CO_2 on CO_2 Selectivity
- FIGURE 13 Effect of Added CO_2 on Formaldehyde Selectivity
- FIGURE 14 Effect of Added CO_2 on Hydrocarbon Conversion
- FIGURE 15 Effect of Added CO_2 on Methane Conversion
- FIGURE 16 Effect of Added CO_2 on Methanol Yield
- FIGURE 17 Effect of Added H_2 on Methanol Selectivity
- FIGURE 18 Effect of Added H_2 on Carbon Oxide Selectivity
- FIGURE 19 Effect of Added H_2 on Formaldehyde Selectivity
- FIGURE 20 Effect of Added H_2 on Oxygen-based Selectivity
- FIGURE 21 Effect of Added H_2 on Hydrocarbon Conversion
- FIGURE 22 Effect of Added H_2 on Methane Conversion
- FIGURE 23 Effect of Added H_2 on Methanol Yield
- FIGURE 24 Effect of Added H_2 on H_2 Production/Conversion

DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process or service by trade name, mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

TECHNICAL STATUS

This technical status report is being transmitted in advance of DOE review, and no further dissemination or publication will be made of this report without prior approval of the DOE Project/Program Manager.

EXECUTIVE SUMMARY

Amoco Oil Company, under a contract with the United States Department of Energy, is investigating the direct conversion of light hydrocarbon gases to liquid fuels via partial oxidation. This report describes work completed in the seventh quarter of the two-year project. Work continued and progress was made on three tasks during this quarter. In addition, a calculation error was detected and corrected, resulting in improved reproducibility of the results.

Correction of hydrocarbon conversion data: During ongoing efforts to identify and correct sources of experimental error, a calculation error was detected which slightly affected the hydrocarbon conversion and methanol yield values which we have reported in previous reports. Actual hydrocarbon conversion and methanol yield values are slightly lower than those that have been reported. Since this calculation error affected all runs in the same way, the trends observed in the previous work are unchanged, as are the primary conclusions drawn from this study. In addition, correction of this error has improved the reproducibility of the results significantly.

Task 3.4 (Studies of Different Product Quench Systems): Studies were made to test the effects of quenching the hot product gases on hydrocarbon conversion and product selectivity. No significant effects were found, as was anticipated based on earlier residence time studies.

Task 3.5 (Effect of Reactor Geometry): Evidence has been gathered that suggests that the surface-to-volume ratio (S/V) of the reactor vessel may have a strong influence on methanol selectivity at oxygen concentrations below about 5 vol%. Reactors with higher S/V give higher methanol selectivity. Increasing the S/V of a large-diameter reactor by packing it with quartz beads improved methanol selectivity at low oxygen levels (giving a maximum selectivity of around 40 mol%), but had no effect on selectivity at higher oxygen concentrations. These results could be due either to kinetic (wall) effects or to improved heat transfer in the high S/V reactors.

Task 3.6 (Effect of Reactor Recycle): Reactor feeds were spiked with CO₂ and H₂ (both reaction byproducts) to begin investigation of the effects of reactor recycle. Added CO₂ had no effect on either hydrocarbon conversion or product selectivity up to 20 vol% added CO₂. Added hydrogen tended to decrease methanol selectivity and yield, but had no effect on hydrocarbon conversion. Based on these studies, it appears that in a recycle operation the level of hydrogen in the recycle loop will stabilize at between 7 and 15 vol%.

BACKGROUND

Fischer-Tropsch synthesis, gasification processes like Lurgi dry bottom gas, direct coal liquefaction, and remote natural gas all represent sources of substantial quantities of light hydrocarbon gases. Methane is the major and most stable component of all these gases. Steam reforming methane to produce synthesis gas is capital-intensive because it is highly endothermic and requires severe reaction conditions. A process for direct conversion of light gases, especially methane, to methanol, gasoline, or other liquid fuels could be far superior.

Steam reforming is the first stage in traditional commercial methods for the production of liquid fuels. This first step produces synthesis gas:

The synthesis gas is then converted into methanol via a catalytic process.

Reaction 1 produces more hydrogen than required by reaction 2. The excess can either be utilized elsewhere in the case of a domestic refinery or, in the case of a remote operation, is lost. A third step could be the catalytic condensation of methanol to gasoline.

A more efficient route of converting light hydrocarbons would be to directly form methanol by partial oxidation.

Such a process could substantially reduce capital and energy requirements for methanol production. The methanol could be used as a fuel or a fuel blending component, as in the case of M80 fuels (80% methanol, 20% gasoline), or else converted into gasoline through well-known processes, such as MTG. A plant based on Reactions 1 and 2 followed by methanol condensation to gasoline has been built and is operating in New Zealand. However, the process is uneconomical if it were not for the New Zealand Government support. If a process for the direct conversion of light hydrocarbons to methanol is feasible, thereby eliminating the process steps shown by Reactions 1 and 2, then a gas-to-gasoline process could become economically viable.

A proposed process for converting light hydrocarbon gases directly to hydrocarbon liquids, e.g., methanol or formaldehyde, is not new. In 1932 Newitt and Haffner reported the formation of methanol, along with smaller amounts of formaldehyde and formic acid, in the high-pressure oxidation of methane.⁽¹⁾ The reaction was carried out in a static system at 360-393°C and 50-150 atm. The maximum methanol selectivity was ca. 22%; however, CH₄ conversion was only a few percent. More recently, Gesser, Hunter and co-workers have reported methanol selectivities up to 89% and yields of around 7%.⁽²⁾ However, other workers have in general been unable to reproduce these results.

- (1) D. M. Newitt, A. E. Haffner, Proc. R. Soc. London, Ser. A, 134, p. 591
- (2) H. D. Gesser, N. R. Hunter, Chem. Rev., 15(4), p. 235 (1985); H. D. Gesser, U. S. Patent 4,618,732, issued 10/21/86.

PROGRAM OBJECTIVES

The objective of this program is to investigate the direct conversion of light gaseous hydrocarbons, such as those produced during Fischer-Tropsch synthesis or as a product of gasification, to liquid transportation fuels via a partial oxidation process. The process will be tested in an existing pilot plant to obtain credible mass balances. Specific objectives to be met include determination of optimal process conditions, investigation of various processing options (e.g. feed injection, product quench, and recycle systems), and evaluation of an enhanced yield thermal/catalytic system. Economic evaluation of the various options will be performed as experimental data become available.

PROJECT DESCRIPTION

The project is of two years' duration and contains three major tasks. The third task (Pilot Plant Experiments) contains seven subtasks, corresponding to the project objectives outlined above. The tasks and subtasks foreseen when the project began are described below.

Task 1.--Project Management Plan: A plan will be prepared describing the work to be done, milestones, and manpower requirements and cost..

Task 2.--Pilot Plant Modification: An existing pilot plant dedicated to investigation of light hydrocarbon conversion will be modified to provide it with the capability to handle the processes and conditions of this program. These modifications will include construction of a new reactor, construction and installation of reactant injection and product quench systems, and, possibly, addition of a product recycle loop to the unit.

Task 3.1.--Comparison of Preliminary Data With Los Alamos Model: We will determine if the kinetic model developed by Los Alamos National Laboratory can be used to guide our experimental effort. Results from this task will be carefully analyzed and will determine the direction of the subsequent experimental program. This is a major decision point in the project.

Task 3.2.--Pressure/Temperature/Reaction Time Effects: The methane conversion data base will be extended over the following range of conditions:

Temperature:	600 to 1100 F
Pressure:	200 to 1300 psig
Reaction Time:	3 to 90 seconds

These experiments will be guided by the results of Task 3.1 to those process regimes which appear most promising.

Task 3.3.--Study of Different Injection Systems: Different schemes for introducing and mixing reactants before or within the reactor will be evaluated theoretically and/or experimentally. The goal will be to maximize methanol yield.

Task 3.4.--Study of Different Quench Systems: The efficacy of different product cooling techniques will be investigated to determine the effect of quenching on product composition and methanol yield. Both gas and liquid quench options will be investigated.

Task 3.5.--Effect of Reactor Geometry: The effect of reactor geometry, particularly aspect (i.e. length/diameter) ratio, will be investigated to determine mass transfer and mixing effects on product composition and methanol yield.

Task 3.6.--Effect of Reactor Recycle: The effect of recycling unreacted hydrocarbons to the reactor inlet will be evaluated first by appropriately blending the feed stream to simulate reactor recycle. If these results are promising relative to methanol production, a recycle compressor and recycle line will be added to the pilot plant for more detailed tests.

Task 3.7.--Enhanced-Yield Catalyst Study: An attempt will be made to develop a combined thermal/catalytic process in which byproduct carbon monoxide and hydrogen from the thermal process is converted to methanol over a heterogeneous catalyst. Such a combined process may provide higher methanol yields than the thermal process alone.

Reporting will be done periodically throughout the duration of the project according to DOE guidelines.

RESULTS AND DISCUSSION

During this quarter, work was performed on Tasks 3.4 (Study of Different Quench Systems), 3.5 (Effect of Reactor Geometry), and 3.6 (Effect of Reactor Recycle). In addition, reported hydrocarbon conversion calculations were found to be in error and were corrected, resulting in improved reproducibility in the conversion and yield values. These topics are discussed in detail below.

Correction of Previously-Reported Hydrocarbon Conversion Values: While the reproducibility of the conversion and selectivity data obtained in this study have been quite good, an ongoing effort is being made to identify and minimize the sources of experimental error. In the course of these efforts, it was discovered that the computer program used previously to calculate hydrocarbon conversion in our experiments has overestimated the true conversion values typically by about 5-8 absolute percent. This overestimation also resulted in methanol yield values that were typically overstated by about 2-3 absolute percent. Methane conversion values and all selectivity data have been correct as reported.

This calculation error does not affect the overall conclusions drawn from our previous studies. Figures 1 and 2 present the revised hydrocarbon conversion and methanol yield values as a function of oxygen concentration at standard reaction conditions. The corresponding plot of methane conversion (Figure 3) needs no revision, but is included for completeness. Comparison of Figures 1 and 2 with previously reported data indicate that correcting this calculation error greatly improves the reproducibility of the hydrocarbon conversion and methanol yield data. The standard deviation of the hydrocarbon conversion values was reduced from 1.6 to 0.4 absolute percent. The standard deviation of the methanol yield values also decreased by about a factor of four; from 0.7 to 0.2 absolute percent. A series of plots is currently being prepared using the revised hydrocarbon conversion data. These plots will replace and supersede certain figures included in previous reports on the effect of temperature, pressure, oxygen concentration, residence time, reactor diameter, and mixer type on hydrocarbon conversion and methanol yield. All the plots contained in this report contain correct hydrocarbon conversion data.

Study of Different Quench Systems (Task 3.4): Scoping studies have been completed on the effects of product quench. The current pilot plant design utilizes an external cooling water quench located just downstream of the heated reaction zone. Series of experiments of varying oxygen concentration were run both with and without this cooling water quench system operating. The results of these experiments are presented in Figures 4-7. There is no observable effect of the cooling water quench on conversion (Figures 4 and 5), product selectivity (Figure 6), or methanol yield (Figure 7). Since relatively long residence times (20-60 seconds) were found to be optimal, it was not expected that rapid quenching of the products would have any significant effect on this system. In these experiments gas flow rates were adjusted to achieve a residence time of 55 seconds (with the quench on). Based on temperature profiles observed in the reaction and quench zones, running without the cooling water quench caused the product gases to see kinetically significant temperatures (i.e. $T > 650^{\circ}\text{F}$) for about 65 seconds. This is only 10 seconds longer than with the quench operating, leaving the product distribution essentially unchanged. These results corroborate the residence time studies reported in the August 1990 report. Based on these results, there are no plans to study quench effects further.

Effect of Reactor Geometry (Task 3.5): An intriguing result from the earlier studies of reactor geometry (reported in December 1990) was that, in a larger diameter reactor, methanol selectivity exhibited a clear maximum at around 5 vol% oxygen. At lower oxygen levels methanol selectivity decreased sharply. This behavior was the opposite of that observed in smaller diameter reactors, where methanol selectivity increased monotonically with decreasing oxygen concentration. In order to probe this phenomenon more closely, a series of runs was made in which the large-diameter reactor was packed with quartz beads. In this way reactor diameter and surface-to-volume ratio were effectively decoupled.

Figure 1

Effect of Oxygen Concentration on HC Conversion

P=1300 psig, T=800 F, Res. Time=10-60 sec.

Hydrocarbon Conversion (mol%)

Figure 2

Effect of Oxygen Concentration on MeOH Yield

P=1300 psig, T=800 F, Res. Time=10-60 sec.

Methanol Yield (mol%)

Figure 3

Effect of Oxygen Concentration on CH₄ Conversion
P=1300 psig, T=800 F, Res. Time=10-60 sec.

Methane Conversion (mol%)

Figure 4

Effect of Product Quench on Hydrocarbon Conv.
T=800 F; P=1300 psig; 25mm Reactor Diameter

Hydrocarbon Conversion (mol%)

Figure 5

Effect of Product Quench on Methane Conversion
T=800 F; P=1300 psig; 25mm Reactor Diameter

Methane Conversion (mol%)

Figure 6

Effect of Product Quench on Methanol Selectivity
T=800 F; P=1300 psig; 25mm Reactor Diameter

Methanol Selectivity (mol%)

Figure 7

Effect of Product Quench on Methanol Yield
T=800 F; P=1300 psig; 25mm Reactor Diameter
Methanol Yield (mol%)

Figures 8 and 9 present results of a series of packed bed and open tube runs with different oxygen concentrations. Figure 8 clearly shows the maximum in methanol selectivity with the large diameter (30mm) reactor, and indicates that packing the large diameter reactor makes it behave more like the smaller (11mm diameter) reactor. Figure 9 indicates that methanol yields in the packed reactor are not significantly different than those in the open (unpacked) reactors. This is because at lower oxygen concentrations, where the selectivity difference is greatest, hydrocarbon conversion and therefore methanol yield are extremely low. Calculated surface-to-volume ratios were 1.4 cm^{-1} for the large reactor, 6.4 cm^{-1} for the small reactor, and between 10 and 18 cm^{-1} for the packed reactor (depending on how much of the bead surface was accessible).

At this stage it appears that reactor surface-to-volume ratio may be an important reactor design parameter, especially at low oxygen (high selectivity) conditions. Higher surface-to-volume ratios seem to increase methanol selectivity at low (<5 vol%) oxygen concentrations. There are two possible explanations for this. One is that there is a kinetic (wall) effect that stabilizes methanol-producing intermediates at low oxygen concentrations. Another possibility is that heat transfer is better in the high S/V reactors. If this were the case, the reaction exotherm would cause the internal temperature of the reactor to be higher in low S/V reactors. High reaction temperatures ($T > 900^\circ\text{F}$) have been shown to be detrimental in previous studies. Actual measurements of internal temperature have been inconclusive because they are taken at discrete points in the reactor which may not correspond to the reactor hot spot.

Effect of Reactor Recycle (Task 3.6): A series of runs is being completed in which various product gas species (CO_2 , CO and H_2) are added to the natural gas feed to simulate the effects of reactor recycle. In the initial runs, these product gases have been individually added to the feed to determine their fate in the reactor and any effects they may have on conversion or product selectivity. In later runs, mixtures of these gases will be simultaneously added to simulate a true mixed feed/recycle stream. Experiments have been completed in which various levels of CO_2 , CO and H_2 were added to the reactor feed at a number of oxygen concentrations. Results obtained for CO_2 and H_2 addition are reported here. The effects of added CO are currently being analyzed and will be presented in future reports.

Addition of CO_2 : As indicated in Figures 10-13, the addition of 5-20 vol% CO_2 to the reactor feed has a negligible effect on product selectivity and feed conversion. Figure 10 compares methanol selectivity in runs with feeds containing 0, 5, 10 and 20 vol% added CO_2 . Methanol selectivity appears to be slightly (2-3 abs%) lower in the presence of added CO_2 at all oxygen concentrations. However, given the level of scatter in the data, this difference is only statistically significant (>90% confidence) at 12.5 vol% oxygen. At lower oxygen concentrations the level of scatter in the data dilutes the statistical significance of any CO_2 effect, rendering it indistinguishable from experimental error. Figures 11 and 12 show the effects of added CO_2 on

Figure 8

Effect of Reactor Packing on MeOH Selectivity

T=800F; P=1300 psig; R.T.=40-80 seconds

Methanol Selectivity (mol%)

Figure 9

Effect of Reactor Packing on Methanol Yield

T=800 F; P=1300 psig; R.T.=40-80 seconds

Methanol Yield (mol%)

Figure 10

Effect of Added CO₂ on Methanol Selectivity

P=1300 psig, T=800 F, RT=40-50 sec.

Methanol Selectivity (mol%)

No added CO₂ 5% CO₂ in feed 10% CO₂ in feed 20% CO₂ in feed

Figure 11

Effect of Added CO₂ on CO Selectivity

P=1300 psig, T=800 F, RT=40-50 sec.

CO Selectivity (mol%)

No added CO₂ 5% CO₂ in feed 10% CO₂ in feed 20% CO₂ in feed

Figure 12

Effect of Added CO₂ on Net CO₂ Selectivity

P=1300 psig, T=800 F, RT=40-50 sec.

Net CO₂ Selectivity (mol%)

No added CO₂ 5% CO₂ in feed 10% CO₂ in feed 20% CO₂ in feed

Figure 13

Effect of Added CO₂ on Formaldehyde Selectivity

P=1300 psig, T=800 F, RT=40-50 sec.

Formaldehyde Selectivity (mol%)

No added CO₂ 5% CO₂ in feed 10% CO₂ in feed 20% CO₂ in feed

net CO and CO₂ selectivity, respectively. They indicate that addition of 0-20 vol% CO₂ to the feed gas has no apparent effect on CO_x selectivity. There is considerable scatter in these data, particularly at high levels of CO₂ addition and low oxygen concentrations. This occurs because under these circumstances the added CO₂ accounts for a majority of the carbon oxide in the product. Calculated CO_x selectivities therefore depend on a small difference between two large numbers, leading to large experimental errors. Figure 13 further shows that formaldehyde selectivity in these systems is low (0-3 mol%) and is unaffected by the addition of CO₂.

In addition, conversion of the hydrocarbon feed is not affected by adding CO₂ to the feed gas, as shown in Figures 14 (hydrocarbon conversion) and 15 (methane conversion). Finally, Figure 16 indicates that methanol yield is also not affected by CO₂ levels up to 20 vol%. The data presented above conclusively show that the presence of up to 20 vol% CO₂ in the feed has no effect on product selectivity or feed conversion in this system.

Addition of H₂: Following the CO₂ addition studies, feeds were spiked with varying levels (3-15 vol%) of hydrogen gas. Again, various oxygen concentrations were used in these runs. Methanol selectivity is considerably lower in the presence of added hydrogen, especially at lower oxygen concentrations (Figure 17). Moreover, it appears that the higher the level of H₂ in the feed, the lower the methanol selectivity in the reactor. For example, adding 15 vol% hydrogen to the feed lowered methanol selectivity by 5-15 mol%, while adding 3 vol% H₂ lowered selectivity by only around 2 mol%. Figure 18 shows that the decrease in methanol selectivity is accompanied by an increase in selectivity to carbon oxides (CO and CO₂). There is no change in formaldehyde selectivity with hydrogen addition, as shown in Figure 19.

Figure 20 shows the oxygen-based selectivity values for methanol and water, clearly indicating that adding hydrogen to the reactor feed increases the amount of feed O₂ that ends up as water. From this it can be postulated that oxygen reacts with hydrogen in the reaction zone. It is somewhat surprising, then, that hydrocarbon conversion in general and methane conversion in particular appear to be unaffected by hydrogen addition to the feed (Figures 21 and 22, respectively) up to levels of 15 vol%. This suggests that, though oxygen apparently reacts with gaseous hydrogen, it does not directly produce water:

Instead it probably produces free radical species which can further react, involving methane (and other hydrocarbons) in the chain. One possible reaction between hydrogen and oxygen produces a hydrogen and hydroperoxy radical

Figure 14

Effect of Added CO₂ on Hydrocarbon Conversion

P=1300 psig, T=800 F, RT=40-50 sec.

Hydrocarbon Conversion (mol%)

No added CO₂ 5% CO₂ in feed 10% CO₂ in feed 20% CO₂ in feed

Figure 15

Effect of Added CO₂ on Methane Conversion

P=1300 psig, T=800 F, RT=40-50 sec.

Methane Conversion (mol%)

No added CO₂ 5% CO₂ in feed 10% CO₂ in feed 20% CO₂ in feed

Figure 16

Effect of Added CO₂ on Methanol Yield

P=1300 psig, T=800 F, RT=40-50 sec.

Methanol Yield (mol%)

No added CO₂ 5% CO₂ in feed 10% CO₂ in feed 20% CO₂ in feed

Figure 17

Effect of Added H₂ on Methanol Selectivity

P=1300 psig, T=800 F, RT=40-50 sec.

Methanol Selectivity (mol%)

Figure 18

Effect of Added H₂ on CO_x Selectivity

P=1300 psig, T=800 F, RT=40-50 sec.

CO_x Selectivity (mol%)

No added H₂ 3% H₂ in feed 7% H₂ in feed 15% H₂ in feed

Figure 19

Effect of Added H₂ on Formaldehyde Selectivity

P=1300 psig, T=800 F, RT=40-50 sec.

Formaldehyde Selectivity (mol%)

No added H₂ 3% H₂ in feed 7% H₂ in feed 15% H₂ in feed

Figure 20

Effect of Added H₂ on Oxygen Selectivity

P=1300 psig, T=800 F, RT=40-50 sec.

Oxygen Selectivity (mol%)

No added H₂ 3% H₂ in feed 7% H₂ in feed 15% H₂ in feed

Figure 21

Effect of Added H₂ on Hydrocarbon Conversion

P=1300 psig, T=800 F, RT=40-50 sec.

Hydrocarbon Conversion (mol%)

No added H₂ 3% H₂ in feed 7% H₂ in feed 15% H₂ in feed

Figure 22

Effect of Added H₂ on Methane Conversion

P=1300 psig, T=800 F, RT=40-50 sec.

Methane Conversion (mol%)

While the ΔH of this reaction at standard conditions (298°K) is large and positive, it is quite similar to that for the initial reaction of methane and oxygen

which occurs readily at reaction temperatures. The products of reaction (2) could either initiate reactions with hydrocarbons themselves, or they could recombine to form hydroxyl radicals

which could in turn initiate reactions with hydrocarbon species. Whatever the fundamental kinetic pathway, adding hydrogen to the feed appears have a negligible effect on the level of hydrocarbon conversion in this system.

The effects of added hydrogen on methanol selectivity and hydrocarbon conversion combine in such a way that overall methanol yield is lowered upon addition of hydrogen to the reactor feed (Figure 23).

At typical reaction conditions (without hydrogen addition), H_2 has been observed to be a product of the methane partial oxidation reaction. This being the case, the above results suggest that recycling the unreacted gases from the methanol recovery section will serve to lower per-pass methanol selectivity and yield since hydrogen would build up in the recycle stream. However, we would expect addition of hydrogen to the reactor feed to affect the production of hydrogen in the reactor itself. Figure 24 illustrates this effect with data from these studies, showing how the level of H_2 in the feed affects the net yield of hydrogen in the reactor. It can be seen that at concentrations up to about 7 vol% hydrogen in the feed, H_2 is still a net product of the reaction at all oxygen concentrations. At the 15 vol% H_2 level, however, there is net consumption of hydrogen at every oxygen concentration. This suggests that in a steady state recycle operation, the hydrogen concentration at the reactor inlet should stabilize at a value somewhere between 7 and 15 vol%. The extent of the yield penalty in this hydrogen concentration range will depend somewhat on the level of oxygen in the reactor feed, but should fall between 0.1 and 0.5 abs% (from Figure 23).

CONCLUSIONS

Four conclusions can be drawn from the above results:

1. There is no significant effect of quenching the hot reaction gases in this system. Both feed conversion and product selectivity were unchanged when the existing quench system was disabled. Given the relatively long residence times employed in these studies (10-60 seconds), this result is not surprising.

Figure 23

Effect of Added H₂ on Methanol Yield
 P=1300 psig, T=800 F, RT=40-50 sec.

Methanol Yield (mol%)

No added H₂ 3% H₂ in feed 7% H₂ in feed 15% H₂ in feed

Figure 24

Effect of Added H₂ on H₂ Production/Conversion
 P=1300 psig, T=800 F, RT=40-50 sec.

H₂ Production (+) and Conversion (-) (mmol/hr)

No added H₂ 3% H₂ in feed 7% H₂ in feed 15% H₂ in feed

2. The surface-to-volume ratio of the reactor vessel seems to have a strong influence on methanol selectivity at oxygen concentrations below about 5 vol%. The large diameter (low S/V) reactor had lower methanol selectivity than reactors with higher S/V. When this reactor was packed with quartz beads (increasing S/V) methanol selectivity increased to become equal with the other reactors. It is not clear if this is due to kinetic (wall) effects, or to improved heat transfer in the high S/V reactors.
3. The presence of up to 20 vol% CO₂ in the reactor feed had no observable effect on feed conversion or product selectivity.
4. Adding H₂ to the feed decreased methanol selectivity. This decrease appeared to be proportional to the level of H₂ in the feed (up to 15 vol% H₂). Hydrocarbon conversion was not affected by the presence of H₂ over the range studied (3 - 15 vol% H₂). At up to 7 vol% added hydrogen in the feed, H₂ remained a net product of the reaction, while at 15 vol% hydrogen in the feed, there was net consumption of H₂ in the reactor. This suggests that in a full recycle mode, H₂ would build up in the recycle loop to levels between 7 and 15 vol%.

ACKNOWLEDGEMENT

This work was supported by the United States Department of Energy under Contract DE-AC22-89PC89866.

NOTICE

This report was prepared by the organization(s) named below as an account of work sponsored by the United States Department of Energy (DOE). Neither DOE, members of DOE, the organization(s) named below, nor any person acting on behalf of any of them: (a) makes any warranty, express or implied, with respect to the use of any information, apparatus, method, or process disclosed in this report or that such use may not infringe privately owned rights; or (b) assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method, or process disclosed in this report.

Prepared by
Amoco Oil Company (Amoco Corporation)
Naperville, Illinois

MJF/sjm/doe9120a
7/31/91

**DATE
FILMED
8 / 18 / 92**