Effects of Catalytic Mineral Matter on CO/CO₂,
Temperature and Burning Time for Char Combustion

DE-FG22-89PC89774

Prof. John P. Longwell
Prof. Adel F. Sarofim

Chun-Hyuk Lee
A. J. Modestino

Quarterly Progress Report No. 10

January - March 1992

Prepared for

Norey B. Laug
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940, MS 921-165
Pittsburgh, Pennsylvania 15236-0940

by

Massachusetts Institute of Technology
Department of Chemical Engineering
Cambridge, MA 02139

MASTER

ds
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MAY 14 1962

Introduction

The high temperature oxidation of char is of interest in a number of applications in which coal must be burned in confined spaces. These include: the conversion of oil-fired boilers to coal using coal-water slurries, the development of a new generation of pulverized-coal-fired cyclone burners, the injection of coal into the tuyeres of blast furnaces, the use of coal as a fuel in direct-fired gas turbines in large-bore low-speed diesels, and entrained flow gasifiers. In addition, there is a need to better understand the temperature history of char particles in conventional pulverized-coal-fired boilers in order to better understand the processes governing the formation of pollutants and the transformation of mineral matter.

The temperature of a char particle burning in an oxygen containing atmosphere is the product of a strongly coupled balance between particle size and physical properties, heat transfer from the particle, surface reactivity, CO/CO_2 ratio and gas phase diffusion in the surrounding boundary layer and within the particle. In addition to its effects on burning rate, particle temperature has major effects on ash properties and mineral matter vaporization. Measurements of the temperature of individual burning char particles have become available in recent years and have clearly demonstrated large particle to particle temperature variations which depend strongly on particle size and on particle composition. These studies, done with pulverized coal, do not allow direct determination of the CO/CO_2 ratio produced at the char surface or the catalytic effects of mineral matter in the individual char particles and it has generally been assumed that CO is the only product of the carbon-oxygen reaction and that CO_2 is formed by subsequent gas phase reaction. More recent work, however, has pointed out the need to take CO_2 production into consideration in order to account for observed particle temperatures.

The importance of the CO/CO₂ ratio of carbon oxidation products is illustrated by examination of the heats of reaction for formation of these two products

The heat released by formation of CO₂ is a factor of 3.5 higher than for CO so the temperature of a particle will depend strongly on the CO/CO₂ ratio produced. If gas diffusion through the boundary layer is fast, increased direct production of CO₂ produces a higher temperature and a higher burning rate. If the supply of oxygen to the surface is limited by diffusion through the boundary layer, production of CO₂ consumes half as much carbon as production of CO so carbon consumption rate is reduced even though temperature may be somewhat higher. Models of these complex interactions have been developed; however, the CO/CO₂ ratio produced by the carbon-oxygen reaction must, at present be assumed or inferred from measurement of particle temperature.

CO₂/CO ratios can be strongly influenced by catalytic material in the carbon and by the char temperature. In this program we are measuring the CO₂/CO ratio for both catalyzed and uncatalyzed chars over a wide range of temperature. These results will then be used to develop predictive models for char temperature and burning rates. The electrodynamic balance has been successfully used to make such measurements for single 200 μm spherocarb particles. A few theoretical approaches to model a single particle oxidation have been made, but most of them assumed the infinitely thin reaction zone at the particle surface. This approach can not explain pore diffusion limitation, structural change, or reaction at low temperatures inside the particle. Too simplifying solid phase reaction may leads to wrong predictions. In this report, progress on constructing models including both solid and gas phase reaction are reported.

Results

(1) Modeling scheme

A preliminary model of the ignition temperature profile of a single particle was presented in the Progress Report No.4. A more precise model should include CO oxidation in the boundary layer. The heat of reaction of CO oxidation in the gas phase is 66.8 kcal/mol, therefore, the heat generation from this reaction may not be neglected. A set of equations describing the heat balance in the boundary layer was set up in Progress Report No.9. Based on the appropriate assumption that gas diffusion velocity is fast enough to neglect time dependent term of the gas phase governing equation, we can then write the governing equation as followings.

$$r^2 \rho_s v_r = \text{const} \quad (\text{Eq.1})$$

$$\rho_s v_r \frac{dY_i}{dr} = -\frac{1}{r^2} \frac{d}{dr} (r^2 \rho_s Y_i V_i) + R_i \quad (\text{Eq.2})$$

$$\rho_s C_{p,s} v_r \frac{dT}{dr} = \frac{1}{r^2} \frac{d}{dr} (r^2 \lambda_s \frac{dT}{dr}) - \rho_s \sum_{i=1}^n (Y_i V_i C_{p,i}) \frac{dT}{dr} - \sum_{i=1}^n R_i H_i \quad (\text{Eq.3})$$

All the terms like C_p , λ_g , V_i , ρ_g , v_r , R_i , H_i are functions of temperature and some are functions of concentration also. Because the temperature range we are going to consider may reach 2500K, it is not always a good assumption to represent these terms as constants or linear functions of temperature. Solving everything simultaneously, however, may be impossible or may require a tremendous amount of computational time. A better alternative approach is use an iterative scheme to evaluate these parameters.

Fig.1. Iterative scheme for solving a set of coupled nonlinear equations.

As seen in Fig.1, we can use the values of temperature and concentrations calculated one time scale before as a initial value to calculate these terms. Then we will get improved values for temperature and concentration. Iterations can be repeated until the error meets the limitation. Next one must match the solid phase and the gas phase models. We can use the convective heat transfer term to match the interface condition. From the results of the solid phase simulation we can get boundary conditions for solid-gas interface. Using these conditions we can solve gas phase model and compare the temperature gradient at the interface to the convective heat transfer term from the solid. After adjusting, we can solve solid phase again for better values. The schematic diagram is following.

Fig.2 Schematic diagram for modeling

(2) Calculation of ρ , v_r and B.C s

The density of the gas can be calculated by using the ideal gas law which is a good approximation ; however, a more accurate equation of state can be used if needed.

$$\rho = \frac{P}{\left(\sum Y_i / W_i\right) RT} \quad (\text{Eq.4})$$

Flows exist around a particle. Natural convection will be neglected, and only the radial flow due to Stefan flow will be considered in this study. A more advanced model may incorporate an equation of motion, but needs huge memory and computation time.

The radial velocity can be calculated from Eq.1.

$$r^2 \rho v_r = \text{const} = R_o^2 [\rho v_r]_{r=R_o} \quad (\text{Eq.5})$$

If we consider B.C. at $r=R_o$, the flux due to the Stefan flow calculated from net stoichiometry of the reaction.

$$[\rho v_r]_{r=R_o} = \sum r_c \gamma_i f_i \Delta v_i \quad (\text{Eq.6})$$

If we consider CO & CO₂ reaction in the solid phase, Δv for CO reaction is 1/2 and γ for CO is 28/12. Therefore, the radial velocity is

$$v_r = \frac{7 R_o^2 r_c f_{co}}{6 r^2 \rho} \quad (\text{Eq.7})$$

(3) Galerkin finite element method

To calculate the spatial dependence of temperature and concentration, it is necessary to use a numerical method capable of spatial discretization. Among many methods Galerkin finite method is well established for solving partial differential equations. First we need to define basis functions. The solution can be represented as a linear combination of these basis function. For higher accuracy, we can use higher order basis functions. Here, linear basis functions will be used for the simplicity and faster computation time. The space

domain will be divided by N elements and N+1 basis functions can be defined as in Fig. 3. These functions have a value of one at each node, but are zero at the other nodes.

● XY Coordinate

$$\Phi^1 = (1 - \epsilon)/2$$

$$\Phi^2 = (1 + \epsilon)/2$$

● Spherical Coordinate

$$\Phi^{i(+)}(r) = \frac{R_i(R_{i+1} - r)}{r(R_{i+1} - R_i)}$$

$$\Phi^{i(-)}(r) = \frac{R_i(r - R_{i-1})}{r(R_i - R_{i-1})}$$

Fig.3 Basis functions

By multiplying these basis functions to the governing equations and integrating weak formulations, we can get simple tridiagonal matrices. During integration, natural boundary conditions can be easily incorporated. Essential boundary conditions can be added by changing conditions at that node to satisfy condition.

(4) Calculation of thermodynamic and transport properties

For calculation of thermodynamic and transport properties including specific heat, enthalpy, multicomponent diffusion coefficient, thermal diffusion coefficient and thermal conductivity, it is necessary to develop subroutines to calculate these. Well built libraries exist for this purpose, we are going to use packages from Sandia National Laboratory.

Fig.4 Schematic diagram for thermodynamic and transport data

The thermodynamic and transport subroutine can be called from main program to calculate properties needed.

Future Program

During the next quarter modeling calculations will be made and analyzed for effects of important parameters like the surrounding temperature, particle diameter, and gas composition on the burning temperature, CO_2/CO , extinction behavior, and etc..

Nomenclature

[subscript]

'g' means gas mixture in the boundary layer

'i' means the i-th species in the gas mixture

[symbol]

$C_{p,g}$ specific heat at constant pressure

f_i i-th reaction fraction

H_i specific enthalpy

P pressure

R gas constant

R_i mass production rate

R_o particle radius

r radial coordinate

r_c carbon consumption rate [gC/cm²s]

T temperature of the gas phase

T_m mean temperature of boundary layer

T_o temperature at $t=0$

T_p particle temperature

t time

v_r fluid velocity in 'r' direction

V_i diffusion velocity of the 'i' th species

W_i molecular weight of i

Y_i mass fraction

γ_i g of i generated/g C consumed

λ_g thermal conductivity

Δv_i net stoichiometry of i-th reaction

ρ_g density of the gas mixture in the boundary layer

**DATE
FILMED
8/20/92**