DOE-PC-91308-2

DOE-PC-91308-2

Dist. Category UC-90

**PARTICULATE BEHAVIOR IN A CONTROLLED-PROFILE PULVERIZED COAL-FIRED
REACTOR: A STUDY OF COUPLED TURBULENT PARTICLE DISPERSION AND
THERMAL RADIATION TRANSPORT**

DOE/PC/91308--2

DE92 015506

Quarterly Technical Progress Report

For Period December 15, 1991 to March 14, 1992

Mardson Queiroz and Brent W. Webb

Brigham Young University

Provo, UT 84602

**Prepared for the United States Department of Energy
Pittsburgh Energy Technology Center (PETC)**

Under Contract No. DE-FG22-91PC91308

"US/DOE Patent Clearance is not required prior to
the publication of this document"

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

482

DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees nor any of their contractors, subcontractors, or their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would infringe privately owned rights.

FORWARD

This report summarizes technical progress during the first quarter (December 15, 1991 to March 14, 1992) of a three-year study conducted for the Department of Energy (DOE) under contract number DE-FG22-91PC91308. The principal investigators for this work are Dr. Mardson Queiroz and Dr. Brent W. Webb; Dr. Clifford Smith is the technical representative for DOE.

TABLE OF CONTENTS

	PAGE
DISCLAIMER	i
FORWARD	ii
ABSTRACT	iv
1. OBJECTIVES AND SCOPE	1
1.1 BACKGROUND	1
1.2 OBJECTIVES	1
1.3 TECHNICAL APPROACH	1
2. SUMMARY OF TECHNICAL PROGRESS	2
2.1 REACTOR REFURBISHMENT	2
2.2 TRANSMISSOMETER DEVELOPMENT	2
2.3 GRADUATE STUDENT RECRUITMENT	3
3. REFERENCES	4
4. APPENDIX	5

ABSTRACT

During the second quarter progress has been made in the following areas: preparation for reactor refurbishment, instrumentation development, and graduate student recruitment. Plans have been made for the refurbishment of the Controlled Profile Reactor this summer. The experimental testing will begin when NEPA approval has been obtained. Design work has been completed for the local transmissometer probe. The laser-based instrument, combined with the data from the PCSV probe will enable estimate of the local concentration of particulates below $0.5\ \mu\text{m}$ in size. Additionally, it will permit measurement of the temporal statistics of the local particulate number density. Finally, two Ph.D. students and two M.S. students, all with experience in combustion research have been recruited to work on the project.

1. OBJECTIVES AND SCOPE

1.1 BACKGROUND

Improved understanding of the fundamental processes involved in pulverized-coal combustion is needed to make the energy extraction more efficient and the combustion byproducts environmentally safe. While the characterization of the local particulate behavior (concentration, size, and velocity) is important to the understanding of virtually all processes in a pulverized coal-fired furnace, it influences in a more direct way the turbulent particle dispersion and thermal radiation heat transfer. Yet the local particulate dynamics have gone relatively unaddressed, primarily because of lack of adequate instrumentation to carry out such a study. With recent advances in optical techniques such an effort is now possible. This proposal seeks to characterize the local particulate concentration, velocity, and size distribution in a well-controlled, parametrically-varied laboratory-scale reactor using a new laser diagnostic technique. This newly-developed technique is the only one currently available for the investigation of aspherical particles. The particulate data will be collected simultaneously with local gas temperature and wall radiant heat flux distributions.

1.2 OBJECTIVES

This report describes recent progress in a fundamental, three-year investigation of the coupled problem of turbulent particle dispersion and thermal radiation transport. The project's objective is to make measurements of particle size, velocity, number density, temperature and wall radiant heat flux in a parametrically-controlled reactor presently existent at Brigham Young University (BYU). Although the study proposed here is primarily designed to provide experimental data not currently available for the evaluation of turbulent particle dispersion and radiation models, comparisons of analytical predictions and the experimental data obtained will be performed, using appropriate submodels integral to comprehensive pulverized-coal combustion codes existent at BYU.

1.3 TECHNICAL APPROACH

To accomplish the above objectives, the project is divided in the following tasks:

- Design and fabrication of a modified section for the BYU controlled-profile reactor, which will allow access of several probes to be used in the proposed study.
- Design and fabrication of a two-color pyrometer and cooled probe for local particulate temperature measurement.
- Characterization of the non-reacting turbulent flow field in the reactor using the PCSV-P probe, which will serve as an input during the turbulent particle dispersion submodel validation.
- Literature review dealing with particle dispersion and radiation transport in support of the model validation effort.

- Perform the parametrically-controlled measurements in the controlled-profile reactor.
- Experimental data analysis.
- A comprehensive comparison of experimental data and model predictions.
- Final report.

2. SUMMARY OF TECHNICAL PROGRESS

2.1 REACTOR REFURBISHMENT

Although the Controlled-Profile Reactor is designed and functioning, prior use has motivated the need for its refurbishment. While waiting for NEPA approval of the experimental tests, the reactor will undergo a replacement of worn components and an update of several existing systems. The refractory lining will be replaced, and the thermocouples that are currently potted directly into the reactor walls will be encased in ceramic sheaths that will allow individual thermocouple replacement and more accurate depth placement. This will permit more accurate measurement of wall temperatures, a parameter which is critical to the test program. Several wall heating elements, used to maintain near-isothermal reactor wall conditions but currently dysfunctional, will be replaced during the recasting process. Flexible cabling to the heaters will be used to replace the existing rigid electrical power couplings to minimize heater element breakage. Finally, new temperature data acquisition boards will be installed that allow sampling from all 180 wall temperature thermocouples. Reactor wall temperatures, air flow rates, and coal feed rates will be acquired, and closed-loop wall temperature control implemented by a single personal computer. Additionally, feedback control of the pulverized coal feeders is being considered to improve reactor controllability and flame stability.

2.2 TRANSMISSOMETER DEVELOPMENT

One objective of the experimental approach is the measurement of particle size distributions using the Insitec PCSV system. This laser-based system has a lower limit on its sizing capability of 0.5 μm . The transmissometer is being developed to provide capability for estimate of the particulate concentration below 0.5 μm . Additionally, using analysis currently being developed, time-resolved transmission measurements will permit determination of the particulate number density statistics. The transmissometer number density statistics will be compared to related measurements from the PCSV (Bonin, 1992). These corroborative measurements are vital to the analysis of the effect of turbulent particle dynamics on reaction rates and radiation heat transfer.

Figure 1 shows the proposed design for the transmissometer probe. A laser beam traverses a flow channel and is attenuated by the isolated particle cloud. The probe is being designed to accommodate the same water-cooled jacket as the PCSV. This will permit the same probe orientation to be used for both the PCSV and the transmissometer measurements. The probe will measure transmission through the diagnostic volume over two passes to increase the signal/noise ratio. The proposed measurement of the

Figure 1. Schematic of transmissometer probe.

sub-micron particulate concentration by difference with the PCSV data requires very accurate transmission measurements. The probe design calls for a reference detector and a signal detector. By ratio, the instantaneous transmission can be determined, accounting for potential fluctuations in laser output power. Data acquisition will be accomplished by simultaneous sample-and-hold of the two detector signals through a twelve-bit A/D board at a user-defined sampling frequency.

2.3 GRADUATE STUDENT RECRUITMENT

One high priority of the work for the past quarter has been the continued recruitment of Ph.D. students. Two Ph.D. students have now committed to work in the lab. The students both have experience in experimental combustion research. Two additional M.S. students, funded from other sources, will also work on the project. All but one of the students have been exposed to the operation of the Controlled Profile Reactor.

4. REFERENCES

Bonin, M.P. (1992). "Optical Measurement of Particle Size, Velocity and Number Density in Pulverized Coal Flames," Ph.D. Dissertation, Mechanical Engineering Department, Brigham Young University.

5. APPENDIX**REPORT DISTRIBUTION LIST**

Ms. Marilyn Keane
PM-01, MS 922-206
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

Ms. Rhonda L. Dupree
AD-22, MS 921-118
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

Office of Technology Transfer
Attn: Kay Downey
Mail Stop 58-M217
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940

Pittsburgh, PA 15236

Dr. Clifford Smith
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940

Pittsburgh, PA 15236

**DATE
FILMED
8/27/92**