QUARTERLY REPORT

Project No. DE-FG22-^{89PC-89782}~~89PC-89782~~

on

FIELD AND LABORATORY INVESTIGATIONS OF SELENIUM TRANSFORMATION

Submitted to

Mr. Jerry Harness, Project Officer
U.S. Department of Energy
Morgantown Energy Technology Center
Morgantown, WV 26507-0880

December 1, 1990

by

Asmare Atalay and Kurtis J. Koll

University of Oklahoma
Civil Engineering and Environmental Science
202 W. Boyd, Room 334
Norman, OK 73019

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

	Page
LIST OF TABLES	i.
LIST OF FIGURES	ii.
ABSTRACT	1
SITE DESCRIPTION	3
MATERIALS AND METHODS	11
Sample Collection	11
Field Study	12
Laboratory Adsorption/Desorption Mini-Column Study	19
EXPERIMENTAL PROCEDURES	23
Sample Preparation	23
Moisture Determination	23
Soil pH	24
Soil Digestion	24
Soil Extraction	25
Sample Analysis Using Atomic Absorption	25
Sample Analysis Using Ion Chromatography	26
DATA AND RESULTS	27
APPENDIX	30
REFERENCES	55

LIST OF TABLES

TABLE	Page
1. Soil media description for the adsorption/ desorption mini-column study	22
A. Field measurements taken from the Henryetta study area	31
B. Temperature variation with depth for each study site	50
C. pH variation with depth for each study site	51
D. Soil moisture variation with depth for each study site	52

LIST OF FIGURES

FIGURES	Page
1. The coal-producing areas of Northeastern Oklahoma	5
2. A road map system of Okmulgee County	6
3. A map illustrating the location of the data-collection site	7
4. A code, utilizing legal description, adapted from USGS to identify sampling sites and samples	8
5. The investigation site, color-coded, to show the 141 acres in the study site	9
6. An aerial photograph, circa 1983, of the study site prior to any reclamation	13
7. Graphical description of the coal-mining area with locations of the soil air tubes, Pt electrodes, tensionmeters and calomel reference electrode access tubes used for the field study	14
8. An illustration for the design and construction of the platinum electrode which is used with a calomel electrode to measure Eh in a subsurface environment	16
9. The series 2725 Jet Fill Tensiometer is used to measure soil moisture in centibars at designated depths in the subsurface environment	18
10. The diagram illustrates the anion chromatograph system representative of that used in the Dionex system	20
11. A peristaltic pump was used to maintain head, H, over a soil medium	21
12. Vertical profile of Se concentration in coal strip-mine overburden (Henryetta, Oklahoma)	28
13. Adsorption isotherm	29

ABSTRACT

With an increased awareness and renewal in alternate energy sources such as enhanced oil recovery and expanded use of existing coal reserves, it is imperative to further understand the role of man's activity upon potential environmental problems. Regulations and programs exist to productively reclaim mining sites. One criteria addressed by some mining regulations is a chemical parameter analysis, including selenium as potential hazard.

Selenium is a biologically essential element recognized as a metabolic requirement in trace amounts for animals. It is toxic to them when ingested in amounts ranging from about 0.1 to 10mg/kg of food. Accounts are recorded indicating a relationship between selenium and birth deformities in humans and also, for example, in birds. Determination of Se concentrations in several materials indicate Se is widely distributed. The common range for Se in soils is 0.1-2 ppm with the selected average 0.3 ppm (Lindsay, 1979).

Equilibrium provides a reference point for predicting which chemical reactions take place regardless of the kinetic implications. One such equilibrium reaction is the oxidation-reduction reaction involving the selenate-selenite transformation. Redox equilibria in soil solution are generally expressed in terms of Eh:

$$Eh \text{ (millivolts)} = 59.2 \text{ pe}$$

The equation is derived from equilibrium constant expressions and standard electrode potentials. For dissolved species, pH is also a useful variable for reactions in soil solution.

Surface mining and reclamation are activities which are regulated by the Surface Mining Control and Reclamation Act. One parameter addressed in some state regulatory criteria is the analysis of Se (usually expressed only as total Se) in the topsoil and overburden. Available Se is known to be responsible for deficiency diseases and poisonings. The Se species most readily available for plant uptake is selenate, depending on oxidation conditions of the soil environment. High oxidation potential, low pH, and oxic soils would establish selenate as the predominate species.

This quarterly report discusses the preparation and results of a field investigation of a selected coal mine site in Oklahoma. The field investigation has been on-going since July 1990. An analysis of this data would be useful in providing information for potential Se mobility from a coal mine site and the distribution of Se in a soil profile of reclaimed land. Also, included is the investigation and preliminary results of SeO_4^{2-} adsorption and desorption using different soil media, including coal mine spoils (overburden).

SITE DESCRIPTION

The investigation site chosen for this study is an abandoned strip mine consisting of several pits from which coal was once mined. Steep, narrow ridges line the pits where raw clay and shale were piled during mining operations. The pits have been filled with rain and run-off water. The surrounding area is not suitable for cultivation and is generally heavily wooded. The soils are recognized as unsuitable due to unfavorable texture; poor to somewhat excessive drainage; shallowness; medium to high water-holding capacity; and restricted root zone. Mining pits on both sides of Trudgeon Road have been partially reclaimed by the Oklahoma Department of Conservation. It is our understanding that reclamation was done by filling in the mining pit with spoil, compacted and subsequently covered with six inches of topsoil. The reclamation was initiated since Trudgeon Road in that vicinity was considered a driving hazard. The reclamation project was completed about three years ago. The reclaimed land had been seeded with grasses, but the stand of grasses seems poor. Casual observation indicates the topsoil has been eroded to less than two inches in some locations. Evidence of adverse erosion is also evident near the investigation site.

The site is located near Henryetta, Oklahoma, eighty-six miles east of Oklahoma City along Interstate 40. Once in Henryetta, one can arrive at the study site by traveling east of the intersection of Highway 75/62 and Trudgeon Road. It is 0.88 km from the intersection of Trudgeon Road to a graveled entrance to 141 acres of

privately-owned property. Figure 1 outlines the coal-producing areas of Oklahoma and identifies the Henryetta area. Figure 2 is a road map of Okmulgee County and Henryetta. Figure 3 is a drawing that gives the legal description of the property with respect to Henryetta. Eighty-three (83) acres of this property was accessible for mining operations. Figure 4 identifies the legal description of the property by special code which also will identify samples and measurements by code number.

The study area is 0.64 km north of Trudgeon Road and is described as mine spoils (Sm) by the Okmulgee County Soil Survey book. The property is in T.11N., R.13E., Section 8 (Figure 5). For the investigator's, it is worth noting Lake Henryetta to the southeast and Lake Eufala to the east of Henryetta. It is not that the selected field site poses any potential environmental hazard, but that proposed mining sites could potentially affect large surface impoundments. The coal mining operation on the field site was abandoned in the early 1950's (Mrs. Marler, Study Site Owner, personal communication, 1990). The study site was selected because it fulfilled the following criteria: (i) it consists of reclaimed mining land, spoils, and unmined areas (control); (ii) at least 45 years has elapsed since cessation of mining operations allowing time for mineral migration to equilibrate; and (iii) three years have elapsed since reclamation was completed also allowing time for equilibration of the soil environment from reclamation activity.

Figure 2. A road map system of Okmulgee County. The study site is about one mile east of Henryetta. Henryetta and the study site are outlined. (Courtesy of the County Assessor's Office, Okmulgee County)

Figure 3. A map illustrating the location of the data-collection site. A graphical legal description detailing the location of the property.

Figure 4. A code, utilizing legal description, adapted from USGS to identify sampling sites and samples.

Figure 5. The investigation site is color-coded. 141 acres in section 8 of T.11N., R.13E were exposed to surface mining until the early 1950's. Arrows direct attention to large surface impoundments (lakes).

The method for describing the location of a data-collection site is a partial legal description with an identification number added to provide a local number for each site. By this method, the location of the site is given as SW1/4 NE1/4, Sec 8, T.11N., R.13E. followed with an identification number. SW1/4 NE1/4, Sec 8 is replaced with alphabetic characters. The three selected data collection sites will be identified as

11N-13E-8 BC CON (1-9)

11N-13E-8 BC SPO (1-9)

11N-13E-8 BC REC (1-9)

where CON (1-9), SPO (1-9), and REC (1-9) describe one of nine data stations at each site. The three sites will be identified as CON (control), SPO (mine spoils) and REC (reclaimed land).

MATERIALS AND METHODS

The objectives of the laboratory experiments and field investigations are to evaluate (i) the migration characteristics of SeO_3^{2-} and SeO_4^{2-} through a soil mini-column affected by pH and Se concentration, (ii) the Se transformation in coal mine spoils as affected by controlled pH and oxidation-reduction potential and (iii) some environmental limitations for Se speciation at a mining site.

I. Sample Collection

Soil samples from the site were collected periodically at depths of 1 foot (30 cm), 3 feet (91 cm) and 5 feet (152 cm) from control, reclaimed and mine spoil sites. A power auger with a six-inch auger was used to sample from the appropriate depths at each site. A Hoffer tube was used to remove soil samples from the appropriate depth. Approximately 300 grams of wet soil was removed from each bore hole. Samples were placed in Ziploc® plastic bags and transported to the laboratory. Upon arrival, the samples were placed in plastic pans and air-dried. Soils were then mechanically ground and sieved, passing through a No. 10 sieve. The air-dried and <2 mm soil fraction from each is kept in Ziploc® plastic bags until needed for subsequent experiments. Replacement samples will be obtained from the field site as needed.

II. Field Study

The field parameters measured in the site investigation include (i) Eh, (ii) soil pH, (iii) soil moisture and (iv) soil temperature with the ambient air temperature. The three study areas (spoil, reclaimed and control) are identified at the site on a dated aerial photograph (Figure 6). The aerial photograph is prior to any reclamation. Trudgeon Road is east/west or left to right across the center. The larger mining sites along Trudgeon Road have since been reclaimed. On the photograph, the field sites are marked C, control; S, spoils; and R, reclaimed. Each field site will have nine platinum electrodes installed, each accompanied with a calomel reference electrode access tube; nine soil gas access tubes; and nine tensiometers (Figure 7). At each study area (spoils, reclaimed or control), three electrode combinations (platinum and reference), gas access tubes and tensiometers were installed at depths of 30 cm, 91 cm and 152 cm, respectively. During sampling, Eh measurement (in millivolts) were taken using a platinum electrode connected to a Fisher Accemet Model 955 Portable pH/MV Temperature Meter.

The platinum electrode was constructed as follows: a 2.2 cm, 18 gauge platinum wire was soldered to a Type RG-58U copper wire and cable from Radio Shack. Nine electrodes measuring 46 cm in length, nine 107 cm in length and nine 168 cm in length were attached to solderless BNC connectors containing the RG-58 coax cable. The connectors were adapted for use on the Fisher pH/MV/temperature meter. The reference electrode is a calomel electrode (catalog number 13-620-259, manufactured by Fisher Scientific. The calomel reference electrode attaches to the pH/MV meter by a pin jack. The com-

Figure 6. An aerial photograph, circa 1983, of the study site prior to any reclamation. R marks the reclaimed site, C the control site and S the mine spoils site.

Figure 7. Graphical description of the coal mining area with locations of the soil air tubes, Pt electrodes, tensiometers and calomel reference electrode access tubes used for the field study. (a) A distribution of the electrodes and access tubes for each site. (b) A graphical description of the electrodes and access tubes installed at varying depths.

plete assembly (Figure 8) for each platinum electrode, not only consists of solder 0.2 cm of platinum to the copper wire, but uses 3/32 inch shrink tubing ordered from Alpha Wire Corporation (Elizabeth, New Jersey) sealed around the solder joint to protect the connection from moisture and any subsequent corrosion. The coax cable end with the solder connection is inserted through a 1/4 inch hole drilled through a 5/8 inch dowel rod 7/8 inch in length. The platinum wire extends 2.0 cm beyond the dowel rod. The entire length of cable is pushed through 1/2 inch PVC Schedule 40 tubing. The dowel rod "plug" is glued with Elmer's® wood glue into the end of the PVC tubing. Each PVC tube used in the construction of the platinum electrodes is filled with paraffin wax to keep air and moisture from the electrode wire and connection. A second dowel rod "plug" is inserted at the top end of the PVC tube to seal the tube and support the coax cable. Appropriately sized PVC connections with 50 cm lengths of 3/4 inch PVC were employed to design a protective cap for the platinum electrode. When Eh measurements are taken the protective cap can easily be removed from the 1/2 inch PVC to expose a 16 cm length of coax cable with BNC connectors. The reference electrodes are inserted through 3/4 inch PVC at the same depth (30, 90 or 150 $\pm$ 2 cm as the platinum electrodes).

Soil moisture is measured using tensiometers from Soil Moisture Equipment Corporation (Santa Barbara, California). The 2725 series Jet Fill Tensiometer (Figure 9) is used to measure soil moisture potential at designated depths in the subsurface. Soil moisture is measured in centibars. Flooded or ponded conditions contribute to reducing conditions which support the transformation

Figure 8. An illustration for the design and construction of the platinum electrode which is used with a calomel electrode to measure Eh in a subsurface environment.

Figure 9. The series 2725 Jet Fill Tensiometer is used to measure soil moisture in centibars at designated depths the subsurface environment.

of selenate to selenite, the less soluble or less mobile form (Long, et al., 1990).

Soil pH was measured in the field by removing a soil sample from the same depths as are the air access tubes and electrodes. Samples were saturated with deionized water at an approximate volume ratio of 1:1. The pH was measured with a Fisher Accemet Model 955 Portable pH/MV Temperature Meter immediately upon return to the laboratory. After 72 hours the pH was again recorded. Also, pH was measured using air-dried, <2mm soil fractions. 10g of air-dry soil is placed into a 25-ml plastic beaker. 10 ml of deionized water is added to the soil fraction. The soil solution is stirred and left to settle for 30 minutes. pH readings are taken from the clear supernatant.

Soil temperature was taken by placing a Celsius thermometer in selected reference electrode access tubes representative of each depth. Ambient temperature taken 3 ft above the ground surface was also recorded at each study site.

Selected soil samples were analyzed for both SeO_3^{-2} and SeO_4^{-2} concentration and total Se. Digested samples were used to determine total selenium on a Model 951 Instrumentation Laboratory aa/ae Spectrophotometer equipped with a graphite furnace. Undigested water samples were analyzed for SeO_3^{-2} and SeO_4^{-2} using DIONEX AI-450 Ion Chromatograph with the DIONEX conductivity and variable wavelength detectors. Figure 10 schematically diagrams an ion chromatography system.

Figure 10. The diagram illustrates the anion chromatograph system representative of that used in the Dionex system. A typical chromatogram is shown illustrating peak identity. (Instrumental Methods of Analysis, Willard, Hobart H., et al, 6th edition, 1981).

III. Laboratory Adsorption/Desorption Mini-Column Study

100 grams of small particle sand and 100 grams of air-dried, <2 mm soil taken from the reclaimed site were each mixed with 100 ml of deionized water. To each sample was added 10 ml of 100 ppm selenite. The solutions were mechanically shaken for 24 hours. Analysis of a supernatant extract using ion chromatography indicated nearly 100 percent adsorption of selenite on the soil sample and essentially no adsorption on the sand. Thus, it became necessary to perform preliminary experiments using mini-columns (Figure 11) to study both adsorption and potential desorption of selenite on various soil media.

The preliminary experiments using the mini-column design included three types of soil media. Characteristics of the soil media used are described in Table 1. Two grams of the soil medium were placed on top of glass wool which was used to plug the bottom of the mini-column. The soil medium was first wetted with deionized water, then it was loaded with 1 ml of 267 ppm SeO_3^{2-} solution. Immediately, the soil was covered with distilled water (purified to 15.4 megaohm). A constant head of water was maintained using a peristaltic pump. Leachate was collected from each mini-column in 25-ml, acid-washed vial. The leachate collected was refrigerated at 4°C until analyzed on the ion chromatograph.

Figure 11. A peristaltic pump was used to maintain a constant head, H , over a soil medium. A glass wool plug sealed the mini-column. Leachate was collected at specified time intervals.

Table 1. Soil media description for the adsorption/desorption mini-column study.

NO.	SAMPLE	PARTICLE SIZE	SOIL DESCRIPTION
1.	sand	100 mesh	graded commercial sand, acid-washed and rinsed with DI water
2.	top soil	not measured	black soil sampled from the first six inches of topsoil (Cleveland County, Oklahoma)
3.	overburden	< 2mm	soil from the reclaimed site obtained from a depth of 90 cm (Okfuskee County, Oklahoma)

EXPERIMENTAL PROCEDURES

I. Sample Preparation

Calcareous and noncalcareous samples of soil/overburden material should be segregated prior to laboratory analysis. A few drops of 10% HCl were placed on selected soil samples to determine the presence of free carbonates in calcareous samples. Slight to violent effervescence indicates the presence of a calcareous soil. No effervescence was noted for any soil sample.

For a noncalcareous sample, the bulk of the soil sample was air-dried for 72 hours and ground using a Wiley Mill. The samples were passed through a 2-mm steel sieve, and the <2-mm fraction was collected and saved in zip lock bags until analysis.

II. Moisture Determination

Moisture determination of the air-dry soil was expressed as a percent. 5.00 grams of the soil fraction was weighed into a tared 100-ml Pyrex® beaker. The beaker and its contents were placed in an oven set at 105°C for 24 hours. The sample was removed and cooled in a desiccator for 60 minutes. After weighing on an analytical balance, the loss in weight was expressed as a percent of the oven-dry soil.

Undisturbed field samples were also analyzed for percent moisture content. 5.00 grams of the sample was weighed into a tared 100-ml Pyrex® beaker. The beaker and its contents were placed in an oven set at 105°C for 24 hours. The sample was removed and

cooled in a desiccator for 60 minutes. After weighing on an analytical balance, the loss in weight was expressed as a percent of the oven-dry soil.

III. Soil pH

Ten grams of air-dry, <2-mm fraction, disaggregated sample was weighed into a 50-ml plastic beaker. 10 ml of deionized (DI) water was added to the sample and the sample stirred. The suspension was allowed to equilibrate for 30 minutes with occasional stirring. After the clay fraction settled, pH readings were taken from the clear supernatant. Soil pH was measured in undisturbed field samples immediately upon arrival at the laboratory. Measurement of pH was also taken on samples that were allowed to air dry for 72 hours. The pH was taken using the Fisher pH/mv/temperature meter.

IV. Soil Digestion

Selected soil samples which are air-dry, disaggregated fractions were digested using the Tecator 1009 Digester. A 0.50 to 0.75 gram soil samples were placed in 100-ml digestion tubes. The 12 100-ml tubes, each with a digestion rod for uniform boiling, were placed in an aluminum block for even heating. A 5 ml volume of concentrated HNO_3 was added in each tube containing the soil sample and allowed to boil for 1 hour at 100°C . After cooling for 10 minutes, 10 ml of a 3:1 HNO_3 , H_2SO_4 mixture was added. The temperature was gradually increased to 220°C and remained there until a white residue appeared. The sample was diluted to 100-ml with DI water (15.4 megaohm). The

digested soil samples were stored in acid-washed, rinsed bottles at room temperature until analysis using atomic absorption.

V. Soil Extraction

Air-dried and pulverized soil samples were used for a water-soluble extraction of selenium species. One hundred grams of soil sample were weighed into a tared 1 pint glass jar. 100 ml of deionized water was added to the sample. The jar and contents were placed on a mechanical shaker for 24 hours at low speed. After 24 hours, the samples were allowed to settle and filtered using a vacuum filtration system. The filtrate collected was placed in acid-washed, rinsed bottles and stored in a refrigerator at 4°C until analysis on the ion chromatograph.

VI. Sample Analysis Using Atomic Absorption

The Model 951 Instrumentation Laboratory aa/ae Spectrophotometer equipped with a graphite furnace was used for analysis of digested samples. The following operational parameters were used: bandwidth - 2.0; wavelength - 196.0 nm; voltage setting - 700 v; current - 7 ma; injection delay - 7 sec; deposit time - 10 sec, and; temperature settings - 149°, 508°, 620° and 2550°. The integration was with peak height at 4.0 sec. One ml of each digested sample was diluted to 10-ml using a volumetric flask with 1 ml of 100 ppm Ni, 0.1 ml of 1:1 HNO₃, and DI water. Nickel was used as an interference matrix and the solutions were prepared from Ni reference solution, Fisher certified (cat. no. SN70-500) with the Ni as Ni(NO₃)₂. Standards were made from Se reference solution, Fisher certified (cat.

no. SS460-500) with the Se as SeO_2 . The nitric acid used was reagent ACS grade from Fisher Scientific. The standards prepared for total Se analysis were 0 ppb (blank), 10 ppb, 20 ppb, 40 ppb and 50 ppb. Each standard Se solution was prepared using 100-ml volumetric flasks to which had been added 10-ml of 100 ppm Ni and 1-ml of 1:1 HNO_3 .

VII. Sample Analysis Using Ion Chromatography

Extracted samples were diluted with DI water (>15.4 megaohm) as needed to use with the Dionex AI-450 Ion Chromatograph. Each sample was filtered with a micropore filter before injection. Anion species determined in each sample analyzed included Cl^- , SO_4^{2-} , SeO_3^{2-} and SeO_4^{2-} .

DATA AND RESULTS

Field data is tabulated in Table A found in the Appendix. Table B summarizes temperature variation with depth for each study site. Table C summarizes pH variation with depth for each study site. Table D summarizes soil moisture (centibars) variation with depth at each study site.

Table E is total Se concentration in overburden (mine spoils) taken from the Henryetta site. An analysis of all soil samples obtained from coal-mining area showed evidence of no Se in the samples except those taken from the mine spoils. The concentrations (mg/kg) of Se for each depth are tabulated in Table E. Figure 12 illustrates a vertical profile of Se concentration with depth.

Tabulated data for the adsorption studies conducted thus far are presented in Table F. The concentrations in ppm SeO_3^{2-} are listed for topsoil, sand, and overburden material. Figure 13 graphical displays an adsorption isotherm for the adsorption and apparent desorption of SeO_3^{2-} from sand, topsoil and overburden. It demonstrates that no adsorption of SeO_3^{2-} has occurred with sand. However, with both the overburden and topsoil, adsorption of SeO_3^{2-} has occurred, and was followed by an apparent desorption.

FIGURE 12.

Vertical profile of Se concentration in coal strip-mine overburden (Henryetta, Oklahoma)

FIGURE 13. ADSORPTION ISOTHERM

APPENDIX.

TABLE A. Field measurements taken from the Henryetta study area. The measurement components consist of pH, Eh, soil moisture content and temperature. Eh is recorded in millivolts (mv); temperature in °C; and soil moisture in centibars.

DATE/COMPONENT/ SURFACE TEMP./ SITE	DEPTH (cm)	1	2	3	4	5	6	7	8	9
<u>July 26, 1990</u>										
Reclaimed, 31°C										
Eh in mv	30	410	534	470	451	384	417	420	460	465
	90									
	150									
soil moisture (centibars)	30									
	90		19	15	66	54			80	
	150	25				4		4	14	
Control, 31°C										
Eh in mv	30			495	403		065	475		449
	90	367			390	409				
	150	335								
soil moisture	30									
	90		6	28		38		27	32	28
	150		10				9		14	

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
Mine Spoils, 31 °C									
Eh in mv	521	349	-114	440	365	345	376	441	500
soil moisture	54	40	12	15	41	9	12	12	5
							20		
July 31, 1990									
Reclaimed, 27 °C									
soil moisture	5	19	22	54	26	67	4	17	0
Control, 27 °C									
soil moisture		0	36		0		0	0	24
		9				6		9	
Mine Spoils, 27 °C									
soil moisture	59	44	1	76	48	11		4	4
							21		

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
<u>August 15, 1990</u>									
Reclaimed, 32 °C									
Eh in mv	414	494	465	396	460	483	457	319	451
30									
90									
150									
soil moisture									
30									
90		20		38		67	30	23	0
150	7				30		6		
Control, 27 °C									
Eh in mv	451		434	470		-007	-056		485
30									
90	384			441	387				
150									
soil moisture									
30		8	37		3			5	16
90							1		
150		9				4		3	
Mine Spoils, 32 °C									
Eh in mv	557	528	527	577	066	556	578	526	498
30									
90									
150									
soil moisture									
30			26			1		56	10
90	54	48		18	44		29		
150									

TABLE A. (continued)

<u>August 22, 1990</u>		1	2	3	4	5	6	7	8	9
Reclaimed, 31 °C										
Eh in mv	30	408	479	414	399	456	499	461		459
	90								321	
	150									
soil moisture	30			28		69	32	8	24	0
	90		22							
	150	8			30					
temperature	30	31.0								
	90	29.0								
	150	27.0								
Control, 34 °C										
Eh in mv	30			465				-176		489
	90	475			482		096			
	150	385			440	376				
soil moisture	30		14			9			4	14
	90			30				0		
	150		12				4		0	
temperature	30	28.0								
	90	26.0								
	150	24.0								

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
Mine Spoils, 37 °C									
Eh in mv	538	578	532	577	087		586		521
	30								
	90								
	150							561	
soil moisture									
	30		24		63	2		65	0
	90								
	150	51		19			31		
temperature									
	30								
	90								
	150								
<u>August 29, 1990</u>									
Reclaimed, 41 °C									
Eh in mv	416	464	377	403	482	519	293	332	506
	30								
	90								
	150								
soil moisture									
	30								
	90	22				0			0
	150								
pH									
	30								
	90								
	150								
	3.43								
	4.25								
	4.94								

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
temperature	30 90 150								
Control, 42 °C									
Eh in mv			493	484 422	367	207	188		454
soil moisture		26 12	24		16	7	6	12 2	12
pH	5.78 6.93 6.90								
temperature	30 90 150								
Mine Spoils, 41 °C									
Eh in mv	550	578	580	591	111	598	602	575	495
soil moisture	55	54	30	22	60	3		66	12
							42		

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
pH	30 90 150	3.91 4.04 4.19							
temperature	30 90 150	33.0 30.0 28.0							
<u>September 12, 1990</u>									
Reclaimed, 27 °C									
Eh in mv	30 90 150	391 484	376	399	284	537	397	-106	568
soil moisture	30 90 150		0		0	42		19	0
		8	22	33			10		
pH	30 90 150	4.25 4.24 4.16							
temperature	30 90 150	29.0 28.0 26.5							

TABLE A. (continued)

		1	2	3	4	5	6	7	8	9
Control, 32 °C										
Eh in mv	30			484				466		488
	90	448			445		211			
	150	354			431	373				
soil moisture	30		67			63			54	
	90			32				8	3	
	150		11				6			12
pH	30	5.26								
	90	6.09								
	150	6.24								
temperature	30	27.0								
	90	26.0								
	150	25.0								
Mine Spoils, 27 °C										
Eh in mv	30	534	564			118				505
	90				602		599	594	561	
	150			555						
soil moisture	30									
	90	63		67		65	2		0	20
	150		69		22			52		
pH	30	3.99								
	90	3.96								
	150	3.86								

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
temperature	30								
	90								
	150								
<u>September 24, 1990</u>									
Reclaimed, 22 °C									
Eh in mv	30	418	471	364	406	423	406		586
	90							319	
	150								
soil moisture	30								
	90								
	150	10	26	0	34	0	55	38	0
pH	30								
	90	4.66							
	150	4.37							
		4.54							
temperature	30								
	90	21.0							
	150	26.0							
		26.0							
Control, 25 °C									
Eh in mv	30	475	515	481	418	285			502
	90	472		406					
	150	398							

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
soil moisture									
30		2			0			2	
90									
150		10	40			2	0	0	12
pH									
30	6.43								
90	7.36								
150	6.23								
temperature									
30	27.0								
90	24.0								
150	24.0								
Mine Spoils, 24 °C									
Eh in mv									
30	521				197				536
90		583		605		607	602	559	
150			565						
soil moisture									
30	6		0		66			3	26
90	14								
150		75		24			55		
pH									
30	4.17								
90	4.01								
150	4.08								
temperature									
30	22.0								
90	27.0								
150	27.0								

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
<u>October 5, 1990</u>									
Reclaimed, 24 °C									
Eh in mv	370	454	374	420	399	596	-010	272	580
30									
90									
150									
soil moisture			18			0		0	
30		20						49	
90							60		
150	12				36		15		
pH	4.95								
30	5.15								
90	5.23								
150									
temperature	22.0								
30	23.5								
90	25.0								
150									
Control, 24 °C									
Eh in mv	434	499	491	423		260	061	512	
30	399		409						
90									
150									
soil moisture	16	44			10		1	4	14
30									
90	8					5		0	
150									

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
pH	6.95 6.30 6.65								
30									
90									
150									
temperature	22.0 23.0 22.0								
30									
90									
150									
Mine Spoils, 26 °C									
Eh in mv	493	537	555	586	206	589	572	550	517
30									
90									
150									
soil moisture	21		10		24	30		13	15
30									
90									
150		60		25		40			
pH	4.30 4.10 4.21								
30									
90									
150									
temperature	23.5 25.0 25.0								
30									
90									
150									
October 19, 1990									

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
Reclaimed, 17 °C									
Eh in mv	388	421	399	443	443	605	317	261	610
soil moisture	30								
	90								
	150								
soil moisture	30								
	90								
	150								
pH	4.22								
	3.99								
	4.48								
temperature	17.0								
	18.9								
	20.5								
Control, 16 °C									
Eh in mv	467		482	492		309	018		520
	413			442	467				
soil moisture	30								
	90								
	150								
soil moisture	30	11			4			3	15
	90		56				1		
	150	8				4		0	
pH	5.57								
	6.42								
	6.80								

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
temperature	30								
	90								
	150								
Mine Spoils, 17 °C	16.5								
	18.5								
	20.0								
Eh in mv	436	568	523	591	223	603	531	551	495
	30								
	90								
	150								
soil moisture	13	59	5	27	56	12	6	35	10
	30								
	90								
	150								
pH	3.41								
	30								
	90								
	150								
temperature	17.0								
	90								
	150								
October 31, 1990									
Reclaimed, 22 °C									
Eh in mv	---	430	500	530	460	600	290	325	650
	30								
	90								
	150								

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
soil moisture	30 90 150			51		72		65	71
	14	37			44		64 24		
pH	3.69 4.74 150								
temperature	30 90 150								
	18.0 19.5 20.5								
Control, 26 °C									
Eh in mv	30 90 150		462	476 444	476	311	-043		533
	487 314								
soil moisture	30 90 150	15			8		2	5	15
		11	56			6		1	
pH	30 90 150								
	5.87 6.69 6.67								
temperature	30 90 150								
	17.0 18.0 19.0								

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
Mine Spoils, 24 °C									
Eh in mv	550	655	580	610	540	640	590	630	545
soil moisture	18	44	18	31	66	21	12	20	
pH	3.48								
	3.73								
	3.60								
temperature	19.5								
	19.5								
	21.0								
November 16, 1990									
Reclaimed, 17 °C									
Eh in mv	370	415	544	454	420	591	338	306	634
soil moisture	15	40		54	47	70	64	68	72
							30		

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
pH	4.27 4.17 4.07								
30									
90									
150									
temperature	15.0 16.5 18.5								
30									
90									
150									
Control, 18 °C									
Eh in mv	215 -024		508	534 483	470	338	-081		475
30									
90									
150									
soil moisture		2 10	48		0		0	0	16
30									
90									
150									
pH	5.94 6.82 7.05								
30									
90									
150									
temperature	15.0 16.0 18.0								
30									
90									
150									
Mine Spoils, 16 °C									
Eh in mv	-001	577	567	611	127	614	572	568	253
30									
90									
150									

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
soil moisture	30 90 150		2		56	10		0	8
	12	40		36			22		
pH	3.94 3.66 3.76								
temperature	16.0 18.0 19.0								
November 30, 1990									
Reclaimed, 12 °C									
Eh in mv	412	455	459	445	417	588	339	376	640
soil moisture	30 90 150			48		54	62	55	64
	17	40			48		32		
pH	4.21 5.04 ND								
temperature	10.0 8.0 9.0								

TABLE A. (continued)

	1	2	3	4	5	6	7	8	9
Control, 10 °C									
Eh in mv	251 -062		481	625 455	465	328	-064		491
soil moisture		0			0			0	
		8	48			5	0	0	14
pH	5.96 7.10 7.19								
temperature	9.0 11.0 13.0								
Mine Spoils, 14 °C									
Eh in mv	571	625	682	640	064	603	608	565	348
soil moisture	9	32	13		68	7		7	3
				19			15		
pH	4.15 ND ND								
temperature	11.0 15.0 17.0								

TABLE B. Temperature variation with depth for each study site.

Date/Site		Depth, cm		
		30	90	150
8/22	Reclaimed	31.0	29.0	27.0
	Control	28.0	26.0	24.0
	Mine Spoils	31.0	29.3	27.5
8/29	Reclaimed	33.0	29.0	27.0
	Control	28.5	27.0	25.0
	Mine Spoils	33.0	30.0	28.0
9/12	Reclaimed	29.0	28.0	26.5
	Control	27.0	26.0	25.0
	Mine Spoils	29.0	30.0	28.0
9/24	Reclaimed	21.0	26.0	26.0
	Control	27.0	24.0	24.0
	Mine Spoils	22.0	27.0	27.0
10/5	Reclaimed	22.0	23.5	25.0
	Control	22.0	23.0	22.0
	Mine Spoils	23.5	25.0	25.0
10/19	Reclaimed	17.0	18.9	20.5
	Control	16.5	18.5	20.0
	Mine Spoils	17.0	18.5	20.5
10/31	Reclaimed	18.0	19.5	20.5
	Control	17.0	18.0	19.0
	Mine Spoils	19.5	19.5	21.0
11/16	Reclaimed	15.0	16.5	18.5
	Control	15.0	16.0	18.0
	Mine Spoils	16.0	18.0	19.0
11/30	Reclaimed	10.0	8.0	9.0
	Control	9.0	11.0	13.0
	Mine Spoils	11.0	15.0	17.0

TABLE C. $\sqrt{pH}$ Variation with depth for each study site. The depth is measured in centimeters below ground level.

Date/Site	Depth, cm		
	30	90	150
8/29 Reclaimed	3.43	4.25	4.94
	Control 5.78	6.93	6.90
	Mine Spoils 3.91	4.04	4.19
9/12 Reclaimed	4.25	4.24	4.16
	Control 5.26	6.09	6.24
	Mine Spoils 3.99	3.96	3.86
9/24 Reclaimed	4.66	4.37	4.54
	Control 6.43	7.36	6.23
	Mine Spoils 4.17	4.01	4.08
10/5 Reclaimed	4.95	5.15	5.23
	Control 6.95	6.30	6.65
	Mine Spoils 4.30	4.10	4.21
10/19 Reclaimed	4.22	3.99	4.48
	Control 5.57	6.42	6.80
	Mine Spoils 3.41	3.75	3.65
10/31 Reclaimed	3.69	4.74	4.06
	Control 5.87	6.69	6.67
	Mine Spoils 3.48	3.73	3.60
11/16 Reclaimed	4.27	4.17	4.07
	Control 5.94	6.82	7.05
	Mine Spoils 3.94	3.66	3.76
11/30 Reclaimed	4.21	5.04	ND
	Control 5.96	7.10	7.19
	Mine Spoils 4.15	ND	ND

TABLE D. Soil moisture variation with depth for each study site. The values reported in this Table are the average values. For each depth at each study site three measurements were taken. The values are recorded in centibars.

Date/Site		Depth, cm		
		30	90	150
7/26	Reclaimed	67	16	11
	Control	35	28	11
	Mine Spoils	11	48	25
7/31	Reclaimed	40	19	12
	Control	0	20	8
	Mine Spoils	05	37	47
8/15	Reclaimed	35	24	14
	Control	05	18	05
	Mine Spoils	28	36	32
8/22	Reclaimed	32	26	15
	Control	09	15	05
	Mine Spoils	30	39	34
8/29	Reclaimed	01	27	17
	Control	18	14	07
	Mine Spoils	33	42	39
9/12	Reclaimed	00	28	17
	Control	61	14	17
	Mine Spoils	23	49	48
9/24	Reclaimed	00	40	18
	Control	01	17	04
	Mine Spoils	03	35	51
10/5	Reclaimed	06	43	21
	Control	10	23	04
	Mine Spoils	18	20	42
10/19	Reclaimed	22	51	23
	Control	06	24	04
	Mine Spoils	08	26	40
10/31	Reclaimed	65	55	27
	Control	09	24	06
	Mine Spoils	17	35	38
11/16	Reclaimed	65	57	31
	Control	01	21	05
	Mine Spoils	04	25	33
11/30	Reclaimed	55	52	32
	Control	00	21	04
	Mine Spoils	09	27	22

TABLE E. Total Se concentration in selected soil samples taken from the Henryetta site. These measurements are from selected overburden (mine spoils). The concentrations are expressed in mg/kg (ppm).

Date	Depth, cm		
	30	90	150
9/12	0.12	0.09	< 0
9/24	0.14	< 0	0.45
10/5	0.29	0.33	0.12
10/19	0.28	0.62	< 0
10/31	< 0	0.16	< 0

NOTE: Sample 12 containing 10.093 ppm Se as Na_2SeO_4 and Na_2SeO_3 was digested with the above samples.

Sample 12 measured 3.47 ppm Se which is a 66% loss in Se during the digestion process.

TABLE F. ADSORPTION ISOTHERM STUDIES

TOPSOIL		SAND		OVERBURDEN	
conc., ppm	time	conc., ppm	time	conc., ppm	time
8.536	7	137.2	0	31.815	7
2.052	14	64.24	0.5	0.317	14
0.924	21	4.96	6	0.165	21
0.621	28	4.72	11.5	0.175	28
0.472	35		17	0.127	35
0.350	42	4.03	24	ND	42
0.292	49		33.4	ND	49
0.237	56	0.06	45	135.802	56
68.818	63			ND	61
0.139	70			0.090	68
67.640	77			41.43	75
58.677	84			ND	82

* Time is in minutes.

LITERATURE CITED

1. Lindsay, W.L., Chemical Equilibrium in Soils, John Wiley and Sons, New York, 1979.
2. Marker, W. Mrs., personal communication, 1990.
3. Soil Survey Okmulgee County, Oklahoma, U.S. Department of Agriculture, Washington D.C., May, 1968.
4. Instrumental Methods of Analysis, Willard, Hobart H., et al., sixth edition, Wadsworth Publishing Company, Belmont, California, 1981.

END

**DATE
FILMED**

8 / 31 / 92