Progress Report for Quarter 2: Jan 1, 199²~~1~~ to March 31, 1992

**DEVELOPMENT OF A NON-INTRUSIVE PARTICLE TRACING
TECHNIQUE FOR GRANULAR CHUTE FLOWS**

**Sponsored by the U.S. Department of Energy
Contract Number DE-AC22-91PC90181**

New Jersey Institute of Technology
Departments Of Mechanical & Electrical Engineering
Newark, New Jersey 07102

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Investigators

*Dr. Anthony D. Rosato
Dr. Rajesh N. Dave
Dr. Ian S. Fischer
Dr. William N. Carr*

JUN 17 1992

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Table of Contents

Abstract

I.	Introduction	
II.	Theoretical Model	3
III.	Data Acquisition System	5
IV.	Electronics	6
V.	Comparison Between Theory and Experiments	10
VI.	Signal Processing	14
VII.	Radiosonde Sphere Packaging Design	15
VIII.	Chute Apparatus	17
IX.	Related Experiments: Measurement of Particle Properties	19
X.	Cluster Analysis of Granular Flows	21

Appendix 1: Chute Drawings, Sphere Packaging Design

Appendix 2: Recent Relevant Papers

ABSTRACT

MAY 01 1992

The development of a non-intrusive particle tracking system to follow the trajectory of an individual particle in three dimensions within a mass of particles is necessary to experimentally validate developing theories of inclined chute granular flows in conjunction with particle dynamics models. An understanding of the exact nature of such flows is of critical importance to a variety of industries concerned with solids handling, as well as in natural geological events.

The tracking system, based on the principle of "radiosonde" transmitters coupled to receiving antennae by magnetic induction, is being developed. The radiosonde consists of one or more, orthogonally placed miniature circuits with integral loop antennas, mounted into a sphere of approximately 3/4" in diameter. The radiosonde sphere position can be traced during the flow down a chute by analyzing the induced voltage signals in the three or more external orthogonal receiving loop antennas due to the transmitter chips.

I. Introduction and Summary of Accomplishments for Quarter

The objective of this work is to develop an experimental technique to determine the trajectory of a single sphere in a mass of spheres flowing down an inclined chute. A radiosonde transmitter will be developed to be embedded in a prototype test spheres. This transmitter will emit signals which will induce a voltage in parallel sets of receiving antennae via magnetic induction. A theoretical model is developed with which to interpret these voltage signals to the sphere's position.

This report summarizes the progress since this contract work began in January 1991. The reports discusses the model, electronics, and signal processing. Comparisons are shown between the model predictions and experimental data which has been obtained thus far.

New Jersey Institute of Technology is strongly supporting the efforts of the investigators to expand and develop granular flow research within the Mechanical Engineering Division. They have equally matched the DOE support for this contract and have provided additional graduate students for other related experiments and numerical modeling efforts. This work is briefly discussed in the last sections of this report.

Below is a list of specific achievements which have been accomplished during this reporting period, i.e., January 1, 1992 to March 31, 1992.

- New theoretical model with square receiving antennae validated
- Data Acquisition System completed and functional
- Miniature transmitter package with one coil built to fit into sphere
- Tests to compare experimental 1-D trajectory with model-predicted trajectory completed and successful.
- Prototype sphere packaging design completed
- Software to compute the translation and angular velocities of two colliding spheres for subsequent analysis completed.

II Theoretical Model

The use of a circular loop on a rectangular shaped chute results in a "dead space" and a resulting reduction in the signal to noise ratio (See Fig. 1). Therefore a new model was developed for a rectangular shaped receiving loop which could follow the chute's contour very closely.

Figure 1: Diagram of "dead space" for circular loop antenna

By proper positioning and size adjustments it can be made more sensitive to movements in one direction. From a purely computational point of view, this model requires less computations due to the absence of elliptic integrals which appeared in a previous model. The model gives the transfer function for the voltage induced as a function of the transmitter position with respect to the receiver. To derive the transfer function it was assumed that a current I is flowing in the receiver coil (See Fig 2). We treat the rectangular loop as four independent filament sources and then apply Superposition theorem to get the composite response by summing up the individual responses. The magnetic field density due to the current I at a position (x,y,z) is given by

$$\bar{B} = \sum_{i=1}^4 \left(\frac{(\mu_0 I)}{4\pi R_i} (\cos \phi_{i1} - \cos \phi_{i2}) \right) \bar{\theta}_i$$

where $\cos \phi_i$, R_i and the position vector $\bar{\theta}_i$ are functions of the position (x,y,z) and the loop dimensions l and a . The magnetic field density vector $\bar{B}$ can now be represented as

$$\bar{B} = B_x \bar{X} + B_y \bar{Y} + B_z \bar{Z}$$

The voltage induced in a transmitter coil positioned at (x,y,z) and of area A , which is assumed to be elemental, (i.e. , the magnetic field density does not change over it), is given by,

$$V = -\omega (\bar{B} \cdot \bar{A})$$

where $\omega = 2\pi f$, f being the operating frequency. If the normal to the plane of the transmitting coil

Figure 2: Model configuration

has direction cosines l , m , and n respectively, then the induced voltage can be written as,

$$V = -\omega A [B_x l + B_y m + B_z n]$$

An application of the principle of Reciprocity [1], which states that the source and the response in a linear network can be interchanged, gives that a current I flowing in the transmitter will induce a voltage V in the receiver given by the transfer function derived.

III Data Acquisition System

The data acquisition system is the link between the signal processed (amplified and detected) receiver outputs and the reverse simulation program to determine the position using the theoretical model. Its main parts consist of an IBM compatible 486 PC, the National Labwindows software and the National AT-MIO-16 board (See Fig. 3).

Figure 3: Data Acquisition System

The AT-MIO-16 is a multi function analog, digital, and timing I/O board for IBM PC AT and compatibles. It contains a twelve bit analog to digital convertors (ADC) with upto sixteen analog inputs. It has a $9\mu s$ data acquisition convertor which guarantees rates upto 91 K samples/sec. There is a 16 word analog to digital first in first out (FIFO) buffer for fast data acquisitions. The AT-MIO-16 is interfaced to the National Instruments RSTI bus. In the setup, the AT-MIO-16 is

being used with Lab Windows, a program development software package for test and measurement applications. Lab Windows uses and enhances Microsoft QuickBasic and C with an interactive development environment, function panels to generate the source code, and libraries for data acquisition, instrument control, data analysis, and presentation. The ADC is a 12 bit successive approximation ADC. The 12 bit resolution allows the convertor to resolve its input range into 4096 different steps. All the receiver channels are scanned every 0.1 ms with a single scan taking 0.1 ms to get information from all of the channels. The input multiplexer consists of CMOS analog input multiplexers and has 16 input channels. If operated in a differential mode the number of input channels is reduced to 8. The multiplexer output is fed to an instrumentation amplifier which in turn is followed by a sample and hold circuit and the 12 bit ADC. The output of the ADC is stored on the IBM PC hard disk in an ASCII file which is then input to the "reverse simulation program for position determination".

IV Electronics

The "radiosonde" system consists of a transmitter located in the sphere to be tracked, six receiving antennae loops and the associated amplifiers with signal processing. Two antennae are located in each of the orthogonal planes and are placed on opposite sides of the chute. Each antennae pair gives primarily, the displacement of the sphere in the direction as shown in Figures 4 a, b. This displacement is along a line normal to the planes of the antennae. For this system to function correctly, the currents flowing in the antennae must be very small. If this is not the case, the coupling from each antenna to the others would be large and mask the tracking information. With light antenna loading, the signal received by each antenna is only that received by coupling from the sphere being tracked.

Only a few millivolts, at best, are induced into the large antennae loops, which are approximately 3m long by 1m wide. At this time, the antenna size (of the pair of antennae) along the length of the chute has not been determined. However, based upon calculations and experimental measurements, accurate determinations may be made by using a total of three antennae with one being placed at a center of the chute by using a large area antennae.

Figure 4a: Sphere location sensing across the chute width

Figure 5: Antenna rf amplified and signal processor block diagram.

The frequency transmitted by the sphere has been tentatively set at 2 MHz. A high input impedance circuit is used to couple the antenna signal to a low input impedance bandpass amplifier. This is followed by another bandpass amplifier to further narrow the bandpass and attenuate disturbing, unwanted signals and noise in the 2 MHz region. A low output impedance driver with large signal handling capabilities is used to drive a diode detector. Overall gain from the antenna to the output of the driver is about 46 dB, and the 3 dB bandwidth is approximately 40 KHz. Detecting the rf signal with a diode peak type detector is non-linear, especially when the driving signal is less than one volt peak to peak. Also, the detector is very sensitive to transient spikes due to turn on/off of nearby equipments, since it tends to give an output close to the peak amplitude of the input signal.

Figure 6 shows the block diagram of a balanced demodulator, which gives a linear output ver-

Figure 6: Block diagram of alternative balance demodulator.

sus signal input. However, this requires the generated switching signal to have nearly constant amplitude even when the signal input is at a low level. At low enough signal levels the switching signals will decrease and the detected output will be closed to square law rather than linear. In actual operation, linearity at the low or signal levels for the demodulator will be superior to the diode detectors. The balanced demodulator circuit design and construction has been completed and a schematic of the amplifier and the detectors are shown in Figures 7 and 8.

Q1 - Q4 - 2N2222
 L1 - 6 Micro Henry with 20T primary and 6T secondary
 L2, L3 - 10 Micro Henry critically coupled

Fig 8 BANDPASS AMPLIFIER

In the sphere which is to be tracked, a simple one transistor oscillator at 2 MHz has been designed and constructed. The same design has been implemented using surface mounted components on an epoxy printed circuit board. The oscillator operates at 3 V from the wrist watch cells and draws about 2.8 mA of battery current. Figure 9 shows the approximate dimensions of the transmitter. A circuit diagram of the oscillator is shown in Figure 10. Feedback to maintain oscillations is supplied by a secondary wound directly over the primary and properly phased. Using a secondary winding increases the efficiency of the oscillation since no a.c. power is dissipated in the base biasing resistors. Also the coil is easier to construct since an additional tap on the primary is eliminated by simply winding a few turns to give the required transistor based drive. All the components are surface mount except for the coil and the IN914 diode which is extremely small.

Figure 9 : Approximate dimensions of transmitter electronic circuit

It is possible to use surface mount coils for the oscillator, but the induced voltages into the loop antennae would be too small to be usable. In actual practice, the transmitter coil should be made as large as possible within the constraints of the sphere size requirements. Operation of the oscillator is possible down to 2.3 V battery supply voltage, which is the entire useful life of the battery.

Figure 10 : Hartly Oscillator used as transmitter

V Comparison Between Theory and Experiment

For a 8" by 4" four-turn receiving antenna, there is a strong correlation between measured and predicted values of voltage in the Z and X directions as shown in Figures 11 and 12, respectively. As noted in the figures, a scale factor was applied to the theoretical values. This scaling is a consequence of the fact that the measuring instrument has a 50Ω impedance to which the receiving antenna was matched. Consequently, an uniform, constant attenuation factor of approximately 20 was found to exist between measured and model predicted values. In Figure 12, for the $Z = 1$ case, it can be seen that both curves exhibit minimas at -6 and 6 and maximas at -4.7 and 4.7. Also, the measured voltage versus coil orientation shown in Figure 13 follows a cosine relation as predicted by the model.

Figure 11 : Output vs. Z Displacement

Output vs. Displacement along X-axis ($f=2\text{MHz}$, $y=0$)

Figure 12 : Output vs. X Displacement

Output vs. Coil Orientation ($f=2\text{MHz}$, $x=0$, $y=0$, $z=0$)

Figure 13 : Output vs. Orientation

The experimental setup for radiosonde sphere tracking consisted of two parallel receiving loops, 120" x 40", separated by 30.2" as shown in Figures 4a, b. This setup was used for position determination in the Z direction. The transmitter was moved in a path with fixed X and Y position values, i.e., only the Z position was varied. The signals picked up from the receiving loops were

amplified, detected and input to the data acquisition system. The data acquisition system stored the measured voltage values in a column form in an ASCII file. This ASCII file was input to the "Reverse simulation program for position determination". Figures 14a,b show the actual position of the coil versus the position predicted using the model. The figure shows a correlation between the two within ± 1.25 ". The same experiment was then repeated at different X locations.

Figure 14a : Predicted vs. Actual Trajectory at X = 0"

Copyright 1994, Copyright Reserved, Intel Corporation. This document is a confidential document and its contents are not to be disclosed to third parties without the prior written permission of Intel Corporation.

Figure 14b: Predicted vs. Actual Trajectory at X = 30 inches.

VI Signal Processing

The technique to determine the position and orientation of the particle from the measured voltages using a model that gives the induced voltage transfer function (voltage induced in the receiver as a function of the transmitter location) is presented.

The model presented in Section II results in a system of non-linear equations in six unknowns for the sphere's position and orientation. A technique to solve an overdetermined nonlinear system of equations has been developed. This system would result if there were three transmitters within the sphere and at least three receiving antennae. The developed method allows for a unique solution for position and orientation. In the discussion that follows, an outline of the numerical algorithm is presented for the case of nine nonlinear equations in six unknowns. Mathematically, this problem is one of constrained minimization of the overdetermined, non-linear system.

The sphere position and orientation parameters are denoted by $(X) = (x, y, z, \alpha, \beta, \gamma)$, while the voltage induced in the receiver due to the transmitter as predicted by the model is expressed as,

$$V_i(X) = f(x_{tr}y_{tr}z_{tr}\alpha_{tr}\beta_{tr}\gamma_{tr}) \quad i = 1, \dots, 9$$

The notation above signifies that for each transmitter-receiver pair, there is an associated set of position and orientation parameters, $(x_{tr}y_{tr}z_{tr}\alpha_{tr}\beta_{tr}\gamma_{tr})$. The experimentally measured voltage in each receiver is given by $(V_{m1}, V_{m2}, \dots, V_{m9})$. The i^{th} residual, $R_i(X)$, is then expressed as,

$$R_i(X) = V_i(X) - V_{mi} \quad i = 1, \dots, 9$$

The solution of the equation set is conducted by a modification of the non-linear least squares Levenberg-Marquardt algorithm[2]. The problem then is a minimization algorithm, i.e.,

$$\text{minimize } \|R(X_c) + J(X_c - X_2)\|_2$$

$$\text{subject to } \|X_+ - X_c\|_2 \leq \delta_c,$$

where X_+ is the next iterate, X_c is the current value, $J(X_c - X_2)$ is the Jacobian, and δ_c is the maximum length of a successful step from X_c , and $R = (R_1, R_2, \dots, R_9)$.

The solution is given by

$$X_+ = X_c - (J(X_c)^T J(X_c) + m_c I)^{-1} J(X_c)^T R(X_c),$$

The constants $m_c > 0$ and δ_c are constants chosen via a scaled trust region method [3]. If $\delta_c \geq \| (J(X_c)^T J(X_c))^{-1} J(X_c)^T R(X_c) \|_2$, then $m_c = 0$.

Because of the highly non-linear nature of the functions and the complexity of the solution space the problem of convergence to a global minima is present. Figure 15 shows the residual voltages

approaching zero as convergence to the global minima is achieved for the case of a single transmitter and six receivers.

Figure 15: Residual voltages versus number of iterations.

The signal processing task is being conducted in two parts - the Forward Simulation and the Reverse Simulation. The Forward Simulation involves the determination of the voltages induced in the external receivers due to the transmitters based on the model. The Forward Simulation has been completed and it is useful in checking the veracity of the model by comparing the theoretical values with the actual experimental values. It also provided voltage values necessary to conduct the Reverse Simulation before the actual experimental values become available.

The Reverse Simulation involves finding the location of the sphere given the experimental voltages. This also has been successfully completed. A simulation program has been written to graphically display the results. In this, the locations of the sphere as determined from the measured voltages would be displayed on two grids as well as in the chute to visualize the trajectory of the particle.

VII Radiosonde Sphere Packaging Design

Design Objectives

- 1 Good magnetic symmetry.
- 2 The tracking sphere is statically balance.
- 3 The tracking sphere has mass similar to the regular sphere.
- 4 Ease of replacement of batteries, and installation of the transmitter.

- 5 Maximum diameter of the tracking sphere is 1 inch.
- 6 Sphere surface is smooth without any cracks and cavities.
- 7 Ease of manufacture.

Structure of Design and Size

The tracking sphere is composed of eight components plus two batteries and a transmitter. In order to easily replace the battery, mount transmitter and manufacture, a structure of two half-spheres with cavities and internal thread 11/16-48 is adopted. A collar with external thread 11/16-48 is used to link the two half-spheres together. It is also used to mount and fix the transmitter, weight pad and two battery boxes. The transmitter coil, which is 0.18" diameter and 0.315" long, is mounted in the center of the sphere to obtain a symmetrical magnetic field. The transmitter is composed of a print circuit board (PCB) and a coil. The PCB with miniature discrete electronic components is 0.57" diameter and 0.135" thick.

Two "371-silver oxide" batteries provide 3V DC power, and are separately mounted for symmetry. Each battery is 0.175" away from the coil to prevent distortion of the magnetic field. The pair of batteries can be continuously used for approximately 7 hours.

The choice of 1" diameter for the sphere was selected to meet the technical requirements above. The holes in the weight pad and battery boxes are designed to pass the wire connections between the batteries and the transmitter.

Balance Considerations

1. Static balance: As shown in the figures in the appendix, the center of gravity of the tracking sphere is (0.00, 0.00, 0.00) so that the sphere satisfies the requirements of static balance. However, after the real tracking sphere is made, imbalance actually may occur because of the tolerance of manufacturing and assembly.
2. Other properties: The tracking sphere will be immersed in a flow of other spheres of the same diameter and material as the half-sphere. In order to get the real sphere collision motion trajectory, it is necessary to have the smallest difference of properties between the tracking sphere and other regular spheres. The design provides for the mass and moments of inertia of the tracking sphere to be equivalent to a regular solid sphere, as summarized in the table below.

	Tracking Sphere	Regular Sphere
Mass(lbf)	0.0228	0.0217
I_{xy}	0.0	0.0
I_{yz}	0.0	0.0
I_{xz}	0.0	0.0

The relative error of mass between the tracking sphere and the regular sphere is,

$$\Delta\% = (0.0228-0.0217)/0.0217 = 5.07\%$$

Because (I_{xy} , I_{yz} , I_{xz}) are equal to zero, the tracking sphere mass distribution is considered to be balanced. The diameter and position of the wiring holes of the weight pad are designed and revised according to balance requirements.

Material and Density

All components, except the electric components, are composed of resin material. For the material and density shown in below:

Component	Number	Material	Density (lb/in³)
half-house	2	nylon	0.043
collar	1	nylon	0.043
battery box	2	nylon	0.043
pad	2	neoprene	0.043
weight pad	1	polyester	0.060
battery	2		0.149*
coil	1		0.145*
PCB	1		0.052*

*: Actual density

Battery Replacement

Because the tracking sphere is fastened by thread, it is easily opened and closed. After screwing off the half-housing, batteries can be directly removed from the battery boxes. Then fresh batteries will be installed.

VIII Chute Apparatus

Introduction

An experiment apparatus has been designed and is in the final stages of construction which can be used for the study of particulate flows down inclined chutes using the radiosonde non-intrusive particle-tracing technique. Drawing of the chute can be found in the Appendix.

Design Objectives

A chute is being designed with which to conduct tests of the non-intrusive radiosonde particle-tracing system. There are several design objectives for the chute, all of which will be met in the design.

- Appropriate Size

The chute has to be sized appropriately for the spheres to be used. Based primarily on the size of available batteries, it is anticipated that spheres as large as 3/4" diameter will be required. A structure allowing a maximum chute width of 15" will give a reasonable width to diameter ratio of 20. The available laboratory and standard sizes of construction material indicate a chute length of ten feet, which provides a reasonable length to diameter ratio of 160. It is anticipated that this length will provide an adequate observation time during which the transition from "at-rest" to "steady-state flow" can occur.

- Radio Transparency

The chute design must facilitate rather than interfere with the experiments. The material of which it is constructed must be "transparent" to the radio transmissions upon which the flow measurements are based. Plastics have the appropriate transmission qualities and therefore will be used instead of metals. Extren fibreglass structural shapes and lucite plate and sheet has been specified, the later being transparent to allow flows to be visually observed as well as making high-speed video-taping possible. It is noted that all of the fasteners employed in the experiment apparatus are plastic, either nylon or Extren polyfibre.

- Adjustability of Inclination angle and chute width

The design will allow the ready adjustment of chute dimensions. A modular construction will allow variation of width and inclination angle.

- Adjustability of Surface Roughness

Provision is provided for substitution of rubber floor mats, styrofoam ceiling panels and textured plastic plates used for lamp diffusers and architectural effects to enable variation of surface roughness and internal damping.

- Simple Fabrication

The design avoids complex machining. Only sawing and drilling/countersinking holes is required.

Description

The chute structure has been designed as several modules. The "chute section" comprises the length of the chute and consists of a 1/2" thick acrylic base plate reinforced by sills of 6" deep Extren structural shapes. The superstructure of the chute section consists of floor plates and wall plates which can be either smooth acrylic or textured architectural sheets for desired surface roughnesses. Heat-formed acrylic brackets can be located to provide chutes of various widths.

The "low-end support" of the structure is built largely of Extren structural shapes and supports the bottom of the chute section.

"Intermediate supports" of Extren structural shapes will be constructed if the experiments indicate that additional support is required to provide adequate rigidity and minimize deflection of the chute structure.

The "high-end support" holds the top of the chute, allowing for variation of the inclination angle. To adjust the angle, the end of the chute will be hoisted to approximate position by block and tackle, and then the hinge brackets will be connected to the columns. A jack-screw arrangement will then be used to obtain precise selection of the inclination angle. Arrangement is made for clamping the chute in the exact position required. Construction of the high-end support is largely Extren shapes, with acrylic used for the various details.

IX Related Experiments: Particle Properties

The modeling of granular flows and phenomena involving particulates is relevant to many fields, such as industrial solids handling, pharmaceuticals, plastics, materials development and natural granular flows [8]. The highly nonlinear nature of these flows poses enormous complications in developing constitutive models to predict the behavior over a range of conditions. This fact, coupled by the difficulty in performing experiments, has led many to employ particle dynamics simulations to study these flows. Results of the simulation naturally depend on the collisional material properties used, i.e., coefficient of friction and normal and tangential restitution coefficients. In order to better validate developing theories in conjunction with experimental studies, it is necessary to devise a three-dimensional experimental method whereby these properties can be measured.

A prototype experimental apparatus has been built which can launch two spheres such that their resulting collision will occur at different incident angles. There is no restriction on the initial spin of

the spheres. The "launching" system and a high-speed digital camera (Kodak EktaPro 1000) will be controlled by a 486PC, which also houses a high-performance image grabber from Imaging Technology. Low level image processing is done using routines from the VISILOG [6] software library.

By performing motion correspondence between a number of points on the sphere (called feature points), three-dimensional motion can be resolved from a single perspective. Low resolution of the camera, however, severely affects this approach. As an alternative, two orthogonal views of the motion are obtained for achieving the best possible accuracy. The measurement of the motion can be divided into translation and rotation. In order to achieve sub-pixel accuracy in translation, special edge detection techniques are used, coupled with boundary detection methods [5]. Measurements of rotation can be achieved through motion correspondence of the set of feature points on the object. The correspondence is achieved using proximal uniformity constraint [9]. The accuracy of the overall procedure is improved using a least squares error approach on an over-determined system of equations.

The specific tasks of the research are as follows:

- Establish the interface between the PC, the EktaPro 1000, and the sphere projectile triggering mechanism. An I/O card from Data Translation (DT2817) is used to trigger the projectiles and recording on the EktaPro. This interface includes the ability to transfer images from the camera to the PC.
- Design and build the experimental apparatus, lighting system and the imagers.
- Calibrate the images to the world coordinate system.
- Perform the collision experiments.
- Transfer image data to the PC, several images at a time.
- Analyze the images to find positions of the spheres and determine the impact time.
- Analyze a set of frames just before and after the collision.
- Compute the collision parameters from the results obtained.
- Repeat the experiment for spheres of different sizes.

Appendix 2 contains an extended abstract entitled, "Collision Parameter Analysis of Rigid Particles by Computer Vision", which was presented in the Second ASME Region II Graduate Student Technical Conference. (April 12, 1992 at Stevens Institute of Technology).

X. Cluster Analysis of Granular Flows

The second PI (Dr. Dave) has recently begun to apply his work on pattern recognition and clustering algorithms to study cluster formations which have been observed in granular flows [19,20,21, 22]. The objective of Dave's work is to develop automated algorithms to track and formation and break-up of cluster formations in the flows. Basically, cluster analysis is one of the

basic tools for producing classifications from initially unclassified data. Most clustering algorithms based on optimization techniques tend to seek one or the other type of cluster shapes depending on the distance measurement criteria. This is not possible in the case of a granular flow since one does not know beforehand what the shapes will be. Consequently, it is necessary to make as few assumptions about the data as possible in order to avoid any bias. (Note: Families of clustering algorithms have been reported with different applications in mind [10]. Most clustering algorithms based on optimization techniques tend to seek one or the other type of cluster shapes depending on the distance measurement criteria.) It is difficult, though, to find any one method that will work on all types of clustering problems and that will also be able to discard noise to uncover the true structure. The recent approaches of R. Dave [5,11-18] have been able to address these problems.

Several papers by R. Dave have been included in the Appendix 2 for reference.

REFERENCES

- 1 Van Valkenburg, M.E., *Network Analysis*, pg 258, Prentice-Hall, Englewood Cliffs, New Jersey (1974).
- 2 Dennis, J.E. and Schnabel, R.B., *Numerical Methods for Unconstrained Optimization and Nonlinear Equations*, Prentice-Hall (1983).
- 3 Fletcher, R. and Powell, M.J.D., "A Rapidly Convergent Descent Method for Minimization", *Comput. J.* **6**, 163-168 (1963).
- 4 Muammar, H.K. and Nixon M., "Tristage Hough Transform Multiple Ellipse Extraction," *IEE Proceedings-E*, **138**, 27-35 (1991).
- 5 Dave, R.N., "Fuzzy Shell Clustering and Applications to Circle Detection in Digital Images," *International Journal of General Systems* **16**, 343-355 (1990).
- 6 VISILOG, Release 3.6., Noesis S.A.R.L., (1988).
- 7 Mullier M., Tuzun U., and Walton, O.R., "A Single-Particle Friction Cell for Measuring Contact Frictional Properties of Granular Materials", *Powder Tech.*, **65**, 61-74 (1991).
- 8 German, R.M., *Particle Packing Characteristics*, Metal Powder Industries Federation, Princeton, NJ (1989).
- 9 Rangrajan, K., and M. Shah, "Establishing Motion Correspondence," *CVGIP: Image Understanding*, **54**(1), 56-73 (1991).
- 10 Bezdek, J., *Pattern Recognition with Fuzzy Objective Function Algorithms*, Plenum, New York, 1981.
- 11 R.N. Dave and S.K. Bhamidipati, "Application of the fuzzy-shell Clustering Algorithm to Recognize Circular Shapes in Digital Images", *Proceedings of the International Fuzzy Systems Association Congress*, Seattle, pp. 238-24 (1989).
- 12 R. N. Dave and K. J. Patel, "Progressive Fuzzy Clustering Algorithms for Characteristic Shape Recognition", *Proceedings of NAFIPS'90*, pp 121-124, 1990.
- 13 R. N. Dave and K. J. Patel, "Fuzzy ellipsoidal-shell clustering algorithm and detection of ellipsoidal shapes", *Proceedings of the SPIE Conference on Intelligent Robots and Computer Vision IX: Algorithms and Techniques*, Boston, pp. 320-333, Nov. 1990.

- 14 R. N. Dave and K. Bhaswan, "Adaptive C-Shells Clustering", *Proceedings of the North American Fuzzy Information Processing Society Workshop*, Columbia, Missouri, pp. 195-199, 1991.
- 15 R. N. Dave and K. Bhaswan, "New Measures for evaluating fuzzy partitions induced through c-shells clustering", SPIE Conference on Intelligent Robots and Computer Vision X, Boston, November 1991.
- 16 R. N. Dave and K. Bhaswan, "Adaptive Fuzzy c-shells clustering and detection of ellipses", submitted to *IEEE Trans. Neural Networks*.
- 17 R. N. Dave, "Generalized fuzzy c-shells clustering and detection of circular and elliptical boundaries", to appear in *Pattern Recognition*.
- 18 R. N. Dave, "Characterization and detection of noise in clustering", *Pattern Recognition Letters*, Aug. 1991.
- 19 Walton, O.R., Kim H.J., Rosato, A.D, "Microstructure and Stress Differences in Shearing Flows," *Mechanics Computing in 1990s and Beyond, Proceedings of the ASCE Engineering Mechanics Division*, May 20-22, 1991.
- 20 Hopkins, M.A. and Louge, M.Y., *Phys. Fluids A*, 3(1), pp 45-57 (1991).
- 21 Babic, M., "Particle Clustering: An Instability of Rapid Granular Flows," *Proceedings of the Second US-Japan Seminar on Micro-Mechanics of Granular Materials*, Elsevier (1992), in press.
- 22 Sanders, B.E., and Ackermann, N.L., "Microstructure in Rapid Gravity Channel Flow," *Proceedings of the Second US-Japan Seminar on Micro-Mechanics of Granular Materials*, Elsevier (1992), in press.

APPENDIX 1

Chute Drawings SpherePackaging Design

REV	DATE	DESCRIPTION	TITLE			N J I T		DOE Project		DRG NUMBER	SHEET
A	1/29/92	RENAME DRAWING 100-00-A 1/4	CHUTE			cross section				2001	2/13
			SCALE		DSND	BALAJI S					
			1:4		DRWN	BALAJI S	10/06/91				
					APPD	Dr I FISCHER

REV	DATE	DESCRIPTION	TITLE			N J I T		
A	11/29/92	RENAME DRAWING 100-00-A 3/4	CHUTE- Plan view			DOE Project		
			SCALE	DSND	Bala ji S	DRG NUMBER	SHEET	
			1 : 12	DRWN	Bala ji S	2003		4/1
				APPD	Dr. I Fischer			

HAVE FUN!

Public (charity) Tracking Sphere

1-DEAS GRAPHICS

- 1-Select Options_Screen
- 2-BackGround_Color
- 3-Grayscale_Level
- 4-Dynamic_Viewing
- 5-Joystick_Leve
- 6-Trace_Line_Style
- 7-Select_Lat_out
- 8-Define_Latout
- 9-Plot_Points
- 10-Header_Su

1-Back

1-Back

SP-142-40 01-3-25
Display: Restored Screen
... ..

HE BI BY SA LV MP NG PS DI AU DR RE BD HC CL CJ EF BF

Select Menu
Enter BackGround_Color
Enter BackGround_Color

1-Back

1-Back
Setting:
Setting:

preprint + reprint removed;
conf paper cycled
separately. do

END

**DATE
FILMED
8 / 31 / 92**