DOE/ER/53199-T2

Department of Physics
University of California, San Diego
La Jolla, CA 92093

DOE/ER/53199--T2

DE92 002782

Annual Summary of Progress

December, 1990 — July, 1991

"Studies of Plasma Transport"

~~DOE-ER-53199-T2~~

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Principal Investigators:

John H. Malmberg
Thomas M. O'Neil
C. Fred Driscoll

July 22, 1991

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ANNUAL SUMMARY OF PROGRESS

This document gives a Summary of Progress for the first eight months of Year I of the three-year DOE grant DE-FG03-85ER53199. The research project was originally described in UCSD Proposal 90-6522, and this description is still appropriate. The project is progressing on schedule and within budget. Much of the first-year funding is for new equipment, and we project that these funds will be committed by the end of the first year.

We are well underway on design of the upgrade to the present apparatus (called V'). The upgraded apparatus (called CamV) will include a superconducting coil and a new CCD-camera-based data acquisition system. The new apparatus will operate at higher magnetic fields (up to 2 Tesla), and should have significantly smaller error fields. The camera system will enable taking a complete $n(r, \theta)$ "picture" on one shot, thereby removing the shot-to-shot reproducibility limitations of the present imaging system. Also, the camera should enable a resolution of about 0.15 mm, as compared to the present 3 mm, an improvement by a factor of 20.

The CamV superconducting magnet system has been specified and ordered from Cryomagnetics, Inc. The magnet will have a horizontal room-temperature bore 12 3/4 inches in diameter and 68 inches long. Maximum field will be 2 Tesla, and the cryogenic dewar will be of aluminum construction to minimize magnetic field errors. The magnet will be equipped with saddle coils to enable a magnetic field tilt of 10^{-2} radians for magnetic alignment and for plasma manipulation. The delivery of the magnet system is scheduled for November, 1991.

One advantage of the large magnetic field is that it will enable cooling the electrons to room temperature. In a 2 Tesla field, single-electron cyclotron radiation gives an e-folding time of about 1 second, much less than the projected containment times of thousands of seconds. Thus, plasmas with a range of temperatures between

about 5 eV and 1/40th eV can be investigated.

To measure the plasma density, we intend to dump the electrons onto a phosphor, and then look at the light output with a CCD camera outside the vacuum. The dumped electrons must be accelerated to 10 kV without giving them a large cyclotron radius, since this would limit the spatial resolution. We intend to accelerate with a grounded cylinder in front of the phosphor which will be biased at 10 kV. We have performed computer simulations of the electron orbits in this geometry, and have concluded that the image clarity will be acceptable for all magnetic fields above 0.1 Tesla. We also intend to include standard charge collection electrodes as used in previous machines for imaging at lower fields.

We are in the process of specifying and purchasing the CCD camera and associated electronics. Vendors offer complete systems that include a camera fitted with a CCD and Peltier cooling to -40°C for low noise. The systems also include control electronics and a computer interface. We intend to purchase hardware camera which will connect directly to the extensive control electronics and computer system used now on the V' apparatus.

The new vacuum chamber will consist of a 10 inch diameter stainless steel tube that will slip into the superconducting magnet bore. It is intended that the tube will be surrounded by fiberglass insulation and baked in place to achieve an operating pressure of about 10^{-10} Torr. The tube will be connected to the ion pump and vacuum stack of the present V' system.

We are also in the process of designing a new set of containment electrodes. The inner radius of the electrodes will be about 2.2 cm, and will probably include at least two electrodes divided azimuthally into sections for diagnosis and manipulation of θ -asymmetries in the plasma.

Transport experiments are continuing on the V' apparatus while CamV is being developed. Recently we have investigated the free expansion of the plasma column

along the magnetic field. This free expansion is initiated by rapidly removing the confinement potential from one end of the plasma column. The resulting electron transport is probably the fastest that can occur in pure electron columns.

The free expansion is characterized by two regimes: electrostatic pressure dominates at low temperatures where the Debye length is smaller than the plasma radius, whereas kinetic effects dominate for higher temperatures. We have developed a hydrodynamic theory valid in the low temperature regime. This theory describes the free expansion as a self-similar plasma flow consisting of a rarefaction wave propagating into the plasma column. The predictions of this theory are in moderately good agreement with time history measurements of the radially averaged plasma density made at two axial positions along the column. In the high temperature limit, we also obtain moderately good agreement with theory using a simple kinetic model of free expansion. In this limit, the electrons behave like a non-interacting neutral gas, free-streaming out of the confinement region.

We are also continuing investigation of the dynamics and turbulent noise properties of hollow profiles which have substantial shear in their drift rotation profiles. These hollow columns exhibit diocotron instabilities which saturate with the formation of several density clumps (i.e. vortices). Vortex mergers then result in density fluctuations embedded in sheared background rotation flows. The fluctuations finally decay into a reasonably quiet quasi-equilibrium. We are interested in this process for what it can tell us about the dynamics underlying statistical turbulence, in particular the decay mechanism of density fluctuations under a background shear rotation.

We are studying the statistical properties associated with the hollow plasma evolution by measuring the spatial correlations of the plasma density. On the V' apparatus, the density is measured at an array of 9 fixed collectors and one mobile probe each time the plasma is dumped. By averaging over thousands of essentially

identical initial plasmas, we obtain the density correlation versus both r and θ at any given time in the evolution.

We observe that the θ -dependent fluctuations decay exponentially at a rate which is slower than expected from the background shear, and which is relatively insensitive to radial position. In contrast, the shot-to-shot variations of the radial density profile persist hundreds of times longer. This decay behavior is observed on a variety of plasmas with different initial hollow profiles. We are presently investigating the dependence of the decay rate on various plasma parameters. When the CamV apparatus becomes available, it will be a powerful new tool for continuing these turbulence studies.

END

**DATE
FILMED**

12/11/191