DOE OFFICE OF CIVILIAN RADIOACTIVE
WASTE MANAGEMENT (OCRWM)
SYSTEM STUDIES DIGEST

N. B. McLeod^(a)
T. D. Nguyen^(b)
R. Drexelius^(b)
R. W. McKee

June 1992

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Richland, Washington 99352

-
- (a) Johnson & Associates Inc.,
Fairfax, Virginia.
(b) DOE HQ/RW.

MASTER

Summary

The Department of Energy (DOE) Office of Civilian Radioactive Waste Management (OCRWM) has sponsored system studies to support 1) the evaluation of alternative configurations and operations for the Civilian Radioactive Waste Management System (CRWMS) and 2) the development of system requirements and design specifications. These studies are generally directed toward evaluating the impacts of alternatives to the monitored retrievable storage (MRS) and fuel rod consolidation, waste form and characteristics sequences, cask and canister concepts, allocation of waste acceptance rights, and system throughput rates. The objectives of this document are

- to present major system issues and related system element issues in a structured manner
- to discuss key results of major system studies and explain the basis for certain current system assumptions
- to summarize the scope and results of completed system studies that are still relevant at the time this document is published
- to provide the background needed for identifying and prioritizing system issues to be resolved.

Consistent with the objectives, the document does not include low-level subsystem studies addressing system element issues that do not interact with overall system issues. The document is expected to be updated as major new system studies are completed and significant new results are available.

Contents

Summary	iii
Introduction	1
Key System Issues	3
Top-Level System Issues	3
System Element Issues Interacting with System Issues	3
Top-Level System Issues	5
System-Preferred Waste Form and Characteristics Sequence	5
System Design Throughput	5
Major System Uncertainties	6
System Element Issues Interacting With System Issues	7
Interaction With Transportation	7
Interaction With MRS	7
Interaction With Waste Containerization and Emplacement	7
Past System Studies	9
System Impacts of MRS and Rod Consolidation Alternatives	9
System Impacts of Alternative Waste Form and Characteristics Sequence	10
System Impacts of Cask and Canister Concepts	11
System Impacts of Alternative Allocations of Waste Acceptance Rights	12
Determination of Desirable System Throughput Rates	13
Effect of Past System Studies on Current Assumptions	13
Appendix - Summaries of Past Waste Management System Studies	A.1

System Impacts of MRS and Rod Consolidation Alternatives	A.1
<i>MRS System Study Summary Report</i>	A.1
<i>Nuclear Waste: Is There a Need for Federal Interim Storage</i>	A.2
<i>OGR Repository-Specific Rod Consolidation Study: Effect on</i>	
<i>Costs, Schedules, and Operations at the Yucca Mountain Repository</i>	A.5
<i>Final Version Dry Cask Storage Study</i>	A.7
<i>MRS Systems Study, Task F: Transportation Impacts of a Monitored</i>	
<i>Retrievable Storage Facility</i>	A.11
<i>MRS Systems Study Task G Report: The Role and Functions of Surface</i>	
<i>Storage of Radioactive Material in the Federal Waste</i>	
<i>Management System</i>	A.13
System Impacts of Alternative Waste Form and Characteristics	
Sequence	A.15
<i>The Impact of Spent Fuel Age and Exposure on Waste Package and</i>	
<i>Repository Area Thermal Loads</i>	A.15
<i>Effects of Spent Fuel Aging on Repository Disposal Requirements</i>	A.17
<i>Incentives for Selection of Spent Fuel for Delivery to the Federal</i>	
<i>Radioactive Waste Management System - A Preliminary Analysis</i>	A.18
<i>Use of Nonuniform Cask Loadings to Minimize Transportation</i>	
<i>Requirements and Provide Overall System Benefits</i>	A.19
<i>Classification of Spent Nuclear Fuel</i>	A.20
System Impacts of Cask and Canister Concepts	A.22
<i>Phase 1 Study of Metallic Cask Systems for Spent Fuel Management</i>	
<i>from Reactor to Repository</i>	A.22
<i>Use of Transportable Storage Casks in the Nuclear Waste</i>	
<i>Management System</i>	A.23
<i>Acceptance of Spent Nuclear Fuel in Multiple Element Sealed</i>	
<i>Canisters by the Federal Waste Management</i>	A.26
<i>Acceptance of Failed SNF Assemblies by the Federal Waste</i>	
<i>Management System</i>	A.28
<i>Acceptance of Canisters of Consolidated Spent Nuclear Fuel by the</i>	
<i>Federal Waste Management System</i>	A.30
<i>Acceptance of Non-Fuel Assembly Hardware by the Federal Waste</i>	
<i>Management System</i>	A.32
<i>Acceptance of Canisters of High Level Waste by the Federal Waste</i>	
<i>Management System</i>	A.34
<i>Common Canister Study</i>	A.35
<i>Evaluation of Potential Benefits of Transportable Storage Casks</i>	A.36
<i>Requirements for Canisters Used for Delivery of Spent Nuclear</i>	
<i>Fuel and Associated Materials to DOE Under Standard</i>	
<i>Disposal Contracts</i>	A.38

System Impacts of Alternative Allocations of Waste	
Acceptance Rights	A.39
<i>Spent Fuel Acceptance Scenarios Devoted to Shutdown Reactors</i>	A.39
Determination of Desirable System Throughput Rates	A.41
<i>Draft Summary Report on Determination of Cost Effective Waste Management</i>	A.41

Introduction

Since 1984, the Office of Civilian Radioactive Waste Management (OCRWM) has sponsored several system studies in an attempt to address system issues such as the impact of adding the Monitored Retrievable Storage Facility (MRS), the use of transportable storage casks, and strategies for optimal fuel selection. Some of the studies have become obsolete because the U.S. Department of Energy's (DOE) policy has changed or more recent studies have used better data and/or assumptions. Other studies are still valuable because the issues raised several years ago are still present. Pacific Northwest Laboratory (PNL)^(a) has participated in several of these studies. In this document, major system and related system element issues are presented in a structured manner, followed by a discussion of major system study results that provide current understanding of possible solutions, where those were identified. The approach should be useful in identifying areas where additional efforts should be expended. The Appendix in this report contains a summary and conclusions of each currently valid study mentioned in this report. Although no change was made to the conclusions of studies summarized, comments were added to each summary in the appendix as needed to assist the reader in evaluating the studies.

(a) PNL is operated for the U.S. Department of Energy by Battelle Memorial Institute under Contract DE-AC06-76RLO 1830.

Key System Issues

The purpose of the Civilian Radioactive Waste Management System (CRWMS) is to manage safely the disposal of high-level nuclear waste (HLW). Key system issues generally relate to the form and characteristics of the waste and how these drive the design and operational use of the various waste containers (casks, disposal containers) and related handling, preparation, and disposal operations. The desirability of the MRS is an issue that has been resolved in DOE's MRS System Study (1989) and the MRS Review Commission's 1989 report. The following is a concise list of the remaining key system issues that provide a structure for considering a hierarchy of subtier issues. These issues are subdivided into top-level system issues and system element issues interacting with system issues.

Top-Level System Issues

- Forms and quantities of waste that will be accepted
- System-preferred waste form and characteristics sequence
 - desirable waste characteristics at the time of shipment and geologic emplacement
 - preferred control method to achieve these characteristics
- Desirable system waste throughput rates
- Major uncertainties facing the system
- Sensitivity of the resolution of each key issue to these uncertainties
- Timing of design decisions to be valid for the most probable resolution of the uncertainties.

System Element Issues Interacting with System Issues

- Types, numbers, and sequence of transport casks
- Cask operating tactics that will be used in waste transportation
- Prestorage processing, type, and sequence of storage technologies, operating tactics, and post-storage processing to be used
- Prepackaging processing, disposal container types and sizes, container sequences to be used, and location for packaging

- Repository emplacement layouts, container heat criteria, and emplacement operating tactics.

The following is a brief summary of the status of each of these issues, including a few of the more significant subissues.

Top-Level System Issues

System-Preferred Waste Form and Characteristics Sequence

The allocation of fuel acceptance rights among utilities is based on the oldest-fuel-first (OFF) concept. However, when fuel is being delivered under an allocation, the fuel that is selected to be delivered does not have to be the fuel on which the allocation is based. Fuel selection is independent of fuel allocation, and there is substantial potential for controlling the characteristics of the waste stream via the selection process. Selection of the OFF concept is frequently assumed, even though the initial benefits of handling old, cold fuel are totally offset later by the difficulty of handling new, hot fuel when the older fuel runs out.

An initial evaluation of the system-preferred waste characteristics sequence, Task 8 of the Waste Acceptance Criteria evaluations, indicated that a strategy involving reasonably constant average characteristics is probably preferred over the early-cold, later-hot characteristics resulting from OFF selection. Selection methods that give reasonably constant, average waste characteristics are probably preferred over OFF. The Task 8 assessment needs to be extended and focused on providing:

- Justification to the utilities that DOE has legitimate reasons for participating in the utilities' selection of fuel at the time of delivery and possibly participating in the utilities' selection of fuel that is to be committed to dry storage. This approach, if considered, can be formulated to allow flexibility for the utilities to make the selection of spent fuel assemblies that are to be shipped to DOE at any particular time. For example, a utility could make up each shipment with a mix of spent fuel that meets a specified average characteristic, such as a 100-year levelized energy output, or some other characteristic.
- Baseline fuel characteristics sequence and characteristic variances that will be consistently used in designing all equipment and facilities. In addition, a baseline needs to be developed with respect to HLW characteristics sequence and for the method and timing of acceptance of fuel, nonfuel hardware, and other nonfuel wastes.

System Design Throughput

The currently assumed design throughput rate of 3,000 MTU per year of spent fuel has survived without change from the late 1970s and early 1980s, when spent fuel disposal estimates were double the current estimates and there were to be two repositories operating in parallel, each at 3,000 MTU per year. Subsequent studies have consistently shown that this value is close to the minimum cost value for the single-repository system. This may be somewhat on the low side, principally because the fixed component of annual system operating costs is quite high. An evaluation of this issue leading to a formal confirmation or revision of the 3,000 MTU per year rate is a priority study.

Major System Uncertainties

The impacts of uncertainties on the system design process can be minimized if the nature of each uncertainty and its area of influence are systematically evaluated and used as part of an overall design strategy. The major system uncertainties are those whose resolution is on the critical path of achieving spent fuel acceptance in 1998 and the longer term goal of beginning disposal operations in 2010. These major uncertainties include

- Location, startup date, and constraints on operation of the MRS
- Location, startup date, and constraints on operation of the repository
- Impact of host rock and licensing requirements on the disposal container design and emplacement.

A formal assessment of these and other major system uncertainties would permit the development of a sound strategy for making design progress. For example, such a strategy could include limiting the impact of the second and third uncertainties, which are repository related, on the near-term objective of fuel acceptance and interim storage. A principal source of coupling between the MRS and the repository/disposal container elements is that, with a very expensive container, fuel consolidation is likely to be viable. Additional system benefits are available if consolidation occurs prior to waste storage at the MRS and from-MRS transport. However, making a decision to consolidate fuel at the MRS before the disposal container is finalized may result in inefficiencies. Decoupling the second and third uncertainties from the first could thus be achieved by evaluating the uncertainties and the consolidation option and by formally determining for or against prestorage consolidation at the MRS. The current position is not to preconsolidate at the MRS. With this decoupling, an analysis of the impact of the first uncertainty would yield a design and implementation strategy for the from-reactor transport and the MRS system elements. Because transport cask design is a function of waste characteristics at shipment time, a key concern is a significant delay in the availability of the MRS that would cause a design change in the transport cask and in the MRS storage casks and facilities.

System Element Issues Interacting With System Issues

Interaction With Transportation

The transportation element can be adjusted to system throughput requirements simply by varying the number of casks purchased. The cask maintenance facility will require specific adjustment. The system waste sequence preference of constant average characteristics requires that casks be nonuniformly loaded with mixtures of hotter and cooler fuel. This represents a departure from traditional cask design, licensing, and operating practice, which have typically assumed uniform cask loadings with spent fuel assemblies of similar radiological characteristics. Fortunately, the radiological capacity of casks is increased with nonuniform loading, because hot assemblies are placed in the interior cavity of the cask and colder assemblies are placed in the exterior ring to take advantage of the fuel's self-shielding properties. The principal risks of the major uncertainty or the possibility of delayed MRS startup can be managed by knowing the extent of delay that would cause a difference in cask design, due to a difference in the tradeoff between cask physical capacity and cask radiological capacity; adjusted, if appropriate, for possible changes in cask external dose standards. From MRS transport cask design could also be impacted by the consolidation issue discussed below. Although transportation costs are not a major component of the total system costs, strategies that may reduce costs by a reasonable amount should be investigated further.

Interaction With MRS

The MRS and the repository are the principal fixed facilities that have substantial capital and operating costs. Both facilities influence, and are influenced by, the system throughput rate. The design of the MRS is relatively insensitive to the system-preferred characteristics sequence. However, MRS operations should maintain or enhance the sequence of characteristics of the waste entering the waste packaging process. The manageable risks are the same as those for transportation casks; there are additional uncertainties associated with the need for fuel consolidation, its possible location in the MRS, and the possibility of waste packaging at the MRS. The current planning basis for a storage-only MRS is a viable and simple approach. Consolidation and packaging location are largely optimization issues, as distinguished from technical issues, and can be reasonably deferred until there is greater certainty as to the system being optimized.

Interaction With Waste Containerization and Emplacement

The disposal container and host rock environment are the most significant components for long-term waste isolation and therefore tend to drive the system. However, with respect to the near-term goal of 1998 waste acceptance, the principal coupling to the transport and MRS elements is via the repository preference for constant waste characteristics. The uncertainty as to disposal container design could be resolved in the direction of an expensive container, which in turn could impose a cost-driven requirement for consolidation. However, unless such uncertainty were resolved prior to the startup of an early MRS, the repository would be the most likely location for rod consolidation and waste packaging.

Past System Studies

The system studies funded by OCRWM in previous years were generally formulated to address specific issues as they arose. Generally, those studies do not have a structure that corresponds one-for-one to the system issue hierarchy outlined in the previous sections. Nevertheless, past studies did address a significant subset of system and subsystem issues. The studies can be grouped into the following categories:

- System Impacts of MRS and Rod Consolidation Alternatives
- System Impacts of Alternative Waste Form and Characteristics Sequences
- System Impacts of Cask and Canister Concepts
- System Impacts of Alternative Allocations of Waste Acceptance Rights
- Determination of Desirable System Throughput Rates

The following sections discuss the major findings of the studies. The more detailed study summaries, organized by the above titles in the appendix, contain additional information. Full bibliographic information for each study discussed below can be found in the appendix.

System Impacts of MRS and Rod Consolidation Alternatives

This category of studies typically involves analyses of several top-level system issues and system element issues interacting with system issues. The Nuclear Waste Policy Act (NWPA) amendments established an MRS Review Commission to provide an independent assessment of the need for an MRS facility. Shortly thereafter, OCRWM decided to update its analysis of the role of the MRS in the waste management system and published a report on this analysis in 1989.

Both OCRWM's MRS System Study and the MRS Review Commission's independent study identified system benefits resulting from the addition of a basic MRS to the system. The basic MRS is a storage facility without fuel rod consolidation or production of disposal containers. System benefits would be associated primarily with an MRS that is not linked with the repository as provided in the current NWPA linkage. Benefits include such things as relief for utility storage problems, emergency storage, and timely waste acceptance.

A Sandia National Laboratory (SNL) 1988 report documented OCRWM's analysis of the effects of rod consolidation on the repository for two scenarios, consolidation at the repository and consolidation at the MRS. Rod consolidation at the repository was not found to be cost-effective or operationally advantageous. At-MRS rod consolidation would be beneficial to repository economics and operation if compared with the scenario involving at-repository consolidation. Although the SNL study did not assess rod consolidation from an overall system perspective, the previously described 1989 MRS System Study analyzed in some detail system tradeoffs associated with rod consolidation. The results did

not point to compelling reasons for favoring rod consolidation and/or packaging spent fuel at the MRS. As disposal container cost estimates are revised in the future, the conclusions of the study may be revisited.

In a 1989 Dry Cask Storage Study, OCRWM evaluated existing storage technologies and concluded that these are safe and environmentally acceptable options for storing fuel at reactor sites until such a time as a federal facility is available to accept the spent fuel. However, the study also examined the impact of an MRS on reactor storage needs, and concluded that an MRS with the proper ramp-up rate would reduce cumulative reactor storage needs.

System Impacts of Alternative Waste Form and Characteristics Sequences

A 1987 PNL study evaluated the impact of spent fuel age and exposure on allowable waste package and repository area thermal loads in tuff, salt, and basalt. The results were intended to be a basis for identifying possible waste package and emplacement strategies for accommodating a projected range of spent fuel characteristics and to recommend possible incentives for system design improvements. For example, allowing spent fuel to age, increasing the spent fuel matrix thermal conductivity, and reducing the uncertainty in host rock limiting temperature constraints would reduce waste package and repository mining requirements.

In 1991, PNL investigated system impacts of a hypothetical repository delay, with startup in 2060. It was found that additional above-ground cooling would result in significantly reduced mining and waste container requirements. The delay would result in spent fuel characteristics such that maximum bore-hole wall temperatures would be lower, but elevated temperatures would be maintained for longer time periods relative to the 2010 startup scenario, thereby aiding the "hot" emplacement strategy.

A 1991 study involving multiple OCRWM contractors, the Waste Acceptance Criteria Task 8 report entitled *Incentives for Selection of Spent Fuel for Delivery to the Federal Radioactive Waste Management System*, was to determine OCRWM's preferences for spent fuel selection. Once a utility has an allocation of fuel to be delivered, selection is the process by which specific assemblies are chosen for delivery. The study concluded that

- The repository prefers a levelized (constant average) heat and integrated heat per waste package (this implies that some mixing and blending of fuel assemblies is needed, unlike straight selection of OFF).
- The MRS is substantially indifferent to waste selection.
- For uniformly loaded transportation casks (loaded with radiologically similar fuel assemblies), OFF selection is preferred. An analysis of nonuniform fuel loadings in rail casks was included in an appendix of this report.

An OCRWM assessment of nonuniform cask loading, a 1989 study by E.R. Johnson Associates (JAI) and David Andress and Associates (DAA), should also be noted. Nonuniform loading would minimize

Relative to the multipurpose cask, the transportable storage cask (TSC) has the advantage of being decoupled from disposal requirements. In a JAI study of TSCs (1987), it was found that the only significant benefit to the system of accepting TSCs occurs when OCRWM can avoid buying or building similar casks for OCRWM use in transport or MRS storage. For such savings to occur, the utility would have to make a binding commitment to future cask delivery at the same time that OCRWM must otherwise make its own commitment to buying casks or designing and constructing storage facilities. However, the logistics of utility cask storage is such that very few utilities could justify committing to deliver TSCs prior to or during the initial startup of the waste system. Each delivery of fuel in the cask would normally require that the utility purchase and load a new cask to make room for the next fuel discharge, an uneconomical strategy. Only after fuel acceptance rates have exceeded fuel discharge rates for some time can a utility gain enough storage margin to sensibly consider delivering casks to OCRWM. In addition, the ability to maintain the transport certification of casks (for NRC purposes) used for storage over many years remains uncertain.

Another JAI study analyzed the impacts of accepting NUHOMS multiple-element sealed canisters (MESCs), which would be transferred from horizontal storage modules into an OCRWM transport cask for shipment. It was found that several system and system element issues are similar, although not identical, to those associated with the acceptance of TSCs.

Other JAI studies investigated system impacts of receiving failed fuel, canisters of consolidated fuel and compacted hardware resulting from rod consolidation, and nonfuel-assembly hardware (NFAH). Failed fuel that is encapsulated in "standard" canisters, i.e., canisters having an envelope about the same as standard fuel assemblies and meeting other requirements proposed in a 1990 JAI report (these requirements meet both the utility's storage needs and OCRWM's transportation needs), will be handled like fuel assemblies. Failed fuel that is structurally damaged or contained in nonstandard canisters is proposed to be subject to delayed acceptance. For consolidated fuel, provided that a net compaction ratio of at least 1.45 is achieved, the acceptance of consolidated fuel rods and compacted hardware in standard canisters would not cause negative system impacts. For NFAH, its acceptance by OCRWM will impact the system because this is an additional waste stream. Impacts would be reduced, although not eliminated, if utilities were to deliver NFAH integral with fuel assemblies and compact any NFAH that must be delivered separately from assemblies.

System Impacts of Alternative Allocations of Waste Acceptance Rights

In 1989, PNL and Battelle Columbus investigated for OCRWM the system impacts of allocating waste acceptance rights other than on an OFF basis. Allocation scenarios considered included granting exclusive spent fuel acceptance rights to shutdown reactors in order of shutdown date or to reactors with imminent storage capacity needs. Although these preliminary investigations provided useful insight, additional studies should be undertaken to better understand the tradeoffs and constraints. Granting exclusive rights to shutdown reactors was shown to result in major distortions in the number and type of casks needed in some years, distortions that were aggravated further by the need to handle short-cooled fuel.

Appendix

Summaries of Past Waste Management System Studies

System Impacts of MRS and Rod Consolidation Alternatives

MRS System Study Summary Report. June 1989. **DOE/RW-0235, Office of Civilian Radioactive Waste** **Management, U.S. Department of Energy.**

Summary

This report summarizes the results of the Monitored Retrievable Storage Facility (MRS) system studies that were performed. Three scenarios were used to analyze various configurations for the waste management system. The first scenario addressed a system that would dispose of intact spent fuel in a repository that would start operating in 2003. The second scenario examined various configurations of a system that would dispose of consolidated fuel in a repository that starts operating in 2003. The third scenario analyzed the effects of delaying the start of repository operations by both 5 and 10 years. This scenario also examined the effects of the conditions in the Nuclear Waste Policy Amendments Act (NWPAA) that limit the storage capacity of the MRS facility and link its development and operation to the repository.

The DOE's previous position on an MRS facility, as articulated in the 1987 MRS proposal to Congress, held that an MRS facility provides tangible benefits to the waste management system. The results of the MRS system studies support that general conclusion. Of all the system configurations analyzed, a basic MRS facility in the eastern U.S. would provide the greatest benefits to the waste management system in terms of early and adequate acceptance, schedule confidence, and increased system flexibility. The benefits of this configuration would be magnified if the conditions and linkage in the NWPAA were removed or modified.

The basic MRS facility would increase costs by about \$1.3 to \$1.7 billion, depending on the scenario examined. The addition of packaging functions (to load waste into disposal containers) to the MRS facility would increase costs more, by approximately \$0.9 to \$1.5 billion in the intact fuel scenario. If the repository were delayed by 10 years or more, the MRS system would not cost any more than the no-MRS system.

All of the system configurations examined are licensable. For the systems with an MRS facility, licensing is expected to be easiest and quickest for the basic MRS facility. The MRS system studies conclude that a basic MRS facility is preferable at present. No significant benefit was identified for either consolidating spent fuel or encapsulating it into disposal containers at an MRS facility. However, because of the current uncertainties about the waste package, there would be a benefit in retaining the flexibility to add these more complex functions to the MRS facility at a later time if such functions were found to be beneficial or necessary as the system design matures.

Nuclear Waste: Is There a Need for Federal Interim Storage?

November 1989. Monitored Retrievable Storage Commission.

Summary

Congress created the Monitored Retrievable Storage Commission to report on the need for a federal MRS as part of the nation's nuclear waste management system. Congress asked the commission to review the Secretary of Energy's proposal to create an MRS, evaluate the technical need for an MRS, obtain data and comments from affected parties, and recommend whether such a facility should be included in the nuclear waste management system. The following is a summary of the conclusions and recommendations that resulted from this study.

Conclusions

- From a technical perspective, both the no-MRS and MRS options are safe. Although neither option is completely without risk, the commission determined that the risks are expected to be small and within regulatory limits, and the degree of difference in risks is so small that the magnitude of difference should not affect the decision as to whether there should be an MRS.
- The net cost of a waste management system that includes an MRS would be lower than previously estimated because of delays that have already occurred in the expected date of repository operation and the likelihood of further slippage of that date. The economics of an MRS would become more favorable if the repository were delayed and if the MRS were to accept spent fuel as early as possible. These effects would become especially significant if the repository operation were to be delayed beyond 2013, when there will be a sharp increase in the number of nuclear power plants whose current licenses will expire. If a repository were not in operation by that time, utilities would incur major additional costs that would result from the inability to remove spent fuel from plants being decommissioned. However, a system with an MRS would still be somewhat more costly on a discounted basis than one without an MRS.
- No single discriminating factor would cause the MRS alternative to be chosen in preference to the no-MRS alternative. Although the commission found no single factor that would cause it to favor one alternative, it believes that, cumulatively, there are a number of advantages that would justify a central storage facility neither limited in capacity nor linked to the repository schedule and operation. These advantages include
 - Storage for emergency purposes
 - Storage for utilities that do not have sufficient space in their spent fuel pools or onsite storage, or that cannot obtain a license for additional at-reactor storage and hence might be required to shut down an otherwise satisfactorily operating nuclear power plant

- Storage for spent fuel from shutdown reactors
 - Economies in the waste management system if an MRS could be substantially completed before the repository
 - Greater redundancy in the system in the event of unforeseen circumstances
 - More surge capacity to facilitate the flow of spent fuel to the repository
 - More flexibility in storage options and future waste preparation functions
 - Assistance in standardization
 - Initiation of federal responsibility for taking possession of spent fuel.
- An MRS linked as provided in current law would not be justified, especially in light of uncertainties in the completion time for the repository. Consequently, the commission does not recommend a linked MRS as required by current law and proposed by DOE. The commission notes that for many years members of Congress, other public officials, environmental groups, and many private citizens have expressed concern that an unlinked MRS might be regarded as a de facto repository, thereby reducing the impetus for building the repository as expeditiously as possible. Although the commission does not believe that there is a technical basis for the linkages, they agree that, in light of congressional and other concerns about a de facto repository, some linkages are justified.

The schedule linkage presently in the NWPA would make it impossible for an MRS to be operational more than three years before the repository. Because of delays already experienced in the repository schedule and continued uncertainty surrounding the repository's location and date of operation, the value of the MRS would be greatly diminished if its construction were tied to the schedule of the repository. Most of the need for an MRS would have disappeared, because utilities would have had to make other arrangements for storage.

- It would be in the national interest to use some interim storage facilities that would be substantially more limited in capacity and built under conditions different from the DOE-proposed MRS to provide for emergencies and other contingencies. The commission recognizes the need to provide certain services that would be in the national interest but that could not be provided by an MRS restricted by the schedule linkages currently in the law. The commission concludes that spent fuel storage for emergency and other purposes would be in the national interest. Facilities to fulfill this national interest could be more limited in scope and could be built under different conditions than the DOE-proposed MRS.

Recommendations

In view of the conclusions noted above and in light of its extensive studies and deliberations, the commission recommends the following:

- Congress should authorize construction of a Federal Emergency Storage (FES) facility with a capacity limit of 2,000 MTU.
- Congress should authorize construction of a User-Funded Interim Storage facility with a capacity limit of 5,000 MTU. Such a facility would provide storage only and would be used in addition to the FES facility proposed in the above recommendation.
- Congress should reconsider the subject of interim storage by the year 2000 to 1) take into account uncertainties that exist today but might be resolved or clarified within 10 years, 2) consider developments which cannot be anticipated today, and 3) evaluate the experience with the two facilities recommended above.

OGR Repository-Specific Rod Consolidation Study: Effect on Costs, Schedules, and Operations at the Yucca Mountain Repository.

**August 1988. P. D. O'Brien. Sandia
National Laboratory.**

Summary

In this report, repository life-cycle costs are compared and operational tradeoffs are assessed for waste management scenarios with and without spent fuel rod consolidation. Four cases are considered: In Cases 1 and 2, intact spent fuel is received directly from the nuclear utilities; in Cases 3 and 4, most of the fuel is received from an MRS facility. Case 1 features at-repository consolidation, whereas in Case 2 the fuel would be packaged and emplaced as intact fuel assemblies. Case 3 assumes at-MRS consolidation. Case 4 assumes no consolidation either at the MRS or at the repository.

The total life-cycle cost for the Case 1 (reference) repository is about \$6.6 billion (in 1986 dollars). In Case 2, "intact" disposal would save \$0.5 billion and would offer a number of operational advantages. The presence of an MRS in the waste management system would reduce repository costs with or without at-MRS consolidation. Life-cycle costs for Cases 3 and 4 are, respectively, \$1.2 billion and \$1.0 billion less than the cost of Case 1. Consolidation at the MRS would reduce the repository cost by \$0.2 billion. Operationally, the MRS would be advantageous in that it would eliminate or, rather, transfer to the MRS, those operations that are potentially the most hazardous in preparing spent fuel for disposal. On the basis of the guidelines established for this study, and from the analyses and arguments in Sections 3.0 and 4.0 of the referenced OGR report, the following inferences can be drawn with regard to the effect of fuel consolidation on the cost and operation of the candidate Yucca Mountain repository.

- The life-cycle cost of the Case 1 (reference) repository (no MRS, at-repository consolidation) is about \$6.6 billion.
- The life-cycle cost of the Case 2 repository (no MRS, no consolidation) is about \$6.1 billion (elimination of the at-repository consolidation operation saves \$0.5 billion).
- Even a large increase in disposal container costs would not change the cost balance between Cases 1 and 2. Repository life-cycle costs would be equal if the container costs for both cases were multiplied by a factor of 5.7. Therefore, the fact that the container material and design specifications will not be finalized in the near future is not a matter of serious concern, at least insofar as those specifications might influence the decision for or against at-repository consolidation.

- Without at-repository consolidation, full (3,400 MTU/yr) operation of the repository can be achieved approximately one year earlier than is possible with at-repository consolidation.
- As determined from Cases 3 and 4, at-MRS consolidation would save \$0.2 billion in repository life-cycle costs. The effect of consolidation on MRS costs and on waste management system costs depends on factors that are beyond the scope of this study.
- Most of the operational factors that were considered only qualitatively favor spent fuel disposal without consolidation in the Authorized System (no MRS), and disposal with consolidation in the Improved Performance System (MRS). In the context of operation at the Yucca Mountain repository, none of the factors favoring consolidation is considered to be overriding in importance.

In summary, the results of the study indicate that consolidation at the Yucca Mountain repository would be neither cost-effective nor operationally advantageous. At-MRS consolidation is seen to be advantageous from the perspective of repository cost and operation. However, because of its limited scope, the study does not support a recommendation either for or against consolidation at the MRS. As disposal container cost estimates increase, these results should be revisited.

Final Version Dry Cask Storage Study.

February 1989.

**DOE/RW-0220, Office of Civilian Radioactive Waste Management.
U.S. Department of Energy.**

Summary

This report was prepared in response to section 5064 of the NWPA, which directs the Secretary of Energy to conduct a study on using the dry cask storage technology for storing spent fuel at the sites of civilian nuclear reactors until a geologic repository is available. In conducting this study, the Secretary was to consider such factors as costs, effects on human health and the environment, and the extent to which the Nuclear Waste Fund can and should be used to provide funds for at-reactor storage. In addition, the Secretary was to consult with the NRC, include NRC comments in the report, and solicit the views of state and local governments and the public.

To evaluate the costs and impacts of dry cask storage, DOE used the following approach:

- DOE estimated the additional at-reactor storage capacity that would be required to accommodate spent fuel until it is removed from a reactor site. This required projecting how much spent fuel will be discharged, estimating existing storage capacities and considering the rate at which spent fuel will be removed from reactor sites by acceptance into DOE's waste management system.
- DOE identified and evaluated various options for increasing at-reactor storage in terms of design features, spent fuel handling operations, costs, and potential effects on the health and safety of the public and the reactor workers. The options evaluated included the consolidation of spent fuel assemblies and several methods of dry storage.
- DOE evaluated the potential effects of the various options for at-reactor storage and transportation.

Conclusions

Reactor dry storage technology is available and safe. The cumulative aggregate requirements for additional storage range from 12,200 to 20,000 MTHM for the upper and lower bounds on the spent fuel discharge forecasts, respectively. For the reference case (spent fuel acceptance by the repository begins in 2003), the storage inventory peaks within 4 years of the start of spent fuel acceptance by the DOE. However, after the year 2007 an increase in storage capacity will be required at a number of reactor sites because the rates at which these reactors discharge spent fuel will exceed the rate at which the spent fuel is removed from their sites. Consequently, the cumulative additional storage requirements continue to increase and do not peak until the years 2012 and 2016 for the lower and the upper bounds, respectively. The number of reactor sites requiring additional spent fuel storage ranges from

54 (in the year 2012) to 67 (in the year 2016). Because some nuclear power stations contain several reactors located at the same site, the number of reactors requiring additional storage capacity is higher, 83 in 2012 to 107 in 2016.

For the three alternative-acceptance cases examined in this report, the removal of spent fuel from the reactor sites was assumed to start in 1998, 2003, and 2008 at the reference ramp-up rates for the MRS facility. The case where acceptance begins in the year 2003 at the MRS acceptance rate represents the authorized DOE waste management system. A comparison of this case with the reference case (repository-only system) shows that the accelerated MRS ramp-up rate would reduce the additional storage requirements by 2,440 to 3,790 MTHM.

The additional storage requirements are not evenly distributed among reactor sites, because the maximum storage capacities of reactor pools are not related to the projected cumulative discharges. For the lower-bound storage requirement, 29 of the 54 reactor sites needing additional storage in the reference case need 200 MTHM or less, but a few need much more. For the upper-bound storage requirement, 37 of the 67 sites need more than 200 MTHM. (200 MTHM is about 40 percent of a typical pool capacity, or the equivalent of about 20 typical dry casks of intact fuel.)

Technologies for At-Reactor Storage

The dry cask study also examined the options that could be implemented at the sites of U.S. civilian reactors for storing spent fuel, including rod consolidation to increase the capacity of existing storage pools. The dry-storage options include metal casks, concrete casks, horizontal concrete modules, modular concrete vaults, and dual-purpose casks that can be used for both storage and transportation. Although the various options differ somewhat in their technical maturity, no significant technical problems are expected with any of them. Both intact and consolidated spent fuel can be stored in these devices. To date, both storage in metal casks and storage in horizontal concrete modules have been licensed by the NRC. In addition, the NRC staff has approved a topical report on the use of modular concrete vaults and is reviewing a report on the use of concrete casks.

Estimated Costs

The estimated aggregate costs of providing additional at-reactor storage capacity for the reference case (spent fuel acceptance by the repository begins in 2003) range from about \$500 million to \$2 billion. For the three alternative-acceptance cases (start of acceptance by the MRS facility in 1998, 2003, and 2008 at MRS ramp-up rates), the estimated aggregate costs range from \$200 million to \$2.7 billion. Considerable uncertainty is associated with the cost estimates.

Impacts on Health and Safety and the Environment

In its Waste Confidence Decision of August 31, 1984 (49 CFR 171), the NRC stated that "the commission finds reasonable assurance that, if necessary, spent fuel...can be stored safely and without significant environmental impacts" in reactor storage pools or in "independent spent fuel storage installations." The NRC's findings were supported by experience with more than 80 individual safety evaluations of spent fuel storage facilities. For dry storage, the NRC stated its belief that current technologies are capable of providing safe storage for spent nuclear fuel for at least 30 years beyond the expiration of the operating license. The NRC also concluded that the possibility of a major accident or sabotage at a spent fuel storage facility with radiological consequences to the public is extremely remote.

The NRC's findings are supported by the results of the radiation safety analyses conducted for this study, which show that the typical radiation exposure risk for the public is negligible. As an example, the public dose commitment from dry storage at one particular reactor site is only 0.02% of the annual dose received by the same population from natural background radiation.

Transportation Impacts

None of the dry-storage options would significantly affect transportation unless the spent fuel is consolidated. For transportation, intact spent fuel that is stored in casks or other dry-storage devices may be required to be transferred to the same type of shipping cask that would be used for intact spent fuel stored in pools. Thus, no modifications to the transportation system are needed, and there are no changes in the transportation operations or in the number of shipments required for a given quantity of spent fuel.

Using dual-purpose casks, if approved by the NRC for transportation, would have the advantage of eliminating loading spent fuel into shipping casks, thus reducing the number of shipping casks needed for the transportation fleet. The overall impacts on the transportation system would be minimal. Additional cost savings may be realized by using these casks for lag storage at a DOE waste management facility. The benefits to the system would depend on the timely availability of these casks to the utilities as well as to DOE's transportation system.

Spent fuel consolidation can increase the payload per shipping cask, which could reduce the number of shipments required for transporting a given quantity of spent fuel. Reducing the number of shipments depends on optimizing cask capacities. This potential benefit, however, would represent a small portion of the overall cost of waste management.

Use of the Nuclear Waste Fund for At-Reactor Storage

The Nuclear Waste Policy Act of 1982 (NWPA), which established the Nuclear Waste Fund, does not authorize DOE to use the Nuclear Waste Fund to provide direct financial support for storage at reactor

sites. DOE will consider mechanisms whereby the utilities can realize benefits resulting from at-reactor spent fuel management activities if such activities can be demonstrated to be beneficial to the overall waste management system. However, it would be difficult at present to identify and quantify the benefits, because the design and development of the overall waste management system are still in a preliminary stage, and it is not clear which technologies the utilities are likely to select; nor is it clear which technologies would be of benefit to the waste management system, because of its developmental status. Studies being conducted by DOE are examining the potential for at-reactor activities to contribute to the goals of the waste management system. As these efforts proceed, DOE will discuss them with potentially affected parties and factor them, as appropriate, into program planning and facility design activities.

Conclusion

DOE concludes that the existing dry cask storage technologies are technically feasible, safe, and environmentally acceptable options for storing spent fuel at the sites of civilian nuclear reactors until such a time as a federal facility is available to accept the spent fuel.

***MRS Systems Study, Task F: Transportation Impacts of a Monitored
Retrievable Storage Facility. May 1989.***

**L. A. Brentlinger, S. Gupta, A. M. Plummer, L. A. Smith,
and S. Tzemos. BMI/OTSP-07, Battelle Nuclear Systems Group.
Office of Civilian Radioactive Waste Management.**

Summary

This is one of several study tasks supporting DOE's 1989 MRS System Study Summary Report. (Note: 1989 MRS study tasks are not included in this Appendix if their focus was on a nonsystem issue such as design selection or licensing.) This report documents the differences in transportation costs and radiological dose under alternative scenarios pertaining to a nuclear waste management system with and without an MRS, including the effects of various MRS packaging functions and locations. The analysis is limited to the impacts of activities related directly to hauling HLW, including the capital purchase and maintenance costs of the transportation cask system. Loading and unloading impacts are not included in this study because they are treated as facility costs in the other task reports. Transportation costs are based on shipments of 63,000 MTU of spent nuclear fuel and 7,000 MTU equivalent of HLW.

In general, from a transportation standpoint, the MRS is economically more favorable than a no-MRS system when its packaging function maximizes MRS-to-repository cask capacity and minimizes reactor-to-MRS shipment miles. When evaluating the generic eastern and western MRS locations, only the generic eastern MRS, which stores and ships intact fuel with a western strategy or consolidates and canisters fuel, realizes these above efficiencies to the extent that they provide a net transportation cost savings over a no-MRS system. Savings range from \$100 to \$200 million over the 24-year life of the project.

In the store-only case with the generic eastern MRS, the western strategy would be needed to minimize cross-country shipping to bring system transportation costs closer to those of the no-MRS system. For the consolidate-and-containerize and containerize-intact cases, the from-MRS cask efficiency is low, so an eastern MRS location increases costs. The western MRS would not significantly reduce cross-country shipping miles, so none of the western MRS cases would give lower costs than the no-MRS case.

A comparison between the generic eastern MRS and the generic western MRS indicates that the eastern MRS would provide the following (the cost variation depends on whether or not the western strategy is used):

- 5 to 15 percent cost savings for the store-only case

- 15 to 25 percent cost savings for the consolidate-and-canister case and
- 2 to 10 percent increase for the containerized intact spent fuel case.

The minimum shipment-mile location, when compared to the generic eastern location, represents

- 15 to 25 percent cost savings for the store-only case
- 25 to 35 percent cost savings for the consolidate-and-canister case
- 1 to 10 percent cost savings for the consolidate-and-containerize case.

The minimum shipment-mile MRS is located such that the average distance from reactors is shorter in comparison to the eastern MRS location, which results in a cost savings of more than ten percent.

An MRS that consolidates and canisters spent fuel appears superior in terms of reducing transportation costs over the three other alternatives (nonconsolidation alternatives) analyzed in this study, because consolidation of fuel into canisters would allow efficient use of the cask interior space.

With a generic eastern MRS location, a western strategy would reduce transportation costs by about \$95 million for an MRS that would store only, and about \$85 million for an MRS that would consolidate and canister the spent fuel. The total shipment-miles would be reduced by not shipping from the western reactors to an eastern MRS and then back to a western repository. In addition to lower transportation costs, an eastern MRS system would result in a reduced number of shipments and shipment-miles when compared to a western MRS or a no-MRS system.

Using overweight truck casks (5 PWR/12 BWR assemblies) reduces the cost of from-reactor shipments by approximately \$80 to \$160 million compared with legal-weight truck casks (3 PWR/7 BWR assemblies), depending on the Federal Waste Management System (FWMS) configuration and MRS location. The cost reduction is the result of the increased cask capacity and corresponding reduced number of shipments.

The option of shipping HLW directly to the repository is noticeably more cost-effective than shipping through an eastern MRS and marginally more cost-effective than shipping through a western MRS. The total shipping distance for Idaho and Hanford HLW increases significantly for the eastern MRS compared with the no-MRS case. These two sites ship about 45 percent of the total HLW. In analyzing transportation dose, the total transportation dose for the 11 core cases (see study for details) indicates that transporting spent fuel would result in an in-transit dose of 1,400 person-rem for spent fuel consolidation and canistering at an eastern MRS with a western strategy to 2,600 person-rem for a no-MRS system. An eastern MRS would reduce the dose 25 to 45 percent over a western MRS (depending on the packaging selection) or a no-MRS system, because it reduces the number of cross-country shipments.

***MRS Systems Study Task G Report: The Role and Functions
of Surface Storage of Radioactive Material in the
Federal Waste Management System. April 1989.***

**T. W. Wood, M. K. Altenhofen, S. M. Short,
C. A. Mackay, and M. G. Woodruff.
PNL-6876, Pacific Northwest Laboratory.**

Summary

This study investigates the functions that could be performed by surface storage of radioactive material within the radioactive waste management system, including:

- enabling acceptance of spent fuel from utility owners
- scheduling waste preparation processes within the system
- enhancement of system operating reliability
- conditioning the thermal (decay heat) characteristics of spent fuel emplaced in a repository.

While these are not required functions for the FWMS, each represents a potential benefit of storage capacity within the system and was evaluated in the study to determine the storage capacity required to perform it. This evaluation was conducted for a wide range of MRS and repository-only scenarios, including variations in the deployment timing and storage capacity of the MRS and repository, and the extent to which these are linked (as in the NWPA) or independent of each other's schedule.

The analysis focuses particularly on the effects of storage capacity and DOE's acceptance schedule on power reactors. Figures of merit developed include

- the storage capacity [in metric tons of uranium (MTU)] required to be added beyond currently estimated maximum spent fuel storage capacities
- the associated cost
- the number of years that spent fuel pools would remain open after last discharge (in pool years)
- the cost of this period of operation.

Principal Findings

The principal findings of this report are the following:

- The storage capacity provided by an MRS facility could be used to substantially limit the projected burden of utility storage requirements above pool capacities.
- An MRS that began accepting spent fuel as early as possible with a storage capacity of at least 30,000 MTU would maximize this benefit.
- The same MRS deployment scenario could also provide substantial benefit in terms of reduced length of pool operations after last discharge if repository deployment were substantially delayed.
- An MRS deployed per the NWPAA constraints on schedule and storage capacity, while still beneficial, would provide significantly fewer benefits in terms of avoided costs at reactors.
- The storage capacity at an MRS facility could enhance system operating reliability by allowing continuation of either the emplacement or the spent fuel acceptance functions in the event of long-duration reductions in the acceptance or emplacement rates.
- The process scheduling function could be provided satisfactorily in either a repository-only or an MRS system.
- The heat management function, if it proves valuable, could be accomplished either through 25,000 MTU of storage capacity at an MRS or by selection of spent fuel from reactors in a repository-only system.

System Impacts of Alternative Waste Form and Characteristics Sequence

The Impact of Spent Fuel Age and Exposure on Waste Package and Repository Area Thermal Loads. 1987.

**M. K. Altenhofen, N. L. Sevigny, K. I. Johnson, and R. E. Graves.
Pacific Northwest Laboratory.**

Summary

The effects of emplacing 5-, 10-, and 15-year-old pressurized water reactor (PWR) spent fuel on waste package and repository area thermal loads in basalt, salt, and tuff geologic media were evaluated to determine the impact of spent fuel age and exposure on allowable waste package and repository area thermal loads. Separate methodologies were used to analyze waste package and repository area thermal loads, and the results of the independent analyses were integrated to estimate the allowable waste package/repository area thermal design envelope for each spent fuel type and repository medium combination. The results of this study can be used to identify possible waste package and emplacement strategies for accommodating a projected range of spent fuel characteristics and to recommend possible incentives for waste isolation system design improvements.

In general, allowable waste package and repository thermal loads are more sensitive to age than exposure. On an equivalent MTU basis, allowable waste package and repository area mass loads are more sensitive to exposure than to age. The allowable waste package and repository area thermal loads are strongly dependent on site-specific near-field temperature and far-field thermal constraints and spent fuel matrix thermal properties. The assumptions concerning material properties and design parameters are equally important. The general trends observed in this study should be valid for the range of spent fuel age and exposure levels evaluated.

Depending on the spent fuel age, spent fuel matrix thermal conductivity, and host rock temperature constraint, waste packaging and emplacement design strategies can be identified to accommodate an anticipated range of spent fuel exposure characteristics. For the situation resulting from younger spent fuel, a low spent fuel matrix conductivity, and a high host rock temperature limit, the allowable waste package thermal load is generally insensitive to the allowable repository area thermal load. The insensitivity results from the relatively early occurrence of peak temperatures. A variable waste package diameter and constant emplacement pitch design strategy would be favorable in this situation. The variable diameter/fixed emplacement pitch strategy would maintain a maximum constant waste package and repository area thermal load throughout the waste isolation system. In the variable diameter/fixed pitch strategy, the designer would base the number and specification of waste package diameters on the spent fuel initial heat generation rate distribution and the allowable waste package thermal load.

For the situation resulting from older spent fuel, a high spent fuel matrix thermal conductivity, and a low host rock temperature limit, the allowable waste package thermal load is generally sensitive to the allowable repository area thermal load. The sensitivity results from the relatively late occurrence of peak temperatures. A fixed waste package diameter and variable emplacement pitch strategy would be favorable in this situation. This strategy is based on tailoring the emplacement pitch to a variable waste package thermal load to minimize packaging and/or excavation requirements. In the variable diameter/fixed pitch strategy, the waste package diameter would be based on the spent fuel heat generation rate distribution and tradeoffs between waste packaging and excavation costs in the waste isolation system. The designer can base the waste package diameter on an allowable waste package thermal load between the constraints imposed by spent fuel centerline temperatures and far-field criteria.

Several technical and economic tradeoffs need to be evaluated to establish the preferred waste package and emplacement strategy in each medium type. It is possible that some combination of these strategies may be preferred, because age can have a significant impact on the thermal design envelope. In any case, waste packaging and emplacement design strategies must be determined on a site-specific basis, using a projection of the spent fuel age and exposure characteristics to maximize the efficiency of the system.

The results of this study also suggest possible incentives to improve the design of the waste isolation system. Aging spent fuel, increasing the spent fuel matrix thermal conductivity, and reducing the uncertainty in host rock limiting temperature constraints would reduce waste package and repository area requirements and tend to support a fixed waste package diameter strategy. These incentives are based on factors controlled by DOE, particularly the spent fuel age and the matrix thermal conductivity. A fixed waste package and variable emplacement design strategy is attractive because it is more consistent with the current design approach and more practical in terms of interfacing requirements. Increasing the spent fuel matrix thermal conductivity through the use of stabilizer materials (e.g., internal fins, fill gas) would relax the constraint imposed by spent fuel cladding temperature. Reducing the uncertainty in the host rock temperature limits is likely to relax the constraints imposed by emplacement borehole wall temperatures and provide necessary input in support of design optimization.

***Effects of Spent Fuel Aging on Repository Disposal
Requirements (Draft). 1991.***

**R. W. McKee, K. I. Johnson, H. D. Huber, and M. C. Bierschbach.
Pacific Northwest Laboratory**

Summary

This study investigated system impacts of repository schedule slippage beyond the year 2010, when the average spent fuel age will be 28 years. If the repository must be delayed until 2060 (average fuel age of 78 years), requirements would be significantly reduced for mining and waste containers. The delay would result in spent fuel characteristics such that maximum borehole wall temperatures would be lower but elevated temperatures would be maintained for longer time periods relative to the 2010 start-up scenario, thereby aiding the "hot" emplacement strategy. To estimate increased repository waste loadings for aged spent fuel, a new method, Equivalent Energy Deposition (EED), was successfully applied. EED assumes that equal energy deposition from the spent fuel over equal time periods should equate to equal thermal effects. Sandia National Laboratory adopted this method in 1991 for use in Yucca Mountain Project Office (YMPO) analyses. The need for the method is explained below.

Much of the thermal effect of spent fuel on the repository environment is controlled more by the cumulative or integrated thermal energy deposited in the repository over a period of time than by the initial thermal power at the time of emplacement in the repository. If a 100-year period is required to reach a constraining peak temperature for a reference repository waste loading, then any other waste loading that deposits the same thermal energy over a 100-year period should produce a comparable peak temperature. If the spent fuel activity decayed with a constant half-life, this relationship would be exact. However, because of the complex relationships between the decay rates of the constituent radionuclides, the relationship is not exact. As spent fuel ages, the effective decay half-life is continuously changing (i.e., the decay rate is declining and the effective half-life is increasing). Consider two groups of emplaced spent fuel, a younger group and an older group, with each group producing the same 100-year energy deposition. The older spent fuel will start out at a lower areal power density (APD) and end up at a higher APD relative to the younger fuel. The EED method provides a good approximation of the effect of fuel aging on allowable repository waste loadings.

***Incentives for Selection of Spent Fuel for Delivery to the Federal
Radioactive Waste Management System — A Preliminary Analysis
(Draft). 1991. PNL, LLNL, JAI, DAA, SNL.***

Summary

The purpose of this report, the Waste Acceptance Criteria Task 8 Report was to determine DOE's preferences for spent fuel selection. Once a utility has an allocation of fuel to be delivered, selection is the process by which specific assemblies are chosen for delivery. Except for fuel that has been committed to extended storage, utilities do not appear to have strong preferences for any particular waste selection method. As noted below, DOE can achieve specific system benefits via appropriate fuel selection.

Task 8 was a multicontractor effort, including transportation, repository, MRS, and overall system participants, coordinated by PNL. The selection preferences for each of the separate system elements are discussed below.

- **Transportation** - It was initially decided to assume uniform loading of casks because neither the design data nor the methods were readily available for analyzing nonuniform cask loadings. For uniformly loaded casks, OFF selection was preferred.
- **Repository** - A levelized (constant average) heat and integrated heat per package is preferred.
- **MRS** - This system is substantially indifferent to waste selection.
- **System** - Based on consideration of the preferences of the repository and of transportation, there appeared to be a conflict between the goals of the repository and the goals of transportation. However, it was also recognized that the transportation preference for OFF selection was a direct consequence of the assumption of uniform cask loading. Initial assessments of nonuniform loading based on new methods and preliminary design data clearly show that it is preferable to uniform loading because it reduces or eliminates the necessity of reducing cask payloads for the hottest fuels. Thus, with nonuniform loading, the selection preferences of the repository and transportation are very similar — select wastes to achieve a waste stream with constant characteristics, averaged over the cask or waste package load.

In summary, DOE has significant incentives to select fuel that provides relatively constant average radiological and thermal characteristics. Because the Standard Contract does not currently give DOE any specific rights of fuel selection, it may be appropriate to include such a provision among the potential changes that may occur in the Standard Contract.

Use of Nonuniform Cask Loadings to Minimize Transportation Requirements and Provide Overall System Benefits. 1989.

D. Andress and N. B. McLeod. DAA and JAI.

Summary

Strategies to enhance transport cask loading through selection of spent fuel assemblies have been investigated with the objective of reducing the number of cask shipments and subsequent handling at the waste management facilities. The OFF selection was compared with a selection consistent with nonuniform loading of transport casks, in which hot assemblies are placed in the interior cavity of the cask and cold assemblies are placed in the exterior ring to take advantage of the fuel's self-shielding properties. Use of nonuniform loading techniques coupled with judicious fuel sequence and selection will allow the cask to carry a wider spectrum of fuel and minimize the need for cask derating. The study investigated two reactor spent fuel pools and found that nonuniform loading could reduce the number of shipments by about 20 percent for the cases considered.

Classification of Spent Nuclear Fuel (SNF).
March 1990. ORNL/Sub/89-SD841/1, JAI-334,
Oak Ridge National Laboratory and Johnson and Associates, Inc.

Summary

The report recommends revising the waste classification system and the waste inspection and testing requirements that are needed for proper classification. The new classification system includes seven classes of standard fuel that would be accepted by DOE without schedule restraint. The first five of these classes would also have a nonstandard category for wastes not meeting the specifications of the standard waste. Such nonstandard wastes would be subject to uncertain delivery and acceptance priority. The seven classes are

- Intact, nondefective fuel assemblies
- Failed fuel in Type 2 canisters
- Consolidated fuel rods in Type 1 canisters
- Compacted structurals from consolidation, in Type 1 canisters
- Non-fuel assembly (NFA) hardware inserted in or on Class 1 standard fuel
- Transport-certified metal casks containing standard waste in Classes 1 to 5
- Transport-certified multielement sealed canisters containing standard waste in Classes 1 to 5.

The underlying rationale for this classification system is that DOE can accept these waste forms when offered, without unusual operational difficulty. The key to this for Classes 2, 3, and 4 is the using what could be called a standard canister, which can be handled like a single fuel assembly. Class 5, NFA hardware, must be delivered integral in, or on, a standard Class 1 assembly or it is nonstandard and subject to delivery at DOE discretion. Classes 6 and 7, transportable storage casks (TSCs) and multiple element sealed canisters (MESCs), require transport certification to be acceptable. There is no nonstandard category for these two classes. They are either standard or the TSC/MESC must be unloaded by the utility and their contents delivered under Classes 1 to 5.

With respect to the degree of inspection and testing needed for classification at the time of delivery, the report notes that measurement programs for the independent checking of burnup, age, dimensions, and weight cannot be justified in comparison with the use of utility records, on the basis of either better accuracy or cost/benefit. With respect to fuel integrity, a fuel assembly can be classed as nondefective

if utility operating and handling records, normal visual inspection, and the actual loading of fuel do not show evidence of failure or unusual distortion.

Recent Technical Status

The probable use of burnup credit transport casks will impose a requirement for the direct utility measurement of burnup on individual PWR assemblies at the time of cask loading. Because burnup credit is not needed for BWR casks, no burnup measurements are anticipated for BWR fuel.

System Impacts of Cask and Canister Concepts

Phase 1 Study of Metallic Cask Systems for Spent Fuel Management from Reactor to Repository (Draft).

**September 1985. Tennessee Valley Authority
and Florida Power and Light Company.**

WTSD-TME-085, Westinghouse Electric Corporation.

Summary

The study assessed universal self-shielded waste packages (USSWPs) such as multipurpose casks that can be used for spent fuel storage, transport, and removal or rehandling of the contents. Other concepts assessed were the dual-purpose storage cask and a disposal container produced at reactors. The authors concluded that producing a disposal container at reactors is not an attractive option, but a system consisting of conventional casks, dual-purpose casks, and multipurpose casks may be more cost effective than the reference system consisting of storage casks, transport casks, and disposal containers. OCRWM evaluated the concepts and concluded the following:

- A decision at this time to commit to a USSWP would have a high degree of risk because of the current uncertainty associated with repository and waste package licensing requirements.
- The number of USSWPs that would be required and their costs make them an overwhelming cost driver of the system. No cost savings would be possible if each USSWP were to cost more than \$220,000.
- Licensing a USSWP would be complicated because it would be under three separate regulations, 10 CFR Parts 60, 71, and 72.
- The transport storage cask should be investigated further in another study.

***Use of Transportable Storage Casks in the Nuclear
Waste Management System.***

ORNL/Sub/86-SA094/1, HR/JAI-289, December 1987.

ORNL/Sub/86-SA094/4, March 1990.

Oak Ridge National Laboratory.

Scope

These reports describe the incremental system analysis that was done to define the physical and economic impacts on the DOE system of accepting spent fuel and related waste in transportable storage casks (TSCs). The TSC is postulated to have been loaded in the reactor pool, then sealed and put into at-reactor storage, at an earlier time. At the time of delivery it would be removed from storage without being returned to the reactor pool, be certified by the utility as transportable, and be accepted by DOE. DOE would then transport the TSC to an MRS or repository site where DOE would do one of the following:

- unload the cask and immediately put it into service as a DOE transport cask
- unload the cask and use it as process lag storage at the MRS or repository
- put the loaded cask directly into DOE storage.

The cask would then be disposed of.

Current Status

The Standard Contract does not currently include waste contained in TSCs as a waste form that is acceptable to DOE.

General Conclusions

- The only significant benefit to the DOE system of accepting TSCs occurs when DOE can thereby avoid buying or building similar casks for DOE use in transport or storage. For DOE to avoid buying or building such casks, the utility would have to make a binding commitment to future cask delivery at the same time that DOE must otherwise make its own commitment to buying casks or designing and constructing storage. Specifically, DOE could realize system savings of about \$90/kgU for up to 20 transport-licensed casks committed to DOE with sufficient lead time to avoid DOE purchase of such casks for regular transport usage.

of process lag storage. Second, about \$30/kgU could be saved in avoided incremental MRS storage cask costs for casks delivered while the MRS is still increasing its storage capacity, prior to the start of repository operations.

- The principal benefits to the utility of delivering fuel in TSCs are avoiding unloading the storage cask and loading a transport cask, at a cost of \$3 to \$5/kgU, and avoiding ultimate cask disposal at a cost of \$4 to \$6/kgU. Further, among alternative at-reactor storage technologies, TSCs at \$80 to \$100/kgU are the most expensive storage alternative. Nontransportable alternatives cost in the range of \$40 to \$60/kgU. Even after deducting the potential savings of \$7 to \$11/kgU from avoided rehandling and disposal costs, the TSC is still considerably more expensive than the nontransportable alternatives.
- An overall utility-DOE system saving with the TSC is possible, provided the net excess cost of the TSC over alternative storage would be less than the benefit of the TSC to DOE and a benefit-sharing arrangement could be worked out. It appears, however, that logistically very few, if any, utilities could justify committing to deliver TSCs prior to or during the initial startup of the DOE system, which is when DOE must have most of the TSCs to realize benefit from them. Specifically, early delivery of fuel in the cask would normally require that the utility purchase and load a new cask to make room for the next fuel discharge. This is clearly uneconomical. Only after fuel acceptance rates have exceeded fuel discharge rates for some time can a utility gain enough storage margin to sensibly consider reducing the capacity of its out-of-reactor storage (i.e., deliver a cask). For these reasons, the prospects of realizing an overall systems benefit from the use of TSCs are not encouraging.
- In order to allow the full system potential of TSCs and of alternative storage technologies to be realized, the report suggests three alternatives for the acceptance of waste in TSCs:
 - Accept TSC deliveries that meet transportability and other requirements without charge or payment.
 - Accept TSC deliveries with DOE paying some fraction of avoided DOE costs or being paid excess DOE costs that result from TSC acceptance. Timing of delivery would not be an explicit requirement, but would be implicit, because avoided DOE cost would be high for early delivery.
 - Participate in ownership of the cask at the time of purchase, at a level sufficient to offset the excess of TSC cost over nontransportable alternatives, with strict timing conditions to ensure early delivery.

Recent Technical Status

Utilities continue to purchase at-reactor storage technologies with cost savings derived from factors that also reduce transportation licensability. In the structural area, less expensive baskets are also less robust, reducing transport licensability. In the criticality area, most recent PWR storage cask baskets rely on pool boron credit to maintain high storage densities and to avoid the need for direct burnup measurement at the time of loading. It is unlikely that any cask or basket that requires pool boron credit at the time of loading and avoids direct measurement of fuel assembly burnups will be licensable for future transport under current transport criticality regulations.

There have been no new developments affecting two other areas: the acceptability of certifications at the time of transport, based on fuel conditions many years earlier at the time of loading; and the ability to maintain the transport certification of casks used for storage over many years both remain uncertain.

***Acceptance of Spent Nuclear Fuel in Multiple Element Sealed
Canisters by the Federal Waste Management System.***

March 1990. ORNL/Sub/86-094/6, JAI-314,

Oak Ridge National Laboratory and Johnson and Associates, Inc.

Scope

This report describes the incremental system analysis that was done to define the physical and economic impacts on the DOE system of accepting spent fuel and related waste in multiple element sealed canisters (MESCs). These MESCs store either 7 PWR fuel assemblies or 24 PWR fuel assemblies in a canister that is loaded and sealed in the reactor pool, then moved in a shielded transfer cask and transferred to a horizontal concrete storage module. Although not yet designed, it is likely that a similar canister could be licensed to hold in the range of 40 to 52 BWR fuel assemblies. For unloading, the process can be simply reversed; the canister is cut open in the reactor pool and the individual fuel assemblies are removed. However, this report addresses the postulated situation in which the canister would be transferred directly from the horizontal storage module into a DOE transport cask. DOE would then transport the MESC either to an MRS or to a repository site where the canister would be opened and the individual fuel assemblies removed; or to an MRS site where the canister would be transferred into a horizontal storage module for interim storage prior to ultimate opening and removal of the fuel assemblies. In either case, DOE would ultimately dispose of the canister.

Current Status

The Standard Contract does not currently include waste contained in MESCs as a waste form that is acceptable to DOE.

General Conclusions

- The only benefit to the DOE system of accepting MESCs would occur when the utility delivers the 24-PWR MESC to DOE during the period when the MRS is still adding storage capacity and DOE can avoid purchasing a storage basket. The net benefit in this case is about \$5/kgU in smaller quantities and up to \$13/kgU if 10,000 MTU were to be delivered during the MRS storage buildup period. Otherwise, there would always be a net cost to the DOE system, because DOE would require additional facilities, equipment, and operations to accept MESCs. Specifically, DOE requires longer and larger transport casks (but without baskets), heavier lift capability in hot cells, and equipment for opening MESCs; and DOE must pay for MESC disposal. The net cost of these requirements is on the order of \$10/kgU. If larger quantities of 10,000 MTU in large MESCs

were to be delivered to DOE, this net cost to DOE could drop to \$6/kgU. Under all conditions, DOE acceptance of the 7-PWR MESC causes substantial DOE cost increases (at least \$18/kgU if the utility supplies the transport cask).

- The benefits to the utility of delivering fuel in a MESC would be the avoidance of unloading the MESC (not estimated in the report, but probably on the order of \$5/kgU) and the avoidance of MESC disposal estimated at under \$3/kgU.
- For reasons of utility storage logistics, it appears that little, if any, fuel is likely to be delivered to DOE in MESC's during the MRS storage buildup period. Therefore, it appears that the normal impact of accepting large MESC's into the DOE system would be a net cost to DOE that is about equal to the net savings realized by utilities in delivering MESC's to DOE. Thus, the impact of accepting large MESC's on the combined utility-DOE system would be almost neutral. However, potential acceptance of MESC's under these circumstances raises the issue of interutility equity, because unilateral action by one utility would reduce its own costs but would correspondingly increase DOE costs, which are borne collectively by all utilities. Acceptance of the seven-assembly MESC would cost DOE substantially more than the utility would save.
- The report suggests the following three alternative ways for DOE to proceed:
 - DOE would accept MESC's, avoiding the issue of interutility equity.
 - DOE would accept large MESC's without charge or credit, thereby accepting and tolerating interutility inequities. The transport licensability of the MESC would be a utility responsibility.
 - DOE would accept large MESC's, but with charges for added costs and credits for avoided costs, thereby ensuring interutility equity. The transport licensability of the MESC would be a utility responsibility.

Recent Technical Status

The issue of large MESC licensability for transport has some characteristics in common with TSC licensability. With respect to criticality, a 24-PWR MESC that is loaded using pool boron credit to avoid the need for direct assembly burnup measurements would probably not be licensable for subsequent transport. The only loading to date of 24-PWR canisters, at Duke Power's Oconee 1, 2 pool, used pool boron credit. As with TSCs, there is an uncertainty associated with future transportability. The acceptability of utility certifications at the time of transport, based on fuel conditions at the time of canister loading done many years earlier, is an uncertainty.

***Acceptance of Failed SNF Assemblies by the
Federal Waste Management System.***

**March 1990. ORNL/Sub/86-SA094/5, JAI-325,
Oak Ridge National Laboratory and Johnson and Associates, Inc.**

Scope

This report describes the incremental system analysis that was done to define the physical and cost impacts on the DOE system of accepting failed spent nuclear fuel (SNF). The acceptance of failed fuel increases DOE costs because failed fuel reduces the payload of transport and storage casks, requires various types of special handling depending upon the DOE system, and may require special transport casks. In addition to developing recommendations as to the acceptance criteria for failed fuel, the report also suggests a more quantitative definition of failed fuel and the related level of inspection necessary to categorize failed fuel.

Current Status

The Standard Contract defines three categories of failed fuel. All categories are nonstandard and thus subject to uncertain delivery and acceptance priority relative to non-failed intact fuel. The current classification of failed fuel may be unduly restrictive without providing a corresponding benefit to DOE, and the requirement for inspection does not address the degree of inspection rigor.

General Conclusions

- The cost premium for handling failed fuel ranges from \$3 to \$30/kgU, depending on the DOE system configuration, and is lowest for the system with an MRS and disposal of intact fuel assemblies. This range applies when special transport is not needed and increases further by \$25 to \$35/kgU, depending on the extent of special transportation requirements. However, because DOE must accept such fuel, the principal economic issue is not if the expenditure will occur, but rather when it will occur. Out of 57,000 fuel assemblies discharged through 1987, only somewhat more than 200 were classified as failed. Thus, even with a significant cost premium for handling individual failed fuel assemblies, the overall system impact of failed fuel will be small.
- Failed fuel that is encapsulated in standard canisters can be handled and accepted on the same priority basis as standard fuel. It would be appropriate to require that all assemblies containing ruptured fuel rods be encapsulated in the standard canister. Failed fuel that is structurally damaged, or has been encapsulated but is not in standard canisters, is subject to delayed acceptance.

- FWMS equipment and systems are designed presuming some contamination from the crud that is present on the surfaces of most fuel rods. Therefore, the principal concern for defining fuel failure in the DOE system is associated with the potential for the added release of fuel particulates from leaking fuel rods, rather than the presence of any clad penetration whatsoever, as is the case with utility fuel usage. Structural deficiencies that may cause fuel handling problems are also of concern. The report thus recommends that a fuel assembly be defined as failed if 1) it is structurally damaged, 2) it contains ruptured fuel rods to the extent that release of particulates is possible, or 3) it has been encapsulated by the utility.

This definition of failed fuel excludes assemblies that, although damaged, can still be handled the same as standard fuel, and fuel assemblies with leaking rods that do not have the potential for significant leakage of particulates.

- With respect to fuel inspection requirements, there is no quantitative way to determine if a fuel assembly has failed under the practical failed fuel definition suggested in the report. Consequently, it is not reasonable to impose a specific measurement requirement on the utilities, particularly when the cost of such measurements would greatly exceed the cost consequences to DOE of receiving unidentified failed fuel. It is therefore suggested that failed fuel be identified from the reactor operator's observation of fuel performance or unusual handling events during the fuel operating and storage periods, but that additional examination would not normally be required. Two alternatives are suggested for dealing with the added costs of handling unidentified failed fuel in the DOE system:
 - charging the utility with the added cost
 - not charging, unless there is evidence of a disregard of available records or visual observation procedures.

***Acceptance of Canisters of Consolidated Spent Nuclear Fuel by the
Federal Waste Management System.***

**March 1990. ORNL/Sub/86-SA094/7, JAI-322,
Oak Ridge National Laboratory.**

Scope

This report describes the incremental system analysis that was done to define the physical and cost impacts on the DOE system of accepting consolidated fuel rods and related compacted fuel assembly structures contained in assembly-sized canisters. Utilities that select spent fuel consolidated to increase at-reactor storage capacity generally expect a 2:1 consolidation factor on fuel rods and about 10:1 compaction of the fuel assembly structures. Consolidation of ten assemblies will result in five rack locations containing canisters of fuel rods, one location containing a canister of structurals, and four empty locations. The overall compaction ratio is thus 1.67. When these canisters are delivered to DOE, the same compaction ratio relative to intact assemblies favors increased transport and storage cask payloads and reduced handling, except where rehandling of the fuel rods is necessary. Thus, one might normally anticipate cost savings, rather than the cost increases associated with the acceptance of consolidated fuel.

Current Status

Consolidated fuel and fuel disassembly hardware are an acceptable waste form in the standard contract. However, they are classified as nonstandard and thus are subject to uncertain delivery and acceptance priority relative to intact fuel. Provided these wastes are loaded into acceptable canisters, the current classification may be unduly restrictive inasmuch as DOE may be able to handle, transport, and store these wastes at least as efficiently as intact fuel.

General Conclusions

- Provided that a net compaction ratio of at least 1.45 could be realized, the acceptance of consolidated fuel would always result in a net savings to the DOE system. At a compaction ratio of 1.67, waste systems savings would range from a low of \$5/kgU (No-MRS system with disposal of consolidated fuel) to \$30/kgU (MRS storage and repository disposal of intact fuel). The basic reason for these savings is that consolidated fuel canisters can be handled, transported, stored, and disposed of more efficiently than intact fuel.
- There does not appear to be any basis for scheduling the acceptance of consolidated fuel and related structurals on a basis different from standard intact fuel assemblies, provided that 1) the wastes are in acceptable canisters (see the WAC report on canister criteria) and 2) the net compaction ratio of such wastes is greater than 1.45.

Recent Technical Status

Although consolidation was widely viewed 10 years ago as the most promising of the at-reactor storage technologies, concrete storage casks have since proven to have comparable and more predictable costs and simpler operational characteristics. Although approximately 50 PWR assemblies have been consolidated in various demonstration programs, no utility has done significant consolidation or has committed to continue consolidation as its primary storage-extension technology. However, at least one utility still appears likely to do so, and others could follow.

In common with the other at-reactor storage technologies, the logistics of utility spent fuel discharges and storage make it unlikely that a utility would deliver consolidated fuel to DOE until after most or all of the intact fuel in the reactor pool has been shipped to DOE. Delivering consolidated fuel to DOE is the logistic equivalent of delivering fuel plus storage capacity to DOE, and no utility is likely to give up storage capacity until it is certain that such capacity would not have to be repurchased.

Acceptance of Non-Fuel Assembly Hardware by the Federal Waste Management System (Draft).

June 1991. ORNL/Sub/86-SA094/8, JAI-328,

**Supplement to ORNL/Sub/86-SA094/8, JAI-355, March 1990.
Oak Ridge National Laboratory and Johnson and Associates, Inc.**

Scope

These reports describe the incremental systems analysis that was done to define the physical and economical impacts of accepting non-fuel assembly hardware (NFAH). The reports address PWR NFAH items, including control rod assemblies, burnable poison assemblies, neutron source assemblies, thimble plug assemblies, and instrument assemblies. The reports also address BWR NFAH items, including fuel channels, control assemblies, and instrument assemblies. Estimates of total quantities of these items are provided. Estimates are also made of the numbers of additional canisters needed when the NFAH is delivered integral with fuel assemblies (except BWR control assemblies), compacted in canisters, and uncompacted in canisters. Impacts of accepting, transporting, handling, storing, and disposing of these NFAH items are determined under various system processing and configuration assumptions.

Current Status

Under the Standard Contract, NFAH is deliverable to DOE integral with a fuel assembly as standard fuel. If NFAH is not delivered integral with fuel, it is classified as nonstandard fuel and hence subject to uncertain delivery and acceptance priority. The standard contract is unclear on the following number of issues:

- Fuel-related components that qualify as NFAH
- Acceptable forms for non-integral delivery
- Acceptance priority of non-integral NFAH when delivered in acceptable form.

Subsequent to promulgation of the Standard Contract, NRC has determined that Greater-Than-Class C (GTCC) wastes require repository or equivalent disposal. If the wastes are not GTCC, they can be disposed of in shallow-land burials. The Standard Contract, therefore, does not address DOE's obligation to accept non-integral deliveries of NFAH that is not GTCC.

General Conclusions

- The lowest DOE system cost impact from acceptance of NFAH occurs when it is delivered integral with the fuel assemblies. The only significant cost in this instance is \$600 million for the acceptance and ultimate disposal of uncompacted BWR control assemblies, which cannot be delivered integral with the fuel. This cost could be reduced to about \$250 million with at-reactor compaction of BWR control assemblies.
- When NFAH is not delivered integral with fuel, but is delivered uncompacted to DOE, costs of \$1.2 to \$1.5 billion are incurred by DOE for the transport, compaction, and disposal of NFAH. Reductions of \$0.7 to \$0.9 billion in those added DOE costs can be realized if non-integral but compacted NFAH is delivered to DOE.
- DOE system cost impacts would therefore be minimized if utilities were to deliver NFAH integral with fuel and compact any NFAH that could not be so delivered. Uncompacted, non-integral NFAH should probably not be accepted for delivery. The timing of non-integral, compacted NFAH delivered in acceptable canisters should be at DOE discretion.

Recent Technical Status

Regardless of how it is delivered, acceptance and disposal of NFAH would have a significant impact on the DOE system. Even when delivered integral with the fuel, NFAH increases the weight of loaded casks, makes it necessary to extend the internal length of PWR casks to accommodate the control rod or poison inserts, and expands the needed cross-sectional dimension of the BWR assembly to accommodate the BWR channels. These necessary dimensional increments would reduce the fuel payloads that could otherwise be carried in these casks.

***Acceptance of Canisters of High Level Waste by the
Federal Waste Management System.***

**June 1990. ORNL/Sub/89-SD841/2, JAI-331,
Oak Ridge National Laboratory and Johnson and Associates, Inc.**

Summary

This report discusses the basic designs and dimensions of the HLW packages that will be produced by the Defense Waste Processing Facility at Savannah River and the West Valley Demonstration Project. The plans for HLW packages produced by Hanford and the Idaho National Engineering Laboratory are also discussed. These HLW packages are compared with the spent fuel disposal package designs for spent fuel. It is further noted that, although the HLW packages are similar in diameter to spent fuel packages, the HLW package length is only about two-thirds the length of the spent fuel package. It is noted that if the HLW package length could be increased by 50%, the number of packages and emplacements of HLW could be reduced by one-third.

Recent Technical Status

It is understood that the actual waste acceptance criteria and the related waste characterization data to be used in the acceptance process will be covered by a Memorandum of Understanding between DOE/OCRWM and DOE's Office of Environmental Restoration and Waste Management (DOE/EM).

Common Canister Study (Draft). 1986.
Weston, SNL, LLNL, PNL, Ralph M. Parsons,
Battelle ONWI Project, BWIP Project.

Summary

This OCRWM study was intended to identify a design for a multipurpose canister within which spent fuel could be consolidated at the MRS and which could be placed into a repository-specific disposal container at each of the tuff, salt, and basalt sites. Seven canister configurations were examined for compatibility with system requirements to identify any "show stoppers" and to estimate the effects on the total system resulting from the use of each canister type. The seven configurations consisted of four round canisters of different diameters, a triangular canister, a pair of square and half-square cross section canisters, and a canister with a wedge-shaped cross section. In addition to system costs, the criteria used in the evaluation included:

- the ability to handle intact fuel assemblies in addition to consolidated fuel
- the number of sizes required for each canister type
- the total number of canisters
- the total number of waste packages
- the weight of waste package
- the schedule and performance
- the transportation efficiency
- the flexibility
- the heat output
- the licensing.

The study concluded that the square/half-square canister is the only configuration fully acceptable to the MRS and all three repositories. The square canister has essentially the envelope of a fuel assembly and is a precursor to the JAI-proposed "standard" canister described in another study that follows.

Evaluation of Potential Benefits of Transportable Storage Casks.
1989. R. M. Casper, D. M. Collier, W. J. Lee, and J. V. Houston.
Prepared by Nuclear Assurance Corporation for the
Electric Power Research Institute (EPRI).

Summary

While under study in the U.S. for several years, the concept of dual-purpose TSCs has already been incorporated into European plans for spent fuel management. A DOE evaluation of the potential benefits of this technology focused on those elements affecting DOE's fuel transport and disposal responsibilities. This EPRI study represents industry's independent analysis of the same issues with a utility-oriented perspective.

The objectives of this study were to 1) evaluate the potential benefits of TSCs and 2) develop a practical cash-flow model for comparing various waste storage and transport scenarios. Investigators developed five scenarios that covered a range of uses for TSCs. The study also compared the use of TSCs with both storage-only and transport-only casks. Key considerations in structuring the scenarios included making realistic assumptions about the timing and availability of dual-purpose casks and how the casks integrate into projected DOE plans for spent fuel transport and disposal. A cash flow methodology was developed to compare various waste management system scenarios and evaluate the use of TSCs. The net present value was used as the basis for comparing scenarios. The five scenarios were analyzed considering the following:

- at-reactor spent fuel storage in metal casks
- transport of spent fuel by rail from reactors to the DOE facilities
- lag storage and the interim storage of consolidated spent fuel at the MRS facility
- transport of consolidated spent fuel from the MRS to the repository.

The study indicated that the integrated use of TSCs could yield substantial cost savings and reduce handling of casks and spent fuel. For the dual-purpose cask scenario that offers the maximum benefit, the savings calculated for the waste management system ranged from \$39 million to \$75 million, depending on the discount rate selected. The evaluation also determined that incorporating dual-purpose casks into the waste management system would increase overall system flexibility and improve the capability to adapt to future changes that may well occur in the DOE spent fuel transportation and repository program.

Selecting strategies for disposing of HLW is extremely difficult because of the substantial uncertainties associated with repository technology and licensing. This study suggests that using dual-purpose casks offers an attractive alternative that could save money and reduce downstream fuel-handling requirements. However, even though the potential savings are substantial, they represent only a small fraction of the total system cost. Therefore, the authors concluded that it will be difficult in the near term to establish a compelling need to use TSCs. The study concluded that it appears unwise to abandon the TSC option, because it does offer a potential for economic gain without incurring additional program cost.

***Requirements for Canisters Used for Delivery of Spent Nuclear Fuel
and Associated Materials to DOE Under Standard Disposal Contracts.***

June 1990. ORNL/Sub/89-SD841/3, JAI-340,

Oak Ridge National Laboratory and Johnson and Associates, Inc.

Summary

One of the keys to ensuring DOE's ability to handle and accept certain types of waste is packaging those wastes in canisters of known handling and physical characteristics, including general compatibility with utility fuel racks and the baskets of DOE casks. Such canisters are relevant to handling failed fuel, consolidated fuel rods, the compacted assembly hardware from consolidation, and NFAH delivered nonintegral with fuel assemblies. This brief report describes the requirements for a suggested standard canister and provides the rationale for each requirement. This report describes a single basic standard canister. The classification report describes two canisters of slightly different dimensions: a Type 1 for everything except failed fuel and slightly larger Type 2 for failed fuel. The ability to classify certain waste forms as standard and hence deliverable without schedule uncertainty, depends significantly on the establishment of standard canister specifications.

System Impacts of Alternative Allocations of Waste Acceptance Rights

Spent Fuel Acceptance Scenarios Devoted to Shutdown Reactors: A Preliminary Analysis.

**October 1989. T. W. Wood, A. M. Plummer, S. M. Short,
and D. G. Dippold (Battelle Columbus).
PNL-7143, Pacific Northwest Laboratory.**

Summary

Spent fuel acceptance schedules and the allocation of federal acceptance capacity among commercial nuclear power reactors have important operational and cost consequences for reactor operators. Alternative allocation schemes had been investigated to some extent in DOE's 1989 MRS Systems Study. The study discussed here supplements these analyses for a class of acceptance scenarios in which the acceptance capacity of the federal radioactive waste management system is allocated principally to shutdown commercial power reactors and extends the scope of analysis to include considerations of at-reactor cask loading rates.

The report provides estimates of the operational consequences of these scenarios for power reactors, as measured in terms of quantity of spent fuel storage requirements above storage pool capacities and number of years of pool operations after last discharge, and estimates the associated utility costs. This study does not attempt to examine the interutility equity considerations involved in departures from the current OFF allocation rule as specified in the Standard Contract. The alternative allocations are more economically efficient than OFF; they approximate the allocations that could result from free exchange of acceptance rights among utilities. Such a process would preserve interutility equity.

This study shows that a scenario granting exclusive spent fuel acceptance rights to shutdown reactors in order of shutdown date could substantially reduce the average time between last discharge and completion of spent fuel removal for currently operating power reactors and those under construction and expected to be completed. Implementing such a scenario, using a strict "longest-shutdown-first" priority rule, would require at-reactor cask loading rates in excess of the preliminary estimates of capabilities. Because of the relative timing for reactor shutdown and federal acceptance as currently planned, this scenario would not fully utilize the spent fuel acceptance capacity planned for the federal system. In addition, the requirements for additional at-reactor storage would be much greater under such a scenario than under an allocation of acceptance based on spent fuel age.

A modified shutdown priority scenario grants first priority to reactors with imminent storage capacity needs, second priority to shutdown reactors, and third priority based on spent fuel age and individual

at-reactor cask loading constraints as currently estimated. This scenario is shown to have lower at-reactor storage impacts in terms of both capacity requirements and average time between last discharge and fuel pickup than an allocation based on age of spent fuel, and would fully utilize the planned acceptance capacity of the waste management system.

All of the scenarios studied would have some impact on the characteristics of the spent fuel accepted. The effects of fuel characteristics on transportation cask capacity and fleet requirements are treated qualitatively in this report.

Determination of Desirable System Throughput Rates

Draft Summary Report on Determination of Cost Effective Waste Management System Receipt Rates.

**December 1990. R. W. McKee and H. D. Huber.
Pacific Northwest Laboratory.**

Summary

This study investigated system receipt rates from 1,500 to 6,000 MTU of spent fuel per year to determine cost-effective design throughput rates. Cases studied included repository startup in 2010 and 2015 and MRS startup in 1998 and three years prior to repository startup. All of the scenarios assumed that reactors would shut down at the end of their operating license period, and that no license extension would occur. Reactor storage costs are factored into the cost evaluation for shutdown reactors. Higher throughput rates appear to be cost effective (undiscounted costs) if current NWPAs constraints on MRS capacity are removed. With discounting, higher throughput systems cost about the same as the 3,000 MTU per year system.

These preliminary results show that the currently assumed 3,000 MTU/year throughput will result in near minimum costs; they also show that if there are reasons to design for a higher throughput rate, this can be done with little impact on the total cost.

Distribution

No. of
Copies

No. of
Copies

OFFSITE

12 DOE/Office of Scientific and
Technical Information

39 Office of Civilian Radioactive Waste
Management
U.S. Department of Energy
1000 Independence Ave., SW
Washington, DC 20585
ATTN: J. Bartlett
J. Bresee
S. Brocoum
A. Brownstein
J. Carlson
C. Conner
N. Del Gobbo
S. Gomborg
J. Hale
T. Isaacs
C. Kouts
P. Kumar
W. Lemeschewsky
R. Milner
N. Montgomery
T. Nguyen (10)
F. Peters
R. Philpott
J. Pirro
M. Popa
C. Quan
J. Roberts
S. Rousso
J. Saltzman
M. Senderling
R. Servis
D. Shelor
W. Sprecher
T. Truong
J. Williams

D. Address
11008 Harriett Lane
Kensington, MD 20895

4 E. R. Johnson Associates Inc.
9302 Lee Highway #700
Fairfax, VA 22031
ATTN: E. Johnson
B. McLeod
B. Cole
D. Jones

22 TRW Environmental Safety
Systems, Inc.
2650 Park Tower Drive
Vienna, VA 22180
ATTN: W. Bailey
G. Carruth
P. Carter
J. Cassidy
J. Clark
T. Cotton
R. Godman
P. Gottlieb
A. Greenberg
W. Griffin
W. Hollaway
C. Kerrigan
W. Matyskiela
J. Miller
D. Nitti
F. Ridolphi
R. Robertson
G. Rogers
I. Sacks
S. Sareen
G. Vawter
J. Willis

No. of
Copies

- 6 TRW Environmental Safety
Systems, Inc.
101 Convention Center Dr.
Phase II, Suite P110
Las Vegas, NV 89109
ATTN: J. Berg
H. Benton
T. Doering
R. Jiu
G. McKinney
W. Nelson
- 8 Yucca Mountain Project Office
U.S. Department of Energy
P.O. Box 98608
Las Vegas, NV 89193-8608
ATTN: W. Simecka
E. Petrie
M. Blanchard
D. Royer (3)
D. Harrison Geisler
C. Gertz
- 6 Duke Engineering and Services
230 South Tryon St.
Charlotte, NC 28202
ATTN: A. Segrest
J. Stringer (3)
N. Seagle (2)
- 5 Lawrence Livermore National
Laboratory
P.O. Box 806
Livermore, CA 94550
ATTN: L. Ramspott (2)
J. Blink (2)
T. Buscheck

No. of
Copies

- 3 Oak Ridge National Laboratory
P.O. Box 2008
Oak Ridge, TN 37831
ATTN: D. Joy
R. Pope
K. Notz
- 2 Sandia National Laboratories
P.O. Box 5800
Albuquerque, NM 87185
ATTN: R. Kalinski
E. Ryder
- 16 Pacific Northwest Laboratory

S. Bennett
M. Kreiter
J. McElroy
R. McKee
G. McNair
M. Shay
S. Short
R. Smith
S. Vance
T. Wood
Publishing Coordination
Technical Report Files (5)

END

**DATE
FILMED**

8 / 11 / 92