Technical Progress Report

DOE/ER/12821--T2

Phase I (1988-1989)

DE92 015970

for

Research on

EXPERIMENTAL DEVELOPMENT OF NUCLEAR PUMPED LASER CANDIDATE
INERTIAL CONFINEMENT FUSION DRIVER

Supported by

U. S. Department of Energy

Under Contract #DOE DEFG07-88ER12821

_____
George H. Miley
Principal Investigator
Fusion Studies Laboratory
University of Illinois
Urbana, Illinois 61801

May 31, 1989

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Table of Contents

	Page
Introduction	1
Section 1: Overview of 3-Year Project	1
Section 2: Work to Date in 1988-1989 Budget Year. .	7
Literature Survey.	7
Data Analysis Handling	8
Vacuum/Gas Handling System	8
Test Cell.	10
Optical Collection System.	13
Preliminary Test Results	17
Conclusions.	22
References	23

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Technical Progress Report

Introduction

This progress report is submitted at the end of the first year of a 3-year project grant studying development of a nuclear pumped atomic iodine laser. The first section of the report will provide background on the study and briefly describe the original plans for the 3-year project. The second section will detail the work done to date. Included will be a description of the preparations made for experimentation, as well as some preliminary results recently obtained. Plans for the upcoming budget year are covered in the accompanying proposal, "Project Plans for 1989-1990."

Section 1: Overview of 3-Year Project

Nuclear pumped Laser (NPL) technology utilizes the energy from energetic reactions of neutrons (e.g., from a nuclear reactor) with certain materials to "pump" a lasing medium. Significant success has been seen in select laser systems over the past 15 years. However, new developments are needed to attain a practical high power laser system such as required for ICF applications, and this is the driving motivation for the present research.

Table 1 lists the three most common reactions considered in nuclear pumping. While past NPLs have involved mixing these neutron-reacting materials directly with the lasant (hence, the term "Direct Nuclear Pumped Laser"), the present approach involves mixing the materials with gases which will fluoresce in the ultra-violet when exposed to the flux of neutron reaction products. This UV light is then coupled into a cell containing the lasant, causing

Table 1: Common energetic neutron reactions used in nuclear pumped laser.

lasing through photodissociation of the lasing gas. A laser which utilizes UV light as the "pump" to cause lasing is called a "photolytically pumped" laser. The approach of utilizing neutron reaction products to cause gas fluorescence is termed a Nuclear Driven Flashlamp (DNF). Hence, the laser being investigated here is an NDF photolytic laser.

The original idea for such experiments were put forward by Wilson and Shapiro as early as 1980⁽¹⁾, however at that time it was not clear that adequate neutron flux could be obtained in available experimental facilities. They suggested pumping of the atomic iodine laser. This laser has been studied extensively, but with pumping by electronically driven flashlamps. The atomic iodine laser involves photodissociation of an iodine-containing molecule to give an excited iodine atom. A sufficient number of iodine atoms are then created or cascade to the upper laser level for lasing to be achieved. Several different iodine compounds can be used for this purpose, the two most common being CF_3I and $\text{C}_3\text{F}_7\text{I}$.

Atomic iodine lasers are traditionally pumped with UV-emitting electrical flashlamps (e.g. Xe). For nuclear pumping, Wilson & Shapiro originally suggested that a gas excimer mixture could be excited by protons and tritons from the $n(^3\text{H}, \alpha)\text{T}$ reaction to produce UV light to pump the laser. They performed kinetics calculations^(1,2) to show that XeBr and $\text{KrF}/\text{Ar}_2\text{F}$ could be used for this purpose. We have confirmed these calculations but also find that there may be other gas mixtures which are more efficient and have a lower neutron flux requirement. Thus, a major goal of the proposed research is the development of an optimized gas mixture

for the flashlamp which is both efficient and suitable for use in neutron fluxes obtainable from a TRIGA research reactor.

Additionally, our studies indicate that it is worthwhile to attempt direct nuclear pumping of this laser system. This would involve mixing the lasant (iodine) with ^3He to test whether the interaction of the energetic neutron reaction products will cause lasing directly.

Based on our preliminary studies it was concluded that the University of Illinois TRIGA reactor would be ideal for conducting an experimental verification of these concepts. The TRIGA has a pulsing ability with characteristics as outlined in Table 2. Our calculations indicate the lasing threshold for the NDF photolytic atomic iodine laser could be exceeded with an optimized gas mixture in the NDF section and pumped by a TRIGA pulse. A peak power of approximately 100 W at the 1.31 micron line is predicted. A schematic diagram of the proposed experimental laser is shown in Figure 1.

In the original proposal the project was divided into three phases, as follows:

Phase 1: Nuclear-pumped fluorescence studies and optimization

Phase 2: Coupling of fluorescence to a laser cell, and testing of the laser

Phase 3: Direct nuclear pumping of the laser.

The work during the first year of the three-year project was to center on Phase 1, with Phases 2 and 3 to be done in the second and third years, respectively.

Table 2: Characteristics of \$3.00 pulse in University of Illinois TRIGA reactor.

- Pulse length: 15 msec FWHM
- Neutron flux in throughport at pulse peak:
3x10¹⁵ n/cm²-sec
- Pulsing frequency: 4 times per hour

Figure 1: Schematic of proposed laser system.

Section 2: Work to Date in 1988-1989 Budget Year

The effort over this year has centered on developing a test set-up to identify the most promising gas mixture for use in the NDF mixture. Due to the lack of prior experimental work in this area, it is necessary to conduct parametric studies to determine which of the most promising candidate gas mixtures will give the greatest UV light output in the photodissociation band (220-330 nm) of the lasants. In preparation for these tests, several tasks have been accomplished and/or are on-going. These include performing a literature survey on the subject, developing a data analysis system, developing a vacuum/gas handling system, designing and constructing a test cell, and designing an optical collection system. Each of these efforts, in addition to some preliminary results recently obtained, will be reviewed below.

Literature Survey

As originally anticipated the available literature suggests that the most likely NDF gases are excimers, which have unusually high emission efficiency (10-50%). However, our literature survey shows that no experimental studies of nuclear pumping of excimers for purposes similar to this work has been done. This emphasizes the need for the gas selection process carried out in the first phase of this project.

Some estimated efficiencies for excimer emission from mixtures using e-beam pumping or special other electrically-stimulated methods have been reported. (Efficiency is defined as the fraction of energy deposited in the gas which goes into light of interest.) Examples of interest for present purposes, along with their

emission wavelength. are XeBr (282 nm) -- 29%; KrF (249 nm) -- 28%, and XeI (253 nm) -- 37%. It is planned to test these excimers, along with some others, to determine the range of emission efficiencies possible for the present NDF concept.

Data Analysis System

The data to be taken in this research will include the wavelength vs intensity of the emission of various excimers for a range of pressures and mix ratios. These fluorescence spectra must be compared against the photodissociation cross-sections of candidate lasants, as a function of wavelength, to determine the best mix. To simplify this analysis, a computer program has been developed to compare the gas emission against the cross-section of the lasant at integral wavelengths between 230 and 330 nm. The emission intensity is multiplied by the photodissociation cross-section at each wavelength. The sum of this product over all wavelengths gives an "integral," which is a key figure of merit. That is, the larger this integral, the better the match between the gas and the lasant. To test the procedure, the emission data for several gases have been taken from tabulated gas discharge information and compared to the cross-sections of CF_3I and $\text{C}_3\text{F}_7\text{I}$, the two most likely lasant candidates. Examples for Ne and He are shown in Figure 2. This routine will be used in a similar fashion in future experiments where the emission spectra is taken from nuclear pumping experiments.

Vacuum/Gas Handling System

In order to perform the fluorescence tests it was necessary to construct a vacuum and gas handling system to allow evacuation and

Figure 2: Comparison of electrical gas discharge emission of Ne and He against photoabsorption cross-sections of two candidate lasants. The "integral" number, explained in the text, is the figure of merit.

charging of a test cell with candidate gases. Because of the relatively high pressures involved in nuclear fluorescence testing (approximately 1 atm), only a moderate vacuum is required to prevent a buildup of the concentration of impurities (e.g., air) in the mix. For this purpose a Sergeant-Welch rotary vane roughing pump attached to a CVC oil diffusion pump was cleaned and rejuvenated. This system easily attains 1 mtorr, and work is continuing to further reduce impurities and contamination that may effect gas kinetics.

The gas handling system was designed to allow filling of 1 to 4 gases at pressures ranging from 1 to 2500 torr. This was accomplished by using three gauges covering different pressure ranges. The system was also designed with a hold-up tank to store irradiated gases. Sufficient gas is used in the testing that relatively large activities of radioactive gases are produced. Consequently, immediate release to the environment could approach annual release limits for the reactor facility. To prevent this, irradiated gases are diverted to the hold-up tank and stored for several days until the activity has decayed sufficiently for release. A schematic of the vacuum/gas handling system is shown in Figure 3.

Test Cell

The test cell for the parameter study was designed to utilize the $n(^{10}\text{B}, \alpha)^7\text{Li}$ reaction. This is done by coating a thin (approximately 1 micron) layer of enriched boron on the inside of a 1-inch diameter aluminum tube. (These tubes are used in neutron detection chambers.) Neutrons impinging on the tube from the

Figure 3: Vacuum/gas handling system for gas fluorescence testing.

reactor pulse react with the boron, sending half of the energetic reaction products into the aluminum wall, and half into the gas. The limited range of these particles restricts the diameter of the tube to $\sim$ 1-inch. However it was felt a tube of 1-inch diameter by 12-inch length would generate sufficient light for this testing. Because of the limited volume, and because the boron layer results in a non-reflective coating on the cell wall, this scheme is not optimum for a laser cell (see Figure 1). Hence, the final gas selection will be done with a modified design that employs ^3He . This will eliminate the diameter restriction and allow reflective surfaces; hence it is more suitable for the final laser test, while the high cost of the ^3He fill is avoided in the earlier parametric studies. It is anticipated that the boron and helium will generate similar fluorescence per unit energy deposited in the gas, so breaking the work into two phases should not result in discontinuous data.

A measurement of the energy deposition in the cell during a pulse is important to understanding the data. For this purpose a piezoresistive pressure transducer (Kulite IPT-1100-250A) was attached to the test cell. As the reaction product energy is deposited in the cell gas during a pulse, the gas heats up and increases in pressure. This increase is easily measurable, and gives a good indication of the energy deposition in the gas, as suggested by other workers.^(3,4) Preliminary test results indicate good agreement with other dosimetry methods (see the following section). A x250 pre-amplifier was constructed for this device to allow direct monitoring on an oscilloscope.

The vacuum and gas fill lines are attached to the test cell with pneumatic valves. The lines run 4 meters from where the cell is located in the reactor throughport to the position of the vacuum station in the shielding cage. This obviates the need for handling of the cell when changing gases --- an important factor for efficient operation since the cell becomes activated during pulsing and takes some time to "cool down." A schematic of the test cell is shown in Figure 4.

Optical Collection System

The system to collect light from the fluorescing gas was designed with the goal of obtaining fluorescence spectra of the gases along with a measurement of the time-dependence of the fluorescence. The design must allow for calibrations at all wavelengths to determine the absolute fluorescence efficiency from the gas. The dynamic measurement is important to the determination of whether the gas fluoresces linearly with dose rate during the relatively long 15 msec. of the TRIGA pulse, or whether there is saturation at some dose rate. (Dose rate refers to the rate of energy deposition to the gas from the neutron reaction products.)

The fluorescence spectra is taken with an Optical Multi-channel Analyzer (OMA) (Princeton Applied Research model 1450) using a spectral grating allowing a 450-nm wide spectra to be taken anywhere between 200 and 1100 nm. The OMA takes one scan during the pulse, time integrating the spectra over the 15 msec. of the pulse, and storing the information into 512 channels. A mercury discharge lamp (OSRAM model Hg100) was purchased which emits lines in the UV, and was used to spectrally calibrate the OMA. The task

Figure 4: Schematic of cell for testing fluorescing gases.

of accurate intensity calibration of the OMA (i.e., how many watts of light at a given wavelength corresponds to the counts recorded on the OMA) has yet to be performed. However, manufacturer's data on the sensitivity of the equipment gives an order-of-magnitude estimate that is satisfactory for exploratory studies. Thus the comparison of fluorescence of different gas mixtures is being done now, with the calibration performed later.

An effort was also expended to develop a technique to transfer spectral data from the OMA to an AT&T personal computer to allow permanent record storage and data analysis. The AT&T computer is not directly compatible with this system, but after some modifications it is performing satisfactorily.

The second goal of obtaining time-dependence information during the pulse is accomplished by attaching a photomultiplier tube to a GCA/McPherson monochromator with a variable slit width. The monochromator is tuned to the most intense wavelength region of the excimer emission spectrum, and the fluorescence at that wavelength is recorded dynamically during the pulse. The signal from an ion chamber in the reactor is simultaneously recorded to provide the temporal shape of the neutron pulse.

Our analysis (similar to Refs. 1 and 2) of the predicted fluorescence of candidate excimers indicates that the gas in the test cell should fluoresce sufficiently (peak total of 1 to 10 kW) to allow testing without any special optics such as a light pipe running from the cell to the OMA. Thus the OMA is simply placed in a shielded area at 4 meters from the reactor wall (see Figure 5). This makes calculation of absolute light emission by the test cell

Figure 5: Test set-up in Univ. of Ill. TRIGA reactor.

gas relatively straightforward. It was hoped that the monochromator would be sufficiently sensitive to allow similar testing. Preliminary results indicate, however, that it may be necessary to attach a radiation-hardened fiber optic (available from prior work) to the cell to couple sufficient light out to the monochromator. This will be attempted during further testing this summer.

Preliminary Test Results

Testing of gas fluorescence has only recently begun (end of May), so there is limited data to report at this time. Some pulses were done on XeBr, however, with what appear to be promising results. This and associated measurements are presented below.

Figure 6 shows the pressure rise during a pulse, as measured by the pressure transducer on the cell, with gas fill as indicated on the figure. It is seen that the pressure rises to a peak near the end of the pulse, and then begins to decrease again as the heated gas cools against the cell wall. The pressure rise corresponds to approximately a 250°C temperature rise. There is reason to believe that the temperature rise has a significant effect on the kinetic reactions in the gas. This effect will be studied later by varying the pulse size and to the extent possible, by controlling the initial gas temperature.

The peak of the pressure rise can be converted to energy deposited in the gas by assuming ideal gas behavior where the heat capacity equals $3/2 R$ (gas constant). This calculation indicates 0.13 J/cm³ deposited in the gas during this pulse. This figure corresponds well with a theoretical estimate⁽⁵⁾ of 0.18 J/cm³ in

Figure 6: Pressure rise in test cell with 800 torr fill gas during a reactor pulse.

760 torr of He and a measurement using another technique⁽⁶⁾ of 0.16 J/cm³ in 400 torr O₂, both for a 1 inch diameter boron-coated tube in a TRIGA pulse.

Preliminary results for fluorescence of one mix of Xe and Br₂ is shown in Figure 7. The "peak" from 250 to 320 nm is tentatively ascribed to XeBr emission. Figure 8 shows XeBr has its strongest peak at 282 nm, which is the location of the peak in Figure 7. The noise level in the experiment is quite large, mostly due to a long (2 second) scan required for this run because a trigger circuit on the OMA was inoperative. A large background signal is obtained during the long scan time (>1600 counts), so subtracting out this background by doing a pulse with an empty cell leaves considerable noise. This is also the reason for the negative intensities indicated. It is anticipated future tests with an operative trigger will have much smaller noise level, greatly simplifying the identification of the fluorescence peaks.

Using the absolute sensitivity of the OMA from the manufacturer's data, we estimate that the fluorescence energy emitted by the gas within this peak (250 to 320 nm) represents approximately 1% of the energy deposited in the gas. While significantly less than the maximum expected value of roughly 25%, this figure is encouraging since it indicates that the present test set-up should be capable of performing the measurements needed. It is expected that further testing with various gas constituents, mixture ratios, and pressures will allow an optimization of the fluorescence efficiency.

Figure 7: Preliminary results of nuclear-induced XeBr fluorescence obtained recently in the TRIGA.

Figure 8: Published spectrum of XeBr eximer emission (not nuclear pumped). (J.C. Swingle, et al., Appl. Phys. Lett., Vol. 28, No. 7, Apr. 1976, pg 387-388)

Conclusions

Progress made during the present budget year has been largely as anticipated in the original proposal for this project. A unique experimental set-up has been developed to allow testing of candidate nuclear pumped flashlamp gases in the University of Illinois TRIGA reactor. Preliminary results indicate the set-up, as designed, is adequate for use in the measurement program outlined. Testing various gas mixtures will continue this summer, and probably into early Fall. The gas mixture showing the best fluorescence in the wavelengths of interest will be used in design and testing of a nuclear flashlamp-driven atomic iodine laser.

References:

- 1) J. W. Wilson and A. Shapiro, J. Appl. Phys. 51(5), May 1980, pg 2387-2393.
- 2) J. W. Wilson, Appl. Phys. Lett. 37(8), Oct. 1980, pg 695-697.
- 3) C. Duzy and J. Boness, IEEE J. Quant. Elec., QE-16(6), June 1980, pg 640-649.
- 4) J. Rice, et al., IEEE J. Quant. Elec., QE-16(12), Dec. 1980, pg 1315-1325.
- 5) A. Chung and M. Prelas, 1983 IEEE Int. Conf. Plasma Sci, San Diego, CA, 6A5, May (1983).
- 6) H. E. Elsayed-Ali and G. H. Miley, Rev. Sci, Instrum. 55(8), Aug. 1984, pg 1553-1555.

**DATE
FILMED**
8/11/92