QUARTERLY REPORT SIXTH QUARTER, COVERING 1/1/92 TO 3/31/92

FUNDING AGENCY: U.S. Department of Energy P.E.T.C.

GRANT NO: DE-FG22-90PC90297

PROJECT TITLE: Impact of Nonequilibrium Particle
Temperature Considerations on Seeded
Coal Combustion Plasma PropertiesPRINCIPAL INVESTIGATOR: Dr. Adeboyejo A. Oni
INSTITUTION: Morgan State University
School of Engineering
Baltimore, Maryland 21239
(410)319-3231/3129/3249

DOE/PC/90297--T5

DE92 015534

CONTRACT SPECIALIST: Ms Rhonda Dupree
PETC; MS 921-165TECHNICAL OFFICER: Dr. Harold Chambers
PETC; MS 922

THE RESEARCH TEAM:

1. Dr. Adeboyejo A. Oni, Principal Investigator
Associate Professor of Engineering and Applied Science
Morgan State University, Baltimore, Maryland
2. Mr. Feng Lin, Graduate Research Assistant
Ph.D student in Mechanical Engineering (Thermofluids)
University of Maryland, Graduate School Baltimore
Catonsville, Maryland
3. Ms. Kimberly Myles, Undergraduate Research Assistant
Senior Industrial Engineering Student
Morgan State University, Baltimore, Maryland
4. Dr. Robin Khosah, Consultant on Chemical Equilibrium
Combustion Diversified Technologies Inc.
551 Larimar Ave
P.O. Box 5297
Pittsburgh, PA 15206

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

I. ABSTRACT:

The first of the three tasks of this research activity is to develop a model that represents steady, nonequilibrium energy interactions between post-combustion entrained particles and carrier gases, under typical coal-fired MHD operating conditions. The second task is to use the developed model to evaluate, for both the MHD linear channel and disk configurations, the impact of nonequilibrium particle temperatures on predicted gasdynamic and electrical property values that depend, at times critically, on plasma temperatures, and on which the overall MHD system performance depends. The third task is to evaluate the relative impact of gas-particle temperature differences on generator slag phenomena and consequently on MHD channel performance.

II. INTRODUCTION:

Current MHD simulation models do not consider the impact of true particle temperatures on plasma properties and consequently on overall MHD Channel performance, simply for the reasons of reduction computational effort. But some early combustion modeling had shown such impacts do exist and may be important.

Based on Burns and Roe/SAIC MHD Linear Channel code(equilibrium model), an extended quasi one-dimensional, steady state, multiphase nonequilibrium model was established hereby in the last quarter. This nonequilibrium model was used to represent the post combustion energy interactions between entrained particles and gases. The results were obtained from the investigation of the impact of nonequilibrium particle temperatures on the predicted performance of a Faraday-type Channel.

III. QUARTER RESEARCH ACTIVITIES:

Model development, representing the first task of this research effort is complete. An extended quasi one-dimensional model was developed that represented steady, nonequilibrium energy interactions between post-combustion entrained particles and carrier gases, under typical MHD conditions. This model was coupled to the existing Burns and Roe/SAIC MHD Linear Channel simulation code, and was then used to address the second task of the project, which is to evaluate the impact of nonequilibrium particle temperatures on predicted gasdynamic and electrical MHD property values, and consequently such impacts on overall MHD performance predictions.

The simulation of an MHD Linear Channel with this model has just been completed. Work is currently ongoing on applying the nonequilibrium model to the MHD Disk configuration. Channel inlet particle and plasma property initial values, originally to be provided through linkages with the 'first submodel' are being provided, in the interim, as a batch data file. This

is due to lingering modeling challenges in the first submodel with regard to the generation of gas-particle initial property values.

Interim results with the Linear Channel indicate that the nonequilibrium particle temperature considerations has only a moderate effect on the prediction of channel performance over the equilibrium model. The maximum relative increase in predicted values for electrical conductivity, current density, heat loss and gross power generated was found to be 3.5%, 3.0%, 1% and 2.5%, respectively. These numbers may need to be modified somewhat, once the first submodel is available to predict gas-particle initial property values.

This ongoing systematic investigation of the impact of nonequilibrium particle temperatures on state properties and overall predicted MHD system performance will allow for the incorporation of considerations for gas-particle temperature differences into existing Fossil Energy MHD simulation models, and will make for a more analytically realistic MHD performance predictions, for both the Linear and Disk configurations.

IV. PREVIEW OF SEVENTH QUARTER ACTIVITIES:

1. The completion and validation of the first submodel, to be used to predict gas-particle initial property values, is anticipated for the end of June, 1992.
2. In the meantime, investigations of nonequilibrium particle temperature impact on the predicted performance of the Disk channel are planned for July, 1992.
3. Full-scale evaluation studies of plasma properties, using both submodels and for both Linear and Disk channels, including investigation into slag deposition ramifications, will then span the rest of the coming quarter.

**DATE
FILMED
8/26/92**