DOE/ER/13282-6

AROMATICS OXIDATION AND SOOT FORMATION IN FLAMES

Progress Report for Year Beginning 15 August 1988

DOE/ER/13282--6

DE92 016846

Submitted to:

Fundamental Interactions Branch
Division of Chemical Sciences
Office of Basic Energy Sciences
Department of Energy
Washington, DC 20545

Submitted by:

Department of Chemical Engineering
Massachusetts Institute of Technology
Cambridge, Massachusetts 02139
Principal Investigator: J. B. Howard
(617) 253-4574

DOE Contract No. DE-FG02-84ER13282

DOE Report No. DOE/ER/13282-6

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

REPRODUCTION OF THIS DOCUMENT IS UNLIMITED

JUL 02 1992

AROMATICS OXIDATION AND SOOT FORMATION IN FLAMES

Introduction

Work during this contract period has been concerned with the mechanisms through which aromatics are formed and destroyed in flames, and the processes responsible for soot formation. Recent progress has been primarily in two areas: experiments and modeling of the soot nucleation process in low pressure benzene flames and preparation for experiments on the destruction mechanisms of benzene. In addition, we have incorporated "weak collision" formalisms into a fall-off computer code.

Soot Nucleation Experiments and Modeling

Sooting benzene/oxygen/argon flat flames at low pressures (flame conditions listed in Table 1) have been studied to help elucidate the mechanisms of soot nucleation. The experimental apparatus is instrumented with both probe sampling and *in situ* optical particle sizing diagnostics. The polyaromatic hydrocarbon (PAH) intermediates in soot nucleation are removed from the flame with sampling probes for analysis. The primary analytical methods used on the samples have been: capillary GC - which yields detailed concentration profiles of PAH up to 5 aromatic rings, cyano-column chromatography - which fractionates the sample into molecular weight ranges, and UV-visible spectrometry - which is indicative of the size distribution of the PAH's. Light gases are measured with an on-line mass spectrometer.

Figure 1 shows the trends in the PAH concentration measurements in the low pressure sooting flames. Several features are worth noting. *First*, the PAH concentrations all fall precipitously right at the region of soot nucleation (indicated by orange luminosity). This is also the point where the temperature peaks (at about 2000°K in these flames). *Second*, the relative extent of decay of the larger molecules is less than that of the smaller ones. *Third*, the relative magnitudes of biphenyl and acenaphthalene are about equal. The former is indicative of a growth process through which intact aromatic rings collide and react and the latter is a manifestation of a growth mechanism through sequential addition of acetylene.

Traditional Rayleigh scattering and absorption techniques have been used to measure soot particle sizes and number densities. Optical properties of soot from Lee and Tien (1981) have been used. Figure 2 shows number density and particle diameter profiles for the $\phi = 2.4$, 40 torr flame. Also presented on the figure is the predicted number density trend using the Smoluchowski (1917) equation. The excellent agreement between the data and the prediction means 1) that the soot particles do collide with unit sticking efficiency, which is assumed by the calculation, and 2) that there are no significant ionic processes involved which would increase the effective collisional cross-section.

Relative absorption profiles for PAH have been measured optically using the method of Weiner and Harris (1988). Figure 3 shows the absorption profiles for flames at equivalence ratios of $\phi = 2.2$, 2.4, and 2.5. PAH concentration is proportional to the absorption signal. From probe sampling we have determined that the mass concentration of PAH is of the same order as soot in these flames. A surprising trend can be seen in the relative magnitudes of the PAH absorption at different equivalence ratios. While ultimate soot yields from these flames varies over a factor of 15 (from volume fraction $f_v = 1 \times 10^{-8}$ for $\phi = 2.2$ to $f_v = 1.5 \times 10^{-7}$ for $\phi = 2.5$, determined by absorption at 1.4 μm), the relative amounts of PAH produced in the soot nucleation zone varies by less than two fold for all flames. Even more surprising, the PAH concentration of the richest flame ($\phi = 2.5$) is less than that of the $\phi = 2.4$ flame. A possible explanation for this phenomenon is based on pyrolytic decay of the PAH. The $\phi = 2.2$ flame is hotter by 150 K (2150 K vs. 2000 K). The PAH appear to grow quite rapidly in the leaner flame due to higher concentration of H atom, but then

Table I Flame Conditions Studied

Class	I	II	III
P (torr)	20	40	40
ϕ	2.0	2.125	2.2, 2.4, 2.5
V (cm/s)	50	50	25
[Ar]	0.30	0.45	0.10

they are pyrolytically destroyed before they can be converted to soot.

A numerical model has been formulated to quantitatively explain the nucleation phenomenon. Mass growth of PAH and soot is modeled through addition of acetylene to aryl radicals. The rate constant is a fitted parameter, but is close to the value of Fahr *et al.* (1988) for $C_2H_2 + \text{phenyl} \rightarrow \text{phenyl-acetylene}$. The observed profiles cannot be explained if the nuclei are formed from C_2H_2 addition only, so we add a PAH + Aryl coagulation mechanism. The coagulation rate constant is a function of molecular size (e.g. the phenyl + benzene reaction uses the rate of Fahr *et al.* while large PAH's use the gas kinetic rate (sticking efficiency of unity) which has been observed for soot). The primary oxidant of soot precursors is OH. It has been observed (Neoh, 1981) that OH removes carbon from soot with a collision efficiency of approximately 0.2, which is several orders of magnitude higher than the measured collision efficiency for OH + benzene (He *et al.*, 1986). This apparent inconsistency may be resolved by explaining oxidation in a flame environment as OH plus an aryl radical. While this rate has not been directly measured, we would expect it to be close to gas kinetic with little or no activation energy. The model treats the rate as a fitted parameter. The rapid destruction of PAH in the zone where soot nucleates cannot be explained without invoking a highly activated (ca. 75 kcal/mol) unimolecular pyrolytic process. The model uses a slight deviation of the phenyl pyrolysis rate of Braun-Unkloff *et al.* (1988) to describe the pyrolysis of aryl radicals. It is observed that soot particles undergo little, if any, pyrolytic decay in hot H-atom rich environments so the model shuts down the pyrolysis channel once the PAH grow larger than 1000 amu. The aryl concentration is estimated by assuming that the partial equilibration of the reaction $H + PAH \rightleftharpoons H_2 + \text{Aryl Radical}$. Using the rate of Kiefer *et al.* (1985) and the thermodynamic data of Stein (1978), we would expect this equilibrium to be established fairly rapidly. H atom profiles are estimated based on the destruction rate of O_2 , assuming that the only O_2 destruction channel is $H + O_2 \rightarrow OH + O$ and using the rate coefficient recommended by Warnatz (1984).

Figure 4 shows the results of the model in predicting the soot and PAH dynamics of the $\phi = 2.4$, 40 torr flame. The agreement is fairly good, with the exception of the excessive oxidative decay of insolubles (soot) at high heights above burner. The level of agreement is roughly the same for the other flame conditions tested ($\phi = 1.8$, 20 torr and $\phi = 2.2$, 40 torr).

Aromatics Destruction Effort

The molecular-beam/mass spectrometer (MB/MS) combustion apparatus is being prepared for the study of benzene destruction in a well characterized environment. The experimental strategy is to measure the key radical concentration profiles in a hydrogen/oxygen 20 torr flame into which benzene will be introduced in sufficiently small concentrations so as to perturb the flame only slightly. The decay rate of benzene and formation rates of fragments will be measured to yield valuable information on the mechanisms and kinetics of benzene destruction.

A liquid fuel calibration system has been installed and tested which can monitor flow rates to within 0.5%. The near future experimental work includes 1) calibration and improving the alignment of the molecular-beam system and 2) selection of appropriate operating parameters for the $H_2/O_2/Ar/C_6H_6$ system.

We must account for the non-Arrhenius behavior caused by fall-off and chemical activation in working with relatively small molecules at low pressures. The effectiveness at which collisions remove vibrational energy from the adducts is one critical parameter which affects calculations of fall-off and chemical activation. We have produced a version of the QCPE (Quantum Chemistry Program Exchange) program FALLOFF which incorporates an effective collision efficiency, β_c . The program calculates β_c from the Troe (1977) or Gilbert *et al.* (1983) methods, as desired. RRKM densities of states are used, and either $\langle \Delta E \rangle_{down}$ or $\langle \Delta E \rangle_{all}$ may be chosen as temperature independent.

References

- Braun-Unkloff, M., Frank, P., and Just, Th., *in press* (1988)
 Fahr, A., Mallard, W.G., and Stein, S.E., 21st Symp. (Int'l) on Comb., p.825-831 (1988)
 Gilbert, R.G., Luther, L., and Troe, J., *Ber. Bunsenges. Phys. Chem.* **87**, 169 (1983)
 He, Y.Z., Mallard, W.G., and Tsang, W., *J. Chem. Phys.* **90**, 2196 (1986)

- Keifer, J.H., Mizerka, L.J., Patel, M.R., and Wei, H.C., *J. Chem. Phys.* **89**, 2103 (1985)
- Lee, S.C., and Tien, C.L., 18th Symp. (Int'l) on Comb., p. 1159 (1981)
- Neoh, K.G., Howard, J.B., and Sarofim, A.F., in *Particulate Carbon Formation During Combustion*, D.C. Siegl and G.W. Smith, Eds., p. 261, Plenum Press (1981)
- Smoluchowski, M.V., *Z. Phys. Chem.*, **92**, 129 (1917)
- Stein, S.E., *J. Phys. Chem.* **82**(5), 566 (1978)
- Troe, J., *J. Chem. Phys.* **66**, 4745 (1977)
- Warnatz, J., Chapter 5 of *Combustion Chemistry*, W.C. Gardiner, Ed., Springer-Verlag (1984)
- Weiner, A.M. and Harris, S.J., in press (1988). Also presented as Poster P37, 22nd Symp. (Int'l) on Comb.

Figure 1 PAH concentrations vs. Height Above Burner. Triangles: Phenylacetylene, Squares: Biphenyl, Circles: Acenaphthalene, Diamonds: Phenanthrene, $\phi=2.125$, 40 torr

Figure 2 Number density (triangles) and diameter (circles) vs. height above burner. $\phi=2.4$, 40 torr. Dotted line is Smoluchowski model predictions

Figure 3 PAH absorbance. 40 torr, 10%Ar, $\lambda=410$ nm

Figure 4 Numerical model results. $\phi=2.4$, 40 torr

**DATE
FILMED**

8/12/92