SEVENTH QUARTERLY REPORT

Project No. DE-FG22-89PC89782

on

**ENVIRONMENTAL IMPACT ASSESSMENT AND SELENIUM TRANSFORMATION
IN COAL MINE SPOILS**

Submitted to

**Mr. Jerry Harness, Project Officer
U.S. Department of Energy
Morgantown Energy Technology Center
Morgantown, WV 26507-0880**

June 1, 1991

by

Asmare Atalay and Kurtis J. Koll

**University of Oklahoma
Civil Engineering and Environmental Science
202 W. Boyd, Room 334
Norman, OK 73019**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ENVIRONMENTAL IMPACT ASSESSMENT of SELENIUM FROM COAL MINE ACTIVITIES

This quarterly report addresses the continued field investigation of a selected coal mining site in Oklahoma. The field investigation began July 1990, continuing through July 1991. The field methodology was described in an earlier report. Table 1. (Appendix) portrays all the data (field measurements) taken at the Henryetta experimental site. An analysis of this data would be useful in providing information for potential Se migration from a coal mining site and the distribution of Se in a soil profile of land reclaimed to its pristine state. Also addressed is the methodology developed (1) for SeO_4^{2-} and SeO_3^{2-} adsorption on selected soils, (2) leachate migration through a soil column using soil samples from the Henryetta reclamation site, and (3) chemical transformation of SeO_4^{2-} under harsh chemical conditions.

MATERIALS AND METHODS

I. Sample Collection

Soil samples from the Henryetta experimental site were collected periodically at depths of 30, 90, and 150 cm from the control, overburden and reclamation sites. A power drill with a six-inch auger was used to drill the appropriate depths. Hoffer tubes were used to remove soil samples at the designated depth. Approximately 300 grams of wet soil was removed from each bore hole. Samples were placed in Ziploc^R plastic bags and transported to the laboratory. Upon arrival, the samples were placed in plastic pans and air-dried.

Soils were then mechanically sieved, passing through a No. 10 sieve. The air-dried and <2 mm soil fraction from each sample were kept in Ziploc^R plastic bags until needed for subsequent experiments. Replacement samples were obtained from the field site as needed. To provide an additional control (check) for the adsorption study, a soil sample taken 15 cm below surface level from an agricultural site was used.

II. Soil Column Leachate-Mobility Study

A laboratory-constructed, Plexiglass^R soil column was filled with 1329.7 g of <2 mm, oven-dried soil recovered from the reclamation experimental site. The column was saturated with DI water by slowly filling the column from the bottom using a peristaltic pump. The column, filled with DI water, stood for one week to allow for saturation. Using the bottom orifice (effluent port), standing water was drained from the column. The mass of the saturated soil sample was 1768.1 g. The pore volume was calculated as 438.4 ml. The pore volume was defined as the mass of the saturated soil minus the mass of the oven-dried soil, using a density of 1.00 g/ml for the DI water. All masses, including those for the empty soil column, were recorded using an OHAUS Harvard^R trip balance. Outlet (sampling) ports are located along the length of the column. The column, being 61.30 cm long, had four sampling ports spaced every 15 cm (Figure 1). The column of soil has a diameter 5 cm and length 49 cm. A 12.30 cm head space above the soil was filled with DI water. A constant head was maintained using a peristaltic pump. 5 ml of both 380 mmol/m³

SeO_4^{2-} and $424 \text{ mmol/m}^3 \text{ SeO}_3^{2-}$, prepared from sodium salts, were loaded onto the soil surface. Five days were needed to allow the Se solution to saturate the soil, giving time for equilibration with the soil environment. After the Se solution percolated the soil, the effluent port was turned off. With no flow through the column, 5.5 h was used for an equilibration time. The head space was filled with DI water and the effluent port opened to receive leachate. The four outlets located at 15 cm intervals were used to withdraw a soil solution sample. At each sampling time and depth along the column, 4 aliquots were taken using a 12-gauge hypodermic needle and 3-ml plastic syringe. Each sampling episode required four integrated samples from each of the following: top sampling port, middle sampling port, bottom sampling port with one extract at the effluent port. Syringes used to extract soil solution from the column were rinsed in a sample vial containing 1 ml DI water.

III. Chemical Adsorption Equilibrium Study

Three soils, air-dried and sieved to receive a <2 mm fraction, were oven-dried in a NAPCO^R Model 620 oven at $100 \pm 1^\circ \text{C}$ for 48 h. The soils used for the adsorption equilibrium study included samples from the reclamation and control sites and a topsoil sample taken 15 cm below ground surface from an agricultural site located a considerable distance from any coal-mining activities. The topsoil sample was used as an additional experimental control. The reclamation soil sample was a composite of samples taken over a 3-month period.

The oven-dried samples were cooled in a desiccator to room temperature. Using a Mettler Typr H6 analytical balance soil masses ranging from 0.5 - 1.0 g were weighed into 15-ml screwcap Pyrex^R test tubes. Standard stock solutions of SeO_4^{2-} and SeO_3^{2-} were prepared from their sodium salts. The stock solution concentrations were 84 mg SeO_4^{2-} / l and 101 mg SeO_3^{2-} / l. Aliquots of the stock reagent were adjusted to approximate pH's 3, 5, 7, 9 and 12 with 0.10 M HCl and 0.10 M NaOH. A Fisher Accumet Model 420 Digital pH/ion Meter was used to make pH adjustments and record actual pH. 10 ml of either the SeO_4^{2-} or SeO_3^{2-} pH adjusted standard solutions were volumetrically added to each soil sample in the screwcap test tubes. Each sample was mechanically shaken for 24 ± 1 h with a platform shaker (Eberbach Corporation). After shaking, the soil solution was centrifuged 15 minutes using an IEC Spinnette centrifuge (Damon/IEC Division) and the supernatant filtered through #42 Whatman filter paper. The filtrate was collected in 25-ml glass collection vials with plastic, Teflon^R-lined screw caps.

For each soil type and pH duplicates were prepared, along with a blank which contained all reagents but no soils. The three soils were characterized using specific physical and chemical parameters of water extracts of each soil. These parameters included CND (conductivity of the soil solution extract), extract temperature, TDS (total dissolved solids), pH and Eh. The soil extract was collected from 20 g of soil mechanically shaken overnight with 80 ml

of 16 megaohm DI water.

The filtrates collected from each centrifuged and filtered soil were refrigerated until analysis. Filtrates were filtered using a micropore filter and appropriately diluted for analysis using ion chromatography.

IV. Chemical Transformation (Reduction) of SeO_4^{2-}

5 ml of 105 mg SeO_4^{2-} /l was volumetrically delivered into 15-ml screwcap test tubes. In addition each test tube received 5 ml of concentrated HCl (12 M). Duplicates were prepared (8 samples) and placed in a water bath using a Precision^R Model 181 water bath. The water bath temperature was maintained at $90 \pm 1^\circ\text{C}$. After 30 minutes, two test tubes were removed. At times of 60, 90 and 120 minutes, the remaining test tubes were removed. Each of the 8 test tubes contained 10 ml solution. The 10 ml of solution was diluted to 250 ml in a volumetric flask using 15 megaohm DI water. If no chemical conversion occurred, the SeO_4^{2-} concentration would be 2.1 mg/l. The pH was adjusted using 6M NaOH to pH 3.

For analysis using ion chromatography, subsequent dilution was needed because of the Cl^- concentration. The chemical conditions for the Se transformation were harsh. Concentrated HCl and high temperatures (90°C) were needed to actually digest the SeO_4^{2-} .

Figure 1. The peristaltic pump maintained a constant H, head pressure, by pumping DI water into the column. Sampling ports are located along the length of the column. At each sampling site, there are four ports from which to withdraw a soil solution sample. The bottom port (effluent port) was used to collect the column leachate, an additional sample.

APPENDIX

Table 1. Data was collected from the Henryetta experimental study site from July 1990 to July 1991. Access tubes 1 - 9 were used to obtain measurements from three depths; 30, 90 and 150 cm. The dash (-) does not imply missing data, but rather that a particular access tube was not used to measure that specific parameter. Access tube labeled 0 was used to obtain subsurface temperature and soil samples which were used for pH determinations and as a source of soil for experimental procedures. Many dashes may appear but are useful to align columns.

Table 1. Measurements of soil water, pH, Eh, Total Se, and Subsurface Temperature at the Henryetta Experimental Field Site.

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
7-26-90	Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-
		30	-	410	534	-	-	-	-	420	-	-
		90	-	-	-	470	-	384	-	-	-	465
		150	-	-	-	-	451	-	417	-	460	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	66	-	54	-	80	-
		90	-	-	19	15	-	-	-	-	14	-
		150	-	25	-	-	-	04	-	04	-	-
	Temperature °C	0	31	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	495	-	-	-	475	-	449
		90	-	367	-	-	403	-	065	-	-	-
		150	-	335	-	-	390	409	-	-	-	-

Table 1. (continued)

[illegible]

Table 1. (continued)

[illegible]

Table 1. (continued)

[illegible]

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
8-15-90												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	414	494	-	-	-	-	457	-	-
		90	-	-	-	465	-	460	-	-	-	451
		150	-	-	-	-	396	-	483	-	319	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	38	-	67	-	-	00
		90	-	-	20	-	-	-	-	30	23	-
		150	-	07	-	-	-	30	-	06	-	-
	Temperature °C	0	32	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	434	-	-	-	-056	-	485
		90	-	451	-	-	470	-	-007	-	-	-
		150	-	384	-	-	441	387	-	-	-	-

Table 1. (continued)

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube											
			0	1	2	3	4	5	6	7	8	9		
8-22-90	Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
			30	-	408	479	-	-	-	-	461	-	-	-
			90	-	-	-	414	-	456	-	-	-	459	-
			150	-	-	-	-	399	-	499	-	-	321	-
	Soil Moisture (centibars)		0	-	-	-	-	-	-	-	-	-	-	-
			30	-	-	-	28	-	69	-	-	-	00	-
			90	-	-	22	-	-	-	32	-	24	-	-
			150	-	08	-	-	30	-	-	08	-	-	-
	Temperature °C		0	31	-	-	-	-	-	-	-	-	-	-
			30	31	-	-	-	-	-	-	-	-	-	-
			90	29	-	-	-	-	-	-	-	-	-	-
			150	27	-	-	-	-	-	-	-	-	-	-
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-	
		30	-	-	-	465	-	-	-	-176	-	489	-	
		90	-	475	-	-	482	-	096	-	-	-	-	
		150	-	385	-	-	440	376	-	-	-	-	-	

Table 1. (continued)

[illegible]

Table 1. (continued)

[illegible]

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	493	-	-	-	188	-	454
		90	-	462	-	-	484	-	207	-	-	-
		150	-	383	-	-	422	367	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	26	-	-	16	-	-	12	-
		90	-	-	-	24	-	-	-	06	-	12
		150	-	-	12	-	-	-	07	-	02	-
	Temperature °C	0	42	-	-	-	-	-	-	-	-	-
		30	29	-	-	-	-	-	-	-	-	-
		90	27	-	-	-	-	-	-	-	-	-
		150	25	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	5.8	-	-	-	-	-	-	-	-	-
		90	6.9	-	-	-	-	-	-	-	-	-
		150	6.9	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	550	-	-	-	111	-	-	-	495
		90	-	-	578	-	591	-	-	602	-	-
		150	-	-	-	580	-	-	598	-	575	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	30	-	-	03	-	66	-
		90	-	55	-	-	-	60	-	-	-	12
		150	-	-	54	-	22	-	-	42	-	-
	Temperature °C	0	41	-	-	-	-	-	-	-	-	-
		30	33	-	-	-	-	-	-	-	-	-
		90	30	-	-	-	-	-	-	-	-	-
		150	28	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	3.9	-	-	-	-	-	-	-	-	-
		90	4.0	-	-	-	-	-	-	-	-	-
		150	4.2	-	-	-	-	-	-	-	-	-
9-12-90												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	391	484	-	-	-	-	397	-	-
		90	-	-	-	376	-	284	-	-	-	568
		150	-	-	-	-	399	-	537	-	-106	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	00	-	00	-	-	-	-	00
		90	-	-	22	-	-	-	42	-	19	-	-
		150	-	08	-	-	33	-	-	10	-	-	-
	Temperature °C	0	27	-	-	-	-	-	-	-	-	-	-
		30	29	-	-	-	-	-	-	-	-	-	-
		90	28	-	-	-	-	-	-	-	-	-	-
		150	26	-	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-	-
		30	4.2	-	-	-	-	-	-	-	-	-	-
		90	4.2	-	-	-	-	-	-	-	-	-	-
		150	4.2	-	-	-	-	-	-	-	-	-	-
Control Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-	
	30	-	-	-	484	-	-	-	466	-	-	488	
	90	-	448	-	-	445	-	211	-	-	-	-	
	150	-	354	-	-	431	373	-	-	-	-	-	
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-	
	30	-	-	67	-	-	63	-	-	54	-	-	
	90	-	-	-	32	-	-	-	08	03	-	-	
	150	-	-	11	-	-	-	06	-	-	12	-	

Table 1. (continued)

[illegible]

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
9-24-90	pH	0	-	-	-	-	-	-	-	-	-	-	-
		30	4.0	-	-	-	-	-	-	-	-	-	-
		90	4.0	-	-	-	-	-	-	-	-	-	-
		150	3.9	-	-	-	-	-	-	-	-	-	-
	Total Se (mg/kg)	0	-	-	-	-	-	-	-	-	-	-	-
		30	0.12	-	-	-	-	-	-	-	-	-	-
		90	0.09	-	-	-	-	-	-	-	-	-	-
		150	< 0	-	-	-	-	-	-	-	-	-	-
	Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
			30	-	418	471	-	-	-	-	406	-	-
			90	-	-	-	364	-	423	-	-	-	586
			150	-	-	-	-	406	-	417	-	319	-
Soil Moisture (centibars)		0	-	-	-	-	-	-	-	-	-	-	
		30	-	-	-	-	00	-	00	-	-	00	
		90	-	-	26	-	-	-	-	55	38	-	
		150	-	10	-	-	-	34	-	10	-	-	

Table 1. (continued)

[illegible]

Table 1. (continued)

[illegible]

Table 1. (continued)

[illegible]

Table 1. (continued)

[illegible]

Table 1. (continued)

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	482	-	-	-	018	-	520
		90	-	467	-	-	492	-	309	-	-	-
		150	-	413	-	-	442	467	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	11	-	-	04	-	-	03	-
		90	-	-	-	56	-	-	-	01	-	15
		150	-	-	08	-	-	-	04	-	00	-
	Temperature °C	0	16	-	-	-	-	-	-	-	-	-
		30	16	-	-	-	-	-	-	-	-	-
		90	18	-	-	-	-	-	-	-	-	-
		150	20	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	5.6	-	-	-	-	-	-	-	-	-
		90	6.4	-	-	-	-	-	-	-	-	-
		150	6.8	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	436	-	-	-	223	-	-	-	495
		90	-	-	568	-	591	-	-	531	-	-
		150	-	-	-	523	-	-	603	-	551	-

Table 1. (continued)

[illegible]

Table 1. (continued)

[illegible]

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	462	-	-	-	-043	-	533
		90	-	487	-	-	476	-	311	-	-	-
		150	-	314	-	-	444	476	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	15	-	-	08	-	-	05	-
		90	-	-	-	56	-	-	-	02	-	15
		150	-	-	11	-	-	-	06	-	01	-
	Temperature °C	0	26	-	-	-	-	-	-	-	-	-
		30	17	-	-	-	-	-	-	-	-	-
		90	18	-	-	-	-	-	-	-	-	-
		150	19	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	5.9	-	-	-	-	-	-	-	-	-
		90	6.7	-	-	-	-	-	-	-	-	-
		150	6.7	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	550	-	-	-	540	-	-	-	545
		90	-	-	655	-	610	-	-	590	-	-
		150	-	-	-	580	-	-	640	-	630	-

Table 1. (continued)

Data and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	508	-	-	-	-081	-	475
		90	-	215	-	-	534	-	338	-	-	-
		150	-	-024	-	-	483	470	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	02	-	-	00	-	-	00	-
		90	-	-	-	48	-	-	-	00	-	16
		150	-	-	10	-	-	-	04	-	00	-
	Temperature °C	0	18	-	-	-	-	-	-	-	-	-
		30	15	-	-	-	-	-	-	-	-	-
		90	16	-	-	-	-	-	-	-	-	-
		150	18	-	-	-	-	-	-	-	-	-
pH	0	0	-	-	-	-	-	-	-	-	-	
	30	5.9	-	-	-	-	-	-	-	-	-	
	90	6.8	-	-	-	-	-	-	-	-	-	
	150	7.1	-	-	-	-	-	-	-	-	-	
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	
		30	-	-001	-	-	-	127	-	-	-	253
		90	-	-	577	-	611	-	-	572	-	-
		150	-	-	-	567	-	-	614	-	568	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	02	-	-	10	-	00	-
		90	-	12	-	-	-	56	-	-	-	08
		150	-	-	40	-	36	-	-	22	-	-
	Temperature °C	0	16	-	-	-	-	-	-	-	-	-
		30	16	-	-	-	-	-	-	-	-	-
		90	18	-	-	-	-	-	-	-	-	-
		150	19	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	3.9	-	-	-	-	-	-	-	-	-
		90	3.7	-	-	-	-	-	-	-	-	-
		150	3.8	-	-	-	-	-	-	-	-	-
11-30-90												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	412	455	-	-	-	-	339	-	-
		90	-	-	-	459	-	417	-	-	-	640
		150	-	-	-	-	445	-	588	-	376	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	48	-	54	-	-	-	64
		90	-	-	40	-	-	-	-	-	62	55	-
		150	-	17	-	-	-	48	-	-	32	-	-
	Temperature °C	0	12	-	-	-	-	-	-	-	-	-	-
		30	10	-	-	-	-	-	-	-	-	-	-
		90	08	-	-	-	-	-	-	-	-	-	-
		150	09	-	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-	-
		30	4.2	-	-	-	-	-	-	-	-	-	-
		90	5.0	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-	-
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	481	-	-	-	-064	-	-	491
		90	-	251	-	-	625	-	328	-	-	-	-
		150	-	-062	-	-	455	465	-	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	00	-	-	00	-	-	-	00	-
		90	-	-	-	48	-	-	-	00	-	-	14
		150	-	-	08	-	-	-	05	-	-	00	-

Table 1. (continued)

[illegible]

Table 1. (continued)

[illegible]

Table 1. (continued)

[illegible]

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	501	-	-	-	046	-	-	-	284
		90	-	-	492	-	557	-	-	557	-	-
		150	-	-	-	468	-	-	595	-	512	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	14	-	10	-	-	-	-	-
	Temperature °C	0	28	-	-	-	-	-	-	-	-	-
		30	20	-	-	-	-	-	-	-	-	-
		90	23	-	-	-	-	-	-	-	-	-
		150	22	-	-	-	-	-	-	-	-	-
05-30-91												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-199	-239	-	-	-	-	-198	-	-
		90	-	-	-	570	-	364	-	-	-	245
		150	-	-	-	-	542	-	520	-	437	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	06	-	-	-	08	-	-	-	14
		90	-	-	-	-	-	-	03	-	-	-
		150	-	15	-	-	05	-	-	-	-	-
	Temperature °C	0	29	-	-	-	-	-	-	-	-	-
		30	27	-	-	-	-	-	-	-	-	-
		90	25	-	-	-	-	-	-	-	-	-
		150	22	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	297	-	-	-	-	-015	-	-044
		90	-	-025	-	-	-341	-	332	-	-	-
		150	-	-421	-	-	342	461	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	12	-	-	02	-	-	07	-
		90	-	-	-	04	-	-	-	08	-	-
		150	-	-	08	-	-	-	22	-	14	-

Table 1. (continued)

[illegible]

Table 1. (continued)

[illegible]

Table 1. (continued)

Table 1. (continued)

[illegible]

Table 1. (continued)

[illegible]

Table 1. (continued)

Data and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	127	-	-	-	-112	-	-	273
		90	-	-373	-	-	361	-	275	-	-	-	-
		150	-	-462	-	-	325	511	-	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	12	-	-	-	-	-	06	-	-
		90	-	-	-	02	-	04	-	08	-	-	-
		150	-	-	08	-	-	-	20	-	12	-	-
	Temperature °C	0	26	-	-	-	-	-	-	-	-	-	-
		30	26	-	-	-	-	-	-	-	-	-	-
		90	26	-	-	-	-	-	-	-	-	-	-
		150	24	-	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	354	-	-	-	034	-	-	-	-	088
		90	-	-	561	-	497	-	-	601	-	-	-
		150	-	-	-	501	-	-	577	-	032	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	10	-	-	00	-	09	-	-
		90	-	12	-	-	-	24	-	-	-	00	-
		150	-	-	16	-	10	-	-	13	-	-	-

Table 1. (continued)

[illegible]

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	450	-	-	-	420	-	512
		90	-	021	-	-	433	-	198	-	-	-
		150	-	280	-	-	286	307	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	02	-	-	37	-	-	64	-
		90	-	-	-	14	-	-	-	12	-	08
		150	-	-	12	-	-	-	22	-	15	-
	Temperature °C	0	34	-	-	-	-	-	-	-	-	-
		30	29	-	-	-	-	-	-	-	-	-
		90	26	-	-	-	-	-	-	-	-	-
		150	23	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	373	-	-	-	005	-	-	-	236
		90	-	-	460	-	488	-	-	552	-	-
		150	-	-	-	545	-	-	577	-	386	-

Table 1. (continued)

[illegible]

Table 2. SeO_3^{2-} and SeO_4^{2-} mobility through a soil column prepared from soils collected from the Henryetta reclamation site. Aliquots of soil solution were collected from the column with respect to time and length (depth) of the column.

Column Depth (cm)	Sample/Id. No.	Time (h)	Concentration (ppm)	
			SeO_3^{2-}	SeO_4^{2-}
(blank)	SC-1	0	-	-
C_i	SC-2	-	52.26	52.99
0.6	SC-3	1	-	0.25
0.6	SC-4	24	0.54	0.30
15.8	SC-5	24	-	0.70
31.0	SC-6	24	-	0.14
46.0	SC-7	24	-	0.38
0.6	SC-9	65	-	0.19
15.8	SC-10	65	-	0.21
31.0	SC-11	65	-	0.36
46.0	SC-12	65	-	0.08
0.6	SC-13	96	3.82	2.79
15.8	SC-14	96	0.20	0.79
31.0	SC-15	96	-	0.30
46.0	SC-16	96	-	0.28
0.6	SC-17	264	-	0.72
15.8	SC-18	264	0.30	0.93
31.0	SC-19	264	N.D.	8.64
46.0	SC-20	264	-	0.15
0.6	SC-21	379	-	0.36
15.8	SC-22	379	-	0.90
31.0	SC-23	379	-	0.16
46.0	SC-24	379	-	0.18

The column depth is defined as the cm the sampling port is below the soil surface in the column. The identification number identifies (SC) the soil column experiment and the sample number. C_i is the initial concentration of Se species used to load the column. The time is the cumulative time flow occurs in the column. The flow rate is near 1.5 ml per day. The dash (-) indicates no SeO_3^{2-} was measured using ion chromatography. 379 elapsed hours is 16 days.

Table 3. Chemical transformation data is recorded for the conversion of SeO_4^{2-} to SeO_3^{2-} under harsh chemical conditions. The experiment was conducted at 90 °C using concentrated HCl.

Sample Number	Elapsed Time (min)	Concentration (ppm)	
		SeO_3^{2-}	SeO_4^{2-}
C_i	0	00.0	106
1	30	52.0	-
2	30	97.5	14.3
3	60	94.9	15.6
4	60	120.9	-
5	90	32.5	1.3
6	90	61.1	1.3
7	120	N.D.	N.D.
8	120	91.0	-

Raw data is recorded as received from the ion chromatography analysis. The dash (-) indicates no measureable results. N.D. is no acceptable data determined. The data table represents the disappearance of SeO_4^{2-} and the appearance of SeO_3^{2-} . C_i is the initial concentration of SeO_4^{2-} .

Table 2. SeO_3^{2-} and SeO_4^{2-} mobility through a soil column prepared from soils collected from the Henryetta reclamation site. Aliquots of soil solution were collected from the column with respect to time and length (depth) of the column.

Column Depth (cm)	Sample/Id. No.	Time (h)	Concentration (ppm)	
			SeO_3^{2-}	SeO_4^{2-}
(blank)	SC-1	0	-	-
C_i	SC-2	-	52.26	52.99
0.6	SC-3	1	-	0.25
0.6	SC-4	24	0.54	0.30
15.8	SC-5	24	-	0.70
31.0	SC-6	24	-	0.14
46.0	SC-7	24	-	0.38
0.6	SC-9	65	-	0.19
15.8	SC-10	65	-	0.21
31.0	SC-11	65	-	0.36
46.0	SC-12	65	-	0.08
0.6	SC-13	96	3.82	2.79
15.8	SC-14	96	0.20	0.79
31.0	SC-15	96	-	0.30
46.0	SC-16	96	-	0.28
0.6	SC-17	264	-	0.72
15.8	SC-18	264	0.30	0.93
31.0	SC-19	264	N.D.	8.64
46.0	SC-20	264	-	0.15
0.6	SC-21	379	-	0.36
15.8	SC-22	379	-	0.90
31.0	SC-23	379	-	0.16
46.0	SC-24	379	-	0.18

The column depth is defined as the cm the sampling port is below the soil surface in the column. The identification number identifies (SC) the soil column experiment and the sample number. C_i is the initial concentration of Se species used to load the column. The time is the cumulative time flow occurs in the column. The flow rate is near 1.5 ml per day. The dash (-) indicates no SeO_3^{2-} was measured using ion chromatography. 379 elapsed hours is 16 days.

Table 3. Chemical transformation data is recorded for the conversion of SeO_4^{2-} to SeO_3^{2-} under harsh chemical conditions. The experiment was conducted at 90 °C using concentrated HCl.

Sample Number	Elapsed Time (min)	Concentration (ppm)	
		SeO_3^{2-}	SeO_4^{2-}
C_i	0	00.0	106
1	30	52.0	-
2	30	97.5	14.3
3	60	94.9	15.6
4	60	120.9	-
5	90	32.5	1.3
6	90	61.1	1.3
7	120	N.D.	N.D.
8	120	91.0	-

Raw data is recorded as received from the ion chromatography analysis. The dash (-) indicates no measureable results. N.D. is no acceptable data determined. The data table represents the disappearance of SeO_4^{2-} and the appearance of SeO_3^{2-} . C_i is the initial concentration of SeO_4^{2-} .

END

**DATE
FILMED**

8 / 31 / 92