Quarterly Technical Progress Report
Dec. 1, 1989 - April 1, 1990

DOE/PC/89781---1

Title: A NOVEL COAL FEEDER FOR PRODUCTION OF LOW SULFUR FUEL

DE92 016166

T. C. Keener, S. J. Khang, X. L. Yu

College of Engineering
University of Cincinnati
Cincinnati, Ohio 45221

ABSTRACT

A novel coal feeding system is currently undergoing testing and evaluation at the University of Cincinnati. The system consists primarily of an auger feed tube which is used to both convey and provide desulfurization of a high sulfur coal feedstock. The coal is conveyed at temperatures ranging from 350 to 550 °C and under normal atmospheric pressure. Under these mild processing conditions, the coal partially pyrolyzes and emits sulfur in the form of hydrogen sulfide while maintaining a relatively high heating value in the char product. The evolved gases are evacuated from the reactor (the feed tube) to another absorbing bed where H₂S reacts with the sorbent, usually lime or limestone. The resultant sorbent utilization is substantially higher than the values found in current dry scrubbing system and the produced low-sulfur char may then be used in a conventional steam boiler.

The current experimental results revealed that at a low temperature (375 °C) fractional devolatilization increases linearly with increasing residence time while fractional desulfurization approaches an exponential maximum value of about 32 percent as residence time goes to infinity. When desulfurization reaches to 30 percent at 40 minutes residence time, the devolatilization is only about 5 percent (mass basis). This implies that longer residence time may not necessarily produce desirable fuel products in terms of sulfur loss vs. heat value loss. The low fractional desulfurization is expected to be improved by increasing temperature and decreasing particle size. The objective of this investigation is to optimize the pyrolysis conditions to maximize desulfurization and minimize devolatilization.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

An attractive alternative of removing sulfur from stack gas cheaply and effectively is the production of a low cost, low sulfur, coal-derived solid fuel. The proposed novel coal feed system, which is currently under investigation at the University of Cincinnati, is designed to provide such kind of fuel. The sorbent utilization in this system could also be significantly higher than values found in FGD system because of the difference in reactions involved in the sulfur removal process. In addition, the system could be designed to make use of the heat available from the hot ash recycle system to partially pyrolyze the coal feedstock. This makes the system more attractive for practical applications.

BACKGROUND

1) Mild Pyrolysis of Coal

The basic concept behind the proposed novel coal feed system is to pyrolyze coal under mild pyrolysis conditions. Pyrolysis is the first step of any coal conversion process such as combustion, gasification and liquifaction. Different pyrolysis conditions may result in completely different fuel products with different physical form, chemical construction and composition. Conventional gasification and liquifaction processes are generally designed to produce single marketable fuel products, either gas or liquid. These processes require relatively severe pyrolysis conditions such as high temperature and high pressure, complicated operation procedures, complex and expensive equipment and facilities.

Mild pyrolysis of coal is much easier to be performed and has been attracting increasing interest. Available literature shows that most mild pyrolysis studies were conducted with emphasis on the yield and composition of the devolatilization products. Relatively little information has been given in the literature on pyrolysis with emphasis on desulfurization. The Morgantown Energy Technology Center (Morgantown, WV) conducted studies on the production of liquid fuel via low temperature devolatilization of coal^[1]. The produced liquid fuel was reported to be of high quality (low sulfur, high H/C) yet may not be directly used in conventional boilers.

Conditions of mild pyrolysis may also be varied in large ranges. Heating rate, peak temperature, resident time and reactor type etc. are major factors that affect the yield and composition of pyrolysis products. Volatile products from slow pyrolysis of coal have been analyzed by North Carolina State University at Raleigh^[2]. Howard^[3] reviewed the fundamental aspects of rapid coal devolatilization by examining the effects of time, temperature, particle size, gaseous atmosphere, and pressure on product yields. Innumerable studies have been reported in the literature on coal devolatilization using either fix-bed or fluidized-bed or batch reactors. However, no information is available in the literature on coal pyrolysis studies utilizing auger type reactors with emphasis on maximizing the ratio of desulfurization to devolatilization. Westinghouse Electric Corporation^[4] reported their investigations on the production of mix of gaseous, liquid and solid fuel products through less severe pyrolysis processes. In their experiment conducted on Wyoming subbituminous coal, the concept of gas composition/temperature sequencing was employed. As reported, at 600 °C with

the presence of steam and nitrogen, the total sulfur release was about 75 percent and the total carbon release was as high as 43 percent, representing a high degree of devolatilization.

The study presented here was conducted at relatively low temperatures (350-450 °C) with an aim at optimizing operation conditions to maximize desulfurization and minimize devolatilization.

2) Sorbent Utilization

During pyrolysis of coal, the sulfur species in the coal matrix evolve out in the form of H_2S instead of SO_2 . The formation of reduced sulfur compound is the key point to the enhancement of sorbent utilization.

Presently, lime is one of the most commonly used sorbents for the removal of sulfur from coal conversion processes. It is well understood that during calcination of $CaCO_3$, the decomposition to CaO will not generally result in a change in particle dimensions. The molar volume of CaO compared to $CaCO_3$ (16.64 cm³/mole vs. 35.71 cm³/mole) indicates that 53 percent of the original particle volume plus whatever percentage porosity that was available in the parent $CaCO_3$ will be available for reaction products. The molar volume of calcium sulfate ($CaSO_4$) is such (45.9 cm³/mole) that complete conversion of the sorbent with SO_2 is essentially impossible due to blockage of intergrain void space within the particle. This explains the poor sorbent utilization in dry scrubbing process as it is frequently reported in the literature. However, complete conversion of CaO to calcium sulfide (CaS) requires a molar volume of 27.6 cm³/mole which would not result in significant changes in the intergrain boundaries of the calcined particle. The formation of CaS occurs when sorbent CaO reacts with the reduced forms of sulfur (e.g. H_2S) formed from coal pyrolysis.

Studies on the kinetics of the reaction of CaO with H_2S and COS have shown that the reaction may proceed essentially to completion in reasonable times at the temperature of interest. The reaction rate of either H_2S or COS is significantly higher than the rate of CaO with SO_2 at same temperature^[5].

In view of the above, the proposed coal feed system may yield significantly higher sulfur retention levels at the same sorbent consumption rate than the traditional method of dispersing the sorbent directly into the combustor.

EXPERIMENTAL SYSTEM DESCRIPTION

A diagram of the experimental auger feed system is shown in Figure 1. The system consists basically of four sections: 1) the feed unit; 2) the temperature control unit; 3) sampling unit and 4) the analysis unit. In considering the high corrosiveness of H_2S and other evolved gases, all parts that may come into contact with these gases such as the feed tube, auger, sampling tubing and fittings, quenching tank, etc., are made of 316 stainless steel.

The feed unit consists of an insulated stainless steel tube one (1) inch

in I.D., one and quarter (1 1/4) inches in O.D., and three (3) feet in length, an stainless steel auger which is driven by a .75 HP variable speed D.C. motor, a feeding hopper and a quenching tank. By adjusting the speed of driving motor, the residence time can be easily varied from 1 minutes to 60 minutes. When the hot feedstock (char products) are conveyed to the quenching tank, the reaction immediately stops. The residual sulfur content in the char is then analyzed using LECO sulfur analyzer.

Seven (7) band type electrical heaters each of 625 watts are controlled by five (5) temperature controllers to provide a uniform temperature distribution along the feed tube. Both band and prob type thermocouples are employed to sense the surface and inner tube "top" temperatures. The temperature control unit is not shown in the diagram figure.

A sampling port is positioned at the downstream end of the feed tube. The quarter-inch sampling tubing is heated and insulated to prevent the volatiles from condensing inside the tubing. The condensable species in the hot gas stream are condensed by three condensers connected in series. Flasks that catch the condensed tar and liquid can be easily detached from the condensers enabling the subsequent analysis of the condensed species. Cooled gases are then entrained to the analyzers for H₂S and H/C analysis.

Initially, based upon the attempt of monitor the H₂S concentration profile inside the feed tube, five sampling ports were distributed along the feed tube. Because of the small opening of these ports, the connected tubing (1/8 ") were easily blocked by either coal particles or condensed matter, prohibiting effective utilization of these sampling scheme. Redesign of these ports may solve this problem and provide an effective way to monitor the H₂S concentration. But that is beyond of the budget and time schedule.

RESULTS AND DISCUSSION

The results of a limited number of tests on an Ohio No. 8 coal are given in Table 1. The data in Table 1 represents results for pyrolysis conditions of 375 °C. The values of the total mass of coal tsted (M_i) and recovered (M_f) as well as percent sulfur in the product char are given for the various coal residence times. Also given in Table 1 is the value of te product density the percent desulfurization obtained and the percentage of coal devolatilization. The percent desulfurizatoion is based on the ratio of the total mass of sulfur lost from the coal to the total mass of sulfur originally in the coal. The percent coal devolatilization is based on total mass lost to the original mass of the coal. Both the percent desulfurization and percent devolatilization show trendswith respect to coal residence time.

The trends are shown in Figure 2. The data for fractional devolatilization was fit with a linear form as follows:

$$1 - M_f/M_i = 1.152 \times 10^{-3} t$$

Where t -- residence time, min.

Also, the data for fractional desulfurization was fit with an

exponentially decay function of the following form:

$$\text{DeS} = \text{DeS}_\infty [1 - \exp(-0.08t)]$$

Where DeS_∞ -- maximum desulfurization, percent.

DeS_∞ was found to be 0.332 through linear regression.

The desulfurization data in Figure 2 indicates that there is a upper limit to sulfur devolatilization for this type coal at this temperature. That upper limit appear to be similar to the organic sulfur content for this coal. However, it is not known at this time if the sulfur loss can be solely attributed to organic sulfur loss, or from some other mechanism such as the decomposition of ferric sulfur (pyrite) to ferrous sulfide (troilite) in the inorganic sulfur fraction.

Also given in Figure 2 is the fraction (mass basis) of sulfur in the devolatilized material. This fraction is well over 50 percent during the initial stage of pyrolysis indicating that sulfur species are devolatilized first. This implies that high concentrations of reduced forms of sulfur (H_2S , COS , etc.) will be available for subsequent scrubbing by an appropriate sorbent such as lime or limestone.

It is of interest to note that if pyrolysis is allowed to continue, the data indicates that only non-sulfur containing species would be devolatilized after about 50 minutes of residence time. This is illustrated in Figure 3 where the fraction of sulfur in the produced char is predicted for extended residence time based on extrapolation of the empirical mathematical expression for both desulfurization and devolatilization. For a practical system, it would not be beneficial to pyrolyze beyond this lower limit, as shown in Figure 3.

CONCLUSION AND FUTURE PLAN

A study is underway to research the possibility of pyrolyzing coal to release sulfur which may subsequently be removed through reaction with lime or limestone. The most prevalent form of devolatilized sulfur is H_2S which has been shown to be very reactive with lime.

Initial results have been promising and have indicated that over 30 percent of the sulfur in an Ohio No. 8 coal may be removed by mild pyrolysis at 375°C . Total devolatilization of the coal was seen to be less than 6%. Additional work is underway to study the effect of increasing pyrolysis temperature and varying coal particle size.

The mechanical design of a double-screw coal feeder has been nearly completed. Figure 4 shows a preliminary design work.

1. Khan, M.R., Production of a High-Quality Liquid Fuel from Coal by Mild Pyrolysis of Coal-Lime Mixtures, DOE/METC--96/4060, U.S. Department of Energy, Office of Fossil Fuel, Morgantown Energy Technology Center, Morgantown, march 1986.

2. R.M. Felder and F.D. Gilman, Analysis of Volatile Products from The Slow Pyrolysis of Coal, EPA-600 7-84-082, U.S. Environmental Protection Agency, Research Triangle Park, August 1984.
3. Howard, J. In Chemistry of Coal Utilization. 2nd Supplementary Vol., edited by Martin A. Elliott (1981), National Research Council, Wiley-Interscience Publication.
4. M.A. Alvin, D.H. Archer and M.M. Ahmed, Pyrolysis of Coal for production of Low-Sulfur Fuel, AP-5005 Research Project 2051-2, Final Report, Westinghouse Electric Corporation, Pittsburgh, Pennsylvania, 1987
5. R.H. Borgwardt, et al., "EPA Experimental Studies of the Mechanisms of Sulfur Capture by Limestone", in the Proceedings: Joint Symposium on Dry SO₂ and Simultaneous SO₂/NO_x Control Technologies, Vol. 1. Fundamental Research and Process Development, NTIS No. PB85-232353

TABLE 1
PYROLYSIS DATA FOR OHIO #8 COAL

TIME	M(i)	M(f)	%DeV	%S	Rho	%DeS
0	----	----	0.00	3.18*	1.376*	0.00
10	1046	1029	0.02	2.54	1.377	0.21
25	990	962	0.03	2.40	1.347	0.27
40	1235	1179	0.05	2.30	1.334	0.31

* - RAW COAL PROPERTIES;

%DeS = $(Mi \cdot \%Si - Mf \cdot \%Sf) / Mi \cdot \%Si$

%DeV = $(Mi - Mf) / Mi$

ALL DATA AT 375 C

Diagram of Experimental Set-up

Figure 1

OHIO #8 COAL, 375 C

DEVOLATILIZATION & DESULFURIZATION

FIGURE 2.

%SULFUR IN PRODUCT CHAR

OHIO #8 COAL, 375 C

FIGURE 3.

Figure 4. Double-Screw Coal Feeder

**DATE
FILMED**

8 / 18 / 92