REVIEWS OF COMPUTING TECHNOLOGY: AN OVERVIEW OF NEURAL NETWORKS(U)

by

A. E. Rainsford

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

A technical report being deposited at OSTI

The information contained in this paper was developed during the course of work done under Contract No. DE-AC09-89SR18035 with the U.S. Department of Energy. By acceptance of this paper the publisher and/or recipient acknowledges the U.S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Reviews of Computing Technology:

An Overview of Neural Networks (U)

by A. E. Rainsford

WSRC-IM-90-83-4

February 15, 1992

Authorized Derivative Classifier

G. F. Hayhoe

Westinghouse Savannah River Company
P. O. Box 616
Aiken, SC 29802

100-104351
JUL 1962

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by the trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Table of Contents

1	Introduction	1
2	Historical Background	3
	What are Neural Networks?	4
	Perceptrons	7
	The XOR problem	8
	Kolmogorov's Theorem	9
	Relation to Serial AI	9
	Relation to Connectionism	10
	Relation to Fuzzy Logic	11
3	Neural Network Models	13
	Training	14
	Stability and Convergence	14
	Development of the Models	15
	Perceptron Training	15
	Back-propagation	17
	Hebbian Learning	18
	Recurrent Nets, LTM, and STM	19
	ART I, II, and III	20
	Hopfield Nets	22

Boltzman Machine and Simulated Annealing	23
Kohonen Nets	23
Temporal Nets	23
4 Applications	25
Vision	25
Process Control	26
Robotics	27
Specific Applications	29
Uhrig's DOE Work	29
DOE Projects	29
Industry Usage	30
Practical Use Considerations	32
Software Resources	33
Potential SRS Applications	33
5 Hardware	35
Workstations	35
Parallel Processing	35
Integrated Circuits	36
PN Junctions	37
6 Optical Computing	39
7 Summary/Future	43
8 References	45

1 Introduction

Wide categories of computation problems have not been adequately solved yet, even though some of them have been researched for decades. Frequently, the solution has been thought to reside in more computing power, only to discover that the problem continues to evade ever faster machines. The most prominent example is artificial intelligence, but also included are machine vision, speech recognition, machine understanding, robotic control, language translation, and handwriting recognition. This class of problems share many common characteristics:

- selection of a best pattern from a large number of stored patterns
- learning and adaptability
- good generalization when presented with incomplete data
- quick response or recognition times
- sensitivity to contexts
- parallelism and non-procedural function
- ability of people to perform many of these functions virtually without effort

Existing computers and computational methods seem to reach a point of diminishing returns when applied to such problems. Although research is still proceeding, it appears that quick progress in each of these areas was made initially through procedural algorithms but slowed down as subtleties in the problem increased difficulty by orders of magnitude. Many researchers no longer believe that faster machines and more clever algorithms are the answer. Others have long contended that more appropriate methods of computation could be discovered through biological research into the function of nerve cells and interconnected groups of neurons. This research is now yielding a rich understanding of a highly parallel computing method called neural networks.

Neural networks provide some solid computational answers and expeditious solutions to these difficult problems, although the technology is far from mature. In the process of discovery, many other problems are found to have bet-

ter solutions through neural networking, such as mixing batches of industrial chemicals, predicting stock market values, rating loan risk, making medical diagnoses, and analyzing or validating data. In many cases, businesses are using these improved techniques to competitive advantage and are frequently keeping successful applications confidential.

Neural networks will likely become embedded in many mundane applications as integrated circuits directly embody specific functions, such as voice recognition in cellular phones and adaptable home thermostats to save on energy costs. Workstations may have voice recognition cards which will adapt to a user's voice for reliable continuous-speech control using neural net techniques. A number of prominent neural network leaders feel that within 10 to 20 years, a practical, autonomous household robot will not only be possible, but also economical enough for average consumers.

Assessment of practical applications of neural network technology requires employees able to identify potential uses. This review will hopefully assist in that endeavor.

2 Historical Background

Neural network is a relatively new buzzword in computing technology, and yet its roots go back to the beginning of digital computation in the late 1940s into the 1960s. As its name implies, it is based on a biologically-inspired model of computing. The mysteries of how biological neurons compute are now being revealed at an increasing rate, although the basic model of the function of an individual neuron was laid out around 1940. Frank Rosenblatt of MIT was the field's most visible popularizer throughout the early 1960s, with his "Perceptron" pattern recognition machine.

In 1968, several MIT colleagues wrote the book *Perceptrons* to explore the limitations of perceptrons, which galvanized a movement against research funding in exploring neural computing. Only in 1984, after California physicist John J. Hopfield re-popularized the concept of neural networks through his success in solving the "traveling salesman" problem, did funding again become generally available. In the interim, biologists continued making discoveries to unravel biological neural networks, and this work is continuing today. A few "pure neural net" researchers also continued work, frequently without support. Their efforts created a new basis from which research could begin. Of these, Stephen Grossberg of Boston University made tremendous strides, stressing mathematical rigor in his development of biologically-based models.

Since 1984, neural nets have regained respectability and funding. Neural networks are actually a broad research area today, not a single technology ready for purchase. Even at this relatively early stage of development, neural networks have been very successful in solving several applications. Popular success can breed disenchantment, however; several researchers feel that popular attention has forced them to work prematurely on applications, before the basic research had attained a comprehensive footing. Following previous patterns of introduction of technological innovations, disenchantment with neural nets again seems likely. But the issue of technology impact is not popularity, but rather futures and implementation. One potential barrier to deployment may be culture: neural network application requires an entirely separate conceptual outlook compared with conventional data processing. This review evaluates neural nets from several perspectives: historical, biological, research, philosophical, applications, and especially, futures.

The purpose of this review is not to provide a tutorial on neural network mathematical models. Several books published within the last year do so rather well, although a definitive text has yet to be written. Rather, this review presents a cursory overview of the historical and biological origins of neural nets, followed by a brief explanation of basic terms of biology, and then of neural nets. A conceptual overview of some of the more popular models is then followed by explanations of several biologically based models of psychological phenomena which have implications for the historically difficult problems of cognition. MAVIN, an MIT research robot with control embodied solely in networks of neural nets, is described. Hardware on which to implement nets is broken into several major categories, discussed separately, with some emphasis on future developmental possibilities. Optical computing is described for the close congruence with, and potential applications for, neural networks.

To appreciate the significance of neural nets, one must have some understanding of "the big picture," a global perspective of what this technology is, and its relationship to other computing technologies.

But what are neural networks? And how will they fit into tomorrow's applications—or today's?

What are Neural Networks?

Neural networks are in some ways all that computers are not. They are not sequential and are not programmed. They learn by observation, not by being programmed. They could be thought of as being "intuitive," although the more technical terms "collective emergent" or "non-local" are a more frequent description. They are the ultimate in parallel computing as each of many elements performs a very simple non-varying function. They promise to provide capabilities which computers haven't been able to achieve: speech recognition, pattern recognition, visual scene analysis, multi-dimensional control, and many others.

As the name implies, the neural network concept has its roots in the modeling of biologically-based brains ("wetware"). By 1940, several properties of the most basic unit of the brain, a single cell known as a neuron, were known. Figure 1 (see the next page) shows a neuron, with significant parts labeled.

Figure 1: Biological neuron

Although there are many different types of neurons, most seem to conform to the same model of operation. The *axon*, or long output filament, conducts nerve pulses in one direction only, away from the cell body, to the inputs, or *dendrites*, of other nerve cells, or possibly into a muscle cell. The dendrites of the neuron form a *dendritic tree*, so called because it looks like a tree with many branches, that collects many input signals, funneling them in one direction towards the cell body. The points at which this dendritic tree contacts other neurons are called *synapses*, which could be thought of as leaves on a tree. The dendritic tree of a cortical neuron is thought to contain as many as 100,000 synapses. These synapses perform a very important function. Synapses can vary how well they conduct a signal from one nerve's output signal to the dendritic input, as a function of learning. The mechanism by which synapses vary their connection strengths is not yet well understood. The communication between nerve cells at the synapse is accomplished by means of specialized chemicals called *neurotransmitters*. A synapse can either make transmission in the dendritic tree more likely to occur (in the case of an exci-

tatory synapse), or make the transmission less likely (in the case of an *inhibitory* synapse). Neurons act by creating an electrical charge inside the cell which is triggered to rapidly *depolarize*, or *fire*, based on the collective condition of all inputs and synapses in the dendritic tree. Neurons will discharge in 0.001 of a second, and recharge themselves in 0.1 to 0.01 second.

Nerve signals travel down the axon output (which can be several feet long for neurons controlling muscles) at a rate of 100 meters/sec. or less. By contrast, signals in electrical circuits travel near the speed of light, or 300,000,000 meters/sec. How is it that we can recognize a familiar face almost instantly, when statistical pattern recognition cannot practically accomplish the task in any amount of time, although the signals are traveling three million times faster? Clearly this example demonstrates that classical computing methods are inappropriate for wide categories of tasks.

We have defined the "classical" model of a neuron. There are many variations of this model found in biology. Retinal cells permit eyes to perceive light, and have no dendrites; olfactory cells don't exactly fire, and learning may involve mechanisms other than changes in the synapses. In 1943, a mathematical model of this classical neuron was developed, as illustrated in Figure 2:

Figure 2: Mathematical model of a neuron

Synaptic connection strengths are called *weights* (w_i), which are multiplied by input signals $x(i)$. The weights typically can be between 0 and 1 for excitatory connections, or between -1 and 1 for both excitatory and inhibitory connections. All signal strengths are added together. A *threshold* function is then applied to obtain the value of the output y . This threshold function is key in making neural networks work. Any valid *non-linear* function will do (some are shown in Figure 3 on the next page):

Figure 3: Sample valid non-linear functions

The function performed by this element can be written mathematically as:

$$y = f\left(\sum_{i=1}^n w_i x_i\right)$$

Perceptrons

From the beginning of brain research, two essential functions were obvious: pattern recognition and control. Of these, pattern recognition has received more attention. Initial development of what is now known as neural networks did not really begin until about 1950 because of the lack of background research and because of unavailability of any hardware or technique with which to embody models. Development was on equal footing with computing—nonexistent—because there were no computers until about this time, either. During the 1950s, Frank Rosenblatt of MIT developed the first neural network based on the McCulloch-Pitts model. This machine, called the Perceptron, was made from crude (by today's standards) analog circuitry, and was a pattern classifier or recognizer. It attempted to recognize visual patterns and garnered much popular attention.

A Perceptron *neural network* is a *network* of *neurons*, as is shown in Figure 4 (see the next page):

Figure 4: Perceptron neural network

The vertical stacks of processing elements in this figure represent a *layer*. All processing elements of a layer get inputs from the same set of source elements, and deliver to the same set of target elements, with each element functioning independently of all others. Sometimes a layer is considered to be a 2-dimensional array of processing elements. Usually the first layer is considered as a fan-out of the input terminals—not really a true layer. A neural net may have zero, one, or more *hidden layers*. A hidden layer is so named because it cannot be logically observed from either the input or output signals. The perceptron is an example of a *feed-forward* network; that is, no output signal is fed back into the layer from which it is generated, or to any earlier layer. Many important neural networks have extensive feedback and are said to be *recurrent*.

The XOR problem

The Perceptron also had some limitations, which were clearly explained in the book *Perceptrons* by Marvin Minsky and Seymour Papert, both also of MIT. For example, no one had any good ideas how to set the weights on the hidden layers. Chief among the limitations was the “Exclusive-OR” problem. The output from a single layer perceptron could only distinguish between values of the input values which were linearly separable; that is, they could not distinguish a pattern that occurred in disconnected regions. *Perceptrons* also

said that "... our intuitive judgment that the extension [to multilayer systems] is sterile" (p. 232), and generally expressed sharply negative opinions about perceptrons. This condemnation by prestigious authors galvanized the research community against funding this type of research for nearly 15 years. The pessimism of Minsky and Papert may have been accentuated by their conviction about the validity of the serial Artificial Intelligence (AI) paradigm. During the 1960s, apparent progress in the model of intelligence embodied in the LISP programming language, which espoused logical, symbolic processing, had captivated many researchers, including Minsky and Papert.

Kolmogorov's Theorem

Condemnation was premature, however. Methods of training multiple layers of networks have been discovered. And some mathematical results, known as the Kolmogorov theorem, imply that *any* discrimination task can be accomplished in at most three layers. This theorem is not a cookbook formula for describing how to create a neural network to recognize something; it only says that it is mathematically possible to discriminate or recognize any pattern in no more than three layers. Cybenko of Tufts University formally extended this theorem to neural networks in 1988 to demonstrate that only one hidden layer is sufficient.

Relation to Serial AI

Work on Artificial intelligence (AI) began about the time John McCarthy of MIT invented the LISP programming language to express logical, symbolic propositions in the early 1960s. Initial successes in AI convinced many researchers that intelligence works in a serial and symbolic fashion. AI still has many ardent supporters, although the field has not experienced any significant breakthroughs in many years. AI models intelligent behavior by sequentially deciding truth propositions of symbols—variables which stand for real-life objects or concepts. Its strength is that every proposition is decided in a binary manner, which can be modeled very effectively on digital computers. Complex logic, which involves context or propositions beyond yes-or-no, can be built up of many yes-or-no symbolic propositions. The AI paradigm permits development of a context built up over time, and the next expected input symbol is usually one of a very limited set, over which a truth proposition can be rapidly computed.

The largest experiment today in the conventional AI paradigm is the ongoing CYC project, headed by Douglas Lenat at the MCC consortium. This ten-year project, now half completed, has as its goal the creation of an AI machine with "every-day common sense," able to read and interpret a newspaper article the way a person would. If CYC reaches its goal, research into other parameters, such as response time, storage space, context change times, etc.

will be warranted. It remains to be seen how much like human intelligence CYC will perform.

Expert systems (ES) can be described as the most successful offspring of AI. Expert systems are being embedded within many commercial applications and perform specific subfunctions, such as natural language parsing.

The differentiating factors between AI and ES appear to be that ES are not experimental and limit the range of attempted intelligence to table-driven rule bases.

Neural nets and AI are in many ways the opposites of each other, and yet neither creates logic not reachable by the other. Ultimately, it will probably be a matter of engineering to determine which of the two approaches to utilize for a particular application. Most neural nets in use today are simulations of very small nets done in a conventional, serial, computer. And McCulloch and Pitts showed before 1950 that their limited neuron model could be configured to execute *any* Turing machine, which implies that neural networks can be arranged, at least mathematically, to perform any digital and serial logical function. But this observation of mathematical potentialities obscures the strength of neural nets, as compared with more conventional techniques. What neural nets can do well is global optimization executed in parallel, or simultaneous and massively parallel pattern matching with generalization. These are functions which are computationally infeasible to do to any practical extent using conventional serial computing methods because of the required execution time.

Relation to Connectionism

Connectionism is a creation of the Parallel Distributed Processing (PDP) group headed by Rumelhart and McClelland about ten years ago. Connectionism is a "blend" of AI and neural networks. Whereas the model for neural networks is the physical nerves, connectionism attempts to model the brain at a functional level. Connectionism recognizes massive parallelism by modeling networks of active computing elements. Semantic tokens are represented by single network units or by patterns of activity in a large population of units. The connectionist form of processing can embody powerful semantic net representations. Connectionism captures some features of neural nets: ability to generalize; simultaneous presentation of multiple constraints or contexts in problem-solving, an expansion of which creates associative memory; and highly parallel processing. Connectionism also shares, to some extent, the *emergent* property of neural networks: that rules or entities appear during development or training rather than being explicit symbols, if the implementation permits self-organization. Connectionism can be thought of as the application of neural networks to symbolic processing but in its immaturity is far from being an accepted practice for practical applications.

Relation to Fuzzy Logic

"Fuzzy logic" exists to soften the hard yes-or-no rules of logical decision-making inherent in symbolic logic systems, such as AI or expert systems. Effectively, the variables of the logic system assume a defined "probability density function" rather than being yes-or-no, but still perform according to the predefined rules programmed in. In contrast, neural networks simply observe the data they are presented with, training themselves to perform according to some criteria. It makes little difference whether one is attempting to create an accurate model for forecasting or training for action, since these functions are largely equivalent. For neural networks, the "fuzziness" of the variables is only that inherent in the raw data. Relationships previously unsuspected within data elements of a system have been uncovered on numerous occasions by neural networks, such as genetic patterns or underwater objects. This is the emergent property alluded to in the previous paragraph. Ability to analyze input data, or to incorporate the new data into previous history is lacking from fuzzy logic or expert systems, without exceptional *a priori* explicit programming. Fuzzy logic is—and will be—a viable tool for many engineered applications but is distinct from neural networks.

This page left intentionally blank.

3 Neural Network Models

The technology of neural networks is possible through the development of a limited number of specific configurations of idealized mathematical neurons that have defined properties and have been demonstrated to solve particular classes of problems. These *neural network models* define the current state of the art and permit meaningful discussions. Groups of models may share some common features, but no one characteristic is applicable to all models. This section explains the significance of some of the more common features, then describes differentiating characteristics of the more widely referenced models. Model, origin, and best application are noted, relation to other models is explained, and practical advice on use is offered.

The rudimentary Perceptron neural net developed in section 2 exhibits characteristics common to most other models. Each model neuron, or processing element, functions independently of all others. Each element in a layer receives input from many elements of the previous layer. The input contribution from any one element in a previous layer to a single element of the next layer becomes increasingly small as the number of elements becomes very large. This fact, along with independence of operation of each element, implies that operation of a large neural net would not be measurably affected should one element fail. Similarly, the memory or "programming" is embodied in the collective state of all of the synapses throughout the entire network; no single fact is stored at any one synapse. This characteristic means memory is distributed over the network such that loss of a portion will not affect performance. This *fault-tolerant* characteristic can only be physically true if hardware conforms to the logical model. Most neural nets available today are actually software simulations, but this is expected to change. Distributed computation and storage is also responsible for *generalization*; when presented with an input not previously programmed, the net will select the output appropriate for the pattern that is the closest match; the net will "fill in the blanks" or take a guess. *Associative memory* is also an outfall of distributed storage, in which an entire stored dataset is recalled when queried by only a portion of the input data.

Training

Neural nets would not exist without training. Difficulty of training caused many early researchers to go elsewhere. Bernard Widrow gave up on neural nets in 1958, and turned his talents to making digital signal processors. He created the ADALINE and MADALINE digital signal processors, without which long-distance telephone calls would have ringing echoes. The ADALINE is essentially an adaptive single neuron digital signal processor, most significant for its training algorithm.

Training neural nets typically takes far more time than using one in production. Algorithms for training many types of neural nets essentially just "guess" at small changes in synaptic weights and hence require many thousands of training cycles, although generalizations are difficult. For example, Hopfield nets aren't really trained at all; and the ART nets are trained in just one presentation of input. Learning has been shown mathematically to be a difficult problem, especially in the case of unsupervised learning.

In *supervised* learning, the neural net, functioning as an input-output device, is presented with input, with the desired output known. The difference between the net output and the desired output is then used to adjust the synaptic weights. In *unsupervised* learning, the net must be able to group input and output classes into associated categories without any external guidance.

There are many training algorithms, usually associated with a particular neural net model or researcher. We will not go into any explanations now, but some include coincidence learning, of which Hebb learning is an instance; performance learning, of which Widrow/Adaline learning is an example; competitive learning; and reinforcement learning.

Stability and Convergence

During the 1960s, mathematical properties of large numbers of separately functioning processing elements were thought by many to be intractable. Think of it: many independent processing elements with non-linear outputs, each with many variable and adjustable inputs, perhaps several layers of such, with feedback to previous layers. Advances in electronics had been fueled for a half century on the well-developed linear math theory; non-linear math just wasn't accommodating. One of Grossberg's many contributions is that he was able to demonstrate that if a neural network model conformed with a general model (and most do conform with Grossberg's model), if some mathematical conditions were met, then the net could be proven to converge to a stable solution. A visual analogy of this method of solution is that for some given (frozen) set of synaptic weights and/or inputs, the state space of

the neural net can be envisioned as hilly terrain or a mountain range. The stable solution is found by starting from initial conditions, envisioning a ball rolling down the hillside, until it comes to rest in a valley. One continuing problem of this neural net solution—along with its progenitor, system identification of control engineering—is that the valley found is not assured to be the lowest valley. That is, the net may find a *local minimum*, but is not assured of finding a *global minimum*. For many classes of practical problems, finding a good solution—not the mathematically optimal solution—is all that is required.

Under some conditions, the ball representing the solution may ultimately end up rolling around the depression of the valley in a chaotic manner. The chaotic solution would remain a mathematical curiosity and an unwanted side effect, were it not for some recent work by Walter Freeman of the University of California and others suggesting that chaotic behavior underlies some function of higher recognition. For some time it has been generally accepted that visual features are processed independently in separate areas of the brain. For example, the color, texture, and outline of an object are processed in different visual cortex areas. How the features that correspond to a single object are identified and then represented to a higher level of cognition has remained a mystery. Chaotic dynamics could possibly assist in recognition by permitting simultaneous neuron response from separate areas. This line of research has just arisen in the last several years. Grossberg has just published a proposed explanation with modeled simulation, but much work yet needs to be done.

Development of the Models

Unfortunately, a neural network cannot be created based on what has been presented so far and be expected to work. Each of the generic models has been specifically crafted to work on a particular problem, with specific parameters and training methods, and practically, there is no specific “standard” for any of the models. In each instance of an application, one must re-create a standard model and then tune it. This represents an extreme case of non-standardization. Lack of any standardization may hurt the industry, but no relief will be found soon. Semiconductor chip implementations will probably have wider variance than software simulations.

Perceptron Training

Now let us see an example of the simplest neural network, the one-layer, two-unit Perceptron shown in Figure 5 (see the next page):

Figure 5: A simple neural network

The two x inputs represent a measure of two different features of a problem for which you wish to discriminate between two different states for each of the two outputs, y . What Minsky proved was that at best, each output of this simple net could only be determined if the inputs fell on one or the other side of a discriminant line. Figure 6 contains a representative drawing of the inputs:

Figure 6: Inputs to a simple neural network

This simplest net could be trained to recognize a distinct region or input condition corresponding to **A**, but in a one-layer implementation cannot discriminate a condition of **A OR B**.

This network can be trained as follows:

1. Initialize the weights to some random value in the middle of the operative range, say to 0.35 and 0.55 if our permitted range is between 0 and 1.
2. Present a training sample to the inputs x and calculate the output:

$$y_1 = f[w_1 x_1 + w_2 x_2]$$

3. Knowing that the desired output is some value we will call d , calculate the next value of the weights as being the old value for a particular input plus some of the error, $(d-y)$, times the input value for that weight:

$$w_1^{new} = w_1^{old} + a(d - y) x_1$$

where $a < 0.1$, to control the rate of change

4. Repeat the process many times, until you consistently achieve the performance desired.

Real-world training can become enormously more complex than this, but the training process is basically similar.

As a practical matter, training the net will require many iterations. A good approach to training involves grouping a large volume of real-world data into separate sets, called the *training sets* and *testing sets*, before training the net. Criteria are established in advance to determine how good the output results have to be before applying all of the testing set to the trained net. Perfection is seldom realized in practical usage. The purpose of designating training sets, testing sets, and criteria in advance is to avoid *overtraining*, whereby excessive training to one set of criteria results in loss of generalization or higher error rates when presented with unexperienced input.

Back-propagation

The Kolmogorov/Cybenko theorems say any discriminant function can be achieved with only one hidden layer of a multi-layer Perceptron, but doesn't say how. The *back-propagation algorithm* gives a method of training the weight units of the hidden layers. It was initially discovered by Paul Werbos and reported in his 1974 Ph.D. dissertation at Harvard, but remained obscure until popularized by the PDP group under Rumelhart in the mid 1980s. Back-prop creates a method of assigning credit to those units and weights most responsible for output error, using additional neurons for feedback. Back-prop solves the *Credit Assignment Problem* that was cited by Minsky as a major reason that neural network research would be fruitless. Back-prop is a major cause of the re-surgence of neural nets, and continues to be the work-

horse of the industry. Hundreds of very successful applications use back-prop. (Specifics of back-propagation are beyond the scope of this paper.)

Assuming that back-prop works, we can build a net that recognizes input and creates an output as follows in Figure 7:

Figure 7: Neural network utilizing a back-prop

The inputs could be a two-dimensional pattern, such as the set of English letters. The desired output is that only one output unit produces a large signal, indicating recognition of the presented letter.

Theoretically, this neural net should be able to recognize and classify almost anything. But it has several shortcomings. For one, back-prop training is extremely slow and involves many calculations. As a result, it is not reasonably adaptable to real-time changes in input.

Other enhancements to our simple net could include an output function which would guarantee that only one output neuron would be activated, while the rest are (nearly) zero. Another enhancement could be that the input signals could be "sharpened" if the essential features of our input set could be identified in advance. Both of these features can be created by additional layers of network that perform similar functions, both involving feedback within that one layer. Many models and names exist to model functions such as these. Our simple model does not yet use feedback, so successfully employed in all engineering disciplines.

Hebbian Learning

Sometimes we may want a neural net to do the opposite of what our simple model does. We want a net which will take the individual keys of a keyboard as input and produce a visual pattern for the output.

Grossberg calls this "spatial pattern learning" using an "outstar." We could create a model that looks like Figure 8:

Figure 8: Inputs to a simple neural network

We would train this net with *Hebbian learning*, which implements the *classical* conditioning as explained by Pavlov. Hebbian learning can be stated described as follows: To associate an input (the category *A* in the figure) with an output (the pattern *A*), increase the weights between only the active elements of the input and output. This is very simple conceptually, but has a few problems in practice. A more practical implementation is Grossberg's *neo-Hebbian* learning. An even better implementation, almost a perfect model of psychological learning, is the *Drive Reinforcement Theory (DRT)* created by Harry Klopf, which incorporates a time-convolution of stimulus and response. DRT has demonstrated the ability to learn a classical neural net demonstration, "broom-balancing," in one training sample.

Recurrent Nets, LTM, and STM

Now, what if we put these nets back-to-back, where the outputs of our first model are the inputs to the second model? We have a machine which can reproduce its input—pretty useless. But what if we now take the output of the combined net to be *some* of the input, together with the input to be recognized (see Figure 9 on the next page)?

Figure 9: A recurrent net

Assuming the outputs of the net to be zero initially, the input signal begins to select an intermediate neuron indicating recognition of a letter, which in turn reproduces the presented input, to selectively enhance the letter to be recognized. The recognized image would seem to resonate back and forth between the dual nets. The goal is better recognition of the input, and perhaps better selectivity based on more subtle features. This analogy is an enormous simplification of the math, dynamics, and possibility for problems, but does illustrate *feedback*, or a *recurrent* neural net.

The recurrent net now has memory that is an active function of the output or internal variables but which is not stored in any synaptic weights. This internal activation function is called *Short Term Memory* or *STM*, as opposed to the memory embodied in the synaptic weights, called *Long Term Memory* or *LTM*.

How associative memory works can now be better understood. If presented with just the lower half of the letter A, the internal recognition unit representing A may still respond a little more strongly than the other units, which would eventually lead to the complete recreation of the output pattern A.

ART I, II, and III

ART, Adaptive Resonance Theory, represents a class of models created by Grossberg that is somewhat similar to the analogy just developed. In the ART I model, inputs are restricted to being binary 0s or 1s, as are the outputs. The ART models have the ability to "automatically" create new output

categories from uncommitted or recycled processing elements, although the method seems artificial and biologically improbable. This feature could be extremely important, however, for it permits automatic "fine tuning" based on experience. For example, a machine discriminating "truck" from "car" needs to put more emphasis on particular features when presented with examples of small pick-up trucks and Caminos. One way of doing so is to create new separate categories around the area of transition. In practice, all of the ART models are quite complex, with each element of the two layers actually composed of six neurons, and with a complex time sequence of events.

ART II extends the concept to the case where the inputs can be analog variables. It is much more complex than ART I, and in practice just does not work very well.

ART III is an interesting case conceived by Gail Carpenter about two years ago. One problem with recurrent neural nets is that the feedback has a tendency to lock attention onto one solution, whereby only a very large change in input can move out of its state. Some schemes use the equivalent of a "master reset" to zero out all internal states, so that a new, unbiased, selection can be made. Obviously inelegant but biologically plausible. Frequently, a more desirable function would be to temporarily discard the currently selected output to evaluate whether other patterns which are close are actually a better fit.

From biology, it had long been known that a continuously excited nerve will temporarily exhaust its ability to produce chemical neurotransmitters at its output terminals. Carpenter carefully modeled this depletion in ART II to see how behavior was affected. Depletion caused the state space around the solution to become periodically disrupted, but the terrain of state space not near the current solution did not change. Effectively, this discovery means that attention will wander somewhat, and the currently selected output will be periodically re-evaluated with respect to similar things. The overall context, or continuity, of the state of memory is preserved. In our conceptual convergence model, the ball in the valley is "kicked" a little ways from the valley where it settled, rather than being dropped onto the mountain range at a new, random position. Because ART III is new, and since it requires more detailed math than most standard models, little research has yet been done. ART III could be a significant advance.

All ART models share three shortcomings:

1. The loss of one element of the second layer results in the loss of an entire category (the "grandmother cell" problem).
2. ART can't represent hierarchical information.
3. The number of stored categories is limited to the number of units in the second layer.

Hopfield Nets

Hopfield nets are recurrent nets of a slightly different type, as Figure 10 shows.

Figure 10: A Hopfield net

All outputs are fed back into the input field, but the output of an element is not fed back into that same element. The weights represent the constraints of the problem to be solved. No training is involved. The Hopfield net has been successfully used in problems with tight mathematical constraints, such as the "traveling salesman" problem, or an anti-ballistic missile defense targeting problem.

Hopfield played a major role in rejuvenating neural net research in 1984. His prominence as a physicist and his meticulous mathematical formulation carried as much weight as his concept of *energy* as a function of neural nets to be minimized. The analogy of a ball rolling down a terrain contains this energy concept. Grossberg claims that his earlier neural model and energy function is a mathematical superset of Hopfield's work, but Hopfield's contribution is undeniable.

Note that all outputs of the Hopfield net are fed around so that all units can receive input from them. This arrangement is called a *fully-connected* or *cross-bar* net. The number of weights and computations increases dramatically with the number of units, and the computation is also reiterative. Most problems that one would like to solve with these nets demand large numbers of units. Hence, the performance of this class of nets (which include the Brain-

State-in-a-Box and Bi-directional Associative Memory) is relatively low. This class will be of more value when they can be realized optically, as demonstrated by Nebil Farhat and Demetri Psaltis, or in integrated circuits.

Boltzman Machine and Simulated Annealing

The Boltzman Machine model is essentially a discrete time variation of the Hopfield network, using a concept of temperature to search the lowest point in energy space. *Simulated annealing* is a technique using this variable called temperature to randomly "shake" the terrain according to the math of statistical thermodynamics to ensure that the conceptual ball rolling downhill does not get stuck.

Kohonen Nets

Kohonen nets deserve special notice because they do work very well in practice, with relatively few mathematical operations, categorizing automatically in an unsupervised manner. Kohonen set out to model the biological phenomenon that spreads a learned feature space over a continuous area of physical cortex. An optimum equiprobable distribution of continuously-learned weight vectors produces a contiguous set of units. Frequently, a Kohonen layer will be used to help "clean up" data into categories before being applied to other neural nets.

Temporal Nets

Sometimes one may wish either to recognize a complex time sequence or execute a sequence of actions rather than analyzing a static set of data. Any of the associative memories we have already discussed can be given temporal properties by feeding output back as input, but the specifics of the math required can be demanding. An *avalanche* sequence output generator is a conceptual extension of the winner-take-all idea, whereby one unit is activated at a time in a learned sequence. The *recurrent back-prop* extends the back-prop algorithm through time through feedback, but with horrendous math. The *spatio-temporal* net can recognize patterns that occur over time.

This page left intentionally blank.

4 Applications

Vision

Practical machine recognition of pictures has long been a goal of researchers and developers. Experience has shown that functional decomposition of vision is appropriate, following biology. Biological neural nets decompose recognition into separate concurrent and sequential functions. The first function performed in the retina after reception of the light photon by the rod or cone cells enhances features important to survival. This function is called "early vision," and consists of compensation of the variation in light intensity, enhancing contrast across boundaries, and perhaps data reduction into line outline drawings.

After "early vision," the ability to detect and track motion is important, as is the ability to recognize objects. Surprisingly, biological brains seem to process these functions simultaneously, in parallel, in separate areas. Research into the requirements of weapon systems has indicated that a similar partition of the problem is most effective. (This may be more than coincidence, since a biological organism's most basic requirement is defense, and offense if a predator.)

Compensation throughout a layer of a neural net and feature enhancement are accomplished through a layer of elements that are strongly interconnected with each other. Such an interconnected layer performing a specific function is sometimes called a *field*. Biological evidence indicates that brain cortex is composed of sheets of layered fields stacked on top of each other, each performing some as yet unknown function.

A field can be set up to perform the "winner-take-all" function used for many nets, but a slight variant of this same field can be used to reduce a visual field of neurons to a "line drawing," a more compact set of features from which to apply a higher level of pattern recognition. "Hidden lines," which cause havoc in statistical pattern recognition or AI machine vision, can be automatically anticipated and filled in using a variation in field set-up. Properties of modelled fields of neurons can account for cognitive functions such as the "Kanisza triangle." In the Kanisza triangle, one can clearly see a trian-

gle where there is none; its existence is inferred from the background (see Figure 11).

Figure 11: The Kanisza triangle

These seem to be innate pattern recognition functions that are virtually impossible to program into a rule-based or procedural system. This massively parallel, constantly driving pattern-searching mechanism may underlie much of what is considered higher cognitive functions.

Process Control

Use of neural nets for process control has not been pursued nearly so vigorously as pattern recognition, presumably because conventional control engineering works well. Control is largely a solved engineering problem, whereas real-world pattern recognition remains essentially an intractable problem. Nonetheless, the neural network's potential for adaptive and hierarchical control is great. Many vendors of classical control systems have neural network development projects underway. A theory which will describe a neural net's ability to act as an anticipative control may soon be published, permitting both the controlled variable and all of its higher-order derivatives to be arbitrarily close to ideal.

Robotics

Intelligent robotic control has two main components: perception of the external world and activation of its effectors. Quite a bit is known about biological control systems, stemming from a vast background of research. Neural net models for action go back to the Cerebellar Model Articulation Controller (CMAC) of the early 1970s, based on a firm understanding of the function of the biological cerebellum. Grossberg and his numerous co-authors have created an extensive set of models, which both describe biological control function and can serve as a blueprint for robotic control. Grossberg claims to have deduced some specific internal brain functions based on his models, which led to his prediction of certain EEG waves which were later verified.

MAVIN is the most advanced robotic platform for neural net experimentation in the world today. MAVIN was created at MIT under Allen Waxman to test theories about integration of various neural network functions. Unlike any other robot, all of MAVIN's functions are computed by an interconnected network of specific-function neural nets. The schematic of Figure 12 (on the next page) shows the architecture.

Figure 12: MAVIN robot schematic

MAVIN carries on the mobile platform only that which is necessary; computers for the neural nets are rack-mounted Sun workstations and dedicated processors. Note that one network is called "emotion." Grossberg claims that intelligent behavior must be driven, or moderated, by some function which performs many of the same objectives as the "emotion" that humans relate to.

Robotic research is being attacked from a new, recently popularized angle. MIT's Rodney Brooks is building small, real-time robots based on "subsumption architecture." Subsumption architecture means that each low-level arm control function has certain innate behaviors. Only after a low-level control function has been learned is it allowed to be moderated, or orchestrated, by a higher-level layer. Subsumption architecture is patterned on biology. Not all motion is directed by the high levels of the brain: when you grab a hot frying pan, your arm instinctively retracts. Retraction is directly controlled by spinal chord ganglia as a survival reflex. Inhibition and voluntary movement occur only after higher level nerves direct the survival reflex to be overridden. These elements of reflex and hierarchical control are major considerations in neural network control models.

Specific Applications

Applications that have successfully used neural networks are numerous. This section lists either applications or projects that have utilized neural networks, successfully. No detailed description or evaluation is attempted in so short a space. In nearly all cases, the function performed by neural networks could be accomplished by some other method. The reason for using neural nets is that the application can be accomplished better and faster.

Uhrig's DOE Work

Dr. Robert Uhrig of the University of Tennessee is concluding a three year U.S. Department of Energy (DOE) contract to explore the use of neural networks in nuclear reactor applications. He has investigated such applications as:

- monitoring check valves to determine pending failure
- monitoring rotating machinery to determine pending bearing failure
- validation of sensor signals to determine out-of-specification sensors
- emulation of core reloading calculations to optimize output energy or produced materials
- detection of change of mode of nuclear reactor operation
- modeling plant thermodynamics to increase efficiency
- diagnostics in real-time of reactor faults (using the Watts-Barr simulator)

DOE Projects

Dr. Bruce Denby of FermiLab is adapting a neural net to recognize, in almost real-time, patterns of events occurring in high-energy particle detectors that signify a possibly interesting event. His net will be a trigger to other instrumentation equipment which will then capture detailed data.

Robert Farber and Alan Lapedes at Los Alamos used a neural net to identify segments of DNA that are biologically active. Their net uncovered a previously unknown correlation that people and the previous statistical techniques had overlooked. Most of the National Laboratories have undertaken projects utilizing neural nets for such diverse functions as spectral analysis of

spectroscopic data, intrusion detection, modelling biological populations, and many others.

Industry Usage

Many successful industry applications of neural nets are embedded and hence tend to become invisible. For example, all design win-ins in the last two years for handwriting recognition uses neural networking technology or concepts. This includes the pen-based, hand-held computers which are becoming popular now.

A representative list of other industry applications is:

- truck backer-upper for tractor-semi-trailers
- apple sorting
- engine diagnostics
- speech recognition
- text to speech conversion
- diagnosis of electronic equipment
- flight control compensation
- simulation of flight maneuvers
- articulated robotic arm control
- chemical process control
- chemical compound prediction
- inspection of labels on canned product lines
- image compression and data compression
- targeting of incoming missiles in an SDI program
- fingerprint recognition
- medical field applications
 - sonogram diagnosis
 - radiographic diagnosis
 - cell type identification
 - EKG noise filtering
 - diagnosis of diseases

- modeling olfactory systems
- defense applications
 - radar classification
 - automatic target recognition
 - tank tracking
 - pulse radar detection
 - multi-sensor fusion
 - sonar pattern recognition
 - weapons aiming and steering
 - vision systems
- investments/market prediction
 - stocks
 - bonds
 - interest rates
 - bankruptcies
 - loan underwriting
 - mortgage approvals
- insurance rating
 - evaluating risk
 - predicting pay-out

These applications demonstrate the types of computationally difficult problems to which neural networks can be applied. This list is not complete, of course, nor does it indicate the extent to which the neural nets were used in the applications. In most cases, the neural net was used for a well-defined, specific function within the application. Most of these success stories contain some anecdote as to why the problem was impossible, or at least improbably difficult, without neural nets.

Practical Use Considerations

One cannot apply neural nets to an application with the hope that the burden of knowing that application will be eliminated. But neural nets can be successfully employed in domains where only incomplete knowledge is currently available. For example, several developers have reported that a representative time to develop an application using neural nets to perform functions like expert systems is one tenth of what it would be for a human expert to encode his or her knowledge. Frequently, the human expert does not know the rules, but rather has a "feel" for the answer. Neural nets can sometimes model that behavior without having rules to explain it.

Another potentially successful application is data analysis. Neural networks are excellent at data analysis, frequently uncovering correlations not seen before. The financial community is finding that neural nets are the best method currently known for analyzing the volumes of existing data with interrelated variables. Neural nets excel in applications where a great many training examples are known, where the problem is basically one of pattern recognition, and where not all of the rules are explicit.

In nearly all cases, neural nets are one of a suite of tools applied to the problem, not the total solution. Each part of a complex problem is best solved by a technique which works best on that part.

Often, the neural net part of a solution involves a cascade of neural nets, whereby the output of one neural net model feeds into the input of another neural net model.

Several neural net models have a "winner-take-all" structure, whereby one node assumes ascendancy over all other nodes. As a simple model of a small net, this structure works well. However, as the number of nodes expands, the necessity of conforming to a closer biological analog of distributed representation is necessary to avoid the "grandmother cell" problem, whereby loss of a single processing element or neuron will result in the loss of an entire category of learned objects. When the winner-take-all function is applied to only a local neighborhood subset of the entire network layer, then distributed pattern representation will occur. This problem has received little attention because of inadequate tools.

Most of the existing training algorithms have not yet proven they can be extended over large nets. In fact, the Perceptron/back-prop algorithm will not converge over a large number of processing elements.

Because the back-prop algorithm assigns credit of incorrect answers backward based on an *estimated* assignment error, back-prop should not be used

for more than a three-layer net. Experience also indicates that additional layers are of little additional benefit.

Software Resources

Several programs from which one can construct neural network application are available commercially. The following are the most prominent of those products.

- **NeuralWorks** by NeuralWare is the most complete and most complex package for developing real applications for the PC.
- **Explorer Net 2000** by HNC runs only under Windows 3.0 on the PC, and is good for training.
- **Brainmaker** from California Scientific uses only the back-propagation algorithm, but can optionally download computed weight-sets onto a plug-in hardware board that uses the Intel neural chip set.
- **MacBrain** is a simple teaching tool available for the Macintosh only.
- **Plexi** by Lucid is available for Sun workstations only, and is quite expensive.
- **Neural Network Utility/400**, just released by IBM, runs in a client-server fashion, but the server must be an AS/400 computer. Intended applications include business-oriented functions, presumably utilizing data already stored on the AS/400. Applications suggested in the manual include credit scoring, sales forecasting, labor scheduling, sales order processing, product-to-specification advisor, marketing data analysis, and truck routing.

Frequently, once neural network application has been proven, the code will be rewritten, usually in *C* for efficiency and careful control of tuning parameters before being put into production.

Potential SRS Applications

A first estimation of applications where neural networks could be successfully applied in the SRS environment include the following:

- **Data validation** in which exceptional categories or variables beyond certain limits are exceeded. Application areas include business data, technical data, experimental data, and process data.

- **Novelty filter** in which a well-known plant process is monitored to detect the occurrence of an unusual region of operation. Output of the filter would notify personnel to investigate, and possibly trigger an AI/expert system to begin analysis and diagnosis of the problem. If, after thorough investigation, the condition were found to be normal, the occurrence would be incorporated into the neural net filter as normal operation.
- **Sensor validation.** One sensor variable in a process or reactor is nearly always correlated with other measured variables. Trained on sufficient real or simulated data, a neural network could detect the failure of a sensor, or its drift out of specification.
- **Reactor or process surveillance** would constantly monitor the process states, continuously verifying a correct envelope of variables. If also trained with simulated data, the neural net could determine the source of a malfunction very rapidly.
- **Vibration data analysis,** possibly in continuous real-time monitoring, to determine correct operation of rotating machinery, such as pump-motors, by listening for abnormal features in the presence of great noise.
- **Visual Q/A inspection** is most useful for manufactured product lines, but is effective in any situation where numerous items of one or a few types need verification.
- **Chemical analysis,** whereby voluminous data from many components may be embedded in noise, such as gas chromatography or spectrophotometry.
- **Robotic applications** including many functions, such as vision or directional camera control, navigation through multi-sensor fusion, steering and propulsion control, and articulated arm control. The existing robot fleet is remotely-controlled by wire or radio, and hence lacks speed and smoothness of coordinated control systems. Autonomous operation would be a significant asset under many use scenarios.
- **Scheduling** of labor, resources, machinery, truck routes, or any bounded-constraint type of problem. Determination of priority of projects based on limited resources of people, facilities, time, and money operating within a quantifiable demand is a problem that falls this category, but human judgment cannot be appropriately quantified as a variable.

5 Hardware

Workstations

Most of the neural nets you can buy for your workstation today are actually software simulations of neural nets. Many useful functions can be performed in 20 to 40 logical processing units, so computation of weights and outputs during use is quite feasible. Learning the weights based on training samples usually takes much longer, but several hours or overnight runs are feasible. A rough measure of the power or speed of neural net computations is connections per second, and reflects multiplications, additions, and distributions that can be performed per unit of time over a given network.

Some neural net solutions involve plug-in hardware for your workstation. Most of these use a fast microprocessor with dedicated onboard memory, driven by modules optimized to perform specific neural models. A few which utilize neural net chips or VLSI are appearing. HNC offers the Anza/DP Plus neural net coprocessor for a PC which can perform 7.5 million connections-per-Second.

Parallel Processing

Supercomputers can do neural net simulations well, up to a limit, because they are designed to do vectorization or pipelining with the parallelization necessary to execute matrix operations quickly. Software simulations of neural nets are largely matrix operations.

Several massively parallel computers are available now, and more are under development. Neural networks executed on these machines to date have not demonstrated the performance one may expect given the number of processors. Perhaps the reason is that researchers have just not fitted the algorithms to the machine well. A more fundamental reason may be that communications architecture within most parallel processors does not appropriately accommodate the requirements of neural nets. The communications

problem among processing elements was the primary design goal when Daniel Hillis created his Connection Machine, a massively parallel processor with up to 64,000 processors. There is little doubt that neural nets and parallel processors will mesh with each other; they may become inseparable.

Integrated Circuits

Neural network chips typically simulate from 4 to 32 neurons on a single chip. Architectures of the chips vary widely. Analog versus digital computation is a major issue. Computing the weight functions based on inputs, summing the result, and non-linear filtering of the output are basically analog operations. Some chips implement these functions in analog on-chip. Surprisingly, computation time is usually *longer*, because of settling time. These circuits also have more noise and less reproducible results than digital computation. Getting signals on- and off-chip is also a problem for loading externally-computed weights, inputs, and outputs.

Massively parallel neural chip architectures will permit neural nets to be expanded in extent (nodes), permitting parallelism and computing power yet unknown.

Many—maybe *most*—integrated circuit manufacturers are developing neural net chips because the structure of neural nets mimics the marketing dynamics of integrated circuits. That is, *if* the problem of extending neural net signals between many chips is solved, then many identical circuits can be connected in a grid-like pattern to create much larger nets. It is most economical for chip manufacturers to sell large volumes of identical chips. A good toe-hold early in this expanding market could result in a tremendous volume of sales.

Currently available commercial products are shown below. Several others were developed in universities or for internal use within several companies, but are not available commercially.

One could conjecture that neural nets will provide chip makers with incentives for innovation and new chip architectures for at least a couple of decades. Some currently available chips are the following:

- Intel's 80170 Electrically Trainable Artificial Neural Network (ETANN) chip is an analog implementation whose weights must be downloaded. No training is supported on-chip. Training must be done by a software simulation before downloading the weights onto the chip, a process which can take perhaps ten minutes. California Scientific's Brain-maker program has an interface designed to work with the Intel chips.
- NHC's NEP is an analog implementation. HNC is by far the largest company currently in the neural networks industry, primarily in consulting and software.

- **Neural Semiconductor's** NU32 and SU 3232 chips use a pulse-train technology, emulating biology, to assist in overcoming several problems of implementation, especially the off-chip communications problem. Network configurations and weights must be downloaded, a process which can take some time. On-chip learning is not supported.
- **Adaptive Solutions'** chip is now going into beta release, with shipping dates before year's end. Learning is accomplished on-chip, resulting in much faster training times. The company reports that the NetTalk demonstration application that took four and a half hours to train on a Sun workstation took six seconds to train on their chip. Although not yet independently verified, this does represent the increased speed expected in dedicated-purpose chips. The chip implements SIMD in an all-digital format. A complete development system is also offered, for about \$60,000.

These chips have not yet had time to be incorporated into commercial or internal products.

PN Junctions

Another category of neural network hardware was invented by Carver Mead, a leader in the development of very large scale integrated circuits (VLSI). Mead recognized that the nonlinear selection function, and the summing function, shared the same mathematical form as the equations for the semiconductor PN junction. His circuits use a transistor in an unconventional mode, called the sub-threshold region, to directly implement neural net functions in the physics of the PN junction. Mead's approach could best be described as directly embodying the physical analogs of biological nerves in silicon. The advantages are speed, extremely low power, and very high density. One disadvantage is that these very weak signals can't travel very far. In many applications, it is only necessary for neurons to connect with those close to them. Mead has developed a VLSI for "early vision" and an electronic cochlear - the equivalent of early vision in hearing. Not meant as commercial products, these circuits do provide an important tool for discovery, in the same sense that visualization adds to simulation of physical processes. Mead's work could result in major advancement of practical applications.

This page left intentionally blank.

6 Optical Computing

Optical computing may become an important embodiment for neural computing. This section explores why, describing a little of optical computing along the way. Please note that optical computing has not yet become mainstream after twenty years of development for good reasons which may or may not be solved anytime soon. If you accept the premise of optical computing—or reject it completely—you may skip this section.

The most important paradigm of optical computing uses coherent laser light to perform filtering or pattern matching functions. A schematic of a typical setup is shown in Figure 13.

Figure 13: Optical computing paradigm

Mathematically, the spatial Fourier transform function is being performed. It has the characteristic that every feature of the input image is mapped to every point in the filter or output plane, and all mappings (computations) are

performed simultaneously in parallel. That certainly does look and sound like neural networks, doesn't it?

The equivalent of synaptic weights are stored as phase-preserved interference patterns known as holograms. The conjecture that the brain and mind may perform holographic-like function has been around for at least twenty years. Numerous books have been published on this thesis, and research articles about biological memory that do *not* use the holographic paradigm are frequently so flagged in the title.

The advantages of optical holographic computing include the following:

1. **Speed.** An entire image plane or input dataset is computed all at one time, at the speed of light, by adding light phase wavefronts. The limiting factor is the speed of response of the input mechanisms and output detectors.
2. **Size of input and output data sets.** Again the limit is the input transducers and output detectors.
3. **Amount of storage.** Bulk or volume holograms are potentially capable of storing enormous amounts of data.
4. **Associative pattern search.** The best pattern match, even if based on only partial input, is computed over all stored patterns. The input may be trained to evoke a corresponding pattern or dataset.

Sounds even more like neural networks!

Optical computing may be the ultimate in parallel processing as well. The computation is the addition or superposition of light waves; Mother Nature does the computing—all we have to do is catch the answer. Density of computation could become a real concern as integrated circuits become smaller. As circuits become smaller, quantum interference effects of electrons make computation unreliable. This limit is being approached now. Light waves, being photons, are a different class of subatomic particles which don't interfere with each other. This characteristic could permit extremely dense computation at very low power levels.

Barriers to optical computing include the following:

1. **Unavailability of adequate input and output devices.** This is far and away the largest problem. New understandings in quantum devices are continually, if slowly, improving. Bell Laboratories inventions of the SEED and quantum well surface lasers within the last few years may lead to input transducers. MIT Lincoln Laboratories this past spring created the MOET (Monolithic Optical-Electrical Transistor) specifically for use in optical computing.

2. Physical stability. For holograms to work well, the physical dimensions must be held accurate to within less than a wavelength of the light being used. After development of good, small-sized, I/O devices, this will probably collapse to an engineering problem.

Impressive capability in holographic pattern recognition was achieved 20 years ago. The barriers mentioned above were significant, as they precluded reasonable integration with more conventional computing technologies. The all-optical computer seems a technically desirable target, considering the difficulty of conversion from electronic to optical, and vice versa, but will not be realized any time soon.

Despite the I/O hurdle, a more reasonable, nearer-term goal will be hybrid computation wherein the optical components perform specialized functions such as pattern or speech recognition.

Optical computing and neural networking are being heavily researched, separately and jointly, by the defense community for automatic target recognition and tracking. Demetri Psaltis and Nebil Farhat are most well known in the civilian research sector for optical neural computing. Inclusion of the capability of multiple layers of a neural network and feedback would probably permit the embodiment of any neural net. Psaltis' optical neural computer implements the Hopfield net.

This page left intentionally blank.

7 Summary/Future

Neural networks have been extremely successful in appropriate applications, yet they are still far from a mature technology. What path will they follow to becoming universally accepted?

The success or at least potential of neural networks is paradoxically evidenced by the *lack* of reports of successful application. Entire industries are apparently developing applications for *competitive advantage*, hence keeping projects and especially successes confidential.

The financial industry is finding that neural nets can do a better job of determining patterns and making predictions than any other technique known.

The control engineering industry has confidential development as well, because of the possibility of a revolutionary neural net control strategy. Neural nets could offer much not possible with conventional controllers: the ability to learn through observation, control processes based on a comprehensive estimation of state, adjust flexibly to unanticipated inputs, enable direction by hierarchical control elements, etc. Neural nets could bring entirely new concepts and fundamentally different assumptions to this relatively mature industry.

The Department of Defense is heavily investing in neural nets, partially through its contractors, with emphasis on such things as target recognition, tracking, and targeting. The difficulty of these tasks is greater than one may suspect because the conditions or observed variables are not known in human experience. Real-time (and very fast !) response is mandatory under confusing, possibly conflicting situations.

Many of the networks or techniques mentioned in this paper have come into existence within only the last three or four years. Hardware chip implementations are just becoming available now. No generic application solutions exist, nor are these cookbook formulas to determine how to partition a problem. And yet, despite this immaturity, success in many areas has already been recognized. The rapid advancement and potential of neural networks has been demonstrated.

Waiting for the technology of neural networks to mature before employment may be inappropriate, depending on a company's business strategy. In those situations where opportunity for discovery or competitive advantage could depend on novel implementations to assist in the achievement of a goal, waiting implies loss of market and revenue.

Many in the field hold that neural networks as a separate discipline will disappear, as happened to digital electronics or computer design. The technology will become so inextricably intertwined with many other technologies and applications—a technical commodity on which to construct products—that neural network engineering and design will occur only in academia or within commercial product design. Universality of a technology to the point where it is invisible is ultimate ascendancy.

8 References

The following references are good introductory books to neural networks and computational issues.

Albus, J. S. *Brains, Behavior, and Robotics*. BYTE Publications, 1981.

Anderson, J. A., and Rosenfeld, E. *Neurocomputing: Foundations of Research*. MIT Press, 1988.

Arbib, M. A. *The Metaphorical Brain: An Introduction to Schemas and Brain Theory*. 2nd ed. Wiley Interscience, 1988.

Arbib, M. A. *Brains, Machines, and Mathematics*. 2nd ed. Springer-Verlag, 1987.

Grossberg, S. and Kuperstein, M. *Neural Dynamics of Adaptive Sensory-Motor Control*. Pergamon Press, 1989.

Hecht-Nielsen, R. *Neurocomputing*. Addison-Wesley, 1990.

Kohonen, T. *Self-Organization and Associative Memory*. 3rd ed. Springer-Verlag, 1989.

Mead, C. *Analog VLSI and Neural Systems*. Addison-Wesley, 1989.

Minsky, M.L. *The Society of Mind*. Simon & Schuster, 1986.

Minsky, M. L., and Papert, S. *Perceptrons: An Essay in Computational Geometry*. MIT Press, 1969.

Penrose, R. *The Emperor's New Mind*. Oxford University Press, 1989.

Rodgers, S. K., and Kabrisky, M. *An Introduction to Biological and Artificial Neural Networks for Pattern Recognition*. The Society of Photo-Optical Instrumentation Engineers, 1991.

Simpson, P. K. *Artificial Neural Systems*, Pergamon Press, 1990.

Although many thousands of scientific articles have been published in many diverse journals and magazines, there are currently only two scientific journals dedicated to neural networks:

Neural Networks, the official journal of the International Neural Network Society, first started publishing in 1988. For subscription information contact:

INNS Membership
PO Box 491166
Fort Washington, MD 20749

IEEE Transactions on Neural Networks is a journal available to members of the Institute of Electrical and Electronics Engineers, and associated organizations. It first started publication in Spring 1990.

END

**DATE
FILMED
8/04/92**