154
1-8-82
Jude

I-683

①

DR 183

ASSACHUSETTS

INSTITUTE OF

ECHNOLOGY

LASMA

USION

ENTER

ASSOCIATED WITH

- DEPARTMENT OF AERONAUTICS AND ASTRONAUTICS
- DEPARTMENT OF ELECTRICAL ENGINEERING
AND COMPUTER SCIENCE
- DEPARTMENT OF MATERIALS SCIENCE
AND ENGINEERING
- DEPARTMENT OF MECHANICAL ENGINEERING
- DEPARTMENT OF NUCLEAR ENGINEERING
- DEPARTMENT OF PHYSICS
- FRANCIS BITTER NATIONAL MAGNET LABORATORY
- RESEARCH LABORATORY OF ELECTRONICS

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

PFC/RR-80-27

DOE/ET/51013-26
UC20D

MASTER

A PLAN FOR UTILIZING ALCATOR A
FOR DEVELOPING ACTIVELY COOLED LIMITERS
AND PARTICLE-PUMPING METHODS

T.F. Yang ✓
Plasma Fusion Center
Massachusetts Institute of Technology
Cambridge, MA 02139

May, 1980

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

A Plan for Utilizing Alcator A
for Developing Actively Cooled Limiters
and Particle Pumping Methods

T. F. Yang
Plasma Fusion Center
Massachusetts Institute of Technology
Cambridge, Massachusetts

May 19, 1980

Purpose

The purpose of this plan is: to develop a limiter or limiters (subjected to high heat and particle fluxes at plasma edge) for long pulse operation of tokamak fusion devices; to study the particle removal with the limiters; and to study and develop the methods for protections against disruptions and other abnormal operation, such as run-away electrons and arcing.

Alcator A has a peak heat of 5 kW/cm^2 and high particle flux, and as such is an ideal test facility. Access is adequate for small scale tests.

Limiter Types

Active cooling methods will be developed for the conventional poloidal ring type limiter. The complete or partial toroidal rail types will be designed and studied. Innovative ideas will be investigated.

The conventional methods and two conceived innovative ideas are described in the following.

1) Conventional ring type

The present limiters for Alcators are poloidal rings made of molybdenum and are inertially cooled after pulses. For the purpose of comparison, a ring type, water-cooled limiter has been designed by McDonnell Douglas. The preliminary results are shown in Figure 1. The surface of the limiter is a 2 mm molybdenum shell bonded onto an array of copper tubes. The initial design

study of such a limiter is underway and will be evaluated. If judged to be feasible, it will be fabricated for testing. In this conventional method, the water temperature will rise at the exit ends, and thus will reduce the heat removal efficiency. A spray cooling method is proposed here and is illustrated by Figure 2. The surface can be coated with molybdenum or graphite or other materials. The pumping from the back side can be tested.

2) Innovative concepts

Two innovative concepts have been conceived, the spring-like coiled limiter and a series of coiled tops. The coiled limiter is shown in Figure 3. The advantage of the coil limiter is that the plasma will reach the front as well as inner surfaces of the tubes as is illustrated by Figure 3b. This not only increases the surface area, but also reduces the thermal stress. It will be tested if the neutrals inside the coil can be pumped out at the ends. One can vary the pitch of the spring to determine the most effective cooling and particle removal. Because the plasma may pass through the space in between turns, two or more coil limiters may be needed. It is also possible to use a secondary cooling as is shown by Figure 3d with counter flow coolant. It is like a heat exchanger. The primary water will be recooled at each turn so that the temperature over the entire length of the limiter will be nearly uniform and the heat removal will be more effective.

The coiled top-like limiter is illustrated by Figure 4. The tops will be mounted on a duct and water lines will be connected to a manifold. The neutrals scattered into the duct can be pumped away.

The application of the coil limiters to a reactor is illustrated by Figure 5. The whole first wall can be lined with these springs. They do not have to be closely fitted together and can be easily replaced.

The purpose of the above discussion is to demonstrate that innovative methods are conceivable. Alcator-A is a valuable facility in which to carry out the testing of these methods.

Testing Plan

The testing plan is briefly outlined as follows:

- A valid concept will be designed, evaluated and tested.
- The test on the actively cooled limiters will always begin with low power. The power will be raised gradually to highest possible level.

- If the test is successful at normal operation, the limiters will be punished with simulated abnormal operations such as disruption, run-away electrons, etc.
- The limiter will be subjected to many thousands of pulses to test the fatigue
- Coating of different materials with various thicknesses will be tested. Pumping techniques will be tested.
- After the successful limiters are identified, the tests will be repeated by covering the first wall area as much as possible with these limiters

Participants

The scientists who are interested in this program from other laboratories, such as Sandia and Livermore, and from industry, are invited to participate and test their own concept in coordination with M.I.T.

LIMITER CONCEPT 1: FORMED SKIN/COOLANT TUBES

MATERIALS

	<u>SKIN</u>	<u>TUBES</u>	<u>STRUCTURE</u>
(a)	Cu	Cu	} Mo; ST STL
(b)	Ta-10W	Cu	
(c)	Mo	Cu	

THERMAL HYDRAULICS

FOR 5 KW/CM² PEAK HEAT FLUX:

<u>CLNT</u>	<u>SKIN MATERIAL</u>	<u>SKIN T_{MAX}</u>
H ₂ O	Cu	250 180 °C
H ₂ O	Ta-10W	650 420 °C
H ₂ O	Mo	400 280 °C

FABRICATION

- SKIN FORMED OVER PATTERN
- TUBES, SKIN, STRUCTURE BRAZED AS UNIT
- COATING COULD BE ADDED TO SKIN

Figure 1. Water-Cooled Limiter Design

Figure 2. Sketches to Illustrate Different Cooling Methods

Figure 4. Sketches to illustrate coiled top limiters

Application to Reactor

Application to Alcator

Figure 5. Sketches to illustrate the Application to Alcator and the Reactor

LIMITER CONCEPT 1: FORMED SKIN/COOLANT TUBES

MATERIALS

	<u>SKIN</u>	<u>TUBES</u>	<u>STRUCTURE</u>
(a)	Cu	Cu	} Mo; ST STL
(b)	Ta-10W	Cu	
(c)	Mo	Cu	

THERMAL HYDRAULICS

FOR 5 KW/CM² PEAK HEAT FLUX:

<u>CLNT</u>	<u>SKIN MATERIAL</u>	<u>SKIN T_{MAX}</u>
H ₂ O	Cu	250 180 °C
H ₂ O	Ta-10W	650 400 °C
H ₂ O	Mo	400 200 °C

FABRICATION

- SKIN FORMED OVER PATTERN
- TUBES, SKIN, STRUCTURE BRAZED AS UNIT
- COATING COULD BE ADDED TO SKIN

MCDONNELL DOUGLAS
CORPORATION

PFC BASE LIST

INTERNAL MAILINGS (MIT)

G. Bekefi
36-213

A. Bers
38-260

D. Cohn
NW16-250

B. Coppi
26-201

R.C. Davidson
NW16-202

T. Dupree
38-172

S. Foner
NW14-3117

J. Freidberg
38-160

A. Gondhalekar
NW16-278

M.O. Hoenig
NW16-176

M. Kazimi
NW12-209

L. Lidsky
38-174

E. Marmar
NW16-280

J. McCune
31-265

J. Meyer
24-208

D.B. Montgomery
NW16-140

J. Moses
NE43-514

D. Pappas
NW16-272

R.R. Parker
NW16-288

N.T. Pierce
NW16-186

P. Politzer
NW16-286

M. Porkolab
36-293

R. Post
NW21-

H. Praddaude
NW14-3101

D. Rose
24-210

J.C. Rose
NW16-189

R.M. Rose
4-132

B.B. Schwartz
NW14-5121

R.F. Post
NW21-203

L.D. Smullin
38-294

R. Temkin
NW16-254

N. Todreas
NW13-202

J.E.C. Williams
NW14-3210

P. Wolff
36-419

T.-F. Yang
NW16-164

MIT Libraries
Collection Development
ATTN: MIT Reports
14E-210

B. Colby
PFC Library
NW16-255

Industrial Liaison Office
ATTN: Susan Shansky
Monthly List of Publications
39-513

EXTERNAL MAILINGS

National

Argonne National Laboratory
Argonne, IL 60439
ATTN: Library Services Dept.

Battelle-Pacific Northwest Laboratory
P.O. Box 99
Richland, WA 99352
ATTN: Technical Information Center

Brookhaven National Laboratory
Upton, NY 11973
ATTN: Research Library

U.S. Dept. of Energy
Washington, D.C. 20545
ATTN: D.O.E. Library

Roger Derby
Oak Ridge National Lab.
ETF Design Center
Bldg. 9204-1
Oak Ridge, TN 37830

General Atomic Co.
P.O. Box 81608
San Diego, CA 92138
ATTN: Library

Lawrence Berkeley Laboratory
1 Cyclotron Rd.
Berkeley, CA 94720
ATTN: Library

Lawrence Livermore Laboratory
UCLA
P.O. Box 808
Livermore, CA 94550

Oak Ridge National Laboratory
Fusion Energy Div. Library
Bldg. 9201-2, ms/5
P.O. Box "Y"
Oak Ridge, TN 37830

Dr. D. Overskei
General Atomic Co.
P.O. Box 81608
San Diego, CA 92138

Princeton Plasma Physics Laboratory
Princeton University
P.O. Box 451
Princeton, NJ 08540
ATTN: Library

Plasma Dynamics Laboratory
Jonsson Engineering Center
Rensselaer Polytechnic Institute
Troy, NY 12181
ATTN: Ms. R. Reep

University of Wisconsin
Nuclear Engineering Dept.
1500 Johnson Drive
Madison, WI 53706
ATTN: UV Fusion Library

EXTERNAL MAILINGS

International

Professor M.H. Brennan
Willis Plasma Physics Dept.
School of Physics
University of Sydney
N.S.W. 2006, Australia

Division of Plasma Physics
Institute of Theoretical Physics
University of Innsbruck
A-6020 Innsbruck
Austria

c/o Physics Section
International Atomic Energy Agency
Wagramerstrasse 5
P.O. Box 100
A-1400 Vienna, Austria

Laboratoire de Physique des Plasmas
c/o H.W.H. Van Andel
Dept. de Physique
Universite de Montreal
C.P. 6128
Montreal, Que H3C 3J7
Canada

Plasma Physics Laboratory
Dept. of Physics
University of Saskatchewan
Saskatoon, Sask., Canada S7N 0W0

The Library
Institute of Physics
Chinese Academy of Sciences
Beijing, China

Mrs. A. Wolff-Degives
Kernforschungsanlage Julich GmbH
Zentralbibliothek - Exchange Section
D-5170 Julich - Postfach 1913
Federal Republic of Germany

Preprint Library
Central Research Institute for Physics
H-1525 Budapest, P.O. Box 49
Hungary

Plasma Physics Dept.
Israel Atomic Energy Commission
Soreq Nuclear Research Center
Yavne 70600
Israel

The Librarian (Miss DePalo)
Associazione EURATOM - CNEN Fusione
C.P. 65-00044 Frascati (Rome)
Italy

Librarian
Research Information Center
Institute of Plasma Physics
Nagoya University
Nagoya, 464
Japan

Dr. A.J. Hazen
South African Atomic Energy Board
Private Bag X256
Pretoria 0001
South Africa