CHARACTERIZATION OF OIL AND GAS RESERVOIR HETEROGENEITY

Cooperative Agreement DE-FG07-90ID12839

DOE/ID/12839--T4

Petroleum Development Laboratory
University of Alaska, Fairbanks
437 Duckering Building
Fairbanks, AK 99775-1260

DE92 017959

Contract Date: November 1, 1989
Anticipated Completion: October 31, 1992

Principal Investigator:
G. D. Sharma

Project Manager:
Charles Thomas
Idaho Operations Office

Reporting Period: July 1, 1991 - September 30, 1991

OBJECTIVE

The objective of this cooperative research project is to characterize Alaskan petroleum reservoirs in terms of their reserves, physical and chemical properties, geologic configuration in relation to lithofacies and structure, and development potential.

The project has two tasks: Task 1 is a geological description of the reservoirs including petrophysical properties, i.e., porosity, permeability, permeability variation, formation depth, temperature, and net pay, facies changes and reservoir structures as drawn from cores, well logs, and other geological data. Task 2 is reservoir fluid characterization—determination of physical properties of reservoir fluids including density, viscosity, phase distributions and composition as well as petrogenesis—source rock identification; and the study of asphaltene precipitation for Alaskan crude oils and their effect on rock-fluid properties.

MASTER

jsz

SUMMARY OF TECHNICAL PROGRESS

Work performed during this quarter as part of Task 1—the geological reservoir description—includes preliminary reservoir description and determination of petrophysical properties of the Milne Point Unit.

Reservoir Description of the Milne Point Unit

The Milne Point Unit is located adjacent to the West Sak Field. The field is operated by Conoco, Inc. It is estimated to contain 100 million barrels of oil-in-place. Oil production is from the Cretaceous Kuparuk River Formation at depths ranging from 6950 ft to 7000 ft subsea.

Results from drilling and formation evaluation show that the Kuparuk River Formation at Milne Point is composed of two high-quality, consolidated, oil-bearing sandstone members. These sand members are found within the Middle and Lower Kuparuk River Formation. Stratigraphically, the Middle Kuparuk generally thickens toward the southeast. In contrast, the Lower Kuparuk shows no general trend of sand thickening toward the south.

Petrophysical Properties

Petrophysical properties of the Milne Point Unit are derived from analyses of well logs. Core data and completion reports were used to augment the well log data. The results calculated from well logs show that the average porosities in the producing zones range from 16% to 29%, and the average water saturation is between 33% to 45%. Several normal faults have been identified within the Milne Point Unit.

The tasks to be performed in the future include additional well log analysis, study of the detailed reservoir geological description, and analysis of the depositional environment.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Reservoir Fluid Characterization

As part of the reservoir fluid characterization task, a thermodynamic model was developed to predict the conditions for asphaltene precipitation for Alaskan crude oils.

Prediction of Asphaltene Precipitation Using a Polydispersed Molecular Thermodynamic Model

A generalized molecular thermodynamic model has been developed for the prediction of asphaltene equilibria and precipitation of asphaltenes from a crude under the influence of a miscible solvent. The model treats the asphaltenes in the crude oil as a heterogeneous mixture of pseudocomponents. The pseudocomponents of asphaltenes are represented by a discretized normal distribution function. The properties of each asphaltene pseudocomponent are determined from the average molecular weight of each fraction. The model is coupled with the Peng-Robinson equation-of-state model to compute the vapor-liquid equilibria. The Peng-Robinson departure function model is used to calculate the molar volume and to determine the solubility parameter for the equilibrium liquid phase of the oil-solvent mixtures.

The model was then used to obtain 5 model parameters by employing a Least Squares regression technique to fit the experimental asphaltene precipitation data for various West Sak crude oil-solvent mixtures. The model was used to predict the amount of asphaltene precipitation, the solid-liquid equilibrium constants for each asphaltene fraction, the molar distribution of asphaltenes in tank oil, and equilibrium solid and liquid phases. Table 1 shows the comparison of experimental results with model predictions. It lists the amount of asphaltene precipitation for various solvent-to-oil ratios for solvents such as CO₂, ethane, propane, n-butane, n-pentane, n-heptane, NGL and Prudhoe Bay natural gas (PBG). The model predictions show good agreement with the experimental data. Figure 1 shows the molar distribution of asphaltene in the West Sak tank oil, and in the equilibrium solid and liquid phases. The future work will focus on studying the effects of pressure and temperature on the degree of asphaltene precipitation.

REFERENCES

1. "Oil and Gas Journal, 1985, "Milne Point Unit—Small but Welcome," Vol. 83, No. 25, pp. 55-58.
2. Masterson, W.D., and Paris, Chester E., 1987, "Depositional History and Reservoir Description of the Kuparuk River Formation, North Slope, Alaska," in Alaskan North Slope Geology, Vol. 1, p. 95.

**Table 1. Comparison of Experimental Results Versus Model Predictions
of Amount of Asphaltene Precipitation From West Sak Crude
Under Influence of Various Solvents**

SOLVENT	SOLVENT/OIL RATIO BY WEIGHT	WT. % ASPHALTENES (Experimental)	WT. % ASPHALTENES (Predicted)	% ERROR
Ethane	3.00	5.14	5.19	-0.91
Ethane	13.00	5.28	5.22	1.10
Carbon Dioxide	3.60	5.56	5.73	-3.09
Carbon Dioxide	13.60	5.80	5.75	0.88
Carbon Dioxide	15.30	5.89	5.76	2.28
Propane	4.70	8.87	8.88	-0.07
Propane	7.80	8.60	8.88	-3.22
Propane	16.30	9.07	8.88	2.11
N-Butane	2.00	6.22	6.05	2.74
N-Butane	8.13	6.36	6.55	-3.01
N-Butane	13.30	6.45	6.55	-1.56
N-Pentane	2.00	1.79	1.93	-7.69
N-Pentane	7.00	6.20	6.25	-0.65
N-Pentane	12.50	6.30	6.20	1.53
N-Pentane	20.20	6.69	6.20	7.37
N-Heptane	2.00	3.83	3.32	13.31
N-Heptane	7.30	5.34	6.56	-22.76
N-Heptane	13.50	7.50	6.56	12.60
N-Heptane	20.10	7.32	6.56	10.45
NGL	3.20	5.73	5.66	1.16
NGL	7.60	8.80	8.76	0.41
NGL	9.90	8.88	8.78	1.11
PBG	1.59	5.49	4.32	21.24
PBG	1.70	7.40	6.26	15.45
PBG	5.85	8.15	8.12	0.33
PBG	10.42	8.08	8.12	-0.53

Figure 1. Relation Between Molar Distribution as a Function of Molecular Weight of Asphaltene for N-Heptane — West Sak Tank Oil Ratio = 2.0

U.S. DEPARTMENT OF ENERGY
FEDERAL ASSISTANCE PROGRAM/PROJECT STATUS REPORT

FORM EIA-250P
(10/88)

FORM APPROVED
OMB No. 1505-0127

1. Program/Project Identification No. DE-FG07-90ID12839	2. Program/Project Title Characterization of Oil and Gas Reservoir Heterogeneity	3. Reporting Period 07/01/91 through 09/30/91
4. Name and Address Petroleum Development Laboratory, University of Alaska Fairbanks, 437 Duckering Building, Fairbanks, Alaska 99775-1260		5. Program/Project Start Date 11/01/89
		6. Completion Date 10/31/92

7. Approach Changes

☒ None

8. Performance Variances, Accomplishments, or Problems

There were no problems or variations in the performance for the total research effort.

Accomplishments:

Task I: Preliminary reservoir description and determination of petrophysical properties of the Milne Point Unit.

Task II: A generalized molecular thermodynamic model has been developed for the prediction of asphaltene equilibria and precipitation of asphaltenes from a crude under influence of a miscible solvent.

☐ None

9. Open Items

☒ None

10. Status Assessment and Forecast

Task II: A generalized molecular thermodynamic model has been developed for the prediction of asphaltene equilibria and precipitation of asphaltenes from a crude under influence of a miscible solvent.

☐ None

9. Open Items

☒ None

10. Status Assessment and Forecast

☒ No Deviation from Plan is Expected

11. Description of Amendments

☐ None

Please see attached quarterly report for the period
July 1, 1991 - September 30, 1991

12. Signature of Recipient and Date

Dr. G. D. Sharma, Director, PDL

13. Signature of DCE Reviewing Representative and Date

for
11/20/91

END

**DATE
FILMED
9/01/92**