DIRECT CONVERSION OF LIGHT HYDROCARBON
GASES TO LIQUID FUEL

Report No. 31

Quarterly Technical Status Report
for
Fourth Quarter F.Y. 1991

Project Manager: R. D. Kaplan

Principal Investigator: M. J. Foral

Work performed under Contract No. DE-AC22-89PC89866

For

U. S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania

By

Amoco Oil Company
Research & Development Department
Post Office Box 3011
Naperville, IL 60566

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

PR

MAY 07 1982

FINAL QUARTERLY PROGRESS REPORT SUBMITTED TO:

1. George Cinquegrane (2 copies)
Contracting Officer's Representative
U.S. DOE/PETC
P.O. Box 10940
Pittsburgh, PA 15236
2. Dona G. Sheehan
Contract Specialist
U.S. DOE/PETC
P.O. Box 10940
Pittsburgh, PA 15236
3. Robert M. Hamilton
FE-231, E-155/GTN
U.S. Department of Energy
Washington, DC 20545
4. Gilbert V. McGurl
Program Manager
U.S. DOE/PETC, MS 922-H
P.O. Box 10940
Pittsburgh, PA 15236

ADDITIONAL CIRCULATION FOR DRAFT REPORTS TO:

Amoco Corporation
Suite 600
305 East Shuman Boulevard
Naperville, IL 60563-8408
T. H. Fleisch

Amoco Oil Company
P.O. Box 3011
Naperville, IL 50566
R. D. Kaplan, H-4
M. J. Foral, H-4
A. R. LaPuma, H-4
D. W. Washecheck, H-2
D. B. Lerman, H-1
A. S. Couper, H-1
F. W. Hauschildt, H-3

TABLE OF CONTENTS

	<u>Page</u>
EXECUTIVE SUMMARY	7
BACKGROUND	8
PROGRAM OBJECTIVES	9
PROJECT DESCRIPTION	9
RESULTS AND DISCUSSION	10
Task 3.6: Effect of Reactor Recycle.....	10
Task 3.7: Enhanced Yield Studies.....	19
CONCLUSIONS	22
ACKNOWLEDGEMENT	22

LIST OF FIGURES

- FIGURE 1 Effect of Added CO on Methanol Selectivity
- FIGURE 2 Effect of Added CO on CO₂ Selectivity
- FIGURE 3 Effect of Added CO on Net CO Selectivity
- FIGURE 4 Effect of Added CO on Formaldehyde Selectivity
- FIGURE 5 Effect of Added CO on Hydrocarbon Conversion
- FIGURE 6 Effect of Added CO on Methanol Yield
- FIGURE 7 Effect of Added CO on CO Production/Conversion
- FIGURE 8 Effect of Recycle on Methanol Selectivity
- FIGURE 9 Effect of Recycle on Feed Conversion
- FIGURE 10 Effect of Recycle on Methanol Yield
- FIGURE 11 Effect of Recycle on CO₂ Selectivity
- FIGURE 12 Effect of Recycle on CO Selectivity
- FIGURE 13 Enhanced Yield Catalyst Post-Bed
- FIGURE 14 Effect of Catalyst Post-Bed on Methanol Selectivity
- FIGURE 15 Effect of Catalyst Post-Bed on Methanol Yield

DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process or service by trade name, mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

TECHNICAL STATUS

This technical status report is being transmitted in advance of DOE review, and no further dissemination or publication will be made of this report without prior approval of the DOE Project/Program Manager.

EXECUTIVE SUMMARY

Amoco Oil Company, under a contract with the United States Department of Energy, is investigating the direct conversion of light hydrocarbon gases to liquid fuels via partial oxidation. This report describes work completed in the eighth quarter of the two-year project. Work continued and progress was made on two tasks during this quarter. A six-month no-cost extension was granted to the project so that all tasks can be fully completed.

Task 3.6 (Effect of Reactor Recycle): Reactor feeds were spiked with CO and mixtures of CO and H₂ (both are reaction byproducts) to complete investigation of the effects of reactor recycle. Added CO had a significant negative impact on methanol selectivity, but no effect on hydrocarbon conversion. When mixtures of CO and H₂ were added, the trends were the same as when either was added separately. In fact, the effects of the mixture on methanol selectivity could be reasonably predicted by a linear addition of the single component effects. Based on these studies, adding recycle to the system would have a negative impact on methanol selectivity and yield. Based on these results, it was decided not to modify the pilot plant to add a true recycle loop.

Task 3.7 (Enhanced Yield Studies - Effect of Catalyst Post-Bed): Several series of runs were made which tested the efficacy of adding a bed of conventional methanol catalyst at the exit of the thermal partial oxidation zone. The goal was to increase overall methanol selectivity by converting some of the product CO into methanol in the catalyst bed. Attempts to achieve catalytic conversion were not successful. Overall methanol selectivities were either unchanged or lower in the presence of a catalyst post-bed. Further analysis is underway to understand this system more fully.

BACKGROUND

Fischer-Tropsch synthesis, gasification processes like Lurgi dry bottom gas, direct coal liquefaction, and remote natural gas all represent sources of substantial quantities of light hydrocarbon gases. Methane is the major and most stable component of all these gases. Steam reforming methane to produce synthesis gas is capital-intensive because it is highly endothermic and requires severe reaction conditions. A process for direct conversion of light gases, especially methane, to methanol, gasoline, or other liquid fuels could be far superior.

Steam reforming is the first stage in traditional commercial methods for the production of liquid fuels. This first step produces synthesis gas:

The synthesis gas is then converted into methanol via a catalytic process.

Reaction 1 produces more hydrogen than required by reaction 2. The excess can either be utilized elsewhere in the case of a domestic refinery or, in the case of a remote operation, is lost. A third step could be the catalytic condensation of methanol to gasoline.

A more efficient route of converting light hydrocarbons would be to directly form methanol by partial oxidation.

Such a process could substantially reduce capital and energy requirements for methanol production. The methanol could be used as a fuel or a fuel blending component, as in the case of M80 fuels (80% methanol, 20% gasoline), or else converted into gasoline through well-known processes, such as MTG. A plant based on Reactions 1 and 2 followed by methanol condensation to gasoline has been built and is operating in New Zealand. However, the process is uneconomical if it were not for the New Zealand Government support. If a process for the direct conversion of light hydrocarbons to methanol is feasible, thereby eliminating the process steps shown by Reactions 1 and 2, then a gas-to-gasoline process could become economically viable.

A proposed process for converting light hydrocarbon gases directly to hydrocarbon liquids, e.g., methanol or formaldehyde, is not new. In 1932 Newitt and Haffner reported the formation of methanol, along with smaller amounts of formaldehyde and formic acid, in the high-pressure oxidation of methane.⁽¹⁾ The reaction was carried out in a static system at 360-393°C and 50-150 atm. The maximum methanol selectivity was ca. 22%; however, CH₄ conversion was only a few percent. More recently, Gesser, Hunter and co-workers have reported methanol selectivities up to 89% and yields of around 7%.⁽²⁾ However, other workers have in general been unable to reproduce these results.

- (1) D. M. Newitt, A. E. Haffner, Proc. R. Soc. London, Ser. A, 134, p. 591
- (2) H. D. Gesser, N. R. Hunter, Chem. Rev., 15(4), p. 235 (1985); H. D. Gesser, U. S. Patent 4,618,732, issued 10/21/86.

PROGRAM OBJECTIVES

The objective of this program is to investigate the direct conversion of light gaseous hydrocarbons, such as those produced during Fischer-Tropsch synthesis or as a product of gasification, to liquid transportation fuels via a partial oxidation process. The process will be tested in an existing pilot plant to obtain credible mass balances. Specific objectives to be met include determination of optimal process conditions, investigation of various processing options (e.g. feed injection, product quench, and recycle systems), and evaluation of an enhanced yield thermal/catalytic system. Economic evaluation of the various options will be performed as experimental data become available.

PROJECT DESCRIPTION

The project is of two years' duration and contains three major tasks. The third task (Pilot Plant Experiments) contains seven subtasks, corresponding to the project objectives outlined above. The tasks and subtasks foreseen when the project began are described below.

Task 1.--Project Management Plan: A plan will be prepared describing the work to be done, milestones, and manpower requirements and costs.

Task 2.--Pilot Plant Modification: An existing pilot plant dedicated to investigation of light hydrocarbon conversion will be modified to provide it with the capability to handle the processes and conditions of this program. These modifications will include construction of a new reactor, construction and installation of reactant injection and product quench systems, and, possibly, addition of a product recycle loop to the unit.

Task 3.1.--Comparison of Preliminary Data With Los Alamos Model: We will determine if the kinetic model developed by Los Alamos National Laboratory can be used to guide our experimental effort. Results from this task will be carefully analyzed and will determine the direction of the subsequent experimental program. This is a major decision point in the project.

Task 3.2.--Pressure/Temperature/Reaction Time Effects: The methane conversion data base will be extended over the following range of conditions:

Temperature:	600 to 1100 F
Pressure:	200 to 1300 psig
Reaction Time:	3 to 90 seconds

These experiments will be guided by the results of Task 3.1 to those process regimes which appear most promising.

Task 3.3.--Study of Different Injection Systems: Different schemes for introducing and mixing reactants before or within the reactor will be evaluated theoretically and/or experimentally. The goal will be to maximize methanol yield.

Task 3.4.--Study of Different Quench Systems: The efficacy of different product cooling techniques will be investigated to determine the effect of quenching on product composition and methanol yield. Both gas and liquid quench options will be investigated.

Task 3.5.--Effect of Reactor Geometry: The effect of reactor geometry, particularly aspect (i.e. length/diameter) ratio, will be investigated to determine mass transfer and mixing effects on product composition and methanol yield.

Task 3.6.--Effect of Reactor Recycle: The effect of recycling unreacted hydrocarbons to the reactor inlet will be evaluated first by appropriately blending the feed stream to simulate reactor recycle. If these results are promising relative to methanol production, a recycle compressor and recycle line will be added to the pilot plant for more detailed tests.

Task 3.7.--Enhanced-Yield Catalyst Study: An attempt will be made to develop a combined thermal/catalytic process in which byproduct carbon monoxide and hydrogen from the thermal process is converted to methanol over a heterogeneous catalyst. Such a combined process may provide higher methanol yields than the thermal process alone.

Reporting will be done periodically throughout the duration of the project according to DOE guidelines.

RESULTS AND DISCUSSION

During this quarter, work was performed on Tasks 3.6 (Effect of Reactor Recycle) and 3.7 (Enhanced Yield Studies). In addition, a 6-month no-cost extension was granted to this program so that all tasks can be fully completed. The experimental results and conclusions from this quarter are discussed in detail below.

Effect of Reactor Recycle (Task 3.6): A series of runs was completed in which various product gas species (CO_2 , CO and H_2) were added to the natural gas feed to simulate the effects of reactor recycle. In the initial runs, these product gases were individually added to the feed to determine their fate in the reactor and any effects they may have on conversion or product selectivity. In later runs, a mixture of CO and H_2 was added to the feed to more closely simulate a true mixed feed/recycle stream. Experiments have been completed in which various levels of CO_2 , CO and H_2 were added to the reactor feed at a number of oxygen concentrations. Preliminary Results of CO_2 and H_2 addition were described in the last Quarterly Technical Report. The effects of added CO and CO/ H_2 mixtures are reported here.

The natural gas feed was spiked with CO to levels of 3, 7 and 20 vol%. Oxygen concentrations were systematically varied between 1.5 and 12.5 vol%. The temperature and pressure were kept constant at 800°F and 1300 psig, respectively, and the residence time was between 40 and 50 seconds. A 30mm diameter reactor was used. Figure 1 indicates that the presence of CO in the feed gas lowers the selectivity to methanol, especially at low oxygen concentrations. Moreover, the decrease in methanol selectivity seems to be proportional to the amount of CO in the feed: higher CO levels lead to lower methanol selectivities. This decrease in methanol selectivity is accompanied by an increase in CO₂ selectivity (Figure 2) and a decrease in net CO selectivity (Figure 3). At 20 vol% CO in the feed and low oxygen concentration, the hydrocarbon-based selectivity to CO₂ is greater than 100%. This is due to the fact that CO conversion under these conditions is significant and yields mainly CO₂. Formaldehyde selectivity increased somewhat with increasing CO concentration (Figure 4), but the effect was not as pronounced as with the other products.

As with hydrogen (H₂) addition, the presence of CO had no discernable effect on hydrocarbon or methane conversion (Figure 5). In other words, even though CO apparently reacts with oxygen to form CO₂ (indicated by an increase in CO₂ selectivity), apparently other species are created which can react with the hydrocarbon molecules. Once again it is difficult to analyze such a complex free radical reaction, but possible important reactions include

and

In the above reactions there is no net loss of free radicals, allowing the free radical reaction network to proceed and involve hydrocarbon molecules. In such a case overall hydrocarbon conversion would be unaffected by the presence of CO in the feed.

Because hydrocarbon conversion is unaffected by the presence of CO, the trends observed in methanol selectivity are mirrored in the methanol yield plot, shown in Figure 6. The effect of low levels of CO (3 - 7 vol%) is negligible, but at 20 vol% CO there is a clear decrease in methanol yield. As in previous experiments, the maximum methanol yield is around 2.5 mol% and is obtained at oxygen concentrations between 9 and 12.5 vol%.

Since CO is itself a product of the reaction, we would expect that the presence of CO in the feed might affect the production of CO in the reactor. Figure 7 shows the net production and/or consumption of CO in the reactor as a function of both CO and oxygen concentration. In this figure, CO production is indicated by a positive number, consumption by a negative number. It is clear that at the lower CO concentrations (0-7 vol%), CO is still a net product of the reaction. With 20 vol% CO in the feed, however, there is net consumption of CO in the reactor at low oxygen concentrations (<10 vol%), and a small production of CO at the highest oxygen feed level. Based on these observations we would anticipate that in a commercial recycle operation, CO

Figure 1

Effect of Added CO on Methanol Selectivity

P=1300 psig, T=800 F, RT=40-50 sec.

Methanol Selectivity (mol%)

Figure 2

Effect of Added CO on CO₂ Selectivity

P=1300 psig, T=800 F, RT=40-50 sec.

CO₂ Selectivity (mol%)

Figure 3

Effect of Added CO on Net CO Selectivity

P=1300 psig, T=800 F, RT=40-50 sec.

Net CO Selectivity (mol%)

Figure 4

Effect of Added CO on Formaldehyde Selectivity

P=1300 psig, T=800 F, RT=40-50 sec.

Formaldehyde Selectivity (mol%)

Figure 5

Effect of Added CO on Hydrocarbon Conversion

P=1300 psig, T=800 F, RT=40-50 sec.

Hydrocarbon Conversion (mol%)

Figure 6

Effect of Added CO on Methanol Yield

P=1300 psig, T=800 F, RT=40-50 sec.

Methanol Yield (mol%)

Figure 7

Effect of Added CO on CO Production/Conversion

P=1300 psig, T=800 F, RT=40-50 sec.

CO Production(+)/Conversion(-) (mmol/hr)

Figure 8

Effect of Recycle on Methanol Selectivity

T=800F; P=1300 psig; RT=40 sec.

Methanol Selectivity (mol%)

would build up in the recycle loop to a level between 7 and 20 vol%, probably closer to 20 vol%. At this level, methanol selectivity would be depressed by between 2 and 20 abs%, depending on the oxygen level in the feed (from Figure 1).

Next, a series of runs was made in which the natural gas feed was spiked with different amounts of a mixture of CO and H₂. These experiments were made to more closely simulate a true mixed feed/recycle stream and also to investigate any interactions between added CO and H₂.

A mixture of CO and hydrogen with the composition 83% CO and 17% H₂ was used in these studies. This particular composition was chosen because previous studies found that CO and H₂ are produced by the reaction in about this ratio over a range of oxygen concentrations. Therefore, addition of this mixture to the natural gas feed should simulate a recycle operation relatively well. Carbon dioxide was not added to the mixture because of plant hardware limitations and the finding that CO₂ levels up to 20 vol% had no effect on the conversion or selectivity of this reaction. The natural gas feed was spiked with this CO/H₂ mixture to levels of 5, 10 and 20 vol%, which led to CO concentrations of 4, 8 and 16 vol%, and hydrogen concentrations of 1, 2 and 4 vol% in the feed, respectively. Oxygen concentrations were systematically varied between 1.5 and 12.5 vol%, but a full series of oxygen runs was only made for the 10 vol% mixture case, since supplies of the CO/H₂ mixture were limited. Once again the temperature and pressure were kept constant at 800°F and 1300 psig, respectively, and the residence time was maintained between 40 and 50 seconds.

Figure 8 indicates that the presence of mixed CO/H₂ in the feed gas lowers the selectivity to methanol, especially at low oxygen concentrations. This was expected based on the results with pure CO and H₂ spikes, both of which lowered overall methanol selectivity. Moreover, it appears that the effects of CO and H₂ in the reactor are additive. Figure 8 shows how 10 vol% of the mixture (equal to 8% CO and 2% H₂ in the feed) affects methanol selectivity over a range of oxygen concentrations (solid circles and solid curve). Also shown is a prediction of this effect based on a linear interpolation and addition of the previously determined pure CO and pure H₂ effects (open circles and dashed curve). These data show that, within experimental error, the effects of this CO/H₂ mixture can be accurately predicted based on the linear addition of pure component effects. This would be helpful in predicting real selectivities and yields in a true recycle operation. Based on these findings, a computer program is being written to simulate the effects of reactor recycle on product selectivity and yield.

As with pure CO and H₂ addition, hydrocarbon and methane conversion are not affected by the presence of the mixture (Figure 9). Since methanol selectivity decreases and hydrocarbon conversion is unaffected, there is an overall decrease in methanol yield with the addition of CO/H₂, as shown in Figure 10.

The decrease in methanol selectivity observed in Figure 8 is accompanied by an increase in CO₂ selectivity (Figure 11) and a decrease in net CO selectivity (Figure 12). These data consistently show that the presence of CO in the

Figure 9

Effect of Recycle on Feed Conversion

T=800F; P=1300 psig, RT=40 sec.

Hydrocarbon Conversion (mol%)

Figure 10

Effect of Recycle on Methanol Yield

T=800 F; P=1300 psig; RT=40 sec.

Methanol Yield (mol%)

Figure 11

Effect of Recycle on CO₂ Selectivity

T=800F; P=1300 psig; RT=40 sec.

Carbon Dioxide Selectivity (mol%)

Neat feed

Figure 12

Effect of Recycle on CO Selectivity

T=800F; P=1300 psig; RT=40 sec.

Carbon Monoxide Selectivity (mol%)

reactor results in much higher CO₂ selectivity, and that the increase in CO₂ selectivity is directly related to the concentration of CO in the feed.

These results, combined with the results from the pure component spiking studies, offer strong evidence that adding recycle to the reactor system would have a significant negative impact on methanol selectivity and yield. Selectivity to carbon dioxide would increase significantly, while hydrocarbon and methane conversion would be unaffected by the addition of a recycle stream.

The Project Management Plan calls for a decision point at the end of these recycle simulation studies. The option to modify the plant to add true recycle capability was left open in the Management Plan in the event that the recycle simulation experiments looked promising. Based on the findings described above, we have decided that it would not be advisable to modify the plant to add reactor recycle capability.

Effect of Catalyst Post-Bed (Task 3.7): One method that has been proposed for increasing the overall yield of methanol from this system would be to use a catalyst post-bed to convert some or all of the CO formed in the partial oxidation reaction. This catalyst bed would be placed downstream of the thermal conversion zone. Several series of runs have been made in our pilot plant to test such a process, the preliminary results of which are presented here. A complete analysis of the data will be presented in next month's report.

Figure 13 shows the reactor configuration used in these studies. The catalyst used was a commercial Cu/ZnO/Al₂O₃ methanol synthesis catalyst from UCI. Several preliminary runs were made to determine the furnace settings in the thermal zone that would provide typical methanol synthesis temperatures of 450-500°F at the inlet of the catalyst bed. A standard methanol catalyst activation procedure was followed consisting of stepwise reduction in flowing H₂/N₂ mixtures of increasing H₂ concentration (between 1-20 vol%) and at increasing temperatures (between 380 and 470°F). Tests performed in a separate syngas conversion reactor confirmed that these activation procedures produced an active methanol synthesis catalyst.

Previous tests have shown that the gaseous product from the thermal zone of the reactor contains significant amounts of carbon monoxide, but very little hydrogen. Since the methanol synthesis catalyst requires a mixture of hydrogen and carbon monoxide, a number of runs were made in which hydrogen was added to the reactor feed in varying amounts. The effect of the catalyst post-bed on overall methanol selectivity is shown in Figure 14. While there is some scatter in the data, it does not appear that the presence of the catalyst post-bed increases methanol selectivity. Even when up to 25 vol% hydrogen was added to the reactor feed (resulting in an estimated H₂/CO ratio of 5.5 at the catalyst bed inlet), there appears to be no net conversion of carbon monoxide to methanol in the catalyst bed. In fact in some cases the methanol selectivity is actually lower when the catalyst post bed is present. Calculations are currently being made to determine the thermodynamic limits governing this unconventional system. It is possible that some of the

FIGURE 13

FIGURE 14

Effect of Catalyst Post-Bed on MeOH Selectivity

T=725 F/ P=1300 psig/ Res. Time=60 sec.

methanol being formed in the thermal zone is actually being decomposed to CO and H₂ in the catalyst bed.

As expected, hydrocarbon and methane conversion were unaffected by the presence of the catalyst post-bed. The overall methanol yield (Figure 15) was also unchanged by the presence of the catalyst post-bed. From these results we can conclude that, with this reactor configuration, adding a catalytic post-bed does not improve overall methanol selectivity or yield. As mentioned, further analysis of the data is taking place in order to more fully understand this complex system.

CONCLUSIONS

Four conclusions can be drawn from the above results:

1. Adding carbon monoxide to the feed at levels between 3 and 20 vol% has a negative impact on methanol selectivity, but no significant impact on methane or hydrocarbon conversion.
2. The effects of added CO and H₂ on the system appear to be additive. That is, the effect of mixtures of added CO and H₂ can be reasonably predicted by linear addition of the pure component effects.
3. The results of the reactor recycle simulation studies offer strong evidence that adding recycle to the reactor system would have a significant negative impact on methanol selectivity and yield. Selectivity to carbon dioxide would increase significantly, while hydrocarbon and methane conversion would be unaffected.
4. The enhanced yield studies indicate that, with the reactor configuration used, adding the catalytic post-bed does not improve overall methanol selectivity or yield. The existence of thermodynamic limitations is being investigated.

ACKNOWLEDGEMENT

This work was supported by the United States Department of Energy under Contract DE-AC22-89PC89866.

FIGURE 15

Effect of Catalyst Post-Bed on Methanol Yield

T=725 F/ P=1300 psig/ Res. Time=60 sec.

NOTICE

This report was prepared by the organization(s) named below as an account of work sponsored by the United States Department of Energy (DOE). Neither DOE, members of DOE, the organization(s) named below, nor any person acting on behalf of any of them: (a) makes any warranty, express or implied, with respect to the use of any information, apparatus, method, or process disclosed in this report or that such use may not infringe privately owned rights; or (b) assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method, or process disclosed in this report.

Prepared by
Amoco Oil Company (Amoco Corporation)
Naperville, Illinois

MJF/sjm/doe9126
10/31/91

END

**DATE
FILMED**

8 / 19 / 92