27/2-9-90 JS ①

Programs In Renewable Energy

Fiscal Year 1990

U.S. Department of Energy

**DO NOT MICROFILM
COVER**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

This document describes research in FY 1990 sponsored by the Renewable Energy Programs of the U.S. Department of Energy. Summaries of the programs' accomplishments during FY 1989 are available as two-volume sets for each of the following programs:

- Energy Storage and Distribution
- Solar Buildings
- Solar Thermal Energy
- Biofuels
- Geothermal Energy
- Photovoltaic Energy
- Wind Energy
- Ocean Energy

For each program, *Volume I: Overview* contains a short overview of the program; *Volume II: Research Summaries* contains detailed descriptions of each research project. Copies of any of these documents may be obtained by writing:

Solar Energy Research Institute
Technical Inquiry Service
1617 Cole Blvd.
Golden, CO 80401-3393

Programs in Renewable Energy: FY 1990

**Message from
Dr. Robert L. San Martin,
Deputy Assistant
Secretary for
Renewable Energy**

Our nation faces significant challenges as we enter the 1990s: securing a reliable supply of competitively priced energy, improving the quality of our environment, and increasing our share of foreign markets for goods and services. The U.S. Department of Energy's (DOE) Programs in Renewable Energy are working toward meeting these challenges by developing the technologies that make use of our nation's largest energy resource: renewable energy.

The sunlight, wind, biomass, flowing water, ocean energy, and geothermal energy that make up the renewable energy resource can be found throughout our nation. These resources can provide all the forms of energy our nation needs: liquid fuels, electricity, and heating and cooling. Renewable energy meets about 10% of our need for these forms of energy today, yet the potential contribution is many times greater.

DOE's Programs in Renewable Energy are working side-by-side with American industry to develop the technologies that convert renewable energy resources into practical, cost-competitive energy. After a decade of progress in research, several of these technologies are poised to make large contributions during the 1990s and beyond.

This booklet provides an overview of the renewable energy programs and their plans for FY 1990. Sources of additional information are listed at the back of the booklet.

Contents

Introduction	2
Transportation Fuels	
Biofuels	7
Utilities	
Photovoltaic Energy	13
Geothermal Energy	18
Electric Energy Systems	22
Energy Storage Systems	26
Solar Thermal Energy	28
Wind Energy	31
Ocean Energy	35
Heating, Cooling, and Lighting	
Solar Buildings	38
Cross-Cutting Programs	
International Solar Energy Program	41
Resource Assessment	43
Technology Transfer	45
Solar Energy Research Institute Facilities	47
Information Contacts	48

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Introduction

A reliable supply of energy is critical to maintaining our economy, our national security — our way of life. The U.S. Department of Energy (DOE) is charged with ensuring that the scientific and technical knowledge is in place to provide for that energy supply today and in the future. DOE's energy programs support several specific goals:

Ensuring energy security

Maintaining and improving the environment

Promoting health and safety

Enhancing U.S. competitiveness in world markets.

DOE sponsors research programs aimed at utilizing our nation's extremely large resources of renewable energy. These Renewable Energy (RE) Programs contribute to all of DOE's goals. First, the size and distribution of the RE resource make it a natural choice for ensuring energy security —

Renewable energy makes up 92% of our nation's accessible energy resource base, which is defined by the U.S. Geological Survey as those resources "that can be located, mined, or extracted using technology that is currently available or that will be available within 3 to 5 years."

we have more than we need entirely within our boundaries. Second, RE systems produce little pollution. In fact, in some cases RE systems can actually reduce existing pollution by extracting carbon dioxide from the atmosphere or by destroying toxic chemicals. Third, RE technologies promote the health and safety of the public and of workers because few toxic products result from their manufacture or use. Finally, RE systems offer a special export opportunity for U.S. industry because of the critical need for new supplies of affordable energy in developing countries.

A Decade Of Progress

The decade of the 1980s saw significant strides in the advancement of RE technologies. Cost and performance goals set in the 1970s have been met or exceeded in all the RE programs. Equipment costs have dropped by half or more, and efficiencies have doubled or tripled. With continued success in research and development, several technologies will likely see widespread application in the transportation, electricity, and heating and cooling markets during the next five to ten years.

Transportation Fuels

Source: Energy Information Administration

Imports of petroleum will comprise 40% of our petroleum use in 1989, the highest since 1979.

One of our nation's most pressing energy needs is for liquid transportation fuels. In spite of today's low prices, our dependence on foreign oil leaves us vulnerable to disruptions in supply. Imports of oil are expected to comprise 40% of our total consumption for 1989 — the highest since 1979. In addition, conventional fuels are a major source of air pollution in our cities and of carbon dioxide accumulation in the atmosphere.

Biofuels — liquid fuels made from trees, plants, and wastes — offer us a domestic source of transportation fuels. Biofuels can also help clean up urban air pollution because they are clean burning. And because trees and plants absorb as much carbon dioxide while they grow as the resulting fuels produce when they are burned, biofuels can help slow the accumulation of atmospheric carbon dioxide.

The primary biofuel available today is ethanol made from corn. In 1989, domestic ethanol production capacity topped 1.1 billion gallons. Program research is developing the technology for growing biomass as an energy crop and converting it to ethanol, methanol, gasoline, and diesel fuel.

Utilities

Today we have a surplus of electricity, but most predictions show that this situation will change by the mid-1990s. Yet, decisions to begin construction of new capacity are being delayed by regulatory uncertainties and recent environmental concerns.

Several RE technologies can help meet this need:

Photovoltaic systems convert sunlight directly to electricity using solid state materials and technology.

Geothermal systems extract the heat of the earth to power conventional or improved electric generating equipment.

Solar thermal systems concentrate the sun's radiation to heat working fluids that drive conventional electric generating equipment.

Wind energy systems convert the energy in the wind into electricity using rotating turbines.

Ocean energy systems use the temperature difference between the surface and the depths of the ocean to vaporize a fluid, which drives electric generating equipment.

Nearly all of these technologies are contributing electricity to our nation today, although in most cases, large-scale application is still several years away. DOE-sponsored research is helping to bridge this gap through research programs in each technology.

RE systems have inherent advantages for electricity generation. In particular, these systems are modular in nature, allowing utilities to add capacity in step with changes in demand and without long lead times. In addition, RE systems are environmentally sound, because they are virtually free from sulfur or carbon dioxide emissions. And although some forms of the renewable energy resource are intermittent, peak outputs tend to match periods of peak demand experienced by utilities.

*Existing plants plus plants under construction minus retirements.

Projections show that the United States will need large quantities of new electric generating capacity by 2000.

Programs in **energy storage (ES)** and **electric energy systems (EES)** are developing new technologies to make the production, distribution, and use of electricity more efficient. For example, recent breakthroughs in the development of high-temperature superconductors promise to revolutionize the distribution and use of electricity. And research on batteries and fuel cells for electric vehicles could help to expand the practicality of this form of transportation. In addition, by storing electricity in advanced batteries, utilities can meet peaks in demand without adding new generating capacity.

Buildings

The energy requirements of our homes and buildings account for about one-third of our nation's energy use. DOE-sponsored research on solar buildings integrates the age-old use of sunlight with new technologies for building design, heating, cooling, and daylighting. Builders can now reduce energy consumption by up to 40% without substantially increasing the building cost.

Program research continues to develop new materials and advanced building components that should further improve the energy performance and reduce the cost of buildings. These new technologies should allow the building of

2001 to get up to 80% of its energy from the sun. Widespread adoption of these technologies could help ease any future shortage of electricity or fossil fuel.

A Focus On Goals

DOE's RE programs are designed to expand the contributions the technologies can make to our nation through basic and applied research and through cooperative development projects with industry. Progress in the programs is measured against specific cost and efficiency goals set for the near, mid, and long term. During the last several years, the programs have focused carefully on the technologies that have the highest chance of success.

Progress has been achieved through the combined efforts of the national laboratories, universities, and private industry, along with DOE Headquarters. The DOE Headquarters staff provides central management to ensure that program activities are consistent with national energy policy and priorities. Management of technical activities is decentralized among various DOE Field Offices, the Solar Energy Research Institute (SERI), and national laboratories. This approach makes technical expertise available for supervising research.

	Biofuels	PV	Geo	EES	ES	Solar Thermal	Wind	Ocean	Solar Bldgs	RA	Tech Tran
Argonne National Laboratory				•				•			
Brookhaven National Laboratory		•									
Los Alamos National Laboratory			•	•							
Lawrence Berkeley Laboratory					•				•		
Oak Ridge National Laboratory	•			•							
Pacific Northwest Laboratories							•				
Solar Energy Research Institute	•	•				•	•	•	•	•	•
Sandia National Laboratories		•	•		•	•	•				•

Laboratories across the country conduct research on renewable energy technologies. The table shows the laboratories that have primary responsibility for the renewable energy programs.

A Partnership With Universities And Industry

A high level of interaction with universities and private industry is a vital element of the RE programs. The programs support postdoctoral appointments, graduate student research, and collaborative research, thereby playing an active role in helping to ensure an adequate supply of scientists and engineers for our nation's future. And by involving private industry in sub-contracted research, advisory boards, and research consortia, the programs make sure that the research is pertinent to industry needs. The interaction also increases the chance that successful research will be adopted quickly by the private sector.

Government-sponsored research has led to many new businesses — even whole new industries — that are putting renewable energy to work. Since 1974, sales of U.S. renewable energy products and services have totaled more than \$1 billion. This emerging industry will surely grow as the research programs continue to build the foundation for technological advances.

A Look To The Future

During fiscal year (FY) 1990 and beyond, DOE's RE programs will focus on the technologies that can make a contribution to our energy supply. Plans for FY 1990 are presented for each program in the following pages. Within each program, descriptions of FY 1990 research are organized by key activity.

Renewable Energy Program Funding: FY 1990

Program	Appropriation (Million \$)
Biofuels	16.2
Photovoltaic Energy	34.7
Geothermal Energy	18.1
Electric Energy Systems	17.7
Energy Storage	12.3
Solar Thermal Energy	15.0
Wind Energy	9.1
Ocean Energy	4.1
Solar Buildings	4.1
International Solar Energy Program	1.0
Technology Transfer	1.8
Resource Assessment	0.8
Solar Energy Research Institute	0.6
Program Direction & Support	6.6
Total Renewable Energy Funding	142.1

Biofuels: Transportation Fuels

Biofuels are solid, liquid, or gaseous fuels derived from trees, plants, or wastes (biomass). Today, biofuels provide energy to all sectors of our economy, primarily in the form of heat from combustion of wood or industrial wastes. In fact, biofuels provide about 4.5% of our nation's energy supply.

The Biofuels Program is developing technologies to make ethanol, methanol, gasoline, and diesel fuel from trees, plants, and wastes.

Biofuels technologies are unique in their ability to provide liquid transportation fuels from renewable resources, and this is the area of greatest potential. Today's liquid biofuel industry is based on age-old technology for making ethanol from corn. But ethanol and other fuels such as methanol, gasoline, and diesel fuel can be made from non-food crops as well. These "energy crops," such as trees, forage crops, aquatic algae, and municipal wastes, have the potential for being less expensive than food crops and avoid the possibility of competition between food and energy uses of grains. Technologies for growing energy crops and converting them to biofuels are the focus of the Biofuels Program.

Research Direction

The projected price of biofuels has dropped dramatically since the program began its research in the 1970s.

For our nation to develop a major biofuels industry, two basic technologies must be available. First, we must be able to grow appropriate biomass feedstocks in large quantities and at low costs. And second, we must have efficient, cost-effective processes for converting the feedstocks to liquid fuels. The Biofuels Program is working with industry to develop both of these basic technologies and has made significant progress since its inception in 1978. Wholesale prices for several biofuels would range from \$1.35 to \$1.90 per gallon equivalent of gasoline using today's technology. Prices projected for 2000 are less than \$1.00 per gallon equivalent of gasoline.

Research on biomass production, or growth, is aimed at selecting and genetically improving trees and crops specifically for energy production. Poplar, black locust, and forage grasses are examples of the variety of biomass that scientists are working to develop into major energy crops. Through laboratory research and field trials, researchers are increasing crop yields and lowering costs.

For FY 1990, conversion research is focused on biochemical and thermochemical technologies that produce four liquid fuels: methanol, ethanol, gasoline, and diesel fuel. In addition, research on hydrogen production supports the methanol research, because hydrogen is needed for methanol production. The program also supports research on producing biogas, a gaseous fuel that can be used directly or converted to methanol.

The primary emphasis of the program is on the alcohol fuels — methanol and ethanol. These are believed to have the greatest potential for providing transportation fuels in the 1990s. Alcohol fuels also have significant environmental benefits, including high oxygen content, low sulfur content, and high octane, which result in less air pollution and better vehicle performance. Research on gasoline, diesel fuel, and biogas is being maintained with a lower level of funding than is devoted to the alcohol fuels.

FY 1990 Activities

Terrestrial Crops

Developing species and techniques for producing energy crops is critical to the expansion of the biofuels industry. For widespread competitiveness of biofuels, crops must be tailored specifically to individual conversion processes. These crops can then be grown on marginal or excess cropland, providing another source of income for farmers and other landowners.

During FY 1990, researchers will continue to develop short-rotation woody crops using poplars and, to a lesser extent, black locust, silver maple, and sycamore. Through genetic selection and engineering, scientists will tailor

This aerial photograph shows a test site for hardwood trees in short-rotation intensive culture. Different clones of hybrid poplar are planted with different spacings.

these species to have characteristics that are advantageous for conversion processes. In addition, laboratory and field tests will lead to new crop management techniques (silviculture) for improving weed control, herbicide tolerance, and pest management. Also in 1990, a collaborative project with industry will continue single-species field trials begun last year on a 50-acre site in Iowa. Cost and productivity data from the tests will help expand the Short Rotation Data Base at Oak Ridge National Laboratory.

The program will also support research on herbaceous crops such as grasses and shrubs. New genetics research will build on field tests that selected optimum species for the Midwest and Southeast. Tests will continue to identify species for the Great Plains region. Field trials of sorghum, switchgrass, and subtropical grasses will also continue on a small scale. In addition, researchers will conduct studies to quantify the potential resource, to develop a herbaceous crop data base, and to analyze possible effects of energy crops on farm finances and soil erosion.

Field tests of promising varieties of shrubs and grasses help scientists to optimize energy crops. The switchgrass shown in the photo is in year 3 of a 5-year test.

A small effort will continue to develop certain oilseed crops, particularly rapeseed. Oils from these seeds can be extracted and converted to diesel fuel. During FY 1990, rapeseed variety trials in the Southeast will be completed, and the results will be released to industry. In addition, laboratory researchers will use genetic techniques to try to modify the rapeseed plant to make an oil that resembles diesel fuel more closely.

Ethanol

Scientists can use a variety of biologically based processes to convert biomass to fuels. The Biofuels Program focuses on one of these in particular: biochemical conversion of biomass to ethanol.

Wood and grass have three main components: cellulose, hemicellulose, and lignin. Both cellulose and hemicellulose are made up of long chains of sugar molecules, which can be converted to ethanol. The first step of the process is to pretreat the wood to separate the hemicellulose and break it down to individual xylose sugars. The cellulose is then treated separately to break it down to glucose. The glucose can be fermented using technology similar to that used to make beverage alcohol. Applying these process steps on a large scale will require improvements in efficiencies and economics.

The most promising approach for converting the cellulose to ethanol combines a process called enzymatic hydrolysis with fermentation. Enzymatic hydrolysis uses enzymes — biological catalysts — to break down the cellulosic chains to sugar. During FY 1990, scientists will continue research on improving the efficiency of converting biomass to ethanol through process optimization and studies of enzyme recycling. They will also continue research on an enzymatic process to convert xylose to xylulose, a sugar that is more easily fermentable to ethanol. In addition, scientists will explore using lignin, the third major component of biomass, as a process fuel or converting it to high-octane blending agents such as methyl- or ethyl-aryl ether.

A researcher draws a sample from a simultaneous saccharification and fermentation (SSF) reactor. The SSF process is one of the most promising for making ethanol from biomass.

Biogas

The program is developing another biochemical process, anaerobic digestion, that produces biogas, a mixture of methane and other gases. Both agricultural and municipal wastes are suitable feedstocks for anaerobic digestion. The resulting biogas can be burned as a boiler fuel, used to operate engines, or cleaned up for use in natural gas pipelines. It can also be converted to methanol. Anaerobic digestion has potential for helping our nation dispose of the millions of tons of solid wastes generated each year.

Anaerobic digestion is a near-term technology, and program research aims to resolve the few remaining obstacles to commercial development. During FY 1990, researchers will complete laboratory tests of a novel high-solids reactor that will allow the process to generate biogas at higher rates and in larger quantities than ever before. Research will also continue on photo-enhanced processes that use photosynthetic bacteria to speed reaction rates.

Methanol

Scientists can also use thermochemical processes to make biofuels. The main focus of thermochemical research is on gasification, a process that converts biomass to syngas, an intermediate fuel that can be converted to methanol.

Syngas is mainly a mixture of carbon monoxide, hydrogen, and carbon dioxide. Like biogas, syngas can be burned directly or cleaned up for pipeline use, in addition to being used as a precursor to methanol. Earlier research on gasification resulted in several gasifier designs for making syngas, but challenges remain in converting the syngas to methanol. Program-sponsored research aims at meeting these challenges in the next few years, resulting in cost-competitive methanol by the mid-1990s.

Research in FY 1990 will focus on cleaning and conditioning the raw syngas to make it suitable for commercial methanol synthesis. Scientists will test several catalysts that show potential for the process. Research will also address other aspects of syngas processing.

This gasifier is one of several designs capable of producing syngas, which can be converted to methanol.

Gasoline

Biomass can be converted to gasoline by another thermochemical process known as pyrolysis. The reaction transforms the biomass to an oil called biocrude at temperatures of 450°-500°C. The biocrude can be converted catalytically to a gasoline-type hydrocarbon. Researchers have made significant progress in improving the process. When research began in the 1970s, efficiencies were below 20%; today they are around 60%. FY 1990 research will continue this progress with scientists at SERI testing several catalysts and determining optimum operating conditions for the process.

Diesel Fuel

Under certain conditions, microalgae produce oils, or lipids, that can be extracted and upgraded to diesel fuel. These microscopic aquatic plants thrive in salty ponds located in desert environments; they also need large quantities of carbon dioxide to grow and produce lipids. These factors make them a promising option for recycling the carbon dioxide emissions from the large power plants in the southwestern states into diesel fuel. Research in recent

years has identified several promising strains of microalgae and has improved their growth rates and lipid yields through genetic selection. During FY 1990, scientists will continue to test several of these strains in outdoor ponds and will evaluate the performance of the SERI outdoor test facility in Roswell, N. Mex.

Hydrogen

Production of hydrogen from renewable resources is important to the program because making methanol from syngas requires a supply of hydrogen. Research during FY 1990 will continue to explore photo-electrochemical and photobiological processes for producing hydrogen. Photoelectrochemical systems under study use semiconductors to generate the hydrogen; photobiological processes use microorganisms, such as algae, to produce the gas. In addition, scientists will focus on high-efficiency, low-cost processes for splitting water to make hydrogen. Electrolysis at intermediate temperatures (200°-400°C) is particularly attractive for this application. Scientists will also continue work on alternative storage systems such as adsorption of hydrogen on modified activated carbon.

Regional Biomass Energy Programs

Five regional programs provide an important technology transfer mechanism between the federal biomass program and industry. The programs work through state energy offices to help move the technologies that are commercially ready into the marketplace. In FY 1990, the programs will continue to sponsor regionally specific activities that involve resource assessments, technical support, and co-funded demonstration projects to help industry develop local biomass resources and applications.

This large-scale vortex reactor can pyrolyze 100 lb of biomass per hour, allowing researchers to optimize the process for producing gasoline directly.

Photovoltaic Energy: Utilities

Photovoltaic (PV) energy systems convert sunlight directly into electricity using solid state (semiconductor) materials and technology. Today's commercial PV solar cells are most often made of extremely pure crystalline or amorphous silicon with microscopic quantities of certain additives that induce the photovoltaic effect. This "doped" silicon is processed into thin wafers or sheets only micrometers thick. Photovoltaic modules are made by connecting these cells in parallel or in series to produce incremental amounts of electricity. Likewise, arrays of PV modules are connected to provide even greater amounts of electric energy. These photovoltaic building blocks, combined with power conditioning equipment, form the basis for all PV energy systems.

Initially used by the space program to power communications satellites, PV has come down to earth with the help of the National Photovoltaics Program. Envisioning a potential for a safe, clean, and nationally secure energy source, the program has supported advanced research and development during the last decade in cooperation with U.S. industry, universities, and utilities. The investment from both federal and private sources has had results. Sunlight-to-electricity conversion efficiencies for laboratory PV cells have increased from 4.0% to 14.6% for thin-film materials, and industry reports efficiencies as high as 37.0% for crystalline gallium arsenide cells under concentrated sunlight. Today's photovoltaic systems provide cost-effective electricity for remote power and some electronics applications. More than 40 megawatts of PV modules were shipped worldwide in the last year alone.

Photovoltaic systems use semiconductor materials and technology to convert sunlight directly to electricity.

Research Direction

The National Photovoltaics Program sponsors research aimed at the goal of producing PV electricity at a cost of \$0.06/kWh for bulk power markets (electricity from PV today costs about \$0.25-\$0.30/kWh). To achieve this goal, the program conducts research and development in a variety of PV technology areas, thereby increasing the overall probability of success. Through research on materials and devices (solar cells), modules, complete systems and their components, the program helps to develop the foundation for a strong photovoltaics industry in the 1990s. Even today, industry is using the results of program research to develop PV manufacturing facilities for systems believed to offer a path to commercial success.

The United States is today's world leader on all fronts of research in photovoltaic technology. The strategy of the Photovoltaics Program is to maintain this leadership role in advanced research and development. A well-rounded fundamental and applied research program is essential to advance the PV technology base further and to make PV cost competitive with other forms of utility-scale power generation. Continuing the program's initiative to conduct cost-shared research with industry will ensure effective transfer of the technology and allow the U.S. PV industry to maintain its role in the world marketplace.

Long-Term (Year 2000) Technical Goals (1986 dollars) Based on a levelized electricity cost of 6¢/kWh		
	Flat-plate systems	Concentrator systems
Module efficiency at 25°C	15%-20%	25%-30%
Module cost	\$45-\$80/m ²	\$60-\$100/m ²
Balance-of-system costs		
— area-related	\$50-\$100/m ² *	\$125/m ²
— power-related	\$150/kW	\$150/kW
System life expectancy	30 yr	30 yr
* Balance of system costs vary depending on the type of flat-plate system (fixed, one-axis, or two-axis tracking).		

But fundamental research activities are only the first step. The U.S. PV industry is at a pivotal point in developing markets for its products. The National Photovoltaics Program provides market development assistance through such activities as PVUSA (Photovoltaics for Utility-Scale Applications) and CORECT (the Committee on Renewable Energy Commerce and Trade, see p. 41). By promoting PV within other government agencies (such as the Department of Defense and the Environmental Protection Agency) and providing industry and others with assistance through places like the Design Assistance Center at Sandia National Laboratories (SNL) and SERI's laboratory user facilities, the program is taking an important second step in furthering the application of photovoltaic technologies.

FY 1990 Activities

Advanced Thin-Film Materials

Development of advanced thin films is aimed in two directions. Research on amorphous silicon (a-Si) and polycrystalline materials offers the potential of low materials and manufacturing costs but moderate overall efficiency. On the other hand, single-crystal thin films offer higher efficiency, along with

This 41-ft x 44-ft silicon concentrator system, built by Alpha Solarco, Inc., and Solectric Corp., uses sophisticated technology developed at Sandia National Laboratories in Albuquerque, N. Mex.

higher costs. Both of these options offer potential paths to commercial success, and research will continue in both areas during FY 1990.

The success of the program's amorphous silicon research is evidenced by the recognition it has received during the past year. In 1989, the Federal Laboratory Consortium recognized the amorphous silicon government/industry cost-shared program for Excellence in Technology Transfer to Industry. Award-winning research in this area will continue, with another cost-shared program beginning in 1990. Efficiencies in amorphous silicon are now over 13% for laboratory cells as a result of these cooperative efforts, and the new initiative should push them up even further — to 15% for a 1-cm² multijunction amorphous cell and to 11% for a 900-cm² multijunction module. Research will also be directed at stability and fabrication issues such as deposition techniques and the development of alloys. This program will provide industry with the knowledge necessary to develop large multijunction modules that are stable, reliable, inexpensive, and easily processed and manufactured.

Program researchers will also continue to improve the performance of polycrystalline thin films through subcontracted and cost-shared research. In 1989, the efficiencies of small laboratory cells of copper indium diselenide (CIS) surpassed 13% and cells of cadmium telluride (CdTe) were not far behind. Efforts to increase these efficiencies will continue in 1990, and a cost-shared initiative for developing modules using these polycrystalline materials will begin. CIS has proven to be extremely stable (after more than 9000 hours of testing under controlled illumination). Further monitoring of CIS and other polycrystalline materials, including CdTe, will continue in 1990.

Single-crystal gallium arsenide (GaAs) showed promise in the advanced thin-film materials arena during 1989. Displaying high stability, efficiencies for these cells stand at 22.4% for thin films and 24.8% for conventional cells. In FY 1990, scientists will continue to develop GaAs devices by issuing proposals for cost-shared research on crystal growth and fabrication processes.

SERI scientists have developed an ultra-high efficiency gallium indium phosphide/gallium arsenide multijunction solar cell. The cell has achieved a 27.3% efficiency and has the potential for surpassing 30% efficiency.

High-Efficiency Materials

In FY 1990, DOE researchers will explore alternative methods in cell design and processing of crystalline silicon (Si) and GaAs. Specific activities will be to develop lower cost substrates and processing techniques necessary for large-scale manufacturing. Research aimed at developing single-junction and multijunction concentrator devices using Si and GaAs will also continue. During 1989, conversion efficiencies for a module-ready Si concentrator cell reached as high as 27.2%. In FY 1990, competitive awards will be made for fundamental research on ultra-high efficiency cells, and a request for proposals will be issued for cost-shared development of fabrication processes.

Fundamental Materials Research

Accurate efficiency, reliability, and performance measurements are essential in photovoltaic research. In FY 1990, research will continue on developing improved solar radiation models, software, and instrumentation. One example of this research is the development at SERI of the R&D 100 award-winning spectroscopic scanning tunneling microscope (SSTM). The SSTM enables researchers to see individual atoms and defects in materials. Researchers will continue to work with industry to license another SERI invention, the Atmospheric Optical Calibration System.

Materials analysis will continue to expand our basic understanding of photovoltaic materials. High resolution transmission electron microscopy and sub-picosecond lifetime measurements of electric charge carriers are a part of this research and help to accelerate progress on solar cell efficiencies. The state-of-the-art measurement and analysis laboratories at SERI and SNL are made available to industry through the "user facilities." These facilities expect to provide more than 12,000 measurements and analyses for about 120 different PV organizations during 1990.

Collector Research

Program-sponsored collector research involves both flat-plate and concentrator module efforts. In FY 1990, flat-plate module research will be directed at continued improvements in cell performance and stability and module reliability. Scientists are also working to provide design criteria for achieving the DOE goal of a 30-year module lifetime (currently at 10-20 years). Tests of high-efficiency PV cells under concentrated sunlight have yielded excellent performance — 28% for Si, 29% for GaAs, and 31% for a multijunction (unconfirmed reports of a 37%-efficient multijunction cell have also been issued). In FY 1990, the program will build on these successes through cost-shared development of concentrator modules and systems. Through close interactions with the PV community, industry standards groups, and the nation's utility companies, program personnel will transfer the results of these efforts to the private sector.

Systems Research

Improving PV system performance and cost is the focus of this key activity. Personnel at SNL's Design Assistance Center will provide technical assistance directly to PV users. In addition, program researchers will work closely with industry, electric utilities, and other federal and local government agencies to encourage the application of PV for high-value applications such as remote off-grid electrification and intermediate- and large-scale power generation.

PV applications will be encouraged through public/private partnerships such as the PVUSA project in Davis, Calif. Spearheaded by Pacific Gas and Electric and partially funded by DOE (40%), the effort is a demonstration project with utilities, designed to evaluate PV system performance for

PVUSA (Photovoltaics for Utility-Scale Applications) is a joint project between DOE, Pacific Gas and Electric, and several PV manufacturers. In FY 1990, testing of demonstration systems will begin, using different cell materials and configurations.

large-scale power generation. Seven PV manufacturers are supplying complete systems using different cell materials and system designs. Upon completion, PVUSA will be a comprehensive display of the state of the art in photovoltaic systems that can be scaled up for utility use. Installation of the systems will begin in FY 1990.

Geothermal Energy: Utilities

Geothermal energy systems use the heat of the earth to generate electricity.

Geothermal energy is generated by the heat within the earth. Geothermal resources exist in four forms: hydrothermal (steam and hot brine), geopressured brine (hot brine under high pressure containing dissolved natural gas), hot dry rock, and magma (molten rock). Hydrothermal is the only resource being used commercially today. Low- to moderate-temperature hydrothermal liquids (50°-150°C) are used directly for space heating and industrial processes. Steam and high-temperature liquids provide more than 2750 MW of electricity in the western states. The other resources could be used in similar fashion, and geopressured brines could produce natural gas as well. The Geothermal Energy Program supports research and development of all four types.

Research Direction

Industry now has significant experience using the hydrothermal energy resource, particularly in California. But several technical barriers prevent its widespread development. The principal barriers include the difficulty of locating reservoirs and confirming their potential; the high cost of drilling wells into hard, hot rocks; the inefficiency of systems that convert moderate-temperature heat to electric power; the chemical reactivity of brines; and the uncertainty surrounding the practice of injecting spent fluids into the ground. The Geothermal Energy Program has placed a high priority on research designed to resolve these difficulties so that development of the nation's geothermal resource can move forward.

Research on the advanced technologies to use our resources of geopressured brines, hot dry rock, and magma is under way as well. In these cases, field experiments are assessing the feasibility of the processes and identifying the technical problems. Supporting research in geoscience and materials science is developing techniques to identify reservoirs and to recover the energy contained in them. With continued research, these technologies should become competitive around the turn of the century.

Objectives of the Geothermal Program

(constant 1986 \$)

Technology	Cost Goal (¢/kWh)	Year
Hydrothermal	3-7	1997
Geopressured Brine	6-10	1997
Hot Dry Rock	5-8	1997
Magma	10-20	2000

FY 1990 Activities

Hydrothermal: Reservoir Technology

Research on reservoir technology aims to minimize the risks associated with finding and developing hydrothermal resources. For example, existing exploration techniques are often difficult to apply in regions of recent volcanic activity, leaving potentially large resources undiscovered. And the effects of fluid injection and reservoir pressure declines on long-term production are still uncertain. FY 1990 research will address these issues in cost-shared projects at The Geysers, a dry steam field in California, and elsewhere. Specifically, projects will include pressure maintenance studies, development of new fluid injection techniques, and field tests of new exploration technology.

The Geothermal Technology Organization, a consortium of DOE and members of the geothermal industry, will continue its role in jointly sponsored reservoir research. A new project in FY 1990 will monitor seismic response to injection of fluids in wells at the Coso field in California.

Hydrothermal: Conversion Technology

The elevated temperatures and the scaling and corrosion potential of geothermal liquids create problems for energy conversion and waste disposal systems. In FY 1990, research will use three approaches to solving these problems. First, scientists will continue to develop materials that resist corrosion. Specific activities will include field testing of carbon dioxide-resistant cements and analyzing the performance of heat exchanger tubes lined with a polymer-concrete composite. Scientists will also expand the understanding of the complex chemistry of mineral-laden hydrothermal liquids by developing a computer model that will predict scaling rates for specific thermodynamic conditions. Finally, scientists will work to improve the efficiency of energy conversion systems, which are currently well below theoretical limits. Performance tests on mixed working fluids in supercritical cycles will help to improve the efficiency of systems using moderate temperature brines.

Advanced energy conversion concepts are tested at the Heat Cycle Research Facility, an experimental 60-kW binary cycle unit.

Hydrothermal: Hard Rock Penetration

Wells to extract and inject geothermal fluids account for some 30% to 50% of geothermal power plant costs. Program research seeks to reduce these costs. One area of research addresses circulating fluid loss, a costly problem that occurs when the fluid used to cool and lubricate the drill bit is lost into unexpected fractures or voids in the earth. In FY 1990, researchers will verify circulation models and field-test materials to plug loss zones. Scientists will also test a new, insulated drill pipe that will protect the drilling equipment from the intense heat of geothermal environments. In addition, researchers will bench-test new instruments for transmitting data from the bottom of the well to the surface during drilling operations.

Above — Wells, such as this one being drilled at The Geysers, are used to test fluid injection technology.

To the left — The radar fracture mapping tool will help to detect optimal areas of fluid production.

Geopressured Brines

The energy in geopressured brines can be tapped using modified oil and gas technology. Methane dissolved in the brine can be separated and burned on site in power production facilities to augment the heat of the brine. But major uncertainties about the resource exist, including the sustainability of production, the methane content of the brine, and the lifetime of the reservoir.

During FY 1990, long-term flow tests of the Pleasant Bayou well in Texas should result in data on the response of a geopressured reservoir to production conditions. Operation of a hybrid 1.2-MW_e power system on the site, in cooperation with industry, will confirm the feasibility of generating electricity from heat and methane produced by the well. The Gladys McCall well in Louisiana will remain closed to monitor long-term pressure recovery of the reservoir. Supporting research, primarily at universities, will focus on rock mechanics, reservoir modeling, logging, liquid hydrocarbons present in the brines, and environmental effects.

Hot Dry Rock

Experiments at Fenton Hill, N. Mex., have established the technical feasibility of extracting thermal energy from hot rock formations filled with man-made reservoirs. But long-term flow testing of a large-scale reservoir is needed to confirm commercial feasibility.

Tests beginning in FY 1990 should prove the technology's ability to sustain high volume flow, minimize fluid losses, and control thermal drawdown. FY 1990 will be devoted to final preparations for the long-term flow test of the man-made reservoir at Fenton Hill. Researchers will complete procurement and installation of components and conduct preliminary flow tests.

Energy can be extracted from hot, dry rock by creating man-made fluid reservoirs in natural rock formations.

Magma

A shallow lava lake in Hawaii was the site of recent experiments that proved the concept of extracting thermal energy from magma. But the engineering feasibility of locating, accessing, and using magma as a commercial energy resource has yet to be shown. Technology for recovering magma energy must include geoscientific techniques to identify resources, better materials to operate at high temperatures (up to 1200°C), and innovative methods to extract the heat. The strategy of magma research is to drill an exploratory well adjacent to a prospective magma body. The first phase of this research was recently completed with a 2500-ft well at Long Valley, Calif.

In FY 1990, scientists will continue research at the well and will transfer information to private industry and the scientific community. They will also conduct experiments sponsored jointly by DOE and the Continental Scientific Drilling Program, a consortium of the U.S. Geological Survey, the National Science Foundation, and DOE's Office of Basic Energy Research.

Electric Energy Systems: Utilities

Despite increases in energy efficiency during the past 35 years, the United States uses more electricity than ever before. Most predictions show that electricity use will continue to grow at a rate of about 2% per year. As we force our electric system to work closer to full capacity, failures and disturbances in the system become critical. Losses during transmission also take on new importance because they reduce the amount of usable electricity available from the system. And as electricity use continues to climb, the network of high-voltage transmission lines will expand, raising questions of public health and safety. DOE's Electric Energy Systems (EES) Program is developing the technologies that will help to ensure the efficiency, reliability, and security of our nation's electric system.

Research Direction

As the U.S. electric industry enters the 1990s, it faces several challenges. For example, much of the new capacity added during the last few years has been from small, independently owned facilities, some of which use renewable resources. These distributed sources of power must be carefully integrated to ensure the reliability of the electricity supply network. The program sponsors research on a variety of technologies and methods for minimizing disruptions to the electricity supply and lessening the effect of those that happen. Research is also answering questions about the health effects of exposure to electromagnetic fields.

The main focus of EES research is on developing high-temperature superconductivity (HTS) — the ability of a material to conduct electricity with no resistance or losses at relatively high temperatures. HTS could revolutionize the world of electricity generation, distribution, and application. Potential HTS power equipment and devices could function at temperatures as high as 125 K (–150°C), which can be maintained easily and inexpensively with liquid nitrogen.

The EES program is working with industry, universities, and the national laboratories to develop HTS. For example, collaborative projects established through the Pilot Center Program allow industry to direct research and make use of the vital national resource represented by the national laboratories. Six of these collaborative agreements are now in place.

Tomorrow's electricity network will incorporate elements such as renewable energy systems, long-term energy storage, and independent power producers. This diverse mix of generating capacity will result in special challenges to the reliability and safety of our electricity supply.

FY 1990 Activities

Systems and Materials Research

Superconducting materials are the primary focus of systems and materials research. Through the Pilot Centers and the Superconductivity Technology for Electric Power Systems (STEPS) program, EES research aims to provide the technology base for the revolutionary applications that HTS promises. During FY 1990, the program will continue to establish new collaborative agreements through the Pilot Center program. Research within the STEPS program will concentrate on developing HTS coils and cables.

The main objective of research on HTS coils and cables is to improve their ability to carry electrical current. Today's materials lose their superconducting characteristics at certain critical current densities, known as J_c . During FY 1990, scientists will continue research to increase this J_c to values that are closer to the currents that flow through transmission lines and magnets.

Research on high-temperature superconductors aims to increase the materials' critical current density, a measure of their current-carrying capacity. Applications for transformers, generators, and DC transmission cables will require densities shown by region A. AC transmission cables and superconducting magnetic energy storage will require those shown by region B.

As research on these materials proceeds, program emphasis will shift to device development and application by industry.

Besides research on superconducting materials, scientists will investigate various polymers that have other important electrical properties including conduction and insulation. They will also characterize thin-film dielectric polymers and study toxic products from insulating gases that have decomposed.

Reliability Research

Research within this activity is designed to improve the reliability and security of the future electric network. During FY 1990, researchers will develop techniques to integrate distributed power sources into the electric network. Additional research will investigate the vulnerability of systems and components to surges from electromagnetic pulses, solar magnetic storms, or lightning. Scientists will develop techniques to minimize the effects of these transients.

Electric Field Effects

During the last several years, scientific consensus has been growing over the existence of biological changes caused by exposure to electromagnetic fields, but the effects of these changes on human health and safety are unclear. During FY 1990, scientists will conduct experiments on reproductive disorders, abnormal cell and tissue growth, and cellular response resulting from mixed electric and magnetic field exposure. In addition, a second phase of a collaborative experiment with Japan's Central Research Institute for Electric Power Industry (CRIEPI) will examine endocrinal and behavioral effects of electric and magnetic fields on baboons.

Sixty-Hertz electric fields produced by electric power generation, transmission, and distribution facilities induce small electric currents and fields inside the bodies of exposed humans and animals. Conducting models are being used to study the distribution of currents in exposed humans and animals. This information plays a vital role in assessing possible risks to humans resulting from electric-field exposure.

Energy Storage Systems: Utilities

Cost-effective technologies for storing electric and thermal energy could greatly improve the capacity and efficiency of our electric power system in two ways. First, energy storage would allow the electric power industry to separate energy supply from demand by storing electricity generated during off-peak hours for use during peak demand periods. Second, it would allow utilities to make better use of our nation's large renewable energy resources, some of which are naturally variable (e.g., sunlight and wind). These technologies also offer new options for electricity-based transportation. Technologies for storing electric and thermal energy are the focus of DOE's Energy Storage Program.

Research Direction

Scientists are improving the performance and reducing the costs of proton exchange membrane fuel cells, which generate electricity from methanol and air.

Energy storage and utilization technologies offer great promise for supplying electricity more efficiently, for using more domestic sources for transportation fuels, and for expanding the use of renewable energy technologies. For example, program research on fuel cells may provide an efficient way to use domestically produced methanol to power our vehicles as an alternative to combustion. Fuel cells generate an electric current, which can be used to drive an electric motor in a vehicle. The system being developed actually uses hydrogen, derived from the methanol, and oxygen, from the surrounding air, as the reactants. The cell uses a proton exchange membrane (PEM) to separate the reactant gases. Scientists are working to improve the performance and cost of PEM fuel cells. This research provides an important link to research on biomass-derived methanol sponsored by the Biofuels Program.

Scientists are also developing advanced battery concepts that will help utilities meet future electric demands and expand the practicality of electric vehicles. Research is focused mainly on improving the performance, lifetime, and cost of sodium-sulfur and zinc-bromine batteries.

New storage systems based on superconducting magnets are also being developed through program-sponsored research. These systems store energy in large, superconducting magnetic coils. The technology offers the possibility of large-scale utility storage at efficiencies greater than 90%.

Storage of thermal energy also offers important opportunities in energy management, particularly for residential or commercial buildings or for industrial processes. The program supports research on several approaches to storing heat or chill.

FY 1990 Activities

Electrochemical Research

Program-sponsored electrochemical research is focused on improving the performance and marketability of PEM fuel cells. During FY 1990, scientists will examine the potential of different electrode materials for improving the cell's power output. An important focus of research will be on the direct use of methanol in the cell, eliminating the need for conversion to hydrogen. This research centers on identifying catalysts for the electrochemical reaction.

Electrochemical research also supports development of advanced batteries. In FY 1990, scientists will develop new catalysts, evaluate new battery materials, fabricate and test corrosion-resistant components for high-temperature cells, and continue proof-of-concept testing of zinc-air battery systems.

Battery Development

The program is developing several advanced battery concepts. For example, collaborative research with industry will begin in FY 1990 to develop a marketable sealed lead-acid battery for utility storage by the mid-1990s. Longer term options include sodium-sulfur, nickel-hydrogen, and zinc-bromine batteries for transportation, utility, and renewable energy applications, and development of these batteries will continue during FY 1990.

This artist's drawing shows a 200-cell prototype sodium-sulfur battery that will be completed in 1990.

Thermal Energy Storage

The Energy Storage Program has sponsored research in previous years on storing heat or chill in aquifers. This technology is now considered mature, and in FY 1990, the program will complete long-term aquifer storage tests at its test site in Minnesota and document the results. Tests in Alabama will also be documented. The program will sponsor several technology transfer activities; General Motors, the Veterans' Administration, and a brick factory have all shown interest in installing thermal storage.

Superconducting Magnetic Energy Storage (SMES)

During FY 1990, researchers will begin a conceptual study of a compact high-temperature SMES system that can store up to 250 MWh of electricity. The study will compare the required size and costs of the unit with those of a similar unit using low-temperature superconductors. Results of the study will help to guide future research.

Solar Thermal Energy: Utilities

Solar thermal systems concentrate sunlight to heat fluids for electricity generation or for other thermal or photochemical processes.

Solar thermal energy systems use reflective surfaces to concentrate the sun's radiation. This concentrated sunlight can be used to heat working fluids for electricity generation or process heat, or it can be used directly in a variety of photochemical processes. Primary system designs use either a central receiver surrounded by a field of mirrors (heliostats) or distributed receivers mounted at the focal points of parabolic dishes or troughs. Although solar thermal systems can serve a variety of thermal applications, electricity generation is the application thought to have the greatest potential. Therefore, it is the primary focus of the Solar Thermal Program. However, the program is also placing increased emphasis on photochemical processes that use concentrated sunlight to detoxify water and hazardous wastes.

Research Direction

Costs of solar-thermal-derived electricity are nearing competitive levels as a result of program-sponsored research.

The objective of the Solar Thermal Program is to improve the cost and performance of solar thermal systems and to broaden their applicability. DOE-sponsored research complements private efforts aimed at developing commercial solar thermal technology. Program activities are focused on solar concentrators, advanced electric systems, high-flux processes, and technology transfer.

Solar thermal systems have begun to enter the electricity market; about 200 MW are now operating in the United States. Program-sponsored development of new solar concentrators, receivers, and electric conversion systems should allow industry to expand this capacity further. Concentrator costs have dropped by a factor of eight since the program's beginning in 1978, and innovative designs should cut these costs by as much as two-thirds more. Research on receivers and Stirling engines should further reduce costs and improve performance.

Development of high-flux photon processes, a spin-off of solar thermal research, also offers interesting possibilities. The program now includes research on applications including water and waste detoxification, chemicals production, and materials processing. These applications are based on solar-driven chemistry that also involves high temperatures or catalysts.

All these activities involve industry through collaborative research and development. This partnership with industry will help ensure that solar thermal technology will be ready to assume a larger role in providing energy for our nation in the 1990s.

FY 1990 Activities

Concentrator Research

Concentrators represent the largest single cost of today's solar thermal systems. During FY 1990, researchers will work to reduce this cost by developing new reflective films and concentrator designs. Research on heliostats will involve performance testing of designs using both glass and stretched-membrane reflective surfaces. In addition, engineers will begin to design and fabricate a prototype commercial unit using a stretched membrane. In work on dish concentrators, researchers will complete tests of a reflective element for a stretched membrane dish measuring 7 meters in diameter and address other aspects of dish design, including the support structure and the tracking mechanism.

Prototype heliostats are being tested at Sandia National Laboratories in Albuquerque, N. Mex.

Advanced Electric Systems Research

The program sponsors research on both central and distributed receivers through this key activity. Research on central receivers will focus on the direct absorption receiver (DAR) in FY 1990. The DAR heats a working fluid (e.g., molten salt) by letting it flow over the surface of the receiver, thereby exposing it directly to the concentrated sunlight. The DAR should cut receiver costs in half and improve annual performance by about 15%. Basic conceptual studies will be completed in FY 1990 along with a comparative evaluation of various central receiver system designs.

Research on distributed receiver systems is designed to improve the lifetime and performance of Stirling engines. These engines can be mounted at the focal point of individual dishes to generate electricity. In the coming year, researchers will begin outdoor tests of a new kinematic Stirling engine and complete the preliminary design of a free-piston engine.

This artist's drawing shows a possible design of a solar thermal system for treating groundwater contaminated with organic chemicals.

These parabolic trough collectors can be used in solar thermal detoxification systems.

High-Flux Photon Processes

Scientists are studying high-flux photon processes to improve the understanding of the photochemical effects of concentrated solar radiation. In FY 1990, researchers will conduct laboratory tests on sunlight-driven processes for destroying hazardous compounds at high temperatures and on catalysts for destroying organic chemicals in water. Studies will also address special materials processes that can produce coatings to improve the oxidation or corrosion resistance of metals. Also during FY 1990, development of "solar-pumped" lasers will continue; these lasers use flux concentrations equal to more than 60,000 suns. Finally, systems analysts will review ongoing research on solar photocatalytic synthesis of high-value compounds and on near-term applications of solar materials processing.

Technology Development

Program personnel will continue to work closely with industry through the Committee on Renewable Energy Commerce and Trade (p. 41) and through the Design Assistance Center at SNL. Specific projects will include field testing of a water detoxification system and issuing a request for proposals for advanced electric system concepts.

Wind Energy: Utilities

Systems that use the kinetic energy of the wind provide another renewable source of electricity for our country. Wind machines have evolved from centuries-old technology for converting the wind's energy into rotational motion for mechanical or, more recently, electrical applications. Today's machines vary in capacity from 1 kW to 1 MW, or more, and use one of two basic designs. Horizontal-axis wind turbines (HAWTs) often resemble airplane propellers mounted on towers and are oriented either upwind (facing into the wind) or downwind. Vertical-axis wind turbines (VAWTs) look like egg beaters mounted on central columns. VAWTs operate in winds from any direction, without moving their axis of rotation. Wind turbines provide some 1500 MW of electric generating capacity to our nation today, but continued expansion of this capacity depends on the development of machines with higher efficiencies and longer lifetimes.

Wind energy conversion systems, or wind turbines, operate on basic aerodynamic principles similar to those that govern airplane wings. They convert the pressure differential across the turbine blade to rotational motion, which in turn drives an electric generator.

Research Direction

Thousands of wind machines are operating around the country today, mainly in California and Hawaii. These machines produced almost 8 billion kWh by the end of FY 1989, avoiding more than 2 million tons of atmospheric carbon emissions. Yet the experience of the American wind industry has shown

A reliable economic index for wind turbines is turbine costs as a function of the swept area of the rotor. This graph illustrates the cost reductions that have been achieved since the introduction of federally sponsored wind research.

that some of today's machines cannot withstand the unique stresses that result from wind gusts and turbulence. Machines often undergo major structural and fatigue problems that cause premature failure of the turbine. Problems also occur when turbines operate at peak power levels associated with high wind speeds.

The Wind Energy Program focuses on short-term and long-term goals that will help solve these problems for both the wind and utility industries and provide a technology base for producing cost-competitive wind energy systems. Short-term goals include understanding today's technical problems and developing new tools and methods to help industry design advanced machines. The long-term goal is to develop advanced concepts in high-efficiency systems and components through close interaction with the wind industry.

FY 1990 Activities

Structural Dynamics

Research on structural dynamics is vital to reducing the failure rate of machines. Working with industry through the Cooperative Research Program, scientists will continue to study the dynamic response of machines to wind loads in FY 1990. This knowledge will help designers predict machine lifetime under a range of operating conditions. Also during FY 1990, researchers will collect data on the fundamental fatigue and fracture properties of wind turbine materials. This type of information is currently inadequate, particularly for fiberglass composites.

Aerodynamics

Research on aerodynamics aims to expand the understanding of the interaction between the wind and the turbine blades using several novel flow visualization and measurement techniques. This understanding will form the basis for advanced designs of airfoils, the cross-sectional shapes that govern air flow around the blade. Scientists at SERI's Wind Energy Test Center will begin the second phase of an experiment designed to improve turbine

The Combined Experiment, undertaken at the Solar Energy Research Institute, investigates the unique airflow and stress environments that wind turbines experience using innovative techniques such as liquid crystal flow visualization, developed at Sandia National Laboratories.

performance. Using extensive operational data taken on a working machine last year, researchers will optimize turbine operation in the field. This has never before been done on a systematic basis.

Advanced Components

Industry is actively involved in program-sponsored development of advanced turbine blades based on new airfoil designs. These new blades could help to make wind energy more competitive and to allow U.S. industry to capture the market for turbine blades from foreign competition. For example, initial tests of a new 7.9-m fiberglass blade designed by SERI and its subcontractors demonstrated a 15%-20% increase in energy output at wind speeds of 10 to 25 mph. During FY 1990, SERI researchers will work with industry to complete testing of the 7.9-m blade and a new 9-m blade.

Scientists at SNL will continue work on the 34-m vertical axis test bed, including tests of new airfoils that control peak power better than previous designs. This development could help prevent the generator failure that can happen at the high power levels produced at high wind speeds. Also under way are tests of a variable speed rotor, which is expected to help reduce component stress by better matching rotor speed to wind speed.

Another important initiative is the recent solicitation for advanced turbine designs. This activity could have far-reaching effects on the wind industry by developing a machine that has a longer lifetime and produces significantly more power for its size than today's machines. The new designs should also produce cost-effective energy at lower wind speeds, allowing wind energy to be more competitive in areas like the Great Plains. Design studies will begin during FY 1990.

The cooperative field testing of a Northern Power Systems turbine at Altamont Pass, Calif., is an example of the DOE-industry joint projects that will continue as the Advanced Turbine Design Studies get under way in FY 1990.

Atmospheric Fluid Dynamics

The nature of wind flow around the turbine dramatically affects the performance and lifetime of the wind machine. Therefore, a fundamental understanding of wind dynamics is crucial to the design and operation of wind turbines. During FY 1990, the program will continue to develop computer models that characterize wind turbulence and turbine and array wakes. Scientists at the Pacific Northwest Laboratory will refine models that predict wind direction and speed over uneven terrain and analyze flow data on wind as it enters several typical locations. These activities will help industry evaluate sites for windfarms and determine the best type and placement of turbines within those farms.

Supporting Research

Supporting research includes such areas as technical planning, wind-diesel hybrid system development, and research into the effects of wind turbines on power quality in utility grids. In particular, engineers will study the potential benefits of variable speed generation to utilities and windfarm operators. Development of wind industry standards will also continue in cooperation with the American Wind Energy Association.

Ocean Energy: Utilities

The temperature of oceans in many areas of the world can vary by 20°C or more between the surface and depths of around 1000 m. These temperature differences are particularly common in areas at tropical latitudes. A 20°C temperature difference can be used to generate electricity by alternately vaporizing and condensing a working fluid. This process, known as ocean thermal energy conversion (OTEC), forms the basis of the Ocean Energy Program.

OTEC systems are essentially heat engines that use warm seawater to vaporize a working fluid, which in turn drives a turbine. Cold seawater pumped from the ocean's depths condenses the working fluid as it exits the turbine. The working fluid can be either the seawater itself in an open-cycle

Ocean thermal energy conversion (OTEC) systems use the temperature difference between the surface and depths of the ocean to drive electric generating equipment.

$\Delta T(^{\circ}\text{C})$ Between Surface and 1000 Meter Depth

The temperature gradients of the world's oceans make up a tremendous resource for baseload electricity.

system that discharges the turbine vapor directly to the ocean, or it can be a second fluid, such as ammonia, in a closed-cycle system.

Several coastal areas of the United States provide promising locations for OTEC systems. The coasts of Florida and the Gulf states and islands such as Puerto Rico, Hawaii, and the Virgin Islands are well suited to OTEC installations. These areas, which do not have abundant fossil fuel resources, could eventually support 2000 MW of OTEC electric generating capacity.

Research Direction

Since its inception in 1972, the Ocean Energy Program has made important advances in the performance and lifetime of critical components and materials for open- and closed-cycle OTEC systems. Because the open-cycle concept incorporates simpler, less costly, and higher performance components, the program has narrowed its focus to this design. The main objective of the program now is to help industry develop 2- to 15-MW_e open-cycle systems for use just off shore. These modular installations for baseload electricity are believed to have the greatest potential for near-term use. The open-cycle process produces desalinated water as a by-product, further enhancing system applicability and economics.

Research is now focused on systems-level experiments at the Seacoast Test Facility at the Natural Energy Laboratory of Hawaii. Phase I of this experiment was completed in FY 1989, when scale models of the heat exchangers were tested for the first time in seawater under realistic conditions. Engineers will use the data from these tests to design the full-scale heat exchangers, which will be tested in Phase II. A low-pressure open-cycle steam turbine will be added to the experiment in Phase III, completing the assembly of the 165-kW_e open-cycle system.

FY 1990 Activities

Thermodynamic Research and Analysis

Researchers use computer models and laboratory research to evaluate component designs and system requirements for the systems-level tests. During FY 1990, final designs will be completed for the heat exchangers, the turbine, and the on-shore sections of the seawater system. Also in FY 1990, researchers will begin designing the system containment structure and fabricating the turbine.

Experimental Verification and Testing

This activity complements the research and analysis with experimental testing of components. Research during FY 1990 will develop an experimental data base for use in system analysis. The data will result from seawater experiments on key open-cycle components, including the flash evaporator, condensers, mist eliminators, the turbine, and gas sorption processes.

Scale model of side-by-side direct contact condenser in the heat-and mass-transfer scoping test apparatus.

Materials and Structures

No separate research is planned for FY 1990 within this key activity. Determination of materials characteristics of individual components will be conducted as part of the experimental verification and testing activity.

An artist's rendering of the "dome" design of the net power-producing experiment. This facility will help to determine the viability of open-cycle ocean thermal energy conversion.

EA-G0472706

Heating, Cooling, and Lighting: Solar Buildings

Solar heating systems convert sunlight into useful heat by means of discrete solar collection, storage, and distribution elements (active systems) or by the use of the building's structure itself (passive systems). Cooling can also be provided by using the collected energy to power heat-driven cooling or dehumidification equipment such as a desiccant dehumidifier.

Sunlight has provided warmth and light for shelters since the earliest days of human life on earth. Today, the practice of heating, cooling, and lighting buildings with the sun has evolved into an advanced technology that can provide 40% of a building's energy without substantially increasing its cost. Passive heating systems use the sunlight that falls on walls and enters through windows to heat interior space directly. Active heating systems use solar collectors to heat water or another fluid that delivers heat to interior space or to domestic water. Solar energy can also cool buildings through systems that combine evaporative cooling with desiccant dehumidification. And innovative techniques and materials for daylighting can provide half of a building's lighting requirements, simultaneously reducing the cooling load. The Solar Buildings Program works closely with the buildings industry to improve the performance of these technologies, thereby increasing the cost-effective contributions to a building's energy needs.

Research Direction

The Solar Buildings Technology Program is structured around the major applications of heating, cooling, and daylighting. Within the solar heating area, the primary emphasis is on improving the cost-effectiveness and reliability of active solar water and space heating systems. Active systems have achieved some commercial success in certain regional markets, and the challenge is to obtain widespread competitiveness. Research objectives include increasing the annual efficiencies from today's 30% to 40% in the future with 50% cost reductions by simplifying the system design and developing innovative applications. The program also supports research on materials that can improve the performance of passively heated buildings.

In solar cooling, the goal is to develop technology that can supply up to 60% of a building's cooling requirements at competitive costs. Desiccant cooling offers the greatest opportunity for meeting this goal. This technology combines evaporative cooling with desiccant dehumidification to cool building air. Desiccant systems are well suited to hot, humid climates. The program

seeks to double the coefficient of performance, a measure of efficiency, by modifying promising commercially available polymeric desiccants.

The emphasis of daylighting research is on advanced glazings that can modulate the intensity, direction, and quality of sunlight entering the building. Today's daylighting technologies can contribute 40% of a building's lighting requirements. The goal of the program is to increase this contribution to 80% around the building's perimeter and 40% within its core. These lighting contributions will avoid significant waste heat from conventional electric lights, thereby reducing cooling loads by up to 30%. Widespread adoption of daylighting technology would result in energy savings for the building occupants and significant reductions in peak electric capacity requirements for utilities.

FY 1990 Activities

Solar Heating

For near-term applications, the solar heating program is developing "generic system designs" — recommended standardized systems for active solar heating that take much of the guesswork out of system design. During FY 1990, researchers will validate a methodology for substituting components within the generic designs to permit flexibility, while reducing time and costs for testing and certifying solar hot-water heating systems. They will also develop acceptance test procedures to assure reliability of installed systems.

Longer term objectives include developing advanced heating systems and innovative concepts. Research in FY 1990 will investigate new technologies including freeze-resistant thermosyphon systems and air heating systems that do not require storage.

Research on wallboard impregnated with phase change materials (PCMs) will continue with full-scale field tests and analysis. PCMs can be tailored to store and release heat at the appropriate temperatures for human comfort.

Researchers are investigating new desiccant materials in conjunction with high-effectiveness dehumidifier designs to meet performance targets. The spiral wound desiccant wheel shown is one of the most promising concepts.

Incorporating them into building materials can greatly improve the thermal performance of a passively heated building.

Solar Cooling

Research within the solar cooling program will develop improved desiccant materials and dehumidifier geometries. Materials research will involve polymeric desiccants that can absorb up to 20 times their weight in water. FY 1990 research will also include a study of the effects of airborne contaminants on desiccant performance and an investigation of advanced dehumidification concepts.

Daylighting

During FY 1990, research will continue on electrochromic glazings, which can vary their transmittance of natural light and heat from 10% to 80%, in response to a brief electric current applied externally. These devices can be made "spectrally selective" which, for example, allows them to transmit visible sunlight in the summer while reflecting heat. They can also be designed to control the intensity of the transmitted light to reduce unwanted glare. In FY 1990, researchers will continue to test and evaluate candidate materials for an all solid-state, multilayer electrochromic device.

In addition to conducting research on electrochromic devices, scientists will develop guidelines for designing energy-efficient atria and other advanced core daylighting technologies.

Electrochromic devices operate as automated shutters to modulate heat gain and daylight transmittance through windows. Their optical properties change in response to a brief, externally applied current. The chemical reactions resulting from the current flow cause either transparency or slight coloration, affecting heat transmittance.

Cross-Cutting Programs: International Solar Energy Program

The primary activity of the International Solar Energy Program is to support the Committee on Renewable Energy Commerce and Trade. CORECT is an interagency group that facilitates the use of U.S. renewable energy products and services around the world. Established by the Renewable Energy Industry Development Act of 1983, CORECT is made up of representatives from 14 federal agencies. CORECT is chaired by the Secretary of Energy; day-to-day management is provided by the Director of DOE's Photovoltaic Energy Technology Division.

FY 1990 Activities

Small-Scale Financing

Development banks and donor agencies generally make large loans and grants. It is not cost-effective for them to make transactions involving small amounts, such as the \$500 to \$1,000 that individuals or families need to purchase renewable energy systems (a pair of photovoltaic panels, for example). To help the villager or farmer, CORECT is working to establish intermediary organizations that can address these small-scale financing needs. Under this plan, intermediary organizations would borrow large amounts, say \$1 million to \$2 million, and in turn make small loans to individuals.

Design Assistance

Providing advice and assistance on system design has proven itself to be an effective way to encourage the use of RE technologies. Acting as impartial, third-party sources of information, representatives from the Design Assistance Center at SNL have helped many countries (including the United States) to identify cost-effective applications that use indigenous resources. FY 1990 will see a growing emphasis on this type of activity.

Education and Training

Education and training of foreign country officials has always been an important mission of CORECT and will be even more so in FY 1990. Specific activities will target training of technical staff on system operation and maintenance, as well as sharing experience and knowledge of financing methods.

Working with Utilities

CORECT is working hard to dispel the impression of many government officials that RE systems are still experimental. The approach is to integrate RE with the other power systems that utilities consider routinely. During FY 1990, CORECT will continue the Integrated Electric Utility Project, designed to encourage the routine consideration and use of decentralized renewable energy systems for electrical power in developing countries.

One of the major activities of the project is to set up "model" utilities. Using proven technologies, model utilities will help refine the legal, regulatory, institutional, and financial infrastructure necessary to integrate decentralized systems into the generation mix. Such models will provide tangible evidence for developing countries that the concept works. Maui Electric in Hawaii may serve as the first model utility because of its similarity to utilities in developing countries (dispersed population, difficult terrain, similar climatic conditions, and high energy costs).

This photo of a power pole in Mexico City demonstrates the immense challenges faced by the world's developing nations in supplying energy to homes and businesses.

Renewable energy technologies, such as the photovoltaic panels on this house, can provide a clean and cost-effective answer to such challenges.

Cross-Cutting Programs: Resource Assessment

The performance of the technologies that convert sunlight, wind, and other forms of renewable energy to useful heat and electricity is critically dependent on the amount and characteristics of these resources. This dependence creates a fundamental need to understand the nature of the resources — their location, their intensity, and their variability. DOE's Resource Assessment Program is designed to achieve this understanding.

The program is focused on assessing the solar radiation resource (sunlight) in the United States. At SERI, researchers develop data sets, computer models, and measurement techniques to help others understand the nature of the resource. This understanding allows technologists to design better conversion systems and to evaluate their potential performance more accurately. For example, a utility considering a photovoltaic system would need either high-quality, long-term solar radiation data or a predictive computer model to tell how well the system's electricity output will match the utility's demand profile. Uncertainties in the solar resource availability can lead to large uncertainties in the economic viability of the system.

FY 1990 Activities

A top-priority effort in FY 1990 will be to develop a data base of incident solar radiation (insolation) for 1961-1990. The new data base will be the first accurate 30-year data base ever available for the United States. The update will account for climate variations and correct many errors in existing data sets.

A second project will develop the capacity to obtain high-quality solar radiation measurements for the nation so that the data base can be updated at 5-year intervals. In support of this project, researchers will continue working with the National Oceanic and Atmospheric Administration (NOAA) to help manage the National Solar Radiation Monitoring Network operated by NOAA. The program will also continue to support the network of six solar radiation stations at the Historically Black Colleges and Universities in the southeastern United States.

A third project will continue developing data bases and models that describe the spectral (color) content of solar radiation to help optimize and predict the performance of spectrally selective technologies such as photovoltaic

The pyranometers shown above are one type of instrument used to measure solar radiation. The instruments are calibrated outdoors against reference instruments so that the measurements are traceable to world radiometric standards.

The results of human activity, such as jet contrails, contribute to the variability of solar radiation reaching solar collectors and devices. Continuous updates to historical solar radiation data allow researchers to detect changing atmospheric conditions.

cells. Project objectives include producing a solar radiation data base from more than 3000 measured spectra collected so far and from new measurements to be taken in the ultraviolet and near-infrared region of the spectrum. Scientists will also develop spectral simulation models for a variety of realistic climate conditions.

In coming years, the Resource Assessment Program will expand its focus to begin to evaluate the resource at sites outside the United States. Developing international resource data bases will help U.S. industry take advantage of the large export market that exists for renewable energy technologies in many regions of the world.

Cross-Cutting Programs: Technology Transfer

Technology transfer is critically important to the mission of the renewable energy programs. Transferring knowledge gained by the research programs to the private sector enables industry and state and local governments to complete the process of technology development. Within the RE programs, technology transfer takes place through collaborative research, exchange of personnel, technical assistance, licensing, spinoff companies, publication of reports and papers, educational programs, and industry advisory groups.

FY 1990 Activities

During FY 1990, the RE programs will continue to involve the private sector in research. In particular, there will be new cost-shared research initiatives with industry, continued collaborative research with universities all over the country, and extensive use of advisory committees, including the 14 federal agencies who belong to CORECT (p. 41). In addition, workshops and hands-on technical assistance will help industry use new science and technology to develop products and services.

The Technology Transfer Program provides information on the renewable energy technologies to technical audiences and to the general public.

All these technology transfer activities are funded and managed through the individual technology research programs, but three cross-cutting technology transfer projects are managed by the Office of Renewable Energy. During FY 1990, these three projects will continue to provide information to technical audiences and the general public on renewable energy topics.

- **Conservation and Renewable Energy Inquiry and Referral Service (CAREIRS).** CAREIRS, a toll-free telephone service operated by Advanced Sciences, Inc., answers more than 50,000 inquiries about conservation and renewable energy from the public each year. CAREIRS responds to these inquiries with printed fact sheets and reports.
- **Technical Inquiry Service (TIS).** Technical inquiries from entrepreneurs, scientists, and industry are handled by TIS, operated by SERI. TIS responds to more than 2000 requests each year with printed material and referrals to researchers.
- **Solar Technical Information Program (STIP).** STIP, also operated by SERI, produces a variety of booklets, information guides, and reports summarizing DOE-sponsored programs and technologies. During FY 1990, STIP will produce nearly 40 new products including a set of 17 research program summaries. Shorter documents are distributed free by TIS; longer ones are sold through the U.S. Superintendent of Documents.

Cross-Cutting Programs: Solar Energy Research Institute Facilities

SERI, in Golden, Colo., is the nation's center for research and development of solar technologies sponsored by DOE's renewable energy programs. A portion of the RE research budget is dedicated each year to maintaining and improving the scientific excellence of the SERI facilities.

Established in 1977, SERI facilities now include the 80,000-ft² Field Test Laboratory Building (FTLB), several small research buildings, and laboratory and office space in leased buildings. These structures house a variety of research tools, much of which is state-of-the-art equipment. These tools and the facilities must be regularly improved or replaced so that SERI can maintain its position as a world-class research institute. These improvements are also designed to protect the safety of SERI personnel and facilities.

FY 1990 Activities

The RE budget supports improvements to the SERI facilities through two tasks: General Plant Projects (GPP), which provides for physical changes to the buildings or grounds, and General Purpose Equipment (GPE), which allows for the purchase of tools, instruments, and equipment that are used by several different programs.

During FY 1990, GPP will include outfitting new laboratory space in the FTLB for photoelectrochemical research and various repair and maintenance

activities. GPE funds will support the Institute's on-going installation of a computer system based on local area networks (LAN) and the purchase of radio communications equipment to link the permanent and leased sites on the LAN system. The Institute will also buy a state-of-the-art 300-MHz Fourier Transform Infrared (FTIR) spectrophotometer to enhance SERI's capabilities for surface characterization. And new metrology equipment will support the Institute's quality assurance program.

SERI's Field Test Laboratory Building houses state-of-the-art research facilities and equipment.

Information Contacts

U.S. Department of Energy
Forrestal Building
1000 Independence Ave., SW
Washington, DC 20585

Dr. Robert L. San Martin
Deputy Assistant Secretary,
Renewable Energy
(202) 586-9275

Mr. Cliff Carwile
Acting Director, Office of
Solar Heat Technologies
(202) 586-5584

Mr. Ronald R. Loose
Director, Office of Renewable
Energy Technologies
(202) 586-8084

Mr. Louis V. Divone
Director, Office of Solar
Electric Technologies
(202) 586-5540

Dr. Russell Eaton
Acting Director, Office of
Energy Storage and
Distribution
(202) 586-2826

Solar Technical Information Program

Technical Inquiry Service
Solar Energy Research Institute
1617 Cole Blvd.
Golden, CO 80401
(303) 231-7303

Conservation and Renewable Energy Information and Referral Service (CAREIRS)

Renewable Energy Information
Box 8900
Silver Spring, MD 20907
(800) 523-2929

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or any agency thereof.

Printed in the United States of America

Available from:

National Technical Information Service, U.S. Department of Commerce,
5285 Port Royal Road, Springfield, VA 22161

Price: Microfiche A01, Printed Copy A04

Codes are used for pricing all publications. The code is determined by the number of pages in the publication. Information pertaining to the pricing codes can be found in the current issue of the following publications which are generally available in most libraries: *Energy Research Abstracts (ERA)*; *Government Reports Announcements and Index (GRA and I)*; *Scientific and Technical Abstract Reports (STAR)*; and publication NTIS-PR-360 available from NTIS at the above address.

Prepared for the
U.S. Department of Energy
Assistant Secretary, Conservation and Renewable Energy
Washington, D.C. 20585

Prepared by the
Solar Technical Information Program
Solar Energy Research Institute
Golden, CO 80401-3393
Under Contract No. DE-AC02-83CH10093

DOE/CH10093-74
DE89009489
January 1990