DOE/PC/79743--T2

MECHANISMS GOVERNING FINE PARTICULATE EMISSIONS
FROM COAL FLAMES

DOE/PC/79743--T2

DE92 013604

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Quarterly Technical Progress Report No. 2
Reporting Period: January 1, 1988 - March 31, 1988

DE-AC22-87PC 79743

Prepared for:

U. S. Department of Energy
Pittsburgh Energy Technology Center

Prepared by:

W. D. Clark
S. L. Chen
J. C. Kramlich
G. H. Newton
L. A. Ruth

Energy and Environmental Research Corporation
18 Mason
Irvine, California 92718

and

G. S. Samuelsen
University of California, Irvine

April, 1988

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

Section	Page
ABSTRACT.	ii
1.0 INTRODUCTION.	1-1
2.0 ENGINEERING ANALYSIS.	2-1
3.0 EXPERIMENTAL PROGRAM.	3-1
4.0 FUTURE WORK	4-1
5.0 REFERENCES.	5-1

ABSTRACT

Efforts in this period focused on refining the plans for engineering analysis and fundamental experiments based on the results of a literature review, and modifying the Malvern laser diffraction particle sizer to operate at particle sizes down to 0.5 microns. The engineering analysis plan is to concentrate on development of new models and adaptation of existing models for fine particulate formation by three categories of mechanisms: particle breakup/ash coalescence; direct passage, fragmentation, or agglomeration of extraneous mineral matter; and bubble formation/breakup. The plan for fundamental experiments is to develop a fast, online, optical particle sizing technique which will span the 0.5 to 10 micron size range of interest; to perform global experiments to identify the important parameters affecting fine particle formation; and to perform mechanistic experiments to test specific hypotheses about the mechanisms which control fine particle formation in coal combustion. Significant progress has been made in the development of the particle sizing technique. Calculations indicate that Malvern results can be corrected for the effects of Mie scattering which becomes important in the size range of interest. The instrument has been modified to allow measurement of particles down to 0.5 microns (the former limit was 1.2 microns). The modified Malvern is capable of accurately reproducing the size distribution of a calibration standard.

Efforts in the next quarter will concentrate on adaptation and development of models for particle breakup/ash coalescence, on beginning the global experiments, and on verification of the modified Malvern.

1.0 INTRODUCTION

The overall objectives of this project are to:

- provide a basic understanding of the principal processes that govern fine particulate formation in pulverized coal flames
- develop procedures to predict the levels of emission of fine particles from pulverized coal combustors

Particles in the 0.5 to 10 micron size are of interest because:

- 1) A significant fraction of flyash generated in the combustion of pulverized coal falls in this size range.
- 2) Electrostatic precipitators are least efficient in this size range.
- 3) Particles in this size range are most likely to penetrate to and be deposited in the aveolar passages of the human lung.
- 4) Volatile toxic metals tend to concentrate on the surfaces of fine particles.
- 5) It is not clear which mechanisms contribute to formation of flyash particles in this size range.

The project objective will be accomplished through a combination of literature research, experimentation, and model development and application. A project **Work** Plan was developed in Task 1. The remaining tasks in this program include:

Task 2. -Engineering Analysis

Task 3. Experimental Program (Fundamental Experiments and Process Simulation)

Task 4. Reporting

This quarterly report describes the work performed during the period from January 1, 1988 to March 31, 1988. Efforts in this period focused on refining the plans for engineering analysis and fundamental experiments based on the results of a literature review, and modifying the Malvern laser diffraction particle sizer to operate at particle sizes down to 0.5 microns.

2.0 ENGINEERING ANALYSIS

The objective of this task is to modify an existing model to allow the formation of fine particulate in pulverized coal flames to be predicted as a function of coal type and firing conditions. This objective will be accomplished in three subtasks:

- Initial Definition, in which a review of the current state-of-the-art of modeling fine particulate formation will be conducted and the requirements for an improved model will be defined.
- Model Adaptation and Development, in which the model outlined in the initial definition subtask will be assembled.
- Data Interpretation and Scaling, in which the model will be exercised against data generated in the experimental program to help interpret and scale the data and to refine the model.

Efforts in this period were concentrated on completion of the initial definition subtask. Four major categories of mechanisms which may result in fine particle formation were identified:

- Particle breakup/ash coalescence
- Direct passage, fragmentation, or agglomeration of extraneous ash
- Bubble formation/breakup
- Vaporization/condensation

These mechanisms are illustrated in Figure 2-1. Plans were outlined for the adaptation and development of models to predict fine particle formation by the first three categories of mechanisms. The fourth mechanism is believed not to make a major contribution to the mass of ash particles in the 0.5-10 μm size range, although it may be important in accounting for the deposition of volatile metals on the surfaces of these particles. EER has a vaporization/condensation model which is expected to be adequate for the purposes of this program.

PARTICLE BREAKUP / ASH COALESCENCE

BUBBLE FORMATION / BREAKUP

**DIRECT PASSAGE, FRAGMENTATION, OR
AGGLOMERATION OF EXTRANEEOUS ASH**

EVAPORATION / CONDENSATION

Figure 2-1. Mechanisms of fine particulate formation.

2.1 Mineral Matter in Coal

The form of the mineral matter in coal is expected to affect the formation of fine particles in coal combustion. Dahlin (1985) gives a review of the mineral matter in coal. Coal mineral matter is generally classified as either inherent, included, or extraneous.

Inherent mineral matter is organically bound to the coal matrix. It is generally evenly distributed throughout the coal, and inherent mineral "particles" are in the molecular size range. For these reasons, inherent mineral matter cannot be removed by conventional physical grinding and cleaning of the coal. Inherent mineral matter comprises from 5 to 20 percent of the total mineral content of most coals (Van Krevelen, 1961).

Included mineral matter is present in discrete packets which may be randomly distributed in the coal. The size and composition of the individual inclusions is highly variable. Sarofim, et al. (1977) report a mass median inclusion size of around 2 microns for two coals. When coal is ground, breaks tend to occur at inclusion/coal interfaces, and discrete inclusions are often released. Thus, a portion of the included mineral matter can be separated from the coal by grinding and cleaning. Inclusions typically make up 60 to 80 percent of the mineral matter in coal (O'Gorman and Walker, 1972).

Extraneous mineral matter is present as chunks of dirt and rock which have been inadvertently mixed with the coal in the mining process. In the grinding process the extraneous mineral particles, being denser than coal, are recycled to the pulverizer more times. This, coupled with shedding of mineral inclusions during grinding, results in a mineral particle size distribution which is finer than the coal size distribution in the ground coal (Littlejohn, 1966). Extraneous mineral matter can be easily cleaned from the coal by flotation. It comprises about 5 to 20 percent of the coal as mined (Dahlin, 1985).

2.2 Particle Breakup/Ash Coalescence

The breakup mechanism as described by Flagan (1978) has been used to adequately describe the size distribution of flyash particles larger than 2 microns. In its simplest form, as shown in equation 2-1, the breakup model assumes that each coal particle breaks up into a certain number (typically 3-5) of burning char particles. The mineral inclusions in each char particle coalesce into a single flyash particle. The resulting flyash size distribution is proportional to the original coal size distribution with the proportionality factor determined by the fraction of ash in the coal, the ratio of ash to coal density, and the number of char particles formed from each coal particle.

$$n(d_p) = p(p/\alpha_v)^{1/3} n_c [d_p(p/\alpha_v)^{1/3}] \quad (2-1)$$

where: n is the flyash particle size distribution
 d_p is the flyash particle diameter
 p is the number of char particles formed from each coal particle
 α_v is the volume fraction of ash in the coal
 n_c is the coal particle size distribution

However, the breakup model in its traditional form tends to underpredict the smaller (0.5 - 2 micron) end of the size range of interest. It is possible that particles in this size range are formed by another mechanism, or it is possible that particles in the 0.5 to 2 micron size range can be adequately described by a more complex form of the breakup model. Equation 2-1 has several simplifying assumptions which may lead to its underprediction of 0.5 to 2 micron particles:

- 1) Mineral inclusions are homogeneously distributed throughout the coal.
- 2) The number of char particles resulting from a single coal particle is a constant, independent of fuel characteristics or flame conditions.

- 3) The char particles resulting from the breakup of a single coal particle are all of equal size.

It is planned to modify the breakup model of equation 2-1 by introducing distributions for the total volume, number, and size of the flyash particles which result from each coal particle. These distributions will be a function of the coal properties and the combustion conditions. The model constants which define these distributions will come from:

- Review of existing literature
- The experimental portion of this program
- Experimental and modeling results from concurrent programs

In a related DOE program, workers at MIT (Sarofim, et al, 1988) are applying a site lattice percolation model to predict char fragmentation, ash coalescence, and the resulting flyash size distribution as a function of the particle properties and the combustion environment. Initial studies at MIT using this fragmentation model indicate that the flyash size distribution is heavily influenced by the macroporosity of the coal. The fragmentation model requires too much computer time to incorporate it as a submodel to be routinely run for every case of interest. However, the parametric studies being performed with this model can be used to develop correlations which may provide the model constants required by our planned revision of the breakup model.

2.3 Direct Passage, Fragmentation or Agglomeration of Extraneous Ash

After grinding, a portion of the fine end of the coal size distribution consists of extraneous mineral matter and inclusions which have been shed from their parent coal particles. Most of this material is easily

removed by coal cleaning. Most researchers either discount extraneous mineral matter as a significant contributor to the flyash size distribution (Dahlin, 1985) or merely list it as a side issue (Damle, et al, 1982). However, Holve (1986) concludes that a significant fraction of fine flyash particles are the result of direct passage of free minerals or mineral-rich fine coal particles.

It is planned to review the literature to derive correlations for the fraction and size distribution of free mineral matter as a function of mined coal characteristics and the degree of grinding and cleaning. Unless the experiments outlined in Section 3 prove otherwise, it will be assumed that extraneous mineral matter is unaffected by combustion, and thus the loading and size distribution of extraneous mineral matter in the flyash is the same as that in the coal as fired.

2.4 Bubble Formation/Breakup

A potential mechanism for producing fine particles is the formation and bursting of bubbles of molten flyash. Cenospheres (solidified flyash bubbles) have often been observed in pulverized coal combustion. Bubbles form when gases (typically carbon monoxide or carbon dioxide) are generated within molten ash droplets. Gluskoter, et al., (1981) and Smith, et al., (1979) propose that rupture of molten cenospheres may contribute significantly to the yield of fine flyash particles.

In order to estimate the contribution of bubble formation/bursting to the fine particulate yield, it is necessary to predict the quantity of bubbles which will form and burst and the size distribution of the resulting droplets. No such model currently exists, and the development of such a model on a limited schedule and budget would be a high-risk venture. However, there are approaches to each facet of the problem which, in conjunction with the experiments described in Section 3, may help in the assessment of the importance of the phenomenon, in the determination of

whether further model development is warranted, and in the formulation of a detailed model development approach.

Ash viscosity appears to be a controlling factor in the determination of when bubble formation will occur. Lauf (1981) was able to correlate cenosphere production with the viscosity of the ash from several power plants using viscosity correlations by Reid (Hazard, 1980) and by Watt and Fereday (1969). Sarofim, et al. (1977) give an expression for the rate of expansion of a cenosphere as a function of the pressure generated by the evolving gases, the viscosity and surface tension of the molten ash, and the size of the original droplet. Damle, et al. (1982) suggest that a bimodal size distribution may be expected from a burst ash bubble based on aqueous bubble-bursting studies of Tomaides and Whitby (1975).

In this project, as a rough first approximation, gas generation will be assumed to occur as equilibrium is maintained in a heating ash particle. Equilibrium calculations will be performed for various ash temperatures and compositions (keeping in mind that the ash may consist of heterogeneous mixtures of widely different compositions). Ash viscosity calculations will also be performed for these temperatures and compositions. Bubble bursting should occur when gas is evolved at a temperature where the viscosity is in a critical range where it is viscous enough to form a bubble, but not viscous enough to avoid bursting. This type of analysis will help in the planning and interpretation of the bubble bursting experiments described in Section 3.

2.5 Evaporation/Condensation

Under the conditions encountered in pulverized coal combustion, a small fraction of the mineral matter will vaporize and subsequently condense either homogeneously as new particle nuclei or heterogeneously on the surfaces of existing particles. Homogeneous nuclei have an initial size of around 10 angstroms and rapidly grow by heterogeneous condensation and by coagulation until they reach a self-preserving size distribution centered around 0.1 micron (Flagan and Friedlander, 1978). Measurements of flyash size

distributions from pulverized coal combustors indicate that the submicron flyash peak (generally attributed the evaporation/condensation mechanism) occurs in the 0.05 to 0.2 micron size range (Damle, et al., 1982). However, Helble, et al. (1986) observed condensed flyash agglomerates at sizes up to 0.6 microns due to aerodynamic effects in a laboratory scale laminar flow reactor.

No model development is planned to address the evaporation/condensation mechanism in this program. There are several reasons for this decision:

- 1) This mechanism is not expected to contribute significantly to the particulate yield in the 0.5 to 2 micron size range of interest.
- 2) EER's existing modeling capabilities as described by Barton, et al. (1988) adequately address this mechanism.
- 3) Extensive modeling and experimental efforts are being conducted in a related DOE program (PSI, 1988).

3.0 EXPERIMENTS

The experimental portion of this project consists of a study of the fundamental mechanisms followed by a process simulation study conducted on a pilot scale. Information from both of these efforts will be correlated with data obtained in another program at three full-scale utility boilers.

Efforts in this quarter have concentrated on modifying and testing the laser diffraction particle sizer for measurement of particles down to 0.5 microns, on selection of coals for the experiments and on refining the plans for the fundamental experiments.

3.1 Particle Sizing

The purpose of the particle sizing work is to develop a rapid and reliable means of resolving coal ash particle size distributions on-line. The approach is to modify an existing laser diffraction apparatus. This involves both theoretical and hardware oriented issues. During the past quarter the theoretical issues involved in the modification have been resolved and the hardware assembled and tested.

3.1.1 Theoretical Background

The purpose of the following discussion is to outline the theory by which the laser diffraction instrument operates. The implications of reducing the size range can then be developed.

The scattering and absorption of light by particles is one of the classical problems of physics. In general, the interaction of light with solid particles or liquid droplets can come about through a number of mechanisms. These include:

- Diffraction

- Refraction
- Scatter via induced dipole moment
- Reflection.

To first principle, all of these processes are described by Maxwell's equations. These equations were solved for the region within and near spherical particles in 1908 to yield the Mie equations. The Mie equations therefore provide a complete description of the interaction of light with spherical particles, independent of wavelength.

The extreme complexity of the Mie equations has led to the development of simplified forms that are appropriate for specialized cases. If the particle is small relative to the wavelength, then most of the light scattering is due to the induced dipole within the particle. This leads to Rayleigh scattering. Of more practical importance for the present case is diffraction, which dominates when the particle is much larger than the wavelength. Diffraction can be thought of as arising from the bending of the light around the edge of an obstruction. This leads both to scattering (i.e., a change in light direction from the original course) and to interference (i.e., light scattered from different particle surfaces may add or interfere).

The Malvern instrument is generally based on diffraction. Specifically, this is Fraunhofer diffraction, which is a simplification which results when the light approaching the particle is parallel, and the scattering is obtained at distances which are large relative to the particle diameter. Figure 3-1 illustrates the geometry that describes Fraunhofer diffraction. The diffraction from the particle will cause a pattern to form on the spherical screen which will consist of a central maximum and a series of light and dark concentric rings. (Note that we exclude any non-diffracted incident light. As shall be seen shortly, this exclusion can be accomplished by use of lenses.)

The maximum intensity occurs at $\omega = 0$ and is called I_0 . The diffracted light at any angle can thus be represented as the product of I_0 and a

Figure 3-1. Conceptual setup for evaluating diffracted light intensity at any angle ω from the initial light direction.

function that gives the shape of the scattering curve. For Fraunhofer diffraction this is:

$$I(\omega) = I_0[2J_1(\pi d\omega/\lambda)]/(\pi d\omega/\lambda)]^2 \quad (3-1)$$

Here, λ is the light wavelength and J_1 is the Bessel function of the first kind of order one. The value of I_0 is related only to the incident light intensity and wavelength, and to the size of the particle. In general, larger particles are characterized by a higher I_0 and a narrower scattering angle.

The Malvern instrument makes use of these scattering properties by the configuration shown in Figure 3-2. A collimated laser beam falls on a lens. The beam is focused through a pinhole in the detector board which is located one focal length behind the lens. The board is covered with an array of circular detectors, each of which is located at a given radius from the centerline. This setup allows undiffracted light to be dumped into a light trap. The particle shown in Figure 3-2 will exhibit a certain scattering intensity vs. angle relationship. Let us say we wish to characterize the intensity at 3° from centerline. Ray 1 and Ray 2 both emerge from the particle at 3° from centerline. Ray 1 proceeds through the lens and strikes Diode 4 on the detector board. Ray 2 also goes through the lens and also strikes Diode No. 4. Thus, the signal from Diode No. 4 will always represent light that was scattered at 3° from centerline. This means that the signal from the various diodes can represent the $I(\omega)$ vs. ω characteristic for this particle. If two particles are present in the field, the diode signal will represent the sum of the scattering characteristic for the two particles. The following features summarize the optical approach.

- The diode signal is independent of the location of the scattering particle within the field.
- The diode signal represents the sum of the scattering characteristics of all of the particles within the field.

Figure 3-2. Configuration for diffraction sizing instrument.

The instrument operates by (1) assuming a size distribution for the particles, (2) calculating the expected scattering from the assumed distribution, (3) comparing the calculated vs. measured scattering, and (4) adjusting the assumed distribution. These steps are repeated iteratively until the assumed particle size distribution yields scattering behavior which matches the measured value.

The calculation of the scattering from the assumed size distribution is the key point. It is accomplished by use of the "T" matrix as follows:

$$\bar{E} = [T]\bar{X} \quad (3-2)$$

Here, $\bar{X}$ is a vector containing as members the assumed size distribution, as represented by mass fraction in each of the 16 size bins. The T-matrix contains elements which relate a series of scattering angles against a series of particle sizes. As an example consider the situation in which only three diodes are used and it is desired to resolve data into three particle size "bins". The calculation then has the form:

$$\begin{array}{rcl} E_1 & & T_{11} \quad T_{12} \quad T_{13} \quad X_1 \\ E_2 & = & T_{21} \quad T_{22} \quad T_{23} \quad X_2 \\ E_3 & & T_{31} \quad T_{32} \quad T_{33} \quad X_3 \end{array} \quad (3-3)$$

Thus, the light energy onto E_1 , the inner diode, will be calculated as follows:

$$E_1 = T_{11}X_1 + T_{12}X_2 + T_{13}X_3 \quad (3-4)$$

Since E_1 is made up of light scattered to only one angle (or more correctly, light scattered to a small range of angles), then it is calculated by summing the scattering contribution from each size class into that specific angle. Thus, T_{11} represents the energy/unit mass of light scattered into the angle associated with E_1 from particles of size class X_1 . The sum of the contributions from each size class will give the total amount of energy onto Diode 1.

The dynamic range of the instrument covers about two orders of magnitude. Thus, a given configuration can, for example, resolve size distributions between 5 and 500 microns. This two order of magnitude resolution band can be adjusted to any point within the range of 1.2 to 1800 microns by choice of lens focal length and by concurrent adjustment of the T-matrix. Thus, the simplistic approach to resolving the 0.5 - 10 micron size range would be to reduce the focal length of the lens to 26 mm. A number of theoretical and hardware issues must be addressed to do this.

3.1.2 Theoretical Issues

The He/Ne laser light used by the Malvern is 0.6328 microns in wavelength. Thus, a 0.5 micron particle is well within the regime of comparable wavelength vs. particle size. This requires the use of rigorous Mie theory to calculate scattering characteristics. The first step is to determine how the Mie calculations compare with those on which the Malvern data reduction algorithm is based (Fraunhofer) in the 0.5-10 micron range.

Diffraction is essentially independent of the composition of the particle. With Mie scattering, however, the induced dipole moment of the particle begins to assume importance. Thus, the calculations require an assumed value of the complex index of refraction ($n = m - iK$) for the coal ash. The value of m is normally about 1.55, while the value for K varies with both ash composition and wavelength. We have elected to treat K as a parameter which is allowed to range between 0 and 0.4. As the Mie equations are complex and extremely laborious to evaluate, a Mie code at the University of California - Irvine was used to develop the plots contained here.

Figure 3-3 compares the I/I_0 vs. angle characteristic for Fraunhofer and Mie scattering. The plot shows that only a relatively minor adjustment to the baseline Fraunhofer characteristic essentially matches the Mie characteristic. Figure 3-4, however, brings up two problems. This is a plot

Figure 3-3. Scattering angle/intensity relationship.

Figure 3-4. Mie scattering comparison to Fraunhofer.

of the total power scattered per particle, which may be thought of as being proportional to I_0 . The apparent deviation between Mie and Fraunhofer is significant on this log scale. In absolute terms it represents a factor of 2-3 difference. This means that the results will be at least somewhat dependent on the choice of value for index of refraction. The second difficulty is that signal detection becomes increasingly difficult below 1 micron. Thus, a 0.5 micron particle scatters only about 10 percent of the energy as a 1.0 micron particle when exposed to the same incident light flux. Given a "reasonable" ash size distribution, this problem is mitigated by the fact that the number density for the smaller particles will be much higher than that for the larger particles. Thus, if Figure 3-4 is replotted on a total energy scattered basis rather than on an energy/particle basis, the curve will be much more horizontal.

In summary, the theoretical portion of the approach contains the following elements:

- Change the receiving lens to a 26 mm focal length. This will provide a dynamic range of 0.5 - 50 microns.
- Alter the T-matrix in the data reduction routine. This will be designed from Mie calculations, which will require that a complex index of refraction be assumed for the ash. The more likely approach is to assume various values depending on the composition of the ash.

It is key to note that Malvern has introduced Mie considerations into the T-matrix for the shorter focal length lenses. The results are insensitive to index of refraction (e.g., see Figure 3-4 for sizes above about 1 micron). Pure Fraunhofer is included only for focal lengths at or above 600 mm.

3.1.3 Hardware Issues

Most of the hardware related issues originate from the shortness of the focal length of the collection lens. Referring to Figure 3-2, the radius of the outside detector is 15.36 mm. With a 26 mm focal length lens, this means that the maximum scattering angle that can be detected is:

$$\tan^{-1} (15.36/26) = 30.6^{\circ} \quad (3-5)$$

If a particle is too distant from the lens, then light scattered to 30.6° will pass around the outside of the lens and be missed. This means that there is a limit to how far the measurement volume may extend from the lens. There is, however, no limit to how close the particle can be to the lens.

For a particle on the centerline, the maximum distance that it can be from the lens and still have light scattered to 30.6° collected is defined from the lens f-number as follows:

$$X_{\max} = (26/2f)/\tan(30.6) \quad (3-6)$$

where f is the f-number of the lens. In practice this must be reduced somewhat to account for the finite thickness of the laser beam (i.e., a particle at $X_{\max}$ that is on the edge of the beam rather than on centerline will still have some light scattered to 30.6° that misses the lens).

The 26 mm focal length lens has been installed on the Malvern. Operation of the modified Malvern was checked using a reticle containing a distribution of spots of known size etched on a glass plate. Results of measurements taken with the reticle using the 26 mm focal length lens closely matches the reticle's known distribution (Figure 3-5).

Figure 3-5. Calibration check of modified Malvern.

3.2 Coal Selection

The coals to be used in this study are listed in Table 3-1. The two PSI coals are a bituminous coal and a lignite coal. Both of these coals have been extensively characterized by PSI as part of a related DOE program (PSI, 1988). Three coals, all bituminous, from the DOE Clean Coal Project currently being conducted by EER, will be tested on both a fundamental and a pilot scale to provide data for comparison against full scale data obtained at the host boilers. These three coals have already been delivered to EER. Finally, the Utah bituminous coal has been extensively characterized by EER and is currently available in house.

3.3 Plans for the Fundamental Experiments

The fundamental experiments will be conducted in the EER Isothermal Reactor (ITR) facility. Shown in Figure 3-6, the ITR is a 0.9 m long downfired electrically heated drop tube furnace with a fuel precombustor assembly mounted on top. Three independently controlled heating zones compensate for non-uniform heat losses such as radiation at the reactor ends or loss to water cooled sampling probes. The fuel precombustor has a sliding burner which allows the entrance temperature to be adjusted without varying fuel stoichiometry.

The ITR can provide bulk gas temperatures from 800 to 1500°C with typical residence times of 0.2 to 1.2 s. A firing rate of 9.4 kw will provide an average particulate residence time of 0.5 s. Coal is injected just above the convergent cone of the venturi section shown in Figure 3-6 with a calibrated auger type feeder.

Measurement of fly ash particle size will be accomplished with an isokinetically operated water-cooled probe. Water flow rate through the probe is adjusted so that the sampled gas stream cools to approximately 120°C at the probe exit. At this temperature condensation will not occur in the sample lines. The ash/gas sample is transported from the probe to the sample chamber shown in Figure 3-7, passes through the sample chamber and on

TABLE 3-1. COALS TO BE USED IN EXPERIMENTAL WORK.

COAL	MINERAL CONTENT	MINERAL ANALYSIS
Beulah Lignite	9.6%	High Ca, Na
Eagle Butte Subbituminous	4.8%	High Ca Low Na
Illinois Bituminous	9.3%	High Ca, Pyrite
Illinois/Kentucky Bituminous Blend	6.2%	Low Ca, Na
Utah	8.8%	Low Ca, Na, Pyrite High Si

↓ To Sample Cell

Figure 3-6. Isothermal reactor and precombustor assembly.

to various gas analysis equipment. The 26 mm focal length lens is attached to the sample chamber as shown in Figure 3-7. This sample chamber/lens holder assembly is held in place with a fixture which allows the assembly to moved in all three dimensions. This setup keeps the sampled gas stream within the distance prescribed by equation 3-6.

The fundamental experiments will investigate the fundamental mechanisms which result in the formation of particulate matter in the 0.5-10 micron size range. Four possible sources of particles in this size range are considered here:

- 1) The breakup of char particles. Mineral matter present in char particles coalesce to form single ash particles. When a char particle breaks up during the burnout period a number of ash particles are formed from the fragments of the char particle which are smaller than the single ash particle which would have formed if breakup had not occurred. These smaller coalesced ash particles may make a substantial contribution to the 0.5-10 micron size range.
- 2) The extraneous material present in coal which results from the release of minerals during the grinding process. Since coal is rarely ground to sizes under 50 microns this extraneous material should have a mean size on the same order of magnitude as the coal with the small end of its size distribution contributing to the 0.5-10 micron size range.
- 3) Bursting of bubbles formed during the combustion of coal particles. Gas may be generated within the interior of ash particles during combustion to form bubbles. When a bubble bursts a large number of particles may be formed in the 0.5-10 micron size range.
- 4) Agglomeration of particles smaller than this size range. Workers at MIT have noted that particles much smaller than 0.5 microns may agglomerate in the wake of burning coal particles. The largest such agglomerates they found were 0.6 microns. Although some evidence of agglomerates may be found in this study, this mechanism is not expected

Figure 3-7. Sample chamber and lens arrangement.

to significantly influence ash particle size distributions in the 0.5-10 micron size range.

An overlap may exist between the first and second mechanisms when coal particles are ground fine enough so that some of the particles are no longer primarily coal and have a high a fraction of inorganic material. Ash resulting from this type of coal particle would be exposed to temperatures intermediate between those experienced by extraneous material and mineral matter present at lower concentrations in the coal particles.

This portion of the program will therefore be made up of 1) an experiment designed to provide information on the importance of global parameters affecting fine particle formation and 2) a series of mechanistic experiments designed to provide insight into the mechanisms controlling formation of particulate matter in the 0.5-10 micron size range:

- The Influence of Char Breakup;
- Fate of Extraneous Minerals; and
- Influence of Bubble Bursting.

The titles of these mechanistic experiments have been changed from those used in earlier presentations and reports (the earlier titles were influence of coal properties, coal cleaning, pure minerals, and free minerals) to reflect investigations into the potential mechanisms of fine ash particulate formation described in Section 3.3. The experiments described under the old titles (plus additional ones) will still be performed under these new titles. Modifications of the particle sizer and its installation on the experimental reactor (the ITR) are complete and are described in Section 3.1.

3.3.1 Global Experiments

The purpose of this set of experiments is to identify important process parameters which influence the uncontrolled yield of particulate in the size range of interest. The variables which will be studied are:

- coal type;
- temperature;
- oxygen concentration; and
- mixing of coal with the gas phase.

The first three mechanisms discussed in the previous section will contribute to particulate formation when this set of experiments is conducted. (The fourth mechanism is not expected to make a significant contribution.)

The particle size of the coals used here will influence the yield of particulate matter in the 0.5-10 micron size range especially if the second mechanism is a major contributor. Simulation of the particle size of coal injected into a boiler is therefore desirable. Coal injected into a boiler is ground on site and aerodynamically separated so that it has a size less than a 200 mesh screen (74 microns). Those coals which are received unground will therefore be milled to this size.

The coals to be tested are two coals that have been extensively characterized in the PSI program, three coals from the CCT program, and a Utah bituminous coal. Temperatures and oxygen concentrations may be important parameters as they will influence the temperature of burning char particles and thus the temperature of ash particles resulting from the char breakup mechanism. Calculations have shown that injecting even the minimum amount of coal possible with the auger feeder will reduce oxygen concentration from an initial concentration of 6% to 2.5%. At this final O₂ concentration complete burnout of the carbon is not likely. This was confirmed by analyzing ash collected from the ITR and finding a carbon content of 30%. Oxygen in the reactor will therefore be supplemented so that its final concentration is the target concentration rather than the initial concentration. The mixing rate of the coal particles into the gas stream will also influence the ash particle temperature by increasing the diffusion of oxygen to the char particle. The mixing rate will be changed by exchanging the venturi throat on the ITR (shown in Figure 3-6) with a

straight throat which will substantially reduce turbulence in this region and result in slower rates of oxygen mass transfer to the char particles.

Ash size distributions will be determined using the modified Malvern currently installed on the ITR. A size distribution measurement using the Anderson cascade impactor, shown in Figure 3-8, will be made on a baseline case to verify that the particle size measurement system is operating properly. Initial particle size distributions of the coals will be determined by feeding the coal through the ITR at room temperature and making measurements with the modified Malvern. This approach will yield fast and accurate size distributions and will detect any changes in coal particle size caused by the feeder.

Morphology of a typical ash sample will be determined by examination under a scanning electron microscope. Collection of the ash sample will be accomplished with the cascade impactor so that ash morphology can be determined as a function of particle size. This information will give an indication of the origin of the ash particles. Particulate matter resulting from the agglomeration of particles under 0.5 microns will be apparent in SEM photographs. Examination of larger particles will indicate whether they resulted from material included in the coal particles or are from extraneous material. Included minerals will experience higher temperatures than extraneous material and will exhibit such indications of melting as the formation of spheroidal particles while the extraneous material may retain its original shape.

3.3.2 Influence of Char Breakup

This set of mechanistic experiments will investigate the char breakup mechanism. The breakup model of Flagan (1978) predicts that a specific number of ash particles of equal size will result from the combustion of a single coal particle. By varying the size of a well characterized coal, the size and number of ash particles produced from a single coal particle will be reduced and should result in measurable differences in ash size

Figure 3-8. Drawing of cascade impactor sampling system for in-situ particle size measurement in the ITR.

distributions. The use of the breakup model will determine the number of ash particles theoretically resulting from the larger coal particles and will provide information on the influence of grinding on ash particle size. To accomplish this task a coal will be aerodynamically sized down to the minimum size feasible for testing on the ITR. Testing of the cleaned but unsized coal will also be carried out to determine the overall potential for coal cleaning decreasing the extent of fine particulate formation.

To independently study the char breakup mechanism the other two mechanisms which may significantly contribute to fine particulate formation (bubble bursting and extraneous minerals) must be eliminated. Cleaning the coal using gravity separation will remove the extraneous minerals. The formation of cenospheres has been correlated with levels of iron greater than 5%. Rupture of these cenospheres (bubble bursting) should therefore not contribute to the formation of fine particulate if a low iron coal is used. The Utah bituminous coal has a low iron content and will therefore be cleaned and sized for this portion of the fundamental experiments.

The extent of char fragmentation depends on both coal type and coal porosity. Understanding the influence of these variables will be important in developing a comprehensive model of fine particulate formation. Work at PSI has indicated that the degree of initial coal macroporosity has a direct influence on extent of fragmentation. Two different types of cleaned coal, one with a high degree of macroporosity and one with a low degree of macroporosity) will therefore be burned in the ITR and the resultant ash size distribution measured. Their initial porosity and cleaned ash content will be determined prior to injection in the ITR.

Char fragmentation may also depend on the chars' temperature during the combustion process. Both the ambient gas temperature and oxygen concentration affect this by influencing the diffusion mechanisms and reaction kinetics. These two parameters will be varied to determine their influence on the ash size distribution of the cleaned Utah coal.

3.2.3 Fate of Extraneous Minerals

While studying the influence of coal cleaning will indicate whether cleaning affects fine particulate formation, it will not determine the exact fate of the extraneous material. This will be accomplished by injecting reject material from the coal cleaning process into the ITR and measuring the resulting ash size distribution. Comparison of the particle size distribution before and after injection will indicate whether fragmentation of this extraneous material contributes to particulate formation in the 0.5-10 micron size range.

Minerals released from the coal matrix by the grinding process may, rather than remaining separate from the coal particles, be embedded on their surface. Upon combustion of the coal particle, these embedded minerals may either be readsorbed into the ash particle formed from the coal particle or be released as a free particle. The extent of embedding which occurs will be estimated by viewing the ground coal under an SEM.

The use of the rejected extraneous material from the coal cleaning process will prevent the char breakup mechanism from contributing to the formation of fine particulate matter. To prevent the bubble bursting mechanism from participating the reject material will be from a low iron coal. Since pyrite is a common mineral in coal, the size distribution of a pure pyrite will also be characterized before and after injection into the ITR to determine the possible extent of its fragmentation.

Fragmentation of extraneous material could be caused by thermal stresses resulting from the rapid heating which occurs upon injection into a combustion environment. The extent to which this mechanism can occur will be determined by injecting the cleaned inorganic material at both a relatively low heating rate and an extremely high heating rate and comparing the resultant ash size distributions.

The combustion of adjacent coal particles may result in local temperatures in excess of the overall gas temperature. If this occurs both the

higher temperature and the accompanying higher heating rate may increase the extent of fragmentation. The reject extraneous material and the cleaned coal will therefore be mixed at varying ratios, injected into the ITR at a constant ash feed rate, and the resulting ash size distributions measured.

3.2.4 Influence of Bubble Bursting

The formation of cenospheres and their subsequent rupture may make a significant contribution to particles in the 0.5-10 micron size range. Raask (1985) reports that the usual quantity of cenospheres in ash from pulverized fuel fired boilers ranges from 0.5-1.5% with values of up to 4.8% by weight reported. The most likely mechanism for cenosphere production is the generation of carbon monoxide within the ash globule by the reaction:

Both iron and carbon must therefore be present for cenosphere formation by this reaction to occur. Raask (1985) demonstrated this by adding iron powder to an ash globule, heating it, and observing the formation of a cenosphere whereas an iron free globule remained gas free when heated to the same temperature. The equilibrium pressure of CO produced by this reaction reaches 1 atm at 1400°C.

This reaction will be simulated in a controlled manner by taking reject material from the cleaning of a low iron coal, adding iron to it, and measuring the resulting particle size distribution after injection in the ITR. The addition of the iron must be done in such a manner as to ensure that the iron comes in intimate contact with the reject particles. Calculations show that when a mixture of micron sized particles and iron are injected in a dispersed manner the number of collisions which occur in the furnace will be small and very little of the iron would be incorporated into the ash particles. The iron will therefore be precipitated onto the reject material and subsequently dried before injection into the ITR. The quantity of iron precipitate onto the reject material will be varied to determine the influ-

ence of iron concentration. The reject material from a high iron coal will also be tested.

Testing in the ITR will be carried out at temperatures both above and below 1400°C, the temperature where bubble bursting is expected to occur. The presence of carbon is also necessary for the above reaction to proceed. The reject material may, however, be low enough in carbon to prevent bubble bursting from occurring. The "middlings" from the cleaning of the low iron coal shall therefore be tested in a similar manner. Middlings are those particles which sink in a 1300 kg/m³ density liquid but float on a 2000 kg/m³ density liquid and consist of particles of varying ratios of coal and minerals and will be assured of having a high carbon content.

4.0 FUTURE WORK

In the next reporting period the Malvern modification and verification will be completed and the global experiments will be performed.

5.0 REFERENCES

Dahlin, R. S. Modeling the Formation and Size Distribution of Flyash. PhD Dissertation, University of Alabama (1985).

Damle, A. S., D. S. Ensor, And M. B. Ranade. "Coal Combustion Aerosol Formation Mechanisms: A Review." Aerosol Sci. Technol. 1, 119 (1982).

Flagan, R. C. "Submicron Particles from Coal Combustion." 17th Int. Symp. Combust., p. 97, The Combustion Institute (1978).

Flagan, R. C., and S. K. Friedlander. "Particle Formation in Pulverized Coal Combustion - a Review." Recent Developments in Aerosol Science. D. T. Shaw, ed., Wiley, New York (1978).

Gluskoter, H. J., N. F. Shimp, and R. R. Ruch. "Coal Analysis, Trace Elements and Mineral Matter." Chemistry of Coal Utilization, Second Supplemental Volume. M. A. Elliott, Ed., Wiley (1981).

Hazard, H. R., et al. "Influence of Coal Mineral Matter on Slagging of Utility Boilers." EPRI CS-1418 (1980).

Helble, J., M. Neville, and A. F. Sarofim. "Aggregate Formation from Vaporized Ash During Pulverized Coal Combustion." Twenty-First Symposium (International) on Combustion. The Combustion Institute, pp. 411-417 (1986).

Holve, D. J. "In Situ Measurements of Flyash Formation from Pulverized Coal." Combustion Science and Technology. 44, 5+6, pp. 269-288 (1986).

Lauf, R. J. "Cenospheres in Fly Ash and Conditions Favoring their Formation." Fuel. 60, pp 1177-1179 (1981).

Littlejohn, R. F. "Mineral Matter and Ash Distribution in 'As-Fired' Samples of Pulverized Fuels." J. Inst. Fuel. 39, 301, pp. 59-67 (1966).

O'Gorman, J. V., and P. L. Walker. Mineral Matter and Trace Elements in US Coals. US Department of the Interior Office of Coal Research, Research Development Report Number 61, (1972).

PSI Technology Company. Transformations of Inorganic Coal Constituents in Combustion Systems, Quarterly Report No. 5. DOE Contract DE-AC22-86PC90751, January (1988).

Raask, E. Mineral Impurities in Coal Combustion: Behavior, Problems, and Remedial Measures, Hemisphere Publishing Corporation (1985).

Sarofim, A. F., J. M. Beer, and S. G. Kang. "Fundamental Studies of Mineral Matter Vaporization and Residual Ash Formation." Transformations of Inorganic Coal Constituents in Combustion Systems, Quarterly Report No. 5. PSI Technology Company, DOE Contract DE-AC22-86PC90751, January (1988).

Sarofim, A. F., J. B. Howard, and A. S. Padia. "The Physical Transformation of the Mineral Matter in Pulverized Coal Under Simulated Combustion Conditions." Combustion Science and Technology. 16, pp. 187-204 (1977).

Smith, R. D., J. A. Campbell, and K. K. Nielsen. "Characterization and Formation of Submicron Particles in Coal-Fired Plants." Atmospheric Environment. 13, pp. 607-617 (1979).

Tomaides, M., and Whitby, K. T. "Generation of Aerosols by Bursting of Single Bubbles." Presented at Symp. Fine Particles, Minneapolis (1975).

Van Krevelen, D. W. Coal: Typology, Chemistry, Physics, and Constitution. Elsevier, Amsterdam (1961).

Watt, J. D., and Fereday, F. J. Inst. Fuel. 42, 99 (1969).

**DATE
FILMED**

8 / 14 / 92